

Package ‘MediaK’

December 24, 2015

Type Package

Date 2015-12-23

Title Calculate MeDiA_K Distance

Version 1.0

Author Zizhuo Ren, Hesen Peng, Tianwei Yu

Maintainer Zizhuo Ren<zizhuoren@gmail.com>

Description Calculates MeDiA_K (means Mean Distance Association by K-nearest neighbor) in order to detect nonlinear associations.

License GPL

LazyData TRUE

Imports Rcpp (>= 0.11.3)

LinkingTo Rcpp, RcppEigen

NeedsCompilation yes

Repository CRAN

Date/Publication 2015-12-24 13:46:16

R topics documented:

Media_pvalue	1
RcppExports	2

Index	4
--------------	----------

Media_pvalue *functions to calculate pvalue*

Description

This function is created to calculate p values about MeDiA_k

Usage

```
Media_pvalue(iTest,jTest,times,selectvec)
```

Arguments

iTest	a numeric matrix
jTest	a numeric matrix which has the same rows as iTest
selectvec	an integer vector which contains a series of K values you want to get
times	an integer indicates permutation times

Value

Media_pvalue(iTest,jTest,times,selectvec) return a numeric vectors contains p values based on the selectvec(K value you want to select)

Examples

```
iTest <- matrix(rnorm(1000),100)
jTest<- matrix(rnorm(200),100)
times<- 100
selectvec <- c(1:10)
Media_pvalue(iTest,jTest,times,selectvec)
```

RcppExports

Set of functions in example RcppEigen package

Description

These two functions are created to calculate different values about MeDiA_k

Usage

```
dis_value(iTest,jTest,select)
permute(iTest,jTest,times,selectvec)
```

Arguments

iTest	a numeric matrix
jTest	a numeric matrix which has the same rows as iTest
select	an integer which means get k values you want to get
selectvec	an integer vector which contains a series of K values you want to get
times	an integer indicates permutation times

Value

dis_val(iTest,jTest,select) returns a distance permute(iTest,jTest,times,selectvec)
return a list contains mean and sd values based on the selectvec(K value you want to select)

Examples

```
iTest <- matrix(rnorm(1000),100)
jTest<- matrix(rnorm(200),100)
select<- 5
times<- 100
selectvec <- c(1:10)
dis_value(iTest,jTest,select)
permute(iTest,jTest,times,selectvec)
```

Index

`dis_value (RcppExports)`, [2](#)

`Media_pvalue`, [1](#)

`permute (RcppExports)`, [2](#)

`RcppExports`, [2](#)