

Package ‘PetfinderR’

August 23, 2019

Type Package

Title 'Petfinder' API Wrapper

Version 2.0.0

Author Aaron Schlegel

Maintainer Aaron Schlegel <aaron@aaronschlegel.me>

Description

Wrapper of the 'Petfinder API' <<https://www.petfinder.com/developers/v2/docs/>> that implements methods for interacting with and extracting data from the 'Petfinder' database. The 'Petfinder REST API' allows access to the 'Petfinder' database, one of the largest online databases of adoptable animals and animal welfare organizations across North America.

Encoding UTF-8

LazyData true

RoxygenNote 6.1.1

License MIT + file LICENSE

URL <https://github.com/aschleg/PetfinderR>

VignetteBuilder knitr

Imports R6, httr, jsonlite

Suggests testthat, knitr, rmarkdown, dplyr

NeedsCompilation no

Repository CRAN

Date/Publication 2019-08-23 15:30:15 UTC

R topics documented:

.Petfinder.class	2
animals	2
animal_types	4
breeds	4
organizations	5
Petfinder	6

Index	8
--------------	----------

<code>.Petfinder.class</code>	<i>Internal R6 class</i>
-------------------------------	--------------------------

Description

Internal R6 class

Usage

```
.Petfinder.class
```

Format

An object of class `R6ClassGenerator` of length 24.

<code>animals</code>	<i>Returns adoptable animal data from Petfinder based on specified criteria.</i>
----------------------	--

Description

Returns adoptable animal data from Petfinder based on specified criteria.

Usage

```
animals(
  animal_id = NULL, animal_type = NULL, breed = NULL,
  size = NULL, gender = NULL, age = NULL, color = NULL,
  coat = NULL, status = NULL, name = NULL, organization_id = NULL,
  location = NULL, distance = NULL, sort = NULL, pages = 1,
  results_per_page = 20, return_df = FALSE)
```

Arguments

<code>animal_id</code>	Integer or vector or list of integers representing animal IDs obtained from Petfinder. When <code>animal_id</code> is specified, the other function parameters are overridden. If <code>animal_id</code> is not specified, a search of animals on Petfinder matching given criteria is performed.
<code>animal_type</code>	Character vector representing desired animal type to search. Must be one of 'dog', 'cat', 'rabbit', 'small-furry', 'horse', 'bird', 'scales-fins-other', or 'barn-yard'.
<code>breed</code>	Character vector or vector or list of character strings of desired animal type breed to search. Available animal breeds in the Petfinder database can be found using the <code>breeds()</code> method.
<code>size</code>	Character vector or vector or list of character strings of desired animal sizes to return. The specified size(s) must be one of 'small', 'medium', 'large', or 'xlarge'.

gender	Character vector or vector or list of strings representing animal genders to return. Must be of 'male', 'female', or 'unknown'.
age	Character or vector or list of strings specifying animal age(s) to return from search. Must be of 'baby', 'young', 'adult', 'senior'.
color	String representing specified animal 'color' to search. Colors for each available animal type in the Petfinder database can be found using the <code>animal_types()</code> method.
coat	Desired coat(s) to return. Must be of 'short', 'medium', 'long', 'wire', 'hairless', or 'curly'.
status	Animal status to filter search results. Must be one of 'adoptable', 'adopted', or 'found'.
name	Searches for animal names matching or partially matching name.
organization_id	Returns animals associated with given <code>:code:'organization_id'</code> . Can be a vector or a vector or list of character strings representing multiple organizations.
location	Returns results by specified location. Must be in the format 'city, state' for city-level results, 'latitude, longitude' for lat-long results, or 'postal code'.
distance	Returns results within the distance of the specified location. If not given, defaults to 100 miles. Maximum distance range is 500 miles.
sort	Sorts by specified attribute. Leading dashes represents a reverse-order sort. Must be one of 'recent', '-recent', 'distance', or '-distance'.
pages	Specifies which page of results to return. Defaults to the first page of results. If set to NULL, all results will be returned.
results_per_page	Number of results to return per page. Defaults to 20 results and cannot exceed 100 results per page.
return_df	If TRUE, a data.frame will be returned. Does not currently do anything.

Value

List of JSON data of resulting animals.

Examples

```
## Not run:
pf <- Petfinder(key=key, secret=secret) # Initialize Petfinder class
pf$animals(results_per_page = 100, pages = 10)
pf$animals(location='Seattle, WA', distance = 100, results_per_page = 50, pages = 5)
pf$animals(animal_id=c(animalid1, animalid2, animalid3))

## End(Not run)
```

animal_types	<i>Returns data on an animal type, or types available from the Petfinder API. This data includes the available type's coat names and colors, gender and other specific information relevant to the specified type(s). The animal type must be of 'dog', 'cat', 'rabbit', 'small-furry', 'horse', 'bird', 'scales-fins-other', 'barnyard'.</i>
--------------	---

Description

Returns data on an animal type, or types available from the Petfinder API. This data includes the available type's coat names and colors, gender and other specific information relevant to the specified type(s). The animal type must be of 'dog', 'cat', 'rabbit', 'small-furry', 'horse', 'bird', 'scales-fins-other', 'barnyard'.

Usage

```
animal_types(types = NULL)
```

Arguments

types	Specifies the animal type or types to return. Can be a character vector representing a single animal type, or a vector or list of animal types if more than one type is desired. If not specified, all animal types are returned.
-------	---

Value

List of returned JSON data for each specified animal type from the Petfinder API.

Examples

```
## Not run:
pf <- Petfinder(key=key, secret=secret) # Initialize Petfinder class
cat <- pf$animal_types(types='cat')
cat_dog <- pf$animal_types(types=c('cat', 'dog'))
all_types <- pf$animal_types()

## End(Not run)
```

breeds	<i>Returns breed names of specified animal type, or types.</i>
--------	--

Description

Returns breed names of specified animal type, or types.

Usage

```
breeds(types, return_df = TRUE)
```

Arguments

types	Specifies the animal type or types. Can be a character vector representing a single animal type, or a vector or list of animal types if more than one type is desired. If not specified, all available breeds for each animal type is returned. The animal type must be of 'dog', 'cat', 'rabbit', 'small-furry', 'horse', 'bird', 'scales-fins-other', 'barnyard'.
return_df	If TRUE, the result set will be coerced into a pandas data.frame with two columns, breed and name.

Value

List of returned JSON data of available breeds for each specified animal type from the Petfinder API. If the parameter return_df is TRUE, a data.frame is returned instead.

Examples

```
## Not run:
pf <- Petfinder(key=key, secret=secret) # Initialize Petfinder class
cat_breeds <- pf$breeds('cat')
cat_dog_breeds <- pf$breeds(c('cat', 'dog'))
all_breeds <- pf$breeds()
all_breeds_df <- pf$breeds(return_df=TRUE)

## End(Not run)
```

organizations	<i>Returns data on an animal welfare organization, or organizations, based on specified criteria.</i>
---------------	---

Description

Returns data on an animal welfare organization, or organizations, based on specified criteria.

Usage

```
organizations(organization_id = NULL, name = NULL, location = NULL,
  distance = NULL, state = NULL, country = NULL, query = NULL,
  sort = NULL, results_per_page = 20, pages = 1, return_df = FALSE)
```

Arguments

organization_id	Returns results for specified :code:'organization_id'. Can be a character vector or a vector or list of character vectors representing multiple organizations.
name	Returns results matching or partially matching organization name.
location	Returns results by specified location. Must be in the format 'city, state' for city-level results, 'latitude, longitude' for lat-long results, or 'postal code'.
distance	Returns results within the distance of the specified location. If not given, defaults to 100 miles. Maximum distance range is 500 miles.
state	Filters the results by the selected state. Must be a two-letter state code abbreviation of the state name, such as 'WA' for Washington or 'NY' for New York.
country	Filters results to specified country. Must be a two-letter abbreviation of the country and is limited to the United States and Canada.
query	Search matching and partially matching name, city or state.
sort	Sorts by specified attribute. Leading dashes represents a reverse-order sort. Must be one of 'recent', '-recent', 'distance', or '-distance'.
results_per_page	Number of results to return per page. Defaults to 20 results and cannot exceed 100 results per page.
pages	Specifies which page of results to return. Defaults to the first page of results. If set to NULL, all results will be returned.
return_df	If TRUE, the results will be returned as a data.frame. Currently does not do anything.

Value

List of returned JSON data of organizations matching given search criteria.

Examples

```
## Not run:
pf <- Petfinder(key=key, secret=secret) # Initialize Petfinder class
pf$organizations(state='WA', results_per_page = 100, pages = 2)
pf$organizations(organization_id=c(orgid1, orgid2, orgid3))

## End(Not run)
```

Petfinder

Creates an authenticated connection with the Petfinder API. The stored authentication is then used to call the Petfinder API methods. An API key can be obtained from Petfinder by creating an account on their developer page (<https://www.petfinder.com/developers/api-key>). The function wraps the `.Petfinder.class R6` class.

Description

Creates an authenticated connection with the Petfinder API. The stored authentication is then used to call the Petfinder API methods. An API key can be obtained from Petfinder by creating an account on their developer page (<https://www.petfinder.com/developers/api-key>). The function wraps the `.Petfinder.class R6 class`.

Usage

```
Petfinder(key, secret)
```

Arguments

key	The API key received from Petfinder
secret	The secret key received from Petfinder along with the API key.

Value

Intialized Petfinder object that is then used to access the API.

Examples

```
## Not run:  
pf <- Petfinder(key) # Creates the connection with the Petfinder API.  
pf$breeds('cat') # The connection can now be used to access the Petfinder API methods.  
  
## End(Not run)
```

Index

*Topic **datasets**

.Petfinder.class, [2](#)
.Petfinder.class, [2](#)

animal_types, [4](#)
animals, [2](#)

breeds, [4](#)

organizations, [5](#)

Petfinder, [6](#)