

Package ‘Renvlp’

September 11, 2021

Type Package

Title Computing Envelope Estimators

Version 3.0

Date 2021-09-10

Author Minji Lee, Zhihua Su

Maintainer Minji Lee <mlee9@ufl.edu>

Description Provides a general routine, envMU, which allows estimation of the M envelope of $\text{span}(U)$ given root n consistent estimators of M and U . The routine envMU does not presume a model. This package implements response envelopes, partial response envelopes, envelopes in the predictor space, heteroscedastic envelopes, simultaneous envelopes, scaled response envelopes, scaled envelopes in the predictor space, groupwise envelopes, weighted envelopes, envelopes in logistic regression and envelopes in Poisson regression. For each of these model-based routines the package provides inference tools including bootstrap, cross validation, estimation and prediction, hypothesis testing on coefficients are included except for weighted envelopes. Tools for selection of dimension include AIC, BIC and likelihood ratio testing. Background is available at Cook, R. D., Forzani, L. and Su, Z. (2016) <[doi:10.1016/j.jmva.2016.05.006](https://doi.org/10.1016/j.jmva.2016.05.006)>. Optimization is based on a clockwise coordinate descent algorithm.

License GPL-2

NeedsCompilation no

Imports Rsolnp, stats

Suggests MASS

Repository CRAN

Date/Publication 2021-09-11 05:00:02 UTC

R topics documented:

Renvlp-package	3
Berkeley	4
boot.env	6
boot.genv	7
boot.henv	8

boot.logit.env	9
boot.penv	10
boot.pois.env	11
boot.senv	12
boot.stenv	13
boot.sxenv	14
boot.xenv	15
cv.env	16
cv.genv	17
cv.henv	18
cv.logit.env	19
cv.penv	20
cv.pois.env	21
cv.senv	22
cv.stenv	23
cv.sxenv	24
cv.xenv	25
d.stenv	26
env	27
fiberpaper	29
genv	30
henv	32
horseshoecrab	34
logit.env	35
penv	36
pois.env	38
pred.env	40
pred.genv	41
pred.henv	42
pred.logit.env	43
pred.penv	44
pred.pois.env	45
pred.senv	46
pred.stenv	47
pred.sxenv	48
pred.xenv	49
pred2.env	50
sales	51
senv	52
stenv	54
sxenv	56
testcoef.env	58
testcoef.genv	59
testcoef.henv	60
testcoef.logit.env	61
testcoef.penv	63
testcoef.pois.env	64
testcoef.senv	65

testcoef.stenv	66
testcoef.sxenv	68
testcoef.xenv	69
u.env	70
u.genv	71
u.henv	72
u.logit.env	73
u.penv	74
u.pois.env	75
u.pred2.env	76
u.senv	77
u.stenv	78
u.sxenv	79
u.xenv	80
waterstrider	81
weighted.env	82
weighted.penv	83
weighted.pred.env	85
weighted.xenv	86
wheatprotein	88
xenv	89

Index	92
--------------	-----------

Renvlp-package	<i>Computing Envelope Estimators</i>
----------------	--------------------------------------

Description

This package contains functions for estimating envelope models including response envelopes, partial response envelopes, envelopes in the predictor space, heteroscedastic envelopes, simultaneous envelopes, scaled response envelopes, scaled envelopes in the predictor space, groupwise envelopes, weighted envelopes, envelopes in logistic regression and envelopes in poisson regression.

Details

Package:	Renvlp
Type:	Package
Version:	3.0
Date:	2021-09-10
License:	GPL-2
Imports:	Rsolnp
Suggests:	Mass, stats

Author(s)

Minji Lee and Zhihua Su.

Maintainer: Minji Lee <mlee9@ufl.edu>

References

- Cook, R. D., Forzani, L. and Su, Z. (2016) A Note on Fast Envelope Estimation. *Journal of Multivariate Analysis* 150, 42-54.
- Cook, R. D., Li, B. and Chiaromonte, F. (2010). Envelope Models for Parsimonious and Efficient Multivariate Linear Regression (with discussion). *Statist. Sinica* 20, 927- 1010.
- Su, Z. and Cook, R.D. (2011). Partial envelopes for efficient estimation in multivariate linear regression. *Biometrika* 98, 133 - 146.
- Cook, R. D., Helland, I. S. and Su, Z. (2013). Envelopes and Partial Least Squares Regression. *Journal of the Royal Statistical Society: Series B* 75, 851 - 877.
- Su, Z. and Cook, R.D. (2013). Estimation of Multivariate Means with Heteroscedastic Error Using Envelope Models. *Statistica Sinica*, 23, 213-230.
- Cook, R. D., Zhang, X. (2015). Simultaneous Envelopes for Multivariate Linear Regression. *Technometrics* 57, 11 - 25.
- Cook, R. D., Su, Z. (2013). Scaled Envelopes: scale Invariant and Efficient Estimation in Multivariate Linear Regression. *Biometrika* 100, 939 - 954.
- Cook, R. D., Su, Z. (2016). Scaled Predictor Envelopes and Partial Least Squares Regression. *Technometrics* 58, 155 - 165.
- Park, Y., Su, Z. and Zhu, H. (2017) Groupwise envelope models for Imaging Genetic Analysis. *Biometrics*, to appear.
- Eck, D. J. and Cook, R. D. (2017). Weighted Envelope Estimation to Handle Variability in Model Selection. *Biometrika*.
- Cook, R. D., Zhang, X. (2015). Foundations for Envelope Models and Methods. *Journal of the American Statistical Association* 110, 599 - 611.

Berkeley

Berkeley Guidance Study Data

Description

Heights of children born in Berkeley

Usage

```
data("Berkeley")
```

Format

A data frame with 93 observations on the following 32 variables.

- V1 Sex.
- V2 Age 1.
- V3 Age 1.25.
- V4 Age 1.5.
- V5 Age 1.75.
- V6 Age 2.
- V7 Age 3.
- V8 Age 4.
- V9 Age 5.
- V10 Age 6.
- V11 Age 7.
- V12 Age 8.
- V13 Age 8.5.
- V14 Age 9.
- V15 Age 9.5.
- V16 Age 10.
- V17 Age 10.5.
- V18 Age 11.
- V19 Age 11.5.
- V20 Age 12.
- V21 Age 12.5.
- V22 Age 13.
- V23 Age 13.5.
- V24 Age 14.
- V25 Age 14.5.
- V26 Age 15.
- V27 Age 15.5.
- V28 Age 16.
- V29 Age 16.5.
- V30 Age 17.
- V31 Age 17.5.
- V32 Age 18.

Details

This data set contains measurements of heights of children born in 1928-29 in Berkeley, CA.

References

Tuddenham, R. D. and Snyder, M. M. (1954). Physical growth of California boys and girls from birth to eighteen years. *Publications in child developments*. University of California, Berkeley, 1(2), 183-364.

boot.env

Bootstrap for env

Description

Compute bootstrap standard error for the response envelope estimator.

Usage

```
boot.env(X, Y, u, B)
```

Arguments

X	Predictors. An n by p matrix, p is the number of predictors. The predictors can be univariate or multivariate, discrete or continuous.
Y	Multivariate responses. An n by r matrix, r is the number of responses and n is number of observations. The responses must be continuous variables.
u	Dimension of the envelope. An integer between 0 and r.
B	Number of bootstrap samples. A positive integer.

Details

This function computes the bootstrap standard errors for the regression coefficients in the envelope model by bootstrapping the residuals.

Value

The output is an r by p matrix.

bootse The standard error for elements in beta computed by bootstrap.

Examples

```
data(wheatprotein)
X <- wheatprotein[, 8]
Y <- wheatprotein[, 1:6]

u <- u.env(X, Y)
u

B <- 100
bootse <- boot.env(X, Y, 1, B)
bootse
```

`boot.genv`*Bootstrap for genv*

Description

Compute bootstrap standard error for the groupwise envelope.

Usage

```
boot.genv(X, Y, Z, u, B)
```

Arguments

X	Predictors. An n by p matrix, p is the number of predictors. The predictors can be univariate or multivariate, discrete or continuous.
Y	Multivariate responses. An n by r matrix, r is the number of responses and n is number of observations. The responses must be continuous variables.
Z	A group indicator vector of length n , where n denotes the number of observations.
u	Dimension of the groupwise envelope. An integer between 0 and r .
B	Number of bootstrap samples. A positive integer.

Details

This function computes the bootstrap standard errors for the regression coefficients in the groupwise envelope model by bootstrapping the residuals.

Value

The output is an p by r matrix.

`bootse` The standard error for elements in beta computed by bootstrap.

Examples

```
data(fiberpaper)
X <- fiberpaper[, c(5, 7)]
Y <- fiberpaper[, 1:3]
Z <- as.numeric(fiberpaper[, 6] > mean(fiberpaper[, 6]))

## Not run: B <- 100
## Not run: res <- boot.genv(X, Y, Z, 2, B)
## Not run: res$bootse[[1]]
## Not run: res$bootse[[2]]
```

`boot.henv`*Bootstrap for henv*

Description

Compute bootstrap standard error for the heteroscedastic envelope.

Usage

```
boot.henv(X, Y, u, B)
```

Arguments

X	A group indicator vector of length n , where n denotes the number of observations.
Y	Multivariate responses. An n by r matrix, r is the number of responses and n is number of observations. The responses must be continuous variables.
u	Dimension of the heteroscedastic envelope. An integer between 0 and r .
B	Number of bootstrap samples. A positive integer.

Details

This function computes the bootstrap standard errors for the regression coefficients in the heteroscedastic envelope model by bootstrapping the residuals.

Value

The output is an r by p matrix.

`bootse` The standard error for elements in beta computed by bootstrap.

Examples

```
data(waterstrider)
X <- waterstrider[, 1]
Y <- waterstrider[, 2:5]

B <- 100
## Not run: res <- boot.henv(X, Y, 2, B)
## Not run: res
```

boot.logit.env	<i>Bootstrap for logit.env</i>
----------------	--------------------------------

Description

Compute bootstrap standard error for the envelope estimator in logistic regression.

Usage

```
boot.logit.env(X, Y, u, B)
```

Arguments

X	Predictors. An n by p matrix, p is the number of predictors and n is number of observations. The predictors must be continuous variables.
Y	Response. An n by 1 matrix. The univariate response must be binary.
u	Dimension of the envelope. An integer between 0 and p.
B	Number of bootstrap samples. A positive integer.

Details

This function computes the bootstrap standard errors for the coefficients in the logistic regression envelope by the paired bootstrap.

Value

The output is a p by 1 matrix.

bootse The standard error for elements in beta computed by bootstrap.

Examples

```
data(horseshoecrab)
X1 <- as.numeric(horseshoecrab[, 1] == 2)
X2 <- as.numeric(horseshoecrab[, 1] == 3)
X3 <- as.numeric(horseshoecrab[, 1] == 4)
X4 <- as.numeric(horseshoecrab[, 2] == 2)
X5 <- as.numeric(horseshoecrab[, 2] == 3)
X6 <- horseshoecrab[, 3]
X7 <- horseshoecrab[, 5]
X <- cbind(X1, X2, X3, X4, X5, X6, X7)
Y <- as.numeric(ifelse(horseshoecrab[, 4] > 0, 1, 0))

B <- 100
## Not run: bootse <- boot.logit.env(X, Y, 1, B)
## Not run: bootse
```

boot.penv

Bootstrap for penv

Description

Compute bootstrap standard error for the partial envelope estimator.

Usage

```
boot.penv(X1, X2, Y, u, B)
```

Arguments

X1	Predictors of main interest. An n by p_1 matrix, n is the number of observations, and p_1 is the number of main predictors. The predictors can be univariate or multivariate, discrete or continuous.
X2	Covariates, or predictors not of main interest. An n by p_2 matrix, p_2 is the number of covariates.
Y	Multivariate responses. An n by r matrix, r is the number of responses and n is number of observations. The responses must be continuous variables.
u	Dimension of the partial envelope. An integer between 0 and r .
B	Number of bootstrap samples. A positive integer.

Details

This function computes the bootstrap standard errors for the regression coefficients β_1 in the partial envelope model by bootstrapping the residuals.

Value

The output is an r by p_1 matrix.

bootse The standard error for elements in β_1 computed by bootstrap.

Examples

```
data(fiberpaper)
X1 <- fiberpaper[, 7]
X2 <- fiberpaper[, 5:6]
Y <- fiberpaper[, 1:4]

B <- 100
## Not run: bootse <- boot.penv(X1, X2, Y, 1, B)
## Not run: bootse
```

boot.pois.env	<i>Bootstrap for pois.env</i>
---------------	-------------------------------

Description

Compute bootstrap standard error for the envelope estimator in poisson regression.

Usage

```
boot.pois.env(X, Y, u, B)
```

Arguments

X	Predictors. An n by p matrix, p is the number of predictors and n is number of observations. The predictors must be continuous variables.
Y	Response. An n by 1 matrix. The univariate response must be counts.
u	Dimension of the envelope. An integer between 0 and p.
B	Number of bootstrap samples. A positive integer.

Details

This function computes the bootstrap standard errors for the coefficients in the poisson regression envelope by the paired bootstrap.

Value

The output is a p by 1 matrix.

bootse The standard error for elements in beta computed by bootstrap.

Examples

```
data(horseshoecrab)
X1 <- as.numeric(horseshoecrab[ , 1] == 2)
X2 <- as.numeric(horseshoecrab[ , 1] == 3)
X3 <- as.numeric(horseshoecrab[ , 1] == 4)
X4 <- as.numeric(horseshoecrab[ , 2] == 2)
X5 <- as.numeric(horseshoecrab[ , 2] == 3)
X6 <- horseshoecrab[ , 3]
X7 <- horseshoecrab[ , 5]
X <- cbind(X1, X2, X3, X4, X5, X6, X7)
Y <- horseshoecrab[ , 4]

B <- 100
## Not run: bootse <- boot.pois.env(X, Y, 1, B)
## Not run: bootse
```

boot.senv

Bootstrap for senv

Description

Compute bootstrap standard error for the scaled response envelope estimator.

Usage

```
boot.senv(X, Y, u, B)
```

Arguments

X	Predictors. An n by p matrix, p is the number of predictors. The predictors can be univariate or multivariate, discrete or continuous.
Y	Multivariate responses. An n by r matrix, r is the number of responses and n is number of observations. The responses must be continuous variables.
u	Dimension of the scaled envelope. An integer between 0 and r.
B	Number of bootstrap samples. A positive integer.

Details

This function computes the bootstrap standard errors for the regression coefficients in the scaled envelope model by bootstrapping the residuals.

Value

The output is an r by p matrix.

bootse The standard error for elements in beta computed by bootstrap.

Examples

```
data(sales)
X <- sales[, 1:3]
Y <- sales[, 4:7]

u <- u.senv(X, Y)
u

## Not run: B <- 100
## Not run: bootse <- boot.senv(X, Y, 2, B)
## Not run: bootse
```

boot.stenv	<i>Bootstrap for stenv</i>
------------	----------------------------

Description

Compute bootstrap standard error for the simultaneous envelope estimator.

Usage

```
boot.stenv(X, Y, q, u, B)
```

Arguments

X	Predictors. An n by p matrix, p is the number of predictors. The predictors can be univariate or multivariate, discrete or continuous.
Y	Multivariate responses. An n by r matrix, r is the number of responses and n is number of observations. The responses must be continuous variables.
q	Dimension of the X-envelope. An integer between 0 and p.
u	Dimension of the Y-envelope. An integer between 0 and r.
B	Number of bootstrap samples. A positive integer.

Details

This function computes the bootstrap standard errors for the regression coefficients in the envelope model by bootstrapping the residuals.

Value

The output is an p by r matrix.

bootse The standard error for elements in beta computed by bootstrap.

Examples

```
data(fiberpaper)
X <- fiberpaper[, 5:7]
Y <- fiberpaper[, 1:4]
u <- u.stenv(X, Y)
u

## Not run: B <- 100
## Not run: bootse <- boot.stenv(X, Y, 2, 3, B)
## Not run: bootse
```

`boot.sxenv`*Bootstrap for sxenv*

Description

Compute bootstrap standard error for the scaled predictor envelope estimator.

Usage

```
boot.sxenv(X, Y, u, R, B)
```

Arguments

X	Predictors. An n by p matrix, p is the number of predictors. The predictors can be univariate or multivariate, discrete or continuous.
Y	Multivariate responses. An n by r matrix, r is the number of responses and n is number of observations. The responses must be continuous variables.
u	Dimension of the scaled envelope in the predictor space. An integer between 0 and p .
R	The number of replications of the scales. A vector, the sum of all elements of R must be p .
B	Number of bootstrap samples. A positive integer.

Details

This function computes the bootstrap standard errors for the regression coefficients in the scaled envelope model in the predictor space by bootstrapping the residuals.

Value

The output is an p by r matrix.

`bootse` The standard error for elements in beta computed by bootstrap.

Examples

```
data(sales)
Y <- sales[, 1:3]
X <- sales[, 4:7]
R <- rep(1, 4)

u <- u.sxenv(X, Y, R)
u

B <- 100
## Not run: bootse <- boot.sxenv(X, Y, 2, R, B)
## Not run: bootse
```

boot.xenv	<i>Bootstrap for xenv</i>
-----------	---------------------------

Description

Compute bootstrap standard error for the predictor envelope estimator.

Usage

```
boot.xenv(X, Y, u, B)
```

Arguments

X	Predictors. An n by p matrix, p is the number of predictors and n is number of observations. The predictors must be continuous variables.
Y	Responses. An n by r matrix, r is the number of responses. The response can be univariate or multivariate and must be continuous variable.
u	Dimension of the envelope. An integer between 0 and p.
B	Number of bootstrap samples. A positive integer.

Details

This function computes the bootstrap standard errors for the regression coefficients in the envelope model in predictor space by bootstrapping the residuals.

Value

The output is a p by r matrix.

bootse The standard error for elements in beta computed by bootstrap.

Examples

```
data(wheatprotein)
X <- wheatprotein[, 1:6]
Y <- wheatprotein[, 7]

## Not run: B <- 100
## Not run: bootse <- boot.xenv(X, Y, 2, B)
## Not run: bootse
```

cv.env *Cross validation for env*

Description

Compute the prediction error for the response envelope estimator using m-fold cross validation.

Usage

```
cv.env(X, Y, u, m, nperm)
```

Arguments

X	Predictors. An n by p matrix, p is the number of predictors. The predictors can be univariate or multivariate, discrete or continuous.
Y	Multivariate responses. An n by r matrix, r is the number of responses and n is number of observations. The responses must be continuous variables.
u	Dimension of the envelope. An integer between 0 and r.
m	A positive integer that is used to indicate m-fold cross validation.
nperm	A positive integer indicating number of permutations of the observations, m-fold cross validation is run on each permutation.

Details

This function computes prediction errors using m-fold cross validation. For a fixed dimension u, the data is randomly partitioned into m parts, each part is in turn used for testing for the prediction performance while the rest m-1 parts are used for training. This process is repeated for nperm times, and average prediction error is reported. As Y is multivariate, the identity inner product is used for computing the prediction errors.

Value

The output is a real nonnegative number.

cvPE The prediction error estimated by m-fold cross validation.

Examples

```
data(wheatprotein)
X <- wheatprotein[, 8]
Y <- wheatprotein[, 1:6]
u <- u.env(X, Y)
u

m <- 5
nperm <- 50
cvPE <- cv.env(X, Y, 1, m, nperm)
cvPE
```

 cv.genv

Cross validation for genv

Description

Compute the prediction error for the groupwise envelope estimator using m -fold cross validation.

Usage

```
cv.genv(X, Y, Z, u, m, nperm)
```

Arguments

<code>X</code>	Predictors. An n by p matrix, p is the number of predictors. The predictors can be univariate or multivariate, discrete or continuous.
<code>Y</code>	Multivariate responses. An n by r matrix, r is the number of responses and n is number of observations. The responses must be continuous variables.
<code>Z</code>	A group indicator vector of length n , where n denotes the number of observations.
<code>u</code>	Dimension of the groupwise envelope. An integer between 0 and r .
<code>m</code>	A positive integer that is used to indicate m -fold cross validation.
<code>nperm</code>	A positive integer indicating number of permutations of the observations, m -fold cross validation is run on each permutation.

Details

This function computes prediction errors using m -fold cross validation. For a fixed dimension u , the data is randomly partitioned into m parts, each part is in turn used for testing for the prediction performance while the rest $m-1$ parts are used for training. This process is repeated for $nperm$ times, and average prediction error is reported. As Y is multivariate, the identity inner product is used for computing the prediction errors.

Value

The output is a real nonnegative number.

<code>cvPE</code>	The prediction error estimated by m -fold cross validation.
-------------------	---

Examples

```
data(fiberpaper)
X <- fiberpaper[ , c(5, 7)]
Y <- fiberpaper[ , 1:3]
Z <- as.numeric(fiberpaper[ , 6] > mean(fiberpaper[ , 6]))

## Not run: m <- 5
## Not run: nperm <- 50
```

```
## Not run: cvPE <- cv.genv(X, Y, Z, 2, m, nperm)
## Not run: cvPE
```

cv.henv

Cross validation for henv

Description

Compute the prediction error for the heteroscedastic envelope estimator using m -fold cross validation.

Usage

```
cv.henv(X, Y, u, m, nperm)
```

Arguments

X	A group indicator vector of length n , where n denotes the number of observations.
Y	Multivariate responses. An n by r matrix, r is the number of responses and n is number of observations. The responses must be continuous variables.
u	Dimension of the heteroscedastic envelope. An integer between 0 and r .
m	A positive integer that is used to indicate m -fold cross validation.
nperm	A positive integer indicating number of permutations of the observations, m -fold cross validation is run on each permutation.

Details

This function computes prediction errors using m -fold cross validation. For a fixed dimension u , the data is randomly partitioned into m parts, each part is in turn used for testing for the prediction performance while the rest $m-1$ parts are used for training. This process is repeated for $nperm$ times, and average prediction error is reported. As Y is multivariate, the identity inner product is used for computing the prediction errors.

Value

The output is a real nonnegative number.

cvPE	The prediction error estimated by m -fold cross validation.
------	---

Examples

```
data(waterstrider)
X <- waterstrider[, 1]
Y <- waterstrider[, 2:5]

m <- 5
nperm <- 50

## Not run: cvPE <- cv.henv(X, Y, 2, m, nperm)
## Not run: cvPE
```

cv.logit.env

Cross validation for logit.env

Description

Compute the prediction error for the envelope estimator in logistic regression using m-fold cross validation.

Usage

```
cv.logit.env(X, Y, u, m, nperm)
```

Arguments

X	Predictors. An n by p matrix, p is the number of predictors and n is number of observations. The predictors must be continuous variables.
Y	Response. An n by 1 matrix. The univariate response must be binary.
u	Dimension of the envelope. An integer between 0 and p.
m	A positive integer that is used to indicate m-fold cross validation.
nperm	A positive integer indicating number of permutations of the observations, m-fold cross validation is run on each permutation.

Details

This function computes prediction errors using m-fold cross validation. For a fixed dimension u, the data is randomly partitioned into m parts, each part is in turn used for testing for the prediction performance while the rest m-1 parts are used for training. This process is repeated for nperm times, and average prediction error is reported.

Value

The output is a real nonnegative number.

cvPE	The prediction error estimated by m-fold cross validation.
------	--

Examples

```

data(horseshoecrab)
X1 <- as.numeric(horseshoecrab[ , 1] == 2)
X2 <- as.numeric(horseshoecrab[ , 1] == 3)
X3 <- as.numeric(horseshoecrab[ , 1] == 4)
X4 <- as.numeric(horseshoecrab[ , 2] == 2)
X5 <- as.numeric(horseshoecrab[ , 2] == 3)
X6 <- horseshoecrab[ , 3]
X7 <- horseshoecrab[ , 5]
X <- cbind(X1, X2, X3, X4, X5, X6, X7)
Y <- as.numeric(iffelse(horseshoecrab[ , 4] > 0, 1, 0))

m <- 5
nperm <- 50
## Not run: cvPE <- cv.logit.env(X, Y, 1, m, nperm)
## Not run: cvPE

```

cv.penv

Cross validation for penv

Description

Compute the prediction error for the partial envelope estimator using m-fold cross validation.

Usage

```
cv.penv(X1, X2, Y, u, m, nperm)
```

Arguments

X1	Predictors of main interest. An n by p1 matrix, n is the number of observations, and p1 is the number of main predictors. The predictors can be univariate or multivariate, discrete or continuous.
X2	Covariates, or predictors not of main interest. An n by p2 matrix, p2 is the number of covariates.
Y	Multivariate responses. An n by r matrix, r is the number of responses and n is number of observations. The responses must be continuous variables.
u	Dimension of the envelope. An integer between 0 and r.
m	A positive integer that is used to indicate m-fold cross validation.
nperm	A positive integer indicating number of permutations of the observations, m-fold cross validation is run on each permutation.

Details

This function computes prediction errors using m-fold cross validation. For a fixed dimension u , the data is randomly partitioned into m parts, each part is in turn used for testing for the prediction performance while the rest $m-1$ parts are used for training. This process is repeated for $nperm$ times, and average prediction error is reported. As Y is multivariate, the identity inner product is used for computing the prediction errors.

Value

The output is a real nonnegative number.

cvPE The prediction error estimated by m-fold cross validation.

Examples

```
data(fiberpaper)
X1 <- fiberpaper[, 7]
X2 <- fiberpaper[, 5:6]
Y <- fiberpaper[, 1:4]

m <- 5
nperm <- 50
## Not run: cvPE <- cv.penv(X1, X2, Y, 1, m, nperm)
## Not run: cvPE
```

cv.pois.env

Cross validation for pois.env

Description

Compute the prediction error for the envelope estimator in poisson regression using m-fold cross validation.

Usage

```
cv.pois.env(X, Y, u, m, nperm)
```

Arguments

X	Predictors. An n by p matrix, p is the number of predictors and n is number of observations. The predictors must be continuous variables.
Y	Response. An n by 1 matrix. The univariate response must be counts.
u	Dimension of the envelope. An integer between 0 and p .
m	A positive integer that is used to indicate m-fold cross validation.
$nperm$	A positive integer indicating number of permutations of the observations, m-fold cross validation is run on each permutation.

Details

This function computes prediction errors using m-fold cross validation. For a fixed dimension u , the data is randomly partitioned into m parts, each part is in turn used for testing for the prediction performance while the rest $m-1$ parts are used for training. This process is repeated for $nperm$ times, and average prediction error is reported.

Value

The output is a real nonnegative number.

cvPE The prediction error estimated by m-fold cross validation.

Examples

```
data(horseshoecrab)
X1 <- as.numeric(horseshoecrab[ , 1] == 2)
X2 <- as.numeric(horseshoecrab[ , 1] == 3)
X3 <- as.numeric(horseshoecrab[ , 1] == 4)
X4 <- as.numeric(horseshoecrab[ , 2] == 2)
X5 <- as.numeric(horseshoecrab[ , 2] == 3)
X6 <- horseshoecrab[ , 3]
X7 <- horseshoecrab[ , 5]
X <- cbind(X1, X2, X3, X4, X5, X6, X7)
Y <- horseshoecrab[ , 4]

m <- 5
nperm <- 50
## Not run: cvPE <- cv.pois.env(X, Y, 1, m, nperm)
## Not run: cvPE
```

cv.senv

Cross validation for senv

Description

Compute the prediction error for the scaled response envelope estimator using m-fold cross validation.

Usage

```
cv.senv(X, Y, u, m, nperm)
```

Arguments

X Predictors. An n by p matrix, p is the number of predictors. The predictors can be univariate or multivariate, discrete or continuous.

Y Multivariate responses. An n by r matrix, r is the number of responses and n is number of observations. The responses must be continuous variables.

u	Dimension of the scaled envelope. An integer between 0 and r.
m	A positive integer that is used to indicate m-fold cross validation.
nperm	A positive integer indicating number of permutations of the observations, m-fold cross validation is run on each permutation.

Details

This function computes prediction errors using m-fold cross validation. For a fixed dimension u, the data is randomly partitioned into m parts, each part is in turn used for testing for the prediction performance while the rest m-1 parts are used for training. This process is repeated for nperm times, and average prediction error is reported. As Y is multivariate, the identity inner product is used for computing the prediction errors.

Value

The output is a real nonnegative number.

cvPE The prediction error estimated by m-fold cross validation.

Examples

```
data(sales)
X <- sales[, 1:3]
Y <- sales[, 4:7]

m <- 5
nperm <- 50
## Not run: cvPE <- cv.stenv(X, Y, 2, m, nperm)
## Not run: cvPE
```

cv.stenv

Cross validation for stenv

Description

Compute the prediction error for the simultaneous envelope estimator using m-fold cross validation.

Usage

```
cv.stenv(X, Y, q, u, m, nperm)
```

Arguments

X	Predictors. An n by p matrix, p is the number of predictors and n is number of observations. The predictors must be continuous variables.
Y	Responses. An n by r matrix, r is the number of responses. The response can be univariate or multivariate and must be continuous variable.
q	Dimension of the X-envelope. An integer between 0 and p.

u	Dimension of the Y-envelope. An integer between 0 and r.
m	A positive integer that is used to indicate m-fold cross validation.
nperm	A positive integer indicating number of permutations of the observations, m-fold cross validation is run on each permutation.

Details

This function computes prediction errors using m-fold cross validation. For a fixed dimension (q, u), the data is randomly partitioned into m parts, each part is in turn used for testing for the prediction performance while the rest m-1 parts are used for training. This process is repeated for nperm times, and average prediction error is reported. If Y is multivariate, the identity inner product is used for computing the prediction errors.

Value

The output is a real nonnegative number.

cvPE The prediction error estimated by m-fold cross validation.

Examples

```
data(fiberpaper)
X <- fiberpaper[, 5:7]
Y <- fiberpaper[, 1:4]

m <- 5
nperm <- 50
## Not run: cvPE <- cv.stenv(X, Y, 2, 3, m, nperm)
## Not run: cvPE
```

cv.sxenv

Cross validation for sxenv

Description

Compute the prediction error for the scaled predictor envelope estimator using m-fold cross validation.

Usage

```
cv.sxenv(X, Y, u, R, m, nperm)
```


Arguments

X	Predictors. An n by p matrix, p is the number of predictors and n is number of observations. The predictors must be continuous variables.
Y	Responses. An n by r matrix, r is the number of responses. The response can be univariate or multivariate and must be continuous variable.
u	Dimension of the scaled envelope. An integer between 0 and r.
R	The number of replications of the scales. A vector, the sum of all elements of R must be p.
m	A positive integer that is used to indicate m-fold cross validation.
nperm	A positive integer indicating number of permutations of the observations, m-fold cross validation is run on each permutation.

Details

This function computes prediction errors using m-fold cross validation. For a fixed dimension u, the data is randomly partitioned into m parts, each part is in turn used for testing for the prediction performance while the rest m-1 parts are used for training. This process is repeated for nperm times, and average prediction error is reported. As Y is multivariate, the identity inner product is used for computing the prediction errors.

Value

The output is a real nonnegative number.

cvPE The prediction error estimated by m-fold cross validation.

Examples

```
data(sales)
Y <- sales[, 1:3]
X <- sales[, 4:7]
R <- rep(1, 4)

m <- 5
nperm <- 50
## Not run: cvPE <- cv.sxenv(X, Y, 2, R, m, nperm)
## Not run: cvPE
```

Description

Compute the prediction error for the predictor envelope estimator using m-fold cross validation.

Usage

```
cv.xenv(X, Y, u, m, nperm)
```

Arguments

X	Predictors. An n by p matrix, p is the number of predictors and n is number of observations. The predictors must be continuous variables.
Y	Responses. An n by r matrix, r is the number of responses. The response can be univariate or multivariate and must be continuous variable.
u	Dimension of the envelope. An integer between 0 and p.
m	A positive integer that is used to indicate m-fold cross validation.
nperm	A positive integer indicating number of permutations of the observations, m-fold cross validation is run on each permutation.

Details

This function computes prediction errors using m-fold cross validation. For a fixed dimension u, the data is randomly partitioned into m parts, each part is in turn used for testing for the prediction performance while the rest m-1 parts are used for training. This process is repeated for nperm times, and average prediction error is reported. If Y is multivariate, the identity inner product is used for computing the prediction errors.

Value

The output is a real nonnegative number.

cvPE The prediction error estimated by m-fold cross validation.

Examples

```
data(wheatprotein)
X <- wheatprotein[, 1:6]
Y <- wheatprotein[, 7]

m <- 5
nperm <- 50
## Not run: cvPE <- cv.xenv(X, Y, 2, m, nperm)
## Not run: cvPE
```

d.stenv

Select the rank of beta

Description

This function outputs the rank selected by a chi-squared test developed by Bura and Cook (2003) with specified significance level for the beta.

Usage

```
d.stenv(X, Y, alpha = 0.01)
```

Arguments

X	Predictors. An n by p matrix, p is the number of predictors. The predictors can be univariate or multivariate, discrete or continuous.
Y	Multivariate responses. An n by r matrix, r is the number of responses and n is number of observations. The responses must be continuous variables.
alpha	Significance level for testing. The default is 0.01.

Details

This function estimate the rank of beta using a chi-squared test. The test statistic and degrees of freedom are described in Bura and Cook (2003).

Value

rank.beta	Rank of beta guided by the Bura-Cook estimator.
-----------	---

References

Bura, E. and Cook, R. D. (2003). Rank estimation in reduced-rank regression. *Journal of Multivariate Analysis*, 87, 159 - 176.

 env

Fit the response envelope model

Description

Fit the response envelope model in multivariate linear regression with dimension u.

Usage

```
env(X, Y, u, asy = TRUE, init = NULL)
```

Arguments

X	Predictors. An n by p matrix, p is the number of predictors. The predictors can be univariate or multivariate, discrete or continuous.
Y	Multivariate responses. An n by r matrix, r is the number of responses and n is number of observations. The responses must be continuous variables.
u	Dimension of the envelope. An integer between 0 and r.
asy	Flag for computing the asymptotic variance of the envelope estimator. The default is TRUE. When p and r are large, computing the asymptotic variance can take much time and memory. If only the envelope estimators are needed, the flag can be set to asy = FALSE.

`init` The user-specified value of Gamma for the envelope subspace. An r by u matrix. The default is the one generated by function `envMU`.

Details

This function fits the envelope model to the responses and predictors,

$$Y = \mu + \Gamma\eta X + \varepsilon, \Sigma = \Gamma\Omega\Gamma' + \Gamma_0\Omega_0\Gamma_0'$$

using the maximum likelihood estimation. When the dimension of the envelope is between 1 and $r-1$, the starting value and blockwise coordinate descent algorithm in Cook et al. (2016) is implemented. When the dimension is r , then the envelope model degenerates to the standard multivariate linear regression. When the dimension is 0, it means that X and Y are uncorrelated, and the fitting is different.

Value

The output is a list that contains the following components:

<code>beta</code>	The envelope estimator of the regression coefficients.
<code>Sigma</code>	The envelope estimator of the error covariance matrix.
<code>Gamma</code>	An orthonormal basis of the envelope subspace.
<code>Gamma0</code>	An orthonormal basis of the complement of the envelope subspace.
<code>eta</code>	The coordinates of <code>beta</code> with respect to <code>Gamma</code> .
<code>Omega</code>	The coordinates of <code>Sigma</code> with respect to <code>Gamma</code> .
<code>Omega0</code>	The coordinates of <code>Sigma</code> with respect to <code>Gamma0</code> .
<code>mu</code>	The estimated intercept.
<code>loglik</code>	The maximized log likelihood function.
<code>covMatrix</code>	The asymptotic covariance of <code>vec(beta)</code> . The covariance matrix returned are asymptotic. For the actual standard errors, multiply by $1/n$.
<code>asySE</code>	The asymptotic standard error for elements in <code>beta</code> under the envelope model. The standard errors returned are asymptotic, for actual standard errors, multiply by $1/\sqrt{n}$.
<code>ratio</code>	The asymptotic standard error ratio of the standard multivariate linear regression estimator over the envelope estimator, for each element in <code>beta</code> .
<code>n</code>	The number of observations in the data.

References

- Cook, R. D., Li, B. and Chiaromonte, F. (2010). Envelope Models for Parsimonious and Efficient Multivariate Linear Regression (with discussion). *Statist. Sinica* 20, 927- 1010.
- Cook, R. D., Forzani, L. and Su, Z. (2016) A Note on Fast Envelope Estimation. *Journal of Multivariate Analysis*. 150, 42-54.

Examples

```
data(wheatprotein)
X <- wheatprotein[, 8]
Y <- wheatprotein[, 1:6]
u <- u.env(X, Y)
u

m <- env(X, Y, 1)
m
m$beta
```

fiberpaper

Pulp and Paper Data

Description

Pulp and paper property

Usage

```
data("fiberpaper")
```

Format

A data frame with 62 observations on the following 8 variables.

- V1 Breaking length.
- V2 Elastic modulus.
- V3 Stress at failure.
- V4 Burst strength.
- V5 Arithmetic fiber length.
- V6 Long fiber fraction.
- V7 Fine fiber fraction.
- V8 Zero span tensile.

Details

This data set contains measurements of properties of pulp fibers and the paper made from them.

References

Johnson, R.A. and Wichern, D.W. (2007). Applied Multivariate Statistical Analysis, 6th edition.

genv

*Fit the groupwise envelope model***Description**

Fit the groupwise envelope model in multivariate linear regression with dimension u . The groupwise envelope model is designed to accommodate both distinct regression coefficients and distinct error structures for different groups.

Usage

```
genv(X, Y, Z, u, asy = TRUE, fit = TRUE, init = NULL)
```

Arguments

<code>X</code>	Predictors. An n by p matrix, p is the number of predictors. The predictors can be univariate or multivariate, discrete or continuous.
<code>Y</code>	Multivariate responses. An n by r matrix, r is the number of responses and n is number of observations. The responses must be continuous variables.
<code>Z</code>	A group indicator vector of length n , where n denotes the number of observations.
<code>u</code>	Dimension of the groupwise envelope. An integer between 0 and r .
<code>asy</code>	Flag for computing the asymptotic variance of the envelope estimator. The default is TRUE. When p and r are large, computing the asymptotic variance can take much time and memory. If only the envelope estimators are needed, the flag can be set to <code>asy = FALSE</code> .
<code>fit</code>	Flag for computing the fitted response. The default is TRUE.
<code>init</code>	The user-specified value of Gamma for the groupwise envelope subspace. An r by u matrix. The default is the one generated by function <code>genvMU</code> .

Details

This function fits the groupwise envelope model to the responses and predictors,

$$Y_{(l)j} = \mu_{(l)} + \Gamma \eta_{(l)j} X_{(l)j} + \varepsilon_{(l)j}, \Sigma_{(l)} = \Gamma \Omega_{(l)} \Gamma' + \Gamma_0 \Omega_0 \Gamma_0'$$

for $l = 1, \dots, L$, using the maximum likelihood estimation. When the dimension of the groupwise envelope is between 1 and $r-1$, the starting value and blockwise coordinate descent algorithm in Cook et al. (2016) is implemented. When the dimension is r , then the envelope model degenerates to the standard multivariate linear regression. When the dimension is 0, it means that X and Y are uncorrelated, and the fitting is different. When L is 1, the groupwise envelope model degenerates to the envelope model in Cook et al. (2010).

Value

The output is a list that contains the following components:

beta	A list of r by p matrices for the estimator of regression coefficients. beta[[i]] indicates the estimator of regression coefficient for the i th group.
Sigma	A list of the estimator of error covariance matrix. Sigma[[i]] contains the estimated covariance matrix for the i th group.
Gamma	An orthonormal basis of the groupwise envelope subspace.
Gamma0	An orthonormal basis of the complement of the groupwise envelope subspace.
eta	The coordinates of beta with respect to Gamma.
Omega	The coordinates of Sigma with respect to Gamma.
Omega0	The coordinates of Sigma with respect to Gamma0.
mu	The estimator of group mean. A r by L matrix whose i th column contains the mean for the group.
loglik	The maximized log likelihood function.
covMatrix	A list of the asymptotic covariance of vec(beta). The covariance matrix returned are asymptotic. For the actual standard errors, multiply by $1 / n$. covMatrix[[i]] contains the asymptotic covariance matrix for the i th group.
asySE	A list of the asymptotic standard error for elements in beta under the groupwise envelope model. The standard errors returned are asymptotic, for actual standard errors, multiply by $1 / \sqrt{n}$. asySE[[i]] contains the asymptotic standard error for elements in beta[[i]].
ratio	A list of the asymptotic standard error ratio of the standard multivariate linear regression estimator over the groupwise envelope estimator, for each element in beta. ratio[[i]] contains the asymptotic standard error ratio for the i th group.
groupInd	A matrix containing the unique values of group indicators. The matrix has p rows.
n	The number of observations in the data.
ng	The number of observations in each group.
Yfit	Fitted responses.

References

Park, Y., Su, Z. and Zhu, H. (2017) Groupwise envelope models for Imaging Genetic Analysis. *Biometrics*, to appear.

Cook, R. D., Li, B. and Chiaromonte, F. (2010). Envelope Models for Parsimonious and Efficient Multivariate Linear Regression (with discussion). *Statist. Sinica* 20, 927- 1010.

Cook, R. D., Forzani, L. and Su, Z. (2016) A Note on Fast Envelope Estimation. *Journal of Multivariate Analysis*. 150, 42-54.

Examples

```

data(fiberpaper)
X <- fiberpaper[ , c(5, 7)]
Y <- fiberpaper[ , 1:3]
Z <- as.numeric(fiberpaper[ , 6] > mean(fiberpaper[ , 6]))
## Not run: u <- u.genv(X, Y, Z)
## Not run: u
## Not run: m <- genv(X, Y, Z, 2)

```

henv

Fit the heteroscedastic envelope model

Description

Fit the heteroscedastic envelope model derived to incorporate heteroscedastic error structure in the context of estimating multivariate means for different groups with dimension u .

Usage

```
henv(X, Y, u, asy = TRUE, fit = TRUE, init = NULL)
```

Arguments

X	A group indicator vector of length n , where n denotes the number of observations.
Y	Multivariate responses. An n by r matrix, r is the number of responses and n is number of observations. The responses must be continuous variables.
u	Dimension of the heteroscedastic envelope. An integer between 0 and r .
asy	Flag for computing the asymptotic variance of the envelope estimator. The default is TRUE. When p and r are large, computing the asymptotic variance can take much time and memory. If only the envelope estimators are needed, the flag can be set to $asy = FALSE$.
fit	Flag for computing the fitted response. The default is TRUE.
$init$	The user-specified value of Gamma for the heteroscedastic envelope subspace. An r by u matrix. The default is the one generated by function henvMU.

Details

This function fits the heteroscedastic envelope model to the responses,

$$Y_{(i)j} = \mu + \Gamma\eta_{(i)} + \varepsilon_{(i)j}, \Sigma_{(i)} = \Gamma\Omega_{(i)}\Gamma' + \Gamma_0\Omega_0\Gamma_0'$$

for $i = 1, \dots, p$, using the maximum likelihood estimation. When the dimension of the heteroscedastic envelope is between 1 and $r-1$, the starting value and blockwise coordinate descent algorithm in Cook et al. (2016) is implemented. When the dimension is r , then the envelope model degenerates to the standard multivariate linear regression for comparing group means. When the dimension is 0, it means there is no any group effect, and the fitting is different.

Value

The output is a list that contains the following components:

beta	The heteroscedastic envelope estimator of the group main effect. An r by p matrix, the i th column of the matrix contains the main effect for the i th group.
Sigma	A list of the heteroscedastic envelope estimator of the error covariance matrix. Sigma[[i]] contains the estimated covariance matrix for the i th group.
Gamma	An orthonormal basis of the heteroscedastic envelope subspace.
Gamma0	An orthonormal basis of the complement of the heteroscedastic envelope subspace.
eta	A list of the coordinates of beta with respect to Gamma. eta [[i]] indicates the coordinates of the main effect of the i th group with respect to Gamma.
Omega	A list of the coordinates of Sigma with respect to Gamma. Omega[[i]] indicates the coordinates of the covariance matrix of the i th group with respect to Gamma.
Omega0	The coordinates of Sigma with respect to Gamma0.
mu	The heteroscedastic envelope estimator of the grand mean. A r by 1 matrix.
mug	A list of the heteroscedastic envelope estimator of the group mean. An r by p matrix, the i th column of the matrix contains the mean for the i th group.
loglik	The maximized log likelihood function.
covMatrix	The asymptotic covariance of $(\mu, \text{vec}(\beta))'$. An $r(p + 1)$ by $r(p + 1)$ matrix. The covariance matrix returned are asymptotic. For the actual standard errors, multiply by $1 / n$.
asySE	The asymptotic standard error for elements in beta under the heteroscedastic envelope model. An r by p matrix. The standard errors returned are asymptotic, for actual standard errors, multiply by $1 / \text{sqrt}(n)$.
ratio	The asymptotic standard error ratio of the standard multivariate linear regression for comparing group means over the heteroscedastic envelope estimator, for each element in beta. An r by p matrix.
groupInd	A matrix containing the unique values of group indicators. The matrix has p rows.
n	The number of observations in the data.
ng	The number of observations in each group.
Yfit	Fitted responses.

References

- Su, Z. and Cook, R. D. (2013) Estimation of Multivariate Means with Heteroscedastic Error Using Envelope Models. *Statistica Sinica*, 23, 213-230.
- Cook, R. D., Li, B. and Chiaromonte, F. (2010). Envelope Models for Parsimonious and Efficient Multivariate Linear Regression (with discussion). *Statist. Sinica* 20, 927- 1010.
- Cook, R. D., Forzani, L. and Su, Z. (2016) A Note on Fast Envelope Estimation. *Journal of Multivariate Analysis*. 150, 42-54.

Examples

```
data(waterstrider)
X <- waterstrider[, 1]
Y <- waterstrider[, 2:5]

## Not run: u <- u.henv(X, Y)
## Not run: u

## Not run: m <- henv(X, Y, 2)
```

horseshoecrab

Horseshoe Crab Data

Description

The number of satellite male crabs near a female crab upon characteristic of the female horseshoe crabs.

Usage

```
data("horseshoecrab")
```

Format

A data frame with 173 observations on the following 5 variables.

V1 Color.

V2 Condition of spine.

V3 Width of shell.

V4 Satellite.

V5 Weight.

Details

This data set contains the number of satellite male crabs and characteristics of the female horseshoe crabs.

References

Agresti, A. (2007). An Introduction to Categorical Data Analysis, 2nd edition.

logit.env	<i>Fit the envelope model in logistic regression</i>
-----------	--

Description

Fit the envelope model in logistic regression with dimension u .

Usage

```
logit.env(X, Y, u, asy = TRUE, init = NULL)
```

Arguments

X	Predictors. An n by p matrix, p is the number of predictors and n is number of observations. The predictors must be continuous variables.
Y	Response. An n by 1 matrix. The univariate response must be binary.
u	Dimension of the envelope. An integer between 0 and p .
asy	Flag for computing the asymptotic variance of the envelope estimator. The default is TRUE. When p and r are large, computing the asymptotic variance can take much time and memory. If only the envelope estimators are needed, the flag can be set to asy = FALSE.
init	The user-specified value of Gamma for the envelope subspace in logistic regression. An p by u matrix. The default is the one generated by function logit.envMU.

Details

This function fits the envelope model in logistic regression,

$$Y = \exp(\mu + \beta'X) / (1 + \exp(\mu + \beta'X)), \Sigma_X = \Gamma\Omega\Gamma' + \Gamma_0\Omega_0\Gamma_0'$$

using the maximum likelihood estimation. When the dimension of the envelope is between 1 and $p-1$, the starting value and blockwise coordinate descent algorithm in Cook et al. (2016) is implemented. This model works the best when X is multivariate normal.

Value

The output is a list that contains the following components:

beta	The envelope estimator of the canonical parameter.
SigmaX	The envelope estimator of the covariance matrix of X .
Gamma	An orthonormal basis of the envelope subspace.
Gamma0	An orthonormal basis of the complement of the envelope subspace.
eta	The estimated beta of the canonical parameter with respect to Gamma.
Omega	The coordinates of SigmaX with respect to Gamma.

<code>Omega0</code>	The coordinates of <code>SigmaX</code> with respect to <code>Gamma0</code> .
<code>mu</code>	The estimated intercept of the canonical parameter.
<code>loglik</code>	The maximized log likelihood function.
<code>covMatrix</code>	The asymptotic covariance of <code>vec(beta)</code> . The covariance matrix returned are asymptotic. For the actual standard errors, multiply by $1 / n$.
<code>asySE</code>	The asymptotic standard error for elements in <code>beta</code> under the envelope model. The standard errors returned are asymptotic, for actual standard errors, multiply by $1 / \sqrt{n}$.
<code>ratio</code>	The asymptotic standard error ratio of the standard multivariate linear regression estimator over the envelope estimator, for each element in <code>beta</code> .
<code>n</code>	The number of observations in the data.

References

- Cook, R. D., Zhang, X. (2015). Foundations for Envelope Models and Methods. *Journal of the American Statistical Association* 110, 599 - 611.
- Cook, R. D., Forzani, L. and Su, Z. (2016) A Note on Fast Envelope Estimation. *Journal of Multivariate Analysis*. 150, 42-54.

Examples

```
data(horseshoecrab)
X1 <- as.numeric(horseshoecrab[, 1] == 2)
X2 <- as.numeric(horseshoecrab[, 1] == 3)
X3 <- as.numeric(horseshoecrab[, 1] == 4)
X4 <- as.numeric(horseshoecrab[, 2] == 2)
X5 <- as.numeric(horseshoecrab[, 2] == 3)
X6 <- horseshoecrab[, 3]
X7 <- horseshoecrab[, 5]
X <- cbind(X1, X2, X3, X4, X5, X6, X7)
Y <- as.numeric(ifelse(horseshoecrab[, 4] > 0, 1, 0))

## Not run: u <- u.logit.env(X, Y)
## Not run: u

## Not run: m <- logit.env(X, Y, 1)
## Not run: m$beta
```

penv

Fit the partial envelope model

Description

Fit the partial envelope model in multivariate linear regression with dimension `u`. The partial envelope model focuses on the coefficients of main interest.

Usage

```
penv(X1, X2, Y, u, asy = TRUE, init = NULL)
```

Arguments

X1	Predictors of main interest. An n by p1 matrix, n is the number of observations, and p1 is the number of main predictors. The predictors can be univariate or multivariate, discrete or continuous.
X2	Covariates, or predictors not of main interest. An n by p2 matrix, p2 is the number of covariates.
Y	Multivariate responses. An n by r matrix, r is the number of responses and n is number of observations. The responses must be continuous variables.
u	Dimension of the partial envelope. An integer between 0 and r.
asy	Flag for computing the asymptotic variance of the partial envelope estimator. The default is TRUE. When p and r are large, computing the asymptotic variance can take much time and memory. If only the partial envelope estimators are needed, the flag can be set to asy = FALSE.
init	The user-specified value of Gamma for the partial envelope subspace. An r by u matrix. The default is the one generated by function envMU.

Details

This function fits the partial envelope model to the responses Y and predictors X1 and X2,

$$Y = \mu + \Gamma\eta X_1 + \beta_2 X_2 + \varepsilon, \Sigma = \Gamma\Omega\Gamma' + \Gamma_0\Omega_0\Gamma_0'$$

using the maximum likelihood estimation. When the dimension of the envelope is between 1 and $r - 1$, we implemented the algorithm in Su and Cook (2011), but the partial envelope subspace is estimated using the blockwise coordinate descent algorithm in Cook et al. (2016). When the dimension is r, then the partial envelope model degenerates to the standard multivariate linear regression with Y as the responses and both X1 and X2 as predictors. When the dimension is 0, X1 and Y are uncorrelated, and the fitting is the standard multivariate linear regression with Y as the responses and X2 as the predictors.

Value

The output is a list that contains the following components:

beta1	The partial envelope estimator of beta1, which is the regression coefficients for X1.
beta2	The partial envelope estimator of beta2, which is the regression coefficients for X2.
Sigma	The partial envelope estimator of the error covariance matrix.
Gamma	An orthonormal basis of the partial envelope subspace.
Gamma0	An orthonormal basis of the complement of the partial envelope subspace.
eta	The coordinates of beta1 with respect to Gamma.

Omega	The coordinates of Sigma with respect to Gamma.
Omega0	The coordinates of Sigma with respect to Gamma0.
mu	The estimated intercept in the partial envelope model.
loglik	The maximized log likelihood function.
covMatrix	The asymptotic covariance of $\text{vec}(\beta)$, while $\beta = (\beta_1, \beta_2)$. The covariance matrix returned are asymptotic. For the actual standard errors, multiply by $1 / n$.
asySE1	The asymptotic standard error for elements in β_1 under the partial envelope model. The standard errors returned are asymptotic, for actual standard errors, multiply by $1 / \sqrt{n}$.
asySE2	The asymptotic standard error for elements in β_2 under the partial envelope model. The standard errors returned are asymptotic, for actual standard errors, multiply by $1 / \sqrt{n}$.
ratio	The asymptotic standard error ratio of the standard multivariate linear regression estimator over the partial envelope estimator, for each element in β_1 .
n	The number of observations in the data.

References

- Su, Z. and Cook, R.D. (2011). Partial envelopes for efficient estimation in multivariate linear regression. *Biometrika* 98, 133 - 146.
- Cook, R. D., Forzani, L. and Su, Z. (2016) A Note on Fast Envelope Estimation. *Journal of Multivariate Analysis*. 150, 42-54.

Examples

```
data(fiberpaper)
X1 <- fiberpaper[, 7]
X2 <- fiberpaper[, 5:6]
Y <- fiberpaper[, 1:4]
u <- u.penv(X1, X2, Y)
u

m <- penv(X1, X2, Y, 1)
m
m$beta1
```

pois.env

Fit the envelope model in poisson regression

Description

Fit the envelope model in poisson regression with dimension u.

Usage

```
pois.env(X, Y, u, asy = TRUE, init = NULL)
```

Arguments

X	Predictors. An n by p matrix, p is the number of predictors and n is number of observations. The predictors must be continuous variables.
Y	Response. An n by 1 matrix. The univariate response must be counts.
u	Dimension of the envelope. An integer between 0 and p.
asy	Flag for computing the asymptotic variance of the envelope estimator. The default is TRUE. When p and r are large, computing the asymptotic variance can take much time and memory. If only the envelope estimators are needed, the flag can be set to asy = FALSE.
init	The user-specified value of Gamma for the envelope subspace in poisson regression. An p by u matrix. The default is the one generated by function pois.envMU.

Details

This function fits the envelope model in poisson regression,

$$Y = \exp(\mu + \beta'X), \Sigma_X = \Gamma\Omega\Gamma' + \Gamma_0\Omega_0\Gamma_0'$$

using the maximum likelihood estimation. When the dimension of the envelope is between 1 and p-1, the starting value and blockwise coordinate descent algorithm in Cook et al. (2016) is implemented. This model works the best when X is multivariate normal.

Value

The output is a list that contains the following components:

beta	The envelope estimator of the canonical parameter.
SigmaX	The envelope estimator of the covariance matrix of X.
Gamma	An orthonormal basis of the envelope subspace.
Gamma0	An orthonormal basis of the complement of the envelope subspace.
eta	The estimated beta of the canonical parameter with respect to Gamma.
Omega	The coordinates of SigmaX with respect to Gamma.
Omega0	The coordinates of SigmaX with respect to Gamma0.
mu	The estimated intercept of the canonical parameter.
loglik	The maximized log likelihood function.
covMatrix	The asymptotic covariance of vec(beta). The covariance matrix returned are asymptotic. For the actual standard errors, multiply by 1 / n.
asySE	The asymptotic standard error for elements in beta under the envelope model. The standard errors returned are asymptotic, for actual standard errors, multiply by 1 / sqrt(n).
ratio	The asymptotic standard error ratio of the standard multivariate linear regression estimator over the envelope estimator, for each element in beta.
n	The number of observations in the data.

References

Cook, R. D., Zhang, X. (2015). Foundations for Envelope Models and Methods. Journal of the American Statistical Association 110, 599 - 611.

Cook, R. D., Forzani, L. and Su, Z. (2016) A Note on Fast Envelope Estimation. Journal of Multivariate Analysis. 150, 42-54.

Examples

```
data(horseshoecrab)
X1 <- as.numeric(horseshoecrab[, 1] == 2)
X2 <- as.numeric(horseshoecrab[, 1] == 3)
X3 <- as.numeric(horseshoecrab[, 1] == 4)
X4 <- as.numeric(horseshoecrab[, 2] == 2)
X5 <- as.numeric(horseshoecrab[, 2] == 3)
X6 <- horseshoecrab[, 3]
X7 <- horseshoecrab[, 5]
X <- cbind(X1, X2, X3, X4, X5, X6, X7)
Y <- horseshoecrab[, 4]

## Not run: u <- u.pois.env(X, Y)
## Not run: u

m <- pois.env(X, Y, 1)
m$beta
```

pred.env

Estimation or prediction for env

Description

Perform estimation or prediction under the response envelope model.

Usage

```
pred.env(m, Xnew)
```

Arguments

m A list containing estimators and other statistics inherited from env.
Xnew The value of X with which to estimate or predict Y. A p dimensional vector.

Details

This function evaluates the envelope model at new value Xnew. It can perform estimation: find the fitted value when $X = X_{\text{new}}$, or prediction: predict Y when $X = X_{\text{new}}$. The covariance matrix and the standard errors are also provided.

Value

The output is a list that contains following components.

value	The fitted value or the predicted value evaluated at Xnew.
covMatrix.estm	The covariance matrix of the fitted value at Xnew.
SE.estm	The standard error of the fitted value at Xnew.
covMatrix.pred	The covariance matrix of the predicted value at Xnew.
SE.pred	The standard error of the predicted value at Xnew.

Examples

```
data(wheatprotein)
X <- wheatprotein[, 8]
Y <- wheatprotein[, 1:6]
u <- u.env(X, Y)
u

m <- env(X, Y, 1)
m

X <- as.matrix(X)
pred.res <- pred.env(m, X[2, ])
pred.res
```

pred.genv	<i>Estimation or prediction for genv</i>
-----------	--

Description

Perform estimation or prediction under the groupwise envelope model.

Usage

```
pred.genv(m, Xnew, Znew)
```

Arguments

m	A list containing estimators and other statistics inherited from env.
Xnew	The value of X with which to estimate or predict Y. A p dimensional vector.
Znew	A group indicator of X.

Details

This function evaluates the envelope model at new value Xnew. It can perform estimation: find the fitted value when $X = X_{\text{new}}$ with a group indicator $Z = Z_{\text{new}}$, or prediction: predict Y when $X = X_{\text{new}}$ with a group indicator $Z = Z_{\text{new}}$. The covariance matrix and the standard errors are also provided.

Value

The output is a list that contains following components.

value	The fitted value or the predicted value evaluated at Z_{new} .
covMatrix.estm	The covariance matrix of the fitted value at Z_{new} .
SE.estm	The standard error of the fitted value at Z_{new} .
covMatrix.pred	The covariance matrix of the predicted value at Z_{new} .
SE.pred	The standard error of the predicted value at Z_{new} .

Examples

```
data(fiberpaper)
X <- fiberpaper[ , c(5, 7)]
Y <- fiberpaper[ , 1:3]
Z <- as.numeric(fiberpaper[ , 6] > mean(fiberpaper[ , 6]))
u <- u.genv(X, Y, Z)
u

m <- genv(X, Y, Z, 2)
m

X <- as.matrix(X)
pred.res <- pred.genv(m, X[2, ], Z[2])
pred.res
```

pred.henv

Estimation or prediction for henv

Description

Perform estimation or prediction under the heteroscedastic envelope model.

Usage

```
pred.henv(m, Xnew)
```

Arguments

m	A list containing estimators and other statistics inherited from henv.
Xnew	The value of X with which to estimate or predict Y. An r by 1 vector.

Details

This function evaluates the heteroscedastic envelope model at new value X_{new} . It can perform estimation: find the fitted value when $X = X_{new}$, or prediction: predict Y when $X = X_{new}$. The covariance matrix and the standard errors are also provided.

Value

The output is a list that contains following components.

value	The fitted value or the predicted value evaluated at Xnew.
covMatrix.estm	The covariance matrix of the fitted value at Xnew.
SE.estm	The standard error of the fitted value at Xnew.
covMatrix.pred	The covariance matrix of the predicted value at Xnew.
SE.pred	The standard error of the predicted value at Xnew.

Examples

```
data(waterstrider)
X <- waterstrider[, 1]
Y <- waterstrider[, 2:5]

## Not run: m <- henv(X, Y, 2)

## Not run: pred.res <- pred.henv(m, X[2])
```

pred.logit.env

Estimation or prediction for logit.env

Description

Perform estimation or prediction under the envelope model in logistic regression.

Usage

```
pred.logit.env(m, Xnew)
```

Arguments

m	A list containing estimators and other statistics inherited from xenv.
Xnew	The value of X with which to estimate or predict Y. A p dimensional vector.

Details

This function evaluates the envelope model at new value Xnew. It can perform estimation: find the fitted value when $X = X_{new}$. The covariance matrix of estimation and the standard errors of estimation are also provided.

Value

The output is a list that contains following components.

value The fitted value or predicted value evaluated at Xnew.
 covMatrix.estm The covariance matrix of the fitted value at Xnew.
 SE.estm The standard error of the fitted value at Xnew.

Examples

```
data(horseshoecrab)
X1 <- as.numeric(horseshoecrab[ , 1] == 2)
X2 <- as.numeric(horseshoecrab[ , 1] == 3)
X3 <- as.numeric(horseshoecrab[ , 1] == 4)
X4 <- as.numeric(horseshoecrab[ , 2] == 2)
X5 <- as.numeric(horseshoecrab[ , 2] == 3)
X6 <- horseshoecrab[ , 3]
X7 <- horseshoecrab[ , 5]
X <- cbind(X1, X2, X3, X4, X5, X6, X7)
Y <- as.numeric(iffelse(horseshoecrab[ , 4] > 0, 1, 0))

m <- logit.env(X, Y, 1)

pred.res <- pred.logit.env(m, X[1, ])
pred.res
```

 pred.penv

Estimation or prediction for penv

Description

Perform estimation or prediction under the partial envelope model.

Usage

```
pred.penv(m, X1new, X2new)
```

Arguments

m A list containing estimators and other statistics inherited from penv.
 X1new The value of X1 with which to estimate or predict Y. A p1 dimensional vector.
 X2new The value of X2 with which to estimate or predict Y. A p2 dimensional vector.

Details

This function evaluates the partial envelope model at new value Xnew. It can perform estimation: find the fitted value when $X = X_{\text{new}}$, or prediction: predict Y when $X = X_{\text{new}}$. The covariance matrix and the standard errors are also provided.

Value

The output is a list that contains following components.

value	The fitted value or the predicted value evaluated at X1new and X2new.
covMatrix.estm	The covariance matrix of the fitted value at X1new and X2new.
SE.estm	The standard error of the fitted value at X1new and X2new.
covMatrix.pred	The covariance matrix of the predicted value at X1new and X2new.
SE.pred	The standard error of the predicted value at X1new and X2new.

Examples

```
data(fiberpaper)
X1 <- fiberpaper[, 7]
X2 <- fiberpaper[, 5:6]
Y <- fiberpaper[, 1:4]
m <- penv(X1, X2, Y, 1)

pred.res <- pred.penv(m, X1[1], X2[1, ])
pred.res
```

pred.pois.env *Estimation or prediction for pois.env*

Description

Perform estimation or prediction under the envelope model in poisson regression.

Usage

```
pred.pois.env(m, Xnew)
```

Arguments

m	A list containing estimators and other statistics inherited from xenv.
Xnew	The value of X with which to estimate or predict Y. A p dimensional vector.

Details

This function evaluates the envelope in poisson regression at new value Xnew. It can perform estimation: find the fitted value when $X = X_{new}$, or prediction: predict Y when $X = X_{new}$. The covariance matrix of estimation and the standard errors of estimation are also provided.

Value

The output is a list that contains following components.

value	The fitted value or the predicted value evaluated at Xnew.
covMatrix.estm	The covariance matrix of the fitted value at Xnew.
SE.estm	The standard error of the fitted value at Xnew.

Examples

```

data(horseshoecrab)
X1 <- as.numeric(horseshoecrab[ , 1] == 2)
X2 <- as.numeric(horseshoecrab[ , 1] == 3)
X3 <- as.numeric(horseshoecrab[ , 1] == 4)
X4 <- as.numeric(horseshoecrab[ , 2] == 2)
X5 <- as.numeric(horseshoecrab[ , 2] == 3)
X6 <- horseshoecrab[ , 3]
X7 <- horseshoecrab[ , 5]
X <- cbind(X1, X2, X3, X4, X5, X6, X7)
Y <- horseshoecrab[ , 4]

m <- pois.env(X, Y, 1)

pred.res <- pred.pois.env(m, X[1, ])
pred.res

```

pred.senv

Estimation or prediction for senv

Description

Perform estimation or prediction under the scaled response envelope model.

Usage

```
pred.senv(m, Xnew)
```

Arguments

m	A list containing estimators and other statistics inherited from scale.env.
Xnew	The value of X with which to estimate or predict Y. A p dimensional vector.

Details

This function evaluates the scaled envelope model at new value Xnew. It can perform estimation: find the fitted value when $X = X_{\text{new}}$, or prediction: predict Y when $X = X_{\text{new}}$. The covariance matrix and the standard errors are also provided.

Value

The output is a list that contains following components.

value	The fitted value or the predicted value evaluated at Xnew.
covMatrix.estm	The covariance matrix of the fitted value at Xnew.
SE.estm	The standard error of the fitted value at Xnew.
covMatrix.pred	The covariance matrix of the predicted value at Xnew.
SE.pred	The standard error of the predicted value at Xnew.

Examples

```

data(sales)
X <- sales[, 1:3]
Y <- sales[, 4:7]

m <- senv(X, Y, 2)

pred.res <- pred.senv(m, X[2, ])
pred.res

```

pred.stenv

Estimation or prediction for stenv

Description

Perform estimation or prediction under the simultaneous envelope model.

Usage

```
pred.stenv(m, Xnew)
```

Arguments

m	A list containing estimators and other statistics inherited from stenv.
Xnew	The value of X with which to estimate or predict Y. A p dimensional vector.

Details

This function evaluates the simultaneous envelope model at new value Xnew. It can perform estimation: find the fitted value when $X = X_{\text{new}}$, or prediction: predict Y when $X = X_{\text{new}}$. The covariance matrix and the standard errors are also provided.

Value

The output is a list that contains following components.

value	The fitted value or the predicted value evaluated at Xnew.
covMatrix.estm	The covariance matrix of the fitted value at Xnew.
SE.estm	The standard error of the fitted value at Xnew.
covMatrix.pred	The covariance matrix of the predicted value at Xnew.
SE.pred	The standard error of the predicted value at Xnew.

Examples

```

data(fiberpaper)
X <- fiberpaper[, 5:7]
Y <- fiberpaper[, 1:4]

m <- stenv(X, Y, 2, 3)
m

pred.res <- pred.stenv(m, X[1, ])
pred.res

```

pred.sxenv

Estimation or prediction for sxenv

Description

Perform estimation or prediction under the scaled predictor envelope model.

Usage

```
pred.sxenv(m, Xnew)
```

Arguments

m A list containing estimators and other statistics inherited from stenv.
Xnew The value of X with which to estimate or predict Y. A p dimensional vector.

Details

This function evaluates the scaled envelope model in the predictor space at new value Xnew. It can perform estimation: find the fitted value when $X = X_{\text{new}}$, or prediction: predict Y when $X = X_{\text{new}}$. The covariance matrix and the standard errors are also provided.

Value

The output is a list that contains following components.

value The fitted value or the predicted value evaluated at Xnew.
covMatrix.estm The covariance matrix of the fitted value at Xnew.
SE.estm The standard error of the fitted value at Xnew.
covMatrix.pred The covariance matrix of the predicted value at Xnew.
SE.pred The standard error of the predicted value at Xnew.

Examples

```

data(sales)
Y <- sales[, 1:3]
X <- sales[, 4:7]
R <- rep(1, 4)

m <- sxenv(X, Y, 2, R)

pred.res <- pred.sxenv(m, X[1, ])
pred.res

```

pred.xenv

Estimation or prediction for xenv

Description

Perform estimation or prediction under the predictor envelope model.

Usage

```
pred.xenv(m, Xnew)
```

Arguments

m	A list containing estimators and other statistics inherited from xenv.
Xnew	The value of X with which to estimate or predict Y. A p dimensional vector.

Details

This function evaluates the envelope model at new value Xnew. It can perform estimation: find the fitted value when $X = X_{\text{new}}$, or prediction: predict Y when $X = X_{\text{new}}$. The covariance matrix and the standard errors are also provided.

Value

The output is a list that contains following components.

value	The fitted value or the predicted value evaluated at Xnew.
covMatrix.estm	The covariance matrix of the fitted value at Xnew.
SE.estm	The standard error of the fitted value at Xnew.
covMatrix.pred	The covariance matrix of the predicted value at Xnew.
SE.pred	The standard error of the predicted value at Xnew.

Examples

```

data(wheatprotein)
X <- wheatprotein[, 1:6]
Y <- wheatprotein[, 7]

m <- xenv(X, Y, 2)
m

pred.res <- pred.xenv(m, X[1, ])
pred.res

```

pred2.env

Estimation or prediction for env

Description

Perform estimation or prediction under the envelope model through partial envelope model.

Usage

```
pred2.env(X, Y, u, Xnew)
```

Arguments

X	Predictors. An n by p matrix, p is the number of predictors. The predictors can be univariate or multivariate, discrete or continuous.
Y	Multivariate responses. An n by r matrix, r is the number of responses and n is number of observations. The responses must be continuous variables.
u	The dimension of the constructed partial envelope model.
Xnew	The value of X with which to estimate or predict Y. A p dimensional vector.

Details

This function evaluates the envelope model at new value Xnew. It can perform estimation: find the fitted value when X = Xnew, or prediction: predict Y when X = Xnew. The covariance matrix and the standard errors are also provided. Compared to predict.env, this function performs prediction through partial envelope model, which can be more accurate if the partial envelope is of smaller dimension and contains less variant material information. The constructed partial envelope model is obtained by the following: Let A0 by a p by p-1 matrix, such that A = (Xnew, A0) has full rank. Let phi1 = beta * Xnew, phi2 = beta * A0, phi = (phi1, phi2) and X = inverse of A * X = (Z1, Z2')'. Then the model Y = alpha + beta * X + epsilon can be reparameterized as Y = alpha + phi1 * Z1 + phi2 * Z2 + epsilon. We then fit a partial envelope model with Z1 as the predictor of interest, and predict at (Z1, Z2')' = inverse of A * Xnew.

Value

The output is a list that contains following components.

value	The fitted value or the predicted value evaluated at Xnew.
covMatrix.estm	The covariance matrix of the fitted value at Xnew.
SE.estm	The standard error of the fitted value at Xnew.
covMatrix.pred	The covariance matrix of the predicted value at Xnew.
SE.pred	The standard error of the predicted value at Xnew.

Examples

```
data(fiberpaper)
X <- fiberpaper[, 5:7]
Y <- fiberpaper[, 1:4]

u <- u.pred2.env(X, Y, X[10, ])
pred.res <- pred2.env(X, Y, u$u.bic, X[10, ])
pred.res$SE.estm
pred.res$SE.pred
```

sales

Sales staff Data

Description

On the performance of a firm's sales staff

Usage

```
data("sales")
```

Format

A data frame with 50 observations on the following 7 variables.

- V1 Index of sales growth.
- V2 Index of sales profitability.
- V3 Index of new account sales.
- V4 Score on creativity.
- V5 Score on mechanical reasoning test.
- V6 Score on abstract reasoning test.
- V7 Score on Mathematics test.

Details

This data set contains 3 measures of performance and 4 tests scores.

References

Johnson, R.A., Wichern, D.W. (2007). Applied Multivariate Statistical Analysis, 6th edition.

senv

Fit the scaled response envelope model

Description

Fit the scaled response envelope model in multivariate linear regression with dimension u . The scaled response envelope model is a scale-invariant version of the response envelope model.

Usage

```
senv(X, Y, u, asy = TRUE, init = NULL)
```

Arguments

<code>X</code>	Predictors. An n by p matrix, p is the number of predictors. The predictors can be univariate or multivariate, discrete or continuous.
<code>Y</code>	Multivariate responses. An n by r matrix, r is the number of responses and n is number of observations. The responses must be continuous variables.
<code>u</code>	Dimension of the scaled envelope. An integer between 0 and r .
<code>asy</code>	Flag for computing the asymptotic variance of the envelope estimator. The default is TRUE. When p and r are large, computing the asymptotic variance can take much time and memory. If only the scaled envelope estimators are needed, the flag can be set to <code>asy = FALSE</code> .
<code>init</code>	The user-specified value of Gamma for the scaled envelope subspace. An r by u matrix. The default is the one generated by function <code>senvMU</code> .

Details

This function fits the scaled envelope model to the responses and predictors,

$$Y = \mu + \Lambda\Gamma\eta X + \varepsilon, \Sigma = \Lambda\Gamma\Omega\Gamma'\Lambda + \Lambda\Gamma_0\Omega_0\Gamma_0'\Lambda$$

using the maximum likelihood estimation. When the dimension of the scaled envelope is between 1 and $r-1$, the starting value and blockwise coordinate descent algorithm in Cook et al. (2016) is implemented. When the dimension is r , then the scaled envelope model degenerates to the standard multivariate linear regression. When the dimension is 0, it means that X and Y are uncorrelated, and the fitting is different.

Value

The output is a list that contains the following components:

beta	The scaled envelope estimator of the regression coefficients.
Sigma	The scaled envelope estimator of the error covariance matrix.
Lambda	The matrix of estimated scale.
Gamma	An orthonormal basis of the scaled envelope subspace.
Gamma0	An orthonormal basis of the complement of the scaled envelope subspace.
eta	The coordinates of beta with respect to Gamma.
Omega	The coordinates of Sigma with respect to Gamma.
Omega0	The coordinates of Sigma with respect to Gamma0.
mu	The estimated intercept.
loglik	The maximized log likelihood function.
covMatrix	The asymptotic covariance of vec(beta). The covariance matrix returned are asymptotic. For the actual standard errors, multiply by 1 / n.
asySE	The asymptotic standard error for elements in beta under the envelope model. The standard errors returned are asymptotic, for actual standard errors, multiply by 1 / sqrt(n).
ratio	The asymptotic standard error ratio of the standard multivariate linear regression estimator over the envelope estimator, for each element in beta.
n	The number of observations in the data.

References

- Cook, R. D., Su, Z. (2013). Scaled Envelopes: scale Invariant and Efficient Estimation in Multivariate Linear Regression. *Biometrika* 100, 939 - 954.
- Cook, R. D., Forzani, L. and Su, Z. (2016) A Note on Fast Envelope Estimation. *Journal of Multivariate Analysis*. 150, 42-54.

Examples

```
data(sales)
X <- sales[, 1:3]
Y <- sales[, 4:7]

u <- u.senv(X, Y)
u

m <- senv(X, Y, 2)
m$beta
```

 stenv

Fit the simultaneous envelope model

Description

Fit the simultaneous envelope model in multivariate linear regression with dimension (q, u) .

Usage

```
stenv(X, Y, q, u, asy = TRUE, Pinit = NULL, Ginit = NULL)
```

Arguments

X	Predictors. An n by p matrix, p is the number of predictors. The predictors can be univariate or multivariate, discrete or continuous.
Y	Multivariate responses. An n by r matrix, r is the number of responses and n is number of observations. The responses must be continuous variables.
q	Dimension of the X-envelope. An integer between 0 and p .
u	Dimension of the Y-envelope. An integer between 0 and r .
asy	Flag for computing the asymptotic variance of the envelope estimator. The default is TRUE. When p and r are large, computing the asymptotic variance can take much time and memory. If only the envelope estimators are needed, the flag can be set to <code>asy = FALSE</code> .
Pinit	The user-specified value of Phi for the X-envelope subspace. An p by q matrix. The default is the one generated by function <code>stenvMU</code> .
Ginit	The user-specified value of Gamma for the Y-envelope subspace. An r by u matrix. The default is the one generated by function <code>stenvMU</code> .

Details

This function fits the envelope model to the responses and predictors simultaneously,

$$Y = \mu + \Gamma\eta'\Phi'X + \varepsilon, \Sigma_{Y|X} = \Gamma\Omega\Gamma' + \Gamma_0\Omega_0\Gamma_0', \Sigma_X = \Phi\Delta\Phi' + \Phi_0\Delta_0\Phi_0'$$

using the maximum likelihood estimation. When the dimension of the Y-envelope is between 1 and $r-1$ and the dimension of the X-envelope is between 1 and $p-1$, the starting value and blockwise coordinate descent algorithm in Cook et al. (2016) is implemented. When the dimension is (p, r) , then the envelope model degenerates to the standard multivariate linear regression. When the dimension of the Y-envelope is r , then the envelope model degenerates to the standard envelope model. When the dimension of X-envelope is p , then the envelope model degenerates to the envelope model in the predictor space. When the dimension is 0, it means that X and Y are uncorrelated, and the fitting is different.

Value

The output is a list that contains the following components:

beta	The envelope estimator of the regression coefficients.
SigmaYcX	The envelope estimator of the error covariance matrix.
SigmaX	The envelope estimator of the covariance matrix of X.
Gamma	An orthonormal basis of the Y-envelope subspace.
Gamma0	An orthonormal basis of the complement of the Y-envelope subspace.
eta	The coordinates of beta with respect to Gamma and Phi.
Omega	The coordinates of SigmaYcX with respect to Gamma.
Omega0	The coordinates of SigmaYcX with respect to Gamma0.
mu	The estimated intercept.
Phi	An orthonormal basis of the X-envelope subspace.
Phi0	An orthonormal basis of the complement of the X-envelope subspace.
Delta	The coordinates of SigmaX with respect to Phi.
Delta0	The coordinates of SigmaX with respect to Phi0.
loglik	The maximized log likelihood function.
covMatrix	The asymptotic covariance of vec(beta). The covariance matrix returned are asymptotic. For the actual standard errors, multiply by 1 / n.
asySE	The asymptotic standard error for elements in beta under the envelope model. The standard errors returned are asymptotic, for actual standard errors, multiply by 1 / sqrt(n).
ratio	The asymptotic standard error ratio of the standard multivariate linear regression estimator over the envelope estimator, for each element in beta.
n	The number of observations in the data.

References

- Cook, R. D., Zhang, X. (2015). Simultaneous Envelopes for Multivariate Linear Regression. *Technometrics* 57, 11 - 25.
- Cook, R. D., Forzani, L. and Su, Z. (2016) A Note on Fast Envelope Estimation. *Journal of Multivariate Analysis*. 150, 42-54.

Examples

```
data(fiberpaper)
X <- fiberpaper[, 5:7]
Y <- fiberpaper[, 1:4]
u <- u.stenv(X, Y)
u

m <- stenv(X, Y, 2, 3)
m
m$beta
```

 sxenv

Fit the scaled predictor envelope model

Description

Fit the scaled predictor envelope model in multivariate linear regression with dimension u . The scaled predictor envelope model is a scale-invariant version of the predictor envelope model.

Usage

```
sxenv(X, Y, u, R, asy = TRUE, init = NULL)
```

Arguments

<code>X</code>	Predictors. An n by p matrix, p is the number of predictors. The predictors can be univariate or multivariate, discrete or continuous.
<code>Y</code>	Multivariate responses. An n by r matrix, r is the number of responses and n is number of observations. The responses must be continuous variables.
<code>u</code>	Dimension of the scaled envelope in the predictor space. An integer between 0 and p .
<code>R</code>	The number of replications of the scales. A vector, the sum of all elements of R must be p .
<code>asy</code>	Flag for computing the asymptotic variance of the envelope estimator. The default is TRUE. When p and r are large, computing the asymptotic variance can take much time and memory. If only the envelope estimators are needed, the flag can be set to <code>asy = FALSE</code> .
<code>init</code>	The user-specified value of Gamma for the scaled envelope subspace in the predictor space. An p by u matrix. The default is the one generated by function <code>sxenvMU</code> .

Details

This function fits the scaled envelope model in the predictor space to the responses and predictors,

$$Y = \mu_Y + \eta' \Gamma' \Lambda^{-1} (X - \mu_X) + \varepsilon, \Sigma_X = \Lambda \Gamma \Omega \Gamma' \Lambda + \Lambda \Gamma_0 \Omega_0 \Gamma_0' \Lambda$$

using the maximum likelihood estimation. When the dimension of the scaled envelope in the predictor space is between 1 and $p-1$, the starting value and blockwise coordinate descent algorithm in Cook et al. (2016) is implemented. When the dimension is p , then the scaled envelope model in the predictor space degenerates to the standard multivariate linear regression. When the dimension is 0, it means that X and Y are uncorrelated, and the fitting is different.

Value

The output is a list that contains the following components:

beta	The scaled envelope estimator of the regression coefficients.
Sigma	The scaled envelope estimator of the error covariance matrix.
Lambda	The matrix of estimated scale.
Gamma	An orthonormal basis of the scaled envelope subspace.
Gamma0	An orthonormal basis of the complement of the scaled envelope subspace.
eta	The coordinates of beta with respect to Gamma.
Omega	The coordinates of Sigma with respect to Gamma.
Omega0	The coordinates of Sigma with respect to Gamma0.
muY	The mean of Y.
muX	The mean of X.
loglik	The maximized log likelihood function.
covMatrix	The asymptotic covariance of vec(beta). The covariance matrix returned are asymptotic. For the actual standard errors, multiply by 1 / n.
asySE	The asymptotic standard error for elements in beta under the envelope model. The standard errors returned are asymptotic, for actual standard errors, multiply by 1 / sqrt(n).
ratio	The asymptotic standard error ratio of the standard multivariate linear regression estimator over the envelope estimator, for each element in beta.
n	The number of observations in the data.

References

- Cook, R. D., Su, Z. (2016). Scaled Predictor Envelopes and Partial Least Squares Regression. *Technometrics* 58, 155 - 165.
- Cook, R. D., Forzani, L. and Su, Z. (2016) A Note on Fast Envelope Estimation. *Journal of Multivariate Analysis*. 150, 42-54.

Examples

```
data(sales)
Y <- sales[, 1:3]
X <- sales[, 4:7]
R <- rep(1, 4)

u <- u.sxenv(X, Y, R)
u

m <- sxenv(X, Y, 2, R)
m$beta
```

testcoef.env

Hypothesis test of the coefficients of the response envelope model

Description

This function tests the null hypothesis $L * \beta * R = A$ versus the alternative hypothesis $L * \beta * R \neq A$, where β is estimated under the response envelope model.

Usage

```
testcoef.env(m, L, R, A)
```

Arguments

m	A list containing estimators and other statistics inherited from env.
L	The matrix multiplied to beta on the left. It is a d_1 by r matrix, while d_1 is less than or equal to r .
R	The matrix multiplied to beta on the right. It is a p by d_2 matrix, while d_2 is less than or equal to p .
A	The matrix on the right hand side of the equation. It is a d_1 by d_2 matrix. Note that inputs L, R and A must be matrices, if not, use <code>as.matrix</code> to convert them.

Details

This function tests for hypothesis $H_0: L \beta R = A$, versus $H_a: L \beta R \neq A$. The β is estimated by the envelope model. If $L = I_r$, $R = I_p$ and $A = 0$, then the test is equivalent to the standard F test on if $\beta = 0$. The test statistic used is $\text{vec}(L \beta R - A) \hat{\Sigma}^{-1} \text{vec}(L \beta R - A)^T$, where β is the envelope estimator and $\hat{\Sigma}$ is the estimated asymptotic covariance of $\text{vec}(L \beta R - A)$. The reference distribution is chi-squared distribution with degrees of freedom $d_1 * d_2$.

Value

The output is a list that contains following components.

chisqStatistic	The test statistic.
dof	The degrees of freedom of the reference chi-squared distribution.
pValue	p-value of the test.
covMatrix	The covariance matrix of $\text{vec}(L \beta R)$.

Examples

```

data(wheatprotein)
X <- wheatprotein[, 8]
Y <- wheatprotein[, 1:6]
m <- env(X, Y, 1)
m

L <- diag(6)
R <- as.matrix(1)
A <- matrix(0, 6, 1)

test.res <- testcoef.env(m, L, R, A)
test.res

```

testcoef.genv

Hypothesis test of the coefficients of the groupwise envelope model

Description

This function tests the null hypothesis $L * \beta * R = A$ versus the alternative hypothesis $L * \beta * R \neq A$, where β is estimated under the groupwise envelope model.

Usage

```
testcoef.genv(m, L, R, A)
```

Arguments

m	A list containing estimators and other statistics inherited from <code>genv</code> .
L	The matrix multiplied to β on the left. It is a d_1 by r matrix, while d_1 is less than or equal to r .
R	The matrix multiplied to β on the right. It is a p by d_2 matrix, while d_2 is less than or equal to p .
A	The matrix on the right hand side of the equation. It is a d_1 by d_2 matrix. Note that inputs L , R and A must be matrices, if not, use <code>as.matrix</code> to convert them.

Details

This function tests for hypothesis $H_0: L \beta R = A$, versus $H_a: L \beta R \neq A$. The β is estimated by the groupwise envelope model. If $L = I_r$, $R = I_p$ and $A = 0$, then the test is equivalent to the standard F test on if $\beta = 0$. The test statistic used is $\text{vec}(L \beta R - A) \hat{\Sigma}^{-1} \text{vec}(L \beta R - A)^T$, where β is the envelope estimator and $\hat{\Sigma}$ is the estimated asymptotic covariance of $\text{vec}(L \beta R - A)$. The reference distribution is chi-squared distribution with degrees of freedom $d_1 * d_2$.

Value

The output is a list that contains following components.

`chisqStatistic` The test statistic.
`dof` The degrees of freedom of the reference chi-squared distribution.
`pValue` p-value of the test.
`covMatrix` The covariance matrix of $\text{vec}(L \beta R)$.

Examples

```
data(fiberpaper)
X <- fiberpaper[ , c(5, 7)]
Y <- fiberpaper[ , 1:3]
Z <- as.numeric(fiberpaper[ , 6] > mean(fiberpaper[ , 6]))
u <- u.genv(X, Y, Z)
u

m <- genv(X, Y, Z, 2)
m

L <- diag(3)
R <- diag(2)
A <- matrix(0, 3, 2)

test.res <- testcoef.genv(m, L, R, A)
test.res
```

testcoef.henv	<i>Hypothesis test of the coefficients of the heteroscedastic envelope model</i>
---------------	--

Description

This function tests the null hypothesis $L * \beta * R = A$ versus the alternative hypothesis $L * \beta * R \neq A$, where β is estimated under the heteroscedastic envelope model.

Usage

```
testcoef.henv(m, L, R, A)
```

Arguments

`m` A list containing estimators and other statistics inherited from `genv`.
`L` The matrix multiplied to β on the left. It is a d_1 by r matrix, while d_1 is less than or equal to r .
`R` The matrix multiplied to β on the right. It is a p by d_2 matrix, while d_2 is less than or equal to p .

A The matrix on the right hand side of the equation. It is a $d1$ by $d2$ matrix.
Note that inputs L, R and A must be matrices, if not, use `as.matrix` to convert them.

Details

This function tests for hypothesis $H_0: L\beta R = A$, versus $H_a: L\beta R \neq A$. The beta is estimated by the heteroscedastic envelope model. If $L = I_r$, $R = I_p$ and $A = 0$, then the test is equivalent to the standard F test on if $\beta = 0$. The test statistic used is $\text{vec}(L\beta R - A) \hat{\Sigma}^{-1} \text{vec}(L\beta R - A)^T$, where beta is the envelope estimator and $\hat{\Sigma}$ is the estimated asymptotic covariance of $\text{vec}(L\beta R - A)$. The reference distribution is chi-squared distribution with degrees of freedom $d1 * d2$.

Value

The output is a list that contains following components.

`chisqStatistic` The test statistic.
`dof` The degrees of freedom of the reference chi-squared distribution.
`pValue` p-value of the test.
`covMatrix` The covariance matrix of $\text{vec}(L\beta R)$.

Examples

```
data(waterstrider)
X <- waterstrider[, 1]
Y <- waterstrider[, 2:5]

## Not run: m <- henv(X, Y, 2)
## Not run: m

L <- diag(4)
R <- matrix(c(1, -1, 0), 3, 1)
A <- matrix(0, 4, 1)

## Not run: test.res <- testcoef.henv(m, L, R, A)
## Not run: test.res
```

testcoef.logit.env *Hypothesis test of the coefficients of the envelope model*

Description

This function tests the null hypothesis $L * \beta = A$ versus the alternative hypothesis $L * \beta \neq A$, where beta is estimated under the envelope model in logistic regression.

Usage

```
testcoef.logit.env(m, L, A)
```

Arguments

<code>m</code>	A list containing estimators and other statistics inherited from <code>logit.env</code> .
<code>L</code>	The matrix multiplied to beta on the left. It is a $d1$ by p matrix, while $d1$ is less than or equal to p .
<code>A</code>	The matrix on the right hand side of the equation. It is a $d1$ by 1 matrix. Note that inputs <code>L</code> and <code>A</code> must be matrices, if not, use <code>as.matrix</code> to convert them.

Details

This function tests for hypothesis $H_0: L\beta = A$, versus $H_a: L\beta \neq A$. The beta is estimated by the envelope model in predictor space. If $L = I_p$ and $A = 0$, then the test is equivalent to the standard F test on if $\beta = 0$. The test statistic used is $\text{vec}(L\hat{\beta} - A) \hat{\Sigma}^{-1} \text{vec}(L\hat{\beta} - A)^T$, where $\hat{\beta}$ is the envelope estimator and $\hat{\Sigma}$ is the estimated asymptotic covariance of $\text{vec}(L\hat{\beta} - A)$. The reference distribution is chi-squared distribution with degrees of freedom $d1$.

Value

The output is a list that contains following components.

<code>chisqStatistic</code>	The test statistic.
<code>dof</code>	The degrees of freedom of the reference chi-squared distribution.
<code>pValue</code>	p-value of the test.
<code>covMatrix</code>	The covariance matrix of $\text{vec}(L\hat{\beta})$.

Examples

```
data(horseshoecrab)
X1 <- as.numeric(horseshoecrab[, 1] == 2)
X2 <- as.numeric(horseshoecrab[, 1] == 3)
X3 <- as.numeric(horseshoecrab[, 1] == 4)
X4 <- as.numeric(horseshoecrab[, 2] == 2)
X5 <- as.numeric(horseshoecrab[, 2] == 3)
X6 <- horseshoecrab[, 3]
X7 <- horseshoecrab[, 5]
X <- cbind(X1, X2, X3, X4, X5, X6, X7)
Y <- as.numeric(ifelse(horseshoecrab[, 4] > 0, 1, 0))

m <- logit.env(X, Y, 1)

L <- diag(7)
A <- matrix(0, 7, 1)

test.res <- testcoef.logit.env(m, L, A)
test.res
```

testcoef.penv

*Hypothesis test of the coefficients of the partial envelope model***Description**

This function tests the null hypothesis $L * \beta_1 * R = A$ versus the alternative hypothesis $L * \beta_1 * R \neq A$, where β_1 is estimated under the partial envelope model.

Usage

```
testcoef.penv(m, L, R, A)
```

Arguments

<code>m</code>	A list containing estimators and other statistics inherited from <code>penv</code> .
<code>L</code>	The matrix multiplied to β_1 on the left. It is a d_1 by r matrix, while d_1 is less than or equal to r .
<code>R</code>	The matrix multiplied to β_1 on the right. It is a p_1 by d_2 matrix, while d_2 is less than or equal to p_1 .
<code>A</code>	The matrix on the right hand side of the equation. It is a d_1 by d_2 matrix. Note that inputs <code>L</code> , <code>R</code> and <code>A</code> must be matrices, if not, use <code>as.matrix</code> to convert them.

Details

This function tests for hypothesis $H_0: L \beta_1 R = A$, versus $H_a: L \beta_1 R \neq A$. The β_1 is estimated by the partial envelope model. If $L = I_r$, $R = I_{p_1}$ and $A = 0$, then the test is equivalent to the standard F test on if $\beta_1 = 0$. The test statistics used is $\text{vec}(L \beta_1 R - A) \hat{\Sigma}^{-1} \text{vec}(L \beta_1 R - A)^T$, where β_1 is the envelope estimator and $\hat{\Sigma}$ is the estimated asymptotic covariance of $\text{vec}(L \beta_1 R - A)$. The reference distribution is chi-squared distribution with degrees of freedom $d_1 * d_2$.

Value

The output is a list that contains following components.

<code>chisqStatistic</code>	The test statistic.
<code>dof</code>	The degrees of freedom of the reference chi-squared distribution.
<code>pValue</code>	p-value of the test.
<code>covMatrix</code>	The covariance matrix of $\text{vec}(L \beta_1 R)$.

Examples

```

data(fiberpaper)
X1 <- fiberpaper[, 7]
X2 <- fiberpaper[, 5:6]
Y <- fiberpaper[, 1:4]
m <- penv(X1, X2, Y, 1)
m

L <- diag(4)
R <- as.matrix(1)
A <- matrix(0, 4, 1)

test.res <- testcoef.penv(m, L, R, A)
test.res

```

testcoef.pois.env	<i>Hypothesis test of the coefficients of the envelope model</i>
-------------------	--

Description

This function tests the null hypothesis $L * \beta = A$ versus the alternative hypothesis $L * \beta \neq A$, where β is estimated under the envelope model in poisson regression.

Usage

```
testcoef.pois.env(m, L, A)
```

Arguments

m	A list containing estimators and other statistics inherited from pois.env.
L	The matrix multiplied to beta on the left. It is a d1 by p matrix, while d1 is less than or equal to p.
A	The matrix on the right hand side of the equation. It is a d1 by 1 matrix. Note that inputs L and A must be matrices, if not, use as.matrix to convert them.

Details

This function tests for hypothesis $H_0: L \beta = A$, versus $H_a: L \beta \neq A$. The β is estimated by the envelope model in predictor space. If $L = I_p$ and $A = 0$, then the test is equivalent to the standard F test on if $\beta = 0$. The test statistic used is $\text{vec}(L \beta - A) \hat{\Sigma}^{-1} \text{vec}(L \beta - A)^T$, where β is the envelope estimator and $\hat{\Sigma}$ is the estimated asymptotic covariance of $\text{vec}(L \beta - A)$. The reference distribution is chi-squared distribution with degrees of freedom d1.

Value

The output is a list that contains following components.

`chisqStatistic` The test statistic.
`dof` The degrees of freedom of the reference chi-squared distribution.
`pValue` p-value of the test.
`covMatrix` The covariance matrix of `vec(L beta)`.

Examples

```
data(horseshoecrab)
X1 <- as.numeric(horseshoecrab[ , 1] == 2)
X2 <- as.numeric(horseshoecrab[ , 1] == 3)
X3 <- as.numeric(horseshoecrab[ , 1] == 4)
X4 <- as.numeric(horseshoecrab[ , 2] == 2)
X5 <- as.numeric(horseshoecrab[ , 2] == 3)
X6 <- horseshoecrab[ , 3]
X7 <- horseshoecrab[ , 5]
X <- cbind(X1, X2, X3, X4, X5, X6, X7)
Y <- horseshoecrab[ , 4]

m <- pois.env(X, Y, 1)

L <- diag(7)
A <- matrix(0, 7, 1)

test.res <- testcoef.pois.env(m, L, A)
test.res
```

testcoef.senv	<i>Hypothesis test of the coefficients of the scaled response envelope model</i>
---------------	--

Description

This function tests the null hypothesis $L * \beta * R = A$ versus the alternative hypothesis $L * \beta * R \sim A$, where β is estimated under the scaled response envelope model.

Usage

```
testcoef.senv(m, L, R, A)
```

Arguments

`m` A list containing estimators and other statistics inherited from `scale.env`.
`L` The matrix multiplied to β on the left. It is a d_1 by r matrix, while d_1 is less than or equal to r .

R	The matrix multiplied to beta on the right. It is a p by d2 matrix, while d2 is less than or equal to p.
A	The matrix on the right hand side of the equation. It is a d1 by d2 matrix. Note that inputs L, R and A must be matrices, if not, use <code>as.matrix</code> to convert them.

Details

This function tests for hypothesis $H_0: L\beta R = A$, versus $H_a: L\beta R \neq A$. The beta is estimated by the scaled envelope model. If $L = I_r$, $R = I_p$ and $A = 0$, then the test is equivalent to the standard F test on if $\beta = 0$. The test statistic used is $\text{vec}(L\beta R - A) \hat{\Sigma}^{-1} \text{vec}(L\beta R - A)^T$, where beta is the envelope estimator and $\hat{\Sigma}$ is the estimated asymptotic covariance of $\text{vec}(L\beta R - A)$. The reference distribution is chi-squared distribution with degrees of freedom $d_1 * d_2$.

Value

The output is a list that contains following components.

<code>chisqStatistic</code>	The test statistic.
<code>dof</code>	The degrees of freedom of the reference chi-squared distribution.
<code>pValue</code>	p-value of the test.
<code>covMatrix</code>	The covariance matrix of $\text{vec}(L\beta R)$.

Examples

```
data(sales)
X <- sales[, 1:3]
Y <- sales[, 4:7]

m <- senv(X, Y, 2)

L <- diag(4)
R <- as.matrix(c(1, 0, 0))
A <- matrix(0, 4, 1)

test.res <- testcoef.senv(m, L, R, A)
test.res
```

testcoef.stenv

Hypothesis test of the coefficients of the simultaneous envelope model

Description

This function tests the null hypothesis $L * \beta * R = A$ versus the alternative hypothesis $L * \beta * R \neq A$, where beta is estimated under the simultaneous envelope model.

Usage

```
testcoef.stenv(m, L, R, A)
```

Arguments

<code>m</code>	A list containing estimators and other statistics inherited from <code>stenv</code> .
<code>L</code>	The matrix multiplied to beta on the left. It is a d_1 by p matrix, while d_1 is less than or equal to p .
<code>R</code>	The matrix multiplied to beta on the right. It is an r by d_2 matrix, while d_2 is less than or equal to r .
<code>A</code>	The matrix on the right hand side of the equation. It is a d_1 by d_2 matrix. Note that inputs <code>L</code> , <code>R</code> and <code>A</code> must be matrices, if not, use <code>as.matrix</code> to convert them.

Details

This function tests for hypothesis $H_0: L\beta R = A$, versus $H_a: L\beta R \neq A$. The beta is estimated by the simultaneous envelope model. If $L = I_p$, $R = I_r$ and $A = 0$, then the test is equivalent to the standard F test on if $\beta = 0$. The test statistic used is $\text{vec}(L\beta R - A) \hat{\Sigma}^{-1} \text{vec}(L\beta R - A)^T$, where beta is the envelope estimator and $\hat{\Sigma}$ is the estimated asymptotic covariance of $\text{vec}(L\beta R - A)$. The reference distribution is chi-squared distribution with degrees of freedom $d_1 * d_2$.

Value

The output is a list that contains following components.

<code>chisqStatistic</code>	The test statistic.
<code>dof</code>	The degrees of freedom of the reference chi-squared distribution.
<code>pValue</code>	p-value of the test.
<code>covMatrix</code>	The covariance matrix of $\text{vec}(L\beta R)$.

Examples

```
data(fiberpaper)
X <- fiberpaper[ , 5:7]
Y <- fiberpaper[ , 1:4]
m <- stenv(X, Y, 2, 3)

L <- diag(3)
R <- as.matrix(c(1, 0, 0, 0), nrow = 4)
A <- matrix(0, 3, 1)

test.res <- testcoef.stenv(m, L, R, A)
test.res
```

testcoef.sxenv	<i>Hypothesis test of the coefficients of the scaled predictor envelope model</i>
----------------	---

Description

This function tests the null hypothesis $L * \beta * R = A$ versus the alternative hypothesis $L * \beta * R \neq A$, where β is estimated under the scaled predictor envelope model.

Usage

```
testcoef.sxenv(m, L, R, A)
```

Arguments

m	A list containing estimators and other statistics inherited from scale.sxenv.
L	The matrix multiplied to beta on the left. It is a d_1 by p matrix, while d_1 is less than or equal to p .
R	The matrix multiplied to beta on the right. It is an r by d_2 matrix, while d_2 is less than or equal to r .
A	The matrix on the right hand side of the equation. It is a d_1 by d_2 matrix. Note that inputs L, R and A must be matrices, if not, use <code>as.matrix</code> to convert them.

Details

This function tests for hypothesis $H_0: L \beta R = A$, versus $H_a: L \beta R \neq A$. The β is estimated by the scaled envelope model in the predictor space. If $L = I_p$, $R = I_r$ and $A = 0$, then the test is equivalent to the standard F test on if $\beta = 0$. The test statistic used is $\text{vec}(L \beta R - A) \hat{\Sigma}^{-1} \text{vec}(L \beta R - A)^T$, where β is the envelope estimator and $\hat{\Sigma}$ is the estimated asymptotic covariance of $\text{vec}(L \beta R - A)$. The reference distribution is chi-squared distribution with degrees of freedom $d_1 * d_2$.

Value

The output is a list that contains following components.

chisqStatistic	The test statistic.
dof	The degrees of freedom of the reference chi-squared distribution.
pValue	p-value of the test.
covMatrix	The covariance matrix of $\text{vec}(L \beta R)$.

Examples

```

data(sales)
Y <- sales[, 1:3]
X <- sales[, 4:7]
R <- rep(1, 4)

u <- u.sxenv(X, Y, R)
u

m <- sxenv(X, Y, 2, R)

L <- diag(4)
R <- as.matrix(c(1, 0, 0))
A <- matrix(0, 4, 1)

test.res <- testcoef.sxenv(m, L, R, A)
test.res

```

testcoef.xenv

Hypothesis test of the coefficients of the predictor envelope model

Description

This function tests the null hypothesis $L * \beta * R = A$ versus the alternative hypothesis $L * \beta * R \neq A$, where β is estimated under the predictor envelope model.

Usage

```
testcoef.xenv(m, L, R, A)
```

Arguments

<code>m</code>	A list containing estimators and other statistics inherited from <code>xenv</code> .
<code>L</code>	The matrix multiplied to β on the left. It is a d_1 by p matrix, while d_1 is less than or equal to p .
<code>R</code>	The matrix multiplied to β on the right. It is an r by d_2 matrix, while d_2 is less than or equal to r .
<code>A</code>	The matrix on the right hand side of the equation. It is a d_1 by d_2 matrix. Note that inputs <code>L</code> , <code>R</code> and <code>A</code> must be matrices, if not, use <code>as.matrix</code> to convert them.

Details

This function tests for hypothesis $H_0: L \beta R = A$, versus $H_a: L \beta R \neq A$. The β is estimated by the envelope model in predictor space. If $L = I_p$, $R = I_r$ and $A = 0$, then the test is equivalent to the standard F test on if $\beta = 0$. The test statistic used is $\text{vec}(L \beta R - A) \hat{\Sigma}^{-1} \text{vec}(L \beta R - A)^T$, where β is the envelope estimator and $\hat{\Sigma}$ is the estimated asymptotic covariance of $\text{vec}(L \beta R - A)$. The reference distribution is chi-squared distribution with degrees of freedom $d_1 * d_2$.

Value

The output is a list that contains following components.

`chisqStatistic` The test statistic.
`dof` The degrees of freedom of the reference chi-squared distribution.
`pValue` p-value of the test.
`covMatrix` The covariance matrix of $\text{vec}(L \beta R)$.

Examples

```
data(wheatprotein)
X <- wheatprotein[, 1:6]
Y <- wheatprotein[, 7]
m <- xenv(X, Y, 2)
m

L <- diag(6)
R <- as.matrix(1)
A <- matrix(0, 6, 1)

test.res <- testcoef.xenv(m, L, R, A)
test.res
```

u.env

Select the dimension of env

Description

This function outputs dimensions selected by Akaike information criterion (AIC), Bayesian information criterion (BIC) and likelihood ratio testing with specified significance level for the response envelope model.

Usage

```
u.env(X, Y, alpha = 0.01)
```

Arguments

`X` Predictors. An n by p matrix, p is the number of predictors. The predictors can be univariate or multivariate, discrete or continuous.

`Y` Multivariate responses. An n by r matrix, r is the number of responses and n is number of observations. The responses must be continuous variables.

`alpha` Significance level for testing. The default is 0.01.

Value

u.aic	Dimension of the envelope subspace selected by AIC.
u.bic	Dimension of the envelope subspace selected by BIC.
u.lrt	Dimension of the envelope subspace selected by the likelihood ratio testing procedure.
loglik.seq	Log likelihood for dimension from 0 to r.
aic.seq	AIC value for dimension from 0 to r.
bic.seq	BIC value for dimension from 0 to r.

Examples

```
data(wheatprotein)
X <- wheatprotein[, 8]
Y <- wheatprotein[, 1:6]
u <- u.env(X, Y)
u
```

u.genv

Select the dimension of genv

Description

This function outputs dimensions selected by Akaike information criterion (AIC), Bayesian information criterion (BIC) and likelihood ratio testing with specified significance level for the group-wise envelope model.

Usage

```
u.genv(X, Y, Z, alpha = 0.01)
```

Arguments

X	Predictors. An n by p matrix, p is the number of predictors. The predictors can be univariate or multivariate, discrete or continuous.
Y	Multivariate responses. An n by r matrix, r is the number of responses and n is number of observations. The responses must be continuous variables.
Z	A group indicator vector of length n , where n denotes the number of observations.
alpha	Significance level for testing. The default is 0.01.

Value

u.aic	Dimension of the groupwise envelope subspace selected by AIC.
u.bic	Dimension of the groupwise envelope subspace selected by BIC.
u.lrt	Dimension of the groupwise envelope subspace selected by the likelihood ratio testing procedure.
loglik.seq	Log likelihood for dimension from 0 to r.
aic.seq	AIC value for dimension from 0 to r.
bic.seq	BIC value for dimension from 0 to r.

Examples

```
data(fiberpaper)
X <- fiberpaper[ , c(5, 7)]
Y <- fiberpaper[ , 1:3]
Z <- as.numeric(fiberpaper[ , 6] > mean(fiberpaper[ , 6]))

u <- u.genv(X, Y, Z)
u
```

u.henv

Select the dimension of henv

Description

This function outputs dimensions selected by Akaike information criterion (AIC), Bayesian information criterion (BIC) and likelihood ratio testing with specified significance level for the heteroscedastic envelope model.

Usage

```
u.henv(X, Y, alpha = 0.01)
```

Arguments

X	A group indicator vector of length n , where n denotes the number of observations.
Y	Multivariate responses. An n by r matrix, r is the number of responses and n is number of observations. The responses must be continuous variables.
alpha	Significance level for testing. The default is 0.01.

Value

u.aic	Dimension of the heteroscedastic envelope subspace selected by AIC.
u.bic	Dimension of the heteroscedastic envelope subspace selected by BIC.
u.lrt	Dimension of the heteroscedastic envelope subspace selected by the likelihood ratio testing procedure.
loglik.seq	Log likelihood for dimension from 0 to r.
aic.seq	AIC value for dimension from 0 to r.
bic.seq	BIC value for dimension from 0 to r.

Examples

```
data(waterstrider)
X <- waterstrider[, 1]
Y <- waterstrider[, 2:5]

## Not run: u <- u.henv(X, Y)
## Not run: u
```

u.logit.env *Select the dimension of logit.env*

Description

This function outputs dimensions selected by Akaike information criterion (AIC), Bayesian information criterion (BIC) and likelihood ratio testing with specified significance level for the envelope model in logistic regression.

Usage

```
u.logit.env(X, Y, alpha = 0.01)
```

Arguments

X	Predictors. An n by p matrix, p is the number of predictors and n is number of observations. The predictors must be continuous variables.
Y	Response. An n by 1 matrix. The univariate response must be binary.
alpha	Significance level for testing. The default is 0.01.

Value

u.aic	Dimension of the envelope subspace selected by AIC.
u.bic	Dimension of the envelope subspace selected by BIC.
u.lrt	Dimension of the envelope subspace selected by the likelihood ratio testing procedure.
loglik.seq	Log likelihood for dimension from 0 to p.
aic.seq	AIC value for dimension from 0 to p.
bic.seq	BIC value for dimension from 0 to p.

Examples

```

data(horseshoecrab)
X1 <- as.numeric(horseshoecrab[, 1] == 2)
X2 <- as.numeric(horseshoecrab[, 1] == 3)
X3 <- as.numeric(horseshoecrab[, 1] == 4)
X4 <- as.numeric(horseshoecrab[, 2] == 2)
X5 <- as.numeric(horseshoecrab[, 2] == 3)
X6 <- horseshoecrab[, 3]
X7 <- horseshoecrab[, 5]
X <- cbind(X1, X2, X3, X4, X5, X6, X7)
Y <- as.numeric(iffelse(horseshoecrab[, 4] > 0, 1, 0))

## Not run: u <- u.logit.env(X, Y)
## Not run: u

```

u.penv

Select the dimension of penv

Description

This function outputs dimensions selected by Akaike information criterion (AIC), Bayesian information criterion (BIC) and likelihood ratio testing with specified significance level for the partial envelope model.

Usage

```
u.penv(X1, X2, Y, alpha = 0.01)
```

Arguments

X1	Predictors of main interest. An n by p1 matrix, n is the number of observations, and p1 is the number of main predictors. The predictors can be univariate or multivariate, discrete or continuous.
X2	Covariates, or predictors not of main interest. An n by p2 matrix, p2 is the number of covariates.
Y	Multivariate responses. An n by r matrix, r is the number of responses and n is number of observations. The responses must be continuous variables.
alpha	Significance level for testing. The default is 0.01.

Value

u.aic	Dimension of the partial envelope subspace selected by AIC.
u.bic	Dimension of the partial envelope subspace selected by BIC.
u.lrt	Dimension of the partial envelope subspace selected by the likelihood ratio testing procedure.
loglik.seq	Log likelihood for dimension from 0 to r.
aic.seq	AIC value for dimension from 0 to r.
bic.seq	BIC value for dimension from 0 to r.

Examples

```

data(fiberpaper)
X1 <- fiberpaper[, 7]
X2 <- fiberpaper[, 5:6]
Y <- fiberpaper[, 1:4]

u <- u.penv(X1, X2, Y)
u

```

u.pois.env

Select the dimension of pois.env

Description

This function outputs dimensions selected by Akaike information criterion (AIC), Bayesian information criterion (BIC) and likelihood ratio testing with specified significance level for the envelope model in poisson regression.

Usage

```
u.pois.env(X, Y, alpha = 0.01)
```

Arguments

X	Predictors. An n by p matrix, p is the number of predictors and n is number of observations. The predictors must be continuous variables.
Y	Response. An n by 1 matrix. The univariate response must be counts.
alpha	Significance level for testing. The default is 0.01.

Value

u.aic	Dimension of the envelope subspace selected by AIC.
u.bic	Dimension of the envelope subspace selected by BIC.
u.lrt	Dimension of the envelope subspace selected by the likelihood ratio testing procedure.
loglik.seq	Log likelihood for dimension from 0 to p.
aic.seq	AIC value for dimension from 0 to p.
bic.seq	BIC value for dimension from 0 to p.

Examples

```

data(horseshoecrab)
X1 <- as.numeric(horseshoecrab[, 1] == 2)
X2 <- as.numeric(horseshoecrab[, 1] == 3)
X3 <- as.numeric(horseshoecrab[, 1] == 4)
X4 <- as.numeric(horseshoecrab[, 2] == 2)
X5 <- as.numeric(horseshoecrab[, 2] == 3)
X6 <- horseshoecrab[, 3]
X7 <- horseshoecrab[, 5]
X <- cbind(X1, X2, X3, X4, X5, X6, X7)
Y <- horseshoecrab[, 4]

## Not run: u <- u.pois.env(X, Y)
## Not run: u

```

u.pred2.env

Select the dimension of the constructed partial envelope for prediction based on envelope model

Description

This function outputs dimensions selected by Akaike information criterion (AIC), Bayesian information criterion (BIC) and likelihood ratio testing with specified significance level for the constructed partial envelope model.

Usage

```
u.pred2.env(X, Y, Xnew, alpha = 0.01)
```

Arguments

X	Predictors. An n by p matrix, p is the number of predictors. The predictors can be univariate or multivariate, discrete or continuous.
Y	Multivariate responses. An n by r matrix, r is the number of responses and n is number of observations. The responses must be continuous variables.
Xnew	The value of X with which to estimate or predict Y. A p dimensional vector.
alpha	Significance level for testing. The default is 0.01.

Value

u.aic	Dimension of the constructed partial envelope subspace selected by AIC.
u.bic	Dimension of the constructed partial envelope subspace selected by BIC.
u.lrt	Dimension of the constructed partial envelope subspace selected by the likelihood ratio testing procedure.
loglik.seq	Log likelihood for dimension from 0 to r.
aic.seq	AIC value for dimension from 0 to r.
bic.seq	BIC value for dimension from 0 to r.

Examples

```

data(fiberpaper)
X <- fiberpaper[, 5:7]
Y <- fiberpaper[, 1:4]

u <- u.pred2.env(X, Y, X[10, ])
u

```

u.senv

Select the dimension of senv

Description

This function outputs dimensions selected by Akaike information criterion (AIC), Bayesian information criterion (BIC) for the scaled response envelope model.

Usage

```
u.senv(X, Y)
```

Arguments

X Predictors. An n by p matrix, p is the number of predictors. The predictors can be univariate or multivariate, discrete or continuous.

Y Multivariate responses. An n by r matrix, r is the number of responses and n is number of observations. The responses must be continuous variables.

Value

u.aic Dimension of the scaled envelope subspace selected by AIC.

u.bic Dimension of the scaled envelope subspace selected by BIC.

aic.seq AIC value for dimension from 0 to r .

bic.seq BIC value for dimension from 0 to r .

Examples

```

data(sales)
X <- sales[, 1:3]
Y <- sales[, 4:7]

u <- u.senv(X, Y)
u

```

`u.stenv`*Select the dimension of stenv*

Description

This function outputs dimensions selected by Akaike information criterion (AIC), Bayesian information criterion (BIC) and likelihood ratio testing with specified significance level for the simultaneous envelope model.

Usage

```
u.stenv(X, Y, alpha = 0.01)
```

Arguments

<code>X</code>	Predictors. An n by p matrix, p is the number of predictors. The predictors can be univariate or multivariate, discrete or continuous.
<code>Y</code>	Multivariate responses. An n by r matrix, r is the number of responses and n is number of observations. The responses must be continuous variables.
<code>alpha</code>	Significance level for testing. The default is 0.01.

Value

<code>d</code>	Rank of beta selected by the Bura-Cook estimator.
<code>u.aic</code>	Dimension of the simultaneous envelope subspace selected by AIC.
<code>u.bic</code>	Dimension of the simultaneous envelope subspace selected by BIC.
<code>u.lrt</code>	Dimension of the simultaneous envelope subspace selected by the likelihood ratio testing procedure.
<code>loglik.mat</code>	Log likelihood for dimension from (1, 1) to (r, p).
<code>aic.mat</code>	AIC value for dimension from (1, 1) to (r, p).
<code>bic.mat</code>	BIC value for dimension from (1, 1) to (r, p).

Examples

```
data(fiberpaper)
X <- fiberpaper[, 5:7]
Y <- fiberpaper[, 1:4]

u <- u.stenv(X, Y)
u
```

`u.sxenv`*Select the dimension of sxenv*

Description

This function outputs dimensions selected by Akaike information criterion (AIC), Bayesian information criterion (BIC) for the scaled predictor envelope model.

Usage

```
u.sxenv(X, Y, R)
```

Arguments

X	Predictors. An n by p matrix, p is the number of predictors. The predictors can be univariate or multivariate, discrete or continuous.
Y	Multivariate responses. An n by r matrix, r is the number of responses and n is number of observations. The responses must be continuous variables.
R	The number of replications of the scales. A vector, the sum of all elements of R must be p.

Value

u.aic	Dimension of the scaled envelope subspace in the predictor space selected by AIC.
u.bic	Dimension of the scaled envelope subspace in the predictor space selected by BIC.
aic.seq	AIC value for dimension from 0 to p.
bic.seq	BIC value for dimension from 0 to p.

Examples

```
data(sales)
Y <- sales[, 1:3]
X <- sales[, 4:7]
R <- rep(1, 4)

u <- u.sxenv(X, Y, R)
u
```

`u.xenv`*Select the dimension of xenv*

Description

This function outputs dimensions selected by Akaike information criterion (AIC), Bayesian information criterion (BIC) and likelihood ratio testing with specified significance level for the predictor envelope model.

Usage

```
u.xenv(X, Y, alpha = 0.01)
```

Arguments

<code>X</code>	Predictors. An n by p matrix, p is the number of predictors and n is number of observations. The predictors must be continuous variables.
<code>Y</code>	Responses. An n by r matrix, r is the number of responses. The response can be univariate or multivariate and must be continuous variable.
<code>alpha</code>	Significance level for testing. The default is 0.01.

Value

<code>u.aic</code>	Dimension of the envelope subspace selected by AIC.
<code>u.bic</code>	Dimension of the envelope subspace selected by BIC.
<code>u.lrt</code>	Dimension of the envelope subspace selected by the likelihood ratio testing procedure.
<code>loglik.seq</code>	Log likelihood for dimension from 0 to p .
<code>aic.seq</code>	AIC value for dimension from 0 to p .
<code>bic.seq</code>	BIC value for dimension from 0 to p .

Examples

```
data(wheatprotein)
X <- wheatprotein[, 1:6]
Y <- wheatprotein[, 7]

u <- u.xenv(X, Y)
u
```

waterstrider	<i>Water strider data</i>
--------------	---------------------------

Description

Measures of characteristics of the water striders

Usage

```
data("waterstrider")
```

Format

A data frame with 90 observations on the following 9 variables.

- V1 Index of water strider species.
- V2 Logarithm of length of the first antennal segment.
- V3 Logarithm of length of the second antennal segment.
- V4 Logarithm of length of the third antennal segment.
- V5 Logarithm of length of the fourth antennal segment.
- V6 Logarithm of length of fomora of middle leg.
- V7 Logarithm of length of tibiae of middle leg.
- V8 Logarithm of length of fomora of hind leg.
- V9 Logarithm of length of tibiae of hind leg.

Details

This data set contains 8 measures of water striders and an indicator of the species of water striders.

References

Klingenberg, C. R. and Spence, J. R. (1993). Heterochrony and Allometry Lessons from the Water Strider Genus *Limnopus*. *Evolution* 47, 1834-1853

weighted.env	<i>Weighted response envelope estimator</i>
--------------	---

Description

Compute the weighted response envelope estimator with weights computed from BIC.

Usage

```
weighted.env(X, Y, bstrpNum = 0, min.u = 1,
max.u = ncol(as.matrix(Y)), boot.resi = "full")
```

Arguments

X	Predictors. An n by p matrix, p is the number of predictors. The predictors can be univariate or multivariate, discrete or continuous.
Y	Multivariate responses. An n by r matrix, r is the number of responses and n is number of observations. The responses must be continuous variables.
bstrpNum	Number of bootstrap samples. A positive integer.
min.u	Lower bound of the range of u to compute bootstrap error. A positive integer between 1 and p. This argument is relevant only when bstrpNum>0.
max.u	Upper bound of the range of u to compute bootstrap error. A positive integer between 1 and p. This argument is relevant only when bstrpNum>0.
boot.resi	A string that can be "full" or "weighted" indicating the model from which the residuals are calculated. If the input is "full", then the residuals are obtained using the standard estimators; and if the input is "weighted", then the residuals are obtained using the weighted envelope estimators. This argument is for computing residuals in residual bootstrap, and it is relevant only when bstrpNum>0.

Details

This function computes the weighted envelope estimator in a standard multivariate linear regression. And the weighted envelope estimator takes the form

$$\hat{\beta}_w = \sum_{j=1}^r w_j \hat{\beta}_j,$$

where $\hat{\beta}_j$ is the envelope estimator of β with $u = j$ and w_j 's are the weights computed from BIC values

$$w_j = \frac{\exp(-b_j)}{\sum_{k=1}^r \exp(-b_k)},$$

where b_j is the BIC criterion evaluated at the envelope estimator $\hat{\beta}_j$. For details, see Eck and Cook (2017).

The variation of the weighted envelope estimator is estimated by residual bootstrap. The user can specify the range for bootstrap $u = (\text{min.u}, \text{max.u})$, if the weights outside of the range are small.

Value

The output is a list that contains the following components:

beta	The weighted envelope estimator of the regression coefficients.
mu	The weighted estimated intercept.
Sigma	The weighted envelope estimator of the error covariance matrix.
w	Weights computed based on BIC.
loglik	The log likelihood function computed with weighted envelope estimator.
n	The number of observations in the data.
bootse	The standard error for elements in beta computed by residual bootstrap. This output is available only when bstrpNum>0.
ratios	The bootstrap standard error ratio of the standard multivariate linear regression estimator over the weighted envelope estimator for each element in beta. This output is available only when bstrpNum>0.
bic_select	A table that lists how many times BIC selected each candidate dimension. If BIC never selects a dimension, this dimension does not appear on the table. This output is available only when bstrpNum>0.

References

Eck, D. J. and Cook, R. D. (2017). Weighted Envelope Estimation to Handle Variability in Model Selection. *Biometrika*. To appear.

Examples

```
data(wheatprotein)
X <- wheatprotein[, 8]
Y <- wheatprotein[, 1:6]
m <- weighted.env(X, Y)
m$w
m$beta

## Not run: m2 <- weighted.env(X, Y, bstrpNum = 100, min.u = 1, max.u = 6, boot.resi = "full")
## Not run: m2$bic_select
## Not run: m2$bootse
```

weighted.penv

Weighted partial envelope estimator

Description

Compute the weighted partial envelope estimator with weights computed from BIC.

Usage

```
weighted.penv(X1, X2, Y, bstrpNum = 0, min.u = 1,
max.u = ncol(as.matrix(Y)), boot.resi = "full")
```

Arguments

X1	Predictors of main interest. An n by p1 matrix, n is the number of observations, and p1 is the number of main predictors. The predictors can be univariate or multivariate, discrete or continuous.
X2	Covariates, or predictors not of main interest. An n by p2 matrix, p2 is the number of covariates.
Y	Multivariate responses. An n by r matrix, r is the number of responses and n is number of observations. The responses must be continuous variables.
bstrpNum	Number of bootstrap samples. A positive integer.
min.u	Lower bound of the range of u to compute bootstrap error. A positive integer between 1 and p. This argument is relevant only when bstrpNum>0.
max.u	Upper bound of the range of u to compute bootstrap error. A positive integer between 1 and p. This argument is relevant only when bstrpNum>0.
boot.resi	A string that can be "full" or "weighted" indicating the model from which the residuals are calculated. If the input is "full", then the residuals are obtained using the standard estimators; and if the input is "weighted", then the residuals are obtained using the weighted envelope estimators. This argument is for computing residuals in residual bootstrap, and it is relevant only when bstrpNum>0.

Details

This function computes the weighted partial envelope estimator in a standard multivariate linear regression. And the weighted partial envelope estimator takes the form

$$\hat{\beta}_w = \sum_{j=1}^r w_j \hat{\beta}_j,$$

where $\hat{\beta}_j$ is the partial envelope estimator of β with $u = j$ and w_j 's are the weights computed from BIC values

$$w_j = \frac{\exp(-b_j)}{\sum_{k=1}^r \exp(-b_k)},$$

where b_j is the BIC criterion evaluated at the partial envelope estimator $\hat{\beta}_j$. For details, see Eck and Cook (2017).

The variation of the weighted partial envelope estimator is estimated by residual bootstrap. The user can specify the range for bootstrap $u = (\text{min.u}, \text{max.u})$, if the weights outside of the range are small.

Value

The output is a list that contains the following components:

beta	The weighted partial envelope estimator of the regression coefficients.
mu	The weighted estimated intercept.
Sigma	The weighted partial envelope estimator of the error covariance matrix.
w	Weights computed based on BIC.

loglik	The log likelihood function computed with weighted partial envelope estimator.
n	The number of observations in the data.
bootse	The standard error for elements in beta1 computed by residual bootstrap. This output is available only when bstrpNum>0.
ratios	The bootstrap standard error ratio of the standard multivariate linear regression estimator over the weighted partial envelope estimator for each element in beta1. This output is available only when bstrpNum>0.
bic_select	A table that lists how many times BIC selected each candidate dimension. If BIC never selects a dimension, this dimension does not appear on the table. This output is available only when bstrpNum>0.

References

Eck, D. J. and Cook, R. D. (2017). Weighted Envelope Estimation to Handle Variability in Model Selection. *Biometrika*. To appear.

Examples

```
data(fiberpaper)
X1 <- fiberpaper[, 7]
X2 <- fiberpaper[, 5:6]
Y <- fiberpaper[, 1:4]
m <- weighted.penv(X1, X2, Y)
m$w
m$beta1

m2 <- penv(X1, X2, Y, 2)
m2$beta1

## Not run: m3 <- weighted.penv(X1, X2, Y, bstrpNum = 100, boot.resi = "full")
## Not run: m3$w
## Not run: m3$bic_select
## Not run: m3$bootse

## Not run: boot.penv(X1, X2, Y, 2, 100)
```

weighted.pred.env *Estimation or prediction using weighted partial envelope*

Description

Perform estimation or prediction through weighted partial envelope model.

Usage

```
weighted.pred.env(X, Y, Xnew)
```

Arguments

X	Predictors. An n by p matrix, p is the number of predictors. The predictors can be univariate or multivariate, discrete or continuous.
Y	Multivariate responses. An n by r matrix, r is the number of responses and n is number of observations. The responses must be continuous variables.
Xnew	The value of X with which to estimate or predict Y. A p dimensional vector.

Details

This function evaluates the envelope model at new value Xnew. It can perform estimation: find the fitted value when $X = X_{\text{new}}$, or prediction: predict Y when $X = X_{\text{new}}$. But it does not provide the estimation or prediction error. This function performs prediction using the same procedure as in `pred2.env`, except that the partial envelope estimator with dimension u is replaced by a weighted partial envelope estimator. The weights are decided based on BIC values.

Value

value	The fitted value or the predicted value evaluated at Xnew.
-------	--

Examples

```
data(fiberpaper)
X <- fiberpaper[, 5:7]
Y <- fiberpaper[, 1:4]

## Not run: pred.res <- weighted.pred.env(X, Y, X[10, ])
```

 weighted.xenv

Weighted predictor envelope estimator

Description

Compute the weighted predictor envelope estimator with weights computed from BIC.

Usage

```
weighted.xenv(X, Y, bstrpNum = 0, min.u = 1,
max.u = ncol(as.matrix(X)), boot.resi = "full")
```

Arguments

X	Predictors. An n by p matrix, p is the number of predictors and n is number of observations. The predictors must be continuous variables.
Y	Responses. An n by r matrix, r is the number of responses. The response can be univariate or multivariate and must be continuous variable.

bstrpNum	Number of bootstrap samples. A positive integer.
min.u	Lower bound of the range of u to compute bootstrap error. A positive integer between 1 and p. This argument is relevant only when bstrpNum>0.
max.u	Upper bound of the range of u to compute bootstrap error. A positive integer between 1 and p. This argument is relevant only when bstrpNum>0.
boot.resi	A string that can be "full" or "weighted" indicating the model from which the residuals are calculated. If the input is "full", then the residuals are obtained using the standard estimators; and if the input is "weighted", then the residuals are obtained using the weighted predictor envelope estimators. This argument is for computing residuals in residual bootstrap, and it is relevant only when bstrpNum>0.

Details

This function computes the weighted predictor envelope estimator in a standard multivariate linear regression. And the weighted predictor envelope estimator takes the form

$$\hat{\beta}_w = \sum_{j=1}^p w_j \hat{\beta}_j,$$

where $\hat{\beta}_j$ is the predictor envelope estimator of β with $u = j$ and w_j 's are the weights computed from BIC values

$$w_j = \frac{\exp(-b_j)}{\sum_{k=1}^p \exp(-b_k)},$$

where b_j is the BIC criterion evaluated at the predictor envelope estimator $\hat{\beta}_j$. For details, see Eck and Cook (2017).

The variation of the weighted predictor envelope estimator is estimated by residual bootstrap. The user can specify the range for bootstrap $u = (\text{min.u}, \text{max.u})$, if the weights outside of the range are small.

Value

The output is a list that contains the following components:

beta	The weighted predictor envelope estimator of the regression coefficients.
mu	The weighted estimated intercept.
SigmaX	The weighted predictor envelope estimator of the covariance matrix of X.
SigmaYcX	The weighted predictor envelope estimator of the error covariance matrix.
w	Weights computed based on BIC.
loglik	The log likelihood function computed with weighted predictor envelope estimator.
n	The number of observations in the data.
bootse	The standard error for elements in beta computed by residual bootstrap. This output is available only when bstrpNum>0.

ratios	The bootstrap standard error ratio of the standard multivariate linear regression estimator over the weighted predictor envelope estimator for each element in beta. This output is available only when bstrpNum>0.
bic_select	A table that lists how many times BIC selected each candidate dimension. If BIC never selects a dimension, this dimension does not appear on the table. This output is available only when bstrpNum>0.

References

Eck, D. J. and Cook, R. D. (2017). Weighted Envelope Estimation to Handle Variability in Model Selection. *Biometrika*. To appear.

Examples

```
data(wheatprotein)
X <- wheatprotein[, 1:6]
Y <- wheatprotein[, 7]
m <- weighted.xenv(X, Y)
m$w
m$beta

## Not run: m2 <- weighted.xenv(X, Y, bstrpNum = 100, min.u = 2, max.u = 4, boot.resi = "full")
## Not run: m2$w
## Not run: m2$bootse
```

wheatprotein

Wheat Protein Data

Description

The protein content of ground wheat samples.

Usage

```
data(wheatprotein)
```

Format

A data frame with 50 observations on the following 8 variables.

V1 Measurements of the reflectance of NIR radiation by the wheat samples at 1680nm. The measurements were made on the $\log(1/\text{reflectance})$ scale.

V2 Measurements of the reflectance of NIR radiation by the wheat samples at 1806nm.

V3 Measurements of the reflectance of NIR radiation by the wheat samples at 1932nm.

V4 Measurements of the reflectance of NIR radiation by the wheat samples at 2058nm.

V5 Measurements of the reflectance of NIR radiation by the wheat samples at 2184nm.

V6 Measurements of the reflectance of NIR radiation by the wheat samples at 2310nm.

- V7 The protein content of each sample (in percent).
- V8 Binary indicator, 0 for high protein content and 1 for low protein content. The cut off point is if the protein content is smaller than 9.75.

Details

The data are the result of an experiment to calibrate a near infrared reflectance (NIR) instrument for measuring the protein content of ground wheat samples. The protein content of each sample (in percent) was measured by the standard Kjeldahl method. In Fearn (1983), the problem is to find a linear combination of the measurements that predicts protein content. The estimated coefficients can then be entered into the instrument allowing the protein content of future samples to be read directly. The first 24 cases were used for calibration and the last 26 samples were used for prediction.

References

Fearn, T. (1983). A misuse of ridge regression in the calibration of a near infrared reflectance instrument.

xenv

Fit the predictor envelope model

Description

Fit the predictor envelope model in linear regression with dimension u .

Usage

```
xenv(X, Y, u, asy = TRUE, init = NULL)
```

Arguments

X	Predictors. An n by p matrix, p is the number of predictors and n is number of observations. The predictors must be continuous variables.
Y	Responses. An n by r matrix, r is the number of responses. The response can be univariate or multivariate and must be continuous variable.
u	Dimension of the envelope. An integer between 0 and p .
<code>asy</code>	Flag for computing the asymptotic variance of the envelope estimator. The default is TRUE. When p and r are large, computing the asymptotic variance can take much time and memory. If only the envelope estimators are needed, the flag can be set to <code>asy = FALSE</code> .
<code>init</code>	The user-specified value of Gamma for the envelope subspace in the predictor space. An p by u matrix. The default is the one generated by function <code>envMU</code> .

Details

This function fits the envelope model in the predictor space,

$$Y = \mu + \eta' \Omega^{-1} \Gamma' X + \varepsilon, \Sigma_X = \Gamma \Omega \Gamma' + \Gamma_0 \Omega_0 \Gamma_0'$$

using the maximum likelihood estimation. When the dimension of the envelope is between 1 and $p-1$, the starting value and blockwise coordinate descent algorithm in Cook et al. (2016) is implemented. When the dimension is p , then the envelope model degenerates to the standard multivariate linear regression. When the dimension is 0, it means that X and Y are uncorrelated, and the fitting is different.

Value

The output is a list that contains the following components:

beta	The envelope estimator of the regression coefficients.
SigmaX	The envelope estimator of the covariance matrix of X .
Gamma	An orthonormal basis of the envelope subspace.
Gamma0	An orthonormal basis of the complement of the envelope subspace.
eta	The estimated eta. According to the envelope parameterization, $\text{beta} = \text{Gamma} * \text{Omega}^{-1} * \text{eta}$.
Omega	The coordinates of SigmaX with respect to Gamma.
Omega0	The coordinates of SigmaX with respect to Gamma0.
mu	The estimated intercept.
SigmaYcX	The estimated conditional covariance matrix of Y given X .
loglik	The maximized log likelihood function.
covMatrix	The asymptotic covariance of $\text{vec}(\text{beta})$. The covariance matrix returned are asymptotic. For the actual standard errors, multiply by $1 / n$.
asySE	The asymptotic standard error for elements in beta under the envelope model. The standard errors returned are asymptotic, for actual standard errors, multiply by $1 / \text{sqrt}(n)$.
ratio	The asymptotic standard error ratio of the standard multivariate linear regression estimator over the envelope estimator, for each element in beta.
n	The number of observations in the data.

References

- Cook, R. D., Helland, I. S. and Su, Z. (2013). Envelopes and Partial Least Squares Regression. *Journal of the Royal Statistical Society: Series B* 75, 851 - 877.
- Cook, R. D., Forzani, L. and Su, Z. (2016) A Note on Fast Envelope Estimation. *Journal of Multivariate Analysis*. 150, 42-54.

See Also

[simpls.fit](#) for partial least squares (PLS).

Examples

```
## Fit the envelope in the predictor space
data(wheatprotein)
X <- wheatprotein[, 1:6]
Y <- wheatprotein[, 7]
u <- u.xenv(X, Y)
u

m <- xenv(X, Y, 4)
m
m$beta

## Fit the partial least squares
## Not run: m1 <- pls::simpls.fit(X, Y, 4)
## Not run: m1$coefficients
```

Index

* datasets

- Berkeley, 4
- fiberpaper, 29
- horseshoecrab, 34
- sales, 51
- waterstrider, 81
- wheatprotein, 88

Berkeley, 4

boot.env, 6

boot.genv, 7

boot.henv, 8

boot.logit.env, 9

boot.penv, 10

boot.pois.env, 11

boot.senv, 12

boot.stenv, 13

boot.sxenv, 14

boot.xenv, 15

cv.env, 16

cv.genv, 17

cv.henv, 18

cv.logit.env, 19

cv.penv, 20

cv.pois.env, 21

cv.senv, 22

cv.stenv, 23

cv.sxenv, 24

cv.xenv, 25

d.stenv, 26

env, 27

fiberpaper, 29

genv, 30

henv, 32

horseshoecrab, 34

logit.env, 35

penv, 36

pois.env, 38

pred.env, 40

pred.genv, 41

pred.henv, 42

pred.logit.env, 43

pred.penv, 44

pred.pois.env, 45

pred.senv, 46

pred.stenv, 47

pred.sxenv, 48

pred.xenv, 49

pred2.env, 50

Renvlp-package, 3

Revnlp-package (Renvlp-package), 3

sales, 51

senv, 52

simpls.fit, 90

stenv, 54

sxenv, 56

testcoef.env, 58

testcoef.genv, 59

testcoef.henv, 60

testcoef.logit.env, 61

testcoef.penv, 63

testcoef.pois.env, 64

testcoef.senv, 65

testcoef.stenv, 66

testcoef.sxenv, 68

testcoef.xenv, 69

u.env, 70

u.genv, 71

u.henv, 72

u.logit.env, 73

u.penv, 74

u.pois.env, [75](#)
u.pred2.env, [76](#)
u.senv, [77](#)
u.stenv, [78](#)
u.sxenv, [79](#)
u.xenv, [80](#)

waterstrider, [81](#)
weighted.env, [82](#)
weighted.penv, [83](#)
weighted.pred.env, [85](#)
weighted.xenv, [86](#)
wheatprotein, [88](#)

xenv, [89](#)