

Package ‘SKNN’

January 19, 2022

Type Package

Title A Super K-Nearest Neighbor (SKNN) Classification Algorithm

Version 3.0

Date 2022-01-18

Maintainer Yi Ya <Yi.YA_yaya@hotmail.com>

Depends methods, stats

Description It's a Super K-Nearest Neighbor classification method with using kernel density to describe weight of the distance between a training observation and the testing sample.

Collate SKNN.R Dist.R PCAY.R AllClasses.R KNN.R

License GPL-2

NeedsCompilation no

Author Yi Ya [aut, cre],
Yarong Yang [aut],
Nader Ebrahimi [aut],
Yoram Rubin [aut],
Jacob Zhang [aut]

Repository CRAN

Date/Publication 2022-01-19 11:12:42 UTC

R topics documented:

SKNN-package	2
Dist	3
KNN	4
PCAY	5
PCAYd	6
SKNN	7
Index	9

SKNN-package

*Super K-Nearest Neighbor (SKNN) Classification***Description**

It's a Super K-Nearest Neighbor classification method with using kernel density to describe the weight of the distance between a training observation and the sample to be classified.

Details

Package: SKNN
 Type: Package
 Version: 3.0
 Date: 2022-01-18
 License: GPL-2

Author(s)

Yi Ya, Nader Ebrahimi, Yoram Rubin, and Jacob Zhang

References

Nader Ebrahimi, Yi Ya, and Yoram Rubin. SKNN: A Super K-Nearest Neighbor Classification Algorithm. ongoing

Yarong Yang, Matt Over, and Yoram Rubin.(2012) Strategic Placement of Localization Devices (such as Pilot Points and Anchors) in Inverse Modeling Schemes. Water Resources Research, 48, W08519, doi:10.1029/2012WR011864.

B.B.W. Silverman. Density Estimation for Statistics and Data Analysis. London: Chapman and Hall, 1986.

Examples

```
Sepal.Length<-c(4.8, 5.1, 4.6, 5.3, 5.0, 5.7, 5.7, 6.2, 5.1, 5.7, 6.7, 6.3, 6.5, 6.2, 5.9)
Sepal.Width<-c(3.0, 3.8, 3.2, 3.7, 3.3, 3.0, 2.9, 2.9, 2.5, 2.8, 3.0, 2.5, 3.0, 3.4, 3.0)
Petal.Length<-c(1.4, 1.6, 1.4, 1.5, 1.4, 4.2, 4.2, 4.3, 3.0, 4.1, 5.2, 5.0, 5.2, 5.4, 5.1)
Petal.Width<-c(0.3, 0.2, 0.2, 0.2, 0.2, 1.2, 1.3, 1.3, 1.1, 1.3, 2.3, 1.9, 2.0, 2.3, 1.8)
Species<-as.factor(c(rep("red",5),rep("blue",5),rep("green",5)))
iris<-cbind(Sepal.Length,Sepal.Width,Petal.Length,Petal.Width)
Res<-length(nrow(iris))
k<-10
for(i in 1:nrow(iris))
  Res[i]<-SKNN(data=iris,Class=as.vector(Species),k=k,test=iris[i,])
accuracy<-length(which(Res==Species))/length(Species)
```

```
plot(x=1:15,y=rep(1,15),col=as.vector(Species),lwd=4,ylim=c(0,3),xlab="",ylab="",
yaxt = "n",xaxt="n")
par(new=TRUE)
plot(x=1:15,y=rep(2,15),col=Res,lwd=4,ylim=c(0,3),xlab="",ylab="",yaxt = "n",xaxt="n")
ind<-which(Res!=Species)
if(length(ind)>0) {
  for(j in 1:length(ind))
    lines(x=c(ind[j],ind[j]),y=c(1+0.05,2-0.05))
}
text(5,0.3,paste("SKNN Misclassified:",length(ind)))
axis(2,at=2,labels="SKNN",las=1)
text(10,2.5,paste("k: ",k))
```

Dist

Finding the distance between two observations.

Description

It's a function of finding the distance between two observations.

Usage

```
Dist(x,y)
```

Arguments

x Numeric. A vector denoting an observation.

y Numeric. A vector denoting an observation.

Value

A list.

Author(s)

Yi Ya

 KNN

K-Nearest Neighbor Classification

Description

It's implementation of the K-Nearest Neighbor classification method for data of any number of dimentionions.

Usage

```
KNN(data, Class, k, test)
```

Arguments

data	Numeric. The training data set, matrix.
Class	Character. Class of the training observations, vector.
k	Integer. The number of K to be used.
test	Numeric. The sample to be classified.

Value

A character.

Author(s)

Yi Ya

References

A.T. Covert and P. Hart. Nearest Neighbor Pattern Classification. IEEE Transactions on Information Theory, 13(1): 21-27, 1967.

Examples

```
Sepal.Length<-c(4.8, 5.1, 4.6, 5.3, 5.0, 5.7, 5.7, 6.2, 5.1, 5.7, 6.7, 6.3, 6.5, 6.2, 5.9)
Sepal.Width<-c(3.0, 3.8, 3.2, 3.7, 3.3, 3.0, 2.9, 2.9, 2.5, 2.8, 3.0, 2.5, 3.0, 3.4, 3.0)
Petal.Length<-c(1.4, 1.6, 1.4, 1.5, 1.4, 4.2, 4.2, 4.3, 3.0, 4.1, 5.2, 5.0, 5.2, 5.4, 5.1)
Petal.Width<-c(0.3, 0.2, 0.2, 0.2, 0.2, 1.2, 1.3, 1.3, 1.1, 1.3, 2.3, 1.9, 2.0, 2.3, 1.8)
Species<-as.factor(c(rep("red",5),rep("blue",5),rep("green",5)))
iris<-cbind(Sepal.Length,Sepal.Width,Petal.Length,Petal.Width)
Res<-length(nrow(iris))
k<-10
for(i in 1:nrow(iris))
  Res[i]<-KNN(data=iris,Class=as.vector(Species),k=k,test=iris[i,])
accuracy<-length(which(Res==Species))/length(Species)
plot(x=1:15,y=rep(1,15),col=as.vector(Species),lwd=4,ylim=c(0,3),xlab="",ylab="",
yaxt = "n",xaxt="n")
```

```
par(new=TRUE)
plot(x=1:15,y=rep(2,15),col=Res,lwd=4,ylim=c(0,3),xlab="",ylab="",yaxt = "n",xaxt="n")
ind<-which(Res!=Species)
if(length(ind)>0) {
  for(j in 1:length(ind))
    lines(x=c(ind[j],ind[j]),y=c(1+0.05,2-0.05))
}
text(5,0.3,paste("KNN Misclassified:",length(ind)))
axis(2,at=2,labels="KNN",las=1)
text(10,2.5,paste("k: ",k))
```

PCAy

Revised PCA analysis

Description

It's a revised PCA analysis.

Usage

```
PCAy(data)
```

Arguments

`data` Numeric. Data matrix for revised PCA analysis.

Value

An object of class "PCAy".

Author(s)

Yi Ya, Yarong Yang, and Yoram Rubin

References

Yarong Yang, Matt Over, and Yoram Rubin.(2012) Strategic Placement of Localization Devices (such as Pilot Points and Anchors) in Inverse Modeling Schemes. *Water Resources Research*, 48, W08519, doi:10.1029/2012WR011864.

Nader Ebrahimi, Yi Ya, and Yoram Rubin. SKNN: A Super K-Nearest Neighbor Classification Algorithm. ongoing

Examples

```

Sepal.Length<-c(4.8, 5.1, 4.6, 5.3, 5.0, 5.7, 5.7, 6.2, 5.1, 5.7, 6.7, 6.3,
6.5, 6.2, 5.9)
Sepal.Width<-c(3.0, 3.8, 3.2, 3.7, 3.3, 3.0, 2.9, 2.9, 2.5, 2.8, 3.0, 2.5,
3.0, 3.4, 3.0)
Petal.Length<-c(1.4, 1.6, 1.4, 1.5, 1.4, 4.2, 4.2, 4.3, 3.0, 4.1, 5.2, 5.0,
5.2, 5.4, 5.1)
Petal.Width<-c(0.3, 0.2, 0.2, 0.2, 0.2, 1.2, 1.3, 1.3, 1.1, 1.3, 2.3, 1.9,
2.0, 2.3, 1.8)
dat<-cbind(Sepal.Length,Sepal.Width,Petal.Length,Petal.Width)
Res<-PCAy(dat)

```

PCAyD

Class to contain the results from revised PCA analysis.

Description

The function PCAY returns object of class PCAYD.

Objects from the Class

```
new("PCAyD",Var=new("numeric"),PC=new("matrix"),Scores=new("matrix"),IScores=new("numeric"))
```

Slots

Var: An numeric vector giving the variance of each PC.

PC: A numeric matrix about the coefficients of each PC.

Scores: A numeric matrix showing the loading coefficients of each PC.

IScores: A numeric vector with each element being the rowsum of Scores.

Author(s)

Yi Ya, Yarong Yang, and Yoram Rubin

References

Yarong Yang, Matt Over, and Yoram Rubin.(2012) Strategic Placement of Localization Devices (such as Pilot Points and Anchors) in Inverse Modeling Schemes. Water Resources Research, 48, W08519, doi:10.1029/2012WR011864.

Yi Ya, Yarong Yang, Nader Ebrahimi, Yoram Rubin, and Jacob Zhang. SKNN: A Super K-Nearest Neighbor Classification Algorithm. ongoing

Examples

```
showClass("PCAyD")
```

Description

It's a Super K-Nearest Neighbor classification method with using kernel density to describe weight of the distance between a training observation and the testing sample.

Usage

```
SKNN(data, Class, k, test)
```

Arguments

data	Numeric. The training data set, matrix.
Class	Character. Class of the training observations, vector.
k	Integer. The number of K to be used.
test	Numeric. The sample to be classified.

Value

A character.

Author(s)

Yi Ya, Nader Ebrahimi, and Yoram Rubin

References

Nader Ebrahimi, Yi Ya, and Yoram Rubin. SKNN: A Super K-Nearest Neighbor Classification Algorithm. ongoing

Yarong Yang, Matt Over, and Yoram Rubin.(2012) Strategic Placement of Localization Devices (such as Pilot Points and Anchors) in Inverse Modeling Schemes. Water Resources Research, 48, W08519, doi:10.1029/2012WR011864.

B.B.W. Silverman. Density Estimation for Statistics and Data Analysis. London: Chapman and Hall, 1986.

Examples

```
Sepal.Length<-c(4.8, 5.1, 4.6, 5.3, 5.0, 5.7, 5.7, 6.2, 5.1, 5.7, 6.7, 6.3, 6.5, 6.2, 5.9)
Sepal.Width<-c(3.0, 3.8, 3.2, 3.7, 3.3, 3.0, 2.9, 2.9, 2.5, 2.8, 3.0, 2.5, 3.0, 3.4, 3.0)
Petal.Length<-c(1.4, 1.6, 1.4, 1.5, 1.4, 4.2, 4.2, 4.3, 3.0, 4.1, 5.2, 5.0, 5.2, 5.4, 5.1)
Petal.Width<-c(0.3, 0.2, 0.2, 0.2, 0.2, 1.2, 1.3, 1.3, 1.1, 1.3, 2.3, 1.9, 2.0, 2.3, 1.8)
Species<-as.factor(c(rep("red",5),rep("blue",5),rep("green",5)))
iris<-cbind(Sepal.Length,Sepal.Width,Petal.Length,Petal.Width)
Res<-length(nrow(iris))
```

```
k<-10
for(i in 1:nrow(iris))
  Res[i]<-SKNN(data=iris,Class=as.vector(Species),k=k,test=iris[i,])
accuracy<-length(which(Res==Species))/length(Species)
plot(x=1:15,y=rep(1,15),col=as.vector(Species),lwd=4,ylim=c(0,3),xlab="",ylab="",
yaxt = "n",xaxt="n")
par(new=TRUE)
plot(x=1:15,y=rep(2,15),col=Res,lwd=4,ylim=c(0,3),xlab="",ylab="",yaxt = "n",xaxt="n")
ind<-which(Res!=Species)
if(length(ind)>0) {
  for(j in 1:length(ind))
    lines(x=c(ind[j],ind[j]),y=c(1+0.05,2-0.05))
}
text(5,0.3,paste("SKNN Misclassified:",length(ind)))
axis(2,at=2,labels="SKNN",las=1)
text(10,2.5,paste("k: ",k))
```


Index

* **classes**

PCAy, [6](#)

* **package**

SKNN-package, [2](#)

Dist, [3](#)

KNN, [4](#)

PCAy, [5](#)

PCAy, [6](#)

PCAy-class (PCAy), [6](#)

SKNN, [7](#)

SKNN-package, [2](#)