

# Package ‘aRxiv’

October 12, 2022

**Title** Interface to the arXiv API

**Version** 0.6

**Date** 2021-12-06

**Description** An interface to the API for 'arXiv',  
a repository of electronic preprints for  
computer science, mathematics, physics, quantitative biology,  
quantitative finance, and statistics.

**URL** <https://docs.ropensci.org/aRxiv/>,  
<https://github.com/ropensci/aRxiv>

**BugReports** <https://github.com/ropensci/aRxiv/issues>

**Depends** R (>= 3.0.0)

**License** MIT + file LICENSE

**Imports** httr, utils, XML

**Suggests** devtools, knitr, rmarkdown, roxygen2, testthat

**VignetteBuilder** knitr

**Encoding** UTF-8

**LazyData** true

**RoxygenNote** 7.1.2

**NeedsCompilation** no

**Author** Karthik Ram [aut] (<<https://orcid.org/0000-0002-0233-1757>>),  
Karl Broman [aut, cre] (<<https://orcid.org/0000-0002-4914-6671>>)

**Maintainer** Karl Broman <broman@wisc.edu>

**Repository** CRAN

**Date/Publication** 2021-12-06 17:00:02 UTC

## R topics documented:

arxiv_cats . . . . .	2
arxiv_count . . . . .	2
arxiv_open . . . . .	3
arxiv_search . . . . .	4
can_arxiv_connect . . . . .	6
query_terms . . . . .	7

<b>Index</b>	<b>8</b>
--------------	----------

---

arxiv_cats	<i>arXiv subject classifications</i>
------------	--------------------------------------

---

### Description

arXiv subject classifications: their abbreviations and corresponding descriptions.

### Usage

```
data(arxiv_cats)
```

### Format

A data frame with two columns: the abbreviations of the subject classifications (abbreviation) and the corresponding description (description).

### Source

<https://arxiv.org/help/api/user-manual>

### Examples

```
arxiv_cats
```

---

arxiv_count	<i>Count number of results for a given search</i>
-------------	---

---

### Description

Count the number of results for a given search. Useful to check before attempting to pull down a very large number of records.

### Usage

```
arxiv_count(query = NULL, id_list = NULL)
```

**Arguments**

`query` Search pattern as a string; a vector of such strings is also allowed, in which case the elements are combined with AND.

`id_list` arXiv doc IDs, as comma-delimited string or a vector of such strings

**Value**

Number of results (integer). An attribute "search\_info" contains information about the search parameters and the time at which it was performed.

**See Also**

[arxiv\\_search\(\)](#), [query\\_terms\(\)](#), [arxiv\\_cats\(\)](#)

**Examples**

```
# count papers in category stat.AP (applied statistics)
arxiv_count(query = "cat:stat.AP")

# count papers by Peter Hall in any stat category
arxiv_count(query = 'au:"Peter Hall" AND cat:stat*')

# count papers for a range of dates
# here, everything in 2013
arxiv_count("submittedDate:[2013 TO 2014]")
```

---

arxiv\_open

*Open abstract for results of arXiv search*


---

**Description**

Open, in web browser, the abstract pages for each of set of arXiv search results.

**Usage**

```
arxiv_open(search_results, limit = 20)
```

**Arguments**

`search_results` Data frame of search results, as returned from [arxiv\\_search\(\)](#).

`limit` Maximum number of abstracts to open in one call.

**Details**

There is a delay between calls to `utils::browseURL()`, with the amount taken from the R option "aRxiv\_delay" (in seconds); if missing, the default is 3 sec.

**Value**

(Invisibly) Vector of character strings with URLs of abstracts opened.

**See Also**

[arxiv\\_search\(\)](#)

**Examples**

```
z <- arxiv_search('au:"Peter Hall" AND ti:deconvolution')
arxiv_open(z)
```

---

arxiv\_search

*The main search function for aRxiv*

---

**Description**

Allows for programmatic searching of the arXiv pre-print repository.

**Usage**

```
arxiv_search(
  query = NULL,
  id_list = NULL,
  start = 0,
  limit = 10,
  sort_by = c("submitted", "updated", "relevance"),
  ascending = TRUE,
  batchsize = 100,
  force = FALSE,
  output_format = c("data.frame", "list"),
  sep = "|"
)
```

**Arguments**

query	Search pattern as a string; a vector of such strings also allowed, in which case the elements are combined with AND.
id_list	arXiv doc IDs, as comma-delimited string or a vector of such strings
start	An offset for the start of search
limit	Maximum number of records to return.

sort_by	How to sort the results (ignored if id_list is provided)
ascending	If TRUE, sort in ascending order; else descending (ignored if id_list is provided)
batchsize	Maximum number of records to request at one time
force	If TRUE, force search request even if it seems extreme
output_format	Indicates whether output should be a data frame or a list.
sep	String to use to separate multiple authors, affiliations, DOI links, and categories, in the case that output_format="data.frame".

### Value

If output\_format="data.frame", the result is a data frame with each row being a manuscript and columns being the various fields.

If output\_format="list", the result is a list parsed from the XML output of the search, closer to the raw output from arXiv.

The data frame format has the following columns.

[,1]	id	arXiv ID
[,2]	submitted	date first submitted
[,3]	updated	date last updated
[,4]	title	manuscript title
[,5]	summary	abstract
[,6]	authors	author names
[,7]	affiliations	author affiliations
[,8]	link_abstract	hyperlink to abstract
[,9]	link_pdf	hyperlink to pdf
[,10]	link_doi	hyperlink to DOI
[,11]	comment	authors' comment
[,12]	journal_ref	journal reference
[,13]	doi	published DOI
[,14]	primary_category	primary category
[,15]	categories	all categories

The contents are all strings; missing values are empty strings ("").

The columns authors, affiliations, link\_doi, and categories may have multiple entries separated by sep (by default, "|").

The result includes an attribute "search\_info" that includes information about the details of the search parameters, including the time at which it was completed. Another attribute "total\_results" is the total number of records that match the query.

### See Also

[arxiv\\_count\(\)](#), [arxiv\\_open\(\)](#), [query\\_terms\(\)](#), [arxiv\\_cats\(\)](#)

## Examples

```
# search for author Peter Hall with deconvolution in title
z <- arxiv_search(query = 'au:"Peter Hall" AND ti:deconvolution', limit=2)
attr(z, "total_results") # total no. records matching query
z$title

# search for a set of documents by arxiv identifiers
z <- arxiv_search(id_list = c("0710.3491v1", "0804.0713v1", "1003.0315v1"))
# can also use a comma-separated string
z <- arxiv_search(id_list = "0710.3491v1,0804.0713v1,1003.0315v1")
# Journal references, if available
z$journal_ref

# search for a range of dates (in this case, one day)
z <- arxiv_search("submittedDate:[199701010000 TO 199701012400]", limit=2)
```

---

can\_arxiv\_connect      *Check for connection to arXiv API*

---

## Description

Check for connection to arXiv API

## Usage

```
can_arxiv_connect(max_time = 5)
```

## Arguments

max\_time      Maximum wait time in seconds

## Value

Returns TRUE if connection is established and FALSE otherwise.

## Examples

```
can_arxiv_connect(2)
```

---

query_terms	<i>arXiv query field terms</i>
-------------	--------------------------------

---

**Description**

Possible terms that correspond to different fields in arXiv searches.

**Usage**

```
data(query_terms)
```

**Format**

A data frame with two columns: the term and corresponding description.

**Author(s)**

Karl W Broman

**Source**

<https://arxiv.org/help/api/user-manual>

**Examples**

```
query_terms
```

# Index

## \* datasets

arxiv\_cats, [2](#)  
query\_terms, [7](#)

arxiv\_cats, [2](#)  
arxiv\_cats(), [3](#), [5](#)  
arxiv\_count, [2](#)  
arxiv\_count(), [5](#)  
arxiv\_open, [3](#)  
arxiv\_open(), [5](#)  
arxiv\_search, [4](#)  
arxiv\_search(), [3](#), [4](#)

can\_arxiv\_connect, [6](#)

query\_terms, [7](#)  
query\_terms(), [3](#), [5](#)

utils::browseURL(), [4](#)