

Package ‘altair’

January 23, 2020

Version 4.0.1

Title Interface to 'Altair'

Description Interface to 'Altair' <<https://altair-viz.github.io>>, which itself is a 'Python' interface to 'Vega-Lite' <<https://vega.github.io/vega-lite>>. This package uses the 'Reticulate' framework <<https://rstudio.github.io/reticulate>> to manage the interface between R and 'Python'.

SystemRequirements Python (>= 3.5.0), (Python) Altair (>= 4.0.0)

License MIT + file LICENSE

Encoding UTF-8

LazyData true

ByteCompile true

URL <https://github.com/vegawidget/altair>

BugReports <https://github.com/vegawidget/altair/issues>

Imports reticulate (>= 1.9), htmlwidgets, assertthat, magrittr, utils, vegawidget (>= 0.3.1), repr

Suggests httr, rprojroot, purrr, readr, knitr, rmarkdown, tibble, listviewer (>= 2.0.0), testthat, pryr, stringr, tidyr, dplyr, pkgdown, processx, rsvg, png, fs

RoxygenNote 7.0.2

NeedsCompilation no

Author Ian Lyttle [aut, cre] (<<https://orcid.org/0000-0001-9962-4849>>),
Haley Jeppson [aut],
Altair Developers [aut],
Alicia Schep [ctb] (<<https://orcid.org/0000-0002-3915-0618>>),
Jake Vanderplas [ctb] (Altair library),
Brian Granger [ctb] (Altair library)

Maintainer Ian Lyttle <ian.lyttle@schneider-electric.com>

Repository CRAN

Date/Publication 2020-01-23 20:10:02 UTC

R topics documented:

| | |
|--|-----------|
| alt | 2 |
| altair | 3 |
| altair_concatenation | 3 |
| altair_version | 5 |
| as_chart | 5 |
| as_vegaspec.altair.vegalite.v4.api.TopLevelMixin | 6 |
| check_altair | 6 |
| image | 7 |
| import_vega_data | 8 |
| install_altair | 9 |
| knit_print.altair.vegalite.v4.api.TopLevelMixin | 10 |
| renderVegawidget | 10 |
| vegawidget | 11 |
| vegawidgetOutput | 11 |
| vega_embed | 11 |
| vw_as_json | 12 |
| Index | 13 |

| | |
|-----|----------------------|
| alt | <i>Altair object</i> |
|-----|----------------------|

Description

Uses the reticulate framework to access the Altair API.

Usage

```
alt
```

Format

An object of class `python.builtin.module` (inherits from `python.builtin.object`) of length 5.

Details

The Altair Python library is exposed through the `alt` object. You can create and add to chart using its methods and classes, as outlined in the [Altair Python documentation](#).

In this package, use the `$` operator wherever you see the `.` operator used in Python.

See Also

[Altair Python documentation](#), [altair: Field Guide to Python Issues](#)

Examples

```
if (interactive()) {
  vega_data <- import_vega_data()

  plot_basic <-
    alt$Chart(vega_data$cars())$
    encode(
      x = "Miles_per_Gallon:Q",
      y = "Horsepower:Q",
      color = "Origin:N"
    )$
    mark_point()

  plot_basic
}
```

| | |
|--------|--|
| altair | <i>altair: Create and embed Vega-Lite charts using the Altair Python package</i> |
|--------|--|

Description

The goal of altair is to help you build **Vega-Lite** visualizations. Using the **reticulate** package, it provides an interface to the **Altair** Python package.

Details

In this documentation, the capitalized word **Altair** shall refer to the Python package; the lower-case word **altair** shall refer to this R package.

See Also

[altair pkgdown website](#), [Altair Python package](#), [Vega-Lite](#)

| | |
|----------------------|----------------------------------|
| altair_concatenation | <i>Altair plot concatenation</i> |
|----------------------|----------------------------------|

Description

Altair plots can be concatenated using the following operators: `+`, `|`, and `&`

Usage

```
## S3 method for class 'altair.vegalite.v4.api.TopLevelMixin'
e1 | e2

## S3 method for class 'altair.vegalite.v4.api.TopLevelMixin'
e1 + e2

## S3 method for class 'altair.vegalite.v4.api.TopLevelMixin'
e1 & e2
```

Arguments

```
e1           Altair chart object
e2           Altair chart object
```

Value

Compound Altair chart object

Examples

```
if (interactive()){

  # Examples using the beaver1 and beaver2 body temperature data sets
  # Layering Charts
  base <- alt$Chart(beaver1)$encode(
    x = alt$X('time'),
    y = alt$Y('temp', scale = alt$Scale(zero = FALSE))
  )

  scatter_plot <- base$mark_point()
  line_plot <- base$mark_line()

  combined_plot <- scatter_plot + line_plot

  # Horizontal Concatenation
  base2 <- alt$Chart(beaver2)$
    encode(
      x = alt$X("time"),
      y = alt$Y("temp", scale = alt$Scale(zero = FALSE))
    )

  scatter_plot2 <- base2$mark_point()
  line_plot2 <- base2$mark_line()

  combined_plot <-
    (scatter_plot + line_plot)$
    properties(title = "Beaver 1", width = 200)

  combined_plot2 <-
```

```
(scatter_plot2 + line_plot2)$  
  properties(title = "Beaver 2", width = 200)  
  
hconcat_plot <- combined_plot | combined_plot2  
  
# Vertical Concatenation  
vconcat_plot <- combined_plot & combined_plot2  
  
}
```

| | |
|----------------|---|
| altair_version | <i>Installed versions of Altair, Vega, etc.</i> |
|----------------|---|

Description

Returns a named list of version tags for Altair, Vega, Vega-Lite, and Vega-Embed

Usage

```
altair_version()
```

Value

named list of version tags

Examples

```
if (interactive()) {  
  altair_version()  
}
```

| | |
|----------|--|
| as_chart | <i>Create Altair chart from vegaspec</i> |
|----------|--|

Description

Create Altair chart from vegaspec

Usage

```
as_chart(spec)
```

Arguments

spec An object to be coerced to vegaspec, a Vega/Vega-Lite specification

Value

altair object

Examples

```
if (interactive()) {
  as_chart(vegawidget::spec_mtcars)
}
```

as_vegaspec.altair.vegalite.v4.api.TopLevelMixin
Coerce to vegaspec

Description

See `vegawidget::as_vegaspec` for details.

Usage

```
## S3 method for class 'altair.vegalite.v4.api.TopLevelMixin'
as_vegaspec(spec, ...)
```

Arguments

| | |
|------|---|
| spec | An object to be coerced to vegaspec, a Vega/Vega-Lite specification |
| ... | Other arguments (attempt to future-proof) |

check_altair *Check the Altair installation*

Description

Provides feedback on any differences between your installed version of Altair and the version this package supports.

Usage

```
check_altair(quiet = FALSE)
```

Arguments

| | |
|-------|--|
| quiet | logical, if TRUE, suppresses message upon successful check |
|-------|--|

Details

If the supported Altair version is different from your installed version, this function will act according to where the difference in the version numbers:

- major version leads to an **error**
- minor version leads to a **warning**
- patch version leads to a **message**

If there is no difference:

- quiet = FALSE, success message showing version-numbers
- quiet = TRUE, no message

To install the supported version into a Python environment called "r-reticulate", use `install_altair()`.

Value

invisible NULL, called for side-effects

See Also

`reticulate::py_config()`, `install_altair()`, `altair_version()`

Examples

```
## Not run:  
# not run because it requires Python  
check_altair()  
  
## End(Not run)
```

image

Create or write image

Description

See `vegawidget::image` for details.

import_vega_data *Import Vega datasets*

Description

Lets you access Vega datasets.

Usage

```
import_vega_data()
```

Details

Returns the data object in the Python package [vega-datasets](#). In the documentation for this package, the convention is to assign this object to the name `vega_data`.

Value

An S3 object of class `vega_datasets.core.DataLoader`

See Also

[Vega datasets documentation](#)

Examples

```
if (interactive()) {
  vega_data <- import_vega_data()

  # To list available datasets
  print(vega_data$list_datasets())

  # When accessing a dataset, substitute any "-" in the name with a "_"
  print(head(vega_data$sf_temps()))

  # Metadata are available for each dataset:
  print(vega_data$anscombe$references)
  print(vega_data$anscombe$description)
  print(vega_data$anscombe$url)

  # For local datasets, local path is available
  print(vega_data$sf_temps$filepath)
}
```

| | |
|----------------|--------------------------------------|
| install_altair | <i>Install Altair Python package</i> |
|----------------|--------------------------------------|

Description

This function wraps installation functions from [reticulate](#) to install the Python packages **altair** and **vega_datasets**.

Usage

```
install_altair(  
  method = c("conda", "virtualenv"),  
  envname = "r-reticulate",  
  pip = FALSE,  
  version = getOption("altair.python.version"),  
  ...  
)
```

Arguments

| | |
|---------|--|
| method | character, indicates to use "conda" or "virtualenv" |
| envname | character, name of environment into which to install |
| pip, | logical, used for conda installation to indicate to use pip (will be set to TRUE for release-candidates) |
| version | character, version of Altair to install. For general use of this package, this is set automatically, so you should not need to specify this. |
| ... | other arguments sent to reticulate::conda_install() or reticulate::virtualenv_install() |

Details

This package uses the [reticulate](#) package to make an interface with the **Altair** Python package. To promote consistency in usage of **reticulate** among different R packages, it is **recommended** to use a common Python environment, called "r-reticulate".

Depending on your setup, you can create this environment using [reticulate::conda_create\(\)](#) or [reticulate::virtualenv_create\(\)](#), as described in this [reticulate article](#), or in this package's [Installation article](#).

Value

invisible NULL, called for side-effects

See Also

[altiar: Installation](#), [reticulate: Using reticulate in an R Package](#), [reticulate: Installing Python Packages](#)

Examples

```
## Not run:
# not run because it requires Python
install_altair()

## End(Not run)
```

```
knit_print.altair.vegalite.v4.api.TopLevelMixin
Knit-print method
```

Description

See `vegawidget::knit_print.vegaspec` for details, particularly on additional packages that may have to be installed.

Usage

```
knit_print.altair.vegalite.v4.api.TopLevelMixin(spec, ..., options = NULL)
```

Arguments

| | |
|----------------------|---|
| <code>spec</code> | An object to be coerced to <code>vegaspec</code> , a Vega/Vega-Lite specification |
| <code>...</code> | other arguments |
| <code>options</code> | list, knitr options |

```
renderVegawidget Render shiny-output for vegawidget
```

Description

Deprecated, please use `vegawidget::renderVegawidget`.

Usage

```
renderVegawidget(expr, env = parent.frame(), quoted = FALSE)
```

Arguments

| | |
|---------------------|--|
| <code>expr</code> | expression that generates a <code>vegawidget</code> . This can be a <code>vegawidget</code> or a <code>vegaspec</code> . |
| <code>env</code> | The environment in which to evaluate <code>expr</code> . |
| <code>quoted</code> | Is <code>expr</code> a quoted expression (with <code>quote()</code>)? This is useful if you want to save an expression in a variable. |

| | |
|------------|---|
| vegawidget | <i>Create a Vega/Vega-Lite htmlwidget</i> |
|------------|---|

Description

See `vegawidget::vegawidget` for details.

| | |
|------------------|------------------------------------|
| vegawidgetOutput | <i>Shiny-output for vegawidget</i> |
|------------------|------------------------------------|

Description

Deprecated, please use `vegawidget::vegawidgetOutput`.

Usage

```
vegawidgetOutput(outputId, width = "auto", height = "auto")
```

Arguments

| | |
|----------|--|
| outputId | output variable to read from |
| width | Must be a valid CSS unit (like "100%", "400px", "auto") or a number, which will be coerced to a string and have "px" appended. For vegawidgets, "auto" is useful because, as of now, the spec determines the size of the widget, then the widget determines the size of the container. |
| height | Must be a valid CSS unit (like "100%", "400px", "auto") or a number, which will be coerced to a string and have "px" appended. For vegawidgets, "auto" is useful because, as of now, the spec determines the size of the widget, then the widget determines the size of the container. |

| | |
|------------|---------------------------|
| vega_embed | <i>Vega embed options</i> |
|------------|---------------------------|

Description

See `vegawidget::vega_embed` for details.

`vw_as_json`*Coerce vegaspec to JSON*

Description

Deprecated, please use `vegawidget::vw_as_json`.

Usage

```
vw_as_json(spec, pretty = TRUE)
```

Arguments

| | |
|---------------------|---|
| <code>spec</code> | An object to be coerced to vegaspec, a Vega/Vega-Lite specification |
| <code>pretty</code> | logical indicates to use pretty (vs. minified) formatting |

Value

`jsonlite::json` object

Index

- *Topic **datasets**
- alt, [2](#)
- + .altair.vegalite.v4.api.TopLevelMixin
(altair_concatenation), [3](#)
- & .altair.vegalite.v4.api.TopLevelMixin
(altair_concatenation), [3](#)

- alt, [2](#)
- altair, [3](#)
- altair_concatenation, [3](#)
- altair_version, [5](#)
- altair_version(), [7](#)
- as_chart, [5](#)
- as_vegaspec, [6](#)
- as_vegaspec
(as_vegaspec.altair.vegalite.v4.api.TopLevelMixin),
[6](#)
- as_vegaspec.altair.vegalite.v4.api.TopLevelMixin,
[6](#)

- check_altair, [6](#)

- image, [7](#), [7](#)
- import_vega_data, [8](#)
- install_altair, [9](#)
- install_altair(), [7](#)

- knit_print.altair.vegalite.v4.api.TopLevelMixin,
[10](#)
- knit_print.vegaspec, [10](#)
- knit_print.vegaspec
(knit_print.altair.vegalite.v4.api.TopLevelMixin),
[10](#)

- renderVegawidget, [10](#), [10](#)
- reticulate, [9](#)
- reticulate::conda_create(), [9](#)
- reticulate::conda_install(), [9](#)
- reticulate::py_config(), [7](#)
- reticulate::virtualenv_create(), [9](#)
- reticulate::virtualenv_install(), [9](#)

- vega_embed, [11](#), [11](#)
- vegawidget, [11](#), [11](#)
- vegawidgetOutput, [11](#), [11](#)
- vw_as_json, [12](#), [12](#)
- vw_to_bitmap(image), [7](#)
- vw_to_svg(image), [7](#)
- vw_write_png(image), [7](#)
- vw_write_svg(image), [7](#)