

# Package ‘amerifluxr’

October 12, 2022

**Type** Package

**Title** Interface to 'AmeriFlux' Data Services

**Version** 1.0.0

**Description** Programmatic interface to the 'AmeriFlux' database  
(<<https://ameriflux.lbl.gov/>>). Provide query, download,  
and data summary tools.

**License** BSD\_3\_clause + file LICENSE

**Encoding** UTF-8

**LazyData** true

**URL** <https://github.com/chuhousen/amerifluxr>

**BugReports** <https://github.com/chuhousen/amerifluxr/issues>

**Depends** R (>= 3.6)

**Imports** heatmaply, httr, jsonlite, memoise, RCurl, readxl, tools

**RoxygenNote** 7.1.2

**Suggests** covr, data.table, knitr, pander, qpdf, remotes, rmarkdown,  
testthat, mockr

**VignetteBuilder** knitr

**NeedsCompilation** no

**Author** Housen Chu [aut, cre] (<<https://orcid.org/0000-0002-8131-4938>>),  
Koen Hufkens [ctb] (<<https://orcid.org/0000-0002-5070-8109>>)

**Maintainer** Housen Chu <hchu@lbl.gov>

**Repository** CRAN

**Date/Publication** 2022-02-08 16:30:08 UTC

## R topics documented:

amf_base	2
amf_bif	4
amf_check_site_id	4

amf_data_coverage . . . . .	5
amf_download_base . . . . .	6
amf_download_bif . . . . .	7
amf_extract_badm . . . . .	9
amf_filter_base . . . . .	10
amf_list_data . . . . .	12
amf_list_metadata . . . . .	13
amf_parse_basename . . . . .	14
amf_plot_datasummary . . . . .	15
amf_plot_datayear . . . . .	17
amf_read_base . . . . .	18
amf_read_bif . . . . .	19
amf_sites . . . . .	20
amf_site_info . . . . .	21
amf_summarize_data . . . . .	22
amf_variables . . . . .	23
amf_var_info . . . . .	24

<b>Index</b>	<b>26</b>
--------------	-----------

---

amf_base	<i>BASE data example</i>
----------	--------------------------

---

## Description

Continuous flux/met data (i.e., AmeriFlux BASE data product) for the US-CRT site, as an example for demonstration. Also see AmeriFlux webpage <https://ameriflux.lbl.gov/data/aboutdata/data-variables/#base> for variable definitions and details.

## Usage

amf\_base

## Format

A data frame with 336 rows and 36 variables

## Details

- `TIMESTAMP_START` - ISO timestamp start of averaging period (YYYYMMDDHHMM)
- `TIMESTAMP_END` - ISO timestamp end of averaging period (YYYYMMDDHHMM)
- `CO2` - Carbon Dioxide (CO<sub>2</sub>) mole fraction in wet air (μmolCO<sub>2</sub> mol<sup>-1</sup>)
- `H2O` - Water (H<sub>2</sub>O) vapor in mole fraction of wet air (mmolH<sub>2</sub>O mol<sup>-1</sup>)
- `FC` - Carbon Dioxide (CO<sub>2</sub>) turbulent flux (μmolCO<sub>2</sub> m<sup>-2</sup> s<sup>-1</sup>)
- `NEE_PI` - Net Ecosystem Exchange (μmolCO<sub>2</sub> m<sup>-2</sup> s<sup>-1</sup>)
- `CH4` - Methane (CH<sub>4</sub>) mole fraction in wet air (nmolCH<sub>4</sub> mol<sup>-1</sup>)

- FCH4 - Methane (CH<sub>4</sub>) turbulent flux (nmolCH<sub>4</sub> m<sup>-2</sup> s<sup>-1</sup>)
- H - Sensible heat turbulent flux (W m<sup>-2</sup>)
- LE - Latent heat turbulent flux (W m<sup>-2</sup>)
- G\_1\_1\_1 - Soil heat flux at horizontal location #1 (W m<sup>-2</sup>)
- G\_2\_1\_1 - Soil heat flux at horizontal location #2 (W m<sup>-2</sup>)
- WD - Wind direction (Decimal degrees)
- WS - Wind speed (m s<sup>-1</sup>)
- USTAR - Friction velocity (m s<sup>-1</sup>)
- ZL - data value
- MO\_LENGTH - Monin-Obukhov Stability parameter (nondimensional)
- W\_SIGMA - Standard deviation of vertical velocity fluctuations (m s<sup>-1</sup>)
- V\_SIGMA - Standard deviation of lateral velocity fluctuations (m s<sup>-1</sup>)
- U\_SIGMA - Standard deviation of along-wind velocity fluctuations (m s<sup>-1</sup>)
- T\_SONIC - Sonic temperature (deg C)
- T\_SONIC\_SIGMA - Standard deviation of sonic temperature (deg C)
- PA - Atmospheric pressure (kPa)
- RH - Relative humidity (%)
- TA - Air temperature (deg C)
- TS\_1\_1\_1 - Soil temperature at horizontal location #1 (deg C)
- TS\_2\_1\_1 - Soil temperature at horizontal location #2 (deg C)
- WTD - Water table depth (m)
- SWC - Soil water content (%)
- NETRAD - Net radiation (W m<sup>-2</sup>)
- PPF<sub>IN</sub> - Photosynthetic photon flux density, incoming (μmolPhoton m<sup>-2</sup> s<sup>-1</sup>)
- SW\_IN - Shortwave radiation, incoming (W m<sup>-2</sup>)
- SW\_OUT - Shortwave radiation, outgoing (W m<sup>-2</sup>)
- LW\_IN - Longwave radiation, incoming (W m<sup>-2</sup>)
- LW\_OUT - Longwave radiation, outgoing (W m<sup>-2</sup>)
- P - Rainfall (mm)

**Source**

<https://ameriflux.lbl.gov/>

---

`amf_bif`*BADM data example*

---

**Description**

The BADM file provides a description, general background, geo-location, relevant publications and references for the site. The BADM files also list what is measured at the site (this list may include chamber, gradient or other eddy covariance measurements that are a super-set of the data available in AmeriFlux). Also see AmeriFlux web page <https://ameriflux.lbl.gov/data/aboutdata/badm-data-product/> for details.

**Usage**`amf_bif`**Format**

A data frame with 443 rows and 5 variables

**Details**

- SITE\_ID - 6 digit AmeriFlux site ID (CC-Sss)
- GROUP\_ID - A unique identifier for data entries belonging to the same instance of a reported variable group
- VARIABLE\_GROUP - Define a set of variables that are reported together
- VARIABLE - Variable names
- DATAVALUE - Data value

**Source**

<https://ameriflux.lbl.gov/>

---

`amf_check_site_id`*Check valid AmeriFlux site ID*

---

**Description**

Check if the character is a valid AmeriFlux site ID (CC-Sss)

**Usage**`amf_check_site_id(x)`**Arguments**

`x` A vector or scalar of characters

**Value**

logical vector or scalar

**Examples**

```
## Not run:  
# Check if valid site ID  
check_id <- amf_check_site_id(c("US-CRT", "US-crt", "USCRT"))  
  
## End(Not run)
```

---

amf\_data\_coverage      *Returns a list of data coverage*

---

**Description**

AmeriFlux data coverage statistics

**Usage**

```
amf_data_coverage(data_product = "BASE-BADM", data_policy = "CCBY4.0")
```

**Arguments**

data_product	A scalar of character specifying the data product Currently, only "BASE-BADM" is supported.
data_policy	A scalar of character specifying the data policy Currently, "CCBY4.0" and "LEGACY" are supported. The default is "CCBY4.0".

**Value**

AmeriFlux data coverage

- SITE\_ID - Six character site identifier (CC-Sss)
- URL - Site page link (url)
- publish\_years - List of data available years (YYYY)

**Examples**

```
## Not run:  
# download the variable availability  
data_year <- amf_data_coverage()  
  
# download variable availability for LEGACY policy  
data_year <- amf_data_coverage(data_policy = "LEGACY")  
  
## End(Not run)
```

---

amf\_download\_base      *Download AmeriFlux BASE data product*

---

## Description

This function downloads AmeriFlux BASE and BADM data files. Note: Access to AmeriFlux data requires creating an AmeriFlux account first. Register an account through the link <https://ameriflux-data.lbl.gov/Pages/RequestAccount.aspx>.

For details about BASE and BADM data files, see AmeriFlux web pages <https://ameriflux.lbl.gov/data/data-processing-pipelines/base-publish/> and <https://ameriflux.lbl.gov/data/aboutdata/badm-data-product/>.

## Usage

```
amf_download_base(
  user_id,
  user_email,
  site_id,
  data_product = "BASE-BADM",
  data_policy,
  agree_policy,
  intended_use,
  intended_use_text,
  out_dir = tempdir(),
  verbose = TRUE
)
```

## Arguments

user_id	AmeriFlux account username (character)
user_email	AmeriFlux account user email (character)
site_id	A scalar or vector of character specifying the AmeriFlux Site ID (CC-Sss)
data_product	AmeriFlux data product. Currently, only "BASE-BADM" is supported and used as default. (character)
data_policy	"CCBY4.0" or "LEGACY" (character). AmeriFlux data are shared under two tiers of licenses as chosen by site's PI. See <a href="https://ameriflux.lbl.gov/data/data-policy/#data-use">https://ameriflux.lbl.gov/data/data-policy/#data-use</a> for data use guidelines under each license. Note: Data use policy selected affects which sites' data are available for download.
agree_policy	Acknowledge you read and agree to the AmeriFlux Data use policy (TRUE/FALSE)
intended_use	The intended use category. Currently, it needs to be one of the followings: <ul style="list-style-type: none"> <li>• "synthesis" (i.e., Multi-site synthesis)</li> <li>• "model" (i.e., Land model/Earth system model)</li> <li>• "remote_sensing" (i.e., Remote sensing research)</li> <li>• "other_research" (i.e., Other research) "</li> </ul>

- "education" (i.e., Education (Teacher or Student))
- "other"

intended_use_text	Enter a brief description of intended use. This will be recorded in the download log and emailed to site's PI (character).
out_dir	Output directory for downloaded data, default tempdir()
verbose	Show feedback on download progress (TRUE/FALSE)

**Value**

A vector of download file names on the local drive

**Examples**

```
## Not run:
## Download a single site, under CCBY4.0 policy
amf_download_base(user_id = "test",
  user_email = "test_at_mail.com",
  site_id = "US-CRT",
  data_product = "BASE-BADM",
  data_policy = "CCBY4.0",
  agree_policy = TRUE,
  intended_use = "other",
  intended_use_text = "testing download",
  out_dir = tempdir())

## Download several sites, under LEGACY data policy
# When finished, return a list of downloaded files
# in your local drive.
file.ls <- amf_download_base(user_id = "test",
  user_email = "test_at_mail.com",
  site_id = c("US-CRT", "US-WPT", "US-Oho"),
  data_product = "BASE-BADM",
  data_policy = "LEGACY",
  agree_policy = TRUE,
  intended_use = "other",
  intended_use_text = "testing download",
  out_dir = tempdir())

## End(Not run)
```

## Description

This function downloads all AmeriFlux sites' BADM data files in a single file. Note: Access to AmeriFlux data requires creating an AmeriFlux account first. Register an account through the link <https://ameriflux-data.lbl.gov/Pages/RequestAccount.aspx>.

For details about BADM data files, see AmeriFlux web page <https://ameriflux.lbl.gov/data/aboutdata/badm-data-product/>.

## Usage

```
amf_download_bif(
  user_id,
  user_email,
  data_policy,
  agree_policy,
  intended_use,
  intended_use_text,
  out_dir = tempdir(),
  verbose = TRUE,
  site_w_data = FALSE
)
```

## Arguments

user_id	AmeriFlux account username (character)
user_email	AmeriFlux account user email (character)
data_policy	"CCBY4.0" or "LEGACY". AmeriFlux data are shared under two tiers of licenses as chosen by site's PI. See <a href="https://ameriflux.lbl.gov/data/data-policy/#data-use">https://ameriflux.lbl.gov/data/data-policy/#data-use</a> for data use guidelines under each license. Note: Data use policy selected affects which sites' data are available for download.
agree_policy	Acknowledge you read and agree to the AmeriFlux Data use policy (TRUE/FALSE)
intended_use	The intended use category. Currently, it needs to be one of the followings: <ul style="list-style-type: none"> <li>• "synthesis" (i.e., Multi-site synthesis)</li> <li>• "model" (i.e., Land model/Earth system model)</li> <li>• "remote_sensing" (i.e., Remote sensing research)</li> <li>• "other_research" (i.e., Other research) "</li> <li>• "education" (i.e., Education (Teacher or Student))</li> <li>• "other"</li> </ul>
intended_use_text	Enter a brief description of intended use. This will be recorded in the data download log and emailed to site's PI (character).
out_dir	Output directory for downloaded data, default tempdir()
verbose	Show feedback on download progress (TRUE/FALSE)
site_w_data	Logical, download all registered sites (FALSE) or only sites with available BASE data (TRUE)



**Value**

A vector of download file names on the local drive

**See Also**

[amf\\_download\\_base](#)

**Examples**

```
## Not run:
## Download all sites with BASE data, under CCBY4.0 policy
amf_download_bif(user_id = "test",
  user_email = "test@mail.com",
  data_policy = "CCBY4.0",
  agree_policy = TRUE,
  intended_use = "other",
  intended_use_text = "testing download",
  out_dir = tempdir(),
  site_w_data = TRUE)

## Download all registered sites, under LEGACY policy
amf_download_bif(user_id = "test",
  user_email = "test@mail.com",
  data_policy = "LEGACY",
  agree_policy = TRUE,
  intended_use = "other",
  intended_use_text = "testing download",
  out_dir = tempdir(),
  site_w_data = FALSE)

## End(Not run)
```

---

amf_extract_badm	<i>Extract BADM data of a specific BADM group</i>
------------------	---

---

**Description**

This function extracts BADM data of a specific BADM group from the imported BADM (BIF) file. Use function [amf\\_read\\_bif](#) to import BADM (BIF) file.

**Usage**

```
amf_extract_badm(bif_data, select_group)
```

**Arguments**

- bif\_data      A data frame consists of 5 columns: SITE\_ID, GROUP\_ID, VARIABLE\_GROUP, VARIABLE, DATAVALUE, imported from function [amf\\_read\\_bif](#).
- select\_group    A string (character), selected from VARIABLE\_GROUP in the bif\_data

**Value**

A data frame of re-structured BADM data with the following columns:

- GROUP\_ID - A unique identifier for data belonging to the same instance of a reported variable group
- SITE\_ID - Six character site identifier (CC-Sss)
- VALUE - Values for all available VARIABLES in the selected group
- ...

**See Also**

[amf\\_read\\_bif](#)

**Examples**

```
# read the BADM BIF file, using an example data file
bif <- amf_read_bif(file = system.file("extdata",
                                     "AMF_AA-Flx_BIF_CCBY4_20201218.xlsx",
                                     package = "amerifluxr"))

# get a list of valid VARIABLE_GROUP
unique(bif$VARIABLE_GROUP)

# extract the selected VARIABLE_GROUP
amf_extract_badm(bif_data = bif, select_group = "GRP_FLUX_MEASUREMENTS")
amf_extract_badm(bif_data = bif, select_group = "GRP_IGBP")
```

---

amf\_filter\_base

*Filter AmeriFlux BASE data based on plausible range*

---

**Description**

The function filters BASE data based on the expected plausible ranges specified for each variable.

See AmeriFlux web site <https://ameriflux.lbl.gov/data/data-processing-pipelines/data-qaqc/> for description of the plausible ranges.

**Usage**

```
amf_filter_base(
  data_in,
  limit_ls = NULL,
  basename_decode = NULL,
  loose_filter = 0.05
)
```

**Arguments**

<code>data_in</code>	A data frame containing BASE data, e.g., import from <a href="#">amf_read_base</a> .
<code>limit_ls</code>	A data frame with at least three columns: <ul style="list-style-type: none"> <li>• Name: variable base name</li> <li>• Min: expected lower bound</li> <li>• Max: expected upper bound</li> </ul> If not specified, use <a href="#">amf_variables</a> by default.
<code>basename_decode</code>	A data frame with at least two columns: <ul style="list-style-type: none"> <li>• <code>variable_name</code>: actual variable name</li> <li>• <code>basename</code>: variable base name</li> </ul> If not specified, use <a href="#">amf_parse_basename</a> by default.
<code>loose_filter</code>	A number in ratio (0-1) used to adjust the physical range for filtering. Set it to 0 if not used. The default is 0.05.

**Value**

A data frame similar to `data_in` filtered out off-range points

**Examples**

```
## Not run:
# read the BASE from a csv file
base <- amf_read_base(file = system.file("extdata",
                                         "AMF_US-CRT_BASE_HH_2-5.csv",
                                         package = "amerifluxr"),
                     unzip = FALSE,
                     parse_timestamp = FALSE)

# filter data, using default physical range +/- 5% buffer
base_f <- amf_filter_base(data_in = base)

# filter data, using default physical range without buffer
base_f <- amf_filter_base(data_in = base, loose_filter = 0)

## End(Not run)
```

---

amf_list_data	<i>Get BASE data variable availability</i>
---------------	--

---

### Description

This function obtains the BASE data availability for all or selected AmeriFlux sites. See AmeriFlux page <https://ameriflux.lbl.gov/data/aboutdata/data-variables/> for details about the variable naming.

### Usage

```
amf_list_data(site_set = NULL, var_set = NULL)
```

### Arguments

site_set	A scalar or vector of character specifying the target AmeriFlux Site ID (CC-Sss). If not specified, it returns all sites.
var_set	A scalar or vector of character specifying the target variables as in basename. See AmeriFlux page <a href="https://ameriflux.lbl.gov/data/aboutdata/data-variables/#base">https://ameriflux.lbl.gov/data/aboutdata/data-variables/#base</a> for a list of variable names. If not specified, it returns all variables.

### Value

A data frame of variable-specific data availability (per year) for selected AmeriFlux sites.

- Site\_ID - Six character site identifier (CC-Sss)
- VARIABLE - Variable name of the data included in the BASE file
- BASENAME - Variable base name of the data included in the BASE file.
- GAP\_FILLED - Whether a variable is a gap-filled variable (TRUE/FALSE)
- Y1990 - Percentage of data availability in the year 1990 (0-1).
- Y1991 - Percentage of data availability in the year 1991 (0-1).
- Y1992 - Percentage of data availability in the year 1992 (0-1).
- ...

### Examples

```
## Not run:
# obtain the data variable availability for all sites
data_aval <- amf_list_data()

# obtain the data variable availability for selected sites
data_aval <- amf_list_data(site_set = c("US-CRT", "US-WPT"))

# obtain the data variable availability for selected variables
data_aval <- amf_list_data(var_set = c("FCH4", "WTD"))

## End(Not run)
```

---

amf_list_metadata	<i>Get metadata availability</i>
-------------------	----------------------------------

---

## Description

This function obtains the metadata (i.e., BADM) availability for all or selected AmeriFlux sites. See AmeriFlux page <https://ameriflux.lbl.gov/data/badm/> for details about the BADM.

## Usage

```
amf_list_metadata(site_set = NULL, group_only = TRUE)
```

## Arguments

site_set	A scalar or vector of character specifying the target AmeriFlux Site ID (CC-Sss). If not specified, it returns all sites.
group_only	Logical (TRUE/FALSE). Should it return availability for BADM variable groups or variables? BADM Groups contain Variables that describe related metadata or an observation with related metadata.

## Value

A data frame of data variable availability (per year) for selected AmeriFlux sites. The first column contains the SITE ID. The remaining columns contains the number of entries for a variable or a variable group, with column names specifying the BADM variable or group names.

- Site\_ID - Six character site identifier (CC-Sss)
- ...

## Examples

```
## Not run:  
# obtain the metadata availability for all sites, at variable group levels  
metadata_aval <- amf_list_metadata()  
  
# obtain the metadata availability for selected sites, at variable levels  
metadata_aval <- amf_list_metadata(site_set = c("US-CRT", "US-WPT"),  
group_only = FALSE)  
  
## End(Not run)
```

---

amf\_parse\_basename      *Parse BASE data variable name and qualifier*

---

### Description

This function parse variable names and qualifiers of AmeriFlux BASE data product. See AmeriFlux web page <https://ameriflux.lbl.gov/data/aboutdata/data-variables/> about the details of variable naming and qualifiers.

### Usage

```
amf_parse_basename(var_name, FP_ls = NULL, gapfill_postfix = "_PI_F")
```

### Arguments

`var_name`            A vector of variable names (character) to be parsed

`FP_ls`                A vector of standard variable names. If not specified, use `amf_variables` by default to get the latest list.

`gapfill_postfix`    A scalar of expected suffix (character) appended to a variable that is gap-filled. The default is "\_PI\_F".

### Value

A data frame containing the parsed results for all variables in `var_name`:

- `variable_name` - original variable name
- `basename` - associated basename, w/o qualifier
- `qualifier_gf` - qualifier associated with gap-filling
- `qualifier_pi` - qualifier associated with PI version, excluding gap-filling
- `qualifier_pos` - qualifier associated with position
- `qualifier_ag` - qualifier associated with layer-aggregation, e.g., `_N`, `_SD`
- `layer_index` - layer index provided, if any
- `H_index` - H index provided, if any
- `V_index` - V index provided, if any
- `R_index` - R index provided, if any
- `is_correct_basename` - is the parsed basename recognized in FP-Standard
- `is_pi_provide` - is this a PI provided variable e.g., `_PI`
- `is_gapfill` - is this a gap-filled variable, `_PF_F` or `_F`
- `is_fetch` - is this a fetch quantile variable, e.g., `FETCH_70...`
- `is_layer_aggregated` - is this a layer-integrated variable, i.e., `_#`
- `is_layer_SD` - is this a standard deviation of layer-integrated variable, i.e., spatial variability

- `is_layer_number` - is this a number of samples of layer-integrated variable, i.e., spatial variability
- `is_replicate_aggregated` - is this a replicate-averaged variable, e.g., `_1_1_A`
- `is_replicate_SD` - is this a standard deviation of replicate-averaged variable, e.g., `_1_1_A_SD`
- `is_replicate_number` - is this a number of samples of replicate-averaged variable, e.g., `_1_1_A_N`
- `is_quadruplet` - is this a quadruplet, e.g., `_1_1_1`

### See Also

[amf\\_variables](#)

### Examples

```
## Not run:
# read the BASE from a csv file
base <- amf_read_base(file = system.file("extdata",
                                         "AMF_US-CRT_BASE_HH_2-5.csv",
                                         package = "amerifluxr"),
                    unzip = FALSE,
                    parse_timestamp = FALSE)

# parse variable names/qualifiers
basename_decode <- amf_parse_basename(var_name = colnames(base))

## End(Not run)
```

---

`amf_plot_datasummary` *Plot data summary*

---

### Description

This function visualizes the BASE data summary for selected AmeriFlux sites and variables. This is a wrapper around [amf\\_summarize\\_data](#). However, it is strongly advised to subset either sites or variables for faster processing and better visualization.

### Usage

```
amf_plot_datasummary(
  data_sum = NULL,
  site_set = NULL,
  var_set = NULL,
  nonfilled_only = TRUE,
  show_cluster = FALSE,
  scale = FALSE
)
```

**Arguments**

data_sum	<p>A data frame with following columns:</p> <ul style="list-style-type: none"> <li>• Site_ID - Six character site identifier (CC-Sss)</li> <li>• VARIABLE - Variable name of the data included in the BASE file</li> <li>• BASENAME - Variable base name of the data included in the BASE file.</li> <li>• GAP_FILLED - Whether a variable is a gap-filled variable (TRUE/FALSE)</li> <li>• Any statistics, e.g., P01, P05... output from <a href="#">amf_summarize_data</a></li> </ul> <p>If not specified, use <a href="#">amf_summarize_data</a> by default.</p>
site_set	A scalar or vector of character specifying the target AmeriFlux Site ID (CC-Sss). If not specified, it returns all sites.
var_set	A scalar or vector of character specifying the target variables as in basename. See AmeriFlux page <a href="https://ameriflux.lbl.gov/data/aboutdata/data-variables/#base">https://ameriflux.lbl.gov/data/aboutdata/data-variables/#base</a> for a list of variable names. If not specified, it returns all variables.
nonfilled_only	Logical, whether only showing non-filled variables, or both non- and gap-filled variables. The default is TRUE.
show_cluster	Logical, whether showing clustering (dendrogram) of site-variables. The default is FALSE.
scale	Logical, whether the values should be centered and scaled among site-variables. The default is FALSE.

**Value**

An object of class 'plotly' from [heatmaply](#)

**See Also**

[amf\\_summarize\\_data](#), [heatmaply](#)

**Examples**

```
## Not run:
# plot data summary for selected variables at two sites
amf_plot_datasummary(site_set = c("US-CRT", "US-WPT"),
                     var_set = c("H", "LE", "NETRAD"))

# plot data summary for FCH4 at all sites, and show
# clustering among sites
amf_plot_datasummary(var_set = "FCH4",
                     show_cluster = TRUE)

# plot data summary for TA at all grassland sites,
# and show clustering among sites
sites <- amf_site_info()
sites <- subset(sites, IGBP == "CRO")
amf_plot_datasummary(site_set = sites$SITE_ID,
                     var_set = "TA",
                     show_cluster = TRUE)
```



```
# normalize TA among sites
amf_plot_datasummary(site_set = sites$SITE_ID,
                     var_set = "TA",
                     show_cluster = TRUE,
                     scale = TRUE)

## End(Not run)
```

---

amf\_plot\_datayear      *Plot data availability*

---

## Description

This function visualizes the BASE data availability for selected AmeriFlux sites, variables, and years. This is a wrapper around [amf\\_list\\_data](#). However, it is strongly advised to subset the sites, variables, and/or years for faster processing and better visualization.

## Usage

```
amf_plot_datayear(
  data_aval = NULL,
  site_set = NULL,
  var_set = NULL,
  nonfilled_only = TRUE,
  year_set = NULL
)
```

## Arguments

data_aval	<p>A data frame with at least five columns:</p> <ul style="list-style-type: none"> <li>• SITE_ID:</li> <li>• VARIABLE:</li> <li>• BASENAME: variable basename</li> <li>• GAP_FILLED</li> <li>• Y1990: Percentage of data availability in the year 1990 (0-1).</li> <li>• ...</li> </ul> <p>If not specified, use <a href="#">amf_list_data</a> by default.</p>
site_set	<p>A scalar or vector of character specifying the target AmeriFlux Site ID (CC-Sss). If not specified, it returns all sites.</p>
var_set	<p>A scalar or vector of character specifying the target variables as in basename. See AmeriFlux page <a href="https://ameriflux.lbl.gov/data/aboutdata/data-variables/#base">https://ameriflux.lbl.gov/data/aboutdata/data-variables/#base</a> for a list of variable names. If not specified, it returns all variables.</p>
nonfilled_only	<p>Logical, whether only showing non-filled variables, or both non- and gap-filled variables. The default is TRUE.</p>
year_set	<p>A scalar or vector of integers. If not specified, it plots only years with any available data in selected sites and variables</p>

**Value**

An object of class 'plotly' from [heatmaply](#)

**See Also**

[amf\\_list\\_data](#), [heatmaply](#)

**Examples**

```
## Not run:
# plot data availability for all variables at a single site
# in all years
amf_plot_datayear(site_set = "US-CRT",
                  nonfilled_only = FALSE)

# plot data availability for non-filled FCH4 and WTD at all
# sites in all years
amf_plot_datayear(var_set = c("FCH4", "WTD"),
                  nonfilled_only = TRUE)

# plot data availability for non-filled FCH4 at all sites
# in 2018-2020
amf_plot_datayear(var_set = "FCH4",
                  year_set = c(2018:2020),
                  nonfilled_only = TRUE)

## End(Not run)
```

---

amf\_read\_base

*Read AmeriFlux BASE data product*


---

**Description**

This function read in the BASE data file downloaded from AmeriFlux. See AmeriFlux web page <https://ameriflux.lbl.gov/data/data-processing-pipelines/base-publish/> for details about BASE data product. Use [amf\\_variables](#) to get a list of standard variable names and units.

**Usage**

```
amf_read_base(file, unzip = TRUE, parse_timestamp = FALSE)
```

**Arguments**

file	A BASE data file, either in a zipped file or a comma-separated value (csv) file
unzip	Logical, whether to unzip. The default is TRUE. Set FALSE if reading from a previously unzipped csv file.
parse_timestamp	Logical, whether to parse the time stamp. Set TRUE to parse and add timekeeping columns.

**Value**

A data frame containing data. See AmeriFlux website <https://ameriflux.lbl.gov/data/aboutdata/data-variables/> for details about file format, variable definition, units, and convention. If `parse_timestamp = TRUE`, the following six time-keeping columns are added in the returned data frame:

- YEAR - Year (YYYY)
- MONTH - Month (MM)
- DAY - Day of the month (DD)
- DOY - Day of the year (DDD)
- HOUR - Hour of the day (HH), based on the middle time of the interval
- MINUTE - Minute of the hour (mm), based on the middle time of the interval
- TIMESTAMP - An object of class "POSIXlt" in the UTC time zone, based on the middle time of the interval

**See Also**

[amf\\_parse\\_basename](#), [amf\\_filter\\_base](#)

**Examples**

```
# read the BASE from a zip file, using the example data file
base <- amf_read_base(file = system.file("extdata",
                                         "AMF_US-CRT_BASE-BADM_2-5.zip",
                                         package = "amerifluxr"),
                    unzip = TRUE,
                    parse_timestamp = TRUE)

# read the BASE from a csv file
base <- amf_read_base(file = system.file("extdata",
                                         "AMF_US-CRT_BASE_HH_2-5.csv",
                                         package = "amerifluxr"),
                    unzip = FALSE,
                    parse_timestamp = FALSE)
```

---

amf\_read\_bif

*Read AmeriFlux BADM data product*

---

**Description**

This function read in the BADM data file formatted in BADM Interchange Format (BIF).

**Usage**

```
amf_read_bif(file)
```

**Arguments**

file                    A BADM data file

**Value**

A data frame containing the following 5 columns. See AmeriFlux website <https://ameriflux.lbl.gov/data/aboutdata/badm-data-product/> for details.

- SITE\_ID - Six character site identifier (CC-Sss)
- GROUP\_ID - A unique identifier for data belonging to the same instance of a reported variable group
- VARIABLE\_GROUP - A set of variables that are reported together
- VARIABLE - The variable name
- DATAVALUE - The reported value of a variable

**Examples**

```
# read the BADM BIF file, using an example data file
bif <- amf_read_bif(file = system.file("extdata",
                                       "AMF_AA-Flx_BIF_CCBY4_20201218.xlsx",
                                       package = "amerifluxr"))
```

---

amf\_sites

*Lists AmeriFlux sites*

---

**Description**

Lists available site (names) and basic meta-data

**Usage**

```
amf_sites()
```

**Value**

A data frame containing the following columns. See AmeriFlux BADM standard <https://ameriflux.lbl.gov/data/badm/> for detailed explanation.

- SITE\_ID - Six character site identifier (CC-Sss)
- SITE\_NAME - Site name (free text)
- COUNTRY - Country (free text)
- STATE - State (free text)
- IGBP - Vegetation type based on the IGBP definition (character)
- URL\_AMERIFLUX - Site web site URL, maintained by AmeriFlux (URL)
- TOWER\_BEGAN - The starting year of flux measurement (YYYY)

- TOWER\_END - The ending year of flux measurement (YYYY), NA if still active or unspecified
- LOCATION\_LAT - Latitude of the site (decimal deg ref WGS84)
- LOCATION\_LONG - Longitude of the site (decimal deg ref WGS84)
- LOCATION\_ELEV - Elevation of the site above sea level (m)
- CLIMATE\_KOEPPEL - Koppen climate classification (character)
- MAT - Long-term mean annual average air temperature (degree C)
- MAP - Long-term mean annual average precipitation (mm)
- DATA\_POLICY - LEGACY / CCBY4.0 (character)

### Examples

```
## Not run:  
# download a list of sites and basic info  
sites <- amf_sites()  
  
## End(Not run)
```

---

amf\_site\_info

*Get AmeriFlux site general info*

---

### Description

This function obtains the latest AmeriFlux site list and sites' general info through the AmeriFlux web service.

### Usage

```
amf_site_info()
```

### Details

This combines the information of various other functions.

### Value

A data frame containing the following columns. See AmeriFlux BADM standard <https://ameriflux.lbl.gov/data/badm/> for detailed explanation.

- SITE\_ID - Six character site identifier (CC-Sss)
- SITE\_NAME - Site name (free text)
- COUNTRY - Country (free text)
- STATE - State (free text)

- IGBP - Vegetation type based on the IGBP definition (character)
- URL\_AMERIFLUX - Site web site URL, maintained by AmeriFlux (URL)
- TOWER\_BEGAN - The starting year of flux measurement (YYYY)
- TOWER\_END - The ending year of flux measurement (YYYY), NA if still active or unspecified
- LOCATION\_LAT - Latitude of the site (decimal deg ref WGS84)
- LOCATION\_LONG - Longitude of the site (decimal deg ref WGS84)
- LOCATION\_ELEV - Elevation of the site above sea level (m)
- CLIMATE\_KOEPPE - Koppen climate classification (character)
- MAT - Long-term mean annual average air temperature (degree C)
- MAP - Long-term mean annual average precipitation (mm)
- DATA\_POLICY - LEGACY / CCBY4.0 (character)
- DATA\_START - The starting year with published AmeriFlux BASE data (YYYY)
- DATA\_END - The ending year with published AmeriFlux BASE data (YYYY)

### Examples

```
## Not run:
# obtain the basic general info for all sites
site <- amf_site_info()

## End(Not run)

## End(Not run)
```

---

```
amf_summarize_data      Get BASE data summary
```

---

### Description

This function obtains the BASE data summary for all or selected AmeriFlux sites. See AmeriFlux page <https://ameriflux.lbl.gov/data/aboutdata/data-variables/> for details about the variable naming.

### Usage

```
amf_summarize_data(site_set = NULL, var_set = NULL)
```

### Arguments

site_set	A scalar or vector of character specifying the target AmeriFlux Site ID (CC-Sss). If not specified, it returns all sites.
var_set	A scalar or vector of character specifying the target variables as in basename. See AmeriFlux page <a href="https://ameriflux.lbl.gov/data/aboutdata/data-variables/#base">https://ameriflux.lbl.gov/data/aboutdata/data-variables/#base</a> for a list of variable names. If not specified, it returns all variables.

**Value**

A data frame of site-specific variable summary statistics (selected percentiles) for selected AmeriFlux sites.

- Site\_ID - Six character site identifier (CC-Sss)
- VARIABLE - Variable name of the data included in the BASE file
- BASENAME - Variable base name of the data included in the BASE file.
- GAP\_FILLED - Whether a variable is a gap-filled variable (TRUE/FALSE)
- DATA\_RECORD - Number of supposed data record (counts)
- DATA\_MISSING - Number of missing data record (counts)
- Q01 - 1th percentile of the data
- Q05 - 5th percentile of the data
- ...
- Q95 - 95th percentile of the data
- Q99 - 99th percentile of the data

**Examples**

```
## Not run:
# obtain the data variable availability for all sites & variables
data_sum <- amf_summarize_data()

# obtain the data variable availability for selected sites, all variables
data_sum <- amf_summarize_data(site_set = c("US-CRT", "US-WPT"))

# obtain the data variable availability for selected sites & variables
data_sum <- amf_summarize_data(site_set = c("US-CRT", "US-WPT"),
                              var_set = c("FC", "LE", "H"))

## End(Not run)
```

---

amf\_variables

*Get FP (Flux-Processing) Standard Variable List*


---

**Description**

This function obtains the latest AmeriFlux FP (Flux-Processing) standard variable list. FP standard defines the variable names and units used for continuously sampled data within the AmeriFlux. Also see AmeriFlux Data Variables page <https://ameriflux.lbl.gov/data/aboutdata/data-variables/> for details.

**Usage**

```
amf_variables()
```

**Value**

A data frame containing the following columns:

- Name - Standard variable name
- Description - Description of the variable
- Units - Standard variable unit
- Min - Expected minimal value
- Max - Expected maximal value

**Examples**

```
## Not run:
# download the list of standard variable names and units
FP_ls <- amf_variables()

## End(Not run)
```

---

amf_var_info	<i>Get variable information</i>
--------------	---------------------------------

---

**Description**

This function obtains the measurement height metadata for the AmeriFlux BASE data product. See AmeriFlux page <https://ameriflux.lbl.gov/data/measurement-height/> for details.

**Usage**

```
amf_var_info(out_dir = tempdir(), verbose = TRUE)
```

**Arguments**

out_dir	The output directory (default = tempdir())
verbose	Logical, whether to show download progress (TRUE/FALSE)

**Value**

A data frame of measurement height data for all AmeriFlux sites #'

- Site\_ID - Six character site identifier (CC-Sss)
- Variable - Variable name of the data included in the BASE file
- Start\_Date - Date when the information first applies
- Height - Distance above the ground surface in meters
- Instrument\_Model - Instrument model used to collect the data variable
- Instrument\_Model2 - A second instrument model used to collect the data variable
- Comment - Additional information provided by the site team
- BASE\_Version - The most recent BASE data product version number for which the information applies



**Examples**

```
## Not run:  
# download the measurement height data for all sites  
var_info <- amf_var_info()  
  
## End(Not run)
```

# Index

## \* datasets

amf\_base, [2](#)

amf\_bif, [4](#)

amf\_base, [2](#)

amf\_bif, [4](#)

amf\_check\_site\_id, [4](#)

amf\_data\_coverage, [5](#)

amf\_download\_base, [6](#), [9](#)

amf\_download\_bif, [7](#)

amf\_extract\_badm, [9](#)

amf\_filter\_base, [10](#), [19](#)

amf\_list\_data, [12](#), [17](#), [18](#)

amf\_list\_metadata, [13](#)

amf\_parse\_basename, [11](#), [14](#), [19](#)

amf\_plot\_datasummary, [15](#)

amf\_plot\_datayear, [17](#)

amf\_read\_base, [11](#), [18](#)

amf\_read\_bif, [9](#), [10](#), [19](#)

amf\_site\_info, [21](#)

amf\_sites, [20](#)

amf\_summarize\_data, [15](#), [16](#), [22](#)

amf\_var\_info, [24](#)

amf\_variables, [11](#), [14](#), [15](#), [18](#), [23](#)

heatmaply, [16](#), [18](#)