

Package ‘antaresEditObject’

March 10, 2023

Type Package

Title Edit an 'Antares' Simulation

Version 0.5.0

Description Edit an 'Antares' simulation before running it : create new areas, links, thermal clusters or binding constraints or edit existing ones. Update 'Antares' general & optimization settings.

'Antares' is an open source power system generator, more information available here : [<https://antares-simulator.org/>](https://antares-simulator.org/).

License GPL (>= 2) | file LICENSE

URL <https://github.com/rte-antares-rpackage/antaresEditObject>

BugReports <https://github.com/rte-antares-rpackage/antaresEditObject/issues>

Encoding UTF-8

RoxygenNote 7.2.2

Depends antaresRead (>= 2.4.2)

Imports assertthat, cli, data.table, httr, grDevices, jsonlite, whisker, doParallel, doFuture, memuse, progressr, pbapply, parallel, future, plyr, yaml

Suggests testthat, covr, knitr, rmarkdown

VignetteBuilder knitr

NeedsCompilation no

Author Veronique Bachelier [aut, cre],

Frederic Breant [aut],

Victor Perrier [aut],

Baptiste Seguinot [ctb],

Benoit Thieurmél [ctb],

Titouan Robert [ctb],

Jalal-Edine Zawam [ctb],

Etienne Sanchez [ctb],

Janus De Bondt [ctb],

Assil Mansouri [ctb],

RTE [cph]

Maintainer Veronique Bachelier <veronique.bachelier@rte-france.com>

Repository CRAN

Date/Publication 2023-03-10 22:00:05 UTC

R topics documented:

activateRES	3
adequacyOptions	4
backupStudy	4
check-version	5
checkRemovedArea	6
cleanUpOutput	6
computeOtherFromHourlyMulti	7
computeOtherFromHourlyYear	8
computeTimeStampFromHourly	9
convertConfigToAdq	10
copyOutput	10
create-binding-constraint	11
create-cluster	13
create-study	16
createArea	17
createDistrict	19
createDSR	20
createLink	21
createPSP	23
dicoGeneralSettings	25
dicoOptimizationSettings	26
edit-cluster	27
editArea	28
editBindingConstraint	30
editLink	31
filteringOptions	33
getJobLogs	33
getJobs	34
mockSimulationAPI	35
nodalOptimizationOptions	35
playlist	36
propertiesLinkOptions	37
remove-cluster	38
removeArea	40
removeBindingConstraint	40
removeLink	41
runSimulation	42
runTsGenerator	43
scenario-builder	44
searchStudy	46
setAPImode	47

activateRES 3

setSolverPath	48
updateAdequacySettings	49
updateGeneralSettings	50
updateInputSettings	53
updateOptimizationSettings	53
updateOutputSettings	55
variant	56
variant-commands	57
write-ini	58
writeEconomicOptions	59
writeInputTS	60
writeMiscGen	61
writeOutputValues	62
writeSeriesPrepro	62
writeWaterValues	64

Index 65

activateRES *Activate RES in an Antares study*

Description

Helper to activate Renewables Energy Sources. This will update `renewable.generation.modelling` parameter and create appropriate structure for RES clusters.

Usage

```
activateRES(opts = antaresRead::simOptions(), quietly = !interactive())
```

Arguments

<code>opts</code>	List of simulation parameters returned by the function <code>antaresRead::setSimulationPath</code>
<code>quietly</code>	Display or not a message to the user if success.

Value

An updated list containing various information about the simulation.

Examples

```
## Not run:  
  
library(antaresEditObject)  
tmp <- tempfile()  
createStudy(path = tmp)  
opts <- antaresRead::setSimulationPath(tmp)  
activateRES()
```

```
# then you can use createClusterRES()...

## End(Not run)
```

adequacyOptions *Adequacy patch parameters for creating an area*

Description

Adequacy patch parameters for creating an area

Usage

```
adequacyOptions(adequacy_patch_mode = "outside")
```

Arguments

```
adequacy_patch_mode
    character, default to "outside"
```

Value

a named list

Examples

```
adequacyOptions()
```

backupStudy *Create a backup with an Antares Study*

Description

Antares API: **NO**
 Save an Antares Study or only inputs in a .tar.gz file

Usage

```
backupStudy(
  backupfile,
  what = c("input", "study"),
  opts = antaresRead::simOptions()
)
```

Arguments

backupfile	Name of the backup, without extension. If missing, either the name of the study or 'input' according argument what.
what	Which folder to save, input for the input folder or study for the whole study.
opts	List of simulation parameters returned by the function <code>antaresRead::setSimulationPath</code>

Value

The path of the backup

Examples

```
## Not run:
backupStudy()

## End(Not run)
```

check-version	<i>Is study an Antares v7 study ?</i>
---------------	---------------------------------------

Description

Is study an Antares v7 study ?

Usage

```
is_antares_v7(opts = antaresRead::simOptions())

is_antares_v820(opts = antaresRead::simOptions())
```

Arguments

opts	List of simulation parameters returned by the function <code>antaresRead::setSimulationPath()</code>
------	--

Value

a logical, TRUE if study is v7 or above, FALSE otherwise.

Examples

```
## Not run:
# setSimulationPath

is_antares_v7()

## End(Not run)
```

checkRemovedArea	<i>Seek for a removed area</i>
------------------	--------------------------------

Description

Check if it remains trace of a deleted area in the input folder

Usage

```
checkRemovedArea(area, all_files = TRUE, opts = antaresRead::simOptions())
```

Arguments

area	An area
all_files	Check files in study directory.
opts	List of simulation parameters returned by the function antaresRead::setSimulationPath

Value

a named list with two elements

Examples

```
## Not run:
checkRemovedArea("myarea")

## End(Not run)
```

cleanUpOutput	<i>Clean up output based on geographic trimming</i>
---------------	---

Description

Clean up output based on geographic trimming

Usage

```
cleanUpOutput(areas = NULL, opts = simOptions())
```

Arguments

areas	Character. vector of areas (folders). Links will also be cleaned based on getLinks() results
opts	List. simulation options

`computeOtherFromHourlyMulti`

Compute daily, weekly, monthly and annual mc-ind from hourly data multiyear. (new)

Description

Compute daily, weekly, monthly and annual mc-ind from hourly data multiyear. (new)

Usage

```
computeOtherFromHourlyMulti(  
  opts = simOptions(),  
  areas = "all",  
  type = c("areas", "links", "clusters"),  
  timeStep = c("daily", "monthly", "annual", "weekly"),  
  mcYears = simOptions()$mcYears,  
  writeOutput = F,  
  nbcl = 8,  
  verbose = F  
)
```

Arguments

<code>opts</code>	study opts
<code>areas</code>	vector of areas
<code>type</code>	type of aggregation
<code>timeStep</code>	timestep of aggregation (daily, monthly and annual, NO weekly)
<code>mcYears</code>	vector of years to compute
<code>writeOutput</code>	boolean to write data in mc-ind folder
<code>nbcl</code>	number of cpu cores for parallelization
<code>verbose</code>	logical for printing output

Note

Recommended only with studies spanning on two years.

See Also

[computeOtherFromHourlyYear](#)

computeOtherFromHourlyYear

Compute daily, weekly, monthly and annual mc-ind from hourly data for one year. (new)

Description

Compute daily, weekly, monthly and annual mc-ind from hourly data for one year. (new)

Usage

```
computeOtherFromHourlyYear(  
  mcYear,  
  type,  
  areas = "all",  
  opts = simOptions(),  
  timeStep = c("daily", "monthly", "annual", "weekly"),  
  writeOutput = F  
)
```

Arguments

mcYear	vector of years to compute
type	type of data (areas, links, clusters, clustersRes)
areas	vector of areas. links type will use getLinks() to get data.
opts	study opts
timeStep	timestep of aggregation (daily, monthly and annual, NO weekly)
writeOutput	boolean to write data in mc-ind folder

Note

Recommended only with studies spanning on two years.

See Also

[computeOtherFromHourlyMulti](#)

`computeTimeStampFromHourly`*Compute daily, weekly, monthly and annual mc-ind from hourly data.*

DescriptionAntares API: **NO**

Compute daily, weekly, monthly and annual mc-ind from hourly data.

Usage

```
computeTimeStampFromHourly(  
  opts,  
  mcYears = "all",  
  nbcl = 8,  
  verbose = 1,  
  type = c("areas", "links", "clusters")  
)
```

Arguments

<code>opts</code>	opts simulation path.
<code>mcYears</code>	mcYears to compute.
<code>nbcl</code>	number of thread for parallel computing.
<code>verbose</code>	verbose for execution.
<code>type</code>	type of file to compute.

Note

Deprecated on studies v8 or higher.

Examples

```
## Not run:  
  
library(antaresEditObject)  
opts <- setSimulationPath("my_study")  
computeTimeStampFromHourly(opts)  
  
## End(Not run)
```

convertConfigToAdq *Read adequacy patch config.yml into Antares (v8.5+)*

Description

Use this function to load config.yml used in older Antares versions for adequacy patch. Areas in config will be updated to be included in adequacy patch perimeter.

Usage

```
convertConfigToAdq(opts = simOptions(), path = "default")
```

Arguments

opts	List. study options.
path	Character. path to config.yml. Default points to "/user/adequacypatch/" in study

See Also

[updateAdequacySettings](#)

copyOutput *Copy of the output files of an Antares study*

Description

Antares API: **NO**

Copy of the output files of an Antares study.

Usage

```
copyOutput(opts, extname, mcYears = "all")
```

Arguments

opts	List of simulation parameters returned by the function <code>antaresRead::setSimulationPath</code>
extname	Extension to be added to the name of the study, to be used as a name for the newly created folder.
mcYears	mcYears to copy. Can be "all".

Examples

```
## Not run:

library(antaresRead)

# Set simulation path
opts = setSimulationPath(path = "PATH/TO/SIMULATION", simulation = "input")

# Create a new area
copyOutput(opts, "_adq")

## End(Not run)
```

```
create-binding-constraint
      Create a binding constraint
```

Description

Antares API: **OK**

Create a new binding constraint in an Antares study. `createBindingConstraintBulk()` allow to create multiple constraints at once.

Usage

```
createBindingConstraint(
  name,
  id = tolower(name),
  values = NULL,
  enabled = TRUE,
  timeStep = c("hourly", "daily", "weekly"),
  operator = c("both", "equal", "greater", "less"),
  filter_year_by_year = "hourly, daily, weekly, monthly, annual",
  filter_synthesis = "hourly, daily, weekly, monthly, annual",
  coefficients = NULL,
  overwrite = FALSE,
  opts = antaresRead::simOptions()
)

createBindingConstraintBulk(constraints, opts = antaresRead::simOptions())
```

Arguments

<code>name</code>	The name for the binding constraint.
<code>id</code>	An id, default is to use the name.

values	Values used by the constraint. It contains one line per time step and three columns "less", "greater" and "equal".
enabled	Logical, is the constraint enabled ?
timeStep	Time step the constraint applies to : hourly, daily or weekly.
operator	Type of constraint: equality, inequality on one side or both sides.
filter_year_by_year	Marginal price granularity for year by year
filter_synthesis	Marginal price granularity for synthesis
coefficients	A named vector containing the coefficients used by the constraint.
overwrite	If the constraint already exist, overwrite the previous value.
opts	List of simulation parameters returned by the function <code>antaresRead::setSimulationPath()</code>
constraints	A list of several named list containing data to create binding constraints. Warning all arguments for creating a binding constraints must be provided, see examples.

Value

An updated list containing various information about the simulation.

See Also

`editBindingConstraint()` to edit existing binding constraints, `removeBindingConstraint()` to remove binding constraints.

Examples

```
## Not run:
createBindingConstraint(
  name = "myconstraint",
  values = matrix(data = rep(0, 8760 * 3), ncol = 3),
  enabled = FALSE,
  timeStep = "hourly",
  operator = "both",
  coefficients = c("fr%myarea" = 1)
)

# Create multiple constraints

# Prepare data for constraints
bindings_constraints <- lapply(
  X = seq_len(100),
  FUN = function(i) {
    # use arguments of createBindingConstraint()
    # all arguments must be provided !
    list(
      name = paste0("constraints", i),
      id = paste0("constraints", i),
```

```

        values = matrix(data = rep(0, 8760 * 3), ncol = 3),
        enabled = FALSE,
        timeStep = "hourly",
        operator = "both",
        coefficients = c("area1%area2" = 1),
        overwrite = TRUE
    )
}
)
# create all constraints
createBindingConstraintBulk(bindings_constraints)

## End(Not run)

```

create-cluster

Create a cluster

Description

Antares API: **OK** (thermal clusters only)

Create a new thermal or RES (renewable energy source) cluster.

Usage

```

createCluster(
  area,
  cluster_name,
  group = "Other",
  ...,
  time_series = NULL,
  prepro_data = NULL,
  prepro_modulation = NULL,
  add_prefix = TRUE,
  overwrite = FALSE,
  opts = antaresRead::simOptions()
)

createClusterRES(
  area,
  cluster_name,
  group = "Other RES 1",
  ...,
  time_series = NULL,
  add_prefix = TRUE,
  overwrite = FALSE,
  opts = antaresRead::simOptions()
)

```

Arguments

area	The area where to create the cluster.
cluster_name	Name for the cluster, it will be prefixed by area name, unless you set <code>add_prefix = FALSE</code> .
group	Group of the cluster, depends on cluster type: <ul style="list-style-type: none"> • thermal cluster, one of: Gas, Hard coal, Lignite, Mixed fuel, Nuclear, Oil, Other, Other 2, Other 3, Other 4. • renewable cluster, one of: Wind Onshore, Wind Offshore, Solar Thermal, Solar PV, Solar Rooftop, Other RES 1, Other RES 2, Other RES 3, Other RES 4.
...	Parameters to write in the Ini file. Careful! Some parameters must be set as integers to avoid warnings in Antares, for example, to set <code>unitcount</code> , you'll have to use <code>unitcount = 1L</code> .
time_series	the "ready-made" 8760-hour time-series available for simulation purposes.
prepro_data	Pre-process data, a data.frame or matrix, default is a matrix with 365 rows and 6 columns.
prepro_modulation	Pre-process modulation, a data.frame or matrix, if specified, must have 8760 rows and 1 or 4 columns.
add_prefix	If TRUE (the default), <code>cluster_name</code> will be prefixed by area name.
overwrite	Logical, overwrite the cluster or not.
opts	List of simulation parameters returned by the function <code>antaresRead::setSimulationPath()</code>

Value

An updated list containing various information about the simulation.

See Also

`editCluster()` or `editClusterRES()` to edit existing clusters, `removeCluster()` or `removeClusterRES()` to remove clusters.

Examples

```
## Not run:

library(antaresRead)
library(antaresEditObject)

# Create a cluster :
createCluster(
  area = "fr",
  cluster_name = "my_cluster",
  group = "other",
  unitcount = 1L, # or as.integer(1)
  marginal_cost = 50
)
```

```

# by default, cluster name is prefixed
# by the area name
levels(readClusterDesc())$cluster
# > "fr_my_cluster"

# To prevent this, use `add_prefix`
createCluster(
  area = "fr",
  cluster_name = "my_cluster",
  add_prefix = FALSE,
  group = "other",
  marginal_cost = 50
)
levels(readClusterDesc())$cluster
# > "my_cluster"

# Create a RES cluster :
createClusterRES(
  area = "fr",
  cluster_name = "my_cluster_res",
  group = "other",
  unitcount = 1L, # or as.integer(1)
  nominalcapacity = 50,
  ts_interpretation = "power-generation"
)

# You can also specify that the Time-Series of the RES cluster are
# production factors :
createClusterRES(
  area = "fr",
  cluster_name = "my_cluster_res",
  group = "other",
  unitcount = 1L, # or as.integer(1)
  nominalcapacity = 50,
  ts_interpretation = "production-factor"
)

# Pre-process data :

# this is the default data :
createCluster(
  area = "fr",
  cluster_name = "my_cluster",
  prepro_data = matrix(
    data = c(rep(1, times = 365 * 2),
             rep(0, times = 365 * 4)),
    ncol = 6
  )
)

# with a data.frame

```

```

createCluster(
  area = "fr",
  cluster_name = "my_cluster",
  prepro_data = data.frame(
    v1 = rep(7, 365), # column name doesn't matter
    v2 = rep(27, 365),
    v3 = rep(0.05, 365),
    v4 = rep(0.12, 365),
    v5 = rep(0, 365),
    v6 = rep(1, 365)
  )
)

# Pre-process modulation :
# this is the default data
createCluster(
  area = "fr",
  cluster_name = "my_cluster",
  prepro_modulation = matrix(
    data = c(rep(1, times = 365 * 24 * 3),
             rep(0, times = 365 * 24 * 1)),
    ncol = 4
  )
)

# with a data.frame
createCluster(
  area = "fr",
  cluster_name = "my_cluster",
  prepro_modulation = data.frame(
    var1 = rep(0, 8760), # column name doesn't matter
    var2 = rep(1, 8760),
    var3 = rep(0, 8760),
    var4 = rep(1, 8760)
  )
)

## End(Not run)

```

 create-study

 Create an empty Antares study

Description

Create study on disk or with AntaREST server through the API.

Usage

```

createStudy(path, study_name = "my_study", antares_version = "8.2.0")

createStudyAPI(
  host,
  token = NULL,
  study_name = "my_study",
  antares_version = "8.2.0",
  ...
)

```

Arguments

path	Path where to create study, it should be an empty directory, if it doesn't exist, it'll be created.
study_name	Name of the study.
antares_version	Antares number version.
host	Host of AntaREST server API.
token	API personal access token.
...	Other query parameters passed to POST request.

Value

Result of `antaresRead::setSimulationPath()` or `setSimulationPathAPI()` accordingly.

Examples

```

## Not run:

createStudy("path/to/simulation")

## End(Not run)

```

createArea	<i>Create an area in an Antares study</i>
------------	---

Description

Antares API: **OK**
 Create a new area in an Antares study.

Usage

```
createArea(
  name,
  color = grDevices::rgb(230, 108, 44, max = 255),
  localization = c(0, 0),
  nodalOptimization = nodalOptimizationOptions(),
  filtering = filteringOptions(),
  adequacy = adequacyOptions(),
  overwrite = FALSE,
  opts = antaresRead::simOptions()
)
```

Arguments

name	Name of the area as a character, without punctuation except - and _.
color	Color of the node
localization	Localization on the map
nodalOptimization	Nodal optimization parameters, see nodalOptimizationOptions() .
filtering	Filtering parameters, see filteringOptions() .
adequacy	Adequacy parameters, see adequacyOptions() .
overwrite	Overwrite the area if already exist.
opts	List of simulation parameters returned by the function antaresRead::setSimulationPath()

Value

An updated list containing various information about the simulation.

See Also

[editArea\(\)](#), [removeArea\(\)](#)

Examples

```
## Not run:

library(antaresRead)

# Set simulation path
setSimulationPath(path = "PATH/TO/SIMULATION", simulation = "input")

# Create a new area
createArea("fictive_area")

## End(Not run)
```

createDistrict	<i>Create a district</i>
----------------	--------------------------

Description

Allows selecting a set of areas so as to bundle them together in a "district".

Usage

```
createDistrict(
  name,
  caption = NULL,
  comments = NULL,
  apply_filter = c("none", "add-all", "remove-all"),
  add_area = NULL,
  remove_area = NULL,
  output = FALSE,
  overwrite = FALSE,
  opts = antaresRead::simOptions()
)
```

Arguments

name	District's name.
caption	Caption for the district.
comments	Comments for the district.
apply_filter	Possible values are add-all to add all areas to the district, remove-all to clear the district, or none (default) to don't apply a filter.
add_area	Character vector of area(s) to add to the district.
remove_area	Character vector of area(s) to remove from the district.
output	Logical, compute the results for the district or not?
overwrite	Logical, should the district be overwritten if already exist?
opts	List of simulation parameters returned by the function antaresRead::setSimulationPath()

Value

An updated list containing various information about the simulation.

Examples

```
## Not run:
createDistrict(
  name = "mydistrict",
  apply_filter = "add-all",
  remove_area = c("fr", "be")
)
```

```
)
## End(Not run)
```

createDSR *Create a Demand Side Response (DSR)*

Description

Antares API: **OK**
 Create a Demand Side Response (DSR)

Usage

```
createDSR(
  areasAndDSRParam = NULL,
  spinning = 2,
  overwrite = FALSE,
  opts = antaresRead::simOptions()
)

getCapacityDSR(area = NULL, opts = antaresRead::simOptions())

editDSR(
  area = NULL,
  unit = NULL,
  nominalCapacity = NULL,
  marginalCost = NULL,
  spinning = NULL,
  opts = antaresRead::simOptions()
)
```

Arguments

areasAndDSRParam	A data.frame with 4 columns area, unit, nominalCapacity, marginalCost and hour. Hour represent the number of activation hours for the DSR per day.
spinning	DSR spinning
overwrite	Overwrite the DSR plant if already exist. This will overwrite the previous area and links.
opts	List of simulation parameters returned by the function antaresRead::setSimulationPath()
area	an area where to edit the DSR
unit	DSR unit number
nominalCapacity	DSR nominalCapacity
marginalCost	DSR marginalCost

Value

An updated list containing various information about the simulation.

getCapacityDSR() returns DSR capacity (unit * nominalCapacity of virtual cluster) of the area

Examples

```
## Not run:

library(antaresEditObject)
path <- pathToYourStudy
opts <- setSimulationPath(path, simulation = "input")

# area, unit, nominalCapacity and marginalCost
dsrData <- data.frame(area = c("a", "b"), unit = c(10,20),
                      nominalCapacity = c(100, 120), marginalCost = c(52, 65), hour = c(3, 7))

createDSR(dsrData)

createDSR(dsrData, spinning = 3, overwrite = TRUE)
getAreas()

## End(Not run)
## Not run:

getCapacityDSR("a")
editDSR("a", unit = 50, nominalCapacity = 8000)
getCapacityDSR("a")

## End(Not run)
## Not run:

getCapacityDSR("a")
editDSR("a", unit = 50, nominalCapacity = 8000, marginalCost = 45, hour = 9)
getCapacityDSR("a")

## End(Not run)
```

createLink

Create a link between two areas

Description

Antares API: **OK**

Create a new link between two areas in an Antares study.

Usage

```

createLink(
  from,
  to,
  propertiesLink = propertiesLinkOptions(),
  dataLink = NULL,
  tsLink = NULL,
  overwrite = FALSE,
  opts = antaresRead::simOptions()
)

```

Arguments

from, to	The two areas linked together.
propertiesLink	a named list containing the link properties, e.g. hurdles-cost or transmission-capacities for example. See propertiesLinkOptions() .
dataLink	See Details section below.
tsLink	Transmission capacities time series. First N columns are direct TS, following N are indirect ones.
overwrite	Logical, overwrite the previous between the two areas if exist
opts	List of simulation parameters returned by the function antaresRead::setSimulationPath()

Details

The eight potential times-series are:

- **NTC direct** : the upstream-to-downstream capacity, in MW. Default to 1.
- **NTC indirect** : the downstream-to-upstream capacity, in MW. Default to 1.
- **Hurdle cost direct** : an upstream-to-downstream transmission fee, in euro/MWh. Default to 0.
- **Hurdle cost indirect** : a downstream-to-upstream transmission fee, in euro/MWh. Default to 0.
- **Impedances** : virtual impedances that are used in economy simulations to give a physical meaning to raw outputs, when no binding constraints have been defined to enforce Kirchhoff's laws. Default to 0.
- **Loop flow** : amount of power flowing circularly though the grid when all "nodes" are perfectly balanced (no import and no export). Default to 0.
- **PST min** : lower bound of phase-shifting that can be reached by a PST installed on the link, if any. Default to 0.
- **PST max** : upper bound of phase-shifting that can be reached by a PST installed on the link, if any. Default to 0.

According to Antares version, usage may vary :

< **v7.0.0** : 5 first columns are used in the following order: NTC direct, NTC indirect, Impedances, Hurdle cost direct, Hurdle cost indirect.

>= **v7.0.0** : 8 columns in order above are expected.

>= **v8.2.0** : there's 2 cases :

- 8 columns are provided: 2 first are used in tsLink, other 6 are used for link data
- 6 columns are provided: you must provide NTC data in tsLink argument.

Value

An updated list containing various information about the simulation.

Note

In Antares, areas are sorted in alphabetical order to establish links between. For example, link between "fr" and "be" will appear under "be". So the areas are sorted before creating the link between them, and dataLink is rearranged to match the new order.

See Also

[editLink\(\)](#), [removeLink\(\)](#)

Examples

```
## Not run:  
  
library(antaresRead)  
  
# Set simulation path  
setSimulationPath(path = "PATH/TO/SIMULATION", simulation = "input")  
  
# Create a link between two areas  
createLink(from = "first_area", to = "second_area")  
  
## End(Not run)
```

createPSP

Create a Pumped Storage Power plant (PSP)

Description

Antares API: **OK**

Create a Pumped Storage Power plant (PSP)

Usage

```

createPSP(
  areasAndCapacities = NULL,
  namePumping = "Psp_In",
  nameTurbinning = "Psp_Out",
  hurdleCost = 5e-04,
  timeStepBindConstraint = "weekly",
  efficiency = NULL,
  overwrite = FALSE,
  opts = antaresRead::simOptions()
)

getCapacityPSP(
  area = NULL,
  nameTurbinning = "Psp_Out",
  timeStepBindConstraint = "weekly",
  opts = antaresRead::simOptions()
)

editPSP(
  area = NULL,
  capacity = NULL,
  namePumping = "Psp_In",
  nameTurbinning = "Psp_Out",
  timeStepBindConstraint = "weekly",
  hurdleCost = 5e-04,
  opts = antaresRead::simOptions()
)

```

Arguments

<code>areasAndCapacities</code>	A data.frame with 2 columns <code>installedCapacity</code> and <code>area</code> .
<code>namePumping</code>	The name of the pumping area
<code>nameTurbinning</code>	The name of the turbinning area
<code>hurdleCost</code>	The cost of the PSP
<code>timeStepBindConstraint</code>	Time step for the binding constraint : daily or weekly
<code>efficiency</code>	The efficiency of the PSP
<code>overwrite</code>	Overwrite the Pumped Storage Power plant if already exist. This will overwrite the previous area and links.
<code>opts</code>	List of simulation parameters returned by the function antaresRead::setSimulationPath()
<code>area</code>	an area name
<code>capacity</code>	PSP capacity for the area

Value

An updated list containing various information about the simulation.

getCapacityPSP() returns PSP capacity of the area

Examples

```
## Not run:

library(antaresEditObject)
path<-pathToYourStudy
opts<-setSimulationPath(path, simulation = "input")
pspData<-data.frame(area=c("a", "b"), installedCapacity=c(800,900))

createPSP(pspData, efficiency = 0.8)

createPSP(pspData, efficiency = 0.66, overwrite = TRUE)
createPSP(pspData, efficiency = 0.98, timeStepBindConstraint = "daily")
getAreas()

## End(Not run)

## Not run:

getCapacityPSP("a")
editPSP("a", capacity = 8000, hurdleCost = 0.1)
getCapacityPSP("a")

areaName<-"suisse"
createArea(areaName, overwrite = TRUE)
pspData<-data.frame(area=c(areaName), installedCapacity=c(9856))
createPSP(pspData, efficiency = 0.5, overwrite = TRUE, timeStepBindConstraint = "daily")

getCapacityPSP(areaName, timeStepBindConstraint = "daily")

## End(Not run)
```

dicoGeneralSettings *Correspondence between arguments of updateGeneralSettings and actual Antares parameters.*

Description

Correspondence between arguments of updateGeneralSettings and actual Antares parameters.

Usage

```
dicoGeneralSettings(arg)
```

Arguments

arg An argument from function updateGeneralSettings.

Value

The corresponding Antares general parameter.

Examples

```
dicoGeneralSettings("year.by.year") # "year-by-year"
```

dicoOptimizationSettings
*Correspondence between arguments of
updateOptimizationSettings and actual Antares parameters.*

Description

Correspondence between arguments of updateOptimizationSettings and actual Antares parameters.

Usage

```
dicoOptimizationSettings(arg)
```

Arguments

arg An argument from function updateOptimizationSettings.

Value

The corresponding Antares general parameter.

Examples

```
dicoGeneralSettings("year.by.year") # "year-by-year"
```

edit-cluster	<i>Edit an existing cluster</i>
--------------	---------------------------------

Description

Antares API: **OK** (thermal clusters only)

Edit parameters, pre-process data and time series of an existing cluster, thermal or RES (renewable energy source).

Usage

```
editCluster(
  area,
  cluster_name,
  ...,
  time_series = NULL,
  prepro_data = NULL,
  prepro_modulation = NULL,
  add_prefix = TRUE,
  opts = antaresRead::simOptions()
)
```

```
editClusterRES(
  area,
  cluster_name,
  ...,
  time_series = NULL,
  add_prefix = TRUE,
  opts = antaresRead::simOptions()
)
```

Arguments

area	The area where to create the cluster.
cluster_name	Name for the cluster, it will prefixed by area name, unless you set add_prefix = FALSE.
...	Parameters to write in the Ini file. Careful! Some parameters must be set as integers to avoid warnings in Antares, for example, to set unitcount, you'll have to use unitcount = 1L.
time_series	the "ready-made" 8760-hour time-series available for simulation purposes.
prepro_data	Pre-process data, a data.frame or matrix, default is a matrix with 365 rows and 6 columns.
prepro_modulation	Pre-process modulation, a data.frame or matrix, if specified, must have 8760 rows and 1 or 4 columns.

add_prefix If TRUE (the default), cluster_name will be prefixed by area name.
 opts List of simulation parameters returned by the function `antaresRead::setSimulationPath()`

Value

An updated list containing various information about the simulation.

See Also

`createCluster()` or `createClusterRES()` to create new clusters, `removeCluster()` or `removeClusterRES()` to remove clusters.

Examples

```
## Not run:

# Update only nominalCapacity for an existing cluster
editCluster(
  area = "myarea",
  cluster_name = "mycluster",
  nominalcapacity = 10600.000
)

## End(Not run)
```

editArea

Edit an area in an Antares study

Description

Antares API: **OK**

Edit an existing area in an Antares study.

Usage

```
editArea(
  name,
  color = NULL,
  localization = NULL,
  nodalOptimization = NULL,
  filtering = NULL,
  adequacy = NULL,
  opts = antaresRead::simOptions()
)
```

Arguments

name	Name of the area as a character, without punctuation except - and _.
color	Color of the node
localization	Localization on the map
nodalOptimization	Nodal optimization parameters, see nodalOptimizationOptions() .
filtering	Filtering parameters, see filteringOptions() .
adequacy	Adequacy parameters, see adequacyOptions() .
opts	List of simulation parameters returned by the function antaresRead::setSimulationPath()

Value

An updated list containing various information about the simulation.

See Also

[createArea\(\)](#), [removeArea\(\)](#)

Examples

```
## Not run:

library(antaresRead)

# Set simulation path
setSimulationPath(path = "PATH/TO/SIMULATION", simulation = "input")

# Edit an existing area
editArea("area", color = grDevices::rgb(230, 108, 44, max = 255),
        localization = c(1, 1),
        opts = antaresRead::simOptions())

editArea("de", nodalOptimization = list("spilledenergycost" = list(fr = 30)),
        opts = antaresRead::simOptions())

editArea("de", nodalOptimization = nodalOptimizationOptions(),
        opts = antaresRead::simOptions())

## End(Not run)
```

editBindingConstraint *Update an existing binding constraint*

Description

Antares API: **OK**

Update an existing binding constraint in an Antares study.

Usage

```
editBindingConstraint(
  name,
  id = tolower(name),
  values = NULL,
  enabled = NULL,
  timeStep = NULL,
  operator = NULL,
  filter_year_by_year = NULL,
  filter_synthesis = NULL,
  coefficients = NULL,
  opts = antaresRead::simOptions()
)
```

Arguments

name	The name for the binding constraint.
id	An id, default is to use the name.
values	Values used by the constraint. It contains one line per time step and three columns "less", "greater" and "equal".
enabled	Logical, is the constraint enabled ?
timeStep	Time step the constraint applies to : hourly, daily or weekly.
operator	Type of constraint: equality, inequality on one side or both sides.
filter_year_by_year	Marginal price granularity for year by year
filter_synthesis	Marginal price granularity for synthesis
coefficients	A named vector containing the coefficients used by the constraint.
opts	List of simulation parameters returned by the function antaresRead::setSimulationPath()

Value

An updated list containing various information about the simulation.

See Also

[createBindingConstraint\(\)](#) to create new binding constraints, [removeBindingConstraint\(\)](#) to remove binding constraints.

Examples

```
## Not run:
editBindingConstraint(
  name = "myconstraint",
  values = matrix(data = rep(0, 8760 * 3), ncol = 3),
  enabled = FALSE,
  timeStep = "hourly",
  operator = "both",
  coefficients = c("fr%de" = 1)
)

## End(Not run)
```

editLink

Edit a link between two areas

Description

Antares API: **OK**

Edit a link between two areas in an Antares study.

Usage

```
editLink(
  from,
  to,
  hurdles_cost = NULL,
  transmission_capacities = NULL,
  asset_type = NULL,
  display_comments = NULL,
  filter_synthesis = NULL,
  filter_year_by_year = NULL,
  dataLink = NULL,
  tsLink = NULL,
  opts = antaresRead::simOptions()
)
```

Arguments

from, to	The two areas linked together.
hurdles_cost	Logical, which is used to state whether (linear) transmission fees should be taken into account or not in economy and adequacy simulations

<code>transmission_capacities</code>	Character, one of <code>enabled</code> , <code>ignore</code> or <code>infinite</code> , which is used to state whether the capacities to consider are those indicated in 8760-hour arrays or if zero or infinite values should be used instead (actual values / set to zero / set to infinite)
<code>asset_type</code>	Character, one of <code>ac</code> , <code>dc</code> , <code>gas</code> , <code>virt</code> or <code>other</code> . Used to state whether the link is either an AC component (subject to Kirchhoff's laws), a DC component, or another type of asset.
<code>display_comments</code>	Logical, display comments or not.
<code>filter_synthesis</code>	Output synthesis.
<code>filter_year_by_year</code>	Output year-by-year.
<code>dataLink</code>	See Details section below.
<code>tsLink</code>	Transmission capacities time series. First N columns are direct TS, following N are indirect ones.
<code>opts</code>	List of simulation parameters returned by the function <code>antaresRead::setSimulationPath()</code>

Value

An updated list containing various information about the simulation.

Note

See `createLink()` for more documentation

See Also

`createLink()`, `removeLink()`

Examples

```
## Not run:
editLink(
  from = "area1",
  to = "area2",
  transmission_capacities = "infinite"
)

## End(Not run)
```

filteringOptions	<i>Output profile options for creating an area</i>
------------------	--

Description

Output profile options for creating an area

Usage

```
filteringOptions(  
  filter_synthesis = c("hourly", "daily", "weekly", "monthly", "annual"),  
  filter_year_by_year = c("hourly", "daily", "weekly", "monthly", "annual")  
)
```

Arguments

filter_synthesis	Output synthesis
filter_year_by_year	Output Year-by-year

Value

a named list

Examples

```
filteringOptions()
```

getJobLogs	<i>Retrieve job log from API</i>
------------	----------------------------------

Description

Retrieve job log from API

Usage

```
getJobLogs(job_id, opts = antaresRead::simOptions())
```

Arguments

job_id	The job identifier.
opts	List of simulation parameters returned by the function antaresRead::setSimulationPath()

Value

Logs as character string.

Examples

```
## Not run:

antaresRead::setSimulationPathAPI(
  host = "http://localhost:8080",
  study_id = "39c604fc-687f-46c4-9fa6-59b57ff9c8d1",
  token = NULL,
  simulation = "input"
)
job <- runSimulation()
getJobLogs(job)

## End(Not run)
```

getJobs

Retrieve API jobs

Description

Retrieve API jobs

Usage

```
getJobs(job_id = NULL, opts = antaresRead::simOptions())
```

Arguments

job_id	The job identifier, if NULL (default), retrieve all jobs.
opts	List of simulation parameters returned by the function antaresRead::setSimulationPath()

Value

A data.table with information about jobs.

Examples

```
## Not run:

getJobs()

## End(Not run)
```

mockSimulationAPI *Mock API usage*

Description

Use this to generate command without an active API connection, it allow to use function to edit a study to later on get API commands.

Usage

```
mockSimulationAPI(force = FALSE, antares_version = "8.2.0")
```

Arguments

force	Logical, force mocking simulation even if antaresRead::setSimulationPathAPI has already been called.
antares_version	Antares version number.

Value

An updated list containing various information about the simulation.

Examples

```
## Not run:  
# Mock simulation API  
mockSimulationAPI()  
# Create an area  
createArea("new area")  
# Get commands  
getVariantCommands()  
  
## End(Not run)
```

nodalOptimizationOptions
Nodal optimization parameters for creating an area

Description

Nodal optimization parameters for creating an area

Usage

```
nodalOptimizationOptions(
  non_dispatchable_power = TRUE,
  dispatchable_hydro_power = TRUE,
  other_dispatchable_power = TRUE,
  spread_unsupplied_energy_cost = 0,
  spread_spilled_energy_cost = 0,
  average_unsupplied_energy_cost = 0,
  average_spilled_energy_cost = 0
)
```

Arguments

```
non_dispatchable_power
    logical, default to FALSE
dispatchable_hydro_power
    logical, default to FALSE
other_dispatchable_power
    logical, default to FALSE
spread_unsupplied_energy_cost
    numeric, default to 0
spread_spilled_energy_cost
    numeric, default to 0
average_unsupplied_energy_cost
    numeric, default to 0
average_spilled_energy_cost
    numeric, default to 0
```

Value

a named list

Examples

```
nodalOptimizationOptions()
```

playlist

Get the playlist of an Antares study **Antares API: OK**

Description

`getPlaylist` gives the identifier of the MC years which will be simulated in the Antares study, taking into account the potential use of a playlist which can skip some MC years

`setPlaylist` is a function which modifies the input file of an ANTARES study and set the playlist in order to simulate only the MC years given in input

Usage

```
getPlaylist(opts = antaresRead::simOptions())

setPlaylist(playlist, weights = NULL, opts = antaresRead::simOptions())
```

Arguments

opts	List of simulation parameters returned by the function <code>antaresRead::setSimulationPath()</code>
playlist	vector of MC years identifier to be simulated can be a list (V8 compatibility) but not recommended
weights	data.table, 2 columns : mcYears and weights. Only with after antares V8

Value

- `getPlaylist` returns a vector of the identifier of the simulated MC year.
- `setPlaylist` does not return anything. It is used to modify the input of an Antares study.

Examples

```
## Not run:
setSimulationPath("PATH/TO/STUDY/")
# or
setSimulationPathAPI(
  host = "http://localhost:8080",
  study_id = "6f98a393-155d-450f-a581-8668dc355235",
  token = NULL,
  simulation = "input"
)

# augment number of MC years
updateGeneralSettings(nbyears = 10)

# Get the actual playlist
getPlaylist()
# [1] 2 4 6

# set a new playlist
setPlaylist(c(3, 5, 7))

## End(Not run)
```

propertiesLinkOptions *Properties for creating a link*

Description

Properties for creating a link

Usage

```
propertiesLinkOptions(
  hurdles_cost = FALSE,
  transmission_capacities = "enabled",
  asset_type = "ac",
  display_comments = TRUE,
  filter_synthesis = c("hourly", "daily", "weekly", "monthly", "annual"),
  filter_year_by_year = c("hourly", "daily", "weekly", "monthly", "annual")
)
```

Arguments

hurdles_cost Logical, which is used to state whether (linear) transmission fees should be taken into account or not in economy and adequacy simulations

transmission_capacities Character, one of enabled, ignore or infinite, which is used to state whether the capacities to consider are those indicated in 8760-hour arrays or if zero or infinite values should be used instead (actual values / set to zero / set to infinite)

asset_type Character, one of ac, dc, gas, virt or other. Used to state whether the link is either an AC component (subject to Kirchhoff's laws), a DC component, or another type of asset.

display_comments Logical, display comments or not.

filter_synthesis Output synthesis.

filter_year_by_year Output year-by-year.

Value

A named list that can be used in `createLink()`.

Examples

```
propertiesLinkOptions(hurdles_cost = TRUE)
```

remove-cluster

Remove a cluster

Description

Antares API: **OK** (thermal clusters only)

Remove a cluster, thermal or RES (renewable energy source), and all its data.

Usage

```

removeCluster(
  area,
  cluster_name,
  add_prefix = TRUE,
  opts = antaresRead::simOptions()
)

removeClusterRES(
  area,
  cluster_name,
  add_prefix = TRUE,
  opts = antaresRead::simOptions()
)

```

Arguments

area	The area where to create the cluster.
cluster_name	Name for the cluster, it will be prefixed by area name, unless you set <code>add_prefix = FALSE</code> .
add_prefix	If TRUE (the default), <code>cluster_name</code> will be prefixed by area name.
opts	List of simulation parameters returned by the function antaresRead::setSimulationPath()

Value

An updated list containing various information about the simulation.

See Also

[createCluster\(\)](#) or [createClusterRES\(\)](#) to create new clusters, [editCluster\(\)](#) or [editClusterRES\(\)](#) to edit existing clusters.

Examples

```

## Not run:
createCluster(
  area = "fr",
  cluster_name = "fr_gas",
  group = "other",
  `marginal-cost` = 50
)

removeCluster(area = "fr", cluster_name = "fr_gas")

## End(Not run)

```

removeArea	<i>Remove an area from an Antares study</i>
------------	---

Description

Antares API: **OK**

Remove an area in an Antares study.

Usage

```
removeArea(name, opts = antaresRead::simOptions())
```

Arguments

name An area name.

opts List of simulation parameters returned by the function [antaresRead::setSimulationPath\(\)](#)

Value

An updated list containing various information about the simulation.

See Also

[createArea\(\)](#), [editArea\(\)](#)

Examples

```
## Not run:  
removeArea("fictive_area")  
  
## End(Not run)
```

removeBindingConstraint	<i>Remove a Binding Constraint</i>
-------------------------	------------------------------------

Description

Antares API: **OK**

Remove a binding constraint in an Antares study.

Usage

```
removeBindingConstraint(name, opts = antaresRead::simOptions())
```


Arguments

name Name(s) of the binding constraint(s) to remove.
 opts List of simulation parameters returned by the function `antaresRead::setSimulationPath()`

Value

An updated list containing various information about the simulation.

See Also

`createBindingConstraint()` to create new binding constraints, `editBindingConstraint()` to edit existing binding constraints.

Examples

```
## Not run:
removeBindingConstraint("mybindingconstraint")

## End(Not run)
```

removeLink	<i>Remove a link between two areas</i>
------------	--

Description

Antares API: **OK**
 Remove a link between two areas in an Antares study.

Usage

```
removeLink(from, to, opts = antaresRead::simOptions())
```

Arguments

from, to The two areas linked together.
 opts List of simulation parameters returned by the function `antaresRead::setSimulationPath()`

Value

An updated list containing various information about the simulation.

Examples

```
## Not run:
createLink(from = "myarea", to = "myarea2")
removeLink(from = "myarea", to = "myarea2")

## End(Not run)
```

runSimulation	<i>Run an Antares Simulation</i>
---------------	----------------------------------

Description

Antares API: **OK**

Run an ANTARES study

Usage

```
runSimulation(
  name,
  mode = "economy",
  path_solver = getOption("antares.solver"),
  wait = TRUE,
  show_output_on_console = FALSE,
  parallel = TRUE,
  ...,
  opts = antaresRead::simOptions()
)
```

Arguments

name	Name of the simulation. In API mode, name will be used as output_suffix argument.
mode	Simulation mode, can take value "economy", "adequacy" or "draft".
path_solver	Character containing the Antares Solver path
wait	Logical, indicating whether the R interpreter should wait for the simulation to finish, or run it asynchronously.
show_output_on_console	Logical, indicating whether to capture the ANTARES log and show it on the R console.
parallel	Logical. If TRUE the ANTARES simulation will be run in parallel mode (Work only with ANTARES v6.0.0 or more). In that case, the number of cores used by the simulation is the one set in advanced_settings/simulation_cores (see ANTARES interface).
...	Additional arguments (API only), such as nb_cpu, time_limit, ... See API documentation for all available options.
opts	List of simulation parameters returned by the function <code>antaresRead::setSimulationPath()</code>

Value

In API mode it return a list with either the job id in case of success of the command or details about the error produce. In non-API mode the function does not return anything, it is used to launch an ANTARES simulation.

runTsGenerator	<i>Run Time-Series Generator</i>
----------------	----------------------------------

Description

Antares API: **NO**

Usage

```
runTsGenerator(  
  path_solver = getOption("antares.solver"),  
  wait = TRUE,  
  show_output_on_console = FALSE,  
  opts = antaresRead::simOptions()  
)
```

Arguments

path_solver	Character containing the Antares Solver path.
wait	Logical, indicating whether the R interpreter should wait for the simulation to finish, or run it asynchronously.
show_output_on_console	Logical, indicating whether to capture the ANTARES log and show it on the R console.
opts	List of simulation parameters returned by the function <code>antaresRead::setSimulationPath</code> .

Examples

```
## Not run:  
library(antaresRead)  
setSimulationPath(path = "path/to/study")  
  
library(antaresEditObject)  
runTsGenerator(  
  path_solver = "path/to/antares-6.0-solver.exe",  
  show_output_on_console = TRUE  
)  
  
## End(Not run)
```

scenario-builder *Read, create & update scenario builder*

Description

Antares API: **OK**

Read, create & update scenario builder.

Usage

```
scenarioBuilder(  
  n_scenario,  
  n_mc = NULL,  
  areas = NULL,  
  areas_rand = NULL,  
  opts = antaresRead::simOptions()  
)
```

```
readScenarioBuilder(  
  ruleset = "Default Ruleset",  
  as_matrix = TRUE,  
  opts = antaresRead::simOptions()  
)
```

```
updateScenarioBuilder(  
  ldata,  
  ruleset = "Default Ruleset",  
  series = NULL,  
  clusters_areas = NULL,  
  links = NULL,  
  opts = antaresRead::simOptions()  
)
```

```
clearScenarioBuilder(  
  ruleset = "Default Ruleset",  
  opts = antaresRead::simOptions()  
)
```

Arguments

n_scenario	Number of scenario.
n_mc	Number of Monte-Carlo years.
areas	Areas to use in scenario builder, if NULL (default) all areas in Antares study are used.
areas_rand	Areas for which to use "rand".

opts	List of simulation parameters returned by the function <code>antaresRead::setSimulationPath()</code>
ruleset	Ruleset to read.
as_matrix	If TRUE (default) return a matrix, else a list.
ldata	A matrix obtained with <code>scenarioBuilder</code> , or a named list of matrices obtained with <code>scenarioBuilder</code> , names must be 'l', 'h', 'w', 's', 't', 'r' or 'ntc', depending on the series to update.
series	Name(s) of the serie(s) to update if <code>ldata</code> is a single matrix.
clusters_areas	A <code>data.table</code> with two columns <code>area</code> and <code>cluster</code> to identify area/cluster couple to update for thermal or renewable series. Default is to read clusters description and update all couples area/cluster.
links	Links to use if series is "ntc". Either a simple vector with links described as "area01%area02 or a <code>data.table</code> with two columns <code>from</code> and <code>to</code> . Default is to read existing links and update them all.

Value

`scenarioBuilder` : a matrix

`readScenarioBuilder` : a list of matrix or list according to `as_matrix` parameters.

Note

`series = "ntc"` is only available with Antares \geq 8.2.0.

Examples

```
## Not run:

library(antaresRead)
library(antaresEditObject)

# simulation path
setSimulationPath(
  path = "pat/to/simulation",
  simulation = "input"
)

# Create a scenario builder matrix
sbuilder <- scenarioBuilder(
  n_scenario = 51,
  n_mc = 2040,
  areas_rand = c("fr", "be")
)
sbuilder[, 1:6]
dim(sbuilder)

# Read previous scenario builder
# in a matrix format
prev_sb <- readScenarioBuilder()
```

```
# Update scenario builder

# for load serie
updateScenarioBuilder(ldata = sbuilder, series = "load")

# equivalent as
updateScenarioBuilder(ldata = list(l = sbuilder))

# update several series

# same input
sbuilder
updateScenarioBuilder(
  ldata = sbuilder,
  series = c("load", "hydro", "solar")
)

# different input
updateScenarioBuilder(ldata = list(
  l = load_sb,
  h = hydro_sb,
  s = solar_sb
))

## End(Not run)
```

searchStudy

Search study in AntaREST

Description

Search study in AntaREST

Usage

```
searchStudy(
  workspace = NULL,
  folder = NULL,
  name = NULL,
  ...,
  host = NULL,
  token = NULL
)
```

Arguments

workspace	Space in which to search for a study.
folder	Folder in which to search for a study.
name	Name for the study.
...	Other query parameters.
host	Host of AntaREST server API.
token	API personal access token.

Value

a `data.table` with informations about studies on the server.

Examples

```
## Not run:

searchStudies(host = "http://localhost:8080")

## End(Not run)
```

setAPImode

Set API mode

Description

Two modes are available when using the API:

- **async**: record all API calls, but nothing is sent to the server
- **sync**: send query to the API each time a function is used

Usage

```
setAPImode(mode = c("sync", "async"), opts = antaresRead::simOptions())
```

Arguments

mode	The mode you want to use.
opts	List of simulation parameters returned by the function antaresRead::setSimulationPath()

Value

An updated list containing various information about the simulation.

Examples

```
## Not run:  
# See vignette for complete documentation  
vignette("api-variant-management")  
  
# Usage :  
setAPImode("sync")  
  
## End(Not run)
```

setSolverPath	<i>Set path to Antares Solver</i>
---------------	-----------------------------------

Description

Set path to Antares Solver

Usage

```
setSolverPath(path)
```

Arguments

path	(optional) Path to the solver (e.g. antares-6.0-solver.exe in \bin directory where Antares is installed). If missing, a window opens and lets the user choose the directory of the simulation interactively.
------	--

Examples

```
## Not run:  
  
setSolverPath(path = "C:/antares/bin/antares-6.0-solver.exe")  
  
## End(Not run)
```

 updateAdequacySettings

Update adequacy parameters of an Antares study

Description

Antares API: **OK**

Update adequacy parameters of an Antares study

Usage

```
updateAdequacySettings(
  include_adq_patch = NULL,
  set_to_null_ntc_from_physical_out_to_physical_in_for_first_step = NULL,
  set_to_null_ntc_between_physical_out_for_first_step = NULL,
  price_taking_order = NULL,
  include_hurdle_cost_csr = NULL,
  check_csr_cost_function = NULL,
  threshold_initiate_curtailment_sharing_rule = NULL,
  threshold_display_local_matching_rule_violations = NULL,
  threshold_csr_variable_bounds_relaxation = NULL,
  opts = antaresRead::simOptions()
)
```

Arguments

include_adq_patch	Logical. If TRUE, will run Adequacy Patch
set_to_null_ntc_from_physical_out_to_physical_in_for_first_step	Logical. default to TRUE
set_to_null_ntc_between_physical_out_for_first_step	Logical. default to TRUE
price_taking_order	Character. can take values DENS (default value) and Load.
include_hurdle_cost_csr	Logical. default to FALSE
check_csr_cost_function	Logical. default to FALSE
threshold_initiate_curtailment_sharing_rule	Double. default to 0.0
threshold_display_local_matching_rule_violations	Double. default to 0.0
threshold_csr_variable_bounds_relaxation	Integer. default to 3
opts	List of simulation parameters returned by the function <code>antaresRead::setSimulationPath()</code>

Value

An updated list containing various information about the simulation.

Examples

```
## Not run:

updateAdequacySettings(
  include_adq_patch = TRUE,
  set_to_null_ntc_from_physical_out_to_physical_in_for_first_step = TRUE,
  set_to_null_ntc_between_physical_out_for_first_step = TRUE
)

## End(Not run)
```

updateGeneralSettings *Update general parameters of an Antares study*

Description

Antares API: **OK**

Update general parameters of an Antares study

Usage

```
updateGeneralSettings(
  mode = NULL,
  horizon = NULL,
  nbyears = NULL,
  simulation.start = NULL,
  simulation.end = NULL,
  january.1st = NULL,
  first.month.in.year = NULL,
  first.weekday = NULL,
  leapyear = NULL,
  year.by.year = NULL,
  derated = NULL,
  custom.ts.numbers = NULL,
  user.playlist = NULL,
  filtering = NULL,
  active.rules.scenario = NULL,
  generate = NULL,
  nbtimeseriesload = NULL,
  nbtimeserieshydro = NULL,
  nbtimeserieswind = NULL,
```

```

nbtimeseriesthermal = NULL,
nbtimeseries solar = NULL,
refreshseries = NULL,
intra.modal = NULL,
inter.modal = NULL,
refreshintervalload = NULL,
refreshintervalhydro = NULL,
refreshintervalwind = NULL,
refreshintervalthermal = NULL,
refreshinterval solar = NULL,
readonly = NULL,
opts = antaresRead::simOptions()
)

```

Arguments

mode	Economy, Adequacy, Draft.
horizon	Reference year (static tag, not used in the calculations)
nbyears	Number of Monte-Carlo years that should be prepared for the simulation (not always the same as the Number of MC years actually simulated, see 'selection mode' below).
simulation.start	First day of the simulation (e.g. 8 for a simulation beginning on the second week of the first month of the year)
simulation.end	Last day of the simulation (e.g. 28 for a simulation ending on the fourth week of the first month of the year)
january.1st	First day of the year (Mon, Tue, etc.).
first.month.in.year	Actual month by which the Time-series begin (Jan to Dec, Oct to Sep, etc.)
first.weekday	In economy or adequacy simulations, indicates the frame (Mon- Sun, Sat-Fri, etc.) to use for the edition of weekly results.
leapyear	(TRUE/FALSE) indicates whether February has 28 or 29 days.
year.by.year	(False) No individual results will be printed out, (True) For each simulated year, detailed results will be printed out in an individual directory7 : Study_name/OUTPUT/simu_tag/Economy/mc-i-number
derated	See Antares General Reference Guide.
custom.ts.numbers	See Antares General Reference Guide.
user.playlist	See Antares General Reference Guide.
filtering	See Antares General Reference Guide.
active.rules.scenario	See Antares General Reference Guide.
generate	See Antares General Reference Guide.
nbtimeseriesload	See Antares General Reference Guide.

nbtimeserieshydro	See Antares General Reference Guide.
nbtimeserieswind	See Antares General Reference Guide.
nbtimeseriesthermal	See Antares General Reference Guide.
nbtimeseriessolar	See Antares General Reference Guide.
refreshtimeseries	See Antares General Reference Guide.
intra.modal	See Antares General Reference Guide.
inter.modal	See Antares General Reference Guide.
refreshintervalload	See Antares General Reference Guide.
refreshintervalhydro	See Antares General Reference Guide.
refreshintervalwind	See Antares General Reference Guide.
refreshintervalthermal	See Antares General Reference Guide.
refreshintervalsolar	See Antares General Reference Guide.
readonly	See Antares General Reference Guide.
opts	List of simulation parameters returned by the function antaresRead::setSimulationPath()

Value

An updated list containing various information about the simulation.

Examples

```
## Not run:

# Update number of Monte-Carlo years
updateGeneralSettings(nbyears = 42)

# Use a vector to update a parameter that
# can take multiple values
updateGeneralSettings(generate = c("thermal", "hydro"))

## End(Not run)
```

updateInputSettings *Update input parameters of an Antares study*

Description

Antares API: **OK**

Update input parameters of an Antares study

Usage

```
updateInputSettings(import, opts = antaresRead::simOptions())
```

Arguments

import Series to import.

opts List of simulation parameters returned by the function `antaresRead::setSimulationPath()`

Value

An updated list containing various information about the simulation.

Examples

```
## Not run:  
  
updateInputSettings(import = c("thermal"))  
updateInputSettings(import = c("hydro", "thermal"))  
  
## End(Not run)
```

updateOptimizationSettings
Update optimization parameters of an Antares study

Description

Antares API: **OK**

Update optimization parameters and other preferences of an Antares study

Usage

```

updateOptimizationSettings(
  simplex.range = NULL,
  transmission.capacities = NULL,
  include.constraints = NULL,
  include.hurdlecosts = NULL,
  include.tc.min.stable.power = NULL,
  include.tc.min.up.down.time = NULL,
  include.dayahead = NULL,
  include.strategicreserve = NULL,
  include.spinningreserve = NULL,
  include.primaryreserve = NULL,
  include.exportmps = NULL,
  power.fluctuations = NULL,
  shedding.strategy = NULL,
  shedding.policy = NULL,
  unit.commitment.mode = NULL,
  number.of.cores.mode = NULL,
  renewable.generation.modelling = NULL,
  day.ahead.reserve.management = NULL,
  opts = antaresRead::simOptions()
)

```

Arguments

```

simplex.range    week or day
transmission.capacities
                 true, false or infinite (since v8.4 can also take : local-values, null-for-all-links,
                 infinite-for-all-links, null-for-physical-links, infinite-for-physical-links)
include.constraints
                 true or false
include.hurdlecosts
                 true or false
include.tc.min.stable.power
                 true or false
include.tc.min.up.down.time
                 true or false
include.dayahead
                 true or false
include.strategicreserve
                 true or false
include.spinningreserve
                 true or false
include.primaryreserve
                 true or false
include.exportmps
                 true or false (since v8.3.2 can take also : none, optim-1, optim-2, both-optimis)

```

```

power.fluctuations
    free modulations, minimize excursions or minimize ramping
shedding.strategy
    share margins
shedding.policy
    shave peaks or minimize duration
unit.commitment.mode
    fast or accurate
number.of.cores.mode
    minimum, low, medium, high or maximum
renewable.generation.modelling
    aggregated or clusters
day.ahead.reserve.management
    global
opts
    List of simulation parameters returned by the function antaresRead::setSimulationPath()

```

Value

An updated list containing various information about the simulation.

Examples

```

## Not run:

updateOptimizationSettings(
  simplex.range = "week",
  power.fluctuations = "minimize ramping"
)

## End(Not run)

```

updateOutputSettings *Update output parameters of an Antares study*

Description

Antares API: **OK**

Update output parameters of an Antares study

Usage

```

updateOutputSettings(
  synthesis = NULL,
  storenewset = NULL,
  archives = NULL,
  result.format = NULL,
  opts = antaresRead::simOptions()
)

```

Arguments

synthesis	Logical. If TRUE, synthetic results will be stored in a directory Study_name/OUTPUT/simu_tag/Econom all. If FALSE, No general synthesis will be printed out.
storenewset	Logical. See Antares General Reference Guide.
archives	Character vector. Series to archive.
result.format	Character. Output format (txt-files or zip).
opts	List of simulation parameters returned by the function antaresRead::setSimulationPath()

Value

An updated list containing various information about the simulation.

Examples

```
## Not run:

updateOutputSettings(
  synthesis = TRUE,
  storenewset = FALSE,
  archives = c("load", "wind")
  result.format = "zip"
)

## End(Not run)
```

variant	<i>Create a study's variant</i>
---------	---------------------------------

Description

API: create a new variant for a given study or use a pre-existing one.

Usage

```
createVariant(name, opts = antaresRead::simOptions())

useVariant(name, variant_id = NULL, opts = antaresRead::simOptions())
```

Arguments

name	Name for the variant to create or the name of an existent variant.
opts	List of simulation parameters returned by the function antaresRead::setSimulationPath()
variant_id	ID of the variant to use, if specified name is ignored.

Value

An updated list containing various information about the simulation.

Examples

```
## Not run:
# See vignette for complete documentation
vignette("api-variant-management")

## End(Not run)
```

variant-commands	<i>Get API commands generated</i>
------------------	-----------------------------------

Description

Get API commands generated

Usage

```
getVariantCommands(
  last = NULL,
  actions = NULL,
  opts = antaresRead::simOptions()
)

writeVariantCommands(
  path,
  last = NULL,
  actions = NULL,
  ...,
  opts = antaresRead::simOptions()
)
```

Arguments

last	Return the last command generated if TRUE, or a numeric for returning a specified number of commands. Default is to return all commands.
actions	A character vector of actions to return.
opts	List of simulation parameters returned by the function antaresRead::setSimulationPath()
path	Path to the JSON file to write on disk.
...	Additional arguments passed to jsonlite::write_json()

Value

a list of commands to edit a variant

`write-ini`*Write configuration options in file or API*

Description

Write configuration options in file or API

Usage

```
writeIni(  
  listData,  
  pathIni,  
  opts = antaresRead::simOptions(),  
  ...,  
  default_ext = ".ini"  
)  
  
writeIniFile(listData, pathIni, overwrite = FALSE)  
  
writeIniAPI(listData, pathIni, opts)
```

Arguments

<code>listData</code>	list, modified list obtained by <code>antaresRead::readIniFile</code> .
<code>pathIni</code>	Character, Path to ini file.
<code>opts</code>	List of simulation parameters returned by the function <code>antaresRead::setSimulationPath()</code>
<code>...</code>	Additional arguments.
<code>default_ext</code>	Default extension used for config files.
<code>overwrite</code>	logical, should file be overwritten if already exist?

Examples

```
## Not run:  
pathIni <- "D:/exemple_test/settings/generaldata.ini"  
generalSetting <- readIniFile(pathIni)  
generalSetting$output$synthesis <- FALSE  
writeIni(generalSetting, pathIni)  
  
## End(Not run)
```

writeEconomicOptions *Write Economic Options*

Description

Antares API: **OK**

This function allows to create or edit economic options. Areas/options present in the input dataframe are edited, while all other values are left unchanged.

Usage

```
writeEconomicOptions(x, opts = antaresRead::simOptions())
```

Arguments

x	A dataframe. Must contain an area column listing some (but not necessarily all) areas of the study. Can contain up to 7 other columns among: average_unsupplied_energy_cost, spread_unsupplied_energy_cost, average_spilled_energy_cost, spread_spilled_energy_cost (numeric columns), non_dispatchable_power, dispatchable_hydro_power and other_dispatchable_power (logical columns).
opts	List of simulation parameters returned by the function antaresRead::setSimulationPath

Examples

```
## Not run:  
  
library(antaresRead)  
  
# Set simulation path  
setSimulationPath(path = "PATH/TO/SIMULATION", simulation = "input")  
  
# Write some economic options for areas a, b and c  
writeEconomicOptions(data.frame(  
  area = c("a", "b", "c"),  
  dispatchable_hydro_power = c(TRUE, FALSE, FALSE),  
  spread_unsupplied_energy_cost = c(0.03, 0.024, 0.01),  
  average_spilled_energy_cost = c(10, 8, 8),  
  stringsAsFactors = FALSE  
)  
)  
  
## End(Not run)
```

writeInputTS	<i>Write input time series</i>
--------------	--------------------------------

Description

Antares API: **OK**

This function writes input time series in an Antares project.

Usage

```
writeInputTS(
  data,
  type = c("load", "hydroROR", "hydroSTOR", "wind", "solar", "tsLink"),
  area = NULL,
  link = NULL,
  overwrite = TRUE,
  opts = antaresRead::simOptions()
)
```

Arguments

data	A 8760N matrix of hourly time series, except when type is "hydroSTOR". In this latter case, data must either be 365N (Antares v7) or 12*N (v6 and earlier).
type	Serie to write: "load", "hydroROR", "hydroSTOR", "wind", "solar", or "tsLink".
area	The area where to write the input time series.
link	Link for which writing transmission capacities time series, must like "area01%area02" or c("area01", "area02").
overwrite	Logical. Overwrite the values if a file already exists.
opts	List of simulation parameters returned by the function antaresRead::setSimulationPath()

Value

An updated list containing various information about the simulation.

Warning

You cannot use area and link arguments at the same time.

Examples

```
## Not run:

# Write solar time series
writeInputTS(
  area = "fictive_area",
  type = "solar",
```

```
    data = matrix(rep(4, 8760*2), nrow = 8760)
  )

  ## End(Not run)
```

writeMiscGen

Write Misc Gen data

Description

Antares API: **OK**

Usage

```
writeMiscGen(data, area, opts = antaresRead::simOptions())
```

Arguments

data	Data to write.
area	Name of the area for which to write data.
opts	List of simulation parameters returned by the function antaresRead::setSimulationPath()

Value

An updated list containing various information about the simulation.

Examples

```
## Not run:

writeMiscGen(matrix(data = c(rep(0, 8760 * 7), rep(-100000, 8760)), ncol = 8), "area1")

## End(Not run)
```

writeOutputValues *Write output value for Antares*

Description

Antares API: **NO**

This function write all output values for an Antares study.

Usage

```
writeOutputValues(data, opts = NULL)
```

Arguments

data obtain with readAntares

opts List of simulation parameters returned by the function [antaresRead::setSimulationPath\(\)](#)

Examples

```
## Not run:  
  
library(antaresRead)  
library(data.table)  
opts <- setSimulationPath("my_study")  
data <- readAntares(links = "all", areas = "all", clusters = "all")  
writeOutputValues(data)  
  
## End(Not run)
```

writeSeriesPrepro *Write prepro data*

Description

Antares API: **NO**

This function allows to write load, wind and solar prepro data. Using character (0) allows to erase data (cf Examples).

Usage

```
writeSeriesPrepro(
  area,
  type = c("load", "wind", "solar"),
  coefficients = NULL,
  daily_profile = NULL,
  translation = NULL,
  conversion = NULL,
  overwrite = TRUE,
  opts = antaresRead::simOptions()
)
```

Arguments

area	The area where to write prepro data.
type	Type of data to write : "load", "wind" or "solar".
coefficients	A 12*6 matrix of monthly values for the primary parameters alpha, beta, gamma, delta, theta and mu.
daily_profile	A 24*12 matrix of hourly / monthly coefficients K(hm) that are used to modulate the values of the stationary stochastic process by which the actual process is approximated.
translation	A vector of length 8760 (or 8760*1 matrix) to add to the time-series generated, prior or after scaling.
conversion	A 2*N matrix (with 1<=N<=50) that is used to turn the initial time-series produced by the generators into final data. See Antares General Reference Guide.
overwrite	Logical. Overwrite the values if a file already exists.
opts	List of simulation parameters returned by the function antaresRead::setSimulationPath() .

Examples

```
## Not run:

writeSeriesPrepro("fictive_area", type = "solar", daily_profile = matrix(rep(1, 24*12), nrow = 24))

# Erase daily profile data:
writeSeriesPrepro("fictive_area", type = "solar", daily_profile = character(0))

## End(Not run)
```

writeWaterValues	<i>Write water values</i>
------------------	---------------------------

Description

Antares API: **OK**

Write water values for a given area.

Usage

```
writeWaterValues(  
  area,  
  data = NULL,  
  overwrite = TRUE,  
  opts = antaresRead::simOptions()  
)
```

Arguments

area	The area where to add the water values.
data	A 365x101 numeric matrix: table of marginal values for the stored energy, which depends on the date (365 days) and on the reservoir level (101 round percentage values ranging from 0% to 100%). OR a 3-column matrix with 365x101 rows. In this latter case the 3 columns must be 'date', 'level' and 'value' (in this order), and the rows must be sorted by: ascending day, ascending level.
overwrite	Logical. Overwrite the values if a file already exists.
opts	List of simulation parameters returned by the function antaresRead::setSimulationPath() .

Examples

```
## Not run:  
  
writeWaterValues("fictive_area", data = matrix(rep(0, 365*101), nrow = 365))  
  
## End(Not run)
```


Index

activateRES, 3
adequacyOptions, 4
adequacyOptions(), 18, 29
antaresRead::setSimulationPath(), 5, 12, 14, 17–20, 22, 24, 28–30, 32–34, 37, 39–42, 45, 47, 49, 52, 53, 55–58, 60–64
antaresRead::setSimulationPathAPI, 35
backupStudy, 4
check-version, 5
checkRemovedArea, 6
cleanUpOutput, 6
clearScenarioBuilder
 (scenario-builder), 44
computeOtherFromHourlyMulti, 7, 8
computeOtherFromHourlyYear, 7, 8
computeTimeStampFromHourly, 9
convertConfigToAdq, 10
copyOutput, 10
create-binding-constraint, 11
create-cluster, 13
create-study, 16
createArea, 17
createArea(), 29, 40
createBindingConstraint
 (create-binding-constraint), 11
createBindingConstraint(), 31, 41
createBindingConstraintBulk
 (create-binding-constraint), 11
createCluster (create-cluster), 13
createCluster(), 28, 39
createClusterRES (create-cluster), 13
createClusterRES(), 28, 39
createDistrict, 19
createDSR, 20
createLink, 21
createLink(), 32, 38
createPSP, 23
createStudy (create-study), 16
createStudyAPI (create-study), 16
createVariant (variant), 56
dicoGeneralSettings, 25
dicoOptimizationSettings, 26
edit-cluster, 27
editArea, 28
editArea(), 18, 40
editBindingConstraint, 30
editBindingConstraint(), 12, 41
editCluster (edit-cluster), 27
editCluster(), 14, 39
editClusterRES (edit-cluster), 27
editClusterRES(), 14, 39
editDSR (createDSR), 20
editLink, 31
editLink(), 23
editPSP (createPSP), 23
filteringOptions, 33
filteringOptions(), 18, 29
getCapacityDSR (createDSR), 20
getCapacityPSP (createPSP), 23
getJobLogs, 33
getJobs, 34
getPlaylist (playlist), 36
getVariantCommands (variant-commands), 57
is_antares_v7 (check-version), 5
is_antares_v820 (check-version), 5
jsonlite::write_json(), 57
mockSimulationAPI, 35
nodalOptimizationOptions, 35
nodalOptimizationOptions(), 18, 29

playlist, 36
propertiesLinkOptions, 37
propertiesLinkOptions(), 22

readScenarioBuilder (scenario-builder),
44
remove-cluster, 38
removeArea, 40
removeArea(), 18, 29
removeBindingConstraint, 40
removeBindingConstraint(), 12, 31
removeCluster (remove-cluster), 38
removeCluster(), 14, 28
removeClusterRES (remove-cluster), 38
removeClusterRES(), 14, 28
removeLink, 41
removeLink(), 23, 32
runSimulation, 42
runTsGenerator, 43

scenario-builder, 44
scenarioBuilder (scenario-builder), 44
searchStudy, 46
setAPImode, 47
setPlaylist (playlist), 36
setSimulationPathAPI(), 17
setSolverPath, 48

updateAdequacySettings, 10, 49
updateGeneralSettings, 50
updateInputSettings, 53
updateOptimizationSettings, 53
updateOutputSettings, 55
updateScenarioBuilder
(scenario-builder), 44
useVariant (variant), 56

variant, 56
variant-commands, 57

write-ini, 58
writeEconomicOptions, 59
writeIni (write-ini), 58
writeIniAPI (write-ini), 58
writeIniFile (write-ini), 58
writeInputTS, 60
writeMiscGen, 61
writeOutputValues, 62
writeSeriesPrepro, 62

writeVariantCommands
(variant-commands), 57
writeWaterValues, 64