

Package ‘basicMCMCplots’

December 12, 2018

Title Trace Plots, Density Plots and Chain Comparisons for MCMC Samples

Version 0.1.2

Description Provides a function for examining posterior MCMC samples from a single chain using trace plots and density plots, and from multiple chains by comparing posterior medians and credible intervals from each chain. These plotting functions have a variety of options, such as figure sizes, legends, parameters to plot, and saving plots to file. Functions interface with the NIMBLE software package, see de Valpine, Turek, Paciorek, Anderson-Bergman, Temple Lang and Bodik (2017) <doi:10.1080/10618600.2016.1172487>.

Depends R (>= 3.4.0)

License GPL-3

Encoding UTF-8

LazyData true

RoxygenNote 6.1.0

NeedsCompilation no

Author Daniel Turek [aut, cre]

Maintainer Daniel Turek <danielturek@gmail.com>

Repository CRAN

Date/Publication 2018-12-12 20:00:03 UTC

R topics documented:

chainsPlot	2
chainsSummary	2
samplesPlot	3

Index	5
--------------	----------

chainsPlot *Compare trace plots from multiple MCMC chains*

Description

Overlays trace plots from each MCMC chain, for each parameter

Usage

```
chainsPlot(samplesList, var = NULL, scale = FALSE,
  legend = !is.null(names(samplesList)), legend.location = "topright",
  cex = 1, densityplot = FALSE, file = NULL)
```

Arguments

samplesList	List of arrays of MCMC samples from different chains
var	Parameter names to plot
scale	Logical, whether to normalize each posterior chain
legend	Logical, whether to include a legend of chain names
legend.location	Legend location
cex	Expansion coefficient for text
densityplot	Logical, whether to generate posterior density plots instead of trace plots
file	Filename for saving figure to a file

Examples

```
samples1 <- cbind(rnorm(1000, 1), rgamma(1000, 1), rpois(1000, 1))
colnames(samples1) <- c('alpha', 'beta', 'gamma')
samples2 <- cbind(rnorm(1000, 2), rgamma(1000, 2), rpois(1000, 2))
colnames(samples2) <- c('alpha', 'beta', 'gamma')
samplesList <- list(chain1 = samples1, chain2 = samples2)
chainsPlot(samplesList)
```

chainsSummary *Compare summary statistics from multiple MCMC chains*

Description

Plots median and 95

Usage

```
chainsSummary(samplesList, var = NULL, nrows = NULL, scale = FALSE,
  width = 7, height = NULL, legend = !is.null(names(samplesList)),
  legend.location = "topright", jitter = 1, buffer.right = 0,
  buffer.left = 0, cex = 1, file = NULL)
```

Arguments

<code>samplesList</code>	List of arrays of MCMC samples from different chains
<code>var</code>	Parameter names to plot
<code>nrows</code>	Number of rows in the resulting plot
<code>scale</code>	Logical, whether to normalize each posterior chain
<code>width</code>	Width of figure
<code>height</code>	Height of figure
<code>legend</code>	Logical, whether to include a legend of chain names
<code>legend.location</code>	Legend location
<code>jitter</code>	Scale factor for spreading out lines from each chain
<code>buffer.right</code>	Additional buffer on left side of plot
<code>buffer.left</code>	Additional buffer on right side of plot
<code>cex</code>	Expansion coefficient for text
<code>file</code>	Filename for saving figure to a file

Examples

```
samples1 <- cbind(rnorm(1000, 1), rgamma(1000, 1), rpois(1000, 1))
colnames(samples1) <- c('alpha', 'beta', 'gamma')
samples2 <- cbind(rnorm(1000, 2), rgamma(1000, 2), rpois(1000, 2))
colnames(samples2) <- c('alpha', 'beta', 'gamma')
samplesList <- list(chain1 = samples1, chain2 = samples2)
chainsSummary(samplesList, nrow = 1, jitter = .3, buffer.left = .5, buffer.right = .5)
```

samplesPlot

Plot MCMC traceplots and density plots

Description

Plot MCMC traceplots and density plots

Usage

```
samplesPlot(samples, var = colnames(samples), ind = NULL,
  burnin = NULL, scale = FALSE, width = 7, height = 4,
  legend = TRUE, legend.location = "topright", traceplot = TRUE,
  densityplot = TRUE, file = NULL)
```

Arguments

samples	Array of MCMC samples, or a list of samples from multiple chains in which case the first chain is used
var	Parameter names to plot
ind	Chain indices to plot
burnin	Number of initial MCMC samples to discard
scale	Logical, whether to normalize each posterior chain
width	Width of the plot
height	Height of the plot
legend	Logical, whether to include a legend of parameter names
legend.location	Location of legend
traceplot	Logical, whether to include traceplots
densityplot	Logical, whether to include density plots
file	Optional filename to save figure as a file

Examples

```
samples <- cbind(rnorm(1000), rgamma(1000, 1))
colnames(samples) <- c('alpha', 'beta')
samplesPlot(samples)
```

Index

chainsPlot, 2
chainsSummary, 2
samplesPlot, 3