

# Package ‘bit64’

May 8, 2017

**Type** Package

**Title** A S3 Class for Vectors of 64bit Integers

**Version** 0.9-7

**Date** 2017-05-07

**Author** Jens Oehlschlägel <Jens.Oehlschlaegel@truecluster.com>

**Maintainer** Jens Oehlschlägel <Jens.Oehlschlaegel@truecluster.com>

**Depends** R (>= 3.0.1), bit (>= 1.1-12), utils, methods, stats

**Description** Package 'bit64' provides serializable S3 atomic 64bit (signed) integers.

These are useful for handling database keys and exact counting in  $\pm 2^{63}$ .

WARNING: do not use them as replacement for 32bit integers, integer64 are not supported for subscripting by R-core and they have different semantics when combined with double, e.g. integer64 + double => integer64.

Class integer64 can be used in vectors, matrices, arrays and data.frames.

Methods are available for coercion from and to logicals, integers, doubles, characters and factors as well as many elementwise and summary functions.

Many fast algorithmic operations such as 'match' and 'order' support interactive data exploration and manipulation and optionally leverage caching.

**License** GPL-2

**LazyLoad** yes

**ByteCompile** yes

**URL** <http://ff.r-forge.r-project.org/>

**Encoding** UTF-8

**NeedsCompilation** yes

**Repository** CRAN

**Date/Publication** 2017-05-08 13:21:40 UTC

## R topics documented:

bit64-package . . . . .	2
as.character.integer64 . . . . .	16

as.data.frame.integer64 . . . . .	17
as.integer64.character . . . . .	18
benchmark64 . . . . .	19
benchmark64.data . . . . .	22
bit64S3 . . . . .	23
c.integer64 . . . . .	25
cache . . . . .	26
cumsum.integer64 . . . . .	27
duplicated.integer64 . . . . .	29
extract.replace.integer64 . . . . .	30
format.integer64 . . . . .	31
hashcache . . . . .	33
hashmap . . . . .	34
identical.integer64 . . . . .	37
is.sorted.integer64 . . . . .	38
keypos . . . . .	39
match.integer64 . . . . .	41
optimizer64.data . . . . .	43
prank . . . . .	44
qtile . . . . .	45
ramsort.integer64 . . . . .	47
rank.integer64 . . . . .	49
rep.integer64 . . . . .	50
seq.integer64 . . . . .	51
sort.integer64 . . . . .	52
sortnut . . . . .	53
sum.integer64 . . . . .	57
table.integer64 . . . . .	58
tiepos . . . . .	60
unipos . . . . .	61
unique.integer64 . . . . .	62
xor.integer64 . . . . .	64

<b>Index</b>	<b>66</b>
--------------	-----------

---

bit64-package	<i>A S3 class for vectors of 64bit integers</i>
---------------	---

---

## Description

Package 'bit64' provides fast serializable S3 atomic 64bit (signed) integers that can be used in vectors, matrices, arrays and data.frames. Methods are available for coercion from and to logicals, integers, doubles, characters and factors as well as many elementwise and summary functions.

**Version 0.8** With 'integer64' vectors you can store very large integers at the expense of 64 bits, which is by factor 7 better than 'int64' from package 'int64'. Due to the smaller memory footprint, the atomic vector architecture and using only S3 instead of S4 classes, most operations are one to three orders of magnitude faster: Example speedups are 4x for serialization, 250x for adding, 900x for coercion and 2000x for object creation. Also 'integer64' avoids an ongoing (potentially infinite)

penalty for garbage collection observed during existence of 'int64' objects (see code in example section).

**Version 0.9** Package 'bit64' - which extends R with fast 64-bit integers - now has fast (single-threaded) implementations the most important univariate algorithmic operations (those based on hashing and sorting). We now have methods for 'match', 'quantile', 'median' and 'summary'. Regarding data management we also have novel generics 'unipos' (positions of the unique values), 'tiepos' (positions of ties), 'keypos' (positions of foreign keys in a sorted dimension table) and derived methods 'as.factor' and 'as.ordered'. This 64-bit functionality is implemented carefully to be not slower than the respective 32-bit operations in Base R and also to avoid outlying waiting times observed with 'order', 'rank' and 'table' (speedup factors 20/16/200 respective). This increases the dataset size with which we can work truly interactive. The speed is achieved by simple heuristic optimizers in high-level functions choosing the best from multiple low-level algorithms and further taking advantage of a novel caching if activated. In an example R session using a couple of these operations the 64-bit integers performed 22x faster than base 32-bit integers, hash-caching improved this to 24x, sortorder-caching was most efficient with 38x (caching hashing and sorting is not worth it with 32x at duplicated RAM consumption).

### Usage

```
integer64(length)
## S3 method for class 'integer64'
is(x)
## S3 replacement method for class 'integer64'
length(x) <- value
## S3 method for class 'integer64'
print(x, quote=FALSE, ...)
## S3 method for class 'integer64'
str(object, vec.len = str0$vec.len, give.head = TRUE, give.length = give.head, ...)
```

### Arguments

length	length of vector using <a href="#">integer</a>
x	an integer64 vector
object	an integer64 vector
value	an integer64 vector of values to be assigned
quote	logical, indicating whether or not strings should be printed with surrounding quotes.
vec.len	see <a href="#">str</a>
give.head	see <a href="#">str</a>
give.length	see <a href="#">str</a>
...	further arguments to the <a href="#">NextMethod</a>

### Details

Package:	bit64
Type:	Package

```

Version:    0.5.0
Date:      2011-12-12
License:   GPL-2
LazyLoad:  yes
Encoding:  latin1

```

## Value

`integer64` returns a vector of 'integer64', i.e. a vector of `double` decorated with class 'integer64'.

## Design considerations

64 bit integers are related to big data: we need them to overcome address space limitations. Therefore performance of the 64 bit integer type is critical. In the S language – designed in 1975 – atomic objects were defined to be vectors for a couple of good reasons: simplicity, option for implicit parallelization, good cache locality. In recent years many analytical databases have learnt that lesson: column based data bases provide superior performance for many applications, the result are products such as MonetDB, Sybase IQ, Vertica, Exasol, Ingres Vectorwise. If we introduce 64 bit integers not natively in Base R but as an external package, we should at least strive to make them as 'basic' as possible. Therefore the design choice of `bit64` not only differs from `int64`, it is obvious: Like the other atomic types in Base R, we model data type 'integer64' as a contiguous `atomic` vector in memory, and we use the more basic `S3` class system, not `S4`. Like package `int64` we want our 'integer64' to be `serializeable`, therefore we also use an existing data type as the basis. Again the choice is obvious: R has only one 64 bit data type: doubles. By using `doubles`, `integer64` inherits some functionality such as `is.atomic`, `length`, `length<-`, `names`, `names<-`, `dim`, `dim<-`, `dimnames`, `dimnames`.

Our R level functions strictly follow the functional programming paradigm: no modification of arguments or other sideeffects. Before version 0.93 we internally deviated from the strict paradigm in order to boost performance. Our C functions do not create new return values, instead we pass-in the memory to be returned as an argument. This gives us the freedom to apply the C-function to new or old vectors, which helps to avoid unnecessary memory allocation, unnecessary copying and unnecessary garbage collection. Prior to 0.93 *within* our R functions we also deviated from conventional R programming by not using `attr<-` and `attributes<-` because they always did new memory allocation and copying in older R versions. If we wanted to set attributes of return values that we have freshly created, we instead used functions `setattr` and `setattributes` from package `bit`. From version 0.93 `setattr` is only used for manipulating `cache` objects, in `ramsort.integer64` and `sort.integer64` and in `as.data.frame.integer64`.

## Arithmetic precision and coercion

The fact that we introduce 64 bit long long integers – without introducing 128-bit long doubles – creates some subtle challenges: Unlike 32 bit `integers`, the `integer64` are no longer a proper subset of `double`. If a binary arithmetic operation does involve a `double` and a `integer`, it is a no-brainer to return `double` without loss of information. If an `integer64` meets a `double`, it is not trivial what type to return. Switching to `integer64` limits our ability to represent very large numbers, switching to `double` limits our ability to distinguish `x` from `x+1`. Since the latter is the purpose

of introducing 64 bit integers, we usually return integer64 from functions involving integer64, for example in `c`, `cbind` and `rbind`.

Different from Base R, our operators `+`, `-`, `%/%` and `%%` coerce their arguments to integer64 and always return integer64.

The multiplication operator `*` coerces its first argument to integer64 but allows its second argument to be also double: the second argument is internally coerced to 'long double' and the result of the multiplication is returned as integer64.

The division `/` and power `^` operators also coerce their first argument to integer64 and coerce internally their second argument to 'long double', they return as double, like `sqrt`, `log`, `log2` and `log10` do.

argument1	op	argument2	->	coerced1	op	coerced2	->	result
integer64	+	double	->	integer64	+	integer64	->	integer64
double	+	integer64	->	integer64	+	integer64	->	integer64
integer64	-	double	->	integer64	-	integer64	->	integer64
double	-	integer64	->	integer64	-	integer64	->	integer64
integer64	%/%	double	->	integer64	%/%	integer64	->	integer64
double	%/%	integer64	->	integer64	%/%	integer64	->	integer64
integer64	%%	double	->	integer64	%%	integer64	->	integer64
double	%%	integer64	->	integer64	%%	integer64	->	integer64
integer64	*	double	->	integer64	*	long double	->	integer64
double	*	integer64	->	integer64	*	integer64	->	integer64
integer64	/	double	->	integer64	/	long double	->	double
double	/	integer64	->	integer64	/	long double	->	double
integer64	^	double	->	integer64	/	long double	->	double
double	^	integer64	->	integer64	/	long double	->	double

### Creating and testing S3 class 'integer64'

Our creator function `integer64` takes an argument `length`, creates an atomic double vector of this length, attaches an S3 class attribute 'integer64' to it, and that's it. We simply rely on S3 method dispatch and interpret those 64bit elements as 'long long int'.

`is.double` currently returns TRUE for integer64 and might return FALSE in a later release. Consider `is.double` to have undefined behaviour and do query `is.integer64` *before* querying `is.double`.

The methods `is.integer64` and `is.vector` both return TRUE for integer64. Note that we did not patch `storage.mode` and `typeof`, which both continue returning 'double' Like for 32 bit `integer`, `mode` returns 'numeric' and `as.double` tries coercing to `double`). It is likely that 'integer64' becomes a `vmode` in package `ff`.

Further methods for creating integer64 are `range` which returns the range of the data type if called without arguments, `rep`, `seq`.

For all available methods on integer64 vectors see the index below and the examples.

### Index of implemented methods

creating,testing,printing	see also	description
NA_integer64_	NA_integer_	NA constant

integer64	integer	create zero atomic vector
rep.integer64	rep	
seq.integer64	seq	
is.integer64	is	
is.vector.integer64	is.integer	inherited from Base R
identical.integer64	is.vector	
length<-.integer64	identical	
	length<-	inherited from Base R
	length	inherited from Base R
	names<-	inherited from Base R
	names	inherited from Base R
	dim<-	inherited from Base R
	dim	inherited from Base R
	dimnames<-	inherited from Base R
	dimnames	inherited from Base R
	str	inherited from Base R, does not print values correctly
print.integer64	print	
str.integer64	str	
<b>coercing to integer64</b>	<b>see also</b>	<b>description</b>
as.integer64		generic
as.integer64.character	character	
as.integer64.double	double	
as.integer64.integer	integer	
as.integer64.integer64	integer64	
as.integer64.logical	logical	
as.integer64.NULL	NULL	
<b>coercing from integer64</b>	<b>see also</b>	<b>description</b>
as.bitstring	as.bitstring	generic
as.bitstring.integer64		
as.character.integer64	as.character	
as.double.integer64	as.double	
as.integer.integer64	as.integer	
as.logical.integer64	as.logical	
<b>data structures</b>	<b>see also</b>	<b>description</b>
c.integer64	c	vector concatenate
cbind.integer64	cbind	column bind
rbind.integer64	rbind	row bind
as.data.frame.integer64	as.data.frame	coerce atomic object to data.frame
	data.frame	inherited from Base R since we have coercion
<b>subscripting</b>	<b>see also</b>	<b>description</b>
[.integer64	[	vector and array extract
[<-.integer64	[<-	vector and array assign
[ [.integer64	[[	scalar extract
[ [<-.integer64	[ [<-	scalar assign

<b>binary operators</b>	<b>see also</b>	<b>description</b>
<code>+.integer64</code>	<code>+</code>	returns integer64
<code>-.integer64</code>	<code>-</code>	returns integer64
<code>*.integer64</code>	<code>*</code>	returns integer64
<code>^.integer64</code>	<code>^</code>	returns double
<code>/.integer64</code>	<code>/</code>	returns double
<code>%/.integer64</code>	<code>%/</code>	returns integer64
<code>%%.integer64</code>	<code>%%</code>	returns integer64
<b>comparison operators</b>	<b>see also</b>	<b>description</b>
<code>==.integer64</code>	<code>==</code>	
<code>!=.integer64</code>	<code>!=</code>	
<code>&lt;.integer64</code>	<code>&lt;</code>	
<code>&lt;=.integer64</code>	<code>&lt;=</code>	
<code>&gt;.integer64</code>	<code>&gt;</code>	
<code>&gt;=.integer64</code>	<code>&gt;=</code>	
<b>logical operators</b>	<b>see also</b>	<b>description</b>
<code>!.integer64</code>	<code>!</code>	
<code>&amp;.integer64</code>	<code>&amp;</code>	
<code> .integer64</code>	<code> </code>	
<code>xor.integer64</code>	<code>xor</code>	
<b>math functions</b>	<b>see also</b>	<b>description</b>
<code>is.na.integer64</code>	<code>is.na</code>	returns logical
<code>format.integer64</code>	<code>format</code>	returns character
<code>abs.integer64</code>	<code>abs</code>	returns integer64
<code>sign.integer64</code>	<code>sign</code>	returns integer64
<code>log.integer64</code>	<code>log</code>	returns double
<code>log10.integer64</code>	<code>log10</code>	returns double
<code>log2.integer64</code>	<code>log2</code>	returns double
<code>sqrt.integer64</code>	<code>sqrt</code>	returns double
<code>ceiling.integer64</code>	<code>ceiling</code>	dummy returning its argument
<code>floor.integer64</code>	<code>floor</code>	dummy returning its argument
<code>trunc.integer64</code>	<code>trunc</code>	dummy returning its argument
<code>round.integer64</code>	<code>round</code>	dummy returning its argument
<code>signif.integer64</code>	<code>signif</code>	dummy returning its argument
<b>cumulative functions</b>	<b>see also</b>	<b>description</b>
<code>cummin.integer64</code>	<code>cummin</code>	
<code>cummax.integer64</code>	<code>cummax</code>	
<code>cumsum.integer64</code>	<code>cumsum</code>	
<code>cumprod.integer64</code>	<code>cumprod</code>	
<code>diff.integer64</code>	<code>diff</code>	
<b>summary functions</b>	<b>see also</b>	<b>description</b>
<code>range.integer64</code>	<code>range</code>	

<code>min.integer64</code>	<code>min</code>	
<code>max.integer64</code>	<code>max</code>	
<code>sum.integer64</code>	<code>sum</code>	
<code>mean.integer64</code>	<code>mean</code>	
<code>prod.integer64</code>	<code>prod</code>	
<code>all.integer64</code>	<code>all</code>	
<code>any.integer64</code>	<code>any</code>	
<b>algorithmically complex functions</b>	<b>see also</b>	<b>description (caching)</b>
<code>match.integer64</code>	<code>match</code>	position of x in table (h//o/so)
<code>%in%.integer64</code>	<code>%in%</code>	is x in table? (h//o/so)
<code>duplicated.integer64</code>	<code>duplicated</code>	is current element duplicate of previous one? (h//o/so)
<code>unique.integer64</code>	<code>unique</code>	(shorter) vector of unique values only (h/s/o/so)
<code>unipos.integer64</code>	<code>unipos</code>	positions corresponding to unique values (h/s/o/so)
<code>tiepos.integer64</code>	<code>tiepos</code>	positions of values that are tied (//o/so)
<code>keypos.integer64</code>	<code>keypos</code>	position of current value in sorted list of unique values (//o/so)
<code>as.factor.integer64</code>	<code>as.factor</code>	convert to (unordered) factor with sorted levels of previous values (//o/so)
<code>as.ordered.integer64</code>	<code>as.ordered</code>	convert to ordered factor with sorted levels of previous values (//o/so)
<code>table.integer64</code>	<code>table</code>	unique values and their frequencies (h/s/o/so)
<code>sort.integer64</code>	<code>sort</code>	sorted vector (/s/o/so)
<code>order.integer64</code>	<code>order</code>	positions of elements that would create sorted vector (//o/so)
<code>rank.integer64</code>	<code>rank</code>	(average) ranks of non-NAs, NAs kept in place (/s/o/so)
<code>quantile.integer64</code>	<code>quantile</code>	(existing) values at specified percentiles (/s/o/so)
<code>median.integer64</code>	<code>median</code>	(existing) value at percentile 0.5 (/s/o/so)
<code>summary.integer64</code>	<code>summary</code>	(/s/o/so)
<b>helper functions</b>	<b>see also</b>	<b>description</b>
<code>minusclass</code>	<code>minusclass</code>	removing class attribute
<code>plusclass</code>	<code>plusclass</code>	inserting class attribute
<code>binattr</code>	<code>binattr</code>	define binary op behaviour
<b>tested I/O functions</b>	<b>see also</b>	<b>description</b>
	<code>read.table</code>	inherited from Base R
	<code>write.table</code>	inherited from Base R
	<code>serialize</code>	inherited from Base R
	<code>unserialize</code>	inherited from Base R
	<code>save</code>	inherited from Base R
	<code>load</code>	inherited from Base R
	<code>dput</code>	inherited from Base R
	<code>dget</code>	inherited from Base R

### Limitations inherited from implementing 64 bit integers via an external package

- **vector size** of atomic vectors is still limited to `.Machine$integer.max`. However, external memory extending packages such as `ff` or `bigmemory` can extend their address space now



with `integer64`. Having 64 bit integers also help with those not so obvious address issues that arise once we exchange data with SQL databases and datawarehouses, which use big integers as surrogate keys, e.g. on indexed primary key columns. This puts R into a relatively strong position compared to certain commercial statistical softwares, which sell database connectivity but neither have the range of 64 bit integers, nor have integers at all, nor have a single numeric data type in their macro-glue-language.

- **literals** such as `123LL` would require changes to Base R, up to then we need to write (and call) `as.integer64(123L)` or `as.integer64(123)` or `as.integer64('123')`. Only the latter allows to specify numbers beyond Base R's numeric data types and therefore is the recommended way to use – using only one way may facilitate migrating code to literals at a later stage.

### Limitations inherited from Base R, Core team, can you change this?

- `identical` with default parameters does not distinguish all bit-patterns of doubles. For testing purposes we provide a wrapper `identical.integer64` that will distinguish all bit-patterns. It would be desirable to have a single call of `identical` handle both, `double` and `integer64`.
- the `colon` operator `:` officially does not dispatches S3 methods, however, we have made it generic

```
from <- lim.integer64()[1]
to <- from+99
from:to
```

As a limitation remains: it will only dispatch at its first argument `from` but not at its second `to`.

- `is.double` does not dispatches S3 methods, However, we have made it generic and it will return `FALSE` on `integer64`.
- `c` only dispatches `c.integer64` if the first argument is `integer64` and it does not recursively dispatch the proper method when called with argument `recursive=TRUE` Therefore

```
c(list(integer64, integer64))
```

does not work and for now you can only call

```
c.integer64(list(x,x))
```

- **generic binary operators** fail to dispatch *any* user-defined S3 method if the two arguments have two different S3 classes. For example we have two classes `bit` and `bitwhich` sparsely representing boolean vectors and we have methods `&.bit` and `&.bitwhich`. For an expression involving both as in `bit & bitwhich`, none of the two methods is dispatched. Instead a standard method is dispatched, which neither handles `bit` nor `bitwhich`. Although it lacks symmetry, the better choice would be to dispatch simply the method of the class of the first argument in case of class conflict. This choice would allow authors of extension packages providing coherent behaviour at least within their contributed classes. But as long as none of the package authors methods is dispatched, he cannot handle the conflicting classes at all.
- `unlist` is not generic and if it were, we would face similar problems as with `c()`

- `vector` with argument `mode='integer64'` cannot work without adjustment of Base R
- `as.vector` with argument `mode='integer64'` cannot work without adjustment of Base R
- `is.vector` does not dispatch its method `is.vector.integer64`
- `mode<-` drops the class 'integer64' which is returned from `as.integer64`. Also it does not remove an existing class 'integer64' when assigning mode 'integer'.
- `storage.mode<-` does not support external data types such as `as.integer64`
- `matrix` does drop the 'integer64' class attribute.
- `array` does drop the 'integer64' class attribute. In current R versions (1.15.1) this can be circumvented by activating the function `as.vector.integer64` further down this file. However, the CRAN maintainer has requested to remove `as.vector.integer64`, even at the price of breaking previously working functionality of the package.
- `str` does not print the values of `integer64` correctly

### further limitations

- **subscripting** non-existing elements and subscripting with NAs is currently not supported. Such subscripting currently returns 9218868437227407266 instead of NA (the NA value of the underlying double code). Following the full R behaviour here would either destroy performance or require extensive C-coding.

### Note

`integer64` are useful for handling database keys and exact counting in  $\pm 2^{63}$ . Do not use them as replacement for 32bit integers, `integer64` are not supported for subscripting by R-core and they have different semantics when combined with `double`. Do understand that `integer64` can only be useful over `double` if we do not coerce it to `double`.

While

`integer + double -> double + double -> double`

or

`1L + 0.5 -> 1.5`

for additive operations we coerce to `integer64`

`integer64 + double -> integer64 + integer64 -> integer64`

hence

`as.integer64(1) + 0.5 -> 1LL + 0LL -> 1LL`

see section "Arithmetic precision and coercion" above

### Author(s)

Jens Oehlschlägel <Jens.Oehlschlaegel@truecluster.com> Maintainer: Jens Oehlschlägel <Jens.Oehlschlaegel@truecluster.c

### See Also

[integer](#) in base R

**Examples**

```

message("Using integer64 in vector")
x <- integer64(8) # create 64 bit vector
x
is.atomic(x)      # TRUE
is.integer64(x)   # TRUE
is.numeric(x)     # TRUE
is.integer(x)     # FALSE - debatable
is.double(x)     # FALSE - might change
x[] <- 1:2        # assigned value is recycled as usual
x[1:6]           # subscripting as usual
length(x) <- 13  # changing length as usual
x
rep(x, 2)         # replicate as usual
seq(as.integer64(1), 10) # seq.integer64 is dispatched on first given argument
seq(to=as.integer64(10), 1) # seq.integer64 is dispatched on first given argument
seq.integer64(along.with=x) # or call seq.integer64 directly
# c.integer64 is dispatched only if *first* argument is integer64 ...
x <- c(x,runif(length(x), max=100))
# ... and coerces everything to integer64 - including double
x
names(x) <- letters # use names as usual
x

message("Using integer64 in array - note that 'matrix' currently does not work")
message("as.vector.integer64 removed as requested by the CRAN maintainer")
message("as consequence 'array' also does not work anymore")

message("we still can create a matrix or array by assigning 'dim'")
y <- rep(as.integer64(NA), 12)
dim(y) <- c(3,4)
dimnames(y) <- list(letters[1:3], LETTERS[1:4])
y["a",] <- 1:2 # assigning as usual
y
y[1:2,-4] # subscripting as usual
# cbind.integer64 dispatched on any argument and coerces everything to integer64
cbind(E=1:3, F=runif(3, 0, 100), G=c("-1","0","1"), y)

message("Using integer64 in data.frame")
str(as.data.frame(x))
str(as.data.frame(y))
str(data.frame(y))
str(data.frame(I(y)))
d <- data.frame(x=x, y=runif(length(x), 0, 100))
d
d$x

message("Using integer64 with csv files")
fi64 <- tempfile()
write.csv(d, file=fi64, row.names=FALSE)
e <- read.csv(fi64, colClasses=c("integer64", NA))
unlink(fi64)

```

```

str(e)
identical.integer64(d$x,e$x)

message("Serializing and unserializing integer64")
dput(d, fi64)
e <- dget(fi64)
identical.integer64(d$x,e$x)
e <- d[,]
save(e, file=fi64)
rm(e)
load(file=fi64)
identical.integer64(d,e)

### A couple of unit tests follow hidden in a dontshow{} directive ###

## Not run:
message("== Differences between integer64 and int64 ==")
require(bit64)
require(int64)

message("-- integer64 is atomic --")
is.atomic(integer64())
#is.atomic(int64())
str(integer64(3))
#str(int64(3))

message("-- The following performance numbers are measured under RWin64 --")
message("-- under RWin32 the advantage of integer64 over int64 is smaller --")

message("-- integer64 needs 7x/5x less RAM than int64 under 64/32 bit OS
(and twice the RAM of integer as it should be) --")
#as.vector(object.size(int64(1e6))/object.size(integer64(1e6)))
as.vector(object.size(integer64(1e6))/object.size(integer(1e6)))

message("-- integer64 creates 2000x/1300x faster than int64 under 64/32 bit OS
(and 3x the time of integer) --")
t32 <- system.time(integer(1e8))
t64 <- system.time(integer64(1e8))
#T64 <- system.time(int64(1e7))*10 # using 1e8 as above stalls our R on an i7 8 GB RAM Thinkpad
#T64/t64
t64/t32

i32 <- sample(1e6)
d64 <- as.double(i32)

message("-- the following timings are rather conservative since timings
of integer64 include garbage collection -- due to looped calls")
message("-- integer64 coerces 900x/100x faster than int64
under 64/32 bit OS (and 2x the time of coercing to integer) --")
t32 <- system.time(for(i in 1:1000)as.integer(d64))
t64 <- system.time(for(i in 1:1000)as.integer64(d64))
#T64 <- system.time(as.int64(d64))*1000

```

```

#T64/t64
t64/t32
td64 <- system.time(for(i in 1:1000)as.double(i32))
t64 <- system.time(for(i in 1:1000)as.integer64(i32))
#T64 <- system.time(for(i in 1:10)as.int64(i32))*100
#T64/t64
t64/td64

message("-- integer64 serializes 4x/0.8x faster than int64
  under 64/32 bit OS (and less than 2x/6x the time of integer or double) --")
t32 <- system.time(for(i in 1:10)serialize(i32, NULL))
td64 <- system.time(for(i in 1:10)serialize(d64, NULL))
i64 <- as.integer64(i32);
t64 <- system.time(for(i in 1:10)serialize(i64, NULL))
rm(i64); gc()
#I64 <- as.int64(i32);
#T64 <- system.time(for(i in 1:10)serialize(I64, NULL))
#rm(I64); gc()
#T64/t64
t64/t32
t64/td64

message("-- integer64 adds 250x/60x faster than int64
  under 64/32 bit OS (and less than 6x the time of integer or double) --")
td64 <- system.time(for(i in 1:100)d64+d64)
t32 <- system.time(for(i in 1:100)i32+i32)
i64 <- as.integer64(i32);
t64 <- system.time(for(i in 1:100)i64+i64)
rm(i64); gc()
#I64 <- as.int64(i32);
#T64 <- system.time(for(i in 1:10)I64+I64)*10
#rm(I64); gc()
#T64/t64
t64/t32
t64/td64

message("-- integer64 sums 3x/0.2x faster than int64
  (and at about 5x/60X the time of integer and double) --")
td64 <- system.time(for(i in 1:100)sum(d64))
t32 <- system.time(for(i in 1:100)sum(i32))
i64 <- as.integer64(i32);
t64 <- system.time(for(i in 1:100)sum(i64))
rm(i64); gc()
#I64 <- as.int64(i32);
#T64 <- system.time(for(i in 1:100)sum(I64))
#rm(I64); gc()
#T64/t64
t64/t32
t64/td64

message("-- integer64 diffs 5x/0.85x faster than integer and double
  (int64 version 1.0 does not support diff) --")

```

```

td64 <- system.time(for(i in 1:10)diff(d64, lag=2L, differences=2L))
t32 <- system.time(for(i in 1:10)diff(i32, lag=2L, differences=2L))
i64 <- as.integer64(i32);
t64 <- system.time(for(i in 1:10)diff(i64, lag=2L, differences=2L))
rm(i64); gc()
t64/t32
t64/td64

```

```

message("-- integer64 subscripts 1000x/340x faster than int64
(and at the same speed / 10x slower as integer) --")
ts32 <- system.time(for(i in 1:1000)sample(1e6, 1e3))
t32<- system.time(for(i in 1:1000)i32[sample(1e6, 1e3)])
i64 <- as.integer64(i32);
t64 <- system.time(for(i in 1:1000)i64[sample(1e6, 1e3)])
rm(i64); gc()
#I64 <- as.int64(i32);
#T64 <- system.time(for(i in 1:100)I64[sample(1e6, 1e3)])*10
#rm(I64); gc()
#(T64-ts32)/(t64-ts32)
(t64-ts32)/(t32-ts32)

```

```

message("-- integer64 assigns 200x/90x faster than int64
(and 50x/160x slower than integer) --")
ts32 <- system.time(for(i in 1:100)sample(1e6, 1e3))
t32 <- system.time(for(i in 1:100)i32[sample(1e6, 1e3)] <- 1:1e3)
i64 <- as.integer64(i32);
i64 <- system.time(for(i in 1:100)i64[sample(1e6, 1e3)] <- 1:1e3)
rm(i64); gc()
#I64 <- as.int64(i32);
#I64 <- system.time(for(i in 1:10)I64[sample(1e6, 1e3)] <- 1:1e3)*10
#rm(I64); gc()
#(T64-ts32)/(t64-ts32)
(t64-ts32)/(t32-ts32)

```

```

tdfi32 <- system.time(dfi32 <- data.frame(a=i32, b=i32, c=i32))
tdfsi32 <- system.time(dfi32[1e6:1,])
fi32 <- tempfile()
tdfwi32 <- system.time(write.csv(dfi32, file=fi32, row.names=FALSE))
tdfri32 <- system.time(read.csv(fi32, colClasses=rep("integer", 3)))
unlink(fi32)
rm(dfi32); gc()

```

```

i64 <- as.integer64(i32);
tdfi64 <- system.time(dfi64 <- data.frame(a=i64, b=i64, c=i64))
tdfsi64 <- system.time(dfi64[1e6:1,])
fi64 <- tempfile()
tdfwi64 <- system.time(write.csv(dfi64, file=fi64, row.names=FALSE))
tdfri64 <- system.time(read.csv(fi64, colClasses=rep("integer64", 3)))
unlink(fi64)
rm(i64, dfi64); gc()

```

```

#I64 <- as.int64(i32);
#tdfI64 <- system.time(dfI64<-data.frame(a=I64, b=I64, c=I64))
#tdfsI64 <- system.time(dfI64[1e6:1,])
#fI64 <- tempfile()
#tdfwI64 <- system.time(write.csv(dfI64, file=fI64, row.names=FALSE))
#tdfrI64 <- system.time(read.csv(fI64, colClasses=rep("int64", 3)))
#unlink(fI64)
#rm(I64, dfI64); gc()

message("-- integer64 coerces 40x/6x faster to data.frame than int64
(and factor 1/9 slower than integer) --")
#tdfI64/tdfi64
tdfi64/tdfi32
message("-- integer64 subscripts from data.frame 20x/2.5x faster than int64
(and 3x/13x slower than integer) --")
#tdfsI64/tdfsi64
tdfsi64/tdfsi32
message("-- integer64 csv writes about 2x/0.5x faster than int64
(and about 1.5x/5x slower than integer) --")
#tdfwI64/tdfwi64
tdfwi64/tdfwi32
message("-- integer64 csv reads about 3x/1.5 faster than int64
(and about 2x slower than integer) --")
#tdfrI64/tdfri64
tdfri64/tdfri32

rm(i32, d64); gc()

message("-- investigating the impact on garbage collection: --")
message("-- the fragmented structure of int64 messes up R's RAM --")
message("-- and slows down R's gargbage collection just by existing --")

td32 <- double(21)
td32[1] <- system.time(d64 <- double(1e7))[3]
for (i in 2:11)td32[i] <- system.time(gc(), gcFirst=FALSE)[3]
rm(d64)
for (i in 12:21)td32[i] <- system.time(gc(), gcFirst=FALSE)[3]

t64 <- double(21)
t64[1] <- system.time(i64 <- integer64(1e7))[3]
for (i in 2:11)t64[i] <- system.time(gc(), gcFirst=FALSE)[3]
rm(i64)
for (i in 12:21)t64[i] <- system.time(gc(), gcFirst=FALSE)[3]

#T64 <- double(21)
#T64[1] <- system.time(I64 <- int64(1e7))[3]
#for (i in 2:11)T64[i] <- system.time(gc(), gcFirst=FALSE)[3]
#rm(I64)
#for (i in 12:21)T64[i] <- system.time(gc(), gcFirst=FALSE)[3]

#matplot(1:21, cbind(td32, t64, T64), pch=c("d","i","I"), log="y")
matplot(1:21, cbind(td32, t64), pch=c("d","i"), log="y")

```

```
## End(Not run)
```

---

```
as.character.integer64
```

*Coerce from integer64*

---

## Description

Methods to coerce integer64 to other atomic types. 'as.bitstring' coerces to a human-readable bit representation (strings of zeroes and ones). The methods [format](#), [as.character](#), [as.double](#), [as.logical](#), [as.integer](#) do what you would expect.

## Usage

```
as.bitstring(x, ...)
## S3 method for class 'integer64'
as.bitstring(x, ...)
## S3 method for class 'integer64'
as.character(x, ...)
## S3 method for class 'integer64'
as.double(x, keep.names = FALSE, ...)
## S3 method for class 'integer64'
as.integer(x, ...)
## S3 method for class 'integer64'
as.logical(x, ...)
## S3 method for class 'integer64'
as.factor(x)
## S3 method for class 'integer64'
as.ordered(x)
```

## Arguments

x	an integer64 vector
keep.names	FALSE, set to TRUE to keep a names vector
...	further arguments to the <a href="#">NextMethod</a>

## Value

as.bitstring returns a string of .  
The other methods return atomic vectors of the expected types

## Author(s)

Jens Oehlschlägel <Jens.Oehlschlaegel@truecluster.com>



**See Also**

[as.integer64.character integer64](#)

**Examples**

```
as.character(lim.integer64())
as.bitstring(lim.integer64())
```

---

```
as.data.frame.integer64
```

*integer64: Coercing to data.frame column*

---

**Description**

Coercing integer64 vector to data.frame.

**Usage**

```
## S3 method for class 'integer64'
as.data.frame(x, ...)
```

**Arguments**

x	an integer64 vector
...	passed to NextMethod <a href="#">as.data.frame</a> after removing the 'integer64' class attribute

**Details**

'as.data.frame.integer64' is rather not intended to be called directly, but it is required to allow integer64 as data.frame columns.

**Value**

a one-column data.frame containing an integer64 vector

**Note**

This is currently very slow – any ideas for improvement?

**Author(s)**

Jens Oehlschlägel <Jens.Oehlschlaegel@truecluster.com>

**See Also**

[cbind.integer64 integer64](#)

**Examples**

```
as.data.frame.integer64(as.integer64(1:12))
data.frame(a=1:12, b=as.integer64(1:12))
```

---

```
as.integer64.character
```

*Coerce to integer64*

---

**Description**

Methods to coerce from other atomic types to integer64.

**Usage**

```
NA_integer64_
as.integer64(x, ...)
## S3 method for class 'integer64'
as.integer64(x, ...)
## S3 method for class 'NULL'
as.integer64(x, ...)
## S3 method for class 'character'
as.integer64(x, ...)
## S3 method for class 'double'
as.integer64(x, keep.names = FALSE, ...)
## S3 method for class 'integer'
as.integer64(x, ...)
## S3 method for class 'logical'
as.integer64(x, ...)
## S3 method for class 'factor'
as.integer64(x, ...)
```

**Arguments**

x	an atomic vector
keep.names	FALSE, set to TRUE to keep a names vector
...	further arguments to the <a href="#">NextMethod</a>

**Details**

as.integer64.character is realized using C function strtoll which does not support scientific notation. Instead of '1e6' use '1000000'.

**Value**

The other methods return atomic vectors of the expected types

**Author(s)**

Jens Oehlschlägel <Jens.Oehlschlaegel@truecluster.com>

**See Also**

[as.character.integer64](#) [integer64](#)

**Examples**

```
as.integer64(as.character(lim.integer64()))
```

---

benchmark64

*Function for measuring algorithmic performance  
of high-level and low-level integer64 functions*

---

**Description**

benchmark64 compares high-level integer64 functions against the integer functions from Base R  
optimizer64 compares for each high-level integer64 function the Base R integer function with  
several low-level integer64 functions with and without caching

**Usage**

```
benchmark64(nsmall = 2^16, nbig = 2^25, timefun = repeat.time
)
optimizer64(nsmall = 2^16, nbig = 2^25, timefun = repeat.time
, what = c("match", "%in%", "duplicated", "unique", "unipos", "table", "rank", "quantile")
, uniorder = c("original", "values", "any")
, taborder = c("values", "counts")
, plot = TRUE
)
```

**Arguments**

nsmall	size of smaller vector
nbig	size of larger bigger vector
timefun	a function for timing such as <a href="#">repeat.time</a> or <a href="#">system.time</a>
what	a vector of names of high-level functions
uniorder	one of the order parameters that are allowed in <a href="#">unique.integer64</a> and <a href="#">unipos.integer64</a>
taborder	one of the order parameters that are allowed in <a href="#">table.integer64</a>
plot	set to FALSE to suppress plotting

**Details**

benchmark64 compares the following scenarios for the following use cases:

scenario name	explanation
32-bit	applying Base R function to 32-bit integer data
64-bit	applying bit64 function to 64-bit integer data (with no cache)
hashcache	dito when cache contains <a href="#">hashmap</a> , see <a href="#">hashcache</a>
sortordercache	dito when cache contains sorting and ordering, see <a href="#">sortordercache</a>
ordercache	dito when cache contains ordering only, see <a href="#">ordercache</a>
allcache	dito when cache contains sorting, ordering and hashing

use case name	explanation
cache	filling the cache according to scenario
match(s,b)	match small in big vector
s %in% b	small %in% big vector
match(b,s)	match big in small vector
b %in% s	big %in% small vector
match(b,b)	match big in (different) big vector
b %in% b	big %in% (different) big vector
duplicated(b)	duplicated of big vector
unique(b)	unique of big vector
table(b)	table of big vector
sort(b)	sorting of big vector
order(b)	ordering of big vector
rank(b)	ranking of big vector
quantile(b)	quantiles of big vector
summary(b)	summary of of big vector
SESSION	exemplary session involving multiple calls (including cache filling costs)

Note that the timings for the cached variants do *not* contain the time costs of building the cache, except for the timing of the exemplary user session, where the cache costs are included in order to evaluate amortization.

## Value

benchmark64 returns a matrix with elapsed seconds, different high-level tasks in rows and different scenarios to solve the task in columns. The last row named 'SESSION' contains the elapsed seconds of the exemplary session.

optimizer64 returns a dimensioned list with one row for each high-level function timed and two columns named after the values of the nsmall and nbig sample sizes. Each list cell contains a matrix with timings, low-level-methods in rows and three measurements c("prep", "both", "use") in columns. If it can be measured separately, prep contains the timing of preparatory work such as sorting and hashing, and use contains the timing of using the prepared work. If the function timed does both, preparation and use, the timing is in both.

## Author(s)

Jens Oehlschlägel <Jens.Oehlschlaegel@truecluster.com>

**See Also**[integer64](#)**Examples**

```

message("this small example using system.time does not give serious timings\n
this we do this only to run regression tests")
benchmark64(nsmall=2^7, nbig=2^13, timefun=function(expr)system.time(expr, gcFirst=FALSE))
optimizer64(nsmall=2^7, nbig=2^13, timefun=function(expr)system.time(expr, gcFirst=FALSE)
, plot=FALSE
)
## Not run:
message("for real measurement of sufficiently large datasets run this on your machine")
benchmark64()
optimizer64()

## End(Not run)
message("let's look at the performance results on Core i7 Lenovo T410 with 8 GB RAM")
data(benchmark64.data)
print(benchmark64.data)

matplot(log2(benchmark64.data[-1,1]/benchmark64.data[-1,])
, pch=c("3", "6", "h", "s", "o", "a")
, xlab="tasks [last=session]"
, ylab="log2(relative speed) [bigger is better]"
)
matplot(t(log2(benchmark64.data[-1,1]/benchmark64.data[-1,]))
, type="b", axes=FALSE
, lwd=c(rep(1, 14), 3)
, xlab="context"
, ylab="log2(relative speed) [bigger is better]"
)
axis(1
, labels=c("32-bit", "64-bit", "hash", "sortorder", "order", "hash+sortorder")
, at=1:6
)
axis(2)
data(optimizer64.data)
print(optimizer64.data)
oldpar <- par(no.readonly = TRUE)
par(mfrow=c(2,1))
par(cex=0.7)
for (i in 1:nrow(optimizer64.data)){
  for (j in 1:2){
    tim <- optimizer64.data[[i,j]]
    barplot(t(tim))
    if (rownames(optimizer64.data)[i]=="match")
      title(paste("match", colnames(optimizer64.data)[j], "in", colnames(optimizer64.data)[3-j]))
    else if (rownames(optimizer64.data)[i]=="in%")
      title(paste(colnames(optimizer64.data)[j], "%in%", colnames(optimizer64.data)[3-j]))
    else
      title(paste(rownames(optimizer64.data)[i], colnames(optimizer64.data)[j]))
  }
}

```

```

}
}
par(mfrow=c(1,1))

```

---

benchmark64.data	<i>Results of performance measurement on a Core i7 Lenovo T410 8 GB RAM under Windows 7 64bit</i>
------------------	---

---

## Description

These are the results of calling [benchmark64](#)

## Usage

```
data(benchmark64.data)
```

## Format

The format is: num [1:16, 1:6] 2.55e-05 2.37 2.39 1.28 1.39 ... - attr(\*, "dimnames")=List of 2 ..\$ : chr [1:16] "cache" "match(s,b)" "s %in% b" "match(b,s)" ... ..\$ : chr [1:6] "32-bit" "64-bit" "hashcache" "sortordercache" ...

## Examples

```

data(benchmark64.data)
print(benchmark64.data)
matplot(log2(benchmark64.data[-1,1]/benchmark64.data[-1,])
, pch=c("3", "6", "h", "s", "o", "a")
, xlab="tasks [last=session]"
, ylab="log2(relative speed) [bigger is better]"
)
matplot(t(log2(benchmark64.data[-1,1]/benchmark64.data[-1,]))
, axes=FALSE
, type="b"
, lwd=c(rep(1, 14), 3)
, xlab="context"
, ylab="log2(relative speed) [bigger is better]"
)
axis(1
, labels=c("32-bit", "64-bit", "hash", "sortorder", "order", "hash+sortorder")
, at=1:6
)
axis(2)

```

**Description**

Turn those base functions S3 generic which are used in bit64

**Usage**

```

from:to
  #--as-cran complains about \method{:}{default}(from, to)
  #--as-cran complains about \method{:}{integer64}(from, to)
is.double(x)
  ## Default S3 method:
is.double(x)
  ## S3 method for class 'integer64'
is.double(x)
match(x, table, ...)
  ## Default S3 method:
match(x, table, ...)
x %in% table
  ## Default S3 method:
x %in% table
rank(x, ...)
  ## Default S3 method:
rank(x, ...)

order(...)
  ## Default S3 method:
order(...)

```

**Arguments**

x	integer64 vector: the values to be matched, optionally carrying a cache created with <a href="#">hashcache</a>
table	integer64 vector: the values to be matched against, optionally carrying a cache created with <a href="#">hashcache</a> or <a href="#">sortordercache</a>
from	scalar denoting first element of sequence
to	scalar denoting last element of sequence
...	ignored

**Details**

The following functions are turned into S3 generics in order to dispatch methods for [integer64](#):

```
\code{\link{:}}
\code{\link{is.double}}
\code{\link{match}}
\code{\link{%in%}}

\code{\link{rank}}
\code{\link{order}}
```

## Value

[invisible](#)

## Note

[is.double](#) returns FALSE for [integer64](#)  
: currently only dispatches at its first argument, thus `as.integer64(1):9` works but `1:as.integer64(9)` doesn't [match](#) currently only dispatches at its first argument and expects its second argument also to be [integer64](#), otherwise throws an error. Beware of something like `match(2, as.integer64(0:3))`  
[%in%](#) currently only dispatches at its first argument and expects its second argument also to be [integer64](#), otherwise throws an error. Beware of something like `2 %in% as.integer64(0:3)` [order](#) currently only orders a single argument, trying more than one raises an error

## Author(s)

Jens Oehlschlägel <Jens.Oehlschlaegel@truecluster.com>

## See Also

[bit64](#), [S3](#)

## Examples

```
is.double(as.integer64(1))
as.integer64(1):9
match(as.integer64(2), as.integer64(0:3))
as.integer64(2) %in% as.integer64(0:3)
```

```
unique(as.integer64(c(1,1,2)))
rank(as.integer64(c(1,1,2)))
```

```
order(as.integer64(c(1,NA,2)))
```



---

`c.integer64`*Concatenating integer64 vectors*

---

**Description**

The usual functions 'c', 'cbind' and 'rbind'

**Usage**

```
## S3 method for class 'integer64'  
c(..., recursive = FALSE)  
## S3 method for class 'integer64'  
cbind(...)  
## S3 method for class 'integer64'  
rbind(...)
```

**Arguments**

...	two or more arguments coerced to 'integer64' and passed to <a href="#">NextMethod</a>
recursive	logical. If recursive = TRUE, the function recursively descends through lists (and pairlists) combining all their elements into a vector.

**Value**

`c` returns a integer64 vector of the total length of the input  
`cbind` and `rbind` return a integer64 matrix

**Note**

R currently only dispatches generic 'c' to method 'c.integer64' if the first argument is 'integer64'

**Author(s)**

Jens Oehlschlägel <Jens.Oehlschlaegel@truecluster.com>

**See Also**

[rep.integer64](#) [seq.integer64](#) [as.data.frame.integer64](#) [integer64](#)

**Examples**

```
c(as.integer64(1), 2:6)  
cbind(1:6, as.integer(1:6))  
rbind(1:6, as.integer(1:6))
```

---

 cache

*Atomic Caching*


---

## Description

Functions for caching results attached to atomic objects

## Usage

```

newcache(x)
jamcache(x)
cache(x)
setcache(x, which, value)
getcache(x, which)
remcache(x)
## S3 method for class 'cache'
print(x, all.names = FALSE, pattern, ...)
still.identical(x, y)

```

## Arguments

<code>x</code>	an integer64 vector (or a cache object in case of <code>print.cache</code> )
<code>y</code>	an integer64 vector
<code>which</code>	A character naming the object to be retrieved from the cache or to be stored in the cache
<code>value</code>	An object to be stored in the cache
<code>all.names</code>	passed to <code>ls</code> when listing the cache content
<code>pattern</code>	passed to <code>ls</code> when listing the cache content
<code>...</code>	ignored

## Details

A cache is an `link{environment}` attached to an atomic object with the `link{attrib}` name 'cache'. It contains at least a reference to the atomic object that carries the cache. This is used when accessing the cache to detect whether the object carrying the cache has been modified meanwhile.

Function `still.identical(x,y)` checks whether the objects `x` and `y`

Function `newcache(x)` creates a new cache referencing `x`

Function `jamcache(x)` forces `x` to have a cache

Function `cache(x)` returns the cache attached to `x` if it is not found to be outdated

Function `setcache(x, which, value)` assigns a value into the cache of `x`

Function `getcache(x, which)` gets cache value 'which' from `x`

Function `remcache` removes the cache from `x`

**Value**

see details

**Author(s)**

Jens Oehlschlägel <Jens.Oehlschlaegel@truecluster.com>

**See Also**

Functions that get and set small cache-content automatically when a cache is present: [na.count](#), [nvalid](#), [is.sorted](#), [nunique](#) and [nties](#)

Setting big caches with a relevant memory footprint requires a conscious decision of the user: [hashcache](#), [sortcache](#), [ordercache](#) and [sortordercache](#)

Functions that use big caches: [match.integer64](#), [%in%.integer64](#), [duplicated.integer64](#), [unique.integer64](#), [unipos](#), [table.integer64](#), [as.factor.integer64](#), [as.ordered.integer64](#), [keypos](#), [tiepos](#), [rank.integer64](#), [prank](#), [qtile](#), [quantile.integer64](#), [median.integer64](#) and [summary.integer64](#)

**Examples**

```
x <- as.integer64(sample(c(rep(NA, 9), 1:9), 32, TRUE))
y <- x
still.identical(x,y)
y[1] <- NA
still.identical(x,y)
mycache <- newcache(x)
ls(mycache)
mycache
rm(mycache)
jamcache(x)
cache(x)
x[1] <- NA
cache(x)
getcache(x, "abc")
setcache(x, "abc", 1)
getcache(x, "abc")
remcache(x)
cache(x)
```

**Description**

Cumulative Sums, Products, Extremes and lagged differences

**Usage**

```
## S3 method for class 'integer64'  
cummin(x)  
## S3 method for class 'integer64'  
cummax(x)  
## S3 method for class 'integer64'  
cumsum(x)  
## S3 method for class 'integer64'  
cumprod(x)  
## S3 method for class 'integer64'  
diff(x, lag = 1L, differences = 1L, ...)
```

**Arguments**

x	an atomic vector of class 'integer64'
lag	see <a href="#">diff</a>
differences	see <a href="#">diff</a>
...	ignored

**Value**

[cummin](#), [cummax](#), [cumsum](#) and [cumprod](#) return a integer64 vector of the same length as their input  
[diff](#) returns a integer64 vector shorter by lag\*differences elements

**Author(s)**

Jens Oehlschlägel <Jens.Oehlschlaegel@truecluster.com>

**See Also**

[sum.integer64](#) [integer64](#)

**Examples**

```
cumsum(rep(as.integer64(1), 12))  
diff(as.integer64(c(0,1:12)))  
cumsum(as.integer64(c(0, 1:12)))  
diff(cumsum(as.integer64(c(0,0,1:12))), differences=2)
```

---

duplicated.integer64 *Determine Duplicate Elements of integer64*

---

### Description

duplicated() determines which elements of a vector or data frame are duplicates of elements with smaller subscripts, and returns a logical vector indicating which elements (rows) are duplicates.

### Usage

```
## S3 method for class 'integer64'  
duplicated(x, incomparables = FALSE, nunique = NULL, method = NULL, ...)
```

### Arguments

x	a vector or a data frame or an array or NULL.
incomparables	ignored
nunique	NULL or the number of unique values (including NA). Providing nunique can speed-up matching when x has no cache. Note that a wrong nunique can cause undefined behaviour up to a crash.
method	NULL for automatic method selection or a suitable low-level method, see details
...	ignored

### Details

This function automatically chooses from several low-level functions considering the size of x and the availability of a cache.

Suitable methods are [hashdup](#) (hashing), [sortorderdup](#) (fast ordering) and [orderdup](#) (memory saving ordering).

### Value

duplicated(): a logical vector of the same length as x.

### Author(s)

Jens Oehlschlägel <Jens.Oehlschlaegel@truecluster.com>

### See Also

[duplicated](#), [unique.integer64](#)

### Examples

```
x <- as.integer64(sample(c(rep(NA, 9), 1:9), 32, TRUE))  
duplicated(x)  
  
stopifnot(identical(duplicated(x), duplicated(as.integer(x))))
```

---

`extract.replace.integer64`*Extract or Replace Parts of an integer64 vector*

---

## Description

Methods to extract and replace parts of an integer64 vector.

## Usage

```
## S3 method for class 'integer64'  
x[...]  
## S3 replacement method for class 'integer64'  
x[...] <- value  
## S3 method for class 'integer64'  
x[[...]]  
## S3 replacement method for class 'integer64'  
x[[...]] <- value
```

## Arguments

<code>x</code>	an atomic vector
<code>value</code>	an atomic vector with values to be assigned
<code>...</code>	further arguments to the <a href="#">NextMethod</a>

## Value

A vector or scalar of class 'integer64'

## Note

You should not subscript non-existing elements and not use NAs as subscripts. The current implementation returns 9218868437227407266 instead of NA.

## Author(s)

Jens Oehlschlägel <Jens.Oehlschlaegel@truecluster.com>

## See Also

[ [integer64](#) ]

**Examples**

```
as.integer64(1:12)[1:3]
x <- as.integer64(1:12)
dim(x) <- c(3,4)
x
x[]
x[,2:3]
```

---

format.integer64

*Unary operators and functions for integer64 vectors*

---

**Description**

Unary operators and functions for integer64 vectors.

**Usage**

```
## S3 method for class 'integer64'
format(x, justify="right", ...)
## S3 method for class 'integer64'
is.na(x)
## S3 method for class 'integer64'
is.nan(x)
## S3 method for class 'integer64'
is.finite(x)
## S3 method for class 'integer64'
is.infinite(x)
## S3 method for class 'integer64'
!x
## S3 method for class 'integer64'
sign(x)
## S3 method for class 'integer64'
abs(x)
## S3 method for class 'integer64'
sqrt(x)
## S3 method for class 'integer64'
log(x, base)
## S3 method for class 'integer64'
log2(x)
## S3 method for class 'integer64'
log10(x)
## S3 method for class 'integer64'
floor(x)
## S3 method for class 'integer64'
ceiling(x)
## S3 method for class 'integer64'
trunc(x, ...)
```

```
## S3 method for class 'integer64'  
round(x, digits=0)  
## S3 method for class 'integer64'  
signif(x, digits=6)  
## S3 method for class 'integer64'  
scale(x, center = TRUE, scale = TRUE)
```

### Arguments

x	an atomic vector of class 'integer64'
base	an atomic scalar (we save 50% log-calls by not allowing a vector base)
digits	integer indicating the number of decimal places (round) or significant digits (signif) to be used. Negative values are allowed (see <a href="#">round</a> )
justify	should it be right-justified (the default), left-justified, centred or left alone.
center	see <a href="#">scale</a>
scale	see <a href="#">scale</a>
...	further arguments to the <a href="#">NextMethod</a>

### Value

[format](#) returns a character vector  
[is.na](#) and [!](#) return a logical vector  
[sqrt](#), [log](#), [log2](#) and [log10](#) return a double vector  
[sign](#), [abs](#), [floor](#), [ceiling](#), [trunc](#) and [round](#) return a vector of class 'integer64'  
[signif](#) is not implemented

### Author(s)

Jens Oehlschlägel <Jens.Oehlschlaegel@truecluster.com>

### See Also

[xor.integer64](#) [integer64](#)

### Examples

```
sqrt(as.integer64(1:12))
```



---

hashcache *Big caching of hashing, sorting, ordering*

---

### Description

Functions to create cache that accelerates many operations

### Usage

```
hashcache(x, nunique=NULL, ...)
sortcache(x, has.na = NULL)
sortordercache(x, has.na = NULL, stable = NULL)
ordercache(x, has.na = NULL, stable = NULL, optimize = "time")
```

### Arguments

x	an atomic vector (note that currently only integer64 is supported)
nunique	giving <i>correct</i> number of unique elements can help reducing the size of the hashmap
has.na	boolean scalar defining whether the input vector might contain NAs. If we know we don't have NAs, this may speed-up. <i>Note</i> that you risk a crash if there are unexpected NAs with has.na=FALSE
stable	boolean scalar defining whether stable sorting is needed. Allowing non-stable may speed-up.
optimize	by default ramsort optimizes for 'time' which requires more RAM, set to 'memory' to minimize RAM requirements and sacrifice speed
...	passed to <a href="#">hashmap</a>

### Details

The result of relative expensive operations [hashmap](#), [ramsort](#), [ramsortorder](#) and [ramorder](#) can be stored in a cache in order to avoid multiple executions. Unless in very specific situations, the recommended method is [hashsortorder](#) only.

### Value

x with a [cache](#) that contains the result of the expensive operations, possible together with small derived information (such as [nunique.integer64](#)) and previously cached results.

### Note

Note that we consider storing the big results from sorting and/or ordering as a relevant side-effect, and therefore storing them in the cache should require a conscious decision of the user.

### Author(s)

Jens Oehlschlägel <Jens.Oehlschlaegel@truecluster.com>

**See Also**

[cache](#) for caching functions and [nunique](#) for methods benefiting from small caches

**Examples**

```
x <- as.integer64(sample(c(rep(NA, 9), 1:9), 32, TRUE))
sortordercache(x)
```

---

 hashmap

*Hashing for 64bit integers*


---

**Description**

This is an explicit implementation of hash functionality that underlies matching and other functions in R. Explicit means that you can create, store and use hash functionality directly. One advantage is that you can re-use hashmaps, which avoid re-building hashmaps again and again.

**Usage**

```
hashfun(x, ...)
## S3 method for class 'integer64'
hashfun(x, minfac=1.41, hashbits=NULL, ...)
hashmap(x, ...)
## S3 method for class 'integer64'
hashmap(x, nunique=NULL, minfac=1.41, hashbits=NULL, cache=NULL, ...)
hashpos(cache, ...)
## S3 method for class 'cache_integer64'
hashpos(cache, x, nomatch = NA_integer_, ...)
hashrev(cache, ...)
## S3 method for class 'cache_integer64'
hashrev(cache, x, nomatch = NA_integer_, ...)
hashfin(cache, ...)
## S3 method for class 'cache_integer64'
hashfin(cache, x, ...)
hashrin(cache, ...)
## S3 method for class 'cache_integer64'
hashrin(cache, x, ...)
hashdup(cache, ...)
## S3 method for class 'cache_integer64'
hashdup(cache, ...)
hashuni(cache, ...)
## S3 method for class 'cache_integer64'
hashuni(cache, keep.order=FALSE, ...)
hashmapuni(x, ...)
## S3 method for class 'integer64'
hashmapuni(x, nunique=NULL, minfac=1.5, hashbits=NULL, ...)
hashupo(cache, ...)
```

```

## S3 method for class 'cache_integer64'
hashupo(cache, keep.order=FALSE, ...)
hashmapupo(x, ...)
## S3 method for class 'integer64'
hashmapupo(x, nunique=NULL, minfac=1.5, hashbits=NULL, ...)
hashtab(cache, ...)
## S3 method for class 'cache_integer64'
hashtab(cache, ...)
hashmaptab(x, ...)
## S3 method for class 'integer64'
hashmaptab(x, nunique=NULL, minfac=1.5, hashbits=NULL, ...)

```

### Arguments

x	an integer64 vector
hashmap	an object of class 'hashmap' i.e. here 'cache_integer64'
minfac	minimum factor by which the hashmap has more elements compared to the data x, ignored if hashbits is given directly
hashbits	length of hashmap is 2 <sup>hashbits</sup>
cache	an optional <a href="#">cache</a> object into which to put the hashmap (by default a new cache is created)
nunique	giving <i>correct</i> number of unique elements can help reducing the size of the hashmap
nomatch	the value to be returned if an element is not found in the hashmap
keep.order	determines order of results and speed: FALSE (the default) is faster and returns in the (pseudo)random order of the hash function, TRUE returns in the order of first appearance in the original data, but this requires extra work
...	further arguments, passed from generics, ignored in methods

### Details

function	see also	description
hashfun	<a href="#">digest</a>	export of the hash function used in hashmap
hashmap	<a href="#">match</a>	return hashmap
hashpos	<a href="#">match</a>	return positions of x in hashmap
hashrev	<a href="#">match</a>	return positions of hashmap in x
hashfin	<a href="#">%in%.integer64</a>	return logical whether x is in hashmap
hashrin	<a href="#">%in%.integer64</a>	return logical whether hashmap is in x
hashdup	<a href="#">duplicated</a>	return logical whether hashdat is duplicated using hashmap
hashuni	<a href="#">unique</a>	return unique values of hashmap
hashmapuni	<a href="#">unique</a>	return unique values of x
hashupo	<a href="#">unique</a>	return positions of unique values in hashdat
hashmapupo	<a href="#">unique</a>	return positions of unique values in x
hashtab	<a href="#">table</a>	tabulate values of hashdat using hashmap in keep.order=FALSE
hashmaptab	<a href="#">table</a>	tabulate values of x building hashmap on the fly in keep.order=FALSE

**Value**

see details

**Author(s)**

Jens Oehlschlägel <Jens.Oehlschlaegel@truecluster.com>

**See Also**

[match](#)

**Examples**

```
x <- as.integer64(sample(c(NA, 0:9)))
y <- as.integer64(sample(c(NA, 1:9), 10, TRUE))
hashfun(y)
hx <- hashmap(x)
hy <- hashmap(y)
ls(hy)
hashpos(hy, x)
hashrev(hx, y)
hashfin(hy, x)
hashrin(hx, y)
hashdup(hy)
hashuni(hy)
hashuni(hy, keep.order=TRUE)
hashmapuni(y)
hashupo(hy)
hashupo(hy, keep.order=TRUE)
hashmapupo(y)
hashtab(hy)
hashmptab(y)

stopifnot(identical(match(as.integer(x),as.integer(y)),hashpos(hy, x)))
stopifnot(identical(match(as.integer(x),as.integer(y)),hashrev(hx, y)))
stopifnot(identical(as.integer(x) %in% as.integer(y), hashfin(hy, x)))
stopifnot(identical(as.integer(x) %in% as.integer(y), hashrin(hx, y)))
stopifnot(identical(duplicated(as.integer(y)), hashdup(hy)))
stopifnot(identical(as.integer64(unique(as.integer(y))), hashuni(hy, keep.order=TRUE)))
stopifnot(identical(sort(hashuni(hy, keep.order=FALSE)), sort(hashuni(hy, keep.order=TRUE))))
stopifnot(identical(y[hashupo(hy, keep.order=FALSE)], hashuni(hy, keep.order=FALSE)))
stopifnot(identical(y[hashupo(hy, keep.order=TRUE)], hashuni(hy, keep.order=TRUE)))
stopifnot(identical(hashpos(hy, hashuni(hy, keep.order=TRUE)), hashupo(hy, keep.order=TRUE)))
stopifnot(identical(hashpos(hy, hashuni(hy, keep.order=FALSE)), hashupo(hy, keep.order=FALSE)))
stopifnot(identical(hashuni(hy, keep.order=FALSE), hashtab(hy)$values))
stopifnot(identical(as.vector(table(as.integer(y), useNA="ifany"))
, hashtab(hy)$counts[order.integer64(hashtab(hy)$values)]))
stopifnot(identical(hashuni(hy, keep.order=TRUE), hashmapuni(y)))
stopifnot(identical(hashupo(hy, keep.order=TRUE), hashmapupo(y)))
```

```

stopifnot(identical(hashtab(hy), hashmaptab(y)))

## Not run:
message("explore speed given size of the hasmap in 2^hashbits and size of the data")
message("more hashbits means more random access and less collisions")
message("i.e. more data means less random access and more collisions")
bits <- 24
b <- seq(-1, 0, 0.1)
tim <- matrix(NA, length(b), 2, dimnames=list(b, c("bits", "bits+1")))
  for (i in 1:length(b)){
    n <- as.integer(2^(bits+b[i]))
    x <- as.integer64(sample(n))
    tim[i,1] <- repeat.time(hashmap(x, hashbits=bits))[3]
    tim[i,2] <- repeat.time(hashmap(x, hashbits=bits+1))[3]
    print(tim)
    matplot(b, tim)
  }
message("we conclude that n*sqrt(2) is enough to avoid collisions")

## End(Not run)

```

---

identical.integer64    *Identity function for class 'integer64'*

---

## Description

This will discover any deviation between objects containing integer64 vectors.

## Usage

```

identical.integer64(x, y, num.eq = FALSE, single.NA = FALSE
, attrib.as.set = TRUE, ignore.bytecode = TRUE)

```

## Arguments

x	atomic vector of class 'integer64'
y	atomic vector of class 'integer64'
num.eq	see <a href="#">identical</a>
single.NA	see <a href="#">identical</a>
attrib.as.set	see <a href="#">identical</a>
ignore.bytecode	see <a href="#">identical</a>

## Details

This is simply a wrapper to [identical](#) with default arguments num.eq = FALSE, single.NA = FALSE.

**Value**

A single logical value, TRUE or FALSE, never NA and never anything other than a single value.

**Author(s)**

Jens Oehlschlägel <Jens.Oehlschlaegel@truecluster.com>

**See Also**

[==.integer64 identical integer64](#)

**Examples**

```
i64 <- as.double(NA); class(i64) <- "integer64"
identical(i64-1, i64+1)
identical.integer64(i64-1, i64+1)
```

---

is.sorted.integer64    *Small cache access methods*

---

**Description**

These methods are packaged here for methods in packages bit64 and ff.

**Usage**

```
## S3 method for class 'integer64'
is.sorted(x, ...)
## S3 method for class 'integer64'
na.count(x, ...)
## S3 method for class 'integer64'
nvalid(x, ...)
## S3 method for class 'integer64'
nunique(x, ...)
## S3 method for class 'integer64'
nties(x, ...)
```

**Arguments**

x	some object
...	ignored

## Details

All these functions benefit from a [sortcache](#), [ordercache](#) or [sortordercache](#). `na.count`, `nvalid` and `nunique` also benefit from a [hashcache](#).

`is.sorted` checks for sortedness of `x` (NAs sorted first)

`na.count` returns the number of NAs

`nvalid` returns the number of valid data points, usually `length` minus `na.count`.

`nunique` returns the number of unique values

`nties` returns the number of tied values.

## Value

`is.sorted` returns a logical scalar, the other methods return an integer scalar.

## Note

If a [cache](#) exists but the desired value is not cached, then these functions will store their result in the cache. We do not consider this a relevant side-effect, since these small cache results do not have a relevant memory footprint.

## Author(s)

Jens Oehlschlägel <Jens.Oehlschlaegel@truecluster.com>

## See Also

[cache](#) for caching functions and [sortordercache](#) for functions creating big caches

## Examples

```
x <- as.integer64(sample(c(rep(NA, 9), 1:9), 32, TRUE))
length(x)
na.count(x)
nvalid(x)
nunique(x)
nties(x)
table.integer64(x)
x
```

---

keypos

*Extract Positions in redundant dimension table*

---

## Description

`keypos` returns the positions of the (fact table) elements that participate in their sorted unique subset (dimension table)

## Usage

```
keypos(x, ...)  
## S3 method for class 'integer64'  
keypos(x, method = NULL, ...)
```

## Arguments

x	a vector or a data frame or an array or NULL.
method	NULL for automatic method selection or a suitable low-level method, see details
...	ignored

## Details

NAs are sorted first in the dimension table, see [ramorder.integer64](#).

This function automatically chooses from several low-level functions considering the size of x and the availability of a cache. Suitable methods are [sortorderkey](#) (fast ordering) and [orderkey](#) (memory saving ordering).

## Value

an integer vector of the same length as codex containing positions relativ to codesort(unique(x), na.last=FALSE)

## Author(s)

Jens Oehlschlägel <Jens.Oehlschlaegel@truecluster.com>

## See Also

[unique.integer64](#) for the unique subset and [match.integer64](#) for finding positions in a different vector.

## Examples

```
x <- as.integer64(sample(c(rep(NA, 9), 1:9), 32, TRUE))  
keypos(x)  
  
stopifnot(identical(keypos(x), match.integer64(x, sort(unique(x), na.last=FALSE))))
```



---

match.integer64	<i>64-bit integer matching</i>
-----------------	--------------------------------

---

### Description

match returns a vector of the positions of (first) matches of its first argument in its second.

%in% is a more intuitive interface as a binary operator, which returns a logical vector indicating if there is a match or not for its left operand.

### Usage

```
## S3 method for class 'integer64'
match(x, table, nomatch = NA_integer_, nunique = NULL, method = NULL, ...)
## S3 method for class 'integer64'
x %in% table, ...
```

### Arguments

x	integer64 vector: the values to be matched, optionally carrying a cache created with <a href="#">hashcache</a>
table	integer64 vector: the values to be matched against, optionally carrying a cache created with <a href="#">hashcache</a> or <a href="#">sortordercache</a>
nomatch	the value to be returned in the case when no match is found. Note that it is coerced to integer.
nunique	NULL or the number of unique values of table (including NA). Providing nunique can speed-up matching when table has no cache. Note that a wrong nunique can cause undefined behaviour up to a crash.
method	NULL for automatic method selection or a suitable low-level method, see details
...	ignored

### Details

These functions automatically choose from several low-level functions considering the size of x and table and the availability of caches.

Suitable methods for %in%.integer64 are [hashpos](#) (hash table lookup), [hashrev](#) (reverse lookup), [sortorderpos](#) (fast ordering) and [orderpos](#) (memory saving ordering). Suitable methods for match.integer64 are [hashfin](#) (hash table lookup), [hashrin](#) (reverse lookup), [sortfin](#) (fast sorting) and [orderfin](#) (memory saving ordering).

### Value

A vector of the same length as x.

match: An integer vector giving the position in table of the first match if there is a match, otherwise nomatch.

If  $x[i]$  is found to equal  $table[j]$  then the value returned in the  $i$ -th position of the return value is  $j$ , for the smallest possible  $j$ . If no match is found, the value is `nomatch`.

`%in%`: A logical vector, indicating if a match was located for each element of  $x$ : thus the values are TRUE or FALSE and never NA.

### Author(s)

Jens Oehlschlägel <Jens.Oehlschlaegel@truecluster.com>

### See Also

[match](#)

### Examples

```
x <- as.integer64(c(NA, 0:9), 32)
table <- as.integer64(c(1:9, NA))
match.integer64(x, table)
"%in%.integer64"(x, table)

x <- as.integer64(sample(c(rep(NA, 9), 0:9), 32, TRUE))
table <- as.integer64(sample(c(rep(NA, 9), 1:9), 32, TRUE))
stopifnot(identical(match.integer64(x, table), match(as.integer(x), as.integer(table))))
stopifnot(identical("%in%.integer64"(x, table), as.integer(x) %in% as.integer(table)))

## Not run:
message("check when reverse hash-lookup beats standard hash-lookup")
e <- 4:24
timx <- timy <- matrix(NA, length(e), length(e), dimnames=list(e,e))
for (iy in seq_along(e))
  for (ix in 1:iy){
    nx <- 2^e[ix]
    ny <- 2^e[iy]
    x <- as.integer64(sample(ny, nx, FALSE))
    y <- as.integer64(sample(ny, ny, FALSE))
    #hashfun(x, bits=as.integer(5))
    timx[ix,iy] <- repeat.time({
      hx <- hashmap(x)
      py <- hashrev(hx, y)
    })[3]
    timy[ix,iy] <- repeat.time({
      hy <- hashmap(y)
      px <- hashpos(hy, x)
    })[3]
    #identical(px, py)
    print(round(timx[1:iy,1:iy]/timy[1:iy,1:iy], 2), na.print="")
  }

message("explore best low-level method given size of x and table")
B1 <- 1:27
B2 <- 1:27
tim <- array(NA, dim=c(length(B1), length(B2), 5))
```

```

, dimnames=list(B1, B2, c("hashpos", "hashrev", "sortpos1", "sortpos2", "sortpos3")))
for (i1 in B1)
for (i2 in B2)
{
  b1 <- B1[i1]
  b2 <- B1[i2]
  n1 <- 2^b1
  n2 <- 2^b2
  x1 <- as.integer64(c(sample(n2, n1-1, TRUE), NA))
  x2 <- as.integer64(c(sample(n2, n2-1, TRUE), NA))
  tim[i1,i2,1] <- repeat.time({h <- hashmap(x2);hashpos(h, x1);rm(h)})[3]
  tim[i1,i2,2] <- repeat.time({h <- hashmap(x1);hashrev(h, x2);rm(h)})[3]
  s <- clone(x2); o <- seq_along(s); ramsortorder(s, o)
  tim[i1,i2,3] <- repeat.time(sortorderpos(s, o, x1, method=1))[3]
  tim[i1,i2,4] <- repeat.time(sortorderpos(s, o, x1, method=2))[3]
  tim[i1,i2,5] <- repeat.time(sortorderpos(s, o, x1, method=3))[3]
  rm(s,o)
  print(apply(tim, 1:2, function(ti)if(any(is.na(ti)))NA else which.min(ti)))
}

## End(Not run)

```

optimizer64.data

*Results of performance measurement on a Core i7 Lenovo T410 8 GB  
RAM under Windows 7 64bit*

## Description

These are the results of calling [optimizer64](#)

## Usage

```
data(optimizer64.data)
```

## Format

The format is: List of 16 \$ : num [1:9, 1:3] 0 0 1.63 0.00114 2.44 ... ..- attr(\*, "dimnames")=List of 2 .. ..\$ : chr [1:9] "match" "match.64" "hashpos" "hashrev" ... ..\$ : chr [1:3] "prep" "both" "use" \$ : num [1:10, 1:3] 0 0 0 1.62 0.00114 ... ..- attr(\*, "dimnames")=List of 2 .. ..\$ : chr [1:10] "%in%" "match.64" "%in%.64" "hashfin" ... ..\$ : chr [1:3] "prep" "both" "use" \$ : num [1:10, 1:3] 0 0 0.00105 0.00313 0.00313 ... ..- attr(\*, "dimnames")=List of 2 .. ..\$ : chr [1:10] "duplicated" "duplicated.64" "hashdup" "sortorderdup1" ... ..\$ : chr [1:3] "prep" "both" "use" \$ : num [1:15, 1:3] 0 0 0 0.00104 0.00104 ... ..- attr(\*, "dimnames")=List of 2 .. ..\$ : chr [1:15] "unique" "unique.64" "hashmapuni" "hashuni" ... ..\$ : chr [1:3] "prep" "both" "use" \$ : num [1:14, 1:3] 0 0 0 0.000992 0.000992 ... ..- attr(\*, "dimnames")=List of 2 .. ..\$ : chr [1:14] "unique" "unipos.64" "hashmapupo" "hashupo" ... ..\$ : chr [1:3] "prep" "both" "use" \$ : num [1:13, 1:3] 0 0 0 0.000419 ... ..- attr(\*, "dimnames")=List of 2 .. ..\$ : chr [1:13] "tabulate" "table" "table.64" "hashmaptab" ... ..\$ : chr [1:3] "prep" "both" "use" \$ : num [1:7, 1:3] 0 0 0 0.00236 0.00714 ... ..- attr(\*, "dimnames")=List of 2 .. ..\$ : chr [1:7] "rank" "rank.keep" "rank.64" "sortordernk"

```

... ..$. : chr [1:3] "prep" "both" "use" $ : num [1:6, 1:3] 0 0 0.00189 0.00714 0 ... ..- attr(*,
"dimnames")=List of 2 ..$. : chr [1:6] "quantile" "quantile.64" "sortqtl" "orderqtl" ... ..$. : chr
[1:3] "prep" "both" "use" $ : num [1:9, 1:3] 0 0 0.00105 1.17 0 ... ..- attr(*, "dimnames")=List of 2
..$. : chr [1:9] "match" "match.64" "hashpos" "hashrev" ... ..$. : chr [1:3] "prep" "both" "use" $
: num [1:10, 1:3] 0 0 0 0.00104 1.18 ... ..- attr(*, "dimnames")=List of 2 ..$. : chr [1:10] "%in%"
"match.64" "%in%.64" "hashfin" ... ..$. : chr [1:3] "prep" "both" "use" $ : num [1:10, 1:3] 0 0
1.64 2.48 2.48 ... ..- attr(*, "dimnames")=List of 2 ..$. : chr [1:10] "duplicated" "duplicated.64"
"hashdup" "sortorderdup1" ... ..$. : chr [1:3] "prep" "both" "use" $ : num [1:15, 1:3] 0 0 0 1.64
1.64 ... ..- attr(*, "dimnames")=List of 2 ..$. : chr [1:15] "unique" "unique.64" "hashmapuni"
"hashuni" ... ..$. : chr [1:3] "prep" "both" "use" $ : num [1:14, 1:3] 0 0 0 1.62 1.62 ... ..- attr(*,
"dimnames")=List of 2 ..$. : chr [1:14] "unique" "unipos.64" "hashmapupo" "hashupo" ... ..$.
: chr [1:3] "prep" "both" "use" $ : num [1:13, 1:3] 0 0 0 0 0.32 ... ..- attr(*, "dimnames")=List of
2 ..$. : chr [1:13] "tabulate" "table" "table.64" "hashmaptab" ... ..$. : chr [1:3] "prep" "both"
"use" $ : num [1:7, 1:3] 0 0 0 2.96 10.69 ... ..- attr(*, "dimnames")=List of 2 ..$. : chr [1:7]
"rank" "rank.keep" "rank.64" "sortorderrnk" ... ..$. : chr [1:3] "prep" "both" "use" $ : num [1:6,
1:3] 0 0 1.62 10.61 0 ... ..- attr(*, "dimnames")=List of 2 ..$. : chr [1:6] "quantile" "quantile.64"
"sortqtl" "orderqtl" ... ..$. : chr [1:3] "prep" "both" "use" - attr(*, "dim")= int [1:2] 8 2 - attr(*,
"dimnames")=List of 2 ..$. : chr [1:8] "match" "%in%" "duplicated" "unique" ... ..$. : chr [1:2]
"65536" "33554432"

```

## Examples

```

data(optimizer64.data)
print(optimizer64.data)
oldpar <- par(no.readonly = TRUE)
par(mfrow=c(2,1))
par(cex=0.7)
for (i in 1:nrow(optimizer64.data)){
  for (j in 1:2){
    tim <- optimizer64.data[[i,j]]
    barplot(t(tim))
    if (rownames(optimizer64.data)[i]=="match")
      title(paste("match", colnames(optimizer64.data)[j], "in", colnames(optimizer64.data)[3-j]))
    else if (rownames(optimizer64.data)[i]=="%in%")
      title(paste(colnames(optimizer64.data)[j], "%in%", colnames(optimizer64.data)[3-j]))
    else
      title(paste(rownames(optimizer64.data)[i], colnames(optimizer64.data)[j]))
  }
}
par(mfrow=c(1,1))

```

---

prank

*(P)ercent (Rank)s*

---

## Description

Function `prank.integer64` projects the values `[min..max]` via ranks `[1..n]` to `[0..1]`. `qtile.integer64` is the inverse function of `'prank.integer64'` and projects `[0..1]` to `[min..max]`.

**Usage**

```
prank(x, ...)  
## S3 method for class 'integer64'  
prank(x, method = NULL, ...)
```

**Arguments**

x	a integer64 vector
method	NULL for automatic method selection or a suitable low-level method, see details
...	ignored

**Details**

Function `prank.integer64` is based on [rank.integer64](#).

**Value**

`prank` returns a numeric vector of the same length as `x`.

**Author(s)**

Jens Oehlschlägel <Jens.Oehlschlaegel@truecluster.com>

**See Also**

[rank.integer64](#) for simple ranks and [qtile](#) for the inverse function quantiles.

**Examples**

```
x <- as.integer64(sample(c(rep(NA, 9), 1:9), 32, TRUE))  
prank(x)  
  
x <- x[!is.na(x)]  
stopifnot(identical(x, unname(qtile(x, probs=prank(x)))))
```

---

qtile

*(Q)uan(Tile)s*

---

**Description**

Function `prank.integer64` projects the values `[min..max]` via ranks `[1..n]` to `[0..1]`. `qtile.ineger64` is the inverse function of `'prank.integer64'` and projects `[0..1]` to `[min..max]`.

**Usage**

```

qtile(x, probs=seq(0, 1, 0.25), ...)
## S3 method for class 'integer64'
qtile(x, probs = seq(0, 1, 0.25), names = TRUE, method = NULL, ...)
## S3 method for class 'integer64'
quantile(x, probs = seq(0, 1, 0.25), na.rm = FALSE, names = TRUE, type=0L, ...)
## S3 method for class 'integer64'
mean(x, na.rm = FALSE, ...)
## S3 method for class 'integer64'
summary(object, ...)
## mean(x, na.rm = FALSE, ...)
## or
## mean(x, na.rm = FALSE)

```

**Arguments**

x	a integer64 vector
object	a integer64 vector
probs	numeric vector of probabilities with values in [0,1] - possibly containing NAs
names	logical; if TRUE, the result has a names attribute. Set to FALSE for speedup with many probs.
type	an integer selecting the quantile algorithm, currently only 0 is supported, see details
method	NULL for automatic method selection or a suitable low-level method, see details
na.rm	logical; if TRUE, any NA and NaN's are removed from x before the quantiles are computed.
...	ignored

**Details**

Functions `quantile.integer64` with `type=0` and `median.integer64` are convenience wrappers to `qtile`.

Function `qtile` behaves very similar to `quantile.default` with `type=1` in that it only returns existing values, it is mostly symmetric but it is using 'round' rather than 'floor'.

Note that this implies that `median.integer64` does not interpolate for even number of values (interpolation would create values that could not be represented as 64-bit integers).

This function automatically chooses from several low-level functions considering the size of `x` and the availability of a cache. Suitable methods are `sortqtl` (fast sorting) and `orderqtl` (memory saving ordering).

**Value**

`prank` returns a numeric vector of the same length as `x`.

`qtile` returns a vector with elements from `x` at the relative positions specified by `probs`.

**Author(s)**

Jens Oehlschlägel <Jens.Oehlschlaegel@truecluster.com>

**See Also**

[rank.integer64](#) for simple ranks and [quantile](#) for quantiles.

**Examples**

```
x <- as.integer64(sample(c(rep(NA, 9), 1:9), 32, TRUE))
qtile(x, probs=seq(0, 1, 0.25))
quantile(x, probs=seq(0, 1, 0.25), na.rm=TRUE)
median(x, na.rm=TRUE)
summary(x)

x <- x[!is.na(x)]
stopifnot(identical(x, unname(qtile(x, probs=prank(x)))))
```

---

ramsort.integer64

*Low-level integer64 methods for in-RAM sorting and ordering*


---

**Description**

Fast low-level methods for sorting and ordering. The `..sortorder` methods do sorting and ordering at once, which requires more RAM than ordering but is (almost) as fast as sorting.

**Usage**

```
## S3 method for class 'integer64'
shellsort(x, has.na=TRUE, na.last=FALSE, decreasing=FALSE, ...)
## S3 method for class 'integer64'
shellsortorder(x, i, has.na=TRUE, na.last=FALSE, decreasing=FALSE, ...)
## S3 method for class 'integer64'
shellorder(x, i, has.na=TRUE, na.last=FALSE, decreasing=FALSE, ...)
## S3 method for class 'integer64'
mergesort(x, has.na=TRUE, na.last=FALSE, decreasing=FALSE, ...)
## S3 method for class 'integer64'
mergeorder(x, i, has.na=TRUE, na.last=FALSE, decreasing=FALSE, ...)
## S3 method for class 'integer64'
mergesortorder(x, i, has.na=TRUE, na.last=FALSE, decreasing=FALSE, ...)
## S3 method for class 'integer64'
quicksort(x, has.na=TRUE, na.last=FALSE, decreasing=FALSE
, restlevel=floor(1.5*log2(length(x))), ...)
## S3 method for class 'integer64'
quicksortorder(x, i, has.na=TRUE, na.last=FALSE, decreasing=FALSE
, restlevel=floor(1.5*log2(length(x))), ...)
## S3 method for class 'integer64'
```

```

quickorder(x, i, has.na=TRUE, na.last=FALSE, decreasing=FALSE
, restlevel=floor(1.5*log2(length(x))), ...)
## S3 method for class 'integer64'
radixsort(x, has.na=TRUE, na.last=FALSE, decreasing=FALSE, radixbits=8L, ...)
## S3 method for class 'integer64'
radixsortorder(x, i, has.na=TRUE, na.last=FALSE, decreasing=FALSE, radixbits=8L, ...)
## S3 method for class 'integer64'
radixorder(x, i, has.na=TRUE, na.last=FALSE, decreasing=FALSE, radixbits=8L, ...)
## S3 method for class 'integer64'
ramsort(x, has.na = TRUE, na.last=FALSE, decreasing = FALSE, stable = TRUE
, optimize = c("time", "memory"), VERBOSE = FALSE, ...)
## S3 method for class 'integer64'
ramsortorder(x, i, has.na = TRUE, na.last=FALSE, decreasing = FALSE, stable = TRUE
, optimize = c("time", "memory"), VERBOSE = FALSE, ...)
## S3 method for class 'integer64'
ramorder(x, i, has.na = TRUE, na.last=FALSE, decreasing = FALSE, stable = TRUE
, optimize = c("time", "memory"), VERBOSE = FALSE, ...)

```

### Arguments

x	a vector to be sorted by <a href="#">ramsort</a> and <a href="#">ramsortorder</a> , i.e. the output of <a href="#">sort</a>
i	integer positions to be modified by <a href="#">ramorder</a> and <a href="#">ramsortorder</a> , default is 1:n, in this case the output is similar to <a href="#">order</a>
has.na	boolean scalar defining whether the input vector might contain NAs. If we know we don't have NAs, this may speed-up. <i>Note</i> that you risk a crash if there are unexpected NAs with has.na=FALSE
na.last	boolean scalar telling ramsort whether to sort NAs last or first. <i>Note</i> that 'boolean' means that there is no third option NA as in <a href="#">sort</a>
decreasing	boolean scalar telling ramsort whether to sort increasing or decreasing
stable	boolean scalar defining whether stable sorting is needed. Allowing non-stable may speed-up.
optimize	by default ramsort optimizes for 'time' which requires more RAM, set to 'memory' to minimize RAM requirements and sacrifice speed
restlevel	number of remaining recursionlevels before quicksort switches from recursing to shellsort
radixbits	size of radix in bits
VERBOSE	cat some info about chosen method
...	further arguments, passed from generics, ignored in methods

### Details

see [ramsort](#)

### Value

These functions return the number of NAs found or assumed during sorting



**Note**

Note that these methods purposely violate the functional programming paradigm: they are called for the side-effect of changing some of their arguments. The `sort`-methods change `x`, the `order`-methods change `i`, and the `sortorder`-methods change both `x` and `i`

**Author(s)**

Jens Oehlschlägel <Jens.Oehlschlaegel@truecluster.com>

**See Also**

[ramsort](#) for the generic, [ramsort.default](#) for the methods provided by package `ff`, [sort.integer64](#) for the sort interface and [sortcache](#) for caching the work of sorting

**Examples**

```
x <- as.integer64(sample(c(rep(NA, 9), 1:9), 32, TRUE))
x
message("ramsort example")
s <- clone(x)
ramsort(s)
message("s has been changed in-place - whether or not ramsort uses an in-place algorithm")
s
message("ramorder example")
s <- clone(x)
o <- seq_along(s)
ramorder(s, o)
message("o has been changed in-place - s remains unchanged")
s
o
s[o]
message("ramsortorder example")
o <- seq_along(s)
ramsortorder(s, o)
message("s and o have both been changed in-place - this is much faster")
s
o
```

---

rank.integer64

*Sample Ranks from integer64*


---

**Description**

Returns the sample ranks of the values in a vector. Ties (i.e., equal values) are averaged and missing values propagated.

**Usage**

```
## S3 method for class 'integer64'
rank(x, method = NULL, ...)
```

**Arguments**

x	a integer64 vector
method	NULL for automatic method selection or a suitable low-level method, see details
...	ignored

**Details**

This function automatically chooses from several low-level functions considering the size of x and the availability of a cache. Suitable methods are [sortorderank](#) (fast ordering) and [orderank](#) (memory saving ordering).

**Value**

A numeric vector of the same length as x.

**Author(s)**

Jens Oehlschlägel <Jens.Oehlschlaegel@truecluster.com>

**See Also**

[order.integer64](#), [rank](#) and [prank](#) for percent rank.

**Examples**

```
x <- as.integer64(sample(c(rep(NA, 9), 1:9), 32, TRUE))
rank.integer64(x)

stopifnot(identical(rank.integer64(x), rank(as.integer(x)
, na.last="keep", ties.method = "average")))
```

---

rep.integer64

*Replicate elements of integer64 vectors*

---

**Description**

Replicate elements of integer64 vectors

**Usage**

```
## S3 method for class 'integer64'
rep(x, ...)
```

**Arguments**

x	a vector of 'integer64' to be replicated
...	further arguments passed to <a href="#">NextMethod</a>

**Value**

`rep` returns a integer64 vector

**Author(s)**

Jens Oehlschlägel <Jens.Oehlschlaegel@truecluster.com>

**See Also**

`c.integer64 rep.integer64 as.data.frame.integer64 integer64`

**Examples**

```
rep(as.integer64(1:2), 6)
rep(as.integer64(1:2), c(6,6))
rep(as.integer64(1:2), length.out=6)
```

---

seq.integer64

*integer64: Sequence Generation*

---

**Description**

Generating sequence of integer64 values

**Usage**

```
## S3 method for class 'integer64'
seq(from = NULL, to = NULL, by = NULL, length.out = NULL, along.with = NULL, ...)
```

**Arguments**

<code>from</code>	integer64 scalar (in order to dispatch the integer64 method of <code>seq</code> )
<code>to</code>	scalar
<code>by</code>	scalar
<code>length.out</code>	scalar
<code>along.with</code>	scalar
<code>...</code>	ignored

**Details**

`seq.integer64` does coerce its arguments 'from', 'to' and 'by' to integer64. If not provided, the argument 'by' is automatically determined as +1 or -1, but the size of 'by' is not calculated as in `seq` (because this might result in a non-integer value).

**Value**

an integer64 vector with the generated sequence

**Note**

In base R : currently is not generic and does not dispatch, see section "Limitations inherited from Base R" in [integer64](#)

**Author(s)**

Jens Oehlschlägel <Jens.Oehlschlaegel@truecluster.com>

**See Also**

[c.integer64](#) [rep.integer64](#) [as.data.frame.integer64](#) [integer64](#)

**Examples**

```
# colon not activated: as.integer64(1):12
seq(as.integer64(1), 12, 2)
seq(as.integer64(1), by=2, length.out=6)
```

---

sort.integer64

*High-level intger64 methods for sorting and ordering*

---

**Description**

Fast high-level methods for sorting and ordering. These are wrappers to [ramsort](#) and friends and do not modify their arguments.

**Usage**

```
## S3 method for class 'integer64'
sort(x, decreasing = FALSE, has.na = TRUE, na.last = TRUE, stable = TRUE
, optimize = c("time", "memory"), VERBOSE = FALSE, ...)
## S3 method for class 'integer64'
order(..., na.last = TRUE, decreasing = FALSE, has.na = TRUE, stable = TRUE
, optimize = c("time", "memory"), VERBOSE = FALSE)
```

**Arguments**

x	a vector to be sorted by <a href="#">ramsort</a> and <a href="#">ramsortorder</a> , i.e. the output of <a href="#">sort</a>
has.na	boolean scalar defining whether the input vector might contain NAs. If we know we don't have NAs, this may speed-up. <i>Note</i> that you risk a crash if there are unexpected NAs with has.na=FALSE
na.last	boolean scalar telling ramsort whether to sort NAs last or first. <i>Note</i> that 'boolean' means that there is no third option NA as in <a href="#">sort</a>
decreasing	boolean scalar telling ramsort whether to sort increasing or decreasing
stable	boolean scalar defining whether stable sorting is needed. Allowing non-stable may speed-up.

optimize	by default ramsort optimizes for 'time' which requires more RAM, set to 'memory' to minimize RAM requirements and sacrifice speed
VERBOSE	cat some info about chosen method
...	further arguments, passed from generics, ignored in methods

**Details**

see [sort](#) and [order](#)

**Value**

sort returns the sorted vector and vector returns the order positions.

**Author(s)**

Jens Oehlschlägel <Jens.Oehlschlaegel@truecluster.com>

**See Also**

[sort](#), [sortcache](#)

**Examples**

```
x <- as.integer64(sample(c(rep(NA, 9), 1:9), 32, TRUE))
x
sort(x)
message("the following has default optimize='time' which is faster but requires more RAM
, this calls 'ramorder'")
order.integer64(x)
message("slower with less RAM, this calls 'ramsortorder'")
order.integer64(x, optimize="memory")
```

---

sortnut

*Searching and other uses of sorting for 64bit integers*

---

**Description**

This is roughly an implementation of hash functionality but based on sorting instead on a hasmap. Since sorting is more informative than hashing we can do some more interesting things.

**Usage**

```
sortnut(sorted, ...)
ordernut(table, order, ...)
sortfin(sorted, x, ...)
orderfin(table, order, x, ...)
orderpos(table, order, x, ...)
sortorderpos(sorted, order, x, ...)
```

```

orderdup(table, order, ...)
sortorderdup(sorted, order, ...)
sortuni(sorted, nunique, ...)
orderuni(table, order, nunique, ...)
sortorderuni(table, sorted, order, nunique, ...)
orderupo(table, order, nunique, ...)
sortorderupo(sorted, order, nunique, keep.order = FALSE, ...)
ordertie(table, order, nties, ...)
sortordertie(sorted, order, nties, ...)
sorttab(sorted, nunique, ...)
ordertab(table, order, nunique, ...)
sortordertab(sorted, order, ...)
orderkey(table, order, na.skip.num = 0L, ...)
sortorderkey(sorted, order, na.skip.num = 0L, ...)
orderrnk(table, order, na.count, ...)
sortorderrnk(sorted, order, na.count, ...)
## S3 method for class 'integer64'
sortnut(sorted, ...)
## S3 method for class 'integer64'
ordernut(table, order, ...)
## S3 method for class 'integer64'
sortfin(sorted, x, method=NULL, ...)
## S3 method for class 'integer64'
orderfin(table, order, x, method=NULL, ...)
## S3 method for class 'integer64'
orderpos(table, order, x, nomatch=NA, method=NULL, ...)
## S3 method for class 'integer64'
sortorderpos(sorted, order, x, nomatch=NA, method=NULL, ...)
## S3 method for class 'integer64'
orderdup(table, order, method=NULL, ...)
## S3 method for class 'integer64'
sortorderdup(sorted, order, method=NULL, ...)
## S3 method for class 'integer64'
sortuni(sorted, nunique, ...)
## S3 method for class 'integer64'
orderuni(table, order, nunique, keep.order=FALSE, ...)
## S3 method for class 'integer64'
sortorderuni(table, sorted, order, nunique, ...)
## S3 method for class 'integer64'
orderupo(table, order, nunique, keep.order=FALSE, ...)
## S3 method for class 'integer64'
sortorderupo(sorted, order, nunique, keep.order = FALSE, ...)
## S3 method for class 'integer64'
ordertie(table, order, nties, ...)
## S3 method for class 'integer64'
sortordertie(sorted, order, nties, ...)
## S3 method for class 'integer64'
sorttab(sorted, nunique, ...)

```

```

## S3 method for class 'integer64'
ordertab(table, order, nunique, denormalize=FALSE, keep.order=FALSE, ...)
## S3 method for class 'integer64'
sortordertab(sorted, order, denormalize=FALSE, ...)
## S3 method for class 'integer64'
orderkey(table, order, na.skip.num = 0L, ...)
## S3 method for class 'integer64'
sortorderkey(sorted, order, na.skip.num = 0L, ...)
## S3 method for class 'integer64'
orderrnk(table, order, na.count, ...)
## S3 method for class 'integer64'
sortorderrnk(sorted, order, na.count, ...)
## S3 method for class 'integer64'
sortqtl(sorted, na.count, probs, ...)
## S3 method for class 'integer64'
orderqtl(table, order, na.count, probs, ...)

```

### Arguments

x	an <a href="#">integer64</a> vector
sorted	a sorted <a href="#">integer64</a> vector
table	the original data with original order under the sorted vector
order	an <a href="#">integer</a> order vector that turns 'table' into 'sorted'
nunique	number of unique elements, usually we get this from cache or call <code>sortnut</code> or <code>ordernut</code>
nties	number of tied values, usually we get this from cache or call <code>sortnut</code> or <code>ordernut</code>
denormalize	FALSE returns counts of unique values, TRUE returns each value with its counts
nomatch	the value to be returned if an element is not found in the hashmap
keep.order	determines order of results and speed: FALSE (the default) is faster and returns in sorted order, TRUE returns in the order of first appearance in the original data, but this requires extra work
probs	vector of probabilities in [0..1] for which we seek quantiles
na.skip.num	0 or the number of NAs. With 0, NAs are coded with 1L, with the number of NAs, these are coded with NA, the latter needed for <code>as.factor.integer64</code>
na.count	the number of NAs, needed for this low-level function algorithm
method	see details
...	further arguments, passed from generics, ignored in methods

### Details

sortfun	orderfun	sortorderfun	see also	description
sortnut	ordernut			return number of tied and of unique values
sortfin	orderfin		<a href="#">%in%.integer64</a>	return logical whether x is in table
	orderpos	sortorderpos	<a href="#">match</a>	return positions of x in table
	orderdup	sortorderdup	<a href="#">duplicated</a>	return logical whether values are duplicated

sortuni	orderuni	sortorderuni	<a href="#">unique</a>	return unique values (=dimensiontable)
	orderupo	sortorderupo	<a href="#">unique</a>	return positions of unique values
	ordertie	sortordertie		return positions of tied values
	orderkey	sortorderkey		positions of values in vector of unique values (match in dimensions)
sorttab	ordertab	sortordertab	<a href="#">table</a>	tabulate frequency of values
	orderrnk	sortorderrnk		rank averaging ties
sortqtl	orderqtl			return quantiles given probabilities

The functions `sortfin`, `orderfin`, `orderpos` and `sortorderpos` each offer three algorithms for finding `x` in `table`.

With `method=1L` each value of `x` is searched independently using *binary search*, this is fastest for small tables.

With `method=2L` the values of `x` are first sorted and then searched using *doubly exponential search*, this is the best allround method.

With `method=3L` the values of `x` are first sorted and then searched using simple merging, this is the fastest method if `table` is huge and `x` has similar size and distribution of values.

With `method=NULL` the functions use a heuristic to determine the fastest algorithm.

The functions `orderdup` and `sortorderdup` each offer two algorithms for setting the truth values in the return vector.

With `method=1L` the return values are set directly which causes random write access on a possibly large return vector.

With `method=2L` the return values are first set in a smaller bit-vector – random access limited to a smaller memory region – and finally written sequentially to the logical output vector.

With `method=NULL` the functions use a heuristic to determine the fastest algorithm.

## Value

see details

## Author(s)

Jens Oehlschlägel <Jens.Oehlschlaegel@truecluster.com>

## See Also

[match](#)

## Examples

```
message("check the code of 'optimizer64' for examples:")
print(optimizer64)
```



---

sum.integer64                      *Summary functions for integer64 vectors*

---

### Description

Summary functions for integer64 vectors. Function 'range' without arguments returns the smallest and largest value of the 'integer64' class.

### Usage

```
## S3 method for class 'integer64'  
all(..., na.rm = FALSE)  
## S3 method for class 'integer64'  
any(..., na.rm = FALSE)  
## S3 method for class 'integer64'  
min(..., na.rm = FALSE)  
## S3 method for class 'integer64'  
max(..., na.rm = FALSE)  
## S3 method for class 'integer64'  
range(..., na.rm = FALSE)  
lim.integer64()  
## S3 method for class 'integer64'  
sum(..., na.rm = FALSE)  
## S3 method for class 'integer64'  
prod(..., na.rm = FALSE)
```

### Arguments

...                      atomic vectors of class 'integer64'  
na.rm                    logical scalar indicating whether to ignore NAs

### Details

The numerical summary methods always return integer64. Therefore the methods for min,max and range do not return +Inf, -Inf on empty arguments, but +9223372036854775807, -9223372036854775807 (in this sequence). The same is true if only NAs are submitted with argument na.rm=TRUE. lim.integer64 returns these limits in proper order -9223372036854775807, +9223372036854775807 and without a [warning](#).

### Value

[all](#) and [any](#) return a logical scalar  
[range](#) returns a integer64 vector with two elements  
[min](#), [max](#), [sum](#) and [prod](#) return a integer64 scalar

### Author(s)

Jens Oehlschlägel <Jens.Oehlschlaegel@truecluster.com>

**See Also**

[mean.integer64](#) [cumsum.integer64](#) [integer64](#)

**Examples**

```
lim.integer64()
range(as.integer64(1:12))
```

---

table.integer64	<i>Cross Tabulation and Table Creation for integer64</i>
-----------------	--

---

**Description**

table.integer64 uses the cross-classifying integer64 vectors to build a contingency table of the counts at each combination of vector values.

**Usage**

```
table.integer64(...
, return = c("table", "data.frame", "list")
, order = c("values", "counts")
, nunique = NULL
, method = NULL
, dnn = list.names(...), deparse.level = 1
)
```

**Arguments**

...	one or more objects which can be interpreted as factors (including character strings), or a list (or data frame) whose components can be so interpreted. (For <code>as.table</code> and <code>as.data.frame</code> , arguments passed to specific methods.)
nunique	NULL or the number of unique values of table (including NA). Providing nunique can speed-up matching when table has no cache. Note that a wrong nunique can cause undefined behaviour up to a crash.
order	By default results are created sorted by "values", or by "counts"
method	NULL for automatic method selection or a suitable low-level method, see details
return	choose the return format, see details
dnn	the names to be given to the dimensions in the result (the <i>dimnames names</i> ).
deparse.level	controls how the default dnn is constructed. See 'Details'.

## Details

This function automatically chooses from several low-level functions considering the size of `x` and the availability of a cache. Suitable methods are `hashmptab` (simultaneously creating and using a hashmap), `hashtab` (first creating a hashmap then using it), `sortordertab` (fast ordering) and `ordertab` (memory saving ordering).

If the argument `dnn` is not supplied, the internal function `list.names` is called to compute the ‘dimname names’. If the arguments in `...` are named, those names are used. For the remaining arguments, `deparse.level = 0` gives an empty name, `deparse.level = 1` uses the supplied argument if it is a symbol, and `deparse.level = 2` will deparse the argument.

Arguments `exclude`, `useNA`, are not supported, i.e. NAs are always tabulated, and, different from `table` they are sorted first if `order="values"`.

## Value

By default (with `return="table"`) `table` returns a *contingency table*, an object of class `"table"`, an array of integer values. Note that unlike S the result is always an array, a 1D array if one factor is given. Note also that for multidimensional arrays this is a *dense* return structure which can dramatically increase RAM requirements (for large arrays with high mutual information, i.e. many possible input combinations of which only few occur) and that `table` is limited to  $2^{31}$  possible combinations (e.g. two input vectors with 46340 unique values only). Finally note that the tabulated values or value-combinations are represented as `dimnames` and that the implied conversion of values to strings can cause *severe* performance problems since each string needs to be integrated into R’s global string cache.

You can use the other `return=` options to cope with these problems, the potential combination limit is increased from  $2^{31}$  to  $2^{63}$  with these options, RAM is only required for observed combinations and string conversion is avoided.

With `return="data.frame"` you get a *dense* representation as a `data.frame` (like that resulting from `as.data.frame(table(...))`) where only observed combinations are listed (each as a `data.frame` row) with the corresponding frequency counts (the latter as component named by `responseName`). This is the inverse of `xtabs..`

With `return="list"` you also get a *dense* representation as a simple `list` with components

<code>values</code>	a <code>integer64</code> vector of the technically tabulated values, for 1D this is the tabulated values themselves, for kD these are the values representing the potential combinations of input values
<code>counts</code>	the frequency counts
<code>dims</code>	only for kD: a list with the vectors of the unique values of the input dimensions

## Note

Note that by using `as.integer64.factor` we can also input factors into `table.integer64` – only the `levels` get lost.

Note that because of the existence of `as.factor.integer64` the standard `table` function – within its limits – can also be used for `integer64`, and especially for combining `integer64` input with other data types.

**See Also**

`table` for more info on the standard version coping with Base R's data types, `tabulate` which can faster tabulate `integers` with a limited range [1L .. nL not too big], `unique.integer64` for the unique values without counting them and `unipos.integer64` for the positions of the unique values.

**Examples**

```
message("pure integer64 examples")
x <- as.integer64(sample(c(rep(NA, 9), 1:9), 32, TRUE))
y <- as.integer64(sample(c(rep(NA, 9), 1:9), 32, TRUE))
z <- sample(c(rep(NA, 9), letters), 32, TRUE)
table.integer64(x)
table.integer64(x, order="counts")
table.integer64(x, y)
table.integer64(x, y, return="data.frame")

message("via as.integer64.factor we can use 'table.integer64' also for factors")
table.integer64(x, as.integer64(as.factor(z)))

message("via as.factor.integer64 we can also use 'table' for integer64")
table(x)
table(x, exclude=NULL)
table(x, z, exclude=NULL)
```

---

 tiepos

---

*Extract Positions of Tied Elements*


---

**Description**

`tiepos` returns the positions of those elements that participate in ties.

**Usage**

```
tiepos(x, ...)
## S3 method for class 'integer64'
tiepos(x, nties = NULL, method = NULL, ...)
```

**Arguments**

<code>x</code>	a vector or a data frame or an array or <code>NULL</code> .
<code>nties</code>	<code>NULL</code> or the number of tied values (including <code>NA</code> ). Providing <code>nties</code> can speed-up when <code>x</code> has no cache. Note that a wrong <code>nties</code> can cause undefined behaviour up to a crash.
<code>method</code>	<code>NULL</code> for automatic method selection or a suitable low-level method, see details
<code>...</code>	ignored

**Details**

This function automatically chooses from several low-level functions considering the size of `x` and the availability of a cache. Suitable methods are `sortordertie` (fast ordering) and `ordertie` (memory saving ordering).

**Value**

an integer vector of positions

**Author(s)**

Jens Oehlschlägel <Jens.Oehlschlaegel@truecluster.com>

**See Also**

`rank.integer64` for possibly tied ranks and `unipos.integer64` for positions of unique values.

**Examples**

```
x <- as.integer64(sample(c(rep(NA, 9), 1:9), 32, TRUE))
tiepos(x)

stopifnot(identical(tiepos(x), (1:length(x))[duplicated(x) | rev(duplicated(rev(x)))])))
```

---

unipos

*Extract Positions of Unique Elements*


---

**Description**

`unipos` returns the positions of those elements returned by `unique`.

**Usage**

```
unipos(x, incomparables = FALSE, order = c("original", "values", "any"), ...)
## S3 method for class 'integer64'
unipos(x, incomparables = FALSE, order = c("original", "values", "any")
, nunique = NULL, method = NULL, ...)
```

**Arguments**

<code>x</code>	a vector or a data frame or an array or <code>NULL</code> .
<code>incomparables</code>	ignored
<code>order</code>	The order in which positions of unique values will be returned, see details
<code>nunique</code>	<code>NULL</code> or the number of unique values (including <code>NA</code> ). Providing <code>nunique</code> can speed-up when <code>x</code> has no cache. Note that a wrong <code>nunique</code> can cause undefined behaviour up to a crash.
<code>method</code>	<code>NULL</code> for automatic method selection or a suitable low-level method, see details
<code>...</code>	ignored

**Details**

This function automatically chooses from several low-level functions considering the size of `x` and the availability of a cache. Suitable methods are `hashmapupo` (simultaneously creating and using a hashmap), `hashupo` (first creating a hashmap then using it), `sortorderupo` (fast ordering) and `orderupo` (memory saving ordering).

The default `order="original"` collects unique values in the order of the first appearance in `x` like in `unique`, this costs extra processing. `order="values"` collects unique values in sorted order like in `table`, this costs extra processing with the hash methods but comes for free. `order="any"` collects unique values in undefined order, possibly faster. For hash methods this will be a quasi random order, for sort methods this will be sorted order.

**Value**

an integer vector of positions

**Author(s)**

Jens Oehlschlägel <Jens.Oehlschlaegel@truecluster.com>

**See Also**

`unique.integer64` for unique values and `match.integer64` for general matching.

**Examples**

```
x <- as.integer64(sample(c(rep(NA, 9), 1:9), 32, TRUE))
unipos(x)
unipos(x, order="values")

stopifnot(identical(unipos(x), (1:length(x))[!duplicated(x)]))
stopifnot(identical(unipos(x), match.integer64(unique(x), x)))
stopifnot(identical(unipos(x, order="values"), match.integer64(unique(x, order="values"), x)))
stopifnot(identical(unique(x), x[unipos(x)]))
stopifnot(identical(unique(x, order="values"), x[unipos(x, order="values")]))
```

---

unique.integer64

*Extract Unique Elements from integer64*

---

**Description**

unique returns a vector like `x` but with duplicate elements/rows removed.

**Usage**

```
## S3 method for class 'integer64'
unique(x, incomparables = FALSE, order = c("original", "values", "any")
, nunique = NULL, method = NULL, ...)
```

**Arguments**

x	a vector or a data frame or an array or NULL.
incomparables	ignored
order	The order in which unique values will be returned, see details
nunique	NULL or the number of unique values (including NA). Providing nunique can speed-up matching when x has no cache. Note that a wrong nunique can cause undefined behaviour up to a crash.
method	NULL for automatic method selection or a suitable low-level method, see details
...	ignored

**Details**

This function automatically chooses from several low-level functions considering the size of x and the availability of a cache. Suitable methods are [hashmapuni](#) (simultaneously creating and using a hashmap) , [hashuni](#) (first creating a hashmap then using it) , [sortuni](#) (fast sorting for sorted order only) , [sortorderuni](#) (fast ordering for original order only) and [orderuni](#) (memory saving ordering).

The default order="original" returns unique values in the order of the first appearance in x like in [unique](#), this costs extra processing. order="values" returns unique values in sorted order like in [table](#), this costs extra processing with the hash methods but comes for free. order="any" returns unique values in undefined order, possibly faster. For hash methods this will be a quasi random order, for sort methods this will be sorted order.

**Value**

For a vector, an object of the same type of x, but with only one copy of each duplicated element. No attributes are copied (so the result has no names).

**Author(s)**

Jens Oehlschlägel <Jens.Oehlschlaegel@truecluster.com>

**See Also**

[unique](#) for the generic, [unipos](#) which gives the indices of the unique elements and [table.integer64](#) which gives frequencies of the unique elements.

**Examples**

```
x <- as.integer64(sample(c(rep(NA, 9), 1:9), 32, TRUE))
unique(x)
unique(x, order="values")

stopifnot(identical(unique(x), x[!duplicated(x)]))
stopifnot(identical(unique(x), as.integer64(unique(as.integer(x)))))
stopifnot(identical(unique(x, order="values")
, as.integer64(sort(unique(as.integer(x)), na.last=FALSE))))
```

---

`xor.integer64`*Binary operators for integer64 vectors*

---

**Description**

Binary operators for integer64 vectors.

**Usage**

```
## S3 method for class 'integer64'  
e1 & e2  
## S3 method for class 'integer64'  
e1 | e2  
## S3 method for class 'integer64'  
xor(x,y)  
## S3 method for class 'integer64'  
e1 != e2  
## S3 method for class 'integer64'  
e1 == e2  
## S3 method for class 'integer64'  
e1 < e2  
## S3 method for class 'integer64'  
e1 <= e2  
## S3 method for class 'integer64'  
e1 > e2  
## S3 method for class 'integer64'  
e1 >= e2  
## S3 method for class 'integer64'  
e1 + e2  
## S3 method for class 'integer64'  
e1 - e2  
## S3 method for class 'integer64'  
e1 * e2  
## S3 method for class 'integer64'  
e1 ^ e2  
## S3 method for class 'integer64'  
e1 / e2  
## S3 method for class 'integer64'  
e1 %/% e2  
## S3 method for class 'integer64'  
e1 %% e2  
binattr(e1,e2) # for internal use only
```

**Arguments**

e1                    an atomic vector of class 'integer64'  
e2                    an atomic vector of class 'integer64'



x                    an atomic vector of class 'integer64'  
y                    an atomic vector of class 'integer64'

**Value**

&, |, xor, !=, ==, <, <=, >, >= return a logical vector  
^ and / return a double vector  
+, -, \*, %/%, %% return a vector of class 'integer64'

**Author(s)**

Jens Oehlschlägel <Jens.Oehlschlaegel@truecluster.com>

**See Also**

[format.integer64](#) [integer64](#)

**Examples**

`as.integer64(1:12) - 1`

# Index

- !.integer64 (format.integer64), 31
- !=.integer64 (xor.integer64), 64
- \*Topic **category**
  - table.integer64, 58
- \*Topic **classes**
  - as.character.integer64, 16
  - as.data.frame.integer64, 17
  - as.integer64.character, 18
  - bit64-package, 2
  - c.integer64, 25
  - cumsum.integer64, 27
  - extract.replace.integer64, 30
  - format.integer64, 31
  - identical.integer64, 37
  - rep.integer64, 50
  - seq.integer64, 51
  - sum.integer64, 57
  - xor.integer64, 64
- \*Topic **datasets**
  - benchmark64.data, 22
  - optimizer64.data, 43
- \*Topic **environment**
  - cache, 26
  - hashcache, 33
  - is.sorted.integer64, 38
- \*Topic **logic**
  - duplicated.integer64, 29
  - match.integer64, 41
  - unipos, 61
  - unique.integer64, 62
- \*Topic **manip**
  - as.character.integer64, 16
  - as.data.frame.integer64, 17
  - as.integer64.character, 18
  - bit64-package, 2
  - c.integer64, 25
  - cumsum.integer64, 27
  - duplicated.integer64, 29
  - extract.replace.integer64, 30
  - format.integer64, 31
  - hashmap, 34
  - identical.integer64, 37
  - keypos, 39
  - match.integer64, 41
  - ramsort.integer64, 47
  - rep.integer64, 50
  - seq.integer64, 51
  - sort.integer64, 52
  - sortnut, 53
  - sum.integer64, 57
  - tiepos, 60
  - unipos, 61
  - unique.integer64, 62
  - xor.integer64, 64
- \*Topic **methods**
  - bit64S3, 23
  - is.sorted.integer64, 38
- \*Topic **misc**
  - benchmark64, 19
- \*Topic **package**
  - bit64-package, 2
- \*Topic **programming**
  - hashmap, 34
  - ramsort.integer64, 47
  - sort.integer64, 52
  - sortnut, 53
- \*Topic **univar**
  - keypos, 39
  - prank, 44
  - qtile, 45
  - rank.integer64, 49
  - tiepos, 60
- \*, 5, 7, 65
- \*.integer64, 7
- \*.integer64 (xor.integer64), 64
- +, 5, 7, 65
- +.integer64, 7
- +.integer64 (xor.integer64), 64

-, 7  
 -.integer64, 7  
 -.integer64 (xor.integer64), 64  
 .Machine, 8  
 /, 5, 7, 65  
 /.integer64, 7  
 /.integer64 (xor.integer64), 64  
 :, 9, 24, 52  
 : (bit64S3), 23  
 <, 7, 65  
 <.integer64, 7  
 <.integer64 (xor.integer64), 64  
 <=, 7, 65  
 <= .integer64, 7  
 <= .integer64 (xor.integer64), 64  
 ==, 7, 65  
 ==.integer64, 7, 38  
 ==.integer64 (xor.integer64), 64  
 >, 7, 65  
 >.integer64, 7  
 >.integer64 (xor.integer64), 64  
 >=, 7, 65  
 >=.integer64, 7  
 >=.integer64 (xor.integer64), 64  
 [, 6, 30  
 [.integer64, 6  
 [.integer64  
     (extract.replace.integer64), 30  
 [<-, 6  
 [<-.integer64, 6  
 [<-.integer64  
     (extract.replace.integer64), 30  
 [[, 6  
 [[.integer64, 6  
 [[.integer64  
     (extract.replace.integer64), 30  
 [[<-, 6  
 [[<-.integer64, 6  
 [[<-.integer64  
     (extract.replace.integer64), 30  
 %/.integer64 (xor.integer64), 64  
 %%.integer64 (xor.integer64), 64  
 %in% (bit64S3), 23  
 %in%.integer64 (match.integer64), 41  
 &, 7, 65  
 &.bit, 9  
 &.bitwhich, 9  
 &.integer64, 7  
 &.integer64 (xor.integer64), 64  
 %/%, 5, 7, 65  
 %/%.integer64, 7  
 %%, 5, 7, 65  
 %%.integer64, 7  
 %in%, 8, 24  
 %in%.integer64, 8, 27, 35, 55  
 ^, 5, 7, 65  
 ^.integer64, 7  
 ^.integer64 (xor.integer64), 64  
 abs, 7, 32  
 abs.integer64, 7  
 abs.integer64 (format.integer64), 31  
 all, 8, 57  
 all.integer64, 8  
 all.integer64 (sum.integer64), 57  
 any, 8, 57  
 any.integer64, 8  
 any.integer64 (sum.integer64), 57  
 array, 10  
 as.bitstring, 6  
 as.bitstring (as.character.integer64),  
     16  
 as.bitstring.integer64, 6  
 as.character, 6, 16  
 as.character.integer64, 6, 16, 19  
 as.data.frame, 6, 17  
 as.data.frame.integer64, 4, 6, 17, 25, 51,  
     52  
 as.double, 5, 6, 16  
 as.double.integer64, 6  
 as.double.integer64  
     (as.character.integer64), 16  
 as.factor, 8  
 as.factor.integer64, 8, 27, 55, 59  
 as.factor.integer64  
     (as.character.integer64), 16  
 as.integer, 6, 16  
 as.integer.integer64, 6  
 as.integer.integer64  
     (as.character.integer64), 16  
 as.integer64, 6  
 as.integer64 (as.integer64.character),  
     18  
 as.integer64.character, 6, 17, 18  
 as.integer64.double, 6  
 as.integer64.factor, 59  
 as.integer64.integer, 6

- as.integer64.integer64, 6
- as.integer64.logical, 6
- as.integer64.NULL, 6
- as.logical, 6, 16
- as.logical.integer64, 6
- as.logical.integer64
  - (as.character.integer64), 16
- as.ordered, 8
- as.ordered.integer64, 8, 27
- as.ordered.integer64
  - (as.character.integer64), 16
- as.vector, 10
- atomic, 4
  
- benchmark64, 19, 22
- benchmark64.data, 22
- binattr, 8
- binattr (xor.integer64), 64
- bit, 4, 9
- bit64, 24
- bit64 (bit64-package), 2
- bit64-package, 2
- bit64S3, 23
- bitwhich, 9
  
- c, 5, 6, 9, 25
- c.integer64, 6, 9, 25, 51, 52
- cache, 4, 26, 33–35, 39
- cbind, 5, 6, 25
- cbind.integer64, 6, 17
- cbind.integer64 (c.integer64), 25
- ceiling, 7, 32
- ceiling.integer64, 7
- ceiling.integer64 (format.integer64), 31
- character, 6
- cummax, 7, 28
- cummax.integer64, 7
- cummax.integer64 (cumsum.integer64), 27
- cummin, 7, 28
- cummin.integer64, 7
- cummin.integer64 (cumsum.integer64), 27
- cumprod, 7, 28
- cumprod.integer64, 7
- cumprod.integer64 (cumsum.integer64), 27
- cumsum, 7, 28
- cumsum.integer64, 7, 27, 58
  
- data.frame, 6, 59
- dget, 8
  
- diff, 7, 28
- diff.integer64, 7
- diff.integer64 (cumsum.integer64), 27
- digest, 35
- dim, 4, 6
- dim<-, 6
- dimnames, 4, 6
- dimnames<-, 6
- double, 4–6, 9
- dput, 8
- duplicated, 8, 29, 35, 55
- duplicated.integer64, 8, 27, 29
  
- extract.replace.integer64, 30
  
- ff, 5, 8, 49
- floor, 7, 32
- floor.integer64, 7
- floor.integer64 (format.integer64), 31
- format, 7, 16, 32
- format.integer64, 7, 31, 65
  
- getcache (cache), 26
  
- hashcache, 20, 23, 27, 33, 39, 41
- hashdup, 29
- hashdup (hashmap), 34
- hashfin, 41
- hashfin (hashmap), 34
- hashfun (hashmap), 34
- hashmap, 20, 33, 34
- hashmaptab, 59
- hashmaptab (hashmap), 34
- hashmapuni, 63
- hashmapuni (hashmap), 34
- hashmapupo, 62
- hashmapupo (hashmap), 34
- hashpos, 41
- hashpos (hashmap), 34
- hashrev, 41
- hashrev (hashmap), 34
- hashrin, 41
- hashrin (hashmap), 34
- hashtab, 59
- hashtab (hashmap), 34
- hashuni, 63
- hashuni (hashmap), 34
- hashupo, 62
- hashupo (hashmap), 34

- identical, [6](#), [9](#), [37](#), [38](#)
- identical.integer64, [6](#), [9](#), [37](#)
- inherits, [4](#)
- integer, [3–6](#), [10](#), [55](#), [60](#)
- integer64, [17](#), [19](#), [21](#), [23–25](#), [28](#), [30](#), [32](#), [38](#), [51](#), [52](#), [55](#), [58](#), [59](#), [65](#)
- integer64 (bit64-package), [2](#)
- invisible, [24](#)
- is, [6](#)
- is.atomic, [4](#)
- is.double, [5](#), [9](#), [24](#)
- is.double (bit64S3), [23](#)
- is.finite.integer64 (format.integer64), [31](#)
- is.infinite.integer64 (format.integer64), [31](#)
- is.integer, [6](#)
- is.integer.integer64 (bit64-package), [2](#)
- is.integer64, [5](#), [6](#)
- is.integer64 (bit64-package), [2](#)
- is.na, [7](#), [32](#)
- is.na.integer64, [7](#)
- is.na.integer64 (format.integer64), [31](#)
- is.nan.integer64 (format.integer64), [31](#)
- is.sorted, [27](#)
- is.sorted.integer64, [38](#)
- is.vector, [5](#), [6](#), [10](#)
- is.vector.integer64, [6](#), [10](#)
- is.vector.integer64 (bit64-package), [2](#)
- jamcache (cache), [26](#)
- keypos, [8](#), [27](#), [39](#)
- keypos.integer64, [8](#)
- length, [4](#), [6](#), [39](#)
- length<-, [6](#)
- length<- .integer64, [6](#)
- length<- .integer64 (bit64-package), [2](#)
- levels, [59](#)
- lim.integer64 (sum.integer64), [57](#)
- list, [59](#)
- load, [8](#)
- log, [5](#), [7](#), [32](#)
- log.integer64, [7](#)
- log.integer64 (format.integer64), [31](#)
- log10, [5](#), [7](#), [32](#)
- log10.integer64, [7](#)
- log10.integer64 (format.integer64), [31](#)
- log2, [5](#), [7](#), [32](#)
- log2.integer64, [7](#)
- log2.integer64 (format.integer64), [31](#)
- logical, [6](#)
- ls, [26](#)
- match, [8](#), [24](#), [35](#), [36](#), [42](#), [55](#), [56](#)
- match (bit64S3), [23](#)
- match.integer64, [8](#), [27](#), [40](#), [41](#), [62](#)
- matrix, [10](#)
- max, [8](#), [57](#)
- max.integer64, [8](#)
- max.integer64 (sum.integer64), [57](#)
- mean, [8](#)
- mean.integer64, [8](#), [58](#)
- mean.integer64 (qtile), [45](#)
- median, [8](#)
- median.integer64, [8](#), [27](#)
- median.integer64 (qtile), [45](#)
- mergeorder.integer64 (ramsort.integer64), [47](#)
- mergesort.integer64 (ramsort.integer64), [47](#)
- mergesortorder.integer64 (ramsort.integer64), [47](#)
- min, [8](#), [57](#)
- min.integer64, [8](#)
- min.integer64 (sum.integer64), [57](#)
- minusclass, [8](#)
- mode, [5](#)
- mode<-, [10](#)
- na.count, [27](#)
- na.count.integer64 (is.sorted.integer64), [38](#)
- NA\_integer64\_ (as.integer64.character), [18](#)
- NA\_integer\_, [5](#)
- names, [4](#), [6](#)
- names<-, [6](#)
- newcache (cache), [26](#)
- NextMethod, [3](#), [16](#), [18](#), [25](#), [30](#), [32](#), [50](#)
- nties, [27](#)
- nties.integer64 (is.sorted.integer64), [38](#)
- NULL, [6](#)
- nunique, [27](#), [34](#)
- nunique.integer64, [33](#)

- nunique.integer64
  - (is.sorted.integer64), 38
- nvalid, 27
- nvalid.integer64 (is.sorted.integer64), 38
- optimizer64, 43
- optimizer64 (benchmark64), 19
- optimizer64.data, 43
- order, 8, 24, 48, 53
- order (bit64S3), 23
- order.integer64, 8, 50
- order.integer64 (sort.integer64), 52
- ordercache, 20, 27, 39
- ordercache (hashcache), 33
- orderdup, 29
- orderdup (sortnut), 53
- orderfin, 41
- orderfin (sortnut), 53
- orderkey, 40
- orderkey (sortnut), 53
- ordernut (sortnut), 53
- orderpos, 41
- orderpos (sortnut), 53
- orderqtl, 46
- orderqtl (sortnut), 53
- orderrnk, 50
- orderrnk (sortnut), 53
- ordertab, 59
- ordertab (sortnut), 53
- ordertie, 61
- ordertie (sortnut), 53
- orderuni, 63
- orderuni (sortnut), 53
- orderupo, 62
- orderupo (sortnut), 53
- plusclass, 8
- prank, 27, 44, 50
- prank.integer64, 45
- print, 6
- print.cache (cache), 26
- print.integer64, 6
- print.integer64 (bit64-package), 2
- prod, 8, 57
- prod.integer64, 8
- prod.integer64 (sum.integer64), 57
- qtile, 27, 45, 45
- qtile.integer64, 44
- quantile, 8, 47
- quantile.integer64, 8, 27
- quantile.integer64 (qtile), 45
- quickorder.integer64
  - (ramsort.integer64), 47
- quicksort.integer64
  - (ramsort.integer64), 47
- quicksortorder.integer64
  - (ramsort.integer64), 47
- radixorder.integer64
  - (ramsort.integer64), 47
- radixsort.integer64
  - (ramsort.integer64), 47
- radixsortorder.integer64
  - (ramsort.integer64), 47
- ramorder, 33, 48
- ramorder.integer64, 40
- ramorder.integer64 (ramsort.integer64), 47
- ramsort, 33, 48, 49, 52
- ramsort.default, 49
- ramsort.integer64, 4, 47
- ramsortorder, 33, 48, 52
- ramsortorder.integer64
  - (ramsort.integer64), 47
- range, 5, 7, 57
- range.integer64, 7
- range.integer64 (sum.integer64), 57
- rank, 8, 50
- rank (bit64S3), 23
- rank.integer64, 8, 27, 45, 47, 49, 61
- rbind, 5, 6, 25
- rbind.integer64, 6
- rbind.integer64 (c.integer64), 25
- read.table, 8
- remcache (cache), 26
- rep, 5, 6, 51
- rep.integer64, 6, 25, 50, 51, 52
- repeat.time, 19
- round, 7, 32
- round.integer64, 7
- round.integer64 (format.integer64), 31
- S3, 4, 24
- S4, 4
- save, 8
- scale, 32

- scale.integer64 (format.integer64), 31
- seq, 5, 6, 51
- seq.integer64, 6, 25, 51
- serialize, 4, 8
- setattr, 4
- setattributes, 4
- setcache (cache), 26
- shellorder.integer64
  - (ramsort.integer64), 47
- shellsort.integer64
  - (ramsort.integer64), 47
- shellsortorder.integer64
  - (ramsort.integer64), 47
- sign, 7, 32
- sign.integer64, 7
- sign.integer64 (format.integer64), 31
- signif, 7, 32
- signif.integer64, 7
- signif.integer64 (format.integer64), 31
- sort, 8, 48, 52, 53
- sort.integer64, 4, 8, 49, 52
- sortcache, 27, 39, 49, 53
- sortcache (hashcache), 33
- sortfin, 41
- sortfin (sortnut), 53
- sortnut, 53
- sortordercache, 20, 23, 27, 39, 41
- sortordercache (hashcache), 33
- sortorderdup, 29
- sortorderdup (sortnut), 53
- sortorderkey, 40
- sortorderkey (sortnut), 53
- sortorderpos, 41
- sortorderpos (sortnut), 53
- sortorderrnk, 50
- sortorderrnk (sortnut), 53
- sortordertab, 59
- sortordertab (sortnut), 53
- sortordertie, 61
- sortordertie (sortnut), 53
- sortorderuni, 63
- sortorderuni (sortnut), 53
- sortorderupo, 62
- sortorderupo (sortnut), 53
- sortqtl, 46
- sortqtl (sortnut), 53
- sorttab (sortnut), 53
- sorttuni, 63
- sorttuni (sortnut), 53
- sqrt, 5, 7, 32
- sqrt.integer64, 7
- sqrt.integer64 (format.integer64), 31
- still.identical (cache), 26
- storage.mode, 5
- storage.mode<-, 10
- str, 3, 6, 10
- str.integer64, 6
- str.integer64 (bit64-package), 2
- sum, 8, 57
- sum.integer64, 8, 28, 57
- summary, 8
- summary.integer64, 8, 27
- summary.integer64 (qtile), 45
- system.time, 19
- table, 8, 35, 56, 59, 60, 62, 63
- table.integer64, 8, 19, 27, 58, 63
- tabulate, 60
- tiepos, 8, 27, 60
- tiepos.integer64, 8
- trunc, 7, 32
- trunc.integer64, 7
- trunc.integer64 (format.integer64), 31
- typeof, 5
- unipos, 8, 27, 61, 63
- unipos.integer64, 8, 19, 60, 61
- unique, 8, 35, 56, 61–63
- unique.integer64, 8, 19, 27, 29, 40, 60, 62, 62
- unlist, 9
- unserialize, 8
- vector, 10
- vmode, 5
- warning, 57
- write.table, 8
- xor, 7, 65
- xor.integer64, 7, 32, 64
- xtabs, 59