

Package ‘bomrang’

December 15, 2017

Type Package

Title Australian Government Bureau of Meteorology Data from R

Version 0.1.1

Description Provides functions to interface with Australian Government Bureau of Meteorology (BoM) data, fetching data and returning a tidy data frame of précis forecasts, current weather data from stations, agriculture bulletin data, BoM 0900 or 1500 weather bulletins or a raster stack object of satellite imagery from GeoTIFF files. Data (c) Australian Government Bureau of Meteorology Creative Commons (CC) Attribution 3.0 licence or Public Access Licence (PAL) as appropriate. See <http://www.bom.gov.au/other/copyright.shtml> for further details.

URL <https://github.com/ropensci/bomrang>

BugReports <https://github.com/ropensci/bomrang/issues>

License MIT + file LICENSE

Depends R (>= 3.2.0)

Imports curl (>= 2.8.1), data.table (>= 1.10.4), dplyr (>= 0.7.0), foreign, httr (>= 1.2.1), hoardr, janitor, jsonlite (>= 1.5), magrittr (>= 1.5), raster, rgdal, readr (>= 1.1.1), rvest, tidyr (>= 0.6.3), utils, xml2 (>= 1.1.1)

Encoding UTF-8

LazyData true

Suggests covr, testthat, knitr, rmarkdown, ggplot2, ggthemes, grid, gridExtra, maps, mapproj

RoxygenNote 6.0.1

NeedsCompilation no

ByteCompile TRUE

VignetteBuilder knitr

X-schema.org-applicationCategory Tools

X-schema.org-keywords bom, meteorological-data, weather-forecast, australia, weather, weather-data, meteorology, australia-bureau-of-meteorology

X-schema.org-isPartOf <https://ropensci.org>

Author Adam Sparks [aut, cre] (0000-0002-0061-8359),
 Mark Padgham [aut] (0000-0003-2172-5265),
 Hugh Parsonage [aut] (0000-0003-4055-0835),
 Keith Pembleton [aut] (0000-0002-1896-4516)

Maintainer Adam Sparks <adamhsparks@gmail.com>

Repository CRAN

Date/Publication 2017-12-15 08:17:37 UTC

R topics documented:

bomrang	2
bomrang-deprecated	3
get_ag_bulletin	3
get_available_imagery	5
get_current_weather	6
get_precis_forecast	7
get_satellite_imagery	9
get_weather_bulletin	10
manage_cache	12
sweep_for_stations	13
update_forecast_towns	13
update_station_locations	14

Index	15
--------------	-----------

bomrang	<i>Fetches Australian Government Bureau of Meteorology (BoM) Weather Data Files and Returns a Tidy Data Frame or Raster Stack Object of the Data.</i>
---------	---

Description

Fetches Australian Government Bureau of Meteorology (BoM) Weather Data Files and Returns a Tidy Data Frame or Raster Stack Object of the Data.

Author(s)

Adam H Sparks and Mark Padgham and Hugh Parsonage and Keith Pembleton

See Also

Useful links:

- <https://github.com/ropensci/bomrang>
- Report bugs at <https://github.com/ropensci/bomrang/issues>

bomrang-deprecated *Deprecated function(s) in the bomrang package*

Description

These functions are now deprecated in **bomrang**.

Usage

bomrang_cache_list()

bomrang_cache_details()

bomrang_cache_delete()

bomrang_cache_delete_all()

Details

bomrang_cache_list	now superceded by manage_cache\$list
bomrang_cache_details	now superceded by manage_cache\$details
bomrang_cache_delete	now superceded by manage_cache\$delete
bomrang_cache_delete_all	now superceded by manage_cache\$delete_all

get_ag_bulletin *Get BoM Agriculture Bulletin Information for Select Stations*

Description

Fetch the BoM agricultural bulletin information and return it in a tidy data frame

Usage

```
get_ag_bulletin(state = "AUS")
```

Arguments

state	Australian state or territory as full name or postal code. Fuzzy string matching via agrep is done. Defaults to "AUS" returning all state bulletins, see details for more.
-------	--

Details

Allowed state and territory postal codes, only one state per request or all using AUS.

NSW New South Wales

NT Northern Territory

QLD Queensland

SA South Australia

TAS Tasmania

VIC Victoria

WA Western Australia

AUS Australia, returns bulletin for all states and NT

Value

Tidy data frame of a Australia BoM agricultural bulletin information. For full details of fields and units returned see Appendix 3 in the *bomrang* vignette, use `vignette("bomrang", package = "bomrang")` to view.

Author(s)

Adam H Sparks, <adamhsparks@gmail.com>

References

Agricultural observations are retrieved from the Australian Bureau of Meteorology (BoM) Weather Data Services Agriculture Bulletins, <http://www.bom.gov.au/catalogue/observations/about-agricultural.shtml>

and

Australian Bureau of Meteorology (BoM) Weather Data Services Observation of Rainfall, <http://www.bom.gov.au/climate/how/observations/rain-measure.shtml>

Station location and other metadata are sourced from the Australian Bureau of Meteorology (BoM) webpage, Bureau of Meteorology Site Numbers: <http://www.bom.gov.au/climate/cdo/about/site-num.shtml>

Examples

```
## Not run:  
ag_bulletin <- get_ag_bulletin(state = "QLD")  
  
## End(Not run)
```

get_available_imagery *Get a Listing of Available BoM Satellite GeoTIFF Imagery*

Description

Fetch a listing of BoM GeoTIFF satellite imagery from <ftp://ftp.bom.gov.au/anon/gen/gms/> to determine which files are currently available for download. Files are available at ten minute update frequency with a 24 hour delete time. Useful to know the most recent files available and then specify in the [get_satellite_imagery](#) function.

Usage

```
get_available_imagery(product_id = "all")
```

Arguments

product_id	Character. BoM product ID of interest for which a list of available images will be returned. Defaults to all images currently available.
------------	--

Details

Valid BoM satellite Product IDs for GeoTIFF files include:

- IDE00420** AHI cloud cover only 2km FD GEOS GIS
- IDE00421** AHI IR (Ch13) greyscale 2km FD GEOS GIS
- IDE00422** AHI VIS (Ch3) greyscale 2km FD GEOS GIS
- IDE00423** AHI IR (Ch13) Zehr 2km FD GEOS GIS
- IDE00425** AHI VIS (true colour) / IR (Ch13 greyscale) composite 1km FD GEOS GIS
- IDE00426** AHI VIS (true colour) / IR (Ch13 greyscale) composite 2km FD GEOS GIS
- IDE00427** AHI WV (Ch8) 2km FD GEOS GIS
- IDE00430** AHI cloud cover only 2km AUS equirect. GIS
- IDE00431** AHI IR (Ch13) greyscale 2km AUS equirect. GIS
- IDE00432** AHI VIS (Ch3) greyscale 2km AUS equirect. GIS
- IDE00433** AHI IR (Ch13) Zehr 2km AUS equirect. GIS
- IDE00435** AHI VIS (true colour) / IR (Ch13 greyscale) composite 1km AUS equirect. GIS
- IDE00436** AHI VIS (true colour) / IR (Ch13 greyscale) composite 2km AUS equirect. GIS
- IDE00437** AHI WV (Ch8) 2km AUS equirect. GIS
- IDE00439** AHI VIS (Ch3) greyscale 0.5km AUS equirect. GIS

Value

A vector of all available files for the requested Product ID(s).

Author(s)

Adam H Sparks, <adamhsparks@gmail.com>

References

Australian Bureau of Meteorology (BoM) High-definition satellite images <http://www.bom.gov.au/australia/satellite/index.shtml>

Examples

```
## Not run:
Check availability of AHI VIS (true colour) / IR (Ch13 greyscale) composite
1km FD GEOS GIS images
imagery <- get_available_imagery(product_id = "IDE00425")

## End(Not run)
```

get_current_weather *Get Current Weather Observations of a BoM Station*

Description

Get Current Weather Observations of a BoM Station

Usage

```
get_current_weather(station_name, strict = FALSE, latlon = NULL,
  raw = FALSE, emit_latlon_msg = TRUE, as.data.table = FALSE)
```

Arguments

station_name	The name of the weather station. Fuzzy string matching via agrep is done.
strict	(logical) If TRUE, station_name must match the station name exactly, except that station_name need not be upper case. Note this may be different to full_name in the response. See Details .
latlon	A length-2 numeric vector giving the decimal degree latitude and longitude (in that order), e.g. latlon = c(-34, 151) for Sydney. When given instead of station_name, the nearest station (in this package) is used, with a message indicating the nearest such station. (See also sweep_for_stations .) Ignored if used in combination with station_name, with a warning.
raw	Logical. Do not convert the columns data.table to the appropriate classes. (FALSE by default.)
emit_latlon_msg	Logical. If TRUE (the default), and latlon is selected, a message is emitted before the table is returned indicating which station was actually used (i.e. which station was found to be nearest to the given coordinate).
as.data.table	Return result as a data.table.

Details

Station names are not consistently named within the Bureau, so the response may contain a different `full_name` to the one matched, even if `strict = TRUE`. For example, `get_current_weather("CASTLEMAINE PRISON")` is Castlemaine, not Castlemaine Prison.

Note that the column `local_date_time_full` is set to a POSIXct object in the local time of the **user**. For more details see the vignette "Current Weather Fields": `vignette("Current Weather Fields", package = "bomrang")` for a complete list of fields and units.

Value

full details of fields and units returned, see Appendix 1 in the *bomrang* vignette, use `vignette("bomrang", package = "bomrang")` to view.

Author(s)

Hugh Parsonage, <hugh.parsonage@gmail.com>

References

Weather data observations are retrieved from: Australian Bureau of Meteorology (BoM) Weather Data Services, Observations - individual stations: <http://www.bom.gov.au/catalogue/data-feeds.shtml>

Station location and other metadata are sourced from the Australian Bureau of Meteorology (BoM) webpage, Bureau of Meteorology Site Numbers: <http://www.bom.gov.au/climate/cdo/about/site-num.shtml>

Examples

```
## Not run:
# warning
Melbourne_weather <- get_current_weather("Melbourne")

# no warning
Melbourne_weather <- get_current_weather("Melbourne (Olympic Park)")

# Get weather by latitude and longitude:
get_current_weather(latlon = c(-34, 151))

## End(Not run)
```

get_precis_forecast *Get BoM Daily Précis Forecast for Select Towns*

Description

Fetch the BoM daily précis forecast and return a tidy data frame of the seven day town forecast for a specified state or territory.

Usage

```
get_precis_forecast(state = "AUS")
```

Arguments

state Australian state or territory as full name or postal code. Fuzzy string matching via [agrep](#) is done. Defaults to "AUS" returning all state bulletins, see details for further information.

Details

Allowed state and territory postal codes, only one state per request or all using AUS.

ACT Australian Capital Territory (will return NSW)

NSW New South Wales

NT Northern Territory

QLD Queensland

SA South Australia

TAS Tasmania

VIC Victoria

WA Western Australia

AUS Australia, returns forecast for all states, NT and ACT

Value

Tidy data frame of a Australia BoM précis seven day forecasts for select towns. For full details of fields and units returned see Appendix 2 in the *bomrang* vignette, use `vignette("bomrang", package = "bomrang")` to view.

Author(s)

Adam H Sparks, <adamhsparks@gmail.com> and Keith Pembleton, <keith.pembleton@usq.edu.au>

References

Forecast data come from Australian Bureau of Meteorology (BoM) Weather Data Services <http://www.bom.gov.au/catalogue/data-feeds.shtml>

Location data and other metadata for towns come from the BoM anonymous FTP server with spatial data <ftp://ftp.bom.gov.au/anon/home/adfd/spatial/>, specifically the DBF file portion of a shapefile, <ftp://ftp.bom.gov.au/anon/home/adfd/spatial/IDM00013.dbf>

Examples

```
## Not run:  
BoM_forecast <- get_precis_forecast(state = "QLD")  
  
## End(Not run)
```

get_satellite_imagery *Get BoM Satellite GeoTIFF Imagery*

Description

Fetch BoM satellite GeoTIFF imagery from <ftp://ftp.bom.gov.au/anon/gen/gms/> and return a raster [stack](#) object of GeoTIFF files. Files are available at ten minute update frequency with a 24 hour delete time. Suggested to check file availability first by using [get_available_imagery](#).

Usage

```
get_satellite_imagery(product_id = NULL, scans = 1, cache = FALSE)
```

Arguments

product_id	Character. BoM product ID to download in GeoTIFF format and import as a stack object. A vector of values from get_available_imagery may be used here. Value is required.
scans	Numeric. Number of scans to download, starting with most recent and progressing backwards, <i>e.g.</i> , 1 - the most recent single scan available , 6 - the most recent hour available, 12 - the most recent 2 hours available, etc. Negating will return the oldest files first. Defaults to 1. Value is optional.
cache	Logical. Store image files locally for later use? If FALSE, the downloaded files are removed when R session is closed. To take advantage of cached files in future sessions, use cache = TRUE. Defaults to FALSE. Value is optional.

Details

Valid BoM satellite Product IDs include:

- IDE00420** AHI cloud cover only 2km FD GEOS GIS
- IDE00421** AHI IR (Ch13) greyscale 2km FD GEOS GIS
- IDE00422** AHI VIS (Ch3) greyscale 2km FD GEOS GIS
- IDE00423** AHI IR (Ch13) Zehr 2km FD GEOS GIS
- IDE00425** AHI VIS (true colour) / IR (Ch13 greyscale) composite 1km FD GEOS GIS
- IDE00426** AHI VIS (true colour) / IR (Ch13 greyscale) composite 2km FD GEOS GIS
- IDE00427** AHI WV (Ch8) 2km FD GEOS GIS
- IDE00430** AHI cloud cover only 2km AUS equirect. GIS
- IDE00431** AHI IR (Ch13) greyscale 2km AUS equirect. GIS
- IDE00432** AHI VIS (Ch3) greyscale 2km AUS equirect. GIS
- IDE00433** AHI IR (Ch13) Zehr 2km AUS equirect. GIS
- IDE00435** AHI VIS (true colour) / IR (Ch13 greyscale) composite 1km AUS equirect. GIS
- IDE00436** AHI VIS (true colour) / IR (Ch13 greyscale) composite 2km AUS equirect. GIS

IDE00437 AHI WV (Ch8) 2km AUS equirect. GIS

IDE00439 AHI VIS (Ch3) greyscale 0.5km AUS equirect. GIS

We cache using **hoardr**, find your cache folder by executing `manage_cache$cache_path_get`.

Value

A raster stack of GeoTIFF images with layers named by BoM Product ID, timestamp and band.

Author(s)

Adam H Sparks, <adamhsparks@gmail.com>

References

Australian Bureau of Meteorology (BoM) High-definition satellite images <http://www.bom.gov.au/australia/satellite/index.shtml>

See Also

[get_available_imagery](#) [manage_cache](#)

Examples

```
## Not run:
# Fetch AHI VIS (true colour) / IR (Ch13 greyscale) composite 1km FD
# GEOS GIS raster stack for most recent single scan available

imagery <- get_satellite_imagery(product_id = "IDE00425", scans = 1)

# Get a list of available image files and use that to specify files for
# download, downloading the two most recent files available

avail <- get_available_imagery(product_id = "IDE00425")
imagery <- get_satellite_imagery(product_id = avail, scans = 2)

## End(Not run)
```

get_weather_bulletin *Get BoM 0900 or 1500 Weather Bulletin*

Description

Fetch the daily BoM 0900 or 1500 weather bulletins and return a tidy data frame for a specified state or territory.

Usage

```
get_weather_bulletin(state = "qld", morning = TRUE)
```

Arguments

state	Australian state or territory as full name or postal code. Fuzzy string matching via <code>agrep</code> is done.
morning	If TRUE, return the 9am bulletin for the nominated state; otherwise return the 3pm bulletin.

Details

Allowed state and territory postal codes:

ACT Australian Capital Territory (will return NSW)

NSW New South Wales

NT Northern Territory

QLD Queensland

SA South Australia

TAS Tasmania

VIC Victoria

WA Western Australia

It is not possible to return weather bulletins for the entire country in a single call. Rainfall figures for the 9am bulletin are generally for the preceding 24 hours, while those for the 3pm bulletin are for the preceding 6 hours since 9am. Note that values are manually entered into the bulletins and sometimes contain typographical errors which may lead to warnings about "NAs introduced by coercion".

Value

Tidy data frame of Australian 9am or 3pm weather observations for a state. For full details of fields and units returned see Appendix 4 in the *bomrang* vignette, use `vignette("bomrang", package = "bomrang")` to view.

Author(s)

Mark Padgham, <mark.padgham@email.com>

References

Daily observation data come from Australian Bureau of Meteorology (BoM) website. The 3pm bulletin for Queensland is, for example, http://www.bom.gov.au/qld/observations/3pm_bulletin.shtml

Examples

```
## Not run:
qld_weather <- get_weather_bulletin (state = "QLD", morning = FALSE)

## End(Not run)
```

`manage_cache`*Manage Locally Cached BoM Files*

Description

Manage cached **bomrang** satellite imagery files with **hoardr**.

Details

The default cache directory is `file.path(rappdirs::user_cache_dir(), "R/bomrang")`, but you can set your own path using `manage_cache$cache_path_set()`

`manage_cache$cache_delete` only accepts one file name, while `manage_cache$cache_delete_all` does not accept any names, but deletes all files. For deleting many specific files, use `manage_cache$cache_delete` in an `lapply()` type call.

Useful user functions

- `manage_cache$cache_path_get()` - get cache path
- `manage_cache$cache_path_set()` - set cache path
- `manage_cache$list()` - returns a character vector of full path file names
- `manage_cache$files()` - returns file objects with metadata
- `manage_cache$details()` - returns files with details
- `manage_cache$delete()` - delete specific files
- `manage_cache$delete_all()` - delete all files, returns nothing

Examples

```
## Not run:

# list files in cache
manage_cache$list()

# delete certain database files
manage_cache$delete("file path")
manage_cache$list()

# delete all files in cache
manage_cache$delete_all()
manage_cache$list()

# set a different cache path from the default
manage_cache$cache_path_set("~/tmp")

## End(Not run)
```

sweep_for_stations *Find Nearest BoM Weather Stations*

Description

Find Nearest BoM Weather Stations

Usage

```
sweep_for_stations(latlon = c(-35.3, 149.2))
```

Arguments

latlon A length-2 numeric vector. By default, Canberra (approximately).

Value

A data frame of all weather stations (in this package) sorted by distance from latlon, ascending.

Author(s)

Hugh Parsonage, <hugh.parsonage@gmail.com>

update_forecast_towns *Update bomrang Internal Database with Latest BoM Forecast Towns*

Description

Download the latest select forecast towns from the BoM server and update bomrang's internal database of précis forecast town names and AAC codes used by [get_precis_forecast](#). There is no need to use this unless you know that a forecast town exists in a more current version of the BoM précis forecast town name database that is not available in the database distributed with [bomrang](#).

Usage

```
update_forecast_towns()
```

Value

Updated database of BoM précis forecast towns

Author(s)

Adam H Sparks, <adamhsparks@gmail.com>

References

Data are sourced from: Australian Bureau of Meteorology (BoM) webpage, "Weather Data Services", <http://www.bom.gov.au/catalogue/data-feeds.shtml>

Examples

```
## Not run:  
update_forecast_towns()  
  
## End(Not run)
```

update_station_locations

Update bomrang Internal Databases with Latest BoM Station Metadata

Description

Download the latest station locations and metadata and update bomrang's internal databases that support the use of [get_current_weather](#) and [get_ag_bulletin](#). There is no need to use this unless you know that a station exists in BoM's database that is not available in the databases distributed with [bomrang](#).

Usage

```
update_station_locations()
```

Value

Updated internal databases of BoM station locations and JSON URLs

Author(s)

Adam H Sparks, <adamhsparks@gmail.com>

References

Station location and other metadata are sourced from the Australian Bureau of Meteorology (BoM) webpage, Bureau of Meteorology Site Numbers: <http://www.bom.gov.au/climate/cdo/about/site-num.shtml>

Examples

```
## Not run:  
update_station_locations()  
  
## End(Not run)
```

Index

[agrep](#), [3](#), [6](#), [8](#), [11](#)

[bomrang](#), [2](#), [13](#), [14](#)

[bomrang-deprecated](#), [3](#)

[bomrang-deprecated-package](#)
([bomrang-deprecated](#)), [3](#)

[bomrang-package](#) ([bomrang](#)), [2](#)

[bomrang_cache_delete](#)
([bomrang-deprecated](#)), [3](#)

[bomrang_cache_delete_all](#)
([bomrang-deprecated](#)), [3](#)

[bomrang_cache_details](#)
([bomrang-deprecated](#)), [3](#)

[bomrang_cache_list](#)
([bomrang-deprecated](#)), [3](#)

[get_ag_bulletin](#), [3](#), [14](#)

[get_available_imagery](#), [5](#), [9](#), [10](#)

[get_current_weather](#), [6](#), [14](#)

[get_precis_forecast](#), [7](#), [13](#)

[get_satellite_imagery](#), [5](#), [9](#)

[get_weather_bulletin](#), [10](#)

[lapply](#), [12](#)

[manage_cache](#), [10](#), [12](#)

[stack](#), [9](#)

[sweep_for_stations](#), [6](#), [13](#)

[update_forecast_towns](#), [13](#)

[update_station_locations](#), [14](#)