

Package ‘cccrm’

June 10, 2020

Title Concordance Correlation Coefficient for Repeated (and Non-Repeated) Measures

Version 2.0.1

Date 2020-06-10

Author Josep Lluís Carrasco <jlcarrasco@ub.edu>, Josep Puig Martínez <j.puig04@gmail.com>

Maintainer Josep Lluís Carrasco <jlcarrasco@ub.edu>

Depends R (>= 4.0.0)

Imports nlme, dplyr, Deriv, tidyselect

Description Estimates the Concordance Correlation Coefficient to assess agreement. The scenarios considered are non-repeated measures, non-longitudinal repeated measures (replicates) and longitudinal repeated measures. The estimation approaches implemented are variance components and U-statistics approaches.

License GPL (>= 2)

RoxygenNote 7.1.0

Encoding UTF-8

NeedsCompilation no

Repository CRAN

Date/Publication 2020-06-10 12:00:09 UTC

R topics documented:

bdaw	2
bfat	2
bpres	3
ccclon	3
ccclonw	5
cccUst	6
cccvc	8

Index	10
--------------	-----------

bdaw

Blood draw data

Description

Plasma cortisol area under curve (AUC) was calculated from the trapezoidal rule over the 12-h period of the hourly blood draws. The subjects were required to repeat the process in five visits. The aim of the agreement study was to assess how well the plasma cortisol AUC from hourly measurements agreed with plasma cortisol AUC that was measured every two hours.

Usage

```
data("bdaw")
```

References

King, TS; Chinchilli, VM; Carrasco, JL. (2007). A repeated measures concordance correlation coefficient, *Statistics in Medicine* 26, 3095-3113.

bfat

Body fat data

Description

Percentage body fat was estimated from skinfold calipers and DEXA on a cohort of 90 adolescent girls. Skinfold caliper and DEXA measurements were taken at ages 12.5, 13 and 13.5. The objective was to determine the amount of agreement between the skinfold caliper and DEXA measurements of percentage body fat.

Usage

```
data("bfat")
```

References

King, TS; Chinchilli, VM; Carrasco, JL. (2007). A repeated measures concordance correlation coefficient, *Statistics in Medicine* 26, 3095-3113.

bpres	<i>Blood pressure data</i>
-------	----------------------------

Description

Systolic and diastolic blood pressure was measured in a sample of 384 subjects using a handle mercury sphyg momanometer device and an automatic device. The blood pressure was simultaneously measured twice by each instrument, thus every subject had four measurements, two by each method.

Usage

```
data("bpres")
```

References

Carrasco, JL; Jover, L. (2003). Estimating the generalized concordance correlation coefficient through variance components. *Biometrics*, 59, 849:858.

ccclon	<i>Concordance Correlation Coefficient for longitudinal repeated measures estimated by variance components</i>
--------	--

Description

Estimation of the concordance correlation coefficient for repeated measurements using the variance components from a linear mixed model. The appropriate intraclass correlation coefficient is used as estimator of the concordance correlation coefficient.

Usage

```
ccclon(dataset, ry, rind, rtime, rmet, covar = NULL, rho = 0, cl = 0.95,
control.lme=list())
```

Arguments

dataset	An object of class <code>data.frame</code> .
ry	Character string. Name of the outcome in the data set.
rind	Character string. Name of the subject variable in the data set.
rtime	Character string. Name of the time variable in the data set.
rmet	Character string. Name of the method variable in the data set.
covar	Character vector. Name of covariables to include in the linear mixed model as fixed effects.
rho	Within subject correlation structure. A value of 0 (default option) stands for compound simmetry and 1 is used for autoregressive of order 1 structure.

<code>cl</code>	Confidence level.
<code>control.lme</code>	A list of control values for the estimation algorithm used in <code>lme</code> function. For further details see <code>lme help</code> .

Details

The concordance correlation coefficient is estimated using the appropriate intraclass correlation coefficient (see Carrasco et al, 2009; Carrasco et al, 2013). The variance components estimates are obtained from a linear mixed model estimated by restricted maximum likelihood. The standard error of CCC is computed using an Taylor's series expansion of 1st order (delta method). Confidence interval is built by applying the Fisher's Z-transformation.

Value

An object of class `ccc`. Generic function `summary` show a summary of the results. The output is a list with the following components:

<code>ccc</code>	Concordance Correlation Coefficient estimate
<code>model</code>	Summary of the linear mixed model
<code>vc</code>	Variance components estimates
<code>sigma</code>	Variance components asymptotic covariance matrix

Author(s)

Josep Puig-Martinez and Josep L. Carrasco

References

Carrasco, JL; King, TS; Chinchilli, VM. (2009). The concordance correlation coefficient for repeated measures estimated by variance components. *Journal of Biopharmaceutical Statistics*, 19, 90:105.

Carrasco, JL; Phillips, BR; Puig-Martinez, J; King, TS; Chinchilli, VM. (2013). Estimation of the concordance correlation coefficient for repeated measures using SAS and R. *Computer Methods and Programs in Biomedicine*, 109, 293-304.

See Also

[ccclonw](#)

Examples

```
data(bdaw)
estccc<-ccclon(bdaw, "AUC", "SUBJ", "VNUM", "MET")
estccc
summary(estccc)
```

ccclonw	<i>Weighted Concordance Correlation Coefficient for longitudinal repeated measures estimated by variance components</i>
---------	---

Description

Estimation of the concordance correlation coefficient (CCC) for repeated measurements using the variance components from a linear mixed model. The appropriate intraclass correlation coefficient is used as estimator of the concordance correlation coefficient. Weights are assigned to repeated measurements in the CCC computation process.

Usage

```
ccclonw(dataset, ry, rind, rtime, rmet, vecD, covar = NULL, rho = 0, cl = 0.95,
control.lme=list())
```

Arguments

dataset	an object of class <code>data.frame</code> .
ry	Character string. Name of the outcome in the data set.
rind	Character string. Name of the subject variable in the data set.
rtime	Character string. Name of the time variable in the data set.
rmet	Character string. Name of the method variable in the data set.
vecD	Vector of weights. The length of the vector must be the same as the number of repeated measures.
covar	Character vector. Name of covariables to include in the linear mixed model as fixed effects.
rho	Within subject correlation structure. A value of 0 (default option) stands for compound symmetry and 1 is used for autoregressive of order 1 structure.
cl	Confidence level.
control.lme	A list of control values for the estimation algorithm used in <code>lme</code> function. For further details see <code>lme</code> help.

Details

The concordance correlation coefficient is estimated using the appropriate intraclass correlation coefficient which expression is modified accordingly to assign different weights to each repeated measurement (see Carrasco et al, 2009; Carrasco et al, 2013). The variance components estimates are obtained from a linear mixed model estimated by restricted maximum likelihood. The standard error of CCC is computed using an Taylor's series expansion of 1st order (delta method). Confidence interval is built by applying the Fisher's Z-transformation.

Value

An object of class ccc. Generic function summary show a summary of the results. The output is a list with the following components:

ccc	Concordance Correlation Coefficient estimate
model	Summary of the linear mixed model
vc	Variance components estimates
sigma	Variance components asymptotic covariance matrix

Author(s)

Josep Puig-Martinez and Josep L. Carrasco

References

Carrasco, JL; King, TS; Chinchilli, VM. (2009). The concordance correlation coefficient for repeated measures estimated by variance components. *Journal of Biopharmaceutical Statistics*, 19, 90:105.

Carrasco, JL; Phillips, BR; Puig-Martinez, J; King, TS; Chinchilli, VM. (2013). Estimation of the concordance correlation coefficient for repeated measures using SAS and R. *Computer Methods and Programs in Biomedicine*, 109, 293-304.

See Also

[ccclon](#)

Examples

```
data(bfat)
estccc<-ccclonw(bfat,"BF","SUBJECT","VISITNO","MET",vecD=c(2,1,1))
estccc
summary(estccc)
```

cccUst	<i>Repeated Measures Concordance Correlation Coefficient estimated by U-statistics</i>
--------	--

Description

Estimation of the concordance correlation coefficient for repeated measurements using the U-statistics approach. The function is also applicable for the non-repeated measurements scenario.

Usage

```
cccUst(dataset, ry, rmet, rtime = NULL, Dmat = NULL, delta = 1, cl = 0.95)
```

Arguments

dataset	An object of class <code>data.frame</code> .
ry	Character string. Name of the outcome in the data set.
rmet	Character string. Name of the method variable in the data set.
rtime	Character string. Name of the time variable in the data set.
Dmat	Matrix of weights.
delta	Power of the differences. A value of 0 provides an estimate that is comparable to a repeated measures version of kappa index.
cl	Confidence level.

Value

A vector that includes the point estimate, confidence interval and standard error of the CCC. Additionally the Fisher's Z-transformation value and its standard error are also provided.

Author(s)

Josep Puig-Martinez and Josep L. Carrasco

References

King, TS and Chinchilli, VM. (2001). A generalized concordance correlation coefficient for continuous and categorical data. *Statistics in Medicine*, 20, 2131:2147.

King, TS; Chinchilli, VM; Carrasco, JL. (2007). A repeated measures concordance correlation coefficient. *Statistics in Medicine*, 26, 3095:3113.

Carrasco, JL; Phillips, BR; Puig-Martinez, J; King, TS; Chinchilli, VM. (2013). Estimation of the concordance correlation coefficient for repeated measures using SAS and R. *Computer Methods and Programs in Biomedicine*, 109, 293-304.

Examples

```
# Non-longitudinal scenario
data(bpres)
newdat=bpres[bpres$NM==1,]
estccc=cccUst(newdat,"DIA","METODE")
estccc

# Longitudinal scenario
data(bdaw)
estccc=cccUst(bdaw,"AUC","MET","VNUM")
estccc

# Weighted CCC
data(bfat)
estccc=cccUst(bfat,"BF","MET","VISITNO",Dmat=diag(c(2,1,1)))
estccc
```

cccvc	<i>Concordance Correlation Coefficient estimated by Variance Components</i>
-------	---

Description

Estimation of the concordance correlation coefficient for non-repeated measurements and non-longitudinal repeated measurements (replicates) using the variance components from a linear mixed model. The appropriate intraclass correlation coefficient is used as estimator of the concordance correlation coefficient.

Usage

```
cccvc(dataset, ry, rind, rmet, covar = NULL, int = FALSE, cl=0.95, control.lme=list())
```

Arguments

dataset	an object of class <code>data.frame</code> .
ry	Character string. Name of the outcome in the data set.
rind	Character string. Name of the subject variable in the data set.
rmet	Character string. Name of the method variable in the data set.
covar	Character vector. Name of covariables to include in the linear mixed model as fixed effects.
int	Boolean indicating if the subject-method interaction has to be included in the model
cl	Confidence level.
control.lme	A list of control values for the estimation algorithm used in <code>lme</code> function. For further details see <code>lme</code> help.

Details

The concordance correlation coefficient is estimated using the appropriate intraclass correlation coefficient (see Carrasco and Jover, 2003; Carrasco et al., 2009; Carrasco et al, 2013). The scenarios considered are non-repeated measurements (only one measurement by subject and method) and non-longitudinal repeated measurements, i.e. replicates (multiple measurements by subject and method). The variance components estimates are obtained from a linear mixed model estimated by restricted maximum likelihood. The standard error of CCC is computed using an Taylor's series expansion of 1st order (delta method). Confidence interval is built by applying the Fisher's Z-transformation.

Value

An object of class `ccc`. Generic function summary show a summary of the results. The output is a list with the following components:

ccc	Concordance Correlation Coefficient estimate
-----	--

model	Summary of the linear mixed model
vc	Variance components estimates
sigma	Variance components asymptotic covariance matrix

Author(s)

Josep Puig-Martinez and Josep L. Carrasco

References

Carrasco, JL; Jover, L. (2003). Estimating the generalized concordance correlation coefficient through variance components. *Biometrics*, 59, 849:858.

Carrasco, JL; King, TS; Chinchilli, VM. (2009). The concordance correlation coefficient for repeated measures estimated by variance components. *Journal of Biopharmaceutical Statistics*, 19, 90:105.

Carrasco, JL; Phillips, BR; Puig-Martinez, J; King, TS; Chinchilli, VM. (2013). Estimation of the concordance correlation coefficient for repeated measures using SAS and R. *Computer Methods and Programs in Biomedicine*, 109, 293-304.

Examples

```
data(bpres)

# Scenario 1.
#Only 1 measure by subject and method.
#No subject-method interaction included in the model.

newdat=bpres[bpres$NM==1,]
estccc=cccvc(newdat,"DIA","ID","METODE")
estccc
summary(estccc)

# Scenario 2.
#Two measures by subject and method.
#No subject-method interaction included in the model.

estccc=cccvc(bpres,"DIA","ID","METODE")
estccc
summary(estccc)
```

Index

*Topic **datasets**

- bdaw, [2](#)
- bfat, [2](#)
- bpres, [3](#)

- bdaw, [2](#)
- bfat, [2](#)
- bpres, [3](#)

- ccclon, [3](#), [6](#)
- ccclonw, [4](#), [5](#)
- cccUst, [6](#)
- cccvc, [8](#)