

Package ‘clam’

July 26, 2025

Type Package

Title Classical Age-Depth Modelling of Cores from Deposits

Version 2.6.3

Description Performs 'classical' age-depth modelling of dated sediment deposits - prior to applying more sophisticated techniques such as Bayesian age-depth modelling. Any radiocarbon dated depths are calibrated. Age-depth models are constructed by sampling repeatedly from the dated levels, each time drawing age-depth curves. Model types include linear interpolation, linear or polynomial regression, and a range of splines. See Blaauw (2010) <[doi:10.1016/j.quageo.2010.01.002](https://doi.org/10.1016/j.quageo.2010.01.002)>.

License GPL (>= 2)

Language en-GB

Imports grDevices, graphics, stats, utils, data.table, rintcal (>= 1.3.0), rice (>= 1.3.0)

RoxygenNote 7.3.2

Suggests knitr, rmarkdown, utf8

VignetteBuilder knitr

Encoding UTF-8

NeedsCompilation no

Author Maarten Blaauw [aut, cre] (ORCID:
<<https://orcid.org/0000-0002-5680-1515>>),
J. Andres Christen [ctb] (ORCID:
<<https://orcid.org/0000-0002-5795-4345>>),
Judith Esquivel Vazquez [ctb],
Simon Goring [ctb]

Maintainer Maarten Blaauw <maarten.blaauw@qub.ac.uk>

Repository CRAN

Date/Publication 2025-07-26 07:50:02 UTC

Contents

| | |
|------------------------|---|
| clam-package | 2 |
|------------------------|---|

| | |
|-------------------------|----|
| add.dates | 2 |
| clam | 4 |
| deptime.age | 11 |
| deptime.depth | 12 |
| plot_proxies | 13 |

| | |
|--------------|-----------|
| Index | 15 |
|--------------|-----------|

| | |
|--------------|-------------|
| clam-package | <i>clam</i> |
|--------------|-------------|

Description

Classical (non-Bayesian) age-depth modelling.

Author(s)

Maintainer: Maarten Blaauw <maarten.blaauw@qub.ac.uk> ([ORCID](#))

Other contributors:

- J. Andres Christen ([ORCID](#)) [contributor]
- Judith Esquivel Vazquez [contributor]
- Simon Goring [contributor]

| | |
|-----------|-------------------------------------|
| add.dates | <i>Add dates to age-depth plots</i> |
|-----------|-------------------------------------|

Description

Add dated depths to plots, e.g. to show dates that weren't used in the age-depth model

Usage

```
add.dates(
  mn,
  sdev,
  depth,
  cc = 1,
  above = 0.001,
  exx = 50,
  normal = TRUE,
  normalise = TRUE,
  t.a = 3,
  t.b = 4,
  age.res = 100,
  times = 20,
```

```

col = rgb(1, 0, 0, 0.5),
border = rgb(1, 0, 0, 0.5),
rotate.axes = FALSE,
mirror = TRUE,
up = TRUE,
BCAD = FALSE
)

```

Arguments

| | |
|-------------|--|
| mn | Reported mean of the date. Can be multiple dates. |
| sdev | Reported error of the date. Can be multiple dates. |
| depth | Depth of the date. |
| cc | The calibration curve to use: cc=1 for IntCal20 (northern hemisphere terrestrial), cc=2 for Marine20 (marine), cc=3 for SHcal20 (southern hemisphere terrestrial), cc=0 for none (dates that are already on the cal BP scale). |
| above | Threshold for plotting of probability values. Defaults to above=1e-3. |
| exx | Exaggeration of probability distribution plots. Defaults to exx=50. |
| normal | By default, Bacon uses the student's t-distribution to treat the dates. Use normal=TRUE to use the normal/Gaussian distribution. This will generally give higher weight to the dates. |
| normalise | By default, the date is normalised to an area of 1 (normalise=TRUE). |
| t.a | The dates are treated using the student's t distribution by default (normal=FALSE). The student's t-distribution has two parameters, t.a and t.b, set at 3 and 4 by default (see Christen and Perez, 2010). If you want to assign narrower error distributions (more closely resembling the normal distribution), set t.a and t.b at for example 33 and 34 respectively (e.g., for specific dates in your .csv file). For symmetry reasons, t.a must always be equal to t.b-1. |
| t.b | The dates are treated using the student's t distribution by default (normal=FALSE). The student's t-distribution has two parameters, t.a and t.b, set at 3 and 4 by default (see Christen and Perez, 2010). If you want to assign narrower error distributions (more closely resembling the normal distribution), set t.a and t.b at for example 33 and 34 respectively (e.g., for specific dates in your .csv file). For symmetry reasons, t.a must always be equal to t.b-1. |
| age.res | Resolution of the date's distribution. Defaults to date.res=100. |
| times | The extent of the range to be calculated for each date. Defaults to times=20. |
| col | The colour of the ranges of the date. Default is semi-transparent red: col=rgb(1,0,0,.5). |
| border | The colours of the borders of the date. Default is semi-transparent red: border=rgb(1,0,0,0.5). |
| rotate.axes | The default of plotting age on the horizontal axis and event probability on the vertical one can be changed with rotate.axes=TRUE. |
| mirror | Plot the dates as 'blobs'. Set to mirror=FALSE to plot simple distributions. |
| up | Directions of distributions if they are plotted non-mirrored. Default up=TRUE. |
| BCAD | The calendar scale of graphs is in cal BP by default, but can be changed to BC/AD using BCAD=TRUE. |

Details

Sometimes it is useful to add additional dating information to age-depth plots, e.g., to show outliers or how dates calibrate with different estimated offsets.

Value

A date's distribution, added to an age-depth plot.

Author(s)

Maarten Blaauw, J. Andres Christen

Examples

```
base_temp_dir <- tempdir()
clam_dir <- file.path(base_temp_dir, "clam_runs")
dir.create(clam_dir, recursive = TRUE, showWarnings = FALSE)
clam(, coredir=clam_dir, ask=FALSE)
add.dates(5000, 100, 60)
```

clam

clam: Classical Age-Depth Modelling of Cores from Deposits

Description

Performs 'classical' age-depth modelling of dated sediment deposits - prior to applying more sophisticated techniques such as Bayesian age-depth modelling. Any radiocarbon dated depths are calibrated. Age-depth models are constructed by sampling repeatedly from the dated levels, each time drawing age-depth curves. Model types include linear interpolation, linear or polynomial regression, and a range of splines. See Blaauw (2010). <doi:10.1016/j.quageo.2010.01.002>.

Produce age-depth models for cores with dated depths.

Usage

```
clam(
  core = "Example",
  type = 1,
  smooth = NULL,
  prob = 0.95,
  its = 1000,
  coredir = NULL,
  ask = TRUE,
  wghts = 1,
  cc = 1,
  cc1 = "3Col_intcal20.14C",
  cc2 = "3Col_marine20.14C",
  cc3 = "3Col_shcal20.14C",
```

```
cc4 = "mixed.14C",
postbomb = FALSE,
pb1 = "postbomb_NH1.14C",
pb2 = "postbomb_NH2.14C",
pb3 = "postbomb_NH3.14C",
pb4 = "postbomb_SH1-2.14C",
pb5 = "postbomb_SH3.14C",
ccdir = "",
outliers = NULL,
ignore = NULL,
youngest = NULL,
extradates = NULL,
slump = NULL,
est = 1,
calibt = FALSE,
mixed.effect = FALSE,
dmin = NULL,
dmax = NULL,
every = 1,
yrmin = NULL,
yrmax = NULL,
yrsteps = 1,
pbsteps = 0.01,
hpdsteps = 1,
BCAD = FALSE,
decimals = 0,
cmyr = FALSE,
ageofdepth = NULL,
depth = "cm",
depthseq = NULL,
depths.file = FALSE,
thickness = 1,
hiatus = NULL,
remove.reverse = 0.5,
times = 5,
sep = ",",
ext = ".csv",
runname = NULL,
storedat = TRUE,
threshold = 1e-06,
proxies = FALSE,
revaxes = FALSE,
revd = TRUE,
revyr = TRUE,
calhght = 0.3,
maxhght = 0.01,
mirror = TRUE,
plotrange = TRUE,
```

```

    bty = "1",
    mar = c(3.5, 3, 2, 1),
    mgp = c(2, 1, 0),
    plotpdf = TRUE,
    plotpng = TRUE,
    greyscale = NULL,
    yrlab = NULL,
    dlab = NULL,
    calcol = rgb(0, 0.5, 0.5, 0.5),
    C14col = rgb(0, 0, 1, 0.5),
    outcol = "red",
    outsize = 1,
    bestcol = "black",
    rangecol = rgb(0, 0, 0, 0.3),
    slumpcol = grey(0.75),
    plotname = TRUE,
    ash = FALSE,
    rule = 1
  )

```

Arguments

| | |
|---------|--|
| core | Name of the core, given using quotes. Defaults to the core provided with clam, core="Example". |
| type | The type of age-depth model. Five different types are provided: <ol style="list-style-type: none"> 1. linear interpolation between neighbouring levels (1, "int", "inter" or "interp") 2. linear or higher polynomial regression (2, "reg", "regr", "poly" or "polyn", default linear) 3. cubic spline (3, "spl" or "spline") 4. smooth spline (4, "sm" or "smooth", default smoothing 0.3) 5. locally weighted spline (5, "loess" or "lowess", default smoothing 0.75, cannot extrapolate) |
| smooth | Degree of smoothing. Gives polynomial degree for model type 2. Not relevant for type=1 or type=3. <ul style="list-style-type: none"> • for type=2: smooth=1 (linear), smooth=2 second-order polynomial, smooth=3 for third-order polynomial, etc. • for type=4: smooth=0.3 • for type=5: smooth=0.75 |
| prob | Confidence intervals (between 0 and 1), default prob=0.95 or 95%. |
| its | Amount of age-model iterations; defaults to its=1000. |
| coredir | The directory where core runs are stored (each core in its own directory named after the core's name). |
| ask | By default, and as per R rules, clam will ask if it is OK to make or write to a directory. Defaults to coredir="clam_runs", or to coredir="Cores" if this folder exists where R is working. |

| | |
|------------|--|
| wghts | Weights can be applied to dated depths as follows: <ul style="list-style-type: none"> • 0 no weighting • 1 weighted to calibrated probabilities of sampled calendar years (default, wghts=1). • 2 weighted to (inverse squared) errors of the dates. |
| cc | calibration curve for C14 dates (1, 2 or 3). |
| cc1 | For terrestrial, northern hemisphere C14 dates. |
| cc2 | For marine C14 dates. |
| cc3 | For southern hemisphere C14 dates. |
| cc4 | For mixed terrestrial/marine C14 dates. |
| postbomb | Use a postbomb curve for negative (i.e. postbomb) 14C ages. 0 = none, 1 = NH1, 2 = NH2, 3 = NH3, 4 = SH1-2, 5 = SH3. See http://calib.org/CALIBomb/ . |
| pb1 | For Northern hemisphere region 1 postbomb C14 dates. |
| pb2 | For Northern hemisphere region 2 postbomb C14 dates. |
| pb3 | For Northern hemisphere region 3 postbomb C14 dates. |
| pb4 | For Southern hemisphere regions 1-2 postbomb C14 dates. |
| pb5 | For Southern hemisphere region 3 postbomb C14 dates. |
| ccdir | Directory where the calibration curves for C14 dates cc are located. By default ccdir="". For example, use ccdir="." to choose current working directory, or ccdir="Curves/" to choose sub-folder Curves/. |
| outliers | The number of any dates to be considered outlying, e.g. c(5,6) for the fifth and sixth dated depth counting from the top of a core. |
| ignore | The number of any dates that should be ignored, e.g., c(5,6) for the fifth and sixth date counting from the top of a core. |
| youngest | The age beyond which dates should be truncated (e.g., youngest=-60 if the core was sampled in -60 cal BP or AD 2010). |
| extradates | Depths of any additional dates with their files of ages and probabilities. |
| slump | Upper and lower depths of sections of abrupt accumulation that should be excised, e.g., c(600, 550, 120, 100) for two sections of 600-550 and 120-100 cm depth. |
| est | Which point estimate to use as 'best' age. It is highly recommended to not only use these 'best' point estimates, as chronological uncertainties are often considerable and should not be ignored. <ol style="list-style-type: none"> 1. averages of age-depth model derived ages (default, est=1) 2. midpoints of age-depth model derived age estimates 3. midpoints of calibrated ranges 4. weighted means of calibrated ranges 5. medians of calibrated distributions 6. maximum densities of calibrated distributions 7. midpoints of entire calibrated distributions (including years outside the calibrated ranges) |

| | |
|----------------|---|
| calibt | Calibration based on the student-t distribution. By default, the Gaussian distribution is used (calibt=FALSE). To use the student-t distribution, provide two parameters such as calibt=c(3,4). |
| mixed.effect | Set to TRUE to activate mixed-effect modelling. |
| dmin | Minimum depth of age-depth model (e.g., extrapolate). |
| dmax | Maximum depth of age-depth model (e.g., extrapolate). |
| every | Resolution at which (ages for) depths are calculated. |
| yrmin | Minimum of calendar axis of age-depth plot (calculate automatically by default). |
| yrmax | Maximum of calendar axis of age-depth plot (calculated automatically by default). |
| yrsteps | Temporal resolution at which calibrated ages are calculated (in calendar years). |
| pbsteps | Temporal resolution at which postbomb C14 ages are calibrated (in calendar years). |
| hpdsteps | Temporal resolution at which highest posterior density ranges are calibrated (in calendar years). |
| BCAD | Use BC/AD or cal BP scale. |
| decimals | Amount of decimals for rounding. |
| cmyr | Accumulation rates can be provided as yr/cm (default, cmyr=TRUE, more accurately named deposition times) or cm/yr (cmyr=FALSE). |
| ageofdepth | Calculate age estimates of a specific depth. |
| depth | Depth units. |
| depthseq | Sequence of depths for which age estimates are to be calculated (default: from dmin to dmax with steps of size every) |
| depths.file | Use a file with depths for depthseq. |
| thickness | Thickness of the dated samples. |
| hiatus | Depths of any hiatuses, e.g., c(500, 300). Each sub-section must have at least 2 dates (4 for smoothing spline; does not work with loess as it cannot extrapolate). |
| remove.reverse | Proportion of age-models with reversals that can be removed before prompting a warning. Set at FALSE to avoid removing models with reversals. |
| times | Half-range of calibration curve used to calibrate dates (multiplication factor for the dates' errors). |
| sep | Separator between the fields of the plain text file containing the dating information. |
| ext | Extension of the file containing the dating information. |
| runname | Text to add to the core name for specific runs, e.g., "MyCore_Test1" |
| storedat | Store the dates and age-model within R after a clam run. Defaults to storedat=TRUE. |
| threshold | Below which value should probabilities be excluded from calculations. |
| proxies | Set to TRUE to plot proxies against age after the run. |
| revaxes | Set to TRUE to plot ages on the vertical axis and depth on the horizontal axis. |
| revd | Plot depth axis in reverse. |

| | |
|-----------|--|
| revyr | Plot age axis in reverse. |
| calhght | Heights of the calibrated distributions in the age-depth plot. |
| maxhght | Maximum height of age probability distributions. |
| mirror | Plot the age distributions in "mirror" style (above and below depth). |
| plotrange | Plot the confidence ranges of the age-model. |
| bty | Type of box to be drawn around plots. Draw a box around the graph ("n" for none, and "1", "7", "c", "u", "j" or "o" for correspondingly shaped boxes). |
| mar | Plot margins (amount of white space along edges of axes 1-4). |
| mgp | Axis text margins (where should titles, labels and tick marks be plotted). |
| plotpdf | Produce a pdf file of the age-depth plot. |
| plotpng | Produce a png file of the age-depth plot. |
| greyscale | Produce a grey-scale representation of all age-models (number gives resolution, e.g., 500 bins; will cancel plotting of the confidence intervals). |
| yr lab | Label of the calendar axis. Defaults to either cal BP or BC/AD. Alternative names can be provided. |
| d lab | Label of the depth axis. Defaults to dlab="Depth (cm)" (assuming depth="cm"), but alternative names can be provided. |
| calcol | Colour of the calibrated distributions in the age-depth plot. |
| C14col | Colour of the calibrated ranges of the dates. |
| outcol | Colour of outlying dates. |
| outsize | Size of symbols outlying dates. |
| bestcol | Colour of the "best" age-depth model (based on chosen value for est). |
| rangecol | Colour of plotted confidence ranges. |
| slumpcol | Colour of slump. |
| plotname | Print the core name on the graph. |
| ash | Plot all distributions at the same height. |
| rule | How should R's approx function deal with extrapolation. If rule=1, the default, then NAs are returned for such points and if it is 2, the value at the closest data extreme is used. |

Details

Cores containing several 14C and/or other dates can be processed semi-automatically in order to obtain age-depth models. In the process, any 14C dates are calibrated, and age-depth curves are repeatedly drawn through point estimates sampled from the dates. Age-depth models can be based on linear interpolation, linear/polynomial regression, or cubic, smooth or locally weighted splines. For each date, the probability of a calendar year being sampled is proportionate to its calibrated probability (see Blaauw, 2010). Uncertainty ranges as well as a 'best' age-model are calculated.

Additional cores should be put in a comma-separated file in a sub-folder of the directory where the cores are stored. By default this parent folder is called `coredir="clam_runs"` (if no folder called "Cores" already exists). If your core is called `MyCore1`, save `MyCore1.csv` as `clam_runs/MyCore1/MyCore1.csv`.

Ensure that the names of the core's folder and filename's root (the part before .csv) match, e.g., using exactly similar upper- and lower case letters.

Avoid the use of spaces or non-standard (non-ASCII) characters within the file or in folder or file names. The plain text file should consist of 6 or 7 columns (also called fields), containing in the following exact order (see the example below):

1. Identification labels (e.g. 14C lab codes)
2. 14C ages for 14C-dated depths; leave empty for non-14C dated depths
3. cal BP ages (for any non-14C dates such as the core surface; leave empty for levels with 14C dates)
4. errors (reported 1 standard deviation errors. This column should never be left empty. Errors should always be larger than 0)
5. age offsets if known (otherwise leave empty)
6. depths (depths in the sequence were the dated samples were taken, default unit depth="cm"; this column should never be left empty)
7. thicknesses of the sampled slices (optional column; leave empty for default of 1)

Add a final empty line to your core's .csv file by pressing 'Enter' after the file's last value.

These files can be made in spreadsheet software such as MS-Excel, but it is always a good idea to check the file's formatting in a plain-text editor such as WordPad. Remove any lines which contain only commas, and it is also recommended to remove quotes (\" or \')

Age-models for the core can then be produced by typing, e.g., `clam("MyCore1")`.

By default the northern hemisphere terrestrial calibration curve is used (`cc=1, cc1="3Col_intcal20.14C"`). To use alternative curves, change `cc` to `cc=2` (`cc2="3Col_marine20.14C"`), `cc=3` (`cc3="3Col_shcal20.14C"`), `cc=4` (`cc4="mixed.14C"`). You can also provide custom-built calibration curves, indicating its location using `ccdir`.

The provided example (default `core="Example"`) is core Quilichao-1 which was sampled from a Colombian lake (Berrio et al., 2002). This core was chosen because it was dated at a rather high resolution, and appears to contain a hiatus (e.g., try `hiatus=450` for a hiatus at 450 cm depth).

Each clam run will produce a range of files within the core's folder. One, ending with `"_calibrated.txt"` contains the calibrated age ranges of the 14C and other dates. The others will be named according to the core's name followed by the model type, and contain the age estimates for all depths (files ending with `"_ages.txt"`), settings (files ending with `"_settings.txt"`) and graphs (files ending with `".pdf"` and `".png"`). The file containing the age estimates has 5 columns; first the depths, then the minima and maxima of the confidence intervals, then a "best" estimate, and finally the reconstructed accumulation rates. The reported values are rounded to 0 decimals by default (`decimals=0`). Accumulation rates are in yr/cm ("deposition time") by default (`cmyr=FALSE`), but can be reported in cm/yr (`cmyr=TRUE`).

see Blaauw 2010 (Quaternary Geochronology 5: 512-518).

Value

Age model construction together with a text output and files saved to a folder in the `coredir/core` directory.

Author(s)

Maarten Blaauw <maarten.blaauw@qub.ac.uk>

Maarten Blaauw

References

Berrio, J.C., Hooghiemstra, H., Marchant, R., Rangel, O., 2002. Late-glacial and Holocene history of the dry forest area in the south Colombian Cauca Valley. *Journal of Quaternary Science* 17, 667-682

Blaauw, M., 2010. Methods and code for 'classical' age-modelling of radiocarbon sequences. *Quaternary Geochronology* 5, 512-518 doi:[10.1016/j.quageo.2010.01.002](https://doi.org/10.1016/j.quageo.2010.01.002)

Examples

```
base_temp_dir <- tempdir()
clam_dir <- file.path(base_temp_dir, "clam_runs")
dir.create(clam_dir, recursive = TRUE, showWarnings = FALSE)
clam(, coredir=clam_dir, ask=FALSE)
clam(, coredir=clam_dir, ask=FALSE, extradates=470)
```

deptime.age

Calculates the slope of a straight curve at the desired age.

Description

Calculates *for each iteration* the slope of a straight curve between depths above and below the desired age. Requires sufficiently dense density of depths, e.g. steps=1.

Usage

```
deptime.age(age, yr cm = TRUE, prob = 0.95)
```

Arguments

| | |
|-------|---|
| age | Age to calculate deposition time (years per cm). |
| yr cm | Calculate in years per cm, or alternatively in cm per yr. |
| prob | Probability level at which to calculate the ranges. |

Details

To calculate deposition times at an age. Before doing this, run your core in clam and store the data, so, make sure the option storedat=TRUE. Renamed from previous accrate.age function to avoid confusion with accrate.age function of rbacon.

Value

Returns (invisibly) the modelled deposition times at a specific age, a histogram and confidence ranges.

Author(s)

Maarten Blaauw

Examples

```
base_temp_dir <- tempdir()
clam_dir <- file.path(base_temp_dir, "clam_runs")
dir.create(clam_dir, recursive = TRUE, showWarnings = FALSE)
clam(core_dir=clam_dir, storedat=TRUE)
dp <- deptime.age(5000)
summary(dp)
deptime.age(5000, yrpcm=FALSE) # to calculate sedimentation times in cm/yr, so accumulation rates
```

| | |
|---------------|---|
| deptime.depth | <i>Calculates *for each iteration* the slope of a straight curve between depths just above and below the desired point.</i> |
|---------------|---|

Description

Calculates *for each iteration* the slope of a straight curve between depths above and below the desired point. Requires sufficiently dense density of depths, e.g. yrsteps=1.

Usage

```
deptime.depth(depth, yrpcm = TRUE, prob = 0.95)
```

Arguments

| | |
|-------|---|
| depth | The depth for which accumulation rate estimates should be calculated. |
| yrpcm | Calculate in years per cm, or alternatively in cm per yr. |
| prob | Probability level at which to calculate the ranges. |

Details

To calculate sedimentation times at a depth. Before running this, run your core in clam and store the data, so, make sure to set storedat=TRUE. Renamed from previous accrate.depth function to avoid confusion with accrate.depth function of rbacon.

Value

Returns (invisibly) the modelled deposition times for a specific depths, a histogram and confidence ranges.

Author(s)

Maarten Blaauw

Examples

```
base_temp_dir <- tempdir()
clam_dir <- file.path(base_temp_dir, "clam_runs")
dir.create(clam_dir, recursive = TRUE, showWarnings = FALSE)
clam(coredir=clam_dir, storedat=TRUE)
dp <- deptime.depth(20)
summary(dp)
deptime.depth(20, FALSE) # to calculate accumulation rates in cm/yr
```

plot_proxies

Produce a plot of proxy values against calendar age.

Description

Produce a plot of proxy values against calendar age.

Usage

```
plot_proxies(prox, errors = TRUE, proxcol = grey(0.5), revyr = TRUE)
```

Arguments

| | |
|---------|--|
| prox | Position of the proxy that should be plotted, e.g. 1 for the first proxy in the file. |
| errors | Plot an error envelope. |
| proxcol | Colour of the error envelope. |
| revyr | Direction of the calendar scale (revyr=TRUE will reverse the calendar scale from the default FALSE). |

Details

Only works after running clam on the core using proxies=TRUE. Requires a file containing the core depths as the first column, and any proxy values on subsequent columns. Values should be separated by comma's. The file should be stored as a .csv file in the core's directory.

Value

A plot of the age model function with proxies.

Author(s)

Maarten Blaauw

Examples

```
base_temp_dir <- tempdir()
clam_dir <- file.path(base_temp_dir, "clam_runs")
dir.create(clam_dir, recursive = TRUE, showWarnings = FALSE)
clam(core_dir=clam_dir, proxies=TRUE)
plot_proxies(3)
plot_proxies(3, revyr=FALSE)
```

Index

`add.dates`, [2](#)

`clam`, [4](#)

`clam-package`, [2](#)

`deptime.age`, [11](#)

`deptime.depth`, [12](#)

`plot_proxies`, [13](#)