

Package ‘climaemet’

February 17, 2023

Title Climate AEMET Tools

Version 1.1.0

Description Tools to download the climatic data of the Spanish Meteorological Agency (AEMET) directly from R using their API and create scientific graphs (climate charts, trend analysis of climate time series, temperature and precipitation anomalies maps, warming stripes graphics, climatograms, etc.).

License GPL-3

URL <https://ropenspain.github.io/climaemet/>,
<https://github.com/rOpenSpain/climaemet>

BugReports <https://github.com/rOpenSpain/climaemet/issues>

Depends R (>= 3.6.0)

Imports dplyr (>= 1.0.0), ggplot2 (>= 3.3.2), httr (>= 1.4.1),
jsonlite (>= 1.7.0), rappdirs (>= 0.3.3), readr (>= 1.4.0),
rlang (>= 0.4.6), tibble (>= 3.0.3), tidyr (>= 1.1.0)

Suggests climatol (>= 3.1.2), gganimate (>= 1.0.5), jpeg (>= 0.1.8),
knitr, lubridate, rmarkdown, scales, sf (>= 0.9.0)

VignetteBuilder knitr

Config/Needs/website mapSpain, classInt, terra, sf, gstat, geoR,
tidyverse, tidyterra, scales, gifski, reactable, leaflet,
geofacet

Copyright © AEMET. See file COPYRIGHTS

Encoding UTF-8

LazyData true

RoxygenNote 7.2.3

X-schema.org-applicationCategory Meteorology

X-schema.org-isPartOf <https://ropenspain.es/>

NeedsCompilation no

Author Manuel Pizarro [aut, cph] (<<https://orcid.org/0000-0002-6981-0154>>),
 Diego Hernangómez [aut, cre] (<<https://orcid.org/0000-0001-8457-4658>>,
 rOpenSpain),
 Gema Fernández-Avilés [aut] (<<https://orcid.org/0000-0001-5934-1916>>)

Maintainer Diego Hernangómez <diego.hernangomezherrero@gmail.com>

Repository CRAN

Date/Publication 2023-02-16 23:10:10 UTC

R topics documented:

aemet_api_key	3
aemet_daily_clim	4
aemet_detect_api_key	6
aemet_extremes_clim	6
aemet_forecast_daily	7
aemet_forecast_tidy	9
aemet_last_obs	11
aemet_monthly	12
aemet_munic	14
aemet_normal	15
aemet_stations	16
climaemet_9434_climatogram	17
climaemet_9434_temp	17
climaemet_9434_wind	18
climaemet_news	19
climatestripes_station	19
climatogram_normal	21
climatogram_period	22
dms2decdegrees	23
first_day_of_year	24
get_data_aemet	25
ggclimat_walter_lieth	26
ggstripes	28
ggwindrose	30
windrose_days	31
windrose_period	33

Index

35

Description

This function will store your AEMET API key on your local machine so it can be called securely without being stored in your code. After you have installed your key, it can be called any time by typing `Sys.getenv("AEMET_API_KEY")` and can be used in package functions by simply typing `AEMET_API_KEY`.

Alternatively, you can install the API Key manually:

- Run `Sys.setenv(AEMET_API_KEY = "Your_Key")`. You would need to run this command on each session (Similar to `install = FALSE`).
- Write this line on your `.Renviron` file: `AEMET_API_KEY = "Your_Key"` (same behavior than `install = TRUE`). This would store your API key permanently.

Usage

```
aemet_api_key(apikey, overwrite = FALSE, install = FALSE)
```

Arguments

apikey	The API key provided to you from the AEMET formatted in quotes. A key can be acquired at https://opendata.aemet.es/centrodedescargas/inicio .
overwrite	If this is set to TRUE, it will overwrite an existing <code>AEMET_API_KEY</code> that you already have in local machine.
install	if TRUE, will install the key in your local machine for use in future sessions. Defaults to FALSE.

Value

None

Note

To locate your API Key on your local machine, run `rappdirs::user_cache_dir("climaemet", "R")`.

See Also

Other aemet_auth: [aemet_detect_api_key\(\)](#)

Examples

```
# Don't run these examples!

if (FALSE) {
  aemet_api_key("111111abc", install = TRUE)

  # You can check it with:
  Sys.getenv("AEMET_API_KEY")
}

if (FALSE) {
  # If you need to overwrite an existing key:
  aemet_api_key("222222abc", overwrite = TRUE, install = TRUE)

  # You can check it with:
  Sys.getenv("AEMET_API_KEY")
}
```

aemet_daily_clim	<i>Daily/annual climatology values</i>
------------------	--

Description

Get climatology values for a station or for all the available stations. Note that `aemet_daily_period()` and `aemet_daily_period_all()` are shortcuts of `aemet_daily_clim()`.

Usage

```
aemet_daily_clim(
  station = "all",
  start = Sys.Date() - 7,
  end = Sys.Date(),
  verbose = FALSE,
  return_sf = FALSE
)
```

```
aemet_daily_period(
  station,
  start = 2020,
  end = 2020,
  verbose = FALSE,
  return_sf = FALSE
)
```

```
aemet_daily_period_all(
  start = 2020,
  end = 2020,
  verbose = FALSE,
```

```
  return_sf = FALSE
)
```

Arguments

station	Character string with station identifier code(s) (see aemet_stations()) or "all" for all the stations.
start, end	Character string with start and end date. See Details.
verbose	Logical TRUE/FALSE. Provides information about the flow of information between the client and server.
return_sf	Logical TRUE or FALSE. Should the function return an sf spatial object? If FALSE (the default value) it returns a tibble. Note that you need to have the sf package installed.

Details

start and end parameters should be:

- For `aemet_daily_clim()`: A Date object or a string with format: YYYY-MM-DD (2020-12-31) coercible with `as.Date()`.
- For `aemet_daily_period()` and `aemet_daily_period_all()`: A string representing the year(s) to be extracted: "2020", "2018".

Value

A tibble or a sf object

API Key

You need to set your API Key globally using `aemet_api_key()`.

See Also

`aemet_api_key()`, `as.Date()`

Other `aemet_api_data`: `aemet_extremes_clim()`, `aemet_forecast_daily()`, `aemet_last_obs()`, `aemet_monthly`, `aemet_normal`, `aemet_stations()`

Examples

```
library(tibble)
obs <- aemet_daily_clim(c("9434", "3195"))
glimpse(obs)
```

aemet_detect_api_key *Check if an AEMET API Key is present for the current session*

Description

The function would detect if an API Key is available on this session:

- If an API Key is already set as an environment variable it would be preserved
- If no environment variable has been set and you have stored permanently an API Key using [aemet_api_key\(\)](#), the latter would be loaded.

Usage

```
aemet_detect_api_key(...)
```

Arguments

... Ignored

Value

TRUE or FALSE

See Also

Other aemet_auth: [aemet_api_key\(\)](#)

Examples

```
aemet_detect_api_key()
```

aemet_extremes_clim *Extreme values for a station*

Description

Get recorded extreme values for a station.

Usage

```
aemet_extremes_clim(  
  station = NULL,  
  parameter = "T",  
  verbose = FALSE,  
  return_sf = FALSE  
)
```

Arguments

station	Character string with station identifier code(s) (see aemet_stations())
parameter	Character string as temperature ("T"), precipitation ("P") or wind ("V") parameter.
verbose	Logical TRUE/FALSE. Provides information about the flow of information between the client and server.
return_sf	Logical TRUE or FALSE. Should the function return an sf spatial object? If FALSE (the default value) it returns a tibble. Note that you need to have the sf package installed.

Value

A tibble or a sf object

API Key

You need to set your API Key globally using [aemet_api_key\(\)](#).

See Also

[aemet_api_key\(\)](#)

Other `aemet_api_data`: [aemet_daily_clim\(\)](#), [aemet_forecast_daily\(\)](#), [aemet_last_obs\(\)](#), [aemet_monthly](#), [aemet_normal](#), [aemet_stations\(\)](#)

Examples

```
library(tibble)
obs <- aemet_extremes_clim(c("9434", "3195"))
glimpse(obs)
```

`aemet_forecast_daily` *Forecast database by municipality*

Description

Get a database of daily or hourly weather forecasts for a given municipality.

Usage

```
aemet_forecast_daily(x, verbose = FALSE)
```

```
aemet_forecast_hourly(x, verbose = FALSE)
```

Arguments

x	A vector of municipality codes to extract. For convenience, climaemet provides this data on the dataset aemet_munic (see <code>municipio</code> field) as of January 2020.
verbose	Logical TRUE/FALSE. Provides information about the flow of information between the client and server.

Details

Forecasts format provided by the AEMET API have a complex structure. Although **climaemet** returns a tibble, each forecasted value is provided as a nested tibble. [aemet_forecast_tidy\(\)](#) helper function can unnest these values and provide a single unnested tibble for the requested variable.

Value

A nested tibble. Forecasted values can be extracted with [aemet_forecast_tidy\(\)](#). See also **Details**

API Key

You need to set your API Key globally using [aemet_api_key\(\)](#).

See Also

[aemet_munic](#) for municipality codes.

Other `aemet_api_data`: [aemet_daily_clim\(\)](#), [aemet_extremes_clim\(\)](#), [aemet_last_obs\(\)](#), [aemet_monthly](#), [aemet_normal](#), [aemet_stations\(\)](#)

Other forecasts: [aemet_forecast_tidy\(\)](#)

Examples

```
# Select a city
data("aemet_munic")
library(dplyr)
munis <- aemet_munic %>%
  filter(municipio_nombre %in% c(
    "Santiago de Compostela",
    "Lugo"
  )) %>%
  pull(municipio)

daily <- aemet_forecast_daily(munis)

# Vars available
aemet_forecast_vars_available(daily)

# This is nested
```



```

daily %>%
  select(municipio, fecha, nombre, temperatura)

# Select and unnest
daily_temp <- aemet_forecast_tidy(daily, "temperatura")

# This is not
daily_temp

# Wrangle and plot
daily_temp_end <- daily_temp %>%
  select(
    elaborado, fecha, municipio, nombre, temperatura_minima,
    temperatura_maxima
  ) %>%
  tidyr::pivot_longer(cols = contains("temperatura"))

# Plot
library(ggplot2)
ggplot(daily_temp_end) +
  geom_line(aes(fecha, value, color = name)) +
  facet_wrap(~nombre, ncol = 1) +
  scale_color_manual(
    values = c("red", "blue"),
    labels = c("max", "min")
  ) +
  scale_x_date(
    labels = scales::label_date_short(),
    breaks = "day"
  ) +
  scale_y_continuous(
    labels = scales::label_comma(suffix = "º")
  ) +
  theme_minimal() +
  labs(
    x = "", y = "",
    color = "",
    title = "Forecast: 7-day temperature",
    subtitle = paste(
      "Forecast produced on",
      format(daily_temp_end$elaborado[1], usetz = TRUE)
    )
  )
)

```

aemet_forecast_tidy *Helper functions for extracting forecasts*

Description

Helpers for [aemet_forecast_daily\(\)](#) and [aemet_forecast_hourly\(\)](#):

- [aemet_forecast_vars_available\(\)](#) extracts the values available on the dataset.
- [aemet_forecast_tidy\(\)](#) produces a tidy tibble with the forecast for var.

Usage

```
aemet_forecast_tidy(x, var)
```

```
aemet_forecast_vars_available(x)
```

Arguments

x	A database extracted with aemet_forecast_daily() or aemet_forecast_hourly() .
var	Name of the desired var to extract

Value

A vector of characters ([aemet_forecast_vars_available\(\)](#)) or a tibble ([aemet_forecast_tidy\(\)](#)).

See Also

Other forecasts: [aemet_forecast_daily\(\)](#)

Examples

```
# Hourly values
hourly <- aemet_forecast_hourly(c("15030", "28080"))

# Vars available
aemet_forecast_vars_available(hourly)

# Get temperature
temp <- aemet_forecast_tidy(hourly, "temperatura")

library(dplyr)
# Make hour - Need lubridate to adjust timezones
temp_end <- temp %>%
  mutate(
    forecast_time = lubridate::force_tz(
      as.POSIXct(fecha) + hora,
      tz = "Europe/Madrid"
    )
  )

# Add also sunset and sunrise
suns <- temp_end %>%
  select(nombre, fecha, orto, ocaso) %>%
  distinct_all() %>%
  group_by(nombre) %>%
  mutate(
    ocaso_end = lubridate::force_tz(
```

```

      as.POSIXct(fecha) + ocase,
      tz = "Europe/Madrid"
    ),
    orto_end = lubridate::force_tz(
      as.POSIXct(fecha) + orto,
      tz = "Europe/Madrid"
    ),
    orto_lead = lead(orto_end)
  ) %>%
  tidyr::drop_na()

# Plot

library(ggplot2)

ggplot(temp_end) +
  geom_rect(data = suns, aes(
    xmin = ocase_end, xmax = orto_lead,
    ymin = min(temp_end$temperatura),
    ymax = max(temp_end$temperatura)
  ), alpha = .4) +
  geom_line(aes(forecast_time, temperatura), color = "blue4") +
  facet_wrap(~nombre, nrow = 2) +
  scale_x_datetime(labels = scales::label_date_short()) +
  scale_y_continuous(labels = scales::label_number(suffix = "°")) +
  labs(
    x = "", y = "",
    title = "Forecast: Temperature",
    subtitle = paste("Forecast produced on", format(temp_end$elaborado[1],
      usetz = TRUE
    ))
  )
)

```

aemet_last_obs

Last observation values for a station

Description

Get last observation values for a station.

Usage

```
aemet_last_obs(station = "all", verbose = FALSE, return_sf = FALSE)
```

Arguments

station	Character string with station identifier code(s) (see aemet_stations()) or "all" for all the stations.
verbose	Logical TRUE/FALSE. Provides information about the flow of information between the client and server.
return_sf	Logical TRUE or FALSE. Should the function return an sf spatial object? If FALSE (the default value) it returns a tibble. Note that you need to have the sf package installed.

Value

A tibble or a sf object.

API Key

You need to set your API Key globally using [aemet_api_key\(\)](#).

See Also

Other aemet_api_data: [aemet_daily_clim\(\)](#), [aemet_extremes_clim\(\)](#), [aemet_forecast_daily\(\)](#), [aemet_monthly](#), [aemet_normal](#), [aemet_stations\(\)](#)

Examples

```
library(tibble)
obs <- aemet_last_obs(c("9434", "3195"))
glimpse(obs)
```

aemet_monthly

Monthly/annual climatology

Description

Get monthly/annual climatology values for a station or all the stations. [aemet_monthly_period\(\)](#) and [aemet_monthly_period_all\(\)](#) allows requests that span several years.

Usage

```
aemet_monthly_clim(
  station = NULL,
  year = 2020,
  verbose = FALSE,
  return_sf = FALSE
)
```

```

aemet_monthly_period(
  station = NULL,
  start = 2018,
  end = 2020,
  verbose = FALSE,
  return_sf = FALSE
)

aemet_monthly_period_all(
  start = 2019,
  end = 2020,
  verbose = FALSE,
  return_sf = FALSE
)

```

Arguments

station	Character string with station identifier code(s) (see aemet_stations())
year	Numeric value as date (format: YYYY).
verbose	Logical TRUE/FALSE. Provides information about the flow of information between the client and server.
return_sf	Logical TRUE or FALSE. Should the function return an sf spatial object? If FALSE (the default value) it returns a tibble. Note that you need to have the sf package installed.
start	Numeric value as start year (format: YYYY).
end	Numeric value as end year (format: YYYY).

Value

A tibble or a sf object

API Key

You need to set your API Key globally using [aemet_api_key\(\)](#).

See Also

Other `aemet_api_data`: [aemet_daily_clim\(\)](#), [aemet_extremes_clim\(\)](#), [aemet_forecast_daily\(\)](#), [aemet_last_obs\(\)](#), [aemet_normal](#), [aemet_stations\(\)](#)

Examples

```

library(tibble)
obs <- aemet_monthly_clim(station = c("9434", "3195"), year = 2000)
glimpse(obs)

```

aemet_munic	<i>Data set with all the municipalities of Spain</i>
-------------	--

Description

A tibble with all the municipalities of Spain as defined by the INE (Instituto Nacional de Estadística) as of January 2020.

Format

A tibble with 8,131 rows and fields:

municipio INE code of the municipality.

municipio_nombre INE name of the municipality.

cpro INE code of the province.

cpro_nombre INE name of the province.

codauto INE code of the autonomous community.

codauto_nombre INE code of the autonomous community.

Source

INE, [Municipality codes by province](#)

See Also

[aemet_forecast_daily\(\)](#), [aemet_forecast_hourly\(\)](#)

Other dataset: [climaemet_9434_climatogram](#), [climaemet_9434_temp](#), [climaemet_9434_wind](#)

Examples

```
data(aemet_munic)
```

```
aemet_munic
```

aemet_normal	<i>Normal climatology values</i>
--------------	----------------------------------

Description

Get normal climatology values for a station (or all the stations with `aemet_normal_clim_all()`). Standard climatology from 1981 to 2010.

Usage

```
aemet_normal_clim(station = NULL, verbose = FALSE, return_sf = FALSE)
```

```
aemet_normal_clim_all(verbose = FALSE, return_sf = FALSE)
```

Arguments

station	Character string with station identifier code(s) (see <code>aemet_stations()</code>) or "all" for all the stations.
verbose	Logical TRUE/FALSE. Provides information about the flow of information between the client and server.
return_sf	Logical TRUE or FALSE. Should the function return an sf spatial object? If FALSE (the default value) it returns a tibble. Note that you need to have the sf package installed.

Value

A tibble or a sf object.

API Key

You need to set your API Key globally using `aemet_api_key()`.

Note

Code modified from project <https://github.com/SevillaR/aemet>

See Also

Other `aemet_api_data`: `aemet_daily_clim()`, `aemet_extremes_clim()`, `aemet_forecast_daily()`, `aemet_last_obs()`, `aemet_monthly`, `aemet_stations()`

Examples

```
library(tibble)
obs <- aemet_normal_clim(c("9434", "3195"))
glimpse(obs)
```

aemet_stations	<i>AEMET stations</i>
----------------	-----------------------

Description

Get AEMET stations.

Usage

```
aemet_stations(verbose = FALSE, return_sf = FALSE)
```

Arguments

verbose	Logical TRUE/FALSE. Provides information about the flow of information between the client and server.
return_sf	Logical TRUE or FALSE. Should the function return an sf spatial object? If FALSE (the default value) it returns a tibble. Note that you need to have the sf package installed.

Value

A tibble or a sf object

API Key

You need to set your API Key globally using [aemet_api_key\(\)](#).

Note

Code modified from project <https://github.com/SevillaR/aemet>

See Also

Other aemet_api_data: [aemet_daily_clim\(\)](#), [aemet_extremes_clim\(\)](#), [aemet_forecast_daily\(\)](#), [aemet_last_obs\(\)](#), [aemet_monthly](#), [aemet_normal](#)

Examples

```
library(tibble)
stations <- aemet_stations()
stations
```

`climaemet_9434_climatogram`*Climatogram data for Zaragoza Airport ("9434") period 1981-2010*

Description

Normal data for Zaragoza Airport (1981-2010). This is an example dataset used to plot climatograms.

Format

A data.frame with columns 1 to 12 (months) and rows:

- **p_mes_md**: Precipitation (mm).
- **tm_max_md**: Maximum temperature (Celsius).
- **tm_min_md**: Minimum temperature (Celsius).
- **ta_min_md**: Absolute monthly minimum temperature (Celsius).

Source

AEMET.

See Also

[ggclimat_walter_lieth\(\)](#), [climatogram_period\(\)](#), [climatogram_normal\(\)](#)

Other dataset: [aemet_munic](#), [climaemet_9434_temp](#), [climaemet_9434_wind](#)

Other climatogram: [climatogram_normal\(\)](#), [climatogram_period\(\)](#), [ggclimat_walter_lieth\(\)](#)

Examples

```
data(climaemet_9434_climatogram)
```

`climaemet_9434_temp`*Average annual temperatures for Zaragoza Airport ("9434") period 1950-2020*

Description

Yearly observations of average temperature for Zaragoza Airport (1950-2020). This is an example dataset.

Format

A tibble with columns:

- **year**: Year of reference.
- **indicativo**: Identifier of the station.
- **temp**: Avg temperature (Celsius).

Source

AEMET.

See Also

Other dataset: [aemet_munic](#), [climaemet_9434_climatogram](#), [climaemet_9434_wind](#)

Other stripes: [climatestripes_station\(\)](#), [ggstripes\(\)](#)

Examples

```
data(climaemet_9434_temp)
```

climaemet_9434_wind *Wind conditions for Zaragoza Airport ("9434") period 2000-2020*

Description

Daily observations of wind speed and directions for Zaragoza Airport (2000-2020). This is an example dataset.

Format

A tibble with columns:

- **fecha**: Date of observation.
- **dir**: Wind directions (0-360).
- **velmedia**: Avg wind speed (km/h).

Source

AEMET.

See Also

Other dataset: [aemet_munic](#), [climaemet_9434_climatogram](#), [climaemet_9434_temp](#)

Other wind: [ggwindrose\(\)](#), [windrose_days\(\)](#), [windrose_period\(\)](#)

Examples

```
data(climaemet_9434_wind)
```

climaemet_news	<i>climaemet_news</i>
----------------	-----------------------

Description

Show the NEWS file of the **climaemet** package.

Usage

```
climaemet_news()
```

Details

(See description)

Value

Open NEWS from climaemet.

See Also

Other helpers: [dms2decdegrees\(\)](#), [first_day_of_year\(\)](#)

Examples

```
## Not run:  
climaemet_news()  
  
## End(Not run)
```

climatestripes_station	<i>Station climate stripes graph</i>
------------------------	--------------------------------------

Description

Plot climate stripes graph for a station

Usage

```
climatestripes_station(  
  station,  
  start = 1950,  
  end = 2020,  
  with_labels = "yes",  
  verbose = FALSE,  
  ...  
)
```

Arguments

station	Character string with station identifier code(s) (see aemet_stations())
start	Numeric value as start year (format: YYYY).
end	Numeric value as end year (format: YYYY).
with_labels	Character string as yes/no. Indicates whether to use labels for the graph or not.
verbose	Logical TRUE/FALSE. Provides information about the flow of information between the client and server.
...	Arguments passed on to ggstripes
n_temp	Numeric value as the number of colors of the palette. (default 11).
col_pal	Character string indicating the name of the hcl.pals() color palette to be used for plotting.

Value

A ggplot2 object

API Key

You need to set your API Key globally using [aemet_api_key\(\)](#).

See Also

[ggstripes\(\)](#)

Other aemet_plots: [climatogram_normal\(\)](#), [climatogram_period\(\)](#), [ggclimat_walter_lieth\(\)](#), [ggstripes\(\)](#), [ggwindrose\(\)](#), [windrose_days\(\)](#), [windrose_period\(\)](#)

Other stripes: [climaemet_9434_temp](#), [ggstripes\(\)](#)

Examples

```
climatestripes_station(  
  "9434",  
  start = 2010,  
  end = 2020,  
  with_labels = "yes",  
  col_pal = "Inferno"  
)
```

climatogram_normal *Walter & Lieth climatic diagram from normal climatology values*

Description

Plot of a Walter & Lieth climatic diagram from normal climatology data for a station. This climatogram are great for showing a summary of climate conditions for a place over a time period (1981-2010).

Usage

```
climatogram_normal(  
  station,  
  labels = "en",  
  verbose = FALSE,  
  ggplot2 = TRUE,  
  ...  
)
```

Arguments

station	Character string with station identifier code(s) (see aemet_stations())
labels	Character string as month labels for the X axis: "en" (english), "es" (spanish), "fr" (french), etc.
verbose	Logical TRUE/FALSE. Provides information about the flow of information between the client and server.
ggplot2	TRUE/FALSE. On TRUE the function uses ggclimat_walter_lieth() , if FALSE uses climatol::diagwl() .
...	Further arguments to climatol::diagwl() or ggclimat_walter_lieth() , depending on the value of ggplot2

Value

A plot.

API Key

You need to set your API Key globally using [aemet_api_key\(\)](#).

Note

The code is based on code from the CRAN package "climatol" by Jose A. Guijarro jguijarro@aemet.es.

References

Walter, H. & Lieth, H (1960): Klimadiagramm Weltatlas. G. Fischer, Jena.

See Also

Other aemet_plots: [climatestripes_station\(\)](#), [climatogram_period\(\)](#), [ggclimat_walter_lieth\(\)](#), [ggstripes\(\)](#), [ggwindrose\(\)](#), [windrose_days\(\)](#), [windrose_period\(\)](#)

Other climatogram: [climaemet_9434_climatogram](#), [climatogram_period\(\)](#), [ggclimat_walter_lieth\(\)](#)

Examples

```
climatogram_normal("9434")
```

```
climatogram_period      Walter & Lieth climatic diagram for a time period
```

Description

Plot of a Walter & Lieth climatic diagram from monthly climatology data for a station. This climatogram are great for showing a summary of climate conditions for a place over a specific time period.

Usage

```
climatogram_period(
  station = NULL,
  start = 1990,
  end = 2020,
  labels = "en",
  verbose = FALSE,
  ggplot2 = TRUE,
  ...
)
```

Arguments

station	Character string with station identifier code(s) (see aemet_stations())
start	Numeric value as start year (format: YYYY).
end	Numeric value as end year (format: YYYY).
labels	Character string as month labels for the X axis: "en" (english), "es" (spanish), "fr" (french), etc.
verbose	Logical TRUE/FALSE. Provides information about the flow of information between the client and server.
ggplot2	TRUE/FALSE. On TRUE the function uses ggclimat_walter_lieth() , if FALSE uses climatol::diagwl() .
...	Further arguments to climatol::diagwl() or ggclimat_walter_lieth() , depending on the value of ggplot2

Value

A plot.

API Key

You need to set your API Key globally using `aemet_api_key()`.

Note

The code is based on code from the CRAN package "climatol" by Jose A. Guijarro jguijarrop@aemet.es.

References

Walter, H. & Lieth, H (1960): Klimadiagramm Weltatlas. G. Fischer, Jena.

See Also

Other aemet_plots: `climatestripes_station()`, `climatogram_normal()`, `ggclimat_walter_lieth()`, `ggstripes()`, `ggwindrose()`, `windrose_days()`, `windrose_period()`

Other climatogram: `climaemet_9434_climatogram`, `climatogram_normal()`, `ggclimat_walter_lieth()`

Examples

```
climatogram_period("9434", start = 2015, end = 2020, labels = "en")
```

dms2decdegrees	<i>Converts dms to decimal degrees</i>
----------------	--

Description

Converts degrees, minutes and seconds to decimal degrees.

Usage

```
dms2decdegrees(input = NULL)
```

Arguments

`input` Character string as DMS coordinates.

Value

A numeric value.

Note

Code modified from project <https://github.com/SevillaR/aemet>

See Also

Other helpers: [climaemet_news\(\)](#), [first_day_of_year\(\)](#)

Examples

```
dms2decdegrees("055245W")
```

first_day_of_year	<i>First and last day of year</i>
-------------------	-----------------------------------

Description

Get first and last day of year.

Usage

```
first_day_of_year(year = NULL)
```

```
last_day_of_year(year = NULL)
```

Arguments

year Numeric value as year (format: YYYY).

Value

Character string as date (format: YYYY-MM-DD).

See Also

Other helpers: [climaemet_news\(\)](#), [dms2decdegrees\(\)](#)

Examples

```
first_day_of_year(2000)
```

```
last_day_of_year(2020)
```

get_data_aemet *Client tool for AEMET API*

Description

Client tool to get data and metadata from AEMET and convert json to tibble.

Usage

```
get_data_aemet(apidest, verbose = FALSE)
get_metadata_aemet(apidest, verbose = FALSE)
```

Arguments

apidest	Character string as destination URL. See https://opendata.aemet.es/dist/index.html .
verbose	Logical TRUE/FALSE. Provides information about the flow of information between the client and server.

Value

A tibble (if possible) or the results of the query as provided by `httr::content()`.

Source

<https://opendata.aemet.es/dist/index.html>

See Also

Some examples on how to use these functions on vignette("extending-climaemet").

Examples

```
# Run this example only if AEMET_API_KEY is detected
url <- "/api/valores/climatologicos/inventarioestaciones/todasestaciones"
get_data_aemet(url)

# Metadata
get_metadata_aemet(url)

# We can get data from any API endpoint

# Plain text
```

```
plain <- get_data_aemet("/api/prediccion/nacional/hoy")
cat(plain)

# An image

image <- get_data_aemet("/api/mapasygraficos/analisis")

# Write and read
tmp <- tempfile(fileext = ".gif")

writeBin(image, tmp)

gganimate::gif_file(tmp)
```

ggclimat_walter_lieth *Walter and Lieth climatic diagram on ggplot2*

Description

Plot of a Walter and Lieth climatic diagram of a station. This function is an updated version of `climatol::diagwl()`, by Jose A. Guijarro.

Usage

```
ggclimat_walter_lieth(
  dat,
  est = "",
  alt = NA,
  per = NA,
  mlab = "es",
  pcol = "#002F70",
  tcol = "#ff0000",
  pfc col = "#9BAEE2",
  sfcol = "#3C6FC4",
  shem = FALSE,
  p3line = FALSE,
  ...
)
```

Arguments

<code>dat</code>	Monthly climatic data for which the diagram will be plotted.
<code>est</code>	Name of the climatological station
<code>alt</code>	Altitude of the climatological station
<code>per</code>	Period on which the averages have been computed

<code>m1ab</code>	Month labels for the X axis. Use 2-digit language code ("en", "es", etc.). See readr::locale() for info.
<code>pcol</code>	Color pen for precipitation.
<code>tcol</code>	Color pen for temperature.
<code>pfcol</code>	Fill color for probable frosts.
<code>sfcol</code>	Fill color for sure frosts.
<code>shem</code>	Set to TRUE for southern hemisphere stations.
<code>p3line</code>	Set to TRUE to draw a supplementary precipitation line referenced to three times the temperature (as suggested by Bogdan Rosca).
<code>...</code>	Other graphic parameters

Details

See Details on [climatol::diagwl\(\)](#).

Climatic data must be passed as a 4x12 matrix or `data.frame` of monthly (January to December) data, in the following order:

- Row 1: Mean precipitation.
- Row 2: Mean maximum daily temperature.
- Row 3: Mean minimum daily temperature.
- Row 4: Absolute monthly minimum temperature.

See [climaemet_9434_climatogram](#) for a sample dataset.

Value

A `ggplot2` object. See `help("ggplot2")`.

API Key

You need to set your API Key globally using [aemet_api_key\(\)](#).

References

Walter, H., and Lieth, H. 1960. *Klimadiagramm-Weltatlas*. G. Fischer.

See Also

[climatol::diagwl\(\)](#), [readr::locale\(\)](#)

Other `aemet_plots`: [climatestripes_station\(\)](#), [climatogram_normal\(\)](#), [climatogram_period\(\)](#), [ggstripes\(\)](#), [ggwindrose\(\)](#), [windrose_days\(\)](#), [windrose_period\(\)](#)

Other `climatogram`: [climaemet_9434_climatogram](#), [climatogram_normal\(\)](#), [climatogram_period\(\)](#)

Examples

```
library(ggplot2)

wl <- ggclimat_walter_lieth(
  climaemet::climaemet_9434_climatogram,
  alt = "249",
  per = "1981-2010",
  est = "Zaragoza Airport"
)

wl

# As it is a ggplot object we can modify it

wl + theme(
  plot.background = element_rect(fill = "grey80"),
  panel.background = element_rect(fill = "grey70"),
  axis.text.y.left = element_text(
    colour = "black",
    face = "italic"
  ),
  axis.text.y.right = element_text(
    colour = "black",
    face = "bold"
  )
)
```

ggstripes

Warming stripes graph

Description

Plot different "climate stripes" or "warming stripes" using **ggplot2**. This graphics are visual representations of the change in temperature as measured in each location over the past 70-100+ years. Each stripe represents the temperature in that station averaged over a year.

Usage

```
ggstripes(
  data,
  plot_type = "stripes",
  plot_title = "",
  n_temp = 11,
  col_pal = "RdBu",
  ...
)
```

Arguments

<code>data</code>	a data.frame with <code>date(year)</code> and <code>temperature(temp)</code> variables.
<code>plot_type</code>	plot type (with labels, background, stripes with line trend and animation). Accepted values are "background", "stripes", "trend" or "animation".
<code>plot_title</code>	character string to be used for the graph title.
<code>n_temp</code>	Numeric value as the number of colors of the palette. (default 11).
<code>col_pal</code>	Character string indicating the name of the <code>hcl.pals()</code> color palette to be used for plotting.
<code>...</code>	further arguments passed to <code>ggplot2::theme()</code> .

Value

A ggplot2 object.

API Key

You need to set your API Key globally using `aemet_api_key()`.

Note

"Warming stripes" charts are a conceptual idea of Professor Ed Hawkins (University of Reading) and are specifically designed to be as simple as possible and alert about risks of climate change. For more details see [ShowYourStripes](#).

See Also

`climatestripes_station()`, `ggplot2::theme()` for more possible arguments to pass to `ggstripes`.

Other `aemet` plots: `climatestripes_station()`, `climatogram_normal()`, `climatogram_period()`, `ggclimat_walter_lieth()`, `ggwindrose()`, `windrose_days()`, `windrose_period()`

Other stripes: `climaemet_9434_temp`, `climatestripes_station()`

Examples

```
library(ggplot2)

data <- climaemet::climaemet_9434_temp

ggstripes(data, plot_title = "Zaragoza Airport") +
  labs(subtitle = "(1950-2020)")

ggstripes(data, plot_title = "Zaragoza Airport", plot_type = "trend") +
  labs(subtitle = "(1950-2020)")
```

ggwindrose

*Windrose (speed/direction) diagram***Description**

Plot a windrose showing the wind speed and direction using **ggplot2**.

Usage

```
ggwindrose(
  speed,
  direction,
  n_directions = 8,
  n_speeds = 5,
  speed_cuts = NA,
  col_pal = "GnBu",
  legend_title = "Wind speed (m/s)",
  calm_wind = 0,
  n_col = 1,
  facet = NULL,
  plot_title = "",
  ...
)
```

Arguments

speed	Numeric vector of wind speeds.
direction	Numeric vector of wind directions.
n_directions	Numeric value as the number of direction bins to plot (petals on the rose). The number of directions defaults to 8.
n_speeds	Numeric value as the number of equally spaced wind speed bins to plot. This is used if speed_cuts is NA (default 5).
speed_cuts	Numeric vector containing the cut points for the wind speed intervals, or NA (default).
col_pal	Character string indicating the name of the <code>hcl.pals()</code> color palette to be used for plotting.
legend_title	Character string to be used for the legend title.
calm_wind	Numeric value as the upper limit for wind speed that is considered calm (default 0).
n_col	The number of columns of plots (default 1).
facet	Character or factor vector of the facets used to plot the various windroses.
plot_title	Character string to be used for the plot title.
...	further arguments (ignored).

Value

A ggplot object.

API Key

You need to set your API Key globally using `aemet_api_key()`.

See Also

`ggplot2::theme()` for more possible arguments to pass to `ggwindrose`.

Other `aemet_plots`: `climatestripes_station()`, `climatogram_normal()`, `climatogram_period()`, `ggclimat_walter_lieth()`, `ggstripes()`, `windrose_days()`, `windrose_period()`

Other `wind`: `climaemet_9434_wind`, `windrose_days()`, `windrose_period()`

Examples

```
library(ggplot2)

speed <- climaemet::climaemet_9434_wind$velmedia
direction <- climaemet::climaemet_9434_wind$dir

rose <- ggwindrose(
  speed = speed,
  direction = direction,
  speed_cuts = seq(0, 16, 4),
  legend_title = "Wind speed (m/s)",
  calm_wind = 0,
  n_col = 1,
  plot_title = "Zaragoza Airport"
)
rose + labs(
  subtitle = "2000-2020",
  caption = "Source: AEMET"
)
```

windrose_days

Windrose (speed/direction) diagram of a station over a days period

Description

Plot a windrose showing the wind speed and direction for a station over a days period.

Usage

```

windrose_days(
  station,
  start = "2000-12-01",
  end = "2000-12-31",
  n_directions = 8,
  n_speeds = 5,
  speed_cuts = NA,
  col_pal = "GnBu",
  calm_wind = 0,
  legend_title = "Wind Speed (m/s)",
  verbose = FALSE
)

```

Arguments

station	Character string with station identifier code(s) (see aemet_stations()) or "all" for all the stations.
start	Character string as start date (format: YYYY-MM-DD).
end	Character string as end date (format: YYYY-MM-DD).
n_directions	Numeric value as the number of direction bins to plot (petals on the rose). The number of directions defaults to 8.
n_speeds	Numeric value as the number of equally spaced wind speed bins to plot. This is used if speed_cuts is NA (default 5).
speed_cuts	Numeric vector containing the cut points for the wind speed intervals, or NA (default).
col_pal	Character string indicating the name of the hcl.pals() color palette to be used for plotting.
calm_wind	Numeric value as the upper limit for wind speed that is considered calm (default 0).
legend_title	Character string to be used for the legend title.
verbose	Logical TRUE/FALSE. Provides information about the flow of information between the client and server.

Value

A ggplot2 object

API Key

You need to set your API Key globally using [aemet_api_key\(\)](#).

See Also

[aemet_daily_clim\(\)](#)

Other aemet_plots: [climatestripes_station\(\)](#), [climatogram_normal\(\)](#), [climatogram_period\(\)](#), [ggclimat_walter_lieth\(\)](#), [ggstripes\(\)](#), [ggwindrose\(\)](#), [windrose_period\(\)](#)

Other wind: [climaemet_9434_wind](#), [ggwindrose\(\)](#), [windrose_period\(\)](#)

Examples

```
windrose_days("9434",
  start = "2000-12-01",
  end = "2000-12-31",
  speed_cuts = 4
)
```

windrose_period

Windrose (speed/direction) diagram of a station over a time period

Description

Plot a windrose showing the wind speed and direction for a station over a time period.

Usage

```
windrose_period(
  station,
  start = 2000,
  end = 2010,
  n_directions = 8,
  n_speeds = 5,
  speed_cuts = NA,
  col_pal = "GnBu",
  calm_wind = 0,
  legend_title = "Wind Speed (m/s)",
  verbose = FALSE
)
```

Arguments

station	Character string with station identifier code(s) (see aemet_stations()) or "all" for all the stations.
start	Numeric value as start year (format: YYYY).
end	Numeric value as end year (format: YYYY).
n_directions	Numeric value as the number of direction bins to plot (petals on the rose). The number of directions defaults to 8.

<code>n_speeds</code>	Numeric value as the number of equally spaced wind speed bins to plot. This is used if <code>speed_cuts</code> is NA (default 5).
<code>speed_cuts</code>	Numeric vector containing the cut points for the wind speed intervals, or NA (default).
<code>col_pal</code>	Character string indicating the name of the <code>hcl.pals()</code> color palette to be used for plotting.
<code>calm_wind</code>	Numeric value as the upper limit for wind speed that is considered calm (default 0).
<code>legend_title</code>	Character string to be used for the legend title.
<code>verbose</code>	Logical TRUE/FALSE. Provides information about the flow of information between the client and server.

Value

A `ggplot2` object

API Key

You need to set your API Key globally using `aemet_api_key()`.

See Also

[aemet_daily_period\(\)](#)

Other `aemet_plots`: [climatestripes_station\(\)](#), [climatogram_normal\(\)](#), [climatogram_period\(\)](#), [ggclimat_walter_lieth\(\)](#), [ggstripes\(\)](#), [ggwindrose\(\)](#), [windrose_days\(\)](#)

Other wind: [climaemet_9434_wind](#), [ggwindrose\(\)](#), [windrose_days\(\)](#)

Examples

```
windrose_period("9434",
  start = 2000, end = 2010,
  speed_cuts = 4
)
```

Index

- * **aemet_api_data**
 - aemet_daily_clim, 4
 - aemet_extremes_clim, 6
 - aemet_forecast_daily, 7
 - aemet_last_obs, 11
 - aemet_monthly, 12
 - aemet_normal, 15
 - aemet_stations, 16
 - * **aemet_api**
 - get_data_aemet, 25
 - * **aemet_auth**
 - aemet_api_key, 3
 - aemet_detect_api_key, 6
 - * **aemet_plots**
 - climatestripes_station, 19
 - climatogram_normal, 21
 - climatogram_period, 22
 - ggclimat_walter_lieth, 26
 - ggstripes, 28
 - ggwindrose, 30
 - windrose_days, 31
 - windrose_period, 33
 - * **climatogram**
 - climaemet_9434_climatogram, 17
 - climatogram_normal, 21
 - climatogram_period, 22
 - ggclimat_walter_lieth, 26
 - * **dataset**
 - aemet_munic, 14
 - climaemet_9434_climatogram, 17
 - climaemet_9434_temp, 17
 - climaemet_9434_wind, 18
 - * **forecasts**
 - aemet_forecast_daily, 7
 - aemet_forecast_tidy, 9
 - * **forecast**
 - aemet_munic, 14
 - * **helpers**
 - climaemet_news, 19
 - dms2decdegrees, 23
 - first_day_of_year, 24
 - * **stripes**
 - climaemet_9434_temp, 17
 - climatestripes_station, 19
 - ggstripes, 28
 - * **wind**
 - climaemet_9434_wind, 18
 - ggwindrose, 30
 - windrose_days, 31
 - windrose_period, 33
- aemet_api_key, 3, 6
- aemet_api_key(), 5–8, 12, 13, 15, 16, 20, 21, 23, 27, 29, 31, 32, 34
- aemet_daily (aemet_daily_clim), 4
- aemet_daily_clim, 4, 7, 8, 12, 13, 15, 16
- aemet_daily_clim(), 33
- aemet_daily_period (aemet_daily_clim), 4
- aemet_daily_period(), 34
- aemet_daily_period_all (aemet_daily_clim), 4
- aemet_detect_api_key, 3, 6
- aemet_extremes_clim, 5, 6, 8, 12, 13, 15, 16
- aemet_forecast_daily, 5, 7, 7, 10, 12, 13, 15, 16
- aemet_forecast_daily(), 9, 10, 14
- aemet_forecast_hourly (aemet_forecast_daily), 7
- aemet_forecast_hourly(), 9, 10, 14
- aemet_forecast_tidy, 8, 9
- aemet_forecast_tidy(), 8, 10
- aemet_forecast_vars_available (aemet_forecast_tidy), 9
- aemet_forecast_vars_available(), 10
- aemet_last_obs, 5, 7, 8, 11, 13, 15, 16
- aemet_monthly, 5, 7, 8, 12, 12, 15, 16
- aemet_monthly_clim (aemet_monthly), 12
- aemet_monthly_period (aemet_monthly), 12

aemet_monthly_period_all
 (aemet_monthly), 12
aemet_munic, 8, 14, 17, 18
aemet_normal, 5, 7, 8, 12, 13, 15, 16
aemet_normal_clim(aemet_normal), 15
aemet_normal_clim_all(aemet_normal), 15
aemet_stations, 5, 7, 8, 12, 13, 15, 16
aemet_stations(), 5, 7, 12, 13, 15, 20–22,
 32, 33
as.Date(), 5

climaemet_9434_climatogram, 14, 17, 18,
 22, 23, 27
climaemet_9434_temp, 14, 17, 17, 18, 20, 29
climaemet_9434_wind, 14, 17, 18, 18, 31, 33,
 34
climaemet_news, 19, 24
climatestripes_station, 18, 19, 22, 23, 27,
 29, 31, 33, 34
climatestripes_station(), 29
climatogram_normal, 17, 20, 21, 23, 27, 29,
 31, 33, 34
climatogram_normal(), 17
climatogram_period, 17, 20, 22, 22, 27, 29,
 31, 33, 34
climatogram_period(), 17
climatol::diagwl(), 21, 22, 26, 27

dms2decdegrees, 19, 23, 24

first_day_of_year, 19, 24, 24

get_data_aemet, 25
get_metadata_aemet(get_data_aemet), 25
ggclimat_walter_lieth, 17, 20, 22, 23, 26,
 29, 31, 33, 34
ggclimat_walter_lieth(), 17, 21, 22
ggplot2::theme(), 29, 31
ggstripes, 18, 20, 22, 23, 27, 28, 31, 33, 34
ggstripes(), 20
ggwindrose, 18, 20, 22, 23, 27, 29, 30, 33, 34

hcl.pals(), 20, 29, 30, 32, 34
htr::content(), 25

last_day_of_year(first_day_of_year), 24

readr::locale(), 27

windrose_days, 18, 20, 22, 23, 27, 29, 31, 31,
 34
windrose_period, 18, 20, 22, 23, 27, 29, 31,
 33, 33