

# Package ‘cobalt’

March 30, 2021

**Title** Covariate Balance Tables and Plots

**Version** 4.3.1

**Description** Generate balance tables and plots for covariates of groups preprocessed through matching, weighting or subclassification, for example, using propensity scores. Includes integration with 'MatchIt', 'twang', 'Matching', 'optmatch', 'CBPS', 'ebal', 'WeightIt', 'cem', 'sbw', and 'designmatch' for assessing balance on the output of their preprocessing functions. Users can also specify data for balance assessment not generated through the above packages. Also included are methods for assessing balance in clustered or multiply imputed data sets or data sets with longitudinal treatments.

**Depends** R (>= 3.3.0)

**Imports** ggplot2 (>= 3.3.0), grid, gtable (>= 0.3.0), gridExtra (>= 2.3), rlang (>= 0.4.0), crayon, backports (>= 1.1.8)

**Suggests** MatchIt, WeightIt (>= 0.5.0), twang (>= 1.6), Matching, optmatch, ebal, CBPS (>= 0.17), designmatch, optweight, mice (>= 3.8.0), MatchThem (>= 0.9.3), cem (>= 1.1.27), mlogit, knitr, rmarkdown

**License** GPL (>= 2)

**Encoding** UTF-8

**LazyData** true

**VignetteBuilder** knitr

**URL** <https://ngreifer.github.io/cobalt/>,  
<https://github.com/ngreifer/cobalt>

**BugReports** <https://github.com/ngreifer/cobalt/issues>

**NeedsCompilation** no

**Author** Noah Greifer [aut, cre] (<<https://orcid.org/0000-0003-3067-7154>>)

**Maintainer** Noah Greifer <[noah.greifer@gmail.com](mailto:noah.greifer@gmail.com)>

**Repository** CRAN

**Date/Publication** 2021-03-30 09:50:18 UTC

**R topics documented:**

bal.plot . . . . .	2
bal.tab . . . . .	6
bal.tab.CBPS . . . . .	11
bal.tab.cem.match . . . . .	15
bal.tab.default . . . . .	18
bal.tab.df.formula . . . . .	21
bal.tab.df.formula.list . . . . .	26
bal.tab.Match . . . . .	30
bal.tab.matchit . . . . .	35
bal.tab.mimids . . . . .	38
bal.tab.ps . . . . .	42
bal.tab.sbw . . . . .	47
bal.tab.weightit . . . . .	50
Balance Statistics . . . . .	54
Balance Summary . . . . .	55
class-bal.tab.cluster . . . . .	61
class-bal.tab.imp . . . . .	63
class-bal.tab.msm . . . . .	64
class-bal.tab.multi . . . . .	65
class-bal.tab.subclass . . . . .	67
Display Options . . . . .	69
f.build . . . . .	72
get.w . . . . .	73
lalonge . . . . .	75
love.plot . . . . .	76
print.bal.tab . . . . .	82
set.cobalt.options . . . . .	85
splitfactor . . . . .	87
var.names . . . . .	89
<b>Index</b>	<b>91</b>

---

bal.plot

*Visualize Distributional Balance*


---

**Description**

Generates density plots, bar graphs, or scatterplots displaying distributional balance between treatment and covariates using **ggplot2**.

**Usage**

```
bal.plot(x,
  var.name,
  ...,
  which,
  which.sub = NULL,
  cluster = NULL,
  which.cluster = NULL,
  imp = NULL,
  which.imp = NULL,
  which.treat = NULL,
  which.time = NULL,
  mirror = FALSE,
  type = "density",
  colors = NULL,
  grid = FALSE,
  sample.names,
  position = "right",
  facet.formula = NULL,
  disp.means = getOption("cobalt_disp.means", FALSE),
  alpha.weight = TRUE)
```

**Arguments**

x	the object for which balance is to be assessed; can be any object for which there is support in <code>bal.tab</code> .
var.name	character; the name of the variable whose values are to be plotted. To view distributions of the distance measure (e.g., propensity score), if any, use "distance" as the argument unless the distance variable has been named. If there are duplicate variable names across inputs, <code>bal.plot()</code> will first look in the covariate data.frame from <code>obj</code> , followed by <code>add1</code> , and then <code>distance</code> , if any. If not specified, will use the first covariate available with a warning.
...	other arguments to define the variable, treatment, and weights. Some inputs are required depending on the method. See Additional Arguments. Can also be used to supply the <code>bw</code> , <code>adjust</code> , <code>kernel</code> , and <code>n</code> arguments for <code>geom_density()</code> and the <code>bins</code> argument for <code>geom_histogram()</code> .
which	whether to display distributional balance for the adjusted ("adjusted") or unadjusted sample ("unadjusted") or both at the same time ("both"). When multiple weights are present, the names of the weights can be supplied, too. The default is to display balance for the adjusted sample only unless no weights, subclasses, or matching strata are specified. Multiple values and abbreviations allowed.
which.sub	numeric; if subclassification is used, a vector corresponding to the subclass(es) for which the distributions are to be displayed. If <code>.all</code> (the default), distributions from all subclasses are displayed in a grid.
cluster	optional; a vector of cluster membership, or the name of a variable in an available data set passed to <code>bal.plot()</code> that contains cluster membership.

<code>which.cluster</code>	if clusters are used, which cluster(s) to display. Can be cluster names or numerical indices for which to display balance. Indices correspond to the alphabetical order of cluster names. If <code>.all</code> (the default), all clusters are displayed. If <code>.none</code> , cluster information is ignored and the marginal distribution of the covariates is displayed.
<code>imp</code>	optional; a vector of imputation indices, or the name of a variable in an available data set passed to <code>bal.plot()</code> that contains imputation indices.
<code>which.imp</code>	if imputations are used, which imputations(s) to display. Must be numerical indices for which to display balance. If <code>.all</code> (the default), all imputations are displayed. If <code>.none</code> , data from all imputations are combined into one distribution.
<code>which.treat</code>	which treatment groups to display. If <code>NULL</code> (the default) or <code>NA</code> , all treatment groups are displayed.
<code>which.time</code>	for longitudinal treatments, which time points to display. Can be treatment names or time period indices. If <code>NULL</code> (the default) or <code>NA</code> , all time points are displayed.
<code>mirror</code>	logical; if the treatment is binary, the covariate is continuous, and densities or histograms are requested, whether to display mirrored densities/histograms or overlapping densities/histograms. Ignored otherwise.
<code>type</code>	character; for binary and multi-category treatments with a continuous covariate, whether to display densities ("density"), histograms ("histogram"), or empirical cumulative density function plots ("ecdf"). The default is to display densities. Abbreviations are allowed.
<code>colors</code>	a vector of colors for the plotted densities/histograms. See 'Color Specification' at <a href="#">par()</a> . Defaults to the default <b>ggplot2</b> colors.
<code>grid</code>	logical; whether gridlines should be shown on the plot. Default is <code>TRUE</code> .
<code>sample.names</code>	character; new names to be given to the samples (i.e., in place of "Unadjusted Sample" and "Adjusted Sample"). For example, when matching it used, it may be useful to enter <code>c("Unmatched", "Matched")</code> .
<code>position</code>	the position of the legend. This can be any value that would be appropriate as an argument to <code>legend.position</code> in <a href="#">theme()</a> .
<code>facet.formula</code>	a formula designating which facets should be on the rows and columns. This should be of the "historical" formula interface to <a href="#">facet_grid()</a> . If of the form <code>a ~ b</code> , <code>a</code> will be faceted on the rows and <code>b</code> on the columns. To only facet on the rows, provide a one-sided formula with an empty left-hand side. To only facet on the columns, the formula should be of the form <code>a ~ .</code> (i.e., with only <code>.</code> on the right-hand side). The allowable facets depend on which arguments have been supplied to <code>bal.plot</code> ; possible values include <code>which</code> , <code>cluster</code> , <code>imp</code> , and (for longitudinal treatments) <code>time</code> . If <code>NULL</code> , <code>bal.plot()</code> will decide what looks best; this argument exists in case you disagree with its choice.
<code>disp.means</code>	logical; for a categorical treatment with a continuous covariate, whether a line should be drawn for each treatment level denoting the (weighted) mean of the covariate. Ignored if <code>type</code> is not "density" or "histogram". Default is <code>FALSE</code> .
<code>alpha.weight</code>	logical; if both the treatment and the covariate are continuous, whether points should be shaded according to their weight. Fainter points are those that have smaller weights. Default is <code>TRUE</code> .

## Details

bal.plot() uses `ggplot()` from the **ggplot2** package, and (invisibly) returns a "ggplot" object. For categorical treatments with continuous covariates or continuous treatments with categorical covariates, density plots are created using `geom_density()`, histograms are created using `geom_histogram()`, and empirical CDF plots are created using `geom_step()`; for categorical treatments with categorical covariates, bar graphs are created using `geom_bar()`; for continuous treatments with continuous covariates, scatterplots are created using `geom_point()`.

For continuous treatments with continuous covariates, four additional lines are presented for aid in balance assessment. The red line is the linear fit line. The blue line is a smoothing curve generated with **ggplot2**'s `geom_smooth()` with `method = "auto"`. The horizontal black line is a horizontal reference line intercepting the (unweighted) treatment mean. The vertical black line is a reference line intercepting the (unweighted) treatment mean. Balance is indicated by the flatness of both fit lines and whether they pass through the intersection of the two black reference lines.

When multiple plots are to be displayed (i.e., when requesting subclass balance, cluster balance, or imputation balance, or when multiple sets of weights are provided or `which = "both"`, or when treatment is longitudinal), the plots will be displayed in a grid using **ggplot2**'s `facet_grid()`. Subclassification cannot be used with clusters or multiply imputed data.

To change the plot and axis titles, use `labs()`. Because the output is a ggplot object, other elements can be changed using **ggplot2** functions; see [here](#) for an example.

## Value

A "ggplot" object, returned invisibly.

## Additional Arguments

bal.plot() works like `bal.tab()` in that it can take a variety of types of inputs and yield the same output for each. Depending on what kind of input is given, different additional parameters are required in . . . . For details on what is required and allowed for each additional input and their defaults, see the help file for the `bal.tab()` method associated with the input. The following are the required additional arguments based on each input type:

- For `matchit` objects: None
- For `weightit` objects: None
- For `ps`, `ps.cont`, `mnps`, and `iptw` objects: (`stop.method`; see [defaults](#)).
- For `Match` objects: `formula` and `data` or `covs` and `treat`.
- For `optmatch` objects: `formula` and `data` or `covs` (`treat` is not required).
- For `CBPS` objects: None
- For `ebalance` objects: `formula` and `data` or `covs` and `treat`.
- For `formulas`: `data`
- For `data.frames`: `treat`
- For `designmatch` objects: `formula` and `data` or `covs` and `treat`.
- For `sbw` objects: None
- For `mimids` and `wimids` objects: None, but an argument to `which.imp` should be specified.
- For other objects processed through `bal.tab()`'s default method, whichever arguments are required to identify treatment, variables, and a conditioning method (if any).

**Author(s)**

Noah Greifer

**See Also**[bal.tab\(\)](#)**Examples**

```

data("lalonde", package = "cobalt")

#Nearest Neighbor Matching
library(MatchIt)
m.out <- matchit(treat ~ age + educ + race +
                 married + nodegree + re74 + re75,
                 data = lalonde)

bal.plot(m.out, "age", which = "both")
bal.plot(m.out, "re74", which = "both", type = "ecdf")
bal.plot(m.out, "race", which = "both")
bal.plot(m.out, "distance", which = "both", mirror = TRUE,
         type = "histogram", colors = c("white", "black"))

#PS weighting with a continuous treatment
library(WeightIt)
w.out <- weightit(re75 ~ age + I(age^2) + educ +
                 race + married + nodegree,
                 data = lalonde)

bal.plot(w.out, "age", which = "both")
bal.plot(w.out, "married", which = "both")

```

---

`bal.tab`*Display Balance Statistics in a Table*

---

**Description**

Generates balance statistics on covariates in relation to an observed treatment variable. It is a generic function that dispatches to the method corresponding to the class of the first argument. This page links to each method page and documents the calculation and details of aspects all `bal.tab()` methods use. For information on the use of `bal.tab()` with specific types of objects, use the following links:

- [bal.tab.matchit\(\)](#) for the method for objects returned by **MatchIt**.
- [bal.tab.weightit\(\)](#) for the method for `weightit` and `weightitMSM` objects returned by **WeightIt**.
- [bal.tab.ps\(\)](#) for the method for `ps`, `mnps`, and `iptw` objects returned by **twang** and for `ps.cont` objects returned by **WeightIt**.

- `bal.tab.Match()` for the method for objects returned by **Matching**.
- `bal.tab.optmatch()` for the method for objects returned by **optmatch**.
- `bal.tab.cem.match()` for the method for objects returned by **cem**.
- `bal.tab.CBPS()` for the method for objects returned by **CBPS**.
- `bal.tab.ebalance()` for the method for objects returned by **ebal**.
- `bal.tab.designmatch()` for the method for objects returned by **designmatch**.
- `bal.tab.mimids()` for the method for objects returned by **MatchThem**.
- `bal.tab.sbw()` for the method for objects returned by **sbw**.
- `bal.tab.formula()` and `bal.tab.data.frame()` for the methods for formula and data frame interfaces when the user has covariate values and weights (including matching weights) or subclasses or wants to evaluate balance on an unconditioned data set. For data that corresponds to a longitudinal treatment (i.e., to be analyzed with a marginal structural model), see `bal.tab.time.list()`.
- `bal.tab.default()` for the method for objects that do not come from one of the explicitly supported conditioning packages.

## Usage

```
bal.tab(x, ...)
```

## Arguments

<code>x</code>	an input object on which to assess balance. Can be the output of a call to a balancing function in another package or a formula or data frame. Input to this argument will determine which <code>bal.tab()</code> method is used.
<code>...</code>	arguments passed to other methods. These arguments may be data-related, computation-related, or print-related. See the help pages (linked above) for the individual methods and pages linked below for other arguments that can be supplied.

## Details

`bal.tab()` performs various calculations on the the data objects given, and some of these calculations are not transparent on the help pages of the individual methods. This page details the calculations that are used across `bal.tab()` methods.

### With Binary Point Treatments:

Balance statistics can be requested with the `stats` argument. The default balance statistic for mean differences for continuous variables is the standardized mean difference, which is the difference in the means divided by a measure of spread (i.e., a d-type effect size measure). This is the default because it puts the mean differences on the same scale for comparison with each other and with a given threshold. For binary variables, the default balance statistic is the raw difference in proportion. Although standardized differences in proportion can be computed, raw differences in proportion for binary variables are already on the same scale, and computing the standardized difference in proportion can obscure the true difference in proportion by dividing the difference in proportion by a number that is itself a function of the observed proportions.

Standardized mean differences are calculated using `col_w_smd()` as follows: the numerator is the mean of the treated group minus the mean of the control group, and the denominator is a measure of spread calculated in accordance with the argument to `s.d.denom` or the default of the specific method used. Common approaches in the literature include using the standard deviation of the treated group or using the "pooled" standard deviation (i.e., the square root of the mean of the group variances) in calculating standardized mean differences. The computed spread `bal.tab()` uses is always that of the full, unadjusted sample (i.e., before matching, weighting, or subclassification), as recommended by Stuart (2010).

Prior to computation, all variables are checked for variable type, which allows users to differentiate balance statistic calculations based on type using the arguments to `continuous` and `binary`. First, if a given covariate is numeric and has only 2 levels, it is converted into a binary (0,1) variable. If 0 is a value in the original variable, it retains its value and the other value is converted to 1; otherwise, the lower value is converted to 0 and the other to 1. Next, if the covariate is not numeric or logical (i.e., is a character or factor variable), it will be split into new binary variables, named with the original variable and the value, separated by an underscore. Otherwise, the covariate will be used as is and treated as a continuous variable.

Variance ratios are computed within-sample using `col_w_vr()`, with the larger of the two variances in the numerator if `abs = TRUE`, yielding values greater than or equal to 1. Variance ratios are not calculated for binary variables since they are only a function of the group proportions and thus provide the same information as differences in proportion.

When weighting or matching are used, an "effective sample size" is calculated for each group using the following formula:  $(\sum w)^2 / \sum w^2$ . The effective sample size is "approximately the number of observations from a simple random sample that yields an estimate with sampling variation equal to the sampling variation obtained with the weighted comparison observations" (Ridgeway et al., 2016). The calculated number tends to underestimate the true effective sample size of the weighted samples. The number depends on the variability of the weights, so sometimes trimming units with large weights can actually increase the effective sample size, even though units are being down-weighted. When matching is used, an additional "unweighted" sample size will be displayed indicating the total number of units contributing to the weighted sample.

When subclassification is used, the balance tables for each subclass stored in `$Subclass.Balance` use values calculated as described above. For the aggregate balance table stored in `$Balance.Across.Subclass`, the values of each statistic are computed as a weighted average of the statistic across subclasses, weighted by the proportion of units in each subclass. See `bal.tab.subclass` for more details.

#### **With Continuous Point Treatments:**

When continuous treatment variables are considered, the balance statistic calculated is the Pearson correlation between the covariate and treatment. The correlation after adjustment is computed using `col_w_cov()` as the weighted covariance between the covariate and treatment divided by the product of the standard deviations of the unweighted covariate and treatment, in an analogous way to how the weighted standardized mean difference uses an unweighted measure of spread in its denominator, with the purpose of avoiding the analogous paradox (i.e., where the covariance decreases but is accompanied by a change in the standard deviations, thereby distorting the actual resulting balance computed using the weighted standard deviations).

#### **With Multi-Category Point Treatments:**

For information on using `bal.tab()` with multi-category treatments, see `bal.tab.multi`. Essentially, `bal.tab()` compares pairs of treatment groups in a standard way.

#### **With Longitudinal Treatments:**



For information on using `bal.tab()` with longitudinal treatments, see `bal.tab.msm`. Essentially, `bal.tab()` summarizes balance at each time point and summarizes across time points.

#### With Clustered or Multiply Imputed Data:

For information on using `bal.tab()` with clustered data, see `bal.tab.cluster`. For information on using `bal.tab()` with multiply imputed data, see `bal.tab.imp`.

#### Quick:

Calculations can take some time, especially when there are many variables, interactions, or clusters. When certain values are not printed, by default they are not computed. In particular, variance ratios, KS statistics, and summary tables are not computed when their display has not been requested. This can speed up the overall production of the output when these values are not to be used later. However, when they are to be used later, such as when output is to be further examined with `print()` or is to be used in some other way after the original call to `bal.tab()`, it may be useful to compute them even if they are not to be printed initially. To do so, users can set `quick = FALSE`, which will cause `bal.tab()` to calculate all values and components it can. Note that `love.plot()` is fully functional even when `quick = TRUE` and values are requested that are otherwise not computed in `bal.tab()` with `quick = TRUE`.

#### Missing Data:

If there is missing data in the covariates (i.e., NAs in the covariates provided to `bal.tab()`), a few additional things happen. A warning will appear mentioning that missing values were present in the data set. The computed balance summaries will be for the variables ignoring the missing values. New variables will be created representing missingness indicators for each variable, named `var:<NA>` (with `var` replaced by the actual name of the variable). If `int = TRUE`, balance for the pairwise interactions between the missingness indicators will also be computed. These variables are treated like regular variables once created.

## Value

An object of class `"bal.tab"`. The use of continuous treatments, subclasses, clusters, and/or imputations will also cause the object to inherit other classes. The class `"bal.tab"` has its own `print()` method (`print.bal.tab()`), which formats the output nicely and in accordance with print-related options given in the call to `bal.tab()`, and which can be called with its own options.

For scenarios with binary point treatments and no subclasses, imputations, or clusters, the following are the elements of the `bal.tab` object:

Balance	<p>A data frame containing balance information for each covariate. Balance contains the following columns, with additional columns present when other balance statistics are requested:</p> <ul style="list-style-type: none"> <li>• Type: Whether the covariate is binary, continuous, or a measure of distance (e.g., the propensity score).</li> <li>• M.0.Un: The mean of the control group prior to adjusting.</li> <li>• SD.0.Un: The standard deviation of the control group prior to adjusting.</li> <li>• M.1.Un: The mean of the treated group prior to adjusting.</li> <li>• SD.1.Un: The standard deviation of the treated group prior to adjusting.</li> </ul>
---------	---

- `Diff.Un`: The (standardized) difference in means between the two groups prior to adjusting. See the binary and continuous arguments on the `bal.tab` method pages to determine whether standardized or raw mean differences are being reported. By default, the standardized mean difference is displayed for continuous variables and the raw mean difference (difference in proportion) is displayed for binary variables.
- `M.0.Adj`: The mean of the control group after adjusting.
- `SD.0.Adj`: The standard deviation of the control group after adjusting.
- `M.1.Adj`: The mean of the treated group after adjusting.
- `SD.1.Adj`: The standard deviation of the treated group after adjusting.
- `Diff.Adj`: The (standardized) difference in means between the two groups after adjusting. See the binary and continuous arguments on the `bal.tab` method pages to determine whether standardized or raw mean differences are being reported. By default, the standardized mean difference is displayed for continuous variables and the raw mean difference (difference in proportion) is displayed for binary variables.
- `M.Threshold`: Whether or not the calculated mean difference after adjusting exceeds or is within the threshold given by `thresholds`. If a threshold for mean differences is not specified, this column will be NA.

`Balanced.Means` If a threshold on mean differences is specified, a table tallying the number of variables that exceed or are within the threshold.

`Max.Imbalance.Means`

If a threshold on mean differences is specified, a table displaying the variable with the greatest absolute mean difference.

`Observations` A table displaying the sample sizes before and after adjusting. Often the effective sample size (ESS) will be displayed. See `Details`.

`call` The original function call, if adjustment was performed by a function in another package.

If the treatment is continuous, instead of producing mean differences, `bal.tab()` will produce correlations between the covariates and the treatment. The corresponding entries in the output will be `"Corr.Un"`, `"Corr.Adj"`, and `"R.Threshold"` (and accordingly for the balance tally and maximum imbalance tables).

If multiple weights are supplied, `"Adj"` in `Balance` will be replaced by the provided names of the sets of weights, and extra columns will be added for each set of weights. Additional columns and rows for other items in the output will be created as well.

For `bal.tab` output with subclassification, see [bal.tab.subclass](#).

### Author(s)

Noah Greifer

### References

Ridgeway, G., McCaffrey, D., Morral, A., Burgette, L., & Griffin, B. A. (2016). Toolkit for Weighting and Analysis of Nonequivalent Groups: A tutorial for the `twang` package. *R vignette*. RAND.

Stuart, E. A. (2010). Matching Methods for Causal Inference: A Review and a Look Forward. *Statistical Science*, 25(1), 1-21. doi: [10.1214/09STS313](https://doi.org/10.1214/09STS313)

---

bal.tab.CBPS

*Balance statistics for CBPS Objects*

---

## Description

Generates balance statistics for CBPS and CBMSM objects from the **CBPS** package.

## Usage

```
## S3 method for class 'CBPS'
bal.tab(x,
        stats,
        int = FALSE,
        poly = 1,
        distance = NULL,
        addl = NULL,
        data = NULL,
        continuous,
        binary,
        s.d.denom,
        thresholds = NULL,
        weights = NULL,
        cluster = NULL,
        imp = NULL,
        pairwise = TRUE,
        s.weights = NULL,
        abs = FALSE,
        subset = NULL,
        quick = TRUE,
        ...)

## S3 method for class 'CBMSM'
bal.tab(x,
        stats,
        int = FALSE,
        poly = 1,
        distance.list = NULL,
        addl.list = NULL,
        data = NULL,
        continuous,
        binary,
        s.d.denom,
        thresholds = NULL,
        weights = NULL,
```

```

cluster = NULL,
imp = NULL,
s.weights = NULL,
abs = FALSE,
subset = NULL,
quick = TRUE,
...)
```

## Arguments

- x** a CBPS or CBMSM object; the output of a call to `CBPS::CBPS()` or `CBPS::CBMSM()`.
- stats** character; which statistic(s) should be reported. See [stats](#) for allowable options. For binary and multi-category treatments, "mean.diffs" (i.e., mean differences) is the default. For continuous treatments, "correlations" (i.e., treatment-covariate Pearson correlations) is the default. Multiple options are allowed.
- int** logical or numeric; whether or not to include 2-way interactions of covariates included in `covs` and in `add1`. If numeric, will be passed to `poly` as well.
- poly** numeric; the highest polynomial of each continuous covariate to display. For example, if 2, squares of each continuous covariate will be displayed (in addition to the covariate itself); if 3, squares and cubes of each continuous covariate will be displayed, etc. If 1, the default, only the base covariate will be displayed. If `int` is numeric, `poly` will take on the value of `int`.
- distance, distance.list** an optional formula or data frame containing distance values (e.g., propensity scores) or a character vector containing their names. If a formula or variable names are specified, `bal.tab()` will look first in the argument to `data`, if specified, and next in the input object. Note that the propensity scores generated by `CBPS()` and `CBMSM()` are automatically included and named "prop.score". For CBMSM objects, can be a list of distance values as described above, with one list entry per time period. Each data set must have one row per individual, unlike the data frame in the original call to `CBMSM()`.
- add1, add1.list** an optional formula or data frame containing additional covariates for which to present balance or a character vector containing their names. If a formula or variable names are specified, `bal.tab()` will look first in the argument to `data`, if specified, and next in the input object. For CBMSM objects, can be a list of additional covariate values as described above, with one list entry per time period. Each data set must have one row per individual, unlike the data frame in the original call to `CBMSM()`.
- data** an optional data frame containing variables that might be named in arguments to `distance`, `add1`, `cluster`, and `imp`. Can also be `mids` object, the output of a call to `mice()` from the `mice` package, containing multiply imputed data sets. In this case, `imp` is automatically supplied using the imputation variable created from processing the `mids` object.
- continuous** whether mean differences for continuous variables should be standardized ("std") or raw ("raw"). Default "std". Abbreviations allowed. This option can be set globally using `set.cobalt.options()`.

binary	whether mean differences for binary variables (i.e., difference in proportion) should be standardized ("std") or raw ("raw"). Default "raw". Abbreviations allowed. This option can be set globally using <code>set.cobalt.options()</code> .
s.d.denom	character; how the denominator for standardized mean differences should be calculated, if requested. See <code>col_w_smd()</code> for allowable options. If not specified, <code>bal.tab()</code> will use "treated" if the estimand of the call to <code>CBPS()</code> is the ATT and "pooled" if the estimand is the ATE. Abbreviations allowed.
thresholds	a named vector of balance thresholds, where the name corresponds to the statistic (i.e., in <code>stats</code> ) that the threshold applies to. For example, to request thresholds on mean differences and variance ratios, one can set <code>thresholds = c(m = .05, v = 2)</code> . Requesting a threshold automatically requests the display of that statistic. See <code>stats</code> .
weights	a named list containing additional weights on which to assess balance. Each entry can be a vector of weights, the name of a variable in data that contains weights, or an object with a <code>get.w()</code> method.
cluster	either a vector containing cluster membership for each unit or a string containing the name of the cluster membership variable in data or the CBPS object. See <code>bal.tab.cluster</code> for details.
imp	either a vector containing imputation indices for each unit or a string containing the name of the imputation index variable in data or the original data set used in the call to <code>CBPS()</code> or <code>CBMSM()</code> . See <code>bal.tab.imp</code> for details. Not necessary if data is a <code>mids</code> object.
pairwise	whether balance should be computed for pairs of treatments or for each treatment against all groups combined. See <code>bal.tab.multi</code> for details. This can also be used with a binary treatment to assess balance with respect to the full sample.
s.weights	Optional; either a vector containing sampling weights for each unit or a string containing the name of the sampling weight variable in data or the CBPS object. If the original call to <code>CBPS()</code> included sampling weights, they should be specified again here to ensure correct computation of balance statistics and unadjusted values. See Details below.
abs	logical; whether displayed balance statistics should be in absolute value or not.
subset	A logical or numeric vector denoting whether each observation should be included or which observations should be included. If logical, it should be the same length as the variables in the original call to <code>CBPS()</code> or <code>CBMSM()</code> . NAs will be treated as FALSE. This can be used as an alternative to <code>cluster</code> to examine balance on subsets of the data.
quick	logical; if TRUE, will not compute any values that will not be displayed. Set to FALSE if computed values not displayed will be used later.
...	Further arguments to control display of output. See <code>display options</code> for details.

### Details

`bal.tab.CBPS()` and `bal.tab.CBMSM()` generate a list of balance summaries for the CBPS or CBMSM object given and functions similarly to `CBPS::balance()`.

The `thresholds` argument controls whether extra columns should be inserted into the Balance table describing whether the balance statistics in question exceeded or were within the threshold. Including these thresholds also creates summary tables tallying the number of variables that exceeded and were within the threshold and displaying the variables with the greatest imbalance on that balance measure.

The CBPS object does not return sampling weights even if they are used; rather, the weights returned already have the sampling weights combined within them. Because some of the checks and defaults in `bal.tab()` rely on patterns in these weights, using sampling weights in `CBPS()` without specifying them in `bal.tab()` can lead to incorrect results. If sampling weights are used in `CBPS()`, it is important that they are specified in `bal.tab()` as well.

### Value

For point treatments, if clusters are not specified, an object of class `"bal.tab"` containing balance summaries for the CBPS object. See [bal.tab\(\)](#) for details.

If clusters are specified, an object of class `"bal.tab.cluster"` containing balance summaries within each cluster and a summary of balance across clusters. See [bal.tab.cluster](#) for details.

If `CBPS()` is used with multi-category treatments, an object of class `"bal.tab.multi"` containing balance summaries for each pairwise treatment comparison and a summary of balance across pairwise comparisons. See [bal.tab.multi](#) for details.

If `CBMSM()` is used for longitudinal treatments, an object of class `"bal.tab.msm"` containing balance summaries for each time period and a summary of balance across time periods. See [bal.tab.msm](#) for details.

### Author(s)

Noah Greifer

### See Also

[bal.tab\(\)](#) for details of calculations. [bal.tab.cluster](#) for more information on clustered data. [bal.tab.multi](#) for more information on multi-category treatments. [bal.tab.msm](#) for more information on longitudinal treatments.

### Examples

```
library(CBPS)
data("lalonde", package = "cobalt")

## Using CBPS() for generating covariate balancing
## propensity score weights
cbps.out <- CBPS(treat ~ age + educ + married + race +
                nodegree + re74 + re75, data = lalonde)

bal.tab(cbps.out)
```

---

 bal.tab.cem.match      *Balance Statistics for cem Objects*


---

## Description

Generates balance statistics for `cem.match` objects from **cem**.

## Usage

```
## S3 method for class 'cem.match'
bal.tab(x,
        data,
        stats,
        int = FALSE,
        poly = 1,
        distance = NULL,
        add1 = NULL,
        continuous,
        binary,
        s.d.denom,
        thresholds = NULL,
        weights = NULL,
        cluster = NULL,
        imp = NULL,
        pairwise = TRUE,
        abs = FALSE,
        subset = NULL,
        quick = TRUE,
        ...)
```

## Arguments

<code>x</code>	a <code>cem.match</code> or <code>cem.match.list</code> object; the output of a call to <code>cem::cem()</code> .
<code>data</code>	a data frame containing the treatment, covariates, and variables that might be named in arguments to <code>distance</code> , <code>add1</code> , <code>cluster</code> , and <code>imp</code> . Can also be <code>mids</code> object, the output of a call to <code>mice()</code> from the <b>mice</b> package, containing multiply imputed data sets. In this case, <code>imp</code> is automatically supplied using the imputation variable created from processing the <code>mids</code> object. An argument to <code>data</code> is required. It must be the same data used in the call to <code>cem()</code> or a <code>mids</code> object from which the data supplied to <code>datalist</code> in the <code>cem()</code> call originated.
<code>stats</code>	character; which statistic(s) should be reported. See <a href="#">stats</a> for allowable options. For binary and multi-category treatments, "mean.diffs" (i.e., mean differences) is the default. Multiple options are allowed.
<code>int</code>	logical or numeric; whether or not to include 2-way interactions of covariates included in <code>covs</code> and in <code>add1</code> . If numeric, will be passed to <code>poly</code> as well.

<code>poly</code>	numeric; the highest polynomial of each continuous covariate to display. For example, if 2, squares of each continuous covariate will be displayed (in addition to the covariate itself); if 3, squares and cubes of each continuous covariate will be displayed, etc. If 1, the default, only the base covariate will be displayed. If <code>int</code> is numeric, <code>poly</code> will take on the value of <code>int</code> .
<code>distance</code>	an optional formula or data frame containing distance values (e.g., propensity scores) or a character vector containing their names. If a formula or variable names are specified, <code>bal.tab()</code> will look in the argument to <code>data</code> , if specified.
<code>addl</code>	an optional formula or data frame containing additional covariates for which to present balance or a character vector containing their names. If a formula or variable names are specified, <code>bal.tab()</code> will look in the arguments to <code>covs</code> and <code>data</code> , if specified.
<code>continuous</code>	whether mean differences for continuous variables should be standardized (" <code>std</code> ") or raw (" <code>raw</code> "). Default " <code>std</code> ". Abbreviations allowed. This option can be set globally using <code>set.cobalt.options()</code> . This argument is used to set <code>std</code> in <code>col_w_smd()</code> .
<code>binary</code>	whether mean differences for binary variables (i.e., difference in proportion) should be standardized (" <code>std</code> ") or raw (" <code>raw</code> "). Default " <code>raw</code> ". Abbreviations allowed. This option can be set globally using <code>set.cobalt.options()</code> . This argument is used to set <code>std</code> in <code>col_w_smd()</code> .
<code>s.d.denom</code>	character; how the denominator for standardized mean differences should be calculated, if requested. See <code>col_w_smd()</code> for allowable options. The default is " <code>treated</code> ", where the treated group corresponds to the <code>baseline.group</code> in the call to <code>cem()</code> . Abbreviations allowed.
<code>thresholds</code>	a named vector of balance thresholds, where the name corresponds to the statistic (i.e., in <code>stats</code> ) that the threshold applies to. For example, to request thresholds on mean differences and variance ratios, one can set <code>thresholds = c(m = .05, v = 2)</code> . Requesting a threshold automatically requests the display of that statistic. See Details.
<code>weights</code>	a named list containing additional weights on which to assess balance. Each entry can be a vector of weights, the name of a variable in <code>data</code> that contains weights, or an object with a <code>get.w()</code> method.
<code>cluster</code>	either a vector containing cluster membership for each unit or a string containing the name of the cluster membership variable in <code>data</code> . See <code>bal.tab.cluster</code> for details.
<code>imp</code>	either a vector containing imputation indices for each unit or a string containing the name of the imputation index variable in <code>data</code> . See <code>bal.tab.imp</code> for details. Not necessary if <code>data</code> is a <code>mids</code> object.
<code>pairwise</code>	whether balance should be computed for pairs of treatments or for each treatment against all groups combined. See <code>bal.tab.multi</code> for details. This can also be used with a binary treatment to assess balance with respect to the full sample.
<code>abs</code>	logical; whether displayed balance statistics should be in absolute value or not.
<code>subset</code>	a logical or numeric vector denoting whether each observation should be included or which observations should be included. If logical, it should be the



	same length as the variables in the original call to <code>cem()</code> . NAs will be treated as FALSE. This can be used as an alternative to <code>cluster</code> to examine balance on subsets of the data.
<code>quick</code>	logical; if TRUE, will not compute any values that will not be displayed. Set to FALSE if computed values not displayed will be used later.
<code>...</code>	further arguments to control display of output. See <a href="#">display options</a> for details.

### Details

`bal.tab.cem.match()` generates a list of balance summaries for the `cem.match` object given, and functions similarly to `cem::imbalance()`.

The `threshold` argument controls whether extra columns should be inserted into the Balance table describing whether the balance statistics in question exceeded or were within the threshold. Including these thresholds also creates summary tables tallying the number of variables that exceeded and were within the threshold and displaying the variables with the greatest imbalance on that balance measure.

### Value

If clusters and imputations are not specified, an object of class `"bal.tab"` containing balance summaries for the `cem.match` object. See [bal.tab\(\)](#) for details.

If imputations are specified, an object of class `"bal.tab.imp"` containing balance summaries for each imputation and a summary of balance across imputations. See [bal.tab.imp](#) for details.

If `cem()` is used with multi-category treatments, an object of class `"bal.tab.multi"` containing balance summaries for each pairwise treatment comparison. See [bal.tab.multi](#) for details.

If clusters are specified, an object of class `"bal.tab.cluster"` containing balance summaries within each cluster and a summary of balance across clusters. See [bal.tab.cluster](#) for details.

### Author(s)

Noah Greifer

### See Also

[bal.tab\(\)](#) for details of calculations.

### Examples

```
library(cem); data("lalonge", package = "cobalt")

## Coarsened exact matching
cem.out <- cem("treat", data = lalonge, drop = "re78")

bal.tab(cem.out, data = lalonge, un = TRUE,
        stats = c("m", "k"))
```

---

bal.tab.default      *Balance Statistics for Other Objects*

---

## Description

Generates balance statistics using an object for which there is not a defined method.

## Usage

```
## Default S3 method:
bal.tab(x, ...)
```

## Arguments

`x`                    An object containing information about conditioning. See Details.

`...`                Arguments that would be passed to `bal.tab.formula()`, `bal.tab.data.frame()`, or `bal.tab.time.list()`. See Details.

## Details

`bal.tab.default()` processes its input and attempt to extract enough information from it to display covariate balance for `x`. The goal of this method was to allow users who have created their own objects containing conditioning information (i.e., weights, subclasses, treatments, covariates, etc.) to access the capabilities of `bal.tab()` without having a special method written for them. By including the correct items in `x`, `bal.tab.default()` can present balance tables as if the input was the output of one of the specifically supported packages (e.g., **MatchIt**, **twang**, etc.).

The function will search `x` for the following named items and attempt to process them:

`treat` A vector (numeric, character, factor) containing the values of the treatment for each unit or the name of the column in data containing them. Essentially the same input to `treat` in `bal.tab.data.frame()`.

`treat.list` A list of vectors (numeric, character, factor) containing, for each time point, the values of the treatment for each unit or the name of the column in data containing them. Essentially the same input to `treat.list` in `bal.tab.time.list()`.

`covs` A data.frame containing the values of the covariates for each unit. Essentially the same input to `covs` in `bal.tab.data.frame()`.

`covs.list` A list of data.frames containing, for each time point, the values of the covariates for each unit. Essentially the same input to `covs.list` in `bal.tab.time.list()`.

`formula` A formula with the treatment variable as the response and the covariates for which balance is to be assessed as the terms. Essentially the same input to `formula` in `bal.tab.formula()`.

`formula.list` A list of formulas with, for each time point, the treatment variable as the response and the covariates for which balance is to be assessed as the terms. Essentially the same input to `formula.list` in `bal.tab.time.list()`.

- `data` A `data.frame` containing variables with the names used in other arguments and components (e.g., `formula`, `weights`, etc.). Essentially the same input to `data` in `bal.tab.formula()`, `bal.tab.data.frame()`, or `bal.tab.time.list()`.
- `weights` A vector, list, or `data.frame` containing weights for each unit or a string containing the names of the weights variables in `data`. Essentially the same input to `weights` in `bal.tab.data.frame()` or `bal.tab.time.list()`.
- `distance` A vector, formula, or `data.frame` containing distance values (e.g., propensity scores) or a character vector containing their names. If a formula or variable names are specified, `bal.tab()` will look in the argument to `data`, if specified. Essentially the same input to `distance` in `bal.tab.data.frame()`.
- `formula.list` A list of vectors or `data.frames` containing, for each time point, distance values (e.g., propensity scores) for each unit or a string containing the name of the distance variable in `data`. Essentially the same input to `distance.list` in `bal.tab.time.list()`.
- `subclass` A vector containing subclass membership for each unit or a string containing the name of the subclass variable in `data`. Essentially the same input to `subclass` in `bal.tab.data.frame()`.
- `match.strata` A vector containing matching stratum membership for each unit or a string containing the name of the matching stratum variable in `data`. Essentially the same input to `match.strata` in `bal.tab.data.frame()`.
- `estimand` A character vector; whether the desired estimand is the "ATT", "ATC", or "ATE" for each set of weights. Essentially the same input to `estimand` in `bal.tab.data.frame()`.
- `s.weights` A vector containing sampling weights for each unit or a string containing the name of the sampling weight variable in `data`. Essentially the same input to `s.weights` in `bal.tab.data.frame()` or `bal.tab.time.list()`.
- `focal` The name of the focal treatment when multi-category treatments are used. Essentially the same input to `focal` in `bal.tab.data.frame()`.
- `call` A call object containing the function call, usually generated by using `match.call()` inside the function that created `x`.

Any of these items can also be supplied directly to `bal.tab.default`, e.g., `bal.tab.default(x, formula = treat ~ x1 + x2)`. If supplied, it will override the object with the same role in `x`. In addition, any arguments to `bal.tab.formula()`, `bal.tab.data.frame()`, and `bal.tab.time.list()` are allowed and perform the same function.

At least some inputs containing information to create the treatment and covariates are required (e.g., `formula` and `data` or `covs` and `treat`). All other arguments are optional and have the same defaults as those in `bal.tab.data.frame()` or `bal.tab.time.list()`. If `treat.list`, `covs.list`, or `formula.list` are supplied in `x` or as an argument to `bal.tab.default()`, the function will proceed considering a longitudinal treatment. Otherwise, it will proceed considering a point treatment.

`bal.tab.default()`, like other `bal.tab` methods, is just a shortcut to supply arguments to `bal.tab.data.frame()` or `bal.tab.time.list()`. Therefore, any matters regarding argument priority or function are described in the documentation for these methods.

## Value

For point treatments, if clusters and imputations are not specified, an object of class "bal.tab" containing balance summaries for the specified treatment and covariates. See `bal.tab()` for details.

If clusters are specified, an object of class "bal.tab.cluster" containing balance summaries within each cluster and a summary of balance across clusters. See [bal.tab.cluster](#) for details.

If imputations are specified, an object of class "bal.tab.imp" containing balance summaries for each imputation and a summary of balance across imputations, just as with clusters. See [bal.tab.imp](#) for details.

If multi-category treatments are used, an object of class "bal.tab.multi" containing balance summaries for each pairwise treatment comparison and a summary of balance across pairwise comparisons. See [bal.tab.multi](#) for details.

If longitudinal treatments are used, an object of class "bal.tab.msm" containing balance summaries at each time point. Each balance summary is its own bal.tab object. See [bal.tab.msm](#) for more details.

### Author(s)

Noah Greifer

### See Also

[bal.tab.data.frame\(\)](#) and [bal.tab.time.list\(\)](#) for additional arguments to be supplied. [bal.tab\(\)](#) for output and details of calculations. [bal.tab.cluster](#) for more information on clustered data. [bal.tab.imp](#) for more information on multiply imputed data. [bal.tab.multi](#) for more information on multi-category treatments.

### Examples

```
data("lalonde", package = "cobalt")
covs <- subset(lalonde, select = -c(treat, re78))

##Writing a function the produces output for direct
##use in bal.tab.default

ate.weights <- function(treat, covs) {
  data <- data.frame(treat, covs)
  formula <- formula(data)
  ps <- glm(formula, data = data,
            family = "binomial")$fitted.values
  weights <- treat/ps + (1-treat)/(1-ps)
  call <- match.call()
  out <- list(treat = treat,
             covs = covs,
             distance = ps,
             weights = weights,
             estimand = "ATE",
             call = call)
  return(out)
}

out <- ate.weights(lalonde$treat, covs)

bal.tab(out, un = TRUE)
```

---

bal.tab.df.formula      *Balance Statistics for Data Sets*

---

### Description

Generates balance statistics for unadjusted, matched, weighted, or stratified data using either a `data.frame` or `formula` interface.

### Usage

```
## S3 method for class 'data.frame'
bal.tab(x,
  treat,
  data = NULL,
  weights = NULL,
  subclass = NULL,
  match.strata = NULL,
  method,
  stats,
  int = FALSE,
  poly = 1,
  distance = NULL,
  add1 = NULL,
  continuous,
  binary,
  s.d.denom,
  thresholds = NULL,
  cluster = NULL,
  imp = NULL,
  pairwise = TRUE,
  focal = NULL,
  s.weights = NULL,
  estimand = NULL,
  abs = FALSE,
  subset = NULL,
  quick = TRUE,
  ...)

## S3 method for class 'formula'
bal.tab(x,
  data = NULL,
  ...)
```

### Arguments

`x`                      either a `data.frame` containing covariate values for each unit or a `formula` with the treatment variable as the response and the covariates for which balance is to

be assessed as the terms. If a formula is supplied, all terms must be present as variable names in data or the global environment.

treat	Either a vector containing treatment status values for each unit or a string containing the name of the treatment variable in data.
data	Optional; a <code>data.frame</code> containing variables with the names used in formula, <code>treat</code> , <code>weights</code> , <code>distance</code> , <code>add1</code> , <code>subclass</code> , <code>match.strata</code> , <code>cluster</code> , and/or <code>imp</code> if any. Can also be a <code>mids</code> object, the output of a call to <code>mice()</code> from the <b>mice</b> package, containing multiply imputed data sets. In this case, <code>imp</code> is automatically supplied using the imputation variable created from processing the <code>mids</code> object.
weights	Optional; a vector, list, or <code>data.frame</code> containing weights for each unit or a string containing the names of the weights variables in data. These can be weights generated by, e.g., inverse probability weighting or matching weights resulting from a matching algorithm. This must be specified in <code>method</code> . If <code>weights=NULL</code> , <code>subclass=NULL</code> and <code>match.strata=NULL</code> , balance information will be presented only for the unadjusted sample.
subclass	Optional; either a vector containing subclass membership for each unit or a string containing the name of the subclass variable in data. If <code>weights=NULL</code> , <code>subclass=NULL</code> and <code>match.strata=NULL</code> , balance information will be presented only for the unadjusted sample.
match.strata	Optional; either a vector containing matching stratum membership for each unit or a string containing the name of the matching stratum variable in data. If <code>weights=NULL</code> , <code>subclass=NULL</code> and <code>match.strata=NULL</code> , balance information will be presented only for the unadjusted sample.
method	A character vector containing the method of adjustment, if any. If <code>weights</code> are specified, the user can specify either "matching" or "weighting"; "weighting" is the default. If multiple sets of weights are used, each must have a corresponding value for <code>method</code> , but if they are all of the same type, only one value is required. If <code>subclass</code> is specified, "subclassification" is the default. Abbreviations allowed. The only distinction between "matching" and "weighting" is how sample sizes are displayed.
stats	character; which statistic(s) should be reported. See <a href="#">stats</a> for allowable options. For binary and multi-category treatments, "mean.diffs" (i.e., mean differences) is the default. For continuous treatments, "correlations" (i.e., treatment-covariate Pearson correlations) is the default. Multiple options are allowed.
int	logical or numeric; whether or not to include 2-way interactions of covariates included in <code>covs</code> and in <code>add1</code> . If numeric, will be passed to <code>poly</code> as well.
poly	numeric; the highest polynomial of each continuous covariate to display. For example, if 2, squares of each continuous covariate will be displayed (in addition to the covariate itself); if 3, squares and cubes of each continuous covariate will be displayed, etc. If 1, the default, only the base covariate will be displayed. If <code>int</code> is numeric, <code>poly</code> will take on the value of <code>int</code> .
distance	an optional formula or data frame containing distance values (e.g., propensity scores) or a character vector containing their names. If a formula or variable names are specified, <code>bal.tab()</code> will look in the argument to <code>data</code> , if specified.

add1	an optional formula or data frame containing additional covariates for which to present balance or a character vector containing their names. If a formula or variable names are specified, <code>bal.tab()</code> will look in the arguments to <code>covs</code> and <code>data</code> , if specified.
continuous	whether mean differences for continuous variables should be standardized ("std") or raw ("raw"). Default "std". Abbreviations allowed. This option can be set globally using <code>set.cobalt.options()</code> .
binary	whether mean differences for binary variables (i.e., difference in proportion) should be standardized ("std") or raw ("raw"). Default "raw". Abbreviations allowed. This option can be set globally using <code>set.cobalt.options()</code> .
s.d.denom	character; how the denominator for standardized mean differences should be calculated, if requested. See <code>col_w_smd()</code> for allowable options. If weights are supplied, each set of weights should have a corresponding entry to <code>s.d.denom</code> . Abbreviations allowed. If left blank and weights, subclasses, or matching strata are supplied, <code>bal.tab()</code> will figure out which one is best based on the estimand, if given (for ATT, "treated"; for ATC, "control"; otherwise "pooled") and other clues if not.
thresholds	a named vector of balance thresholds, where the name corresponds to the statistic (i.e., in <code>stats</code> ) that the threshold applies to. For example, to request thresholds on mean differences and variance ratios, one can set <code>thresholds = c(m = .05, v = 2)</code> . Requesting a threshold automatically requests the display of that statistic. See Details.
cluster	either a vector containing cluster membership for each unit or a string containing the name of the cluster membership variable in <code>data</code> . See <code>bal.tab.cluster</code> for details.
imp	either a vector containing imputation indices for each unit or a string containing the name of the imputation index variable in <code>data</code> . See <code>bal.tab.imp</code> for details. Not necessary if <code>data</code> is a <code>mids</code> object.
pairwise	whether balance should be computed for pairs of treatments or for each treatment against all groups combined. See <code>bal.tab.multi</code> for details. This can also be used with a binary treatment to assess balance with respect to the full sample.
focal	The name of the focal treatment when multiple categorical treatments are used. See <code>bal.tab.multi</code> for details.
s.weights	Optional; either a vector containing sampling weights for each unit or a string containing the name of the sampling weight variable in <code>data</code> . These function like regular weights except that both the adjusted and unadjusted samples will be weighted according to these weights if weights are used.
estimand	character; whether the desired estimand is the "ATT", "ATC", or "ATE" for each set of weights. This argument can be used in place of <code>s.d.denom</code> to specify how standardized differences are calculated.
abs	logical; whether displayed balance statistics should be in absolute value or not.
subset	A logical or numeric vector denoting whether each observation should be included or which observations should be included. If <code>logical</code> , it should be the same length as the treatment and covariates. NAs will be treated as FALSE. This

	can be used as an alternative to <code>cluster</code> to examine balance on subsets of the data.
<code>quick</code>	logical; if TRUE, will not compute any values that will not be displayed. Set to FALSE if computed values not displayed will be used later.
<code>...</code>	For <code>bal.tab.formula()</code> , other arguments to be passed to <code>bal.tab.data.frame()</code> . Otherwise, further arguments to control display of output. See <a href="#">display options</a> for details.

## Details

`bal.tab.data.frame()` generates a list of balance summaries for the covariates and treatment status values given. `bal.tab.formula()` does the same but uses a formula interface instead. When the formula interface is used, the formula and data are reshaped into a treatment vector and `data.frame` of covariates and then simply passed through the `data.frame` method.

The argument to `match.strata` corresponds to a factor vector containing the name or index of each pair/stratum for units conditioned through matching, for example, using the **optmatch** package. If more than one of `weights`, `subclass`, or `match.strata` are specified, `bal.tab()` will attempt to figure out which one to apply. Currently only one of these can be applied at a time. `bal.tab()` behaves differently depending on whether subclasses are used in conditioning or not. If they are used, `bal.tab()` creates balance statistics for each subclass and for the sample in aggregate. See [bal.tab.subclass](#) for more information.

All balance statistics are calculated whether they are displayed by `print` or not, unless `quick = TRUE`. The `threshold` argument controls whether extra columns should be inserted into the Balance table describing whether the balance statistics in question exceeded or were within the threshold. Including these thresholds also creates summary tables tallying the number of variables that exceeded and were within the threshold and displaying the variables with the greatest imbalance on that balance measure. When subclassification is used, the extra threshold columns are placed within the balance tables for each subclass as well as in the aggregate balance table, and the summary tables display balance for each subclass.

The inputs (if any) to `covs` and `data` must be a `data.frame`; if more than one variable is included, this is straightforward (i.e., because `data[,c("v1", "v2")]` is already a `data.frame`), but if only one variable is used with the matrix subsetting syntax (e.g., `data[, "v1"]`), R will coerce it to a vector, thus making it unfit for input. To avoid this, make sure to use the list subsetting syntax (e.g., `data["v1"]`) if only one variable is to be added (this can also be used for multiple variables and is good practice in general). Again, when more than one variable is included, the input is generally already a `data.frame` and nothing needs to be done.

Multiple sets of weights can be supplied simultaneously by entering a `data.frame` or a character vector containing the names of weight variables found in `data` or a list of weights vectors or names. The arguments to `method`, `s.d.denom`, and `estimand`, if any, must be either the same length as the number of sets of weights or of length one, where the sole entry is applied to all sets. When standardized differences are computed for the unadjusted group, they are done using the first entry to `s.d.denom` or `estimand`. When only one set of weights is supplied, the output for the adjusted group will simply be called "Adj", but otherwise will be named after each corresponding set of weights. Specifying multiple sets of weights will also add components to other output of `bal.tab()`.



**Value**

For point treatments, if clusters and imputations are not specified, an object of class "bal.tab" containing balance summaries for the specified treatment and covariates. See [bal.tab\(\)](#) for details.

If imputations are specified, an object of class "bal.tab.imp" containing balance summaries for each imputation and a summary of balance across imputations. See [bal.tab.imp](#) for details.

If multiple categorical treatments are used, an object of class "bal.tab.multi" containing balance summaries for each pairwise treatment comparison. See [bal.tab.multi](#) for details.

If clusters are specified, an object of class "bal.tab.cluster" containing balance summaries within each cluster and a summary of balance across clusters. See [bal.tab.cluster](#) for details.

**Author(s)**

Noah Greifer

**See Also**

[bal.tab\(\)](#) for output and details of calculations. [bal.tab.cluster](#) for more information on clustered data. [bal.tab.imp](#) for more information on multiply imputed data. [bal.tab.multi](#) for more information on multiple categorical treatments.

**Examples**

```
data("lalonde", package = "cobalt")
lalonde$p.score <- glm(treat ~ age + educ + race, data = lalonde,
  family = "binomial")$fitted.values
covariates <- subset(lalonde, select = c(age, educ, race))

## Propensity score weighting using IPTW
lalonde$iptw.weights <- ifelse(lalonde$treat==1,
  1/lalonde$p.score,
  1/(1-lalonde$p.score))

# data frame interface:
bal.tab(covariates, treat = "treat", data = lalonde,
  weights = "iptw.weights", s.d.denom = "pooled")

# Formula interface:
bal.tab(treat ~ age + educ + race, data = lalonde,
  weights = "iptw.weights", s.d.denom = "pooled")

## Propensity score subclassification
lalonde$subclass <- findInterval(lalonde$p.score,
  quantile(lalonde$p.score,
  (0:6)/6), all.inside = TRUE)

# data frame interface:
bal.tab(covariates, treat = "treat", data = lalonde,
  subclass = "subclass", disp.subclass = TRUE,
  s.d.denom = "pooled")
```

```
# Formula interface:
bal.tab(treat ~ age + educ + race, data = lalonde,
        subclass = "subclass", disp.subclass = TRUE,
        s.d.denom = "pooled")
```

---

```
bal.tab.df.formula.list
```

*Balance Statistics for Longitudinal Datasets*

---

### Description

Generates balance statistics for data coming from a longitudinal treatment scenario. The primary input is in the form of a list of formulas or data.frames contain the covariates at each time point. `bal.tab()` automatically classifies this list as either a `data.frame.list` or `formula.list`, respectively.

### Usage

```
## S3 method for class 'data.frame.list'
bal.tab(x,
        treat.list = NULL,
        data = NULL,
        weights = NULL,
        stats,
        int = FALSE,
        poly = 1,
        distance.list = NULL,
        addl.list = NULL,
        method,
        continuous,
        binary,
        s.d.denom,
        thresholds = NULL,
        cluster = NULL,
        imp = NULL,
        pairwise = TRUE,
        s.weights = NULL,
        estimand = "ATE",
        abs = FALSE,
        subset = NULL,
        quick = TRUE,
        ...)

## S3 method for class 'formula.list'
bal.tab(x,
        data = NULL,
        ...)
```

**Arguments**

<code>x</code>	either a list of data frames containing all the covariates to be assessed at each time point or a list of formulas with the treatment for each time period on the left and the covariates for which balance is to be displayed on the right. Covariates to be assessed at multiple points must be included in the entries for each time point. Data must be in the "wide" format, with one row per unit. If a formula list is supplied, an argument to data is required unless all objects in the formulas exist in the environment.
<code>treat.list</code>	treatment status for each unit at each time point. This can be specified as a list or data frame of vectors, each of which contains the treatment status of each individual at each time point, or a list or vector of the names of variables in data that contain treatment at each time point.
<code>data</code>	for <code>bal.tab.data.frame.list()</code> : optional; a data frame containing variables with the names used in <code>treat.list</code> , <code>weights</code> , <code>distance.list</code> , and/or <code>addl.list</code> , if any. For <code>bal.tab.formula.list()</code> : required; a data frame containing all covariates named in the formulas and variables with the names used in the arguments mentioned above. If all objects in the <code>x</code> formulas are present in the environment, can be omitted. data must be in the "wide" format, with one row per unit. Can also be <code>mids</code> object, the output of a call to <code>mice()</code> from the <code>mice</code> package, containing multiply imputed data sets. In this case, <code>imp</code> is automatically supplied using the imputation variable created from processing the <code>mids</code> object.
<code>weights</code>	optional; a vector, list, or data frame containing weights for each unit or a string containing the names of the weights variables in data. These can be weights generated by, e.g., inverse probability weighting. If <code>weights=NULL</code> , balance information will be presented only for the unadjusted sample.
<code>stats</code>	character; which statistic(s) should be reported. See <code>stats</code> for allowable options. For binary and multi-category treatments, "mean.diffs" (i.e., mean differences) is the default. For continuous treatments, "correlations" (i.e., treatment-covariate Pearson correlations) is the default. Multiple options are allowed.
<code>int</code>	logical or numeric; whether or not to include 2-way interactions of covariates included in <code>covs</code> and in <code>addl</code> . If <code>numeric</code> , will be passed to <code>poly</code> as well.
<code>poly</code>	numeric; the highest polynomial of each continuous covariate to display. For example, if 2, squares of each continuous covariate will be displayed (in addition to the covariate itself); if 3, squares and cubes of each continuous covariate will be displayed, etc. If 1, the default, only the base covariate will be displayed. If <code>int</code> is <code>numeric</code> , <code>poly</code> will take on the value of <code>int</code> .
<code>distance.list</code>	optional; distance values (e.g., propensity scores) for each unit. These can be specified as a list of vectors or data frames containing the distance values (one for each time point), or as a single vector or data frame to be applied at all times points. The vectors or data frames can be replaced with the names of variables in data containing the distance values. If a list is used and some time points are not to have distance values, these can be replaced with <code>NULL</code> in the list.
<code>addl.list</code>	optional; additional covariates for which to present balance. These may be covariates included in the original dataset but not included in <code>x</code> . In general, it

	makes more sense to include all desired variables in <code>x</code> than in <code>addl.list</code> . The arguments can be entered the same ways as those to <code>distance.list</code> .
<code>method</code>	a character vector containing the method of adjustment, if any. Currently only "weighting" is supported.
<code>continuous</code>	whether mean differences for continuous variables should be standardized ("std") or raw ("raw"). Default "std". Abbreviations allowed. This option can be set globally using <code>set.cobalt.options()</code> .
<code>binary</code>	whether mean differences for binary variables (i.e., difference in proportion) should be standardized ("std") or raw ("raw"). Default "raw". Abbreviations allowed. This option can be set globally using <code>set.cobalt.options()</code> .
<code>s.d.denom</code>	character; how the denominator for standardized mean differences should be calculated, if requested. See <code>col_w_smd()</code> for allowable options. If weights are supplied, each set of weights should have a corresponding entry to <code>s.d.denom</code> . If left blank and weights are supplied, <code>bal.tab()</code> will try to determine whether the ATT, ATC, or ATE is being estimated based on the pattern of weights and supply <code>s.d.denom</code> accordingly. Abbreviations allowed. If left blank, <code>bal.tab()</code> will try to use the estimand argument. It is recommended not to set this argument for longitudinal treatments.
<code>thresholds</code>	a named vector of balance thresholds, where the name corresponds to the statistic (i.e., in <code>stats</code> ) that the threshold applies to. For example, to request thresholds on mean differences and variance ratios, one can set <code>thresholds = c(m = .05, v = 2)</code> . Requesting a threshold automatically requests the display of that statistic. See Details.
<code>cluster</code>	either a vector containing cluster membership for each unit or a string containing the name of the cluster membership variable in <code>data</code> . See <code>bal.tab.cluster</code> for details.
<code>imp</code>	either a vector containing imputation indices for each unit or a string containing the name of the imputation index variable in <code>data</code> . See <code>bal.tab.imp</code> for details. Not necessary if <code>data</code> is a <code>mids</code> object.
<code>pairwise</code>	when treatment is multi-category, whether balance should be computed for pairs of treatments or for each treatment against all groups combined. See <code>bal.tab.multi</code> for details.
<code>s.weights</code>	optional; either a vector containing sampling weights for each unit or a string containing the name of the sampling weight variable in <code>data</code> . These function like regular weights except that both the adjusted and unadjusted samples will be weighted according to these weights if weights are used.
<code>estimand</code>	the causal estimand of interest. This value is used to set <code>s.d.denom</code> , and should not be changed from "ATE".
<code>abs</code>	logical; whether displayed balance statistics should be in absolute value or not.
<code>subset</code>	A logical or numeric vector denoting whether each observation should be included or which observations should be included. If logical, it should be the same length as the treatment and covariates. NAs will be treated as FALSE. This can be used as an alternative to <code>cluster</code> to examine balance on subsets of the data.

quick	logical; if TRUE, will not compute any values that will not be displayed. Set to FALSE if computed values not displayed will be used later.
...	For <code>bal.tab.formula.list()</code> , other arguments to be passed to <code>bal.tab.data.frame.list()</code> . Otherwise, further arguments to control display of output. See <a href="#">display options</a> for details.

## Details

`bal.tab.formula.list()` and `bal.tab.data.frame.list()` generate a list of balance summaries for each time point based on the treatments and covariates provided. All data must be in the "wide" format, with exactly one row per unit and columns representing variables at different time points. See the [weightitMSM\(\)](#) documentation for an example of how to transform long data into wide data using [reshape\(\)](#).

All balance statistics are calculated whether they are displayed by print or not, unless `quick = TRUE`. The `threshold` argument controls whether extra columns should be inserted into the Balance table describing whether the balance statistics in question exceeded or were within the threshold. Including these thresholds also creates summary tables tallying the number of variables that exceeded and were within the threshold and displaying the variables with the greatest imbalance on that balance measure.

Multiple sets of weights can be supplied simultaneously by including entering a data frame or a character vector containing the names of weight variables found in `data` or a list thereof. The arguments to `method`, `s.d.denom`, and `estimand`, if any, must be either the same length as the number of sets of weights or of length one, where the sole entry is applied to all sets. When standardized differences are computed for the unadjusted group, they are done using the first entry to `s.d.denom` or `estimand`. When only one set of weights is supplied, the output for the adjusted group will simply be called "Adj", but otherwise will be named after each corresponding set of weights. Specifying multiple sets of weights will also add components to other output of `bal.tab()`.

## Value

An object of class `bal.tab.msm` containing balance summaries at each time point. Each balance summary is its own `bal.tab` object. See [bal.tab.msm](#) for more details.

See [bal.tab\(\) base methods](#) for more detailed information on the value of the `bal.tab` objects produced for each time point.

## Author(s)

Noah Greifer

## See Also

[bal.tab\(\) base methods](#) for details of calculations.

[bal.tab.msm](#) for output and related options. [bal.tab.cluster](#) for more information on clustered data. [bal.tab.imp](#) for more information on multiply imputed data. [bal.tab.multi](#) for more information on multi-category treatments.

## Examples

```

data("iptwExWide", package = "twang")
library("cobalt")

## Estimating longitudinal propensity scores and weights
ps1 <- glm(tx1 ~ age + gender + use0,
           data = iptwExWide,
           family = "binomial")$fitted.values
w1 <- ifelse(iptwExWide$tx1 == 1, 1/ps1, 1/(1-ps1))
ps2 <- glm(tx2 ~ age + gender + use0 + tx1 + use1,
           data = iptwExWide,
           family = "binomial")$fitted.values
w2 <- ifelse(iptwExWide$tx2 == 1, 1/ps2, 1/(1-ps2))
ps3 <- glm(tx3 ~ age + gender + use0 + tx1 + use1 + tx2 + use2,
           data = iptwExWide,
           family = "binomial")$fitted.values
w3 <- ifelse(iptwExWide$tx3 == 1, 1/ps3, 1/(1-ps3))

w <- w1*w2*w3

# Formula interface plus addl.list:
bal.tab(list(tx1 ~ use0 + gender,
            tx2 ~ use0 + gender + use1 + tx1,
            tx3 ~ use0 + gender + use1 + tx1 + use2 + tx2),
        data = iptwExWide,
        weights = w,
        distance.list = list(~ps1, ~ps2, ~ps3),
        addl.list = ~age*gender,
        un = TRUE)

# data frame interface:
bal.tab(list(iptwExWide[c("use0", "gender")],
            iptwExWide[c("use0", "gender", "use1", "tx1")],
            iptwExWide[c("use0", "gender", "use1", "tx1", "use2", "tx2")]),
        treat.list = iptwExWide[c("tx1", "tx2", "tx3")],
        weights = w,
        distance.list = list(~ps1, ~ps2, ~ps3),
        un = TRUE)

```

---

bal.tab.Match

*Balance Statistics for Matching*, optmatch, ebal, and designmatch  
Objects

---

## Description

Generates balance statistics for output objects from **Matching**, **optmatch**, **ebal**, and **designmatch**.

**Usage**

```
## S3 method for class 'Match'
bal.tab(x,
  formula = NULL,
  data = NULL,
  treat = NULL,
  covs = NULL,
  stats,
  int = FALSE,
  poly = 1,
  distance = NULL,
  addl = NULL,
  continuous,
  binary,
  s.d.denom,
  thresholds = NULL,
  weights = NULL,
  cluster = NULL,
  imp = NULL,
  pairwise = TRUE,
  abs = FALSE,
  subset = NULL,
  quick = TRUE,
  ...)

## S3 method for class 'optmatch'
bal.tab(x, ...)

## S3 method for class 'ebalance'
bal.tab(x, ...)

## S3 method for class 'designmatch'
bal.tab(x, ...)
```

**Arguments**

x	either a Match object (the output of a call to Matching::Match() or Matching::Matchby()), an optmatch object (the output of a call to optmatch::pairmatch() or optmatch::fullmatch()), an ebalance object (the output of a call to ebal::ebalance() or ebal::ebalance.trim()), or the output of a call to designmatch::bmatch() or related wrapper functions from the <b>designmatch</b> package.
formula	a formula with the treatment variable as the response and the covariates for which balance is to be assessed as the predictors. All named variables must be in data. See Details.
data	Optional; a data.frame containing variables with the names used in formula, treat, weights, distance, addl, cluster, and/or imp if any. Can also be a mids object, the output of a call to <a href="#">mice()</a> from the <b>mice</b> package, containing

	multiply imputed data sets. In this case, <code>imp</code> is automatically supplied using the imputation variable created from processing the <code>mids</code> object. See Details.
<code>treat</code>	a vector of treatment statuses. See Details.
<code>covs</code>	a data frame of covariate values for which to check balance. See Details.
<code>stats</code>	character; which statistic(s) should be reported. See <a href="#">stats</a> for allowable options. For binary and multi-category treatments, "mean.diffs" (i.e., mean differences) is the default. Multiple options are allowed.
<code>int</code>	logical or numeric; whether or not to include 2-way interactions of covariates included in <code>covs</code> and in <code>add1</code> . If numeric, will be passed to <code>poly</code> as well.
<code>poly</code>	numeric; the highest polynomial of each continuous covariate to display. For example, if 2, squares of each continuous covariate will be displayed (in addition to the covariate itself); if 3, squares and cubes of each continuous covariate will be displayed, etc. If 1, the default, only the base covariate will be displayed. If <code>int</code> is numeric, <code>poly</code> will take on the value of <code>int</code> .
<code>distance</code>	an optional formula or data frame containing distance values (e.g., propensity scores) or a character vector containing their names. If a formula or variable names are specified, <code>bal.tab()</code> will look in the argument to <code>data</code> , if specified.
<code>add1</code>	an optional formula or data frame containing additional covariates for which to present balance or a character vector containing their names. If a formula or variable names are specified, <code>bal.tab()</code> will look in the arguments to <code>covs</code> and <code>data</code> , if specified.
<code>continuous</code>	whether mean differences for continuous variables should be standardized ("std") or raw ("raw"). Default "std". Abbreviations allowed. This option can be set globally using <a href="#">set.cobalt.options()</a> .
<code>binary</code>	whether mean differences for binary variables (i.e., difference in proportion) should be standardized ("std") or raw ("raw"). Default "raw". Abbreviations allowed. This option can be set globally using <a href="#">set.cobalt.options()</a> .
<code>s.d.denom</code>	character; how the denominator for standardized mean differences should be calculated, if requested. See <a href="#">col_w_smd()</a> for allowable options. If not specified, for <code>Match</code> objects, <code>bal.tab()</code> will use "treated" if the estimand of the call to <code>Match()</code> is the ATT, "pooled" if the estimand is the ATE, and "control" if the estimand is the ATC; for <code>optmatch</code> , <code>ebal</code> , and <code>designmatch</code> objects, <code>bal.tab()</code> will determine which value makes the most sense based on the input. Abbreviations allowed.
<code>thresholds</code>	a named vector of balance thresholds, where the name corresponds to the statistic (i.e., in <code>stats</code> ) that the threshold applies to. For example, to request thresholds on mean differences and variance ratios, one can set <code>thresholds = c(m = .05, v = 2)</code> . Requesting a threshold automatically requests the display of that statistic. See Details.
<code>weights</code>	a named list containing additional weights on which to assess balance. Each entry can be a vector of weights, the name of a variable in <code>data</code> that contains weights, or an object with a <a href="#">get.w()</a> method.
<code>cluster</code>	either a vector containing cluster membership for each unit or a string containing the name of the cluster membership variable in <code>data</code> or the CBPS object. See <a href="#">bal.tab.cluster</a> for details.



imp	either a vector containing imputation indices for each unit or a string containing the name of the imputation index variable in data or the original data set used in the call to <code>weightit()</code> . See <code>bal.tab.imp</code> for details. Not necessary if data is a <code>mids</code> object.
pairwise	whether balance should be computed between the treatment groups or for each treatment against all groups combined. See <code>bal.tab.multi</code> for details.
abs	logical; whether displayed balance statistics should be in absolute value or not.
subset	a logical or numeric vector denoting whether each observation should be included or which observations should be included. If logical, it should be the same length as the variables in the original call to the conditioning function. NAs will be treated as FALSE. This can be used as an alternative to <code>cluster</code> to examine balance on subsets of the data.
quick	logical; if TRUE, will not compute any values that will not be displayed. Set to FALSE if computed values not displayed will be used later.
...	for <code>bal.tab.optmatch()</code> , <code>bal.tab.ebalance()</code> , and <code>bal.tab.designmatch()</code> , the same arguments as those passed to <code>bal.tab.Match()</code> . Otherwise, further arguments to control display of output. See <a href="#">display options</a> for details.

## Details

`bal.tab()` generates a list of balance summaries for the object given, and function similarly to `Matching::MatchBalance()` and `designmatch::meantab()`. Note that output objects from **designmatch** do not have their own class; `bal.tab()` first checks whether the object meets the criteria to be treated as a `designmatch` object before dispatching the correct method. Renaming or removing items from the output object can create unintended consequences.

The input to `bal.tab.Match()`, `bal.tab.optmatch()`, `bal.tab.ebalance()`, and `bal.tab.designmatch()` must include either both `formula` and `data` or both `covs` and `treat`. Using the `formula + data` inputs mirrors how `MatchBalance()` is used in **Matching**, and using the `covs + treat` input mirrors how `meantab()` is used in **designmatch**. (Note that to see identical results to `meantab()`, `s.d.denom` must be set to "pooled", though this is not recommended.) For `optmatch` output objects, specifying a treatment is not required.

All balance statistics are calculated whether they are displayed by `print` or not, unless `quick = TRUE`. The `threshold` argument controls whether extra columns should be inserted into the Balance table describing whether the balance statistics in question exceeded or were within the threshold. Including these thresholds also creates summary tables tallying the number of variables that exceeded and were within the threshold and displaying the variables with the greatest imbalance on that balance measure.

The inputs (if any) to `covs` must be a data frame; if more than one variable is included, this is straightforward (i.e., because `data[, c("v1", "v2")]` is already a data frame), but if only one variable is used (e.g., `data[, "v1"]`), R will coerce it to a vector, thus making it unfit for input. To avoid this, simply wrap the input to `covs` in `data.frame()` or use `subset()` if only one variable is to be added. Again, when more than one variable is included, the input is general already a data frame and nothing needs to be done.

**Value**

For point treatments, if clusters and imputations are not specified, an object of class "bal.tab" containing balance summaries for the given object. See [bal.tab\(\)](#) for details.

If clusters are specified, an object of class "bal.tab.cluster" containing balance summaries within each cluster and a summary of balance across clusters. See [bal.tab.cluster](#) for details.

**Author(s)**

Noah Greifer

**See Also**

[bal.tab\(\)](#) for details of calculations.

**Examples**

```
##### Matching #####

library(Matching); data("lalonge", package = "cobalt")

p.score <- glm(treat ~ age + educ + race +
              married + nodegree + re74 + re75,
              data = lalonge, family = "binomial")$fitted.values
Match.out <- Match(Tr = lalonge$treat, X = p.score)

## Using formula and data
bal.tab(Match.out, treat ~ age + educ + race +
        married + nodegree + re74 + re75, data = lalonge)

##### optmatch #####

library("optmatch"); data("lalonge", package = "cobalt")

lalonge$prop.score <- glm(treat ~ age + educ + race +
                        married + nodegree + re74 + re75,
                        data = lalonge, family = binomial)$fitted.values
pm <- pairmatch(treat ~ prop.score, data = lalonge)

## Using formula and data
bal.tab(pm, treat ~ age + educ + race +
        married + nodegree + re74 + re75, data = lalonge,
        distance = "prop.score")

##### ebal #####

library("ebal"); data("lalonge", package = "cobalt")

covariates <- subset(lalonge, select = -c(re78, treat, race))
e.out <- ebalance(lalonge$treat, covariates)
```

```

## Using treat and covs
bal.tab(e.out, treat = lalonde$treat, covs = covariates)

##### designmatch #####

library("designmatch"); data("lalonde", package = "cobalt")

covariates <- as.matrix(lalonde[c("age", "educ", "re74", "re75")])
treat <- lalonde$treat
dmout <- bmatch(treat,
                total_groups = sum(treat == 1),
                mom = list(covs = covariates,
                           tols = absstdif(covariates,
                                             treat, .05))
                )

## Using treat and covs
bal.tab(dmout, treat = treat, covs = covariates)

```

---

bal.tab.matchit

*Balance Statistics for MatchIt Objects*


---

## Description

Generates balance statistics for matchit objects from **MatchIt**.

## Usage

```

## S3 method for class 'matchit'
bal.tab(x,
        method,
        stats,
        int = FALSE,
        poly = 1,
        distance = NULL,
        add1 = NULL,
        data = NULL,
        continuous,
        binary,
        s.d.denom,
        thresholds = NULL,
        weights = NULL,
        cluster = NULL,
        imp = NULL,
        pairwise = TRUE,
        s.weights = NULL,
        abs = FALSE,
        subset = NULL,
        quick = TRUE,
        ...)

```

**Arguments**

x	a matchit object; the output of a call to MatchIt::matchit().
method	a character vector containing the method of adjustment. Ignored unless subclassification was used in the original call to matchit(). If "weighting", the subclassification weights will be used and subclasses will be ignored. If "subclassification", balance will be assessed using the subclasses (see <a href="#">bal.tab.subclass</a> for details). Abbreviations allowed.
stats	character; which statistic(s) should be reported. See <a href="#">stats</a> for allowable options. For binary and multi-category treatments, "mean.diffs" (i.e., mean differences) is the default. Multiple options are allowed.
int	logical or numeric; whether or not to include 2-way interactions of covariates included in covs and in add1. If numeric, will be passed to poly as well.
poly	numeric; the highest polynomial of each continuous covariate to display. For example, if 2, squares of each continuous covariate will be displayed (in addition to the covariate itself); if 3, squares and cubes of each continuous covariate will be displayed, etc. If 1, the default, only the base covariate will be displayed. If int is numeric, poly will take on the value of int.
distance	an optional formula or data frame containing distance values (e.g., propensity scores) or a character vector containing their names. If a formula or variable names are specified, bal.tab() will look in the argument to data, if specified. Note that the distance measure (e.g., propensity score) generated by matchit() is automatically included and named "distance".
add1	an optional formula or data frame containing additional covariates for which to present balance or a character vector containing their names. If a formula or variable names are specified, bal.tab() will look first in the argument to data, if specified, and next in the matchit object.
data	an optional data frame containing variables that might be named in arguments to distance, add1, cluster, and imp. Can also be mids object, the output of a call to mice() from the mice package, containing multiply imputed data sets. In this case, imp is automatically supplied using the imputation variable created from processing the mids object.
continuous	whether mean differences for continuous variables should be standardized ("std") or raw ("raw"). Default "std". Abbreviations allowed. This option can be set globally using <a href="#">set.cobalt.options()</a> . This argument is used to set std in <a href="#">col_w_smd()</a> .
binary	whether mean differences for binary variables (i.e., difference in proportion) should be standardized ("std") or raw ("raw"). Default "raw". Abbreviations allowed. This option can be set globally using <a href="#">set.cobalt.options()</a> . This argument is used to set std in <a href="#">col_w_smd()</a> .
s.d.denom	character; how the denominator for standardized mean differences should be calculated, if requested. See <a href="#">col_w_smd()</a> for allowable options. If not specified, bal.tab() will figure out which one is best based on the estimand of the matchit object: if ATT, "treated"; if ATC, "control", otherwise "pooled". Abbreviations allowed.

thresholds	a named vector of balance thresholds, where the name corresponds to the statistic (i.e., in stats) that the threshold applies to. For example, to request thresholds on mean differences and variance ratios, one can set <code>thresholds = c(m = .05, v = 2)</code> . Requesting a threshold automatically requests the display of that statistic. See Details.
weights	a named list containing additional weights on which to assess balance. Each entry can be a vector of weights, the name of a variable in data that contains weights, or an object with a <code>get.w()</code> method.
cluster	either a vector containing cluster membership for each unit or a string containing the name of the cluster membership variable in data or the <code>matchit</code> object. See <a href="#">bal.tab.cluster</a> for details.
imp	either a vector containing imputation indices for each unit or a string containing the name of the imputation index variable in data or the original data set used in the call to <code>matchit()</code> . See <a href="#">bal.tab.imp</a> for details. Not necessary if data is a <code>mids</code> object.
pairwise	whether balance should be computed between the treatment groups or for each treatment against all groups combined. See <a href="#">bal.tab.multi</a> for details.
s.weights	optional; either a vector containing sampling weights for each unit or a string containing the name of the sampling weight variable in data. These function like regular weights except that both the adjusted and unadjusted samples will be weighted according to these weights if weights are used. If <code>s.weights</code> was supplied in the call to <code>matchit()</code> , they will automatically be included and do not need be specified again (though there is no harm if they are).
abs	logical; whether displayed balance statistics should be in absolute value or not.
subset	a logical or numeric vector denoting whether each observation should be included or which observations should be included. If logical, it should be the same length as the variables in the original call to <code>matchit()</code> . NAs will be treated as FALSE. This can be used as an alternative to <code>cluster</code> to examine balance on subsets of the data.
quick	logical; if TRUE, will not compute any values that will not be displayed. Set to FALSE if computed values not displayed will be used later.
...	further arguments to control display of output. See <a href="#">display options</a> for details.

## Details

`bal.tab.matchit()` generates a list of balance summaries for the `matchit` object given, and functions similarly to `MatchIt::summary.matchit()`. `bal.tab()` behaves differently depending on whether subclasses are used in conditioning or not. If they are used, `bal.tab()` creates balance statistics for each subclass and for the sample in aggregate; see [bal.tab.subclass](#) for more information.

The `threshold` argument controls whether extra columns should be inserted into the Balance table describing whether the balance statistics in question exceeded or were within the threshold. Including these thresholds also creates summary tables tallying the number of variables that exceeded and were within the threshold and displaying the variables with the greatest imbalance on that balance measure. When subclassification is used, the extra threshold columns are placed within the balance tables for each subclass as well as in the aggregate balance table, and the summary tables display balance for each subclass.

**Value**

If subclassification is used and method is set to "subclassification", an object of class "bal.tab.subclass" containing balance summaries within and across subclasses. See [bal.tab.subclass](#) for details.

If matching is used and clusters are not specified, an object of class "bal.tab" containing balance summaries for the matchit object. See [bal.tab\(\)](#) for details.

If clusters are specified, an object of class "bal.tab.cluster" containing balance summaries within each cluster and a summary of balance across clusters. See [bal.tab.cluster](#) for details.

**Author(s)**

Noah Greifer

**See Also**

[bal.tab\(\)](#) for details of calculations.

**Examples**

```
library(MatchIt); data("lalonge", package = "cobalt")

## Nearest Neighbor matching
m.out1 <- matchit(treat ~ age + educ + race +
                 married + nodegree + re74 + re75,
                 data = lalonge, method = "nearest")

bal.tab(m.out1, un = TRUE, m.threshold = .1,
        v.threshold = 2)

## Subclassification
m.out2 <- matchit(treat ~ age + educ + race +
                 married + nodegree + re74 + re75,
                 data = lalonge, method = "subclass")

bal.tab(m.out2, disp.subclass = TRUE)
```

**Description**

Generates balance statistics for mimids and wimids objects from **MatchThem**.

**Usage**

```
## S3 method for class 'mimids'
bal.tab(x,
  stats,
  int = FALSE,
  poly = 1,
  distance = NULL,
  add1 = NULL,
  data = NULL,
  continuous,
  binary,
  s.d.denom,
  thresholds = NULL,
  weights = NULL,
  cluster = NULL,
  pairwise = TRUE,
  abs = FALSE,
  subset = NULL,
  quick = TRUE,
  ...)

## S3 method for class 'wimids'
bal.tab(x,
  stats,
  int = FALSE,
  poly = 1,
  distance = NULL,
  add1 = NULL,
  data = NULL,
  continuous,
  binary,
  s.d.denom,
  thresholds = NULL,
  weights = NULL,
  cluster = NULL,
  pairwise = TRUE,
  abs = FALSE,
  subset = NULL,
  quick = TRUE,
  ...)
```

**Arguments**

x	a mimids or wimids object; the output of a call to MatchThem::matchthem() or MatchThem::weightthem().
stats	character; which statistic(s) should be reported. See <a href="#">stats</a> for allowable options. For binary and multi-category treatments, "mean.diffs" (i.e., mean differences) is the default. For continuous treatments, "correlations" (i.e., treatment-

	covariate Pearson correlations) is the default. Multiple options are allowed.
int	logical or numeric; whether or not to include 2-way interactions of covariates included in covs and in add1. If numeric, will be passed to poly as well.
poly	numeric; the highest polynomial of each continuous covariate to display. For example, if 2, squares of each continuous covariate will be displayed (in addition to the covariate itself); if 3, squares and cubes of each continuous covariate will be displayed, etc. If 1, the default, only the base covariate will be displayed. If int is numeric, poly will take on the value of int.
distance	an optional formula or data frame containing distance values (e.g., propensity scores) or a character vector containing their names. If a formula or variable names are specified, bal.tab() will look in the argument to data, if specified. Note that the distance measure generated by matchthem() or weightthem() is automatically included and named "distance" or "prop.score", respectively.
add1	an optional formula or data frame containing additional covariates for which to present balance or a character vector containing their names. If a formula or variable names are specified, bal.tab() will look first in the argument to data, if specified, and next in the mimids or wimids object.
data	an optional data frame or mids object containing variables that might be named in arguments to distance, add1, and cluster. See Examples.
continuous	whether mean differences for continuous variables should be standardized ("std") or raw ("raw"). Default "std". Abbreviations allowed. This option can be set globally using set.cobalt.options().
binary	whether mean differences for binary variables (i.e., difference in proportion) should be standardized ("std") or raw ("raw"). Default "raw". Abbreviations allowed. This option can be set globally using set.cobalt.options().
s.d.denom	character; how the denominator for standardized mean differences should be calculated, if requested. See col_w_smd() for allowable options. The defaults depend on the options specified in the original function calls; see bal.tab.matchit() and bal.tab.weightit() for details on the defaults. Abbreviations allowed.
thresholds	a named vector of balance thresholds, where the name corresponds to the statistic (i.e., in stats) that the threshold applies to. For example, to request thresholds on mean differences and variance ratios, one can set thresholds = c(m = .05, v = 2). Requesting a threshold automatically requests the display of that statistic. See Details.
weights	a named list containing additional weights on which to assess balance. Each entry can be a vector of weights, the name of a variable in data that contains weights, or an object with a get.w() method.
cluster	either a vector containing cluster membership for each unit or a string containing the name of the cluster membership variable in data or the mimids or wimids object. See bal.tab.cluster for details.
pairwise	whether balance should be computed for pairs of treatments or for each treatment against all groups combined. See bal.tab.multi for details. This can also be used with a binary treatment to assess balance with respect to the full sample.
abs	logical; whether displayed balance statistics should be in absolute value or not.



subset	a logical or numeric vector denoting whether each observation should be included or which observations should be included. If logical, it should be the same length as the variables in the original (unimputed) dataset or the call to <code>matchthem()</code> or <code>weightthem()</code> (i.e., one for each individual or one for each individual for each imputation). NAs will be treated as FALSE. This can be used as an alternative to <code>cluster</code> to examine balance on subsets of the data.
quick	logical; if TRUE, will not compute any values that will not be displayed. Set to FALSE if computed values not displayed will be used later.
...	further arguments to control display of output. See <a href="#">display options</a> for details.

### Details

`bal.tab.mimids()` and `bal.tab.wimids()` generate a list of balance summaries for the `mimids` or `wimids` object given.

The `threshold` argument controls whether extra columns should be inserted into the Balance table describing whether the balance statistics in question exceeded or were within the threshold. Including these thresholds also creates summary tables tallying the number of variables that exceeded and were within the threshold and displaying the variables with the greatest imbalance on that balance measure.

### Value

If clusters are not specified, an object of class `"bal.tab.imp"` containing balance summaries for each imputation and a summary of balance across imputations. See [bal.tab.imp](#) for details.

If clusters are specified, an object of class `"bal.tab.imp.cluster"` containing summaries between and across all clusters and imputations.

### Author(s)

Noah Greifer

### See Also

[bal.tab\(\)](#) for details of calculations.

[bal.tab.matchit\(\)](#) and [bal.tab.weightit\(\)](#)

### Examples

```
library(mice)
library(MatchThem)

data("lalonde_mis", package = "cobalt")

#Imputing the missing data
imp <- mice(lalonde_mis, m = 5)

#Matching using within-imputation propensity scores
mt.out1 <- matchthem(treat ~ age + educ + race +
```

```

        married + nodegree + re74 + re75,
        data = imp, approach = "within")
bal.tab(mt.out1)

#Matching using across-imputation average propensity scores
mt.out2 <- matchthem(treat ~ age + educ + race +
        married + nodegree + re74 + re75,
        data = imp, approach = "across")

bal.tab(mt.out2)

#Weighting using within-imputation propensity scores
wt.out <- weightthem(treat ~ age + educ + race +
        married + nodegree + re74 + re75,
        data = imp, approach = "within",
        estimand = "ATT")

bal.tab(wt.out)

```

---

bal.tab.ps

*Balance Statistics for twang Objects*


---

## Description

Generates balance statistics for ps, mnps, and iptw objects from **twang** and for ps.cont objects from **WeightIt**.

## Usage

```

## S3 method for class 'ps'
bal.tab(x,
  stop.method,
  stats,
  int = FALSE,
  poly = 1,
  distance = NULL,
  add1 = NULL,
  data = NULL,
  continuous,
  binary,
  s.d.denom,
  thresholds = NULL,
  weights = NULL,
  cluster = NULL,
  imp = NULL,
  pairwise = TRUE,
  abs = FALSE,
  subset = NULL,

```

```
        quick = TRUE, ...)  
  
## S3 method for class 'mnp'   
bal.tab(x,  
  stop.method,  
  stats,  
  int = FALSE,  
  poly = 1,  
  distance = NULL,  
  add1 = NULL,  
  data = NULL,  
  continuous,  
  binary,  
  s.d.denom,  
  thresholds = NULL,  
  weights = NULL,  
  cluster = NULL,  
  imp = NULL,  
  pairwise = TRUE,  
  abs = FALSE,  
  subset = NULL,  
  quick = TRUE, ...)  
  
## S3 method for class 'iptw'   
bal.tab(x,  
  stop.method,  
  stats,  
  int = FALSE,  
  poly = 1,  
  distance.list = NULL,  
  add1.list = NULL,  
  data = NULL,  
  continuous,  
  binary,  
  s.d.denom,  
  thresholds = NULL,  
  weights = NULL,  
  cluster = NULL,  
  imp = NULL,  
  pairwise = TRUE,  
  abs = FALSE,  
  subset = NULL,  
  quick = TRUE, ...)  
  
## S3 method for class 'ps.cont'   
bal.tab(x,  
  stop.method,  
  stats,
```

```

int = FALSE,
poly = 1,
distance = NULL,
add1 = NULL,
data = NULL,
continuous,
binary,
s.d.denom,
thresholds = NULL,
weights = NULL,
cluster = NULL,
imp = NULL,
abs = FALSE,
subset = NULL,
quick = TRUE, ...)

```

### Arguments

<code>x</code>	a <code>ps</code> , <code>mnp</code> s, <code>iptw</code> , or <code>ps.cont</code> object; the output of a call to <code>twang::ps()</code> , <code>twang::mnp</code> s(), <code>twang::iptw()</code> or <code>WeightIt::ps.cont()</code> .
<code>stop.method</code>	a string containing the names of the stopping methods used in the original call to <code>ps()</code> , <code>mnp</code> s(), <code>iptw()</code> , or <code>ps.cont()</code> . Examples include "es.max" or "ks.mean" for <code>ps</code> and <code>mnp</code> s objects and "p.mean" or "s.max" for <code>ps.cont</code> objects. <code>bal.tab</code> will assess balance for the weights created by those stopping methods. The names can be abbreviated as long as the abbreviations are specific enough. If no stopping methods are provided, <code>bal.tab</code> will default to displaying balance for all available stopping methods.
<code>stats</code>	character; which statistic(s) should be reported. See <a href="#">stats</a> for allowable options. For binary and multi-category treatments, "mean.diffs" (i.e., mean differences) is the default. For continuous treatments, "correlations" (i.e., treatment-covariate Pearson correlations) is the default. Multiple options are allowed.
<code>int</code>	logical or numeric; whether or not to include 2-way interactions of covariates included in <code>covs</code> and in <code>add1</code> . If numeric, will be passed to <code>poly</code> as well.
<code>poly</code>	numeric; the highest polynomial of each continuous covariate to display. For example, if 2, squares of each continuous covariate will be displayed (in addition to the covariate itself); if 3, squares and cubes of each continuous covariate will be displayed, etc. If 1, the default, only the base covariate will be displayed. If <code>int</code> is numeric, <code>poly</code> will take on the value of <code>int</code> .
<code>distance</code> , <code>distance.list</code>	an optional formula or data frame containing distance values (e.g., propensity scores) or a character vector containing their names. If a formula or variable names are specified, <code>bal.tab()</code> will look in the argument to <code>data</code> , if specified. Note that the propensity scores generated by <code>ps()</code> and <code>iptw()</code> (but not <code>mnp</code> s() or <code>ps.cont()</code> ) are automatically included and named "prop.score.stop.method".
<code>add1</code> , <code>add1.list</code>	an optional formula or data frame containing additional covariates for which to present balance or a character vector containing their names. If a formula

or variable names are specified, `bal.tab()` will look first in the argument to `data`, if specified, and next in the input object. For `iptw` objects, can be a list of additional covariate values as described above, with one list entry per time period.

<code>data</code>	an optional data frame containing variables that might be named in arguments to <code>distance</code> , <code>add1</code> , <code>cluster</code> , and <code>imp</code> . Can also be <code>mids</code> object, the output of a call to <code>mice()</code> from the <b>mice</b> package, containing multiply imputed data sets. In this case, <code>imp</code> is automatically supplied using the imputation variable created from processing the <code>mids</code> object.
<code>continuous</code>	whether mean differences for continuous covariates should be standardized (" <code>std</code> ") or raw (" <code>raw</code> "). Default " <code>std</code> ". Abbreviations allowed. This option can be set globally using <code>set.cobalt.options()</code> . This argument is used to set <code>std</code> in <code>col_w_smd()</code> and <code>col_w_corr</code> .
<code>binary</code>	whether mean differences for binary covariates (i.e., difference in proportion) should be standardized (" <code>std</code> ") or raw (" <code>raw</code> "). Default " <code>raw</code> ". Abbreviations allowed. This option can be set globally using <code>set.cobalt.options()</code> . This argument is used to set <code>std</code> in <code>col_w_smd()</code> and <code>col_w_corr</code> .
<code>s.d.denom</code>	character; how the denominator for standardized mean differences should be calculated, if requested. See <code>col_w_smd()</code> for allowable options. If not specified, for <code>ps</code> objects, <code>bal.tab()</code> will use "treated" if the estimand of the call to <code>ps()</code> is the ATT and "pooled" if the estimand is the ATE; for <code>mnpes</code> objects, <code>bal.tab()</code> will use "treated" if <code>treatATT</code> was specified in the original call to <code>mnpes</code> and "pooled" otherwise. Use "all" to get the same values computed by <code>bal.table</code> in <b>twang</b> . Abbreviations allowed.
<code>thresholds</code>	a named vector of balance thresholds, where the name corresponds to the statistic (i.e., in <code>stats</code> ) that the threshold applies to. For example, to request thresholds on mean differences and variance ratios, one can set <code>thresholds = c(m = .05, v = 2)</code> . Requesting a threshold automatically requests the display of that statistic. See Details.
<code>weights</code>	a named list containing additional weights on which to assess balance. Each entry can be a vector of weights, the name of a variable in <code>data</code> that contains weights, or an object with a <code>get.w()</code> method.
<code>cluster</code>	either a vector containing cluster membership for each unit or a string containing the name of the cluster membership variable in <code>data</code> or the <code>ps</code> , <code>mnpes</code> , <code>iptw</code> , or <code>ps.cont</code> object. See <code>bal.tab.cluster</code> for details.
<code>imp</code>	either a vector containing imputation indices for each unit or a string containing the name of the imputation index variable in <code>data</code> or the original data set used in the call to <code>ps()</code> , <code>mnpes()</code> , <code>iptw()</code> , or <code>ps.cont()</code> . See <code>bal.tab.imp</code> for details. Not necessary if <code>data</code> is a <code>mids</code> object.
<code>pairwise</code>	whether balance should be computed for pairs of treatments or for each treatment against all groups combined. See <code>bal.tab.multi</code> for details. This can also be used with a binary treatment to assess balance with respect to the full sample.
<code>abs</code>	logical; whether displayed balance statistics should be in absolute value or not.
<code>subset</code>	a logical or numeric vector denoting whether each observation should be included or which observations should be included. If logical, it should be the

	same length as the variables in the original call to <code>ps()</code> , <code>mmps()</code> , or <code>ps.cont()</code> . NAs will be treated as FALSE. This can be used as an alternative to <code>cluster</code> to examine balance on subsets of the data.
<code>quick</code>	logical; if TRUE, will not compute any values that will not be displayed. Set to FALSE if computed values not displayed will be used later.
<code>...</code>	further arguments to control display of output. See <a href="#">display options</a> for details.

## Details

`bal.tab.ps()` generates a list of balance summaries for the `ps` object given, and functions similarly to `twang::bal.table()`.

The `threshold` argument controls whether extra columns should be inserted into the Balance table describing whether the balance statistics in question exceeded or were within the threshold. Including these thresholds also creates summary tables tallying the number of variables that exceeded and were within the threshold and displaying the variables with the greatest imbalance on that balance measure.

## Value

For binary point treatments, if clusters are not specified, an object of class `"bal.tab"` containing balance summaries for the `ps` object. See [bal.tab\(\)](#) for details.

If clusters are specified, an object of class `"bal.tab.cluster"` containing balance summaries within each cluster and a summary of balance across clusters. See [bal.tab.cluster](#) for details.

If `mmps()` is used with multi-category treatments, an object of class `"bal.tab.multi"` containing balance summaries for each pairwise treatment comparison and a summary of balance across pairwise comparisons. See [bal.tab.multi](#) for details.

## Note

The function `bal.table` in **twang** performs a similar function. The variances used in the denominator of the standardized mean difference are weighted and computed using `survey::svyvar()` in **twang** and are unweighted here (except when `s.weights` are specified, in which case `col_w_sd` is used). **twang** also uses "all" as the default `s.d.denom` when the estimand is the ATE; the default here is "pooled". For this reason, results may differ slightly between the two packages.

## Author(s)

Noah Greifer

## See Also

[bal.tab\(\)](#) for details of calculations.

[bal.tab.cluster](#) for more information on clustered data.

[bal.tab.multi](#) for more information on multi-category treatments.

[bal.tab.msm](#) for more information on longitudinal treatments.

## Examples

```
library(twang); data("lalonge", package = "cobalt")

## Using ps() for generalized boosted modeling
ps.out <- ps(treat ~ age + educ + married + race +
            nodegree + re74 + re75, data = lalonge,
            stop.method = c("ks.mean", "es.mean"),
            estimand = "ATT", verbose = FALSE)

bal.tab(ps.out, stop.method = "ks.mean", un = TRUE,
        m.threshold = .1, disp.ks = TRUE)
```

---

bal.tab.sbw

*Balance Statistics for sbw Objects*

---

## Description

Generates balance statistics for sbwcau objects from **sbw**.

## Usage

```
## S3 method for class 'sbwcau'
bal.tab(x,
        stats,
        int = FALSE,
        poly = 1,
        distance = NULL,
        add1 = NULL,
        data = NULL,
        continuous,
        binary,
        s.d.denom,
        thresholds = NULL,
        weights = NULL,
        cluster = NULL,
        imp = NULL,
        pairwise = TRUE,
        abs = FALSE,
        subset = NULL,
        quick = TRUE,
        ...)
```

## Arguments

x an sbwcau object; the output of a call to `sbw : sbw()`.

stats	character; which statistic(s) should be reported. See <a href="#">stats</a> for allowable options. For binary treatments, "mean.diffs" (i.e., mean differences) is the default. Multiple options are allowed.
int	logical or numeric; whether or not to include 2-way interactions of covariates included in covs and in add1. If numeric, will be passed to poly as well.
poly	numeric; the highest polynomial of each continuous covariate to display. For example, if 2, squares of each continuous covariate will be displayed (in addition to the covariate itself); if 3, squares and cubes of each continuous covariate will be displayed, etc. If 1, the default, only the base covariate will be displayed. If int is numeric, poly will take on the value of int.
distance	an optional formula or data frame containing distance values (e.g., propensity scores) or a character vector containing their names. If a formula or variable names are specified, bal.tab() will look in the argument to data, if specified.
add1	an optional formula or data frame containing distance values (e.g., propensity scores) or a character vector containing their names. If a formula or variable names are specified, bal.tab() will look first in the argument to data, if specified, and next in the sbwcau object.
data	an optional data frame containing variables that might be named in arguments to distance, add1, cluster, and imp. Can also be mids object, the output of a call to <a href="#">mice()</a> from the <b>mice</b> package, containing multiply imputed data sets. In this case, imp is automatically supplied using the imputation variable created from processing the mids object.
continuous	whether mean differences for continuous variables should be standardized ("std") or raw ("raw"). Default "std". Abbreviations allowed. This option can be set globally using <a href="#">set.cobalt.options()</a> . This argument is used to set std in <a href="#">col_w_smd()</a> .
binary	whether mean differences for binary variables (i.e., difference in proportion) should be standardized ("std") or raw ("raw"). Default "raw". Abbreviations allowed. This option can be set globally using <a href="#">set.cobalt.options()</a> . This argument is used to set std in <a href="#">col_w_smd()</a> .
s.d.denom	character; how the denominator for standardized mean differences should be calculated, if requested. See <a href="#">col_w_smd()</a> for allowable options. If not specified, bal.tab() will figure out which one is best based on the par component of the sbwcau object: if "att", "treated"; if "atc", "control"; otherwise "pooled". Abbreviations allowed.
thresholds	a named vector of balance thresholds, where the name corresponds to the statistic (i.e., in stats) that the threshold applies to. For example, to request thresholds on mean differences and variance ratios, one can set thresholds = c(m = .05, v = 2). Requesting a threshold automatically requests the display of that statistic. See Details.
weights	a named list containing additional weights on which to assess balance. Each entry can be a vector of weights, the name of a variable in data that contains weights, or an object with a <a href="#">get.w()</a> method.
cluster	either a vector containing cluster membership for each unit or a string containing the name of the cluster membership variable in data or the sbwcau object. See <a href="#">bal.tab.cluster</a> for details.



imp	either a vector containing imputation indices for each unit or a string containing the name of the imputation index variable in data or the original data set used in the call to sbw(). See <a href="#">bal.tab.imp</a> for details. Not necessary if data is a mids object.
pairwise	whether balance should be computed between the treatment groups or for each treatment against all groups combined. See <a href="#">bal.tab.multi</a> for details.
abs	logical; whether displayed balance statistics should be in absolute value or not.
subset	a logical or numeric vector denoting whether each observation should be included or which observations should be included. If logical, it should be the same length as the variables in the original call to sbw(). NAs will be treated as FALSE. This can be used as an alternative to cluster to examine balance on subsets of the data.
quick	logical; if TRUE, will not compute any values that will not be displayed. Set to FALSE if computed values not displayed will be used later.
...	further arguments to control display of output. See <a href="#">display options</a> for details.

### Details

bal.tab.sbwcau() generates a list of balance summaries for the sbwcau object given, and functions similarly to sbw::summarize().

The thresholds argument controls whether extra columns should be inserted into the Balance table describing whether the balance statistics in question exceeded or were within the threshold. Including these thresholds also creates summary tables tallying the number of variables that exceeded and were within the threshold and displaying the variables with the greatest imbalance on that balance measure.

### Value

If clusters are not specified, an object of class "bal.tab" containing balance summaries for the sbwcau object. See [bal.tab\(\)](#) for details.

If clusters are specified, an object of class "bal.tab.cluster" containing balance summaries within each cluster and a summary of balance across clusters. See [bal.tab.cluster](#) for details.

### Author(s)

Noah Greifer

### See Also

[bal.tab\(\)](#) for details of calculations.

### Examples

```
## Not run: \dontshow{if (requireNamespace("sbw", quietly = TRUE)) {}
library(sbw); data("lalonde", package = "cobalt")

## Stable balancing weights for the ATT
sbw.out <- sbw(splitfactor(lalonde, drop.first = "if2"),
```

```

        ind = "treat",
        bal = list(bal_cov = c("age", "educ", "race_black",
                              "race_hispan", "race_white",
                              "married", "nodegree",
                              "re74", "re75"),
                  bal_alg = FALSE,
                  bal_tol = .001),
        par = list(par_est = "att"))

bal.tab(sbw.out, un = TRUE, poly = 2)
\dontshow{}}
## End(Not run)

```

---

bal.tab.weightit      *Balance Statistics for WeightIt Objects*

---

### Description

Generates balance statistics for weightit and weightitMSM objects from **WeightIt**.

### Usage

```

## S3 method for class 'weightit'
bal.tab(x,
        stats,
        int = FALSE,
        poly = 1,
        distance = NULL,
        add1 = NULL,
        data = NULL,
        continuous,
        binary,
        s.d.denom,
        thresholds = NULL,
        weights = NULL,
        cluster = NULL,
        imp = NULL,
        pairwise = TRUE,
        abs = FALSE,
        subset = NULL,
        quick = TRUE,
        ...)

## S3 method for class 'weightitMSM'
bal.tab(x,
        stats,
        int = FALSE,
        poly = 1,

```

```

distance.list = NULL,
addl.list = NULL,
data = NULL,
continuous,
binary,
s.d.denom,
thresholds = NULL,
weights = NULL,
cluster = NULL,
imp = NULL,
pairwise = TRUE,
abs = FALSE,
subset = NULL,
quick = TRUE,
...)
```

### Arguments

- x** a `weightit` or `weightitMSM` object; the output of a call to `WeightIt::weightit()` or `WeightIt::weightitMSM()`.
- stats** character; which statistic(s) should be reported. See [stats](#) for allowable options. For binary and multi-category treatments, "mean.diffs" (i.e., mean differences) is the default. For continuous treatments, "correlations" (i.e., treatment-covariate Pearson correlations) is the default. Multiple options are allowed.
- int** logical or numeric; whether or not to include 2-way interactions of covariates included in `covs` and in `addl`. If numeric, will be passed to `poly` as well.
- poly** numeric; the highest polynomial of each continuous covariate to display. For example, if 2, squares of each continuous covariate will be displayed (in addition to the covariate itself); if 3, squares and cubes of each continuous covariate will be displayed, etc. If 1, the default, only the base covariate will be displayed. If `int` is numeric, `poly` will take on the value of `int`.
- distance, distance.list**  
an optional formula or data frame containing distance values (e.g., propensity scores) or a character vector containing their names. If a formula or variable names are specified, `bal.tab()` will look first in the argument to `data`, if specified, and next in the `weightit` or `weightitMSM` object. Note that propensity scores generated by `weightit()` and `weightitMSM()` are automatically included and named "prop.score". For `weightitMSM` objects, can be a list of distance values as described above, with one list entry per time period.
- addl, addl.list**  
an optional formula or data frame containing additional covariates for which to present balance or a character vector containing their names. If a formula or variable names are specified, `bal.tab()` will look first in the argument to `data`, if specified, and next in the `weightit` or `weightitMSM` object. For `weightitMSM` objects, can be a list of additional covariate values as described above, with one list entry per time period.

data	an optional data frame containing variables that might be named in arguments to <code>distance</code> , <code>add1</code> , <code>cluster</code> , and <code>imp</code> . Can also be <code>mids</code> object, the output of a call to <code>mice()</code> from the <code>mice</code> package, containing multiply imputed data sets. In this case, <code>imp</code> is automatically supplied using the imputation variable created from processing the <code>mids</code> object.
continuous	whether mean differences for continuous variables should be standardized ("std") or raw ("raw"). Default "std". Abbreviations allowed. This option can be set globally using <code>set.cobalt.options()</code> . This argument is used to set <code>std</code> in <code>col_w_smd()</code> and <code>col_w_cov()</code> .
binary	whether mean differences for binary variables (i.e., difference in proportion) should be standardized ("std") or raw ("raw"). Default "raw". Abbreviations allowed. This option can be set globally using <code>set.cobalt.options()</code> . This argument is used to set <code>std</code> in <code>col_w_smd()</code> and <code>col_w_cov()</code> .
s.d.denom	character; how the denominator for standardized mean differences should be calculated, if requested. See <code>col_w_smd()</code> for allowable options. Can also be the name of the treatment group or "focal" if <code>focal</code> is specified in the original call to <code>weightit</code> . If not specified, <code>bal.tab()</code> will figure out which one is best based on the estimand of the <code>weightit</code> object: if ATT, "treated"; if ATC, "control"; otherwise "pooled". Abbreviations allowed.
thresholds	a named vector of balance thresholds, where the name corresponds to the statistic (i.e., in <code>stats</code> ) that the threshold applies to. For example, to request thresholds on mean differences and variance ratios, one can set <code>thresholds = c(m = .05, v = 2)</code> . Requesting a threshold automatically requests the display of that statistic. See Details.
weights	a named list containing additional weights on which to assess balance. Each entry can be a vector of weights, the name of a variable in <code>data</code> that contains weights, or an object with a <code>get.w()</code> method.
cluster	either a vector containing cluster membership for each unit or a string containing the name of the cluster membership variable in <code>data</code> or the <code>weightit</code> object. See <code>bal.tab.cluster</code> for details.
imp	either a vector containing imputation indices for each unit or a string containing the name of the imputation index variable in <code>data</code> or the original data set used in the call to <code>weightit()</code> . See <code>bal.tab.imp</code> for details. Not necessary if <code>data</code> is a <code>mids</code> object.
pairwise	whether balance should be computed for pairs of treatments or for each treatment against all groups combined. See <code>bal.tab.multi</code> for details. This can also be used with a binary treatment to assess balance with respect to the full sample.
abs	logical; whether displayed balance statistics should be in absolute value or not.
subset	a logical or numeric vector denoting whether each observation should be included or which observations should be included. If logical, it should be the same length as the variables in the original call to <code>weightit()</code> or <code>weightitMSM()</code> . NAs will be treated as FALSE. This can be used as an alternative to <code>cluster</code> to examine balance on subsets of the data.
quick	logical; if TRUE, will not compute any values that will not be displayed. Set to FALSE if computed values not displayed will be used later.

... further arguments to control display of output. See [display options](#) for details.

## Details

`bal.tab.weightit()` generates a list of balance summaries for the `weightit` object given.

The `threshold` argument controls whether extra columns should be inserted into the Balance table describing whether the balance statistics in question exceeded or were within the threshold. Including these thresholds also creates summary tables tallying the number of variables that exceeded and were within the threshold and displaying the variables with the greatest imbalance on that balance measure.

## Value

For point treatments, if clusters and imputations are not specified, an object of class `"bal.tab"` containing balance summaries for the `weightit` object. See [bal.tab\(\)](#) for details.

If imputations are specified, an object of class `"bal.tab.imp"` containing balance summaries for each imputation and a summary of balance across imputations. See [bal.tab.imp](#) for details.

If `weightit()` is used with multi-category treatments, an object of class `"bal.tab.multi"` containing balance summaries for each pairwise treatment comparison. See [bal.tab.multi](#) for details.

If `weightitMSM()` is used for longitudinal treatments, an object of class `"bal.tab.msm"` containing balance summaries for each time period. See [bal.tab.msm](#) for details.

If clusters are specified, an object of class `"bal.tab.cluster"` containing balance summaries within each cluster and a summary of balance across clusters. See [bal.tab.cluster](#) for details.

## Author(s)

Noah Greifer

## See Also

[bal.tab\(\)](#) for details of calculations.

## Examples

```
library(WeightIt)
data("lalonde", package = "cobalt")

## Basic propensity score weighting
w.out1 <- weightit(treat ~ age + educ + race +
                  married + nodegree + re74 + re75,
                  data = lalonde, method = "ps")
bal.tab(w.out1, un = TRUE, m.threshold = .1,
        v.threshold = 2)

## Weighting with a multi-category treatment
w.out2 <- weightit(race ~ age + educ + married +
                  nodegree + re74 + re75,
                  data = lalonde, method = "ps",
```

```

      estimand = "ATE", use.mlogit = FALSE)
bal.tab(w.out2, un = TRUE)

## IPW for longitudinal treatments
data("iptwExWide", package = "twang")
wmsm.out <- weightitMSM(list(tx1 ~ use0 + gender,
                           tx2 ~ use0 + gender + use1 + tx1,
                           tx3 ~ use0 + gender + use1 + tx1 + use2 + tx2),
                       data = iptwExWide,
                       stabilize = TRUE)

bal.tab(wmsm.out)

```

---

Balance Statistics      *Balance Statistics in bal.tab and love.plot*

---

## Description

`bal.tab()` and `love.plot()` display balance statistics for the included covariates. The `stats` argument in each of these functions controls which balance statistics are to be displayed. The argument to `stats` should be a character vector with the names of the desired balance statistics. This page describes all of the available balance statistics and how to request them. Abbreviations are allowed, so you can use the first few letters of each balance statistics to request it instead of typing out its whole name. That convention is used throughout the documentation. For example, to request mean differences and variance ratios in `bal.tab()` or `love.plot()`, you could include `stats = c("m", "v")`. In addition, the `thresholds` argument uses the same naming conventions and can be used to request balance thresholds on each statistic. For example, to request a balance threshold of .1 for mean differences, you could include `thresholds = c(m = .1)`.

Below, each allowable entry to `stats` and `thresholds` are described, along with other details or option that accompany them.

### Binary/Multi-Category Treatments:

"`mean.diffs`" Mean differences as computed by `col_w_smd()`. Can be abbreviated as "m". Setting the arguments `continuous` and `binary` to either "std" or "raw" will determine whether standardized mean differences or raw mean differences are calculated for continuous and categorical variables, respectively. When standardized mean differences are requested, the `s.d.denom` argument controls how the standardization occurs. When `abs = TRUE`, negative values become positive. Mean differences are requested by default when no entry to `stats` is provided.

"`variance.ratios`" Variance ratios as computed by `col_w_vr()`. Can be abbreviated as "v". Will not be computed for binary variables. When `abs = TRUE`, values less than 1 will have their inverse taken. When used with `love.plot`, the x-axis scaled will be logged so that, e.g., .5 is as far away from 1 as 2 is.

"`ks.statistics`" Kolmogorov-Smirnov (KS) statistics as computed by `col_w_ks()`.

"`ovl.coefficients`" Overlapping (OVL) statistics as computed by `col_w_ovl()`. Can be abbreviated as "ovl". Additional arguments passed to `col_w_ovl()`, such as `integrate` or `bw`, can be supplied to `bal.tab()` or `love.plot()`.

**Continuous Treatments:**

"correlations" Pearson correlations as computed by `col_w_cov()`. Can be abbreviated as "cor". Setting the arguments `continuous` and `binary` to either "std" or "raw" will determine whether correlations or covariances are calculated for continuous and categorical variables, respectively (they are both "std" by default). When correlations are requested, the `s.d.denom` argument controls how the standardization occurs. When `abs = TRUE`, negative values become positive. Pearson correlations are requested by default when no entry to `stats` is provided.

"spearman.correlations" Spearman correlations as computed by `col_w_cov()`. Can be abbreviated as "sp". All arguments are the same as those for "correlations". When `abs = TRUE`, negative values become positive.

"mean.diffs.target" Mean differences computed between the weighted and unweighted sample to ensure the weighted sample is representative of the original population. Can be abbreviated as "m". Setting the arguments `continuous` and `binary` to either "std" or "raw" will determine whether standardized mean differences or raw mean differences are calculated for continuous and categorical variables, respectively. The standardization factor will be computed in the unweighted sample. When `abs = TRUE`, negative values become positive. This statistic is only computed for the adjusted samples.

"ks.statistics.target" KS-statistics computed between the weighted and unweighted sample to ensure the weighted sample is representative of the original population. Can be abbreviated as "ks". This statistic is only computed for the adjusted samples.

If a statistic is requested in thresholds, it will automatically be placed in `stats`. For example, `bal.tab(..., stats = "m", thresholds = c(v = 2))` will display both mean differences and variance ratios, and the variance ratios will have a balance threshold set to 2.

**Examples**

```
data(lalonde)

#Binary treatments
bal.tab(treat ~ age + educ + married + re74, data = lalonde,
        stats = c("m", "v", "ks"))
love.plot(treat ~ age + educ + married + re74, data = lalonde,
          stats = c("m", "v", "ks"), binary = "std",
          thresholds = c(m = .1, v = 2))

#Continuous treatments
bal.tab(re75 ~ age + educ + married + re74, data = lalonde,
        stats = c("cor", "sp"))
love.plot(re75 ~ age + educ + married + re74, data = lalonde,
          thresholds = c(cor = .1, sp = .1))
```

## Description

These functions quickly compute balance statistics for the given covariates. These functions are used in `bal.tab()`, but they are available for use in programming without having to call `bal.tab()` to get them.

- `col_w_mean` computes the (weighted) means for a set of covariates and weights and is essentially a weighted version of `colMeans`.
- `col_w_sd` computes the (weighted) standard deviations for a set of covariates and weights.
- `col_w_smd` computes the (weighted) (absolute) (standardized) difference in means for a set of covariates, a binary treatment, and weights.
- `col_w_vr` computes the (weighted) variance ratio for a set of covariates, a binary treatment, and weights.
- `col_w_ks` computes the (weighted) Kolmogorov-Smirnov (KS) statistic for a set of covariates, a binary treatment, and weights.
- `col_w_ovl` computes the complement of the (weighted) overlapping coefficient for a set of covariates, a binary treatment, and weights (based on Franklin et al, 2014).
- `col_w_cov` and `col_w_corr` compute the (weighted) (absolute) treatment-covariate covariance or correlation for a set of covariates, a continuous treatment, and weights.

## Usage

```
col_w_mean(mat, weights = NULL, s.weights = NULL,
           subset = NULL, na.rm = TRUE, ...)
```

```
col_w_sd(mat, weights = NULL, s.weights = NULL,
         bin.vars, subset = NULL, na.rm = TRUE, ...)
```

```
col_w_smd(mat, treat, weights = NULL, std = TRUE,
          s.d.denom = "pooled", abs = FALSE,
          s.weights = NULL, bin.vars,
          subset = NULL, weighted.weights = weights,
          na.rm = TRUE, ...)
```

```
col_w_vr(mat, treat, weights = NULL, abs = FALSE,
         s.weights = NULL, bin.vars,
         subset = NULL, na.rm = TRUE, ...)
```

```
col_w_ks(mat, treat, weights = NULL,
         s.weights = NULL, bin.vars,
         subset = NULL, na.rm = TRUE, ...)
```

```
col_w_ovl(mat, treat, weights = NULL,
          s.weights = NULL, bin.vars,
          integrate = FALSE, subset = NULL,
          na.rm = TRUE, ...)
```

```
col_w_cov(mat, treat, weights = NULL, type = "pearson",
```



```
std = FALSE, s.d.denom = "all", abs = FALSE,
s.weights = NULL, bin.vars,
subset = NULL, weighted.weights = weights,
na.rm = TRUE, ...)
```

```
col_w_corr(mat, treat, weights = NULL, type = "pearson",
s.d.denom = "all", abs = FALSE,
s.weights = NULL, bin.vars,
subset = NULL, weighted.weights = weights,
na.rm = TRUE, ...)
```

### Arguments

mat	a numeric matrix or a data frame containing the covariates for which the statistic is to be computed. If a data frame, <code>splitfactor</code> with <code>drop.first = "if2"</code> will be called if any character or factor variables are present. This can slow down the function, so it's generally best to supply a numeric matrix. If a numeric vector is supplied, it will be converted to a 1-column matrix first.
weights	numeric; an optional set of weights used to compute the weighted statistics. If sampling weights are supplied through <code>s.weights</code> , the weights should not incorporate these weights, as <code>weights</code> and <code>s.weights</code> will be multiplied together prior to computing the weighted statistics.
s.weights	numeric; an optional set of sampling weights used to compute the weighted statistics. If weights are supplied through <code>weights</code> , <code>weights</code> and <code>s.weights</code> will be multiplied together prior to computing the weighted statistics. Some functions use <code>s.weights</code> in a particular way; for others, supplying <code>weights</code> and <code>s.weights</code> is equivalent to supplying their product to either <code>weights</code> or <code>s.weights</code> . See Details.
subset	a logical vector with length equal to the number of rows of <code>mat</code> used to subset the data. See Details for notes on its use with <code>col_w_smd</code> , <code>col_w_cov</code> , and <code>col_w_corr</code> .
na.rm	logical; whether NAs should be ignored or not. If FALSE, any variable with any NAs will have its corresponding statistic returned as NA. If TRUE, any variable with any NAs will have its corresponding statistic computed as if the missing value were not there.
treat	a vector of treatment status for each individual. For <code>col_w_smd</code> , <code>col_w_vr</code> , <code>col_w_ks</code> , and <code>col_w_ovl</code> , <code>treat</code> should have exactly two unique values. For <code>col_w_cov</code> and <code>col_w_corr</code> , <code>treat</code> should be a many-valued numeric vector.
std	logical; for <code>col_w_smd</code> , whether the computed mean differences for each variable should be standardized; for <code>col_w_cov</code> , whether treatment-covariate correlations should be computed (TRUE) rather than covariances (FALSE). Can be either length 1, whereby all variables will be standardized or not, or length equal to the number of columns of <code>mat</code> , whereby only variables with a value of TRUE will be standardized. See Details.
s.d.denom	for <code>col_w_smd</code> and <code>col_w_cov</code> when <code>std</code> is TRUE for some variables, and for <code>col_w_corr</code> , how the standardization factor should be computed. For <code>col_w_smd</code> (i.e., when computing standardized mean differences), allowable options include

- "treated" - uses the standard deviation of the variable in the treated group
- "control" - uses the standard deviation of the variable in the control group
- "pooled" - uses the square root of the average of the variances of the variable in the treated and control groups
- "all" - uses the standard deviation of the variable in the full sample
- "weighted" - uses the standard deviation of the variable in the full sample weighted by `weighted.weights`
- "hedges" - uses the small-sample corrected version of Hedge's G described in the WWC Procedures Handbook (see References)
- the name of one of the treatment values - uses the standard deviation of the variable in that treatment group.

For `col_w_cov` and `col_w_corr`, only "all" and "weighted" are allowed. Abbreviations allowed. This can also be supplied as a numeric vector of standard deviations with length equal to the number of columns of `mat`; the values will be used as the standardization factors.

<code>abs</code>	logical; for <code>col_w_smd</code> , <code>col_w_cov</code> , and <code>col_w_corr</code> , whether the returned statistics should be in absolute value (TRUE) or not. For <code>col_w_vr</code> , whether the ratio should always include the larger variance in the numerator, so that the ratio is always greater than or equal to 1. Default is FALSE.
<code>bin.vars</code>	a vector used to denote whether each variable is binary or not. Can be a logical vector with length equal to the number of columns of <code>mat</code> or a vector of numeric indices or character names of the binary variables. If missing (the default), the function will figure out which covariates are binary or not, which can increase computation time. If NULL, it will be assumed no variables are binary. All functions other than <code>col_w_mean</code> treat binary variables different from continuous variables. If a factor or character variable is in <code>mat</code> , all the dummies created will automatically be marked as binary, but it should still receive an entry when <code>bin.vars</code> is supplied as logical.
<code>weighted.weights</code>	for <code>col_w_smd</code> , <code>col_w_cov</code> , and <code>col_w_corr</code> , when <code>std = TRUE</code> and <code>s.d.denom = "weighted"</code> , a vector of weights to be applied to the computation of the denominator standard deviation. If not specified, will use the argument to <code>weights</code> . When <code>s.d.denom</code> is not "weighted", this is ignored. The main purpose of this is to allow <code>weights</code> to be NULL while weighting the denominator standard deviations for assessing balance in the unweighted sample but using the standard deviations of the weighted sample.
<code>type</code>	for <code>col_w_cov</code> and <code>col_w_corr</code> , the type of covariance/correlation to be computed. Allowable options include "pearson" and "spearman". When "spearman" is requested, the covariates and treatment are first turned into ranks using <a href="#">rank</a> with <code>na.last = "keep"</code> .
<code>integrate</code>	logical; for <code>col_w_ovl</code> , whether to use <a href="#">integrate</a> to calculate the area of overlap. If FALSE, a midpoint Riemann sum with 1000 partitions will be used instead. The Riemann sum is a little slower and very slightly imprecise (unnoticeably in most contexts), but the integral can fail sometimes and thus is less stable. The default is to use the Riemann sum.

... for all functions, additional arguments supplied to `splitfactor` when `mat` is a `data.frame`. `data`, `var.name`, `drop.first`, and `drop.level` are ignored; `drop.first` is automatically set to "if2". For `col_w_ovl`, other arguments passed to `density` besides `x` and `weights`. Note that the default value for `bw` when unspecified is "nrd" rather than the default in `density`, which is "nrd0".

## Details

`col_w_mean` computes column weighted means for a matrix of variables. It is similar to `colMeans` but (optionally) incorporates weights. `weights` and `s.weights` are multiplied together prior to being used, and there is no distinction between them. This could be used to compute the weighted means of each covariate in the general population to examine the degree to which a weighting method has left the weighted samples resembling the original population.

`col_w_sd` computes column weighted standard deviations for a matrix of variables. `weights` and `s.weights` are multiplied together prior to being used, and there is no distinction between them. The variance of binary variables is computed as  $p(1 - p)$ , where  $p$  is the (weighted) proportion of 1s, while the variance of continuous variables is computed using the standard formula; the standard deviation is the square root of this variance.

`col_w_smd` computes the mean difference for each covariate between treatment groups defined by `treat`. These mean differences can optionally be weighted, standardized, and/or in absolute value. The standardization factor is computed using the unweighted standard deviation or variance when `s.weights` are absent, and is computed using the `s.weights`-weighted standard deviation or variance when `s.weights` are present, except when `s.d.denom = "weighted"`, in which case the product of `weighted.weights` and `s.weights` (if present) are used to weight the standardization factor. The standardization factor is computed using the whole sample even when `subset` is used. Note that unlike `bal.tab()`, `col_w_smd` requires the user to specify whether each individual variable should be standardized using `std` rather than relying on continuous or binary. The weighted mean difference is computed using the product of `weights` and `s.weights`, if specified. The variance of binary variables is computed as  $p(1 - p)$ , where  $p$  is the (weighted) proportion of 1s, while the variance of continuous variables is computed using the standard formula.

`col_w_vr` computes the variance ratio for each covariate between treatment groups defined by `treat`. When `abs = TRUE`, `pmax(out, 1/out)` is applied to the output so that the ratio is always greater than or equal to 1. For binary variables, the variance is computed as  $p(1 - p)$ , where  $p$  is the (weighted) proportion of 1s, while the variance of continuous variables is computed using the standard formula. Note that in `bal.tab()`, variance ratios are not computed for binary variables, while here, they are (but likely should not be interpreted). `weights` and `s.weights` are multiplied together prior to being used, and there is no distinction between them. Because of how the weighted variance is computed, exactly balanced groups may have variance ratios that differ slightly from 1.

`col_w_ks` computes the KS statistic for each covariate using the method implemented in `twang`. The KS statistics can optionally be weighted. For binary variables, the KS statistic is just the difference in proportions. `weights` and `s.weights` are multiplied together prior to being used, and there is no distinction between them.

`col_w_ovl` computes the complement of the overlapping coefficient as described by Franklin et al. (2014). It does so by computing the density of the covariate in the treated and control groups, then finding the area where those density overlap, and subtracting that number from 1, yielding a value between 0 and 1 where 1 indicates complete imbalance, and 0 indicates perfect balance. `density` is used to model the density in each group. The bandwidth of the covariate in the smaller

treatment group is used for both groups. The area of overlap can be computed using `integrate`, which quickly and accurately computes the integral, or using a midpoint Riemann sum with 1000 partitions, which approximates the area more slowly. A reason to prefer the Riemann sum is that `integrate` can fail for unknown reasons, though Riemann sums will fail with some extreme distributions. When either method fails, the resulting value will be NA. For binary variables, the complement of the overlapping coefficient is just the difference in proportions. `weights` and `s.weights` are multiplied together prior to being used, and there is no distinction between them. The weights are used to compute the weighted density by supplying them to the `weights` argument of `density`.

`col_w_cov` computes the covariance between a continuous treatment and the covariates to assess balance for continuous treatments as recommended in Austin (2019). These covariance can optionally be weighted or in absolute value or can be requested as correlations (i.e., standardized covariances). The correlations are computed as the covariance between the treatment and covariate divided by a standardization factor, which is equal to the square root of the product of the variance of treatment and the variance of the covariate. The standardization factor is computed using the unweighted variances when `s.weights` are absent, and is computed using the sampling weighted variances when `s.weights` are present, except when `s.d.denom = "weighted"`, in which case the product of `weighted.weights` and `s.weights` (if present) are used to weight the standardization factor. For this reason, the computed correlation can be greater than 1 or less than -1. The standardization factor is always computed using the whole sample even when `subset` is used. The covariance is computed using the product of `weights` and `s.weights`, if specified. The variance of binary variables is computed as  $p(1 - p)$ , where  $p$  is the (weighted) proportion of 1s, while the variance of continuous variables is computed using the standard formula.

`col_w_corr` is a wrapper for `col_w_cov` with `std` set to `TRUE`.

### Value

A vector of balance statistics, one for each variable in `mat`. If `mat` has column names, the output will be named as well.

### References

Franklin, J. M., Rassen, J. A., Ackermann, D., Bartels, D. B., & Schneeweiss, S. (2014). Metrics for covariate balance in cohort studies of causal effects. *Statistics in Medicine*, 33(10), 1685–1699. doi: [10.1002/sim.6058](https://doi.org/10.1002/sim.6058)

Austin, P. C. (2019). Assessing covariate balance when using the generalized propensity score with quantitative or continuous exposures. *Statistical Methods in Medical Research*, 28(5), 1365–1377. doi: [10.1177/0962280218756159](https://doi.org/10.1177/0962280218756159)

What Works Clearinghouse. (2020). WWC Procedures Handbook (Version 4.1). Retrieved from <https://ies.ed.gov/ncee/wwc/Handbooks>

### See Also

[bal.tab\(\)](#)

### Examples

```
library(WeightIt); data("lalonge", package = "cobalt")
```

```

treat <- lalonde$treat
covs <- subset(lalonde, select = -c(treat, re78))
covs <- splitfactor(covs, drop.first = "if2")
bin.vars <- c(FALSE, FALSE, TRUE, TRUE, TRUE,
              TRUE, TRUE, FALSE, FALSE)
W <- weightit(treat ~ covs, method = "ps",
              estimand = "ATE")
weights <- W$weights

round(data.frame(
  m0 = col_w_mean(covs, weights = weights, subset = treat == 0),
  sd0 = col_w_sd(covs, weights = weights,
                 bin.vars = bin.vars, subset = treat == 0),
  m1 = col_w_mean(covs, weights = weights, subset = treat == 1),
  sd1 = col_w_sd(covs, weights = weights,
                 bin.vars = bin.vars, subset = treat == 1),
  smd = col_w_smd(covs, treat = treat, weights = weights,
                  std = TRUE, bin.vars = bin.vars),
  vr = col_w_vr(covs, treat = treat, weights = weights,
                bin.vars = bin.vars),
  ks = col_w_ks(covs, treat = treat, weights = weights,
                bin.vars = bin.vars),
  row.names = colnames(covs)
), 4)

# Compare to bal.tab():
bal.tab(covs, treat, weights = weights, disp = c("m", "sd"),
        stats = c("m", "v", "ks"), estimand = "ATE",
        method = "weighting", binary = "std")

```

---

class-bal.tab.cluster *Using bal.tab() with Clustered Data*

---

## Description

When using `bal.tab()` with clustered data, the output will be different from the case with single-level data, and there are some options that are common across all `bal.tab()` methods. This page outlines the outputs and options in this case.

There are two main components of the output of `bal.tab()` with clustered data: the within-cluster balance summaries and the across-cluster balance summary. The within-cluster balance summaries display balance for units within each cluster separately.

The across-cluster balance summary pools information across the within-cluster balance summaries to simplify balance assessment. It provides a combination (e.g., mean or maximum) of each balance statistic for each covariate across all clusters. This allows you to see how bad the worst imbalance is and what balance looks like on average. The balance summary will not be computed if longitudinal treatments, multi-category treatments, or multiply imputed data are used.

## Arguments

There are four arguments for each `bal.tab()` method that can handle clustered data: `cluster`, `which.cluster`, `cluster.summary`, and `cluster.fun`.

A vector of cluster membership. This can be factor, character, or numeric vector. This argument is required to let `bal.tab()` know that the data is clustered. If a data argument is specified, this can also be the name of a variable in data that contains cluster membership.

`which.cluster` This is a display option that does not affect computation. If `.all` (the default), all clusters in `cluster` will be displayed. If `.none`, no clusters will be displayed. Otherwise, can be a vector of cluster names or numerical indices for which to display balance. Indices correspond to the alphabetical order of cluster names (or the order of cluster levels if a factor).

`cluster.summary` This is a display option that does not affect computation. If `TRUE`, the balance summary across clusters will be displayed. The default is `TRUE`, and if `which.cluster` is `.none`, it will automatically be set to `TRUE`.

`cluster.fun` This is a display option that does not affect computation. Can be "min", "mean", or "max" and corresponds to which function is used in the across-cluster summary to combine results across clusters. For example, if `cluster.fun = "mean"` the mean balance statistic across clusters will be displayed. The default when `abs = FALSE` in the `bal.tab()` call is to display all three. The default when `abs = TRUE` in the `bal.tab()` call is to display just the mean and max balance statistic.

## Value

The output is a `bal.tab.cluster` object, which inherits from `bal.tab`. It has the following elements:

`Cluster.Balance`

For each cluster, a regular `bal.tab` object containing a balance table, a sample size summary, and other balance assessment tools, depending on which options are specified.

`Cluster.Summary`

The balance summary across clusters. This will include the combination of each balance statistic for each covariate across all clusters according to the value of `cluster.fun`.

`Observations`

A table of sample sizes or effective sample sizes for each cluster before and after adjustment.

As with other methods, multiple weights can be specified, and values for all weights will appear in all tables.

## See Also

[bal.tab\(\)](#), [bal.tab.data.frame\(\)](#), [print.bal.tab\(\)](#)

---

class-bal.tab.imp      *Using bal.tab() with Multiply Imputed Data*


---

### Description

When using `bal.tab()` with multiply imputed data, the output will be different from the case with a single data set. Multiply imputed data can be used with all `bal.tab()` methods, and the `mimids` and `wimids` methods for **MatchThem** objects automatically incorporate multiply imputed data. This page outlines the outputs and options available with multiply imputed data.

There are two main components of the output of `bal.tab()` with multiply imputed data: the within-imputation balance summaries and the across-imputation balance summary. The within-imputation balance summaries display balance for units within each imputed data set separately. In general, this will not be very useful because interest rarely lies in the qualities of any individual imputed data set.

The across-imputation balance summary pools information across the within-imputation balance summaries to simplify balance assessment. It provides the average, smallest, and largest balance statistic for each covariate across all imputations. This allows you to see how bad the worst imbalance is and what balance looks like on average across the imputations. The summary behaves differently depending on whether `abs` is specified as `TRUE` or `FALSE`. When `abs = TRUE`, the across-imputation balance summary will display the mean absolute balance statistics and the maximum absolute balance statistics. When `abs = FALSE`, the across-imputation balance summary will display the minimum, mean, and maximum of the balance statistic in its original form.

### Arguments

There are four arguments for each `bal.tab()` method that can handle multiply imputed data: `imp`, `which.imp`, `imp.summary`, and `imp.fun`.

A vector of imputation membership. This can be factor, character, or numeric vector. This argument is required to let `bal.tab()` know that the data is multiply imputed unless **MatchThem** objects are used. If a `data` argument is specified, this can also be the name of a variable in `data` that contains imputation membership. If the `data` argument is a `mids` object, the output of a call to `mice()`, `imp` does not need to be specified and will automatically be extracted from the `mids` object.

<code>which.imp</code>	This is a display option that does not affect computation. If <code>.all</code> , all imputations in <code>imp</code> will be displayed. If <code>.none</code> (the default), no imputations will be displayed. Otherwise, can be a vector of imputation indices for which to display balance.
<code>imp.summary</code>	This is a display option that does not affect computation. If <code>TRUE</code> , the balance summary across imputations will be displayed. The default is <code>TRUE</code> , and if <code>which.imp</code> is <code>.none</code> , it will automatically be set to <code>TRUE</code> .
<code>imp.fun</code>	This is a display option that does not affect computation. Can be "min", "mean", or "max" and corresponds to which function is used in the across-imputation summary to combine results across imputations. For example, if <code>imp.fun = "mean"</code> the mean balance statistic across imputations will be displayed. The

default when `abs = FALSE` in the `bal.tab()` call is to display all three. The default when `abs = FALSE` in the `bal.tab()` call is to display just the mean and max balance statistic.

### Value

The output is a `bal.tab.imp` object, which inherits from `bal.tab`. It has the following elements:

#### Imputation.Balance

For each imputation, a regular `bal.tab` object containing a balance table, a sample size summary, and other balance assessment tools, depending on which options are specified.

#### Balance.Across.Imputations

The balance summary across imputations. This will include the combination of each balance statistic for each covariate across all imputations according to the value of `imp.fun`.

#### Observations

A table of sample sizes or effective sample sizes averaged across imputations before and after adjustment.

As with other methods, multiple weights can be specified, and values for all weights will appear in all tables.

### Author(s)

Noah Greifer

### See Also

[bal.tab\(\)](#), [bal.tab.data.frame\(\)](#), [print.bal.tab\(\)](#)

---

class-bal.tab.msm

*Using bal.tab() with Longitudinal Treatments*

---

### Description

When using `bal.tab()` with longitudinal treatments, the output will be different from the case with point treatments, and there are some options that are common across all `bal.tab()` methods for dealing with longitudinal data. This page outlines the outputs and options in this case.

There are two main components of the output of `bal.tab()` with longitudinal treatments: the time-point-specific balance summary and across-time-points balance summary. The time-point-specific balance summaries are standard point treatment balance summaries at each time point.

The across-time-points balance summary is, for each variable, the greatest imbalance across all time-point-specific balance summaries. If the greatest observed imbalance is tolerable, then all other imbalances for that variable will be tolerable too, so focusing on reducing the greatest imbalance is sufficient for reducing imbalance overall. The balance summary will not be computed if multi-category treatments or multiply imputed data are used.



**Arguments**

There are two additional arguments for each `bal.tab()` method that can handle longitudinal treatments: `which.time` and `msm.summary`.

This is a display option that does not affect computation. If `.all` (the default), all time points will be displayed. If `.none`, no time points will be displayed. Otherwise, can be a vector of treatment names or indices for which to display balance.

**`which.time`** This is a display option that does not affect computation. If TRUE, the balance summary across time points will be displayed. The default is TRUE, and if `which.time` is `.none`, it will automatically be set to TRUE.

**Value**

The output is a `bal.tab.msm` object, which inherits from `bal.tab`. It has the following elements:

**Time.Balance** For each time point, a regular `bal.tab` object containing a balance table, a sample size summary, and other balance assessment tools, depending on which options are specified.

**Balance.Across.Times** The balance summary across time points. This will include the maximum balance statistic(s) for each covariate across all time points.

**Observations** A table of sample sizes or effective sample sizes for each time point before and after adjustment.

As with other methods, multiple weights can be specified, and values for all weights will appear in all tables.

**Author(s)**

Noah Greifer

**See Also**

[bal.tab\(\)](#), [bal.tab.list](#), [print.bal.tab\(\)](#)

---

class-bal.tab.multi    *Using bal.tab() with Multi-Category Treatments*

---

**Description**

When using `bal.tab()` with multi-category treatments, the output will be different from the case with binary or continuous treatments, and there are some options that are common across all `bal.tab()` methods. This page outlines the outputs and options in this case.

There are two main components of the output of `bal.tab()` with multi-category treatments: the two-group treatment comparisons and the balance summary. The two-group treatment comparisons

are standard binary treatment comparison either for pairs of groups (e.g., for treatments A, B, and C, "A vs. B", "A vs. C", and "B vs. C") or each group against all the groups (i.e., the entire sample).

The balance summary is, for each variable, the greatest imbalance across all two-group comparisons. So, for variable X1, if "A vs. B" had a standardized mean difference of 0.52, "A vs. C" had a standardized mean difference of .17, and "B vs. C" had a standardized mean difference of .35, the balance summary would have 0.52 for the value of the standardized mean difference for X1. The same goes for other variables and other measures of balance. If the greatest observed imbalance is tolerable, then all other imbalances for that variable will be tolerable too, so focusing on reducing the greatest imbalance is sufficient for reducing imbalance overall. (Note that when `s.d.denom = "pooled"`, i.e., when the estimand is the ATE, the pooled standard deviation in the denominator will be the average of the standard deviations across all treatment groups, not just those used in the pairwise comparison.) The balance summary will not be computed if multiply imputed data are used.

## Arguments

There are four arguments for each `bal.tab()` method that can handle multi-category treatments: `pairwise`, `focal`, `which.treat`, and `multi.summary`.

Whether to compute the two-group comparisons pairwise or not. If `TRUE`, `bal.tab()` will compute comparisons for each pair of treatments. This can be valuable if treatments are to be compared with one another (which is often the case). If `FALSE`, `bal.tab()` will compute balance for each treatment group against all groups combined (i.e., the entire sample). This only makes sense if the ATE is desired. When `focal` is specified, `pairwise` is automatically set to `TRUE`.

### `pairwise`

When one group is to be compared to multiple control groups in an ATT analysis, the group considered "treated" is the focal group. Only comparisons between other groups and the focal group are of interest. By specifying the name or index of the treatment condition considered focal, `bal.tab()` will only compute and display pairwise balance for treatment comparisons that include the focal group. For example, if "A" was to be compared with "B" and "C", "A" would be considered focal, and the comparison between groups "B" and "C" would not be computed. In general it is only a good idea to specify `focal` if and only if the ATT is sought.

### `which.treat`

This is a display option that does not affect computation. When displaying the `bal.tab` output, which treatments should be displayed? If a vector of length 1 is entered, all comparisons involving that treatment group will be displayed. If a vector of length 2 or more is entered, all comparisons involving treatments that both appear in the input will be displayed. For example, inputting "A" will display "A vs. B" and "A vs. C", while entering `c("A", "B")` will only display "A vs. B". `.none` indicates no treatment comparisons will be displayed, and `.all` indicates all treatment comparisons will be displayed. `.none` is the default.

### `multi.summary`

If `TRUE`, the balance summary across all comparisons will be computed and displayed. This includes one row for each covariate with maximum balance statistic across all pairwise comparisons. Note that, if variance ratios or KS statistics are requested in addition to mean differences, the displayed values may not come

from the same pairwise comparisons; that is, the greatest standardized mean difference and the greatest variance ratio may not come from the same comparison. The default is TRUE, and if `which.treat` is `.none`, it will automatically be set to TRUE.

### Value

The output is a `bal.tab.multi` object, which inherits from `bal.tab`. It has the following elements:

- `Pair.Balance` For each pair of treatment groups, a regular `bal.tab` object containing a balance table, a sample size summary, and other balance assessment tools, depending on which options are specified. If `focal` is specified, only the comparisons involving the focal group are computed. If `pairwise` is FALSE, the comparisons will be between each group and the groups combined (labeled "All").
- `Balance.Across.Pairs` The balance summary across two-group comparisons. This will include the greatest (i.e., maximum) absolute balance statistics(s) for each covariate across all comparisons computed. Thresholds can be requested for each balance measure as with binary treatments.
- `Observations` A table of sample sizes or effective sample sizes for each treatment group before and after adjustment.

As with other methods, multiple weights can be specified, and values for all weights will appear in all tables.

### Author(s)

Noah Greifer

### See Also

[bal.tab\(\)](#), [bal.tab.data.frame\(\)](#), [print.bal.tab\(\)](#)

---

class-bal.tab.subclass

*Using bal.tab() with Subclassified Data*

---

### Description

When using `bal.tab()` with subclassified data, i.e., data split into subclasses where balance may hold, the output will be different from the standard, non-subclassified case, and there is an additional option for controlling display. This page outlines the outputs and options in this case.

There are two main components of the output of `bal.tab()` with subclassified data: the balance within subclasses and the balance summary across subclasses. The within-subclass balance displays essentially are standard balance displays for each subclass, except that only "adjusted" values are available, because the subclassification itself is the adjustment.

The balance summary is, for each variable, like a weighted average of the balance statistics across subclasses. This is computed internally by assigning each individual a weight based on their subclass and treatment group membership and then computing weighted balance statistics as usual with these weights. This summary is the same one would get if subclasses were supplied to the `match.strata` argument rather than to `subclass`. Because the means and mean differences are additive, their computed values will be weighted averages of the subclass-specific values, but for other statistics, the computed values will not be.

## Arguments

There are three arguments for `bal.tab()` that relate to subclasses: `subclass`, `which.subclass`, and `subclass.summary`.

For the `data.frame` and `formula` methods of `bal.tab()`, a vector of subclass membership or the name of the variable in `data` containing subclass membership. When using subclassification with a function compatible with **cobalt**, such as `matchit()` in **MatchIt**, this argument can be omitted because the subclass are in the output object.

`which.subclass` This is a display option that does not affect computation. If `.all`, all subclasses in `subclass` will be displayed. If `.none` (the default), no subclasses will be displayed. Otherwise, can be a vector of subclass indices for which to display balance.

`subclass.summary` This is a display option that does not affect computation. If `TRUE`, the balance summary across subclasses will be displayed. The default is `TRUE`, and if `which.subclass` is `.none`, it will automatically be set to `TRUE`.

## Value

The output is a `bal.tab.subclass` object, which inherits from `bal.tab`. It has the following elements:

`Subclass.Balance`  
A list of data frames containing balance information for each covariate in each subclass.

`Balance.Across.Subclass`  
A data frame containing balance statistics for each covariate aggregated across subclasses and for the original sample (i.e., unadjusted). See `bal.tab()` for details on what this includes.

## Author(s)

Noah Greifer

## See Also

`bal.tab()`, `bal.tab.data.frame()`, `print.bal.tab()`

**Description**

Several additional arguments can be passed to `bal.tab()` that control the display of the output; these arguments are documented here.

Not all arguments are applicable to all uses of `bal.tab()`; for example, `which.subclass`, which controls which subclasses are displayed when subclassification is used, won't do anything when subclassification is not used.

Note that when `quick = TRUE` is set in the call to `bal.tab()` (which is the default), setting any of these arguments to `FALSE` can prevent some values from being computed, which can have unintended effects.

**Arguments**

<code>disp.bal.tab</code>	logical; whether to display the table of balance statistics. Default is <code>TRUE</code> , so the balance table is displayed.
<code>imbalanced.only</code>	logical; whether to display only the covariates that failed to meet at least one of balance thresholds. Default is <code>FALSE</code> , so all covariates are displayed.
<code>un</code>	logical; whether to print statistics for the unadjusted sample as well as for the adjusted sample. Default is <code>FALSE</code> , so only the statistics for the adjusted sample are displayed.
<code>disp</code>	character; which distribution summary statistic(s) should be reported. Allowable options include "means" and "sds". Multiple options are allowed. Abbreviations allowed.
<code>stats</code>	character; which statistic(s) should be reported. See <code>stats</code> to see which options are available. Multiple options are allowed. Abbreviations allowed. For binary and multi-category treatments, the default is "mean.diffs" (i.e., [standardized] mean differences), and for continuous treatments, the default is "correlations" (i.e., treatment-covariate Pearson correlations).
<code>factor_sep</code>	character; the string used to separate factor variables from their levels when variable names are printed. Default is "_".
<code>int_sep</code>	character; the string used to separate two variables involved in an interaction when variable names are printed. Default is "*". Older versions of <b>cobalt</b> used "_".
<code>disp.call</code>	logical; whether to display the function call from the original input object, if present. Default is <code>TRUE</code> , so the function call is displayed.
	<b>When subclassification is used</b>
<code>which.subclass</code>	Which subclasses (if any) should be displayed. If <code>.all</code> , all subclasses will be displayed. If <code>.none</code> (the default), no subclasses will be displayed. Otherwise, can be a vector of subclass indices for which to display balance.

<code>subclass.summary</code>	<p>logical; whether to display the balance summary across subclasses. If TRUE, the balance summary across subclasses will be displayed. The default is TRUE, and if <code>which.subclass</code> is <code>.none</code>, it will automatically be set to TRUE.</p> <p><b>When the treatment is multi-category</b></p>
<code>which.treat</code>	<p>For which treatments or treatment combinations balance tables should be displayed. If a vector of length 1 is entered, all comparisons involving that treatment group will be displayed. If a vector of length 2 or more is entered, all comparisons involving treatments that both appear in the input will be displayed. For example, setting <code>which.treat = "A"</code> will display "A vs. B" and "A vs. C", while setting <code>which.treat = c("A", "B")</code> will only display "A vs. B". <code>.none</code> indicates no treatment comparisons will be displayed, and <code>.all</code> indicates all treatment comparisons will be displayed. Default is <code>.none</code>. See <a href="#">bal.tab.multi</a>.</p>
<code>multi.summary</code>	<p>logical; whether to display the balance summary across all treatment pairs. This includes one row for each covariate with maximum balance statistic across all pairwise comparisons. Note that, if variance ratios or KS statistics are requested, the displayed values may not come from the same pairwise comparisons; that is, the greatest standardized mean difference and the greatest variance ratio may not come from the same comparison. Default is TRUE when <code>which.treat</code> is <code>.none</code> and FALSE otherwise. See <a href="#">bal.tab.multi</a>.</p> <p><b>When clusters are present</b></p>
<code>which.cluster</code>	<p>For which clusters balance tables should be displayed. If <code>.all</code>, all clusters in cluster will be displayed. If <code>.none</code>, no clusters will be displayed. Otherwise, can be a vector of cluster names or numerical indices for which to display balance. Indices correspond to the alphabetical order of cluster names (or the order of cluster levels if a factor). Default is <code>.all</code>. See <a href="#">bal.tab.cluster</a>.</p>
<code>cluster.summary</code>	<p>logical; whether to display the balance summary across clusters. Default is TRUE when <code>which.cluster</code> is <code>.none</code> and FALSE otherwise (note the default for <code>which.cluster</code> is <code>.all</code>). See <a href="#">bal.tab.cluster</a>.</p>
<code>cluster.fun</code>	<p>Which function is used in the across-cluster summary to combine results across clusters. Can be "min", "mean", or "max". For example, if <code>cluster.fun = "mean"</code> the mean balance statistic across clusters will be displayed. The default when <code>abs = FALSE</code> in the <code>bal.tab()</code> call is to display all three. The default when <code>abs = TRUE</code> in the <code>bal.tab()</code> call is to display just the mean and max balance statistic. See <a href="#">bal.tab.cluster</a>.</p> <p><b>When multiple imputations are present</b></p>
<code>which.imp</code>	<p>For which imputations balance tables should be displayed. If <code>.all</code>, all imputations in <code>imp</code> will be displayed. If <code>.none</code>, no imputations will be displayed. Otherwise, can be a vector of imputation indices for which to display balance. Default is <code>.none</code>. See <a href="#">bal.tab.imp</a>.</p>
<code>imp.summary</code>	<p>logical; whether to display the balance summary across imputations. Default is TRUE when <code>which.imp</code> is <code>.none</code> and FALSE otherwise. See <a href="#">bal.tab.imp</a>.</p>
<code>imp.fun</code>	<p>Which function is used in the across-imputation summary to combine results across imputations. Can be "min", "mean", or "max". For example, if <code>imp.fun</code></p>

= "mean" the mean balance statistic across imputations will be displayed. The default when `abs = FALSE` in the `bal.tab()` call is to display all three. The default when `abs = TRUE` in the `bal.tab()` call is to display just the mean and max balance statistic. See [bal.tab.imp](#).

#### When the treatment is longitudinal

<code>which.time</code>	For which time points balance tables should be displayed. If <code>.all</code> , all time points will be displayed. If <code>.none</code> , no time points will be displayed. Otherwise, can be a vector of treatment names or indices for which to display balance. Default is <code>.none</code> . See <a href="#">bal.tab.msm</a> .
<code>msm.summary</code>	logical; whether to display the balance summary across time points. Default is TRUE when <code>which.time</code> is <code>.none</code> and FALSE otherwise. See <a href="#">bal.tab.msm</a> .
<i>Deprecated arguments</i>	
The following arguments are deprecated but still work.	
<code>disp.means</code>	logical; whether to print the group means in balance output. Default is FALSE, so means are not displayed. Deprecated; use <code>disp</code> instead.
<code>disp.sds</code>	logical; whether to print the group standard deviations in balance output. Default is FALSE, so standard deviations are not displayed. Deprecated; use <code>disp</code> instead.
<code>disp.diff</code>	logical; whether to display (standardized) mean differences in balance output for binary and multi-category treatments. Default is TRUE, so mean differences are displayed. Deprecated; use <code>stats</code> instead.
<code>disp.v.ratio</code>	logical; whether to display variance ratios in balance output for binary and multi-category treatments. Default is FALSE, so variance ratios are not displayed. Deprecated; use <code>stats</code> instead.
<code>disp.ks</code>	logical; whether to display Kolmogorov-Smirnov (KS) statistics in balance output for binary and multi-category treatments. Default is FALSE, so KS statistics are not displayed. Deprecated; use <code>stats</code> instead.
<code>disp.ovl</code>	logical; whether to display overlapping (OVL) coefficients in balance output for binary and multi-category treatments. Default is FALSE, so OVL coefficients are not displayed. Deprecated; use <code>stats</code> instead.

#### Details

In addition to being able to be specified as arguments, if you find you frequently set a display option to something other than its default, you can set that as a global option (for the present R session) using [set.cobalt.options\(\)](#) and retrieve it using [get.cobalt.options\(\)](#). Note that global options cannot be set for `which.subclass`, `which.cluster`, `which.imp`, `which.treat`, or `which.time`.

#### Note

When calling `bal.tab()` using [do.call\(\)](#), if you are using `.all` or `.none` as inputs to arguments, you need to use [alist\(\)](#) rather than [list\(\)](#) to group the arguments. For example, `do.call(bal.tab, list(., which.cluster = .none))` will produce an error, but `do.call(bal.tab, alist(., which.cluster = .none))` should work correctly.

**See Also**

[bal.tab\(\)](#), [print.bal.tab\(\)](#)

---

f.build

*Convenient Formula Generation*

---

**Description**

f.build() returns a [formula](#) of the form  $y \sim x_1 + x_2 + \dots$  from a data frame input. It can be much quicker to use f.build() than to hand-write the precise formula, which may contain errors. It can be used in place of a formula in, for example, [glm\(\)](#), [matchit\(\)](#), or [bal.tab\(\)](#). It provides similar functionality to [reformulate\(\)](#).

**Usage**

```
f.build(y, rhs)
```

**Arguments**

y	the quoted name of the response (left hand side) variable in the formula. Only one variable is supported. If missing, NULL, or the empty string (""), the formula will have no response variable. If rhs is not supplied, y will replace rhs and y will be set to "".
rhs	a data frame whose variable names will be the terms on the right hand side of the formula, or a character vector whose values will be the terms on the right hand side of the formula. If missing, the argument to y will replace rhs and y will be set to ""; in essence, f.build("x") is the same as f.build("", "x"), both producing $\sim x$ .

**Value**

a formula object.

**See Also**

[reformulate\(\)](#)

**Examples**

```
data(lalonde)
covs <- subset(lalonde, select = -c(treat, re78))
lm(f.build("treat", covs), data = lalonde)
```



---

`get.w`*Extract Weights from Preprocessing Objects*

---

**Description**

Extracts weights from the outputs of preprocessing functions.

**Usage**

```
get.w(x, ...)  
  
## S3 method for class 'matchit'  
get.w(x, ...)  
  
## S3 method for class 'ps'  
get.w(x, stop.method = NULL, estimand, s.weights = FALSE, ...)  
  
## S3 method for class 'mnps'  
get.w(x, stop.method = NULL, s.weights = FALSE, ...)  
  
## S3 method for class 'iptw'  
get.w(x, stop.method = NULL, s.weights = FALSE, ...)  
  
## S3 method for class 'Match'  
get.w(x, ...)  
  
## S3 method for class 'CBPS'  
get.w(x, estimand, ...)  
  
## S3 method for class 'ebalance'  
get.w(x, treat, ...)  
  
## S3 method for class 'optmatch'  
get.w(x, estimand, ...)  
  
## S3 method for class 'cem.match'  
get.w(x, estimand, ...)  
  
## S3 method for class 'weightit'  
get.w(x, s.weights = FALSE, ...)  
  
## S3 method for class 'mimids'  
get.w(x, ...)  
  
## S3 method for class 'wimids'  
get.w(x, ...)
```

```
## S3 method for class 'designmatch'
get.w(x, treat, estimand, ...)
```

```
## S3 method for class 'sbwcau'
get.w(x, ...)
```

## Arguments

<code>x</code>	output from the corresponding preprocessing packages.
<code>stop.method</code>	the name of the stop method used in the original call to <code>ps()</code> or <code>mnp()</code> in <b>twang</b> , e.g., <code>"es.mean"</code> . If empty, will return weights from all stop method available into a data.frame. Abbreviations allowed.
<code>estimand</code>	if weights are computed using the propensity score (i.e., for the <code>ps</code> and <code>CBPS</code> methods), which estimand to use to compute the weights. If <code>"ATE"</code> , weights will be computed as $1/ps$ for the treated group and $1/(1-ps)$ for the control group. If <code>"ATT"</code> , weights will be computed as 1 for the treated group and $ps/(1-ps)$ for the control group. If not specified, <code>get.w()</code> will try to figure out which estimand is desired based on the object.  If weights are computed using subclasses/matching strata (i.e., for the <code>cem</code> and <code>designmatch</code> methods), which estimand to use to compute the weights. First, a subclass propensity score is computed as the proportion of treated units in each subclass, and the one of the formulas above will be used based on the estimand requested. If not specified, <code>"ATT"</code> is assumed.
<code>treat</code>	a vector of treatment status for each unit. This is required for methods that include <code>treat</code> as an argument. The treatment variable that was used in the original preprocessing function call should be used.
<code>s.weights</code>	whether the sampling weights included in the original call to the fitting function should be included in the weights. If <code>TRUE</code> , the returned weights will be the product of the balancing weights estimated by the fitting function and the sampling weights. If <code>FALSE</code> , only the balancing weights will be returned.
<code>...</code>	further arguments passed to or from other methods.

## Details

The output of `get.w()` can be used in calls to the formula and data frame methods of `bal.tab()` (see example below). In this way, the output of multiple preprocessing packages can be viewed simultaneously and compared. The weights can also be used in `weights` statements in regression methods to compute weighted effects.

**twang** has a function called `get.weights()` that performs the same function on `ps` objects but offers slightly finer control. Note that the weights generated by `get.w()` for `ps` objects do not include sampling weights by default.

When sampling weights are used with `CBPS()` in **CBPS**, the returned weights will already have the sampling weights incorporated. To retrieve the balancing weights on their own, divide the returned weights by the original sampling weights. For other packages, the balancing weights are returned separately unless `s.weights = TRUE`, which means they must be multiplied by the sampling weights for effect estimation.

When `Match()` in **Matching** is used with `CommonSupport = TRUE`, the returned weights will be incorrect. This option is not recommended by the package authors.

### Value

A vector or data frame of weights for each unit. These may be matching weights or balancing weights.

### Author(s)

Noah Greifer

### See Also

[get.weights\(\)](#) in **twang**.

### Examples

```
data("lalonge", package = "cobalt")
library("MatchIt"); library("WeightIt")

m.out <- matchit(treat ~ age + educ + race, data = lalonge)

w.out <- weightit(treat ~ age + educ + race, data = lalonge,
                 estimand = "ATT")

bal.tab(treat ~ age + educ + race, data = lalonge,
        weights = data.frame(matched = get.w(m.out),
                             weighted = get.w(w.out)),
        method = c("matching", "weighting"),
        estimand = "ATT")
```

---

lalonge

*Lalonge's National Supported Work Demonstration Data*

---

### Description

One of the datasets used by Dehejia and Wahba in their paper "Causal Effects in Non-Experimental Studies: Reevaluating the Evaluation of Training Programs." Versions of this data set have been used as an example data set in **MatchIt**, **twang**, **Matching**, and **CBPS**. The data set `lalonge_mis` is the same but with some values missing (set to NA).

### Usage

```
data("lalonge")
data("lalonge_mis")
```

**Format**

A data frame with 614 observations on the following 9 variables.

treat 1 if treated in the National Supported Work Demonstration, 0 if from the Current Population Survey  
 age age  
 educ years of education  
 race factor; black, Hispanic (hispan), or white  
 married 1 if married, 0 otherwise  
 nodegree 1 if no degree, 0 otherwise  
 re74 earnings in 1974 (pretreatment)  
 re75 earnings in 1975 (pretreatment)  
 re78 earnings in 1978 (outcome)

**Source**

<https://users.nber.org/~rdehejia/data/.nswdata2.html>

**References**

Lalonde, R. (1986). Evaluating the econometric evaluations of training programs with experimental data. *American Economic Review* 76: 604-620.  
 Dehejia, R.H. and Wahba, S. (1999). Causal Effects in Nonexperimental Studies: Re-Evaluating the Evaluation of Training Programs. *Journal of the American Statistical Association* 94: 1053-1062.

---

love.plot

*Display Balance Statistics in a Love Plot*

---

**Description**

Generates a "Love" plot graphically displaying covariate balance before and after adjusting. Options are available for producing publication-ready plots.

**Usage**

```
love.plot(x,
  stats,
  abs,
  agg.fun = NULL,
  var.order = NULL,
  drop.missing = TRUE,
  drop.distance = FALSE,
  thresholds = NULL,
  line = FALSE,
```

```

stars = "none",
grid = FALSE,
limits = NULL,
colors = NULL,
shapes = NULL,
alpha = 1,
size = 3,
wrap = 30,
var.names = NULL,
title,
sample.names,
labels = FALSE,
position = "right",
themes = NULL,
...)
```

### Arguments

x	the valid input to a call to <code>bal.tab()</code> (e.g., the output of a preprocessing function). Other arguments that would be supplied to <code>bal.tab()</code> can be entered with <code>...</code> . Can also be a <code>bal.tab</code> object, i.e., the output of a call to <code>bal.tab()</code> . See Examples. If <code>x</code> is not a <code>bal.tab</code> object, <code>love.plot()</code> calls <code>bal.tab()</code> with the arguments supplied.
stats	character; which statistic(s) should be reported. See <code>stats</code> for allowable options. For binary and multi-category treatments, "mean.diffs" (i.e., mean differences) is the default. For continuous treatments, "correlations" (i.e., treatment-covariate Pearson correlations) is the default. Multiple options are allowed.
abs	logical; whether to present the statistic in absolute value or not. For variance ratios, this will force all ratios to be greater than or equal to 1. If <code>x</code> is a <code>bal.tab</code> object, <code>love.plot()</code> might ignore <code>abs</code> depending on the original <code>bal.tab()</code> call. If unspecified, uses whatever was used in the call to <code>bal.tab()</code> .
agg.fun	if balance is to be displayed across clusters or imputations rather than within a single cluster or imputation, which summarizing function ("mean", "max", or "range") of the balance statistics should be used. If "range" is entered, <code>love.plot()</code> will display a line from the min to the max with a point at the mean for each covariate. Abbreviations allowed; "range" is default. Remember to set <code>which.&lt;ARG&gt; = .none</code> (where <code>&lt;ARG&gt;</code> is the grouping argument, such as <code>cluster</code> or <code>imp</code> ) to use <code>agg.fun</code> . See Details.
var.order	a character or <code>love.plot</code> object; how to order the variables in the plot. See Details.
drop.missing	logical; whether to drop rows for variables for which the statistic has a value of NA, for example, variance ratios for binary variables. If FALSE, there will be rows for these variables but no points representing their value. Default is TRUE, so that variables with missing balance statistics are absent. When multiple stats are requested, only variables with NAs for all stats will be dropped if <code>drop.missing = TRUE</code> . This argument used to be called <code>no.missing</code> , and that name still works (but has been deprecated).

drop.distance	logical; whether to ignore the distance measure (if there are any) in plotting.
thresholds	numeric; an optional value to be used as a threshold marker in the plot. Should be a named vector where each name corresponds to the statistic for which the threshold is to be applied. See example at <a href="#">stats</a> . If <code>x</code> is a <code>bal.tab</code> object and a threshold was set in it (e.g., with <code>thresholds</code> ), its threshold will be used unless overridden using the <code>threshold</code> argument in <code>love.plot</code> .
line	logical; whether to display a line connecting the points for each sample.
stars	when mean differences are to be displayed, which variable names should have a star (i.e., an asterisk) next to them. Allowable values are "none", "std" (for variables with mean differences that have been standardized), or "raw" (for variables with mean differences that have not been standardized). If "raw", the x-axis title will be "Standardized Mean Differences". Otherwise, it will be "Mean Differences". Ignored when mean difference are not displayed. See Details for an explanation of the purpose of this option.
grid	logical; whether gridlines should be shown on the plot. Default is FALSE.
limits	numeric; the bounds for the x-axis of the plot. Must a (named) list of vectors of length 2 in ascending order, one for each value of <code>stats</code> that is to have limits; e.g., <code>list(m = c(-.2, .2))</code> . If values exceed the limits, they will be plotted at the edge.
colors	the colors of the points on the plot. See 'Color Specification' at <a href="#">par()</a> or the <code>ggplot2</code> <a href="#">aesthetic specifications</a> page. The first value corresponds to the color for the unadjusted sample, and the second color to the adjusted sample. If only one is specified, it will apply to both. Defaults to the default <code>ggplot2</code> colors.
shapes	the shapes of the points on the plot. Must be one or two numbers between 1 and 25 or the name of a valid shape. See the <code>ggplot2</code> <a href="#">aesthetic specifications</a> page for valid options. Values 15 to 25 are recommended. The first value corresponds to the shape for the unadjusted sample, and the second color to the adjusted sample. If only one is specified, it will apply to both. Defaults to 19 ("circle filled").
alpha	numeric; the transparency of the points. See <a href="#">scale_alpha()</a> .
size	numeric; the size of the points on the plot. Defaults to 3. In previous versions, the size was scaled by a factor of 3. Now size corresponds directly to the size aesthetic in <a href="#">geom_point()</a> .
wrap	numeric; the number of characters at which to wrap axis labels to the next line. Defaults to 30. Decrease this if the axis labels are excessively long.
var.names	an optional object providing alternate names for the variables in the plot, which will otherwise be the variable names as they are stored. This may be useful when variables have ugly names. See Details on how to specify <code>var.names</code> . <a href="#">var.names()</a> can be a useful tool for extracting and editing the names from the <code>bal.tab</code> object.
title	character; the title of the plot.
sample.names	character; new names to be given to the samples (i.e., in place of "Unadjusted" and "Adjusted"). For example, when matching it used, it may be useful to enter <code>c("Unmatched", "Matched")</code> .

labels	logical or character; labels to give the plots when multiple stats are requested. If TRUE, the labels will be capital letters. Otherwise, must be a string with the same length as stats. This can be useful when the plots are to be used in an article.
position	the position of the legend. When stats has length 1, this can be any value that would be appropriate as an argument to legend.position in theme(). When stat has length greater than 1, can be one of "none", "left", "right", "bottom", or "top".
themes	an optional list of theme objects to append to each individual plot. Each entry should be the output of a call to theme() in ggplot2. This is a way to customize the individual plots when multiple stats are requested since the final output is not a manipulable ggplot object. It can be used with length-1 stats, but it probably makes more sense to just add the theme() call after love.plot().
...	additional arguments passed to bal.tab() or options for display of the plot. The following related arguments are currently accepted: use.grid whether to use arrangeGrob() in gridExtra to make the plot when stats has length 1. See section Value. disp.subclass whether to display individual subclasses if subclassification is used. Overrides the disp.subclass option in the original bal.tab() call if x is a bal.tab object. star_char character; when stars are used, the character that should be the "star" next to the starred variables. The default is "*". "†" or "\u2020" (i.e., dagger) might be appealing as well. Additionally, any of the which. arguments used with clustered or multiply imputed data or longitudinal or multi-category treatments can be specified to display balance on selected groupings. Set to .none to aggregate across groups (in which agg.fun comes into effect) and set to .all to view all groups. See display_options for options, and see the vignette "Appendix 2: Using cobalt with Clustered, Multiply Imputed, and Other Segmented Data" for details and examples.

## Details

love.plot can be used with clusters, imputations, and multi-category and longitudinal treatments in addition to the standard case. Setting the corresponding which. argument to .none will aggregate across that dimension. When aggregating, an argument should be specified to agg.fun referring to whether the mean, minimum ("min"), or maximum ("max") balance statistic or range ("range", the default) of balance statistics for each covariate should be presented in the plot. See the vignette "Appendix 2: Using cobalt with Clustered, Multiply Imputed, and Other Segmented Data" for examples.

With subclasses, balance will be displayed for the unadjusted sample and the aggregated subclassified sample. If disp.subclass is TRUE, each subclass will be displayed additionally as a number on the plot.

### Variable order using var.order

The order that the variables are presented in depends on the argument to var.order. If NULL, the default, they will be displayed in the same order as in the call to bal.tab(), which is the order of the

underlying data set. If "alphabetical", they will be displayed in alphabetical order. If "unadjusted", they will be ordered by the balance statistic of the unadjusted sample. To order by the values of the adjusted sample, "adjusted" can be supplied if only one set of weights (or subclasses) are specified; otherwise, the name of the set of weights should be specified.

If multiple stats are requested, the order will be determined by the first entry to stats (e.g., if both "mean.diffs" and "ks.statistics" are requested, and `var.order = "unadjusted"`, the variables will be displayed in order of the unadjusted mean differences for both plots). If multiple plots are produced simultaneously (i.e., for individual clusters or imputations), `var.order` can only be NULL or "alphabetical".

If a `love.plot` object is supplied, the plot being drawn will use the variable order in the supplied `love.plot` object. This can be useful when making more than one plot and the variable order should be the same across plots.

#### **Variable names using `var.names`**

The default in `love.plot` is to present variables as they are named in the output of the call to `bal.tab`, so it is important to know this output before specifying alternate variable names when using `var.names`, as the displayed variable names may differ from those in the original data.

There are several ways to specify alternate names for presentation in the displayed plot using the `var.names` argument by specifying a list of old and new variable names, pairing the old name with the new name. You can do this in three ways: 1) use a vector or list of new variable names, with the names of the values the old variable names; 2) use a data frame with exactly one column containing the new variable names and the row names containing the old variable names; or 3) use a data frame with two columns, the first (or the one named "old") containing the old variable names and the second (or the one named "new") containing the new variable names. If a variable in the output from `bal.tab()` is not provided in the list of old variable names, `love.plot()` will use the original old variable name.

`love.plot()` can replace old variables names with new ones based on exact matching for the name strings or matching using the variable name components. For example, if a factor variable "X" with levels "a", "b", and "c" is displayed with `love.plot()`, the variables "X\_a", "X\_b", and "X\_c" will be displayed. You can enter replacement names for all three variables individually with `var.names`, or you can simply specify a replacement name for "X", and "X" will be replaced by the given name in all instances it appears, including not just factor expansions, but also polynomials and interactions in `int = TRUE` in the original `bal.tab()` call. In an interaction with another variable, say "Y", there are several ways to replace the name of the interaction term "X\_a \* Y". If the entire string ("X\_a \* Y") is included in `var.names`, the entire string will be replaced. If "X\_a" is included in `var.names`, only it will be replaced (and it will be replaced everywhere else it appears). If "X" is included in `var.names`, only it will be replaced (and it will be replaced everywhere else it appears). See example at [var.names\(\)](#).

#### **Stars and the x-axis label with mean differences**

When mean differences are to be displayed, `love.plot()` attempts to figure out the appropriate label for the x-axis. If all mean differences are standardized, the x-axis label will be "Standardized Mean Differences". If all mean differences are raw (i.e., unstandardized), the x-axis label will be "Mean Differences". Otherwise, `love.plot()` turns to the `stars` argument. If "raw", the x-axis label will be "Standardized Mean Differences" (i.e., because un-starred variables have standardized mean differences displayed). If "std", the x-axis label will be "Mean Differences" (i.e., because un-starred variables have raw mean differences displayed). If "none", the x-axis label will be "Mean Differences" and a warning will be issued recommending the use of `stars`.



The default is to display standardized mean differences for continuous variables, raw mean differences for binary variables, and no stars, so this warning will be issued in most default uses of `love.plot()`. The purpose of this is to correct behavior of previous versions of **cobalt** in which the default x-axis label was "Mean Differences", even when standardized mean differences were displayed, yielding a potentially misleading plot. This warning requires the user to think about what values are being displayed. The idea of using stars is that the user can, in a caption for the plot, explain that variables with an asterisk have standardized (or raw) mean differences display, in contrast to un-starred variables.

### Value

When only one type of balance statistic is requested, the returned object is a standard `ggplot` object that can be manipulated using **ggplot2** syntax. This facilitates changing fonts, background colors, and features of the legend outside of what `love.plot()` provides automatically.

When more than one type of balance statistic is requested, the plot is constructed using `arrangeGrob()` in `gridExtra`, which arranges multiple plots and their shared legend into one plot. Because the output of `arrangeGrob` is a `gtable` object, its features cannot be manipulated in the standard way. Use the `themes` argument to change theme elements of the component plots. The original plots are stored in the "plots" attribute of the output object.

### Note

`love.plot` can also be called by using `plot()` or `autoplot()` on a `bal.tab` object. If used in this way, some messages may appear twice. It is recommended that you just use `love.plot()` instead.

### Author(s)

Noah Greifer

### See Also

[bal.tab\(\)](#)

### Examples

```
library(WeightIt); data("lalonge", package = "cobalt")

## Propensity score weighting
w.out1 <- weightit(treat ~ age + educ + race +
                  married + nodegree + re74 + re75,
                  data = lalonge)

love.plot(w.out1, thresholds = c(m = .1), var.order = "unadjusted")

## Using alternate variable names
v <- data.frame(old = c("age", "educ", "race_black", "race_hispan",
                       "race_white", "married", "nodegree", "re74",
                       "re75", "distance"),
                new = c("Age", "Years of Education", "Black",
                       "Hispanic", "White", "Married", "No Degree",
```

```

        "Earnings 1974", "Earnings 1975",
        "Propensity Score"))

love.plot(w.out1, stats = "m", threshold = .1,
          var.order = "unadjusted", var.names = v)

#Using multiple stats
love.plot(w.out1, stats = c("m", "ks"),
          thresholds = c(m = .1, ks = .05),
          var.order = "unadjusted", var.names = v, stars = "raw",
          position = "bottom", wrap = 20)

#Changing visual elements
love.plot(w.out1, thresholds = c(m = .1),
          var.order = "unadjusted", var.names = v, abs = TRUE,
          shapes = c("triangle filled", "circle"),
          colors = c("red", "blue"), line = TRUE,
          grid = FALSE, sample.names = c("Original", "Weighted"),
          stars = "raw", position = "top")

```

---

print.bal.tab

*Print Results of a Call to bal.tab()*


---

## Description

Prints `bal.tab()` output in a clean way. Provides options for printing.

## Usage

```

## S3 method for class 'bal.tab'
print(x,
      imbalanced.only,
      un,
      disp.bal.tab,
      disp.call,
      stats,
      disp.thresholds,
      disp,
      which.subclass,
      subclass.summary,
      which.imp,
      imp.summary,
      imp.fun,
      which.treat,
      multi.summary,
      which.time,
      msm.summary,
      which.cluster,

```

```

cluster.summary,
cluster.fun,
digits = max(3, getOption("digits") - 3),
...)
```

## Arguments

x	a <code>bal.tab</code> object; the output of a call to <code>bal.tab()</code> .
imbalanced.only	logical; whether to display only the covariates that failed to meet at least one of balance thresholds. Depends only on whether threshold were initial set in the call to <code>bal.tab()</code> and not on any arguments to <code>print()</code> (except <code>disp.bal.tab</code> ).
un	logical; whether to display balance values for the unadjusted sample. Ignored (and set to TRUE) if no conditioning was performed.
disp.bal.tab	logical; whether to display the table of balance statistics. If FALSE, only other values (e.g., the call, sample sizes, balance tallies, and maximum imbalances) will be presented.
disp.call	logical; whether to display the function call for the input object, if any.
stats	character; which statistic(s) should be reported. For binary or multi-category treatments, the options are "mean.diffs" for mean differences (standardized or not according the selected <code>bal.tab()</code> options), "variance.ratios" for variance ratios, and "ks.statistics" for Kolmogorov-Smirnov statistics. "mean.diffs" is the default. For continuous treatments, the only option is "correlations" for treatment-covariate correlations. Multiple options are allowed. Abbreviations allowed. Statistics that weren't requested in the original call to <code>bal.tab()</code> cannot be requested with <code>print()</code> unless <code>quick = FALSE</code> in the original call.
disp.thresholds	logical; whether to display thresholds for each statistic for which thresholds were originally requested in the call to <code>bal.tab()</code> . Should be a named logical vector with names corresponding to the thresholds. For example, if thresholds for mean differences were requested in <code>bal.tab()</code> , set <code>disp.thresholds = c(m = FALSE)</code> to prevent them from being printed. If a statistic was prevented from being displayed by another argument to <code>print()</code> , the thresholds will not be displayed.
disp	character; which distribution summary statistics to display. Allowable options include "means" and "sds". Statistics that weren't requested in the original call to <code>bal.tab()</code> cannot be requested with <code>print()</code> unless <code>quick = FALSE</code> in the original call.
which.subclass	when used with subclassification, which subclass(es) to display. If NULL, all subclasses will be displayed. If NA, no subclasses will be displayed. Otherwise, can be a vector of subclass indices for which to display balance. To display the subclasses requested in the original call to <code>bal.tab()</code> , omit this argument. See <a href="#">bal.tab.subclass</a> for details.
subclass.summary	logical; when used with subclassification, whether to display the subclass balance summary table. If <code>which.subclass</code> is NA, <code>subclass.summary</code> will be set to TRUE. See <a href="#">bal.tab.subclass</a> for details.

<code>which.imp</code>	when used with multiply imputed data, which imputation(s) to display. If <code>NULL</code> , all imputations will be displayed. If <code>NA</code> , no imputations will be displayed. Otherwise, can be a vector of imputations numbers for which to display balance. To display the imputations requested in the original call to <code>bal.tab()</code> , omit this argument. See <a href="#">bal.tab.imp</a> for details.
<code>imp.summary</code>	logical; when used with multiply imputed data, whether to display the imputation summary table. If <code>which.imp</code> is <code>NA</code> , <code>imp.summary</code> will be set to <code>TRUE</code> . See <a href="#">bal.tab.imp</a> for details.
<code>imp.fun</code>	character; when used with multiply imputed data, a character vector of functions of balance statistics to display when displaying balance across imputations. Can be "mean", "min", or "max". More than one are allowed. See <a href="#">bal.tab.imp</a> for details.
<code>which.treat</code>	when used with multi-category treatments, which treatments to display. See <a href="#">bal.tab.multi</a> for details.
<code>multi.summary</code>	logical; when used with multi-category treatments, whether to display the balance summary table across pairwise comparisons. See <a href="#">bal.tab.multi</a> for details.
<code>which.time</code>	when used with longitudinal treatments, which time periods to display if longitudinal treatments are used. See <a href="#">bal.tab.msm</a> for details.
<code>msm.summary</code>	logical; when used with longitudinal treatments, whether to display the balance summary table across time periods. See <a href="#">bal.tab.msm</a> for details.
<code>which.cluster</code>	when used with clustered data, which cluster(s) to display. If <code>NULL</code> , all clusters will be displayed. If <code>NA</code> , no clusters will be displayed. Otherwise, can be a vector of cluster names or numerical indices for which to display balance. Indices correspond to the alphabetical order of cluster names. To display the clusters requested in the original call to <code>bal.tab()</code> , omit this argument. See <a href="#">bal.tab.cluster</a> for details.
<code>cluster.summary</code>	logical; when used with clustered data, whether to display the cluster summary table. If <code>which.cluster</code> is <code>NA</code> , <code>cluster.summary</code> will be set to <code>TRUE</code> . See <a href="#">bal.tab.cluster</a> for details.
<code>cluster.fun</code>	character; when used with clustered data, a character vector of functions of balance statistics to display when displaying balance across clusters. Can be "mean", "min", or "max". More than one are allowed. See <a href="#">bal.tab.cluster</a> for details.
<code>digits</code>	the number of digits to display.
<code>...</code>	further arguments passed to or from other methods.

### Details

Simply calling `bal.tab()` will print its results, but it can be useful to store the results into an object and print them again later, possibly with different print options specified. The `print()` function automatically dispatches the correct method for the `bal.tab` object given.

Any parameter used in `bal.tab()` for calculations, such as `int`, `add1`, or `distance`, cannot be used with `print()`; only those parameters listed above, those that solely determine printing options, can be used. To change computation options, a new call to `bal.tab()` must be performed.

Prior versions of `print()` had separate methods for each `bal.tab` class. Now they are dispatched internally.

### Note

Unless `quick = FALSE` in the original call to `bal.tab()` (which is not the default), some values may not be calculated, in which case using `print()` will not display these values even when requested. For example, if `stats = "m"` and `quick = TRUE` in the original call to `bal.tab()` (the default for both), setting `stats = "ks"` in `print()` will not print the KS statistics because they were not calculated.

### Author(s)

Noah Greifer

### See Also

[print\(\)](#), [bal.tab\(\)](#)

[display options](#) for further information on some of these options.

### Examples

```
library(WeightIt); data("lalonge", package = "cobalt")

w.out <- weightit(treat ~ age + educ + married + race + re74 + re75,
                 data = lalonge)

b <- bal.tab(w.out, stats = c("m", "v", "ks"),
             un = TRUE, v.threshold = 2)

print(b, un = FALSE, stats = c("m", "v"),
      disp.thresholds = c(v = FALSE))
```

---

set.cobalt.options      *Set and Get Options in cobalt*

---

### Description

Makes it easier to set **cobalt** options. `set.cobalt.options()` is essentially a wrapper for [options\(\)](#) but performs several checks, and `get.cobalt.options()` is essentially a wrapper for [getOption\(\)](#).

### Usage

```
set.cobalt.options(..., default = FALSE)

get.cobalt.options(...)
```

**Arguments**

...	For set.cobalt.options(), bal.tab() parameters and the values they should take. These should be the name of the parameter in bal.tab() without "cobalt_" preceding them. See examples. If any values are NULL, the corresponding options will be set back to their defaults. For get.cobalt.options(), one or more strings containing the name of a parameter option to be retrieved. See examples. If empty, all available options and their values will be returned.
default	if TRUE, sets all <b>cobalt</b> options not named in ... to their default values.

**Details**

When an option is set to NULL, it is set to its default value. The defaults are not displayed but are listed on the help pages where they appear. Most options correspond to display options, which can be accessed [here](#). Some others (e.g., continuous and binary) are described on the [bal.tab\(\)](#) help page.

**See Also**

[options\(\)](#)

[display\\_options](#) for some arguments that can be set via options.

**Examples**

```
# Set un to be TRUE to always display unadjusted
# balance measures and set binary to "std" to
# produce standardized mean differences for
# binary variables.

set.cobalt.options(un = TRUE, binary = "std")

# Note: the above is equivalent to:
# options(cobalt_un = TRUE, cobalt_binary = "std")
# but performs some additional checks

get.cobalt.options("un", "binary")

# Note: the above is equivalent to:
# getOption("cobalt_un")
# getOption("cobalt_binary")

# Return all cobalt options to their defaults

set.cobalt.options(default = TRUE)

# View all available options
get.cobalt.options()
```

splitfactor

*Split and Unsplit Factors into Dummy Variables***Description**

splitfactor() splits factor variables into dummy (0/1) variables. This can be useful when functions do not process factor variables well or require numeric matrices to operate. unsplitfactor() combines dummy variables into factor variables, undoing the operation of splitfactor().

**Usage**

```
splitfactor(data, var.name, drop.level = NULL,
            drop.first = TRUE, drop.singleton = FALSE,
            drop.na = TRUE, sep = "_", replace = TRUE,
            split.with = NULL, check = TRUE)
```

```
unsplitfactor(data, var.name, dropped.level = NULL,
              dropped.na = TRUE, sep = "_",
              replace = TRUE)
```

**Arguments**

data	A data.frame containing the variables to be split or unsplit. In splitfactor(), can be a factor variable to be split.
var.name	For splitfactor(), the names of the factor variables to split. If not specified, will split all factor variables in data. If data is a factor, the stem for each of the new variables to be created. For unsplitfactor(), the name of the previously split factor. If not specified and data is the output of a call to splitfactor(), all previously split variables will be unsplit.
drop.level	The name of a level of var.name for which to drop the dummy variable. Only works if there is only one variable to be split.
drop.first	Whether to drop the first dummy created for each factor. If "if2", will only drop the first category if the factor has exactly two levels. The default is to always drop the first dummy (TRUE).
drop.singleton	Whether to drop a factor variable if it only has one level.
drop.na	If NAs are present in the variable, how to handle them. If TRUE, no new dummy will be created for NA values, but all created dummies will have NA where the original variable was NA. If FALSE, NA will be treated like any other factor level, given its own column, and the other dummies will have a value of 0 where the original variable is NA.
sep	A character separating the the stem from the value of the variable for each dummy. For example, for "race_black", sep = "_".
replace	Whether to replace the original variable(s) with the new variable(s) (TRUE) or the append the newly created variable(s) to the end of the data set (FALSE).

<code>split.with</code>	A list of vectors or factors with lengths equal to the number of columns of data that are to be split in the same way data is. See Details.
<code>check</code>	Whether to make sure the variables specified in <code>var.name</code> are actually factor (or character) variables. If splitting non-factor (or non-character) variables into dummies, set <code>check = FALSE</code> . If <code>check = FALSE</code> and <code>data</code> is a <code>data.frame</code> , an argument to <code>var.name</code> must be specified.
<code>dropped.level</code>	The value of each original factor variable whose dummy was dropped when the variable was split. If left empty and a dummy was dropped, the resulting factor will have the value <code>NA</code> instead of the dropped value. There should be one entry per variable to unsplit. If no dummy was dropped for a variable, an entry is still required, but it will be ignored.
<code>dropped.na</code>	If <code>TRUE</code> , will assume that NAs in the variables to be unsplit correspond to <code>NA</code> in the unsplit factor (i.e., that <code>drop.na = TRUE</code> was specified in <code>split.factor()</code> ). If <code>FALSE</code> , will assume there is a dummy called <code>"var.name_stem_NA"</code> (e.g., <code>"x_NA"</code> ) that contains 1s where the unsplit factor should be <code>NA</code> (i.e., that <code>drop.na = FALSE</code> was specified in <code>split.factor()</code> ). If NAs are stored in a different column with the same stem, e.g., <code>"x_miss"</code> , that name (e.g., <code>"miss"</code> ) can be entered instead.

### Details

If there are NAs in the variable to be split, the new variables created by `splitfactor()` will have `NA` where the original variable is `NA`.

When using `unsplitfactor()` on a `data.frame` that was generated with `splitfactor()`, the arguments `dropped.na`, and `sep` are unnecessary.

If `split.with` is supplied, the elements will be split in the same way data is. For example, if data contained a 4-level factor that was to be split, the entries of `split.with` at the same index as the factor and would be duplicated so that resulting entries will have the same length as the number of columns of data after being split. The resulting values are stored in the `"split.with"` attribute of the output object. See Examples.

### Value

For `splitfactor()`, a `data.frame` containing the original data set with the newly created dummies. For `unsplitfactor()`, a `data.frame` containing the original data set with the newly created factor variables.

### See Also

[model.matrix\(\)](#)

### Examples

```
data("lalonge", package = "cobalt")

lalonge.split <- splitfactor(lalonge, "race",
                           replace = TRUE,
                           drop.first = TRUE)
# A data set with "race_hispan" and "race_white" instead
```



```
# of "race".

lalonde.unsplit <- unsplitfactor(lalonde.split, "race",
                                replace = TRUE,
                                dropped.level = "black")

all.equal(lalonde, lalonde.unsplit) #TRUE

# Demonstrating the use of split.with:
to.split <- list(letters[1:ncol(lalonde)],
                1:ncol(lalonde))

lalonde.split <- splitfactor(lalonde, split.with = to.split,
                             drop.first = FALSE)
attr(lalonde.split, "split.with")
```

---

var.names	<i>Extract Variable Names from bal.tab Objects</i>
-----------	--

---

## Description

This function extracts variable names from a `bal.tab` object for use in specifying alternate variable names in `love.plot()`. Optionally, a file can be written for easy editing of names.

## Usage

```
var.names(b,
          type,
          file = NULL,
          minimal = FALSE)
```

## Arguments

b	a <code>bal.tab</code> object; the output of a call to <code>bal.tab()</code> .
type	the type of output desired. Can either be "df" for a data.frame or "vec" for a named vector. See "Value". The default is "vec" unless file is not NULL.
file	optional; a file name to save the output if type = "df". See <code>write.csv()</code> , which <code>var.name</code> calls. Must end in <code>.csv</code> .
minimal	whether the output should contain all variable names (i.e., all rows that appear the output of <code>bal.tab()</code> ) or just the unique base variables. See "Details".

## Details

The goal of the function is to make supplying new variable names to the `var.names` argument in `love.plot()` easier. Rather than manually creating a vector or data.frame with all the variable names that one desires to change, one can use `var.names()` to extract variable names from a

bak.tab object and edit the output. Importantly, the output can be saved to a CSV file, which can be easily edited and read back into R for use in love.plot(), as demonstrated in the Example.

When minimal = TRUE, only a minimal set of variables will be output. For example, if the variables analyzed in bal.tab() are age, race, and married, and int = TRUE in bal.tab(), many variables will appear in the output, including expansions of the factor variables, the polynomial terms, and the interactions. Rather than renaming all of these variables individually, one can rename just the three base variables, and all variables that arise from them will be accordingly renamed. Setting minimal = TRUE requests only these base variables.

### Value

If type = "vec", a character vector the the variable names both as the names and the entries.

If type = "df", a data.frame with two columns called "old" and "new", each with the variables as the entries.

If file is not NULL, the output will be returned invisibly.

### Note

Not all programs can properly read the Unicode characters for the polynomial terms when requested. These may appear strange in, e.g., Excel, but R will process the characters correctly.

### Examples

```
data(lalonde, package = "cobalt")

b1 <- bal.tab(treat ~ age + race + married, data = lalonde,
             int = TRUE)
v1 <- var.names(b1, type = "vec", minimal = TRUE)
v1["age"] <- "Age (Years)"
v1["race"] <- "Race/Eth"
v1["married"] <- "Married"
love.plot(b1, var.names = v1)

## Not run:
b2 <- bal.tab(treat ~ age + race + married + educ + nodegree +
             re74 + re75 + I(re74==0) + I(re75==0),
             data = lalonde)
var.names(b2, file = "varnames.csv")

##Manually edit the CSV (e.g., in Excel), then save it.
v2 <- read.csv("varnames.csv")
love.plot(b2, var.names = v2)

## End(Not run)
```

# Index

- \* **datasets**
  - lalonde, 75
- \* **plots**
  - bal.plot, 2
  - love.plot, 76
- \* **support functions**
  - Balance Summary, 55
  - f.build, 72
  - get.w, 73
  - set.cobalt.options, 85
  - splitfactor, 87
  - var.names, 89
- \* **tables**
  - bal.tab, 6
  - bal.tab.CBPS, 11
  - bal.tab.cem.match, 15
  - bal.tab.default, 18
  - bal.tab.df.formula, 21
  - bal.tab.df.formula.list, 26
  - bal.tab.Match, 30
  - bal.tab.matchit, 35
  - bal.tab.mimids, 38
  - bal.tab.ps, 42
  - bal.tab.sbw, 47
  - bal.tab.weightit, 50
  - class-bal.tab.cluster, 61
  - class-bal.tab.imp, 63
  - class-bal.tab.msm, 64
  - class-bal.tab.multi, 65
- alist(), 71
- arrangeGrob(), 79, 81
- bal.plot, 2
- bal.tab, 6
- bal.tab(), 5, 6, 14, 17, 19, 20, 25, 34, 38, 41, 46, 49, 53, 54, 56, 60–65, 67–69, 72, 74, 77, 81, 83, 85, 86, 89
- bal.tab() base methods, 29
- bal.tab.CBMSM (bal.tab.CBPS), 11
- bal.tab.CBPS, 11
- bal.tab.CBPS(), 7
- bal.tab.cem.match, 15
- bal.tab.cem.match(), 7
- bal.tab.cluster, 9, 13, 14, 16, 17, 20, 23, 25, 28, 29, 32, 34, 37, 38, 40, 45, 46, 48, 49, 52, 53, 70, 84
- bal.tab.data.frame
  - (bal.tab.df.formula), 21
- bal.tab.data.frame(), 7, 18–20, 62, 64, 67, 68
- bal.tab.data.frame.list
  - (bal.tab.df.formula.list), 26
- bal.tab.default, 18
- bal.tab.default(), 7
- bal.tab.designmatch (bal.tab.Match), 30
- bal.tab.designmatch(), 7
- bal.tab.df.formula, 21
- bal.tab.df.formula.list, 26
- bal.tab.ebalance (bal.tab.Match), 30
- bal.tab.ebalance(), 7
- bal.tab.formula (bal.tab.df.formula), 21
- bal.tab.formula(), 7, 18, 19
- bal.tab.formula.list
  - (bal.tab.df.formula.list), 26
- bal.tab.imp, 9, 13, 16, 17, 20, 23, 25, 28, 29, 33, 37, 41, 45, 49, 52, 53, 70, 71, 84
- bal.tab.iptw (bal.tab.ps), 42
- bal.tab.list, 65
- bal.tab.list (bal.tab.df.formula.list), 26
- bal.tab.Match, 30
- bal.tab.Match(), 7
- bal.tab.matchit, 35
- bal.tab.matchit(), 6, 40, 41
- bal.tab.mimids, 38
- bal.tab.mimids(), 7
- bal.tab.mnps (bal.tab.ps), 42
- bal.tab.msm, 9, 14, 20, 29, 46, 53, 71, 84

- bal.tab.multi, [8](#), [13](#), [14](#), [16](#), [17](#), [20](#), [23](#), [25](#), [28](#), [29](#), [33](#), [37](#), [40](#), [45](#), [46](#), [49](#), [52](#), [53](#), [70](#), [84](#)
- bal.tab.optmatch (bal.tab.Match), [30](#)
- bal.tab.optmatch(), [7](#)
- bal.tab.ps, [42](#)
- bal.tab.ps(), [6](#)
- bal.tab.sbw, [47](#)
- bal.tab.sbw(), [7](#)
- bal.tab.sbwcau (bal.tab.sbw), [47](#)
- bal.tab.subclass, [8](#), [10](#), [24](#), [36–38](#), [83](#)
- bal.tab.time.list
  - (bal.tab.df.formula.list), [26](#)
- bal.tab.time.list(), [7](#), [18–20](#)
- bal.tab.weightit, [50](#)
- bal.tab.weightit(), [6](#), [40](#), [41](#)
- bal.tab.weightitMSM (bal.tab.weightit), [50](#)
- bal.tab.wimids (bal.tab.mimids), [38](#)
- Balance Statistics, [54](#)
- Balance Summary, [55](#)
- balance.stats (Balance Statistics), [54](#)
  
- class-bal.tab.cluster, [61](#)
- class-bal.tab.imp, [63](#)
- class-bal.tab.msm, [64](#)
- class-bal.tab.multi, [65](#)
- class-bal.tab.subclass, [67](#)
- col\_w\_corr, [45](#)
- col\_w\_corr (Balance Summary), [55](#)
- col\_w\_cov (Balance Summary), [55](#)
- col\_w\_cov(), [8](#), [52](#), [55](#)
- col\_w\_ks (Balance Summary), [55](#)
- col\_w\_ks(), [54](#)
- col\_w\_mean (Balance Summary), [55](#)
- col\_w\_ovl (Balance Summary), [55](#)
- col\_w\_ovl(), [54](#)
- col\_w\_sd, [46](#)
- col\_w\_sd (Balance Summary), [55](#)
- col\_w\_smd (Balance Summary), [55](#)
- col\_w\_smd(), [8](#), [13](#), [16](#), [23](#), [28](#), [32](#), [36](#), [40](#), [45](#), [48](#), [52](#), [54](#)
- col\_w\_vr (Balance Summary), [55](#)
- col\_w\_vr(), [8](#), [54](#)
- colMeans, [56](#)
  
- defaults, [5](#)
- density, [59](#)
- Display Options, [69](#)
  
- display options, [13](#), [17](#), [24](#), [29](#), [33](#), [37](#), [41](#), [46](#), [49](#), [53](#), [85](#)
- display\_options, [86](#)
- display\_options (Display Options), [69](#)
- do.call(), [71](#)
  
- f.build, [72](#)
- facet\_grid(), [4](#), [5](#)
- formula, [72](#)
  
- geom\_bar(), [5](#)
- geom\_density(), [3](#), [5](#)
- geom\_histogram(), [3](#), [5](#)
- geom\_point(), [5](#), [78](#)
- geom\_smooth(), [5](#)
- geom\_step(), [5](#)
- get.cobalt.options
  - (set.cobalt.options), [85](#)
- get.cobalt.options(), [71](#)
- get.w, [73](#)
- get.w(), [13](#), [16](#), [32](#), [37](#), [40](#), [45](#), [48](#), [52](#)
- get.weights(), [75](#)
- getOption(), [85](#)
- ggplot(), [5](#)
- glm(), [72](#)
  
- here, [86](#)
  
- integrate, [58](#)
  
- labs(), [5](#)
- lalonge, [75](#)
- lalonge\_mis (lalonge), [75](#)
- list(), [71](#)
- love.plot, [76](#)
- love.plot(), [54](#), [89](#)
  
- match.call(), [19](#)
- mice(), [12](#), [15](#), [22](#), [27](#), [31](#), [36](#), [45](#), [48](#), [52](#)
- model.matrix(), [88](#)
  
- options(), [85](#), [86](#)
- options-display (Display Options), [69](#)
  
- par(), [4](#), [78](#)
- plot.bal.tab (love.plot), [76](#)
- print(), [85](#)
- print.bal.tab, [82](#)
- print.bal.tab(), [9](#), [62](#), [64](#), [65](#), [67](#), [68](#), [72](#)
  
- rank, [58](#)

reformulate(), 72  
reshape(), 29  
  
scale\_alpha(), 78  
set.cobalt.options, 85  
set.cobalt.options(), 12, 13, 16, 23, 28,  
32, 36, 40, 45, 48, 52, 71  
splitfactor, 57, 59, 87  
stats, 7, 12, 13, 15, 22, 27, 32, 36, 39, 44, 48,  
51, 69, 77, 78  
  
theme(), 4, 79  
  
unsplitfactor (splitfactor), 87  
  
var.names, 89  
var.names(), 78, 80  
  
weightitMSM(), 29  
write.csv(), 89