

Package ‘dbx’

April 25, 2019

Type Package

Title A Fast, Easy-to-Use Database Interface

Version 0.2.5

Date 2019-04-24

Description Provides select, insert, update, upsert, and delete database operations. Supports 'PostgreSQL', 'MySQL', 'SQLite', and more, and plays nicely with the 'DBI' package.

URL <https://github.com/ankane/dbx>

BugReports <https://github.com/ankane/dbx/issues>

License MIT + file LICENSE

LazyData TRUE

RoxygenNote 6.1.1

Encoding UTF-8

Imports DBI (>= 1.0.0)

Suggests testthat (>= 1.0.2), urltools (>= 1.7.0), RSQLite (>= 1.1-2),
RMariaDB, RMySQL, RPostgres, RPostgreSQL, hms, jsonlite, blob,
odbc

NeedsCompilation no

Author Andrew Kane [aut, cre]

Maintainer Andrew Kane <andrew@chartkick.com>

Repository CRAN

Date/Publication 2019-04-24 23:00:03 UTC

R topics documented:

dbxConnect	2
dbxDelete	3
dbxDisconnect	3
dbxExecute	4
dbxInsert	4

dbxSelect	5
dbxUpdate	6
dbxUpsert	6

Index	8
--------------	----------

dbxConnect	<i>Create a database connection</i>
------------	-------------------------------------

Description

Create a database connection

Usage

```
dbxConnect(url = NULL, adapter = NULL, storage_tz = NULL,
  variables = list(), ...)
```

Arguments

url	A database URL
adapter	The database adapter to use
storage_tz	The time zone timestamps are stored in
variables	Session variables
...	Arguments to pass to dbConnect

Examples

```
# SQLite
db <- dbxConnect(adapter="sqlite", dbname=":memory:")

## Not run:

# Postgres
db <- dbxConnect(adapter="postgres", dbname="mydb")

# MySQL
db <- dbxConnect(adapter="mysql", dbname="mydb")

# Others
db <- dbxConnect(adapter=odbc(), database="mydb")

## End(Not run)
```

dbxDelete	<i>Delete records</i>
-----------	-----------------------

Description

Delete records

Usage

```
dbxDelete(conn, table, where = NULL, batch_size = NULL)
```

Arguments

conn	A DBIConnection object
table	The table name to delete records from
where	A data frame of records to delete
batch_size	The number of records to delete in a single statement (defaults to all)

Examples

```
db <- dbxConnect(adapter="sqlite", dbname=":memory:")
table <- "forecasts"
DBI::dbCreateTable(db, table, data.frame(id=1:3, temperature=20:22))

# Delete specific records
bad_records <- data.frame(id=c(1, 2))
dbxDelete(db, table, where=bad_records)

# Delete all records
dbxDelete(db, table)
```

dbxDisconnect	<i>Close a database connection</i>
---------------	------------------------------------

Description

Close a database connection

Usage

```
dbxDisconnect(conn)
```

Arguments

conn	A DBIConnection object
------	------------------------

Examples

```
db <- dbxConnect(adapter="sqlite", dbname=":memory:")
dbxDisconnect(db)
```

dbxExecute	<i>Execute a statement</i>
------------	----------------------------

Description

Execute a statement

Usage

```
dbxExecute(conn, statement, params = NULL)
```

Arguments

conn	A DBIConnection object
statement	The SQL statement to use
params	Parameters to bind

Examples

```
db <- dbxConnect(adapter="sqlite", dbname=":memory:")
DBI::dbCreateTable(db, "forecasts", data.frame(id=1:3, temperature=20:22))

dbxExecute(db, "UPDATE forecasts SET temperature = 20")

dbxExecute(db, "UPDATE forecasts SET temperature = ?", params=list(20))

dbxExecute(db, "UPDATE forecasts SET temperature = ? WHERE id IN (?)", params=list(20, 1:3))
```

dbxInsert	<i>Insert records</i>
-----------	-----------------------

Description

Insert records

Usage

```
dbxInsert(conn, table, records, batch_size = NULL, returning = NULL)
```

Arguments

conn	A DBIConnection object
table	The table name to insert
records	A data frame of records to insert
batch_size	The number of records to insert in a single statement (defaults to all)
returning	Columns to return

Examples

```
db <- dbxConnect(adapter="sqlite", dbname=":memory:")
table <- "forecasts"
DBI::dbCreateTable(db, table, data.frame(id=1:3, temperature=20:22))

records <- data.frame(temperature=c(32, 25))
dbxInsert(db, table, records)
```

dbxSelect	<i>Select records</i>
-----------	-----------------------

Description

Select records

Usage

```
dbxSelect(conn, statement, params = NULL)
```

Arguments

conn	A DBIConnection object
statement	The SQL statement to use
params	Parameters to bind

Examples

```
db <- dbxConnect(adapter="sqlite", dbname=":memory:")
DBI::dbCreateTable(db, "forecasts", data.frame(id=1:3, temperature=20:22))

dbxSelect(db, "SELECT * FROM forecasts")

dbxSelect(db, "SELECT * FROM forecasts WHERE id = ?", params=list(1))

dbxSelect(db, "SELECT * FROM forecasts WHERE id IN (?)", params=list(1:3))
```

dbxUpdate	<i>Update records</i>
-----------	-----------------------

Description

Update records

Usage

```
dbxUpdate(conn, table, records, where_cols, batch_size = NULL)
```

Arguments

conn	A DBIConnection object
table	The table name to update
records	A data frame of records to insert
where_cols	The columns to use for WHERE clause
batch_size	The number of records to update in a single transaction (defaults to all)

Examples

```
db <- dbxConnect(adapter="sqlite", dbname=":memory:")
table <- "forecasts"
DBI::dbCreateTable(db, table, data.frame(id=1:3, temperature=20:22))

records <- data.frame(id=c(1, 2), temperature=c(16, 13))
dbxUpdate(db, table, records, where_cols=c("id"))
```

dbxUpsert	<i>Upsert records</i>
-----------	-----------------------

Description

Upsert records

Usage

```
dbxUpsert(conn, table, records, where_cols, batch_size = NULL,
  returning = NULL, skip_existing = FALSE)
```

Arguments

<code>conn</code>	A DBIConnection object
<code>table</code>	The table name to upsert
<code>records</code>	A data frame of records to upsert
<code>where_cols</code>	The columns to use for WHERE clause
<code>batch_size</code>	The number of records to upsert in a single statement (defaults to all)
<code>returning</code>	Columns to return
<code>skip_existing</code>	Skip existing rows

Examples

```
## Not run:  
  
db <- dbxConnect(adapter="postgres", dbname="dbx")  
table <- "forecasts"  
DBI::dbCreateTable(db, table, data.frame(id=1:3, temperature=20:22))  
  
records <- data.frame(id=c(3, 4), temperature=c(20, 25))  
dbxUpsert(db, table, records, where_cols=c("id"))  
  
## End(Not run)
```

Index

dbxConnect, 2
dbxDelete, 3
dbxDisconnect, 3
dbxExecute, 4
dbxInsert, 4
dbxSelect, 5
dbxUpdate, 6
dbxUpsert, 6