

Package ‘dendroTools’

May 20, 2026

Type Package

Title Linear and Nonlinear Methods for Analyzing Daily and Monthly
Dendroclimatological Data

Version 1.2.16

Description Provides novel dendroclimatological methods, primarily used by the Tree-ring research community. There are four core functions. The first one is `daily_response()`, which finds the optimal sequence of days that are related to one or more tree-ring proxy records. Similar function is `daily_response_seascorr()`, which implements partial correlations in the analysis of daily response functions. For the enthusiast of monthly data, there is `monthly_response()` function. The last core function is `compare_methods()`, which effectively compares several linear and nonlinear regression algorithms on the task of climate reconstruction.

License GPL-3

URL <https://github.com/jernejevsenak/dendroTools>

BugReports <https://github.com/jernejevsenak/dendroTools/issues>

Encoding UTF-8

LazyData true

Suggests testthat, rmarkdown

RoxygenNote 7.3.2

Imports ggplot2 (>= 2.2.0), brnn (>= 0.6), reshape2 (>= 1.4.2), scales (>= 0.4.1), stats, oce (>= 1.2-0), MLmetrics (>= 1.1.1), dplyr (>= 0.7.0), knitr (>= 1.19), magrittr (>= 1.5), plotly (>= 4.7.1), randomForest (>= 4.6-14), Cubist (>= 0.2.2), lubridate (>= 1.7.4), psych (>= 1.8.3.3), boot (>= 1.3-22), viridis (>= 0.5.1), dplR (>= 1.7.2)

Depends R (>= 3.4)

NeedsCompilation no

Repository CRAN

VignetteBuilder knitr

Author Jernej Jevsenak [aut, cre]

Maintainer Jernej Jevsenak <jernej.jevsenak@gmail.com>

Date/Publication 2026-05-20 18:30:02 UTC

Contents

calculate_metrics	2
compare_methods	4
critical_r	10
daily_response	11
daily_response_seascorr	19
dataset_MVA	25
dataset_MVA_individual	26
dataset_TRW	27
dataset_TRW_complete	28
data_MVA	28
data_transform	29
data_TRW	30
data_TRW_1	30
example_dataset_1	31
example_proxies_1	31
example_proxies_individual	32
glimpse_daily_data	33
KRE_daily_temperatures	34
LJ_daily_precipitation	44
LJ_daily_temperatures	45
LJ_monthly_precipitation	55
LJ_monthly_temperatures	56
monthly_response	57
monthly_response_seascorr	63
swit272	68
swit272_daily_precipitation	69
swit272_daily_temperatures	70
years_to_rownames	70
Index	72

calculate_metrics	<i>calculate_metrics</i>
-------------------	--------------------------

Description

Calculates performance metrics for train and test data. Calculated performance metrics are correlation coefficient (r), root mean squared error (RMSE), root relative squared error (RRSE), index of agreement (d), reduction of error (RE), coefficient of efficiency (CE), detrended efficiency (DE) and bias.

Usage

```
calculate_metrics(  
  train_predicted,  
  test_predicted,  
  train_observed,  
  test_observed,  
  digits = 4,  
  formula,  
  test  
)
```

Arguments

train_predicted	a vector indicating predicted data for training set
test_predicted	a vector indicating predicted data for testing set
train_observed	a vector indicating observed data for training set
test_observed	a vector indicating observed data for training set
digits	integer of number of digits to be displayed
formula	an object of class "formula" (or one that can be coerced to that class): a symbolic description of the model to be fitted. This additional argument is needed to calculate DE metrics.
test	data frame with test data.

Value

a data frame of calculated test and train metrics

References

Briffa, K.R., Jones, P.D., Pilcher, J.R., Hughes, M.K., 1988. Reconstructing summer temperatures in northern Fennoscandia back to A.D.1700 using tree ring data from Scots Pine. *Arct. Alp. Res.* 20, 385-394.

Fritts, H.C., 1976. *Tree Rings and Climate*. Academic Press, London 567 pp.

Lorenz, E.N., 1956. *Empirical Orthogonal Functions and Statistical Weather Prediction*. Massachusetts Institute of Technology, Department of Meteorology.

Willmott, C.J., 1981. On the validation of models. *Phys. Geogr.* 2, 184-194.

Witten, I.H., Frank, E., Hall, M.A., 2011. *Data Mining: Practical Machine Learning Tools and Techniques*, 3rd ed. Morgan Kaufmann Publishers, Burlington 629 pp.

Examples

```
data(example_dataset_1)  
test_data <- example_dataset_1[1:30, ]  
train_data <- example_dataset_1[31:55, ]  
lin_mod <- lm(MVA ~., data = train_data)
```

```

train_predicted <- predict(lin_mod, train_data)
test_predicted <- predict(lin_mod, test_data)
train_observed <- train_data[, 1]
test_observed <- test_data[, 1]
calculate_metrics(train_predicted, test_predicted, train_observed,
test_observed, test = test_data, formula = MVA ~.)

test_data <- example_dataset_1[1:20, ]
train_data <- example_dataset_1[21:55, ]
library(brnn)
lin_mod <- brnn(MVA ~., data = train_data)
train_predicted <- predict(lin_mod, train_data)
test_predicted <- predict(lin_mod, test_data)
train_observed <- train_data[, 1]
test_observed <- test_data[, 1]
calculate_metrics(train_predicted, test_predicted, train_observed,
test_observed, test = test_data, formula = MVA ~.)

```

compare_methods

compare_methods

Description

Calculates performance metrics for calibration (train) and validation (test) data of different regression methods: multiple linear regression (MLR), artificial neural networks with Bayesian regularization training algorithm (BRNN), (ensemble of) model trees (MT) and random forest of regression trees (RF). With the subset argument, specific methods of interest could be specified. Calculated performance metrics are the correlation coefficient (r), the root mean squared error (RMSE), the root relative squared error (RRSE), the index of agreement (d), the reduction of error (RE), the coefficient of efficiency (CE), the detrended efficiency (DE) and mean bias. For each of the considered methods, there are also residual diagnostic plots available, separately for calibration, holdout and edge data, if applicable.

Usage

```

compare_methods(
  formula,
  dataset,
  k = 10,
  repeats = 2,
  optimize = TRUE,
  dataset_complete = NULL,
  BRNN_neurons = 1,
  MT_committees = 1,
  MT_neighbors = 5,
  MT_rules = 200,
  MT_unbiased = TRUE,

```

```

MT_extrapolation = 100,
MT_sample = 0,
RF_ntree = 500,
RF_maxnodes = 5,
RF_mtry = 1,
RF_nodesize = 1,
seed_factor = 5,
digits = 3,
blocked_CV = FALSE,
PCA_transformation = FALSE,
log_preprocess = TRUE,
components_selection = "automatic",
eigenvalues_threshold = 1,
N_components = 2,
round_bias_cal = 15,
round_bias_val = 4,
n_bins = 30,
edge_share = 0.1,
MLR_stepwise = FALSE,
stepwise_direction = "backward",
methods = c("MLR", "BRNN", "MT", "RF"),
tuning_metric = "RMSE",
BRNN_neurons_vector = c(1, 2, 3),
MT_committees_vector = c(1, 5, 10),
MT_neighbors_vector = c(0, 5),
MT_rules_vector = c(100, 200),
MT_unbiased_vector = c(TRUE, FALSE),
MT_extrapolation_vector = c(100),
MT_sample_vector = c(0),
RF_ntree_vector = c(100, 250, 500),
RF_maxnodes_vector = c(5, 10, 20, 25),
RF_mtry_vector = c(1),
RF_nodesize_vector = c(1, 5, 10),
holdout = NULL,
holdout_share = 0.1,
holdout_manual = NULL,
total_reproducibility = FALSE
)

```

Arguments

formula	an object of class "formula" (or one that can be coerced to that class): a symbolic description of the model to be fitted.
dataset	a data frame with dependent and independent variables as columns and (optional) years as row names.
k	number of folds for cross-validation
repeats	number of cross-validation repeats. Should be equal or more than 1

optimize	if set to TRUE (default), the optimal values for the tuning parameters will be selected in a preliminary cross-validation procedure
dataset_complete	optional, a data frame with the full length of tree-ring parameter, which will be used to reconstruct the climate variable specified with the formula argument
BRNN_neurons	number of neurons to be used for the brnn method
MT_committees	an integer: how many committee models (e.g. boosting iterations) should be used?
MT_neighbors	how many, if any, neighbors should be used to correct the model predictions
MT_rules	an integer (or NA): define an explicit limit to the number of rules used (NA let's Cubist decide).
MT_unbiased	a logical: should unbiased rules be used?
MT_extrapolation	a number between 0 and 100: since Cubist uses linear models, predictions can be outside of the range seen the training set. This parameter controls how much rule predictions are adjusted to be consistent with the training set.
MT_sample	a number between 0 and 99.9: this is the percentage of the dataset to be randomly selected for model building (not for out-of-bag type evaluation)
RF_ntree	number of trees to grow. This should not be set to too small a number, to ensure that every input row gets predicted at least a few times
RF_maxnodes	maximum number of terminal nodes trees in the forest can have
RF_mtry	number of variables randomly sampled as candidates at each split
RF_nodesize	minimum size of terminal nodes. Setting this number larger causes smaller trees to be grown (and thus take less time).
seed_factor	an integer that will be used to change the seed options for different repeats.
digits	integer of number of digits to be displayed in the final result tables
blocked_CV	default is FALSE, if changed to TRUE, blocked cross-validation will be used to compare regression methods.
PCA_transformation	if set to TRUE, all independent variables will be transformed using PCA transformation.
log_preprocess	if set to TRUE, variables will be transformed with logarithmic transformation before used in PCA
components_selection	character string specifying how to select the Principal Components used as predictors. There are three options: "automatic", "manual" and "plot_selection". If parameter is set to automatic, all scores with eigenvalues above 1 will be selected. This threshold could be changed by changing the eigenvalues_threshold argument. If parameter is set to "manual", user should set the number of components with N_components argument. If component selection is set to "plot_selection", Scree plot will be shown and user must manually enter the number of components used as predictors.
eigenvalues_threshold	threshold for automatic selection of Principal Components

N_components	number of Principal Components used as predictors
round_bias_cal	number of digits for bias in calibration period. Effects the outlook of the final ggplot of mean bias for calibration data (element 3 of the output list)
round_bias_val	number of digits for bias in validation period. Effects the outlook of the final ggplot of mean bias for validation data (element 4 of the output list)
n_bins	number of bins used for the histograms of mean bias
edge_share	the share of the data to be considered as the edge (extreme) data. This argument could be between 0.10 and 0.50. If the argument is set to 0.10, then the 5 considered to be the edge data.
MLR_stepwise	if set to TRUE, stepwise selection of predictors will be used for the MLR method
stepwise_direction	the mode of stepwise search, can be one of "both", "backward", or "forward", with a default of "backward".
methods	a vector of strings related to methods that will be compared. A full method vector is <code>methods = c("MLR", "BRNN", "MT", "RF")</code> . To use only a subset of methods, pass a vector of methods that you would like to compare.
tuning_metric	a string that specifies what summary metric will be used to select the optimal value of tuning parameters. By default, the argument is set to "RMSE". It is also possible to use "RSquared".
BRNN_neurons_vector	a vector of possible values for BRNN_neurons argument optimization
MT_committees_vector	a vector of possible values for MT_committees argument optimization
MT_neighbors_vector	a vector of possible values for MT_neighbors argument optimization
MT_rules_vector	a vector of possible values for MT_rules argument optimization
MT_unbiased_vector	a vector of possible values for MT_unbiased argument optimization
MT_extrapolation_vector	a vector of possible values for MT_extrapolation argument optimization
MT_sample_vector	a vector of possible values for MT_sample argument optimization
RF_ntree_vector	a vector of possible values for RF_ntree argument optimization
RF_maxnodes_vector	a vector of possible values for RF_maxnodes argument optimization
RF_mtry_vector	a vector of possible values for RF_mtry argument optimization
RF_nodesize_vector	a vector of possible values for RF_nodesize argument optimization
holdout	this argument is used to define observations, which are excluded from the cross-validation and hyperparameters optimization. The holdout argument must be a character with one of the following inputs: "early", "late" or "manual". If

"early" or "late" characters are specified, then the early or late years will be used as a holdout data. How many of the "early" or "late" years are used as a holdout is specified with the argument `holdout_share`. If the argument `holdout` is set to "manual", then supply a vector of years (or row names) to the argument `holdout_manual`. Defined years will be used as a holdout. For the holdout data, the same statistical measures are calculated as for the cross-validation. The results for holdout metrics are given in the output element `$holdout_results`.

`holdout_share` the share of the whole dataset to be used as a holdout. Default is 0.10.

`holdout_manual` a vector of years (or row names) which will be used as a holdout. calculated as for the cross-validation.

`total_reproducibility` logical, default is FALSE. This argument ensures total reproducibility despite the inclusion/exclusion of different methods. By default, the optimization is done only for the methods, that are included in the `methods` vector. If one method is absent or added, the optimization phase is different, and this affects all the final cross-validation results. By setting the `total_reproducibility = TRUE`, all methods will be optimized, even though they are not included in the `methods` vector and the final results will be subset based on the `methods` vector. Setting the `total_reproducibility` to TRUE will result in longer optimization phase as well.

Value

a list with 19 elements:

1. `$mean_std` - data frame with calculated metrics for the selected \ regression methods. For each regression method and each calculated metric, mean and standard deviation are given
2. `$ranks` - data frame with ranks of calculated metrics: mean rank and share of `rank_1` are given
3. `$edge_results` - data frame with calculated performance metrics for the central-edge test. The central part of the data represents the calibration data, while the edge data, i.e. extreme values, represent the test/validation data. Different regression models are calibrated using the central data and validated for the edge (extreme) data. This test is particularly important to assess the performance of models for the predictions of the extreme data. The share of the edge (extreme) data is defined with the `edge_share` argument
4. `$holdout_results` - calculated metrics for the holdout data
5. `$bias_cal` - ggplot object of mean bias for calibration data
6. `$bias_val` - ggplot object of mean bias for validation data
7. `$transfer_functions` - ggplot or plotly object with transfer functions of methods
8. `$transfer_functions_together` - ggplot or plotly object with transfer functions of methods plotted together
9. `$parameter_values` - a data frame with specifications of parameters used for different regression methods
10. `$PCA_output` - princomp object: the result output of the PCA analysis
11. `$reconstructions` - ggplot object: reconstructed dependent variable based on the `dataset_complete` argument, `facet` is used to split plots by methods

12. \$reconstructions_together - ggplot object: reconstructed dependent variable based on the dataset_complete argument, all reconstructions are on the same plot
13. \$normal_QQ_cal - normal q-q plot for calibration data
14. \$normal_QQ_holdout - normal q-q plot for holdout data
15. \$normal_QQ_edge- normal q-q plot for edge data
16. \$residuals_vs_fitted_cal - residuals vs fitted values plot for calibration data
17. \$residuals_vs_fitted_holdout - residuals vs fitted values plot for holdout data
18. \$residuals_vs_fitted_edge - residuals vs fitted values plot for edge data
19. \$reconstructions_data - raw data that is used for creating reconstruction plots

References

- Bishop, C.M., 1995. Neural Networks for Pattern Recognition. Oxford University Press, Inc. 482 pp.
- Breiman, L., 1996. Bagging predictors. Machine Learning 24, 123-140.
- Breiman, L., 2001. Random forests. Machine Learning 45, 5-32.
- Burden, F., Winkler, D., 2008. Bayesian Regularization of Neural Networks, in: Livingstone, D.J. (ed.), Artificial Neural Networks: Methods and Applications, vol. 458. Humana Press, Totowa, NJ, pp. 23-42.
- Hastie, T., Tibshirani, R., Friedman, J.H., 2009. The Elements of Statistical Learning : Data Mining, Inference, and Prediction, 2nd ed. Springer, New York xxii, 745 p. pp.
- Ho, T.K., 1995. Random decision forests, Proceedings of the Third International Conference on Document Analysis and Recognition Volume 1. IEEE Computer Society, pp. 278-282.
- Hornik, K., Buchta, C., Zeileis, A., 2009. Open-source machine learning: R meets Weka. Comput. Stat. 24, 225-232.
- Perez-Rodriguez, P., Gianola, D., 2016. Brnn: Brnn (Bayesian Regularization for Feed-forward Neural Networks). R package version 0.6.
- Quinlan, J.R., 1992. Learning with Continuous Classes, Proceedings of the 5th Australian Joint Conference on Artificial Intelligence (AI '92). World Scientific, Hobart, pp. 343-348.

Examples

```
# The examples below are enclosed within donttest{} to minimize the execution
# time during R package checks. #'

# An example with default settings of machine learning algorithms
library(dendroTools)
library(ggplot2)

data(example_dataset_1)
data(dataset_TRW)

example_1 <- compare_methods(formula = MVA ~ T_APR,
dataset = example_dataset_1, k = 5, repeats = 1, BRNN_neurons = 1,
```

```

RF_ntree = 100, RF_mtry = 2, RF_maxnodes = 35, seed_factor = 5)

# example_1$mean_std
# example_1$ranks
# example_1$bias_cal
# example_1$transfer_functions
# example_1$transfer_functions_together
# example_1$PCA_output
# example_1$parameter_values

example_2 <- compare_methods(formula = MVA ~ .,
dataset = example_dataset_1, k = 2, repeats = 2,
methods = c("MLR", "BRNN", "MT"),
optimize = TRUE, MLR_stepwise = TRUE)
# example_2$mean_std
# example_2$ranks
# example_2$bias_val
# example_2$transfer_functions
# example_2$transfer_functions_together
# example_2$parameter_values

comparison_TRW <- compare_methods(formula = T_Jun_Jul ~ TRW, dataset = dataset_TRW,
k = 3, repeats = 5, optimize = FALSE, methods = c("MLR", "BRNN", "RF", "MT"),
seed_factor = 5, dataset_complete = dataset_TRW_complete, MLR_stepwise = TRUE,
stepwise_direction = "backward")

# comparison_TRW$mean_std
# comparison_TRW$bias_val
# comparison_TRW$transfer_functions
# comparison_TRW$reconstructions
# comparison_TRW$reconstructions_together
# comparison_TRW$edge_results
# comparison_TRW$reconstructions_data

```

critical_r

critical_r

Description

Calculates critical value of Pearson correlation coefficient for a selected alpha.

Usage

```
critical_r(n, alpha = 0.05)
```

Arguments

n	number of observations
alpha	significance level

Value

calculated critical value of Pearson correlation coefficient

Examples

```
threshold_1 <- critical_r(n = 55, alpha = 0.01)
threshold_2 <- critical_r(n = 55, alpha = 0.05)
```

daily_response	<i>daily_response</i>
----------------	-----------------------

Description

Function calculates all possible values of a selected statistical metric between one or more response variables and daily sequences of environmental data. Calculations are based on moving window which is defined with two arguments: window width and a location in a matrix of daily sequences of environmental data. Window width could be fixed (use `fixed_width`) or variable width (use `lower_limit` and `upper_limit` arguments). In this case, all window widths between lower and upper limit will be used. All calculated metrics are stored in a matrix. The location of stored calculated metric in the matrix is indicating a window width (row names) and a location in a matrix of daily sequences of environmental data (column names).

Usage

```
daily_response(  
  response,  
  env_data,  
  method = "cor",  
  metric = "r.squared",  
  cor_method = "pearson",  
  lower_limit = 30,  
  upper_limit = 90,  
  fixed_width = 0,  
  previous_year = FALSE,  
  number_previous_years = NULL,  
  neurons = 1,  
  brnn_smooth = TRUE,  
  remove_insignificant = FALSE,  
  alpha = 0.05,  
  row_names_subset = FALSE,  
  aggregate_function = "mean",  
  quantile_prob = 0.5,  
  temporal_stability_check = "sequential",  
  k = 2,  
  k_running_window = 30,  
  cross_validation_type = "blocked",  
  subset_years = NULL,
```

```

ylimits = NULL,
seed = NULL,
tidy_env_data = FALSE,
reference_window = "start",
boot = FALSE,
boot_n = 1000,
boot_ci_type = "norm",
boot_conf_int = 0.95,
day_interval = NULL,
dc_method = NULL,
cor_na_use = "everything",
skip_window_length = 1,
skip_window_position = 1
)

```

Arguments

response	a data frame with tree-ring proxy variables as columns and (optional) years as row names. Row.names should be matched with those from a env_data data frame. If not, set row_names_subset = TRUE.
env_data	a data frame of daily sequences of environmental data as columns and years as row names. Each row represents a year and each column represents a day of a year. Row.names should be matched with those from a response data frame. If not, set row_names_subset = TRUE. Alternatively, env_data could be a tidy data with three columns, i.e. Year, DOY and third column representing values of mean temperatures, sum of precipitation etc. If tidy data is passed to the function, set the argument tidy_env_data to TRUE.
method	a character string specifying which method to use. Current possibilities are "cor" (default), "lm" and "brnn".
metric	a character string specifying which metric to use. Current possibilities are "r.squared" and "adj.r.squared". If method = "cor", metric is not relevant.
cor_method	a character string indicating which correlation coefficient is to be computed. One of "pearson" (default), "kendall", or "spearman".
lower_limit	lower limit of window width
upper_limit	upper limit of window width
fixed_width	fixed width used for calculation. If fixed_width is assigned a value, upper_limit and lower_limit will be ignored
previous_year	logical. If TRUE, previous-year climate data are included in the analysis. If FALSE, no previous-year climate data are included and number_previous_years is ignored.
number_previous_years	integer between 1 and 5 specifying how many previous years should be included in the environmental matrix when previous_year = TRUE. For example, number_previous_years = 2 uses climate data from years t - 2, t - 1 and t for response year t. If NULL and previous_year = TRUE, one previous year is included.
neurons	positive integer that indicates the number of neurons used for brnn method

brnn_smooth	if set to TRUE, a smoothing algorithm is applied that removes unrealistic calculations which are a result of neural net failure.
remove_insignificant	if set to TRUE, removes all correlations below the significant threshold level, based on a selected alpha. For "lm" and "brnn" method, squared correlation is used as a threshold
alpha	significance level used to remove insignificant calculations.
row_names_subset	if set to TRUE, row.names are used to subset env_data and response data frames. Only years from both data frames are kept.
aggregate_function	character string specifying how the daily data should be aggregated. The default is 'mean', the other options are 'median', 'sum', 'min', 'max' and 'quantile'.
quantile_prob	numeric value between 0 and 1 specifying the quantile probability used when aggregate_function = 'quantile'. For example, quantile_prob = 0.95 calculates the 95th percentile. The default is 0.5.
temporal_stability_check	character string, specifying, how temporal stability between the optimal selection and response variable(s) will be analysed. Current possibilities are "sequential", "progressive" and "running_window". Sequential check will split data into k splits and calculate selected metric for each split. Progressive check will split data into k splits, calculate metric for the first split and then progressively add 1 split at a time and calculate selected metric. For running window, select the length of running window with the k_running_window argument.
k	integer, number of breaks (splits) for temporal stability and cross validation analysis.
k_running_window	the length of running window for temporal stability check. Applicable only if temporal_stability argument is set to running window.
cross_validation_type	character string, specifying, how to perform cross validation between the optimal selection and response variables. If the argument is set to "blocked", years will not be shuffled. If the argument is set to "randomized", years will be shuffled.
subset_years	a subset of years to be analyzed. Should be given in the form of subset_years = c(1980, 2005)
ylimits	limit of the y axes for plot_extreme. It should be given in the form of: ylimits = c(0,1)
seed	optional seed argument for reproducible results
tidy_env_data	if set to TRUE, env_data should be inserted as a data frame with three columns: "Year", "DOY", "Precipitation/Temperature/etc."
reference_window	character string, the reference_window argument describes, how each calculation is referred. There are three different options: 'start' (default), 'end' and 'middle'. If the reference_window argument is set to 'start', then each calculation is related to the starting day of window. If the reference_window argument

is set to 'middle', each calculation is related to the middle day of window calculation. If the reference_window argument is set to 'end', then each calculation is related to the ending day of window calculation. For example, if we consider correlations with window from DOY 15 to DOY 35. If reference window is set to 'start', then this calculation will be related to the DOY 15. If the reference window is set to 'end', then this calculation will be related to the DOY 35. If the reference_window is set to 'middle', then this calculation is related to DOY 25. The optimal selection, which describes the optimal consecutive days that returns the highest calculated metric and is obtained by the \$plot_extreme output, is the same for all three reference windows.

boot	logical, if TRUE, bootstrap procedure will be used to calculate estimates correlation coefficients, R squared or adjusted R squared metrics
boot_n	The number of bootstrap replicates
boot_ci_type	A character string representing the type of bootstrap intervals required. The value should be any subset of the values c("norm", "basic", "stud", "perc", "bca").
boot_conf_int	A scalar or vector containing the confidence level(s) of the required interval(s)
day_interval	a vector of two values defining the interval of days used for calculations. Positive values indicate days in the current year. Negative values indicate days in the previous-year block and are used only when previous_year = TRUE. If previous_year = FALSE and negative values are supplied, day_interval is ignored, a warning is issued, and the analysis is performed for the current year only using day_interval = c(1, 366). If number_previous_years > 1, the previous-year block starts with the earliest included previous year. For example, previous_year = TRUE, number_previous_years = 2 and day_interval = c(-1, 366) analyses the full sequence from DOY 1 of year t - 2 to DOY 366 of year t.
dc_method	a character string to determine the method to detrend climate data. Possible values are "none" (default) and "SLD" which refers to Simple Linear Detrending
cor_na_use	an optional character string giving a method for computing covariances in the presence of missing values for correlation coefficients. This must be (an abbreviation of) one of the strings "everything" (default), "all.obs", "complete.obs", "na.or.complete", or "pairwise.complete.obs". See also the documentation for the base cor() function.
skip_window_length	an integer specifying the frequency of window selection for the calculations of climate-growth relationships. The default value is 1, indicating that every window is included in the calculations. When set to a value greater than 1, the function selectively processes windows at regular intervals defined by this parameter. For instance, if skip_window_length = 2, the function processes every second window. Similarly, if skip_window_length = 3, every third window is processed, skipping two windows in between each selected one. This parameter allows for controlling the granularity of the analysis and can help in reducing computation time by focusing on a subset of the data.
skip_window_position	an integer specifying the frequency of window positions used in the calculations of climate-growth relationships. The default value is 1, indicating that every window position is included in the calculations. When set to a value greater than

1, the function selectively processes window positions at regular intervals defined by this parameter. For instance, if `skip_window_position = 2`, the function processes every second window position. Similarly, if `skip_window_position = 3`, every third window position is processed, skipping two positions in between each selected one. This parameter allows for controlling the granularity of the analysis and can help in reducing computation time by focusing on a subset of the data.

Value

a list with 19 elements:

1. `$calculations` - a matrix with calculated metrics
2. `$method` - the character string of a method
3. `$metric` - the character string indicating the metric used for calculations
4. `$analysed_period` - the character string specifying the analysed period based on the information from row names. If there are no row names, this argument is given as NA
5. `$optimized_return` - data frame with two columns, response variable and aggregated (averaged) daily data that return the optimal results. This data.frame could be directly used to calibrate a model for climate reconstruction
6. `$optimized_return_all` - a data frame with aggregated daily data, that returned the optimal result for the entire `env_data` (and not only subset of analysed years)
7. `$transfer_function` - a ggplot object: scatter plot of optimized return and a transfer line of the selected method
8. `$temporal_stability` - a data frame with calculations of selected metric for different temporal subsets
9. `$cross_validation` - a data frame with cross validation results
10. `$plot_heatmap` - ggplot2 object: a heatmap of calculated metrics
11. `$plot_extreme` - ggplot2 object: line plot of a row with the highest value in a matrix of calculated metrics
12. `$type` - the character string describing type of analysis: daily or monthly
13. `$reference_window` - character string, which reference window was used for calculations
14. `$boot_lower` - matrix with lower limit of confidence intervals of bootstrap calculations
15. `$boot_upper` - matrix with upper limit of confidence intervals of bootstrap calculations
16. `$aggregated_climate` - matrix with all aggregated climate series
17. `$previous_year` - logical indicating whether previous-year climate data were used
18. `$number_previous_years` - integer indicating how many previous years were used

Examples

```
# The examples below are enclosed within donttest{} to minimize the execution
# time during R package checks. Additionally, all examples include the
# parameters `skip_window_length` and `skip_window_position`, which limit the
```



```
    skip_window_length = 50,
    skip_window_position = 50)

example_MVA_late <- daily_response(response = data_MVA,
  env_data = LJ_daily_temperatures,
  method = "cor", lower_limit = 21, upper_limit = 60,
  row_names_subset = TRUE, previous_year = TRUE,
  remove_insignificant = TRUE, alpha = 0.05,
  subset_years = c(1981, 2010),
  skip_window_length = 50,
  skip_window_position = 50)

# plot(example_MVA_early, type = 1)
# plot(example_MVA_late, type = 1)
# plot(example_MVA_early, type = 2)
# plot(example_MVA_late, type = 2)

# 3 Example with negative correlations
example_neg_cor <- daily_response(response = data_TRW_1,
  env_data = LJ_daily_temperatures, previous_year = TRUE,
  method = "cor", lower_limit = 21, upper_limit = 90,
  row_names_subset = TRUE, remove_insignificant = TRUE,
  alpha = 0.05, skip_window_length = 50,
  skip_window_position = 50)

# summary(example_neg_cor)
# plot(example_neg_cor, type = 1)
# plot(example_neg_cor, type = 2)

# 4 Example of multiproxy analysis
# summary(example_proxies_1)
# cor(example_proxies_1)

example_multiproxy <- daily_response(response = example_proxies_1,
  env_data = LJ_daily_temperatures,
  method = "lm", metric = "adj.r.squared",
  lower_limit = 21, upper_limit = 180,
  row_names_subset = TRUE, previous_year = FALSE,
  remove_insignificant = TRUE, alpha = 0.05,
  skip_window_length = 50,
  skip_window_position = 50)

# plot(example_multiproxy, type = 1)

# 5 Example to test the temporal stability
example_MVA_ts <- daily_response(response = data_MVA,
  env_data = LJ_daily_temperatures, method = "brnn",
  lower_limit = 100, metric = "adj.r.squared", upper_limit = 180,
  row_names_subset = TRUE, remove_insignificant = TRUE, alpha = 0.05,
  temporal_stability_check = "running_window", k_running_window = 10,
  skip_window_length = 50, skip_window_position = 50)

# Check the results for temporal stability
```

```
# example_MVA_ts$temporal_stability

# 6 Example with nonlinear brnn estimation
example_brnn <- daily_response(response = data_MVA,
  env_data = LJ_daily_temperatures, method = "brnn", boot = FALSE,
  lower_limit = 100, metric = "adj.r.squared", upper_limit = 101,
  row_names_subset = TRUE, remove_insignificant = TRUE, boot_n = 10,
  skip_window_length = 50, skip_window_position = 50)

# summary(example_brnn)

# Example using quantiles for the aggregation
example_q95 <- daily_response(
  response = data_MVA,
  env_data = LJ_daily_temperatures,
  method = "cor",
  fixed_width = 30,
  row_names_subset = TRUE,
  previous_year = TRUE,
  aggregate_function = "quantile",
  quantile_prob = 0.95
)

# Example using two previous years plus the current year
example_two_previous_years <- daily_response(
  response = data_MVA,
  env_data = LJ_daily_temperatures,
  method = "cor",
  fixed_width = 60,
  row_names_subset = TRUE,
  previous_year = TRUE,
  number_previous_years = 2,
  day_interval = c(-1, 250),
  skip_window_length = 50,
  skip_window_position = 50
)

# Example with previous-previous year effects
example_basic <- daily_response(response = data_MVA,
  env_data = LJ_daily_temperatures,
  row_names_subset = TRUE,
  reference_window = "end",
  lower_limit = 35, upper_limit = 75,
  previous_year = TRUE,
  remove_insignificant = TRUE,
  number_previous_years = 3)

plot_heatmap(example_basic)
plot_extreme(example_basic)
summary(example_basic)
```

daily_response_seascorr
daily_response_seascorr

Description

Function calculates all possible partial correlation coefficients between tree-ring chronology and daily environmental (usually climate) data. Calculations are based on moving window which is defined with two arguments: `lower_limit` and `upper_limit`. All calculated (partial) correlation coefficients are stored in a matrix. The location of stored correlation in the matrix is indicating a window width (row names) and a location in a matrix of daily sequences of environmental data (column names).

Usage

```
daily_response_seascorr(  
  response,  
  env_data_primary,  
  env_data_control,  
  lower_limit = 30,  
  upper_limit = 90,  
  fixed_width = 0,  
  previous_year = FALSE,  
  number_previous_years = NULL,  
  pcor_method = "pearson",  
  remove_insignificant = TRUE,  
  alpha = 0.05,  
  row_names_subset = FALSE,  
  aggregate_function_env_data_primary = "mean",  
  quantile_prob_env_data_primary = 0.5,  
  aggregate_function_env_data_control = "mean",  
  quantile_prob_env_data_control = 0.5,  
  temporal_stability_check = "sequential",  
  k = 2,  
  k_running_window = 30,  
  subset_years = NULL,  
  ylimits = NULL,  
  seed = NULL,  
  tidy_env_data_primary = FALSE,  
  tidy_env_data_control = FALSE,  
  reference_window = "start",  
  boot = FALSE,  
  boot_n = 1000,  
  boot_ci_type = "norm",  
  boot_conf_int = 0.95,  
  day_interval = NULL,  
  dc_method = NULL,  
)
```

```

pcor_na_use = "pairwise.complete",
skip_window_length = 1,
skip_window_position = 1
)

```

Arguments

- response** a data frame with tree-ring proxy variable and (optional) years as row names. Row.names should be matched with those from env_data_primary and env_data_control data frame. If not, set the row_names_subset argument to TRUE.
- env_data_primary** primary data frame of daily sequences of environmental data as columns and years as row names. Each row represents a year and each column represents a day of a year. Row.names should be matched with those from the response data frame. If not, set the argument row_names_subset to TRUE. Alternatively, env_data_primary could be a tidy data with three columns, i.e. Year, DOY and third column representing values of mean temperatures, sum of precipitation etc. If tidy data is passed to the function, set the argument tidy_env_data_primary to TRUE.
- env_data_control** a data frame of daily sequences of environmental data as columns and years as row names. This data is used as control for calculations of partial correlation coefficients. Each row represents a year and each column represents a day of a year. Row.names should be matched with those from the response data frame. If not, set the row_names_subset argument to TRUE. Alternatively, env_data_control could be a tidy data with three columns, i.e. Year, DOY and third column representing values of mean temperatures, sum of precipitation etc. If tidy data is passed to the function, set the argument tidy_env_data_control to TRUE.
- lower_limit** lower limit of window width
- upper_limit** upper limit of window width
- fixed_width** fixed width used for calculation. If fixed_width is assigned a value, upper_limit and lower_limit will be ignored
- previous_year** logical. Master switch for previous-year analyses. If FALSE, only the current year is analysed and number_previous_years is ignored. If TRUE, previous-year climate data are included.
- number_previous_years** integer between 1 and 5 specifying how many previous years should be included when previous_year = TRUE. For example, number_previous_years = 2 uses climate data from years t - 2, t - 1 and t for response year t. If previous_year = TRUE and number_previous_years is NULL, one previous year is used for backward compatibility.
- pcor_method** a character string indicating which partial correlation coefficient is to be computed. One of "pearson" (default), "kendall", or "spearman", can be abbreviated.
- remove_ insignificant** if set to TRUE, removes all correlations below the significant threshold level, based on a selected alpha.

alpha	significance level used to remove insignificant calculations.
row_names_subset	if set to TRUE, row.names are used to subset env_data_primary, env_data_control and response data frames. Only years from all three data frames are kept.
aggregate_function_env_data_primary	character string specifying how the daily data from env_data_primary should be aggregated. The default is 'mean', the other options are 'median', 'sum', 'min', 'max' and 'quantile'.
quantile_prob_env_data_primary	numeric value between 0 and 1 specifying the quantile probability used when aggregate_function_env_data_primary = 'quantile'. For example, 0.95 calculates the 95th percentile. The default is 0.5.
aggregate_function_env_data_control	character string specifying how the daily data from env_data_control should be aggregated. The default is 'mean', the other options are 'median', 'sum', 'min', 'max' and 'quantile'.
quantile_prob_env_data_control	numeric value between 0 and 1 specifying the quantile probability used when aggregate_function_env_data_control = 'quantile'. For example, 0.95 calculates the 95th percentile. The default is 0.5.
temporal_stability_check	character string, specifying how temporal stability between the optimal selection and response variable(s) will be analysed. Current possibilities are "sequential", "progressive" and "running_window". Sequential check will split data into k splits and calculate selected metric for each split. Progressive check will split data into k splits, calculate metric for the first split and then progressively add 1 split at a time and calculate selected metric. For running window, select the length of running window with the k_running_window argument.
k	integer, number of breaks (splits) for temporal stability
k_running_window	the length of running window for temporal stability check. Applicable only if temporal_stability argument is set to running window.
subset_years	a subset of years to be analyzed. Should be given in the form of subset_years = c(1980, 2005)
ylimits	limit of the y axes for plot_extreme It should be given in the form of: ylimits = c(0,1)
seed	optional seed argument for reproducible results
tidy_env_data_primary	if set to TRUE, env_data_primary should be inserted as a data frame with three columns: "Year", "DOY", "Precipitation/Temperature/etc."
tidy_env_data_control	if set to TRUE, env_data_control should be inserted as a data frame with three columns: "Year", "DOY", "Precipitation/Temperature/etc."
reference_window	character string, the reference_window argument describes, how each calculation is referred. There are three different options: 'start' (default), 'end' and

'middle'. If the reference_window argument is set to 'start', then each calculation is related to the starting day of window. If the reference_window argument is set to 'middle', each calculation is related to the middle day of window calculation. If the reference_window argument is set to 'end', then each calculation is related to the ending day of window calculation. For example, if we consider correlations with window from DOY 15 to DOY 35. If reference window is set to 'start', then this calculation will be related to the DOY 15. If the reference window is set to 'end', then this calculation will be related to the DOY 35. If the reference_window is set to 'middle', then this calculation is related to DOY 25. The optimal selection, which describes the optimal consecutive days that returns the highest calculated metric and is obtained by the \$plot_extreme output, is the same for all three reference windows.

boot	logical, if TRUE, bootstrap procedure will be used to calculate partial correlation coefficients
boot_n	The number of bootstrap replicates
boot_ci_type	A character string representing the type of bootstrap intervals required. The value should be any subset of the values c("norm", "basic", "stud", "perc", "bca").
boot_conf_int	A scalar or vector containing the confidence level(s) of the required interval(s)
day_interval	a vector of two values defining the interval of days used for calculations. Positive values indicate days in the current year. Negative values indicate days in the previous-year block. If previous_year = FALSE, negative values in day_interval are ignored with a warning and the analysis is performed for the current year only using day_interval = c(1, 366). If previous_year = TRUE and number_previous_years > 1, the previous-year block starts with the earliest included previous year. For example, previous_year = TRUE, number_previous_years = 2 and day_interval = c(-1, 366) analyses the full sequence from DOY 1 of year t - 2 to DOY 366 of year t.
dc_method	a character string to determine the method to detrend climate data. Possible values are "none" (default) and "SLD" which refers to Simple Linear Detrending
pcor_na_use	an optional character string giving a method for computing covariances in the presence of missing values for partial correlation coefficients. This must be (an abbreviation of) one of the strings "all.obs", "everything", "complete.obs", "na.or.complete", or "pairwise.complete.obs" (default). See also the documentation for the base partial.r in psych R package
skip_window_length	an integer specifying the frequency of window selection for the calculations of climate-growth relationships. The default value is 1, indicating that every window is included in the calculations. When set to a value greater than 1, the function selectively processes windows at regular intervals defined by this parameter. For instance, if skip_window_length = 2, the function processes every second window. Similarly, if skip_window_length = 3, every third window is processed, skipping two windows in between each selected one. This parameter allows for controlling the granularity of the analysis and can help in reducing computation time by focusing on a subset of the data.
skip_window_position	an integer specifying the frequency of window positions used in the calculations of climate-growth relationships. The default value is 1, indicating that every

window position is included in the calculations. When set to a value greater than 1, the function selectively processes window positions at regular intervals defined by this parameter. For instance, if `skip_window_position = 2`, the function processes every second window position. Similarly, if `skip_window_position = 3`, every third window position is processed, skipping two positions in between each selected one. This parameter allows for controlling the granularity of the analysis and can help in reducing computation time by focusing on a subset of the data.

Value

a list with 15 elements:

1. `$calculations` - a matrix with calculated metrics
2. `$method` - the character string of a method
3. `$metric` - the character string indicating the metric used for calculations
4. `$analysed_period` - the character string specifying the analysed period based on the information from row names. If there are no row names, this argument is given as NA
5. `$optimized_return` - data frame with two columns, response variable and aggregated (averaged) daily data that return the optimal results. This data.frame could be directly used to calibrate a model for climate reconstruction
6. `$optimized_return_all` - a data frame with aggregated daily data, that returned the optimal result for the entire `env_data_primary` (and not only subset of analysed years)
7. `$transfer_function` - a ggplot object: scatter plot of optimized return and a transfer line of the selected method
8. `$temporal_stability` - a data frame with calculations of selected metric for different temporal subsets
9. `$cross_validation` - not available for partial correlations
10. `$plot_heatmap` - ggplot2 object: a heatmap of calculated metrics
11. `$plot_extreme` - ggplot2 object: line plot of a row with the highest value in a matrix of calculated metrics
12. `$type` - the character string describing type of analysis: daily or monthly
13. `$reference_window` - character string, which reference window was used for calculations
14. `$aggregated_climate_primary` - matrix with all aggregated climate series of primary data
15. `$aggregated_climate_control` - matrix with all aggregated climate series of control data

Examples

```
# The examples below are enclosed within donttest{} to minimize the execution
# time during R package checks. Additionally, all examples include the
# parameters `skip_window_length` and `skip_window_position`, which limit the
# number of combinations evaluated in climate-growth correlation calculations.
# To explore all possible combinations, users should set both parameters to 1.

# Load the dendroTools R package
```



```

        skip_window_position = 50,
        skip_window_length= 50)

# summary(example_fixed_width)
# plot(example_fixed_width, type = 1)
# plot(example_fixed_width, type = 2)
# example_fixed_width$optimized_return
# example_fixed_width$optimized_return_all

# 3 Example using quantiles for primary and control variables
example_quantile <- daily_response_seascorr(
  response = data_MVA,
  env_data_primary = LJ_daily_temperatures,
  env_data_control = LJ_daily_precipitation,
  row_names_subset = TRUE,
  fixed_width = 30,
  previous_year = TRUE,
  aggregate_function_env_data_primary = "quantile",
  quantile_prob_env_data_primary = 0.95,
  aggregate_function_env_data_control = "quantile",
  quantile_prob_env_data_control = 0.95,
  tidy_env_data_primary = FALSE,
  tidy_env_data_control = TRUE,
  skip_window_position = 50
)

# 4 Example using two previous years plus the current year
example_two_previous_years <- daily_response_seascorr(
  response = data_MVA,
  env_data_primary = LJ_daily_temperatures,
  env_data_control = LJ_daily_precipitation,
  row_names_subset = TRUE,
  fixed_width = 60,
  previous_year = TRUE,
  number_previous_years = 2,
  day_interval = c(-1, 250),
  tidy_env_data_primary = FALSE,
  tidy_env_data_control = TRUE,
  skip_window_position = 50
)

```

dataset_MVA

MVA and mean April temperature

Description

A dataset with a mean vessel area (MVA) chronology of *Quercus robur* from a lowland oak forest in Eastern Slovenia and a mean April temperature. This dataset includes years for the period 2012-

1934. For a detailed description about the MVA chronology development, sampling site and the calculations of mean monthly correlations, see Jevšenak and Levanič (2015).

Usage

dataset_MVA

Format

A data frame with 79 rows and 2 variables:

MVA Mean vessel area measurements from 2012 - 1934

T_Apr Mean April temperature for the meteorological station Maribor from 2012 - 1934

Source

Jevšenak J., Levanič T. 2015. Dendrochronological and wood-anatomical features of differently vital pedunculate oak (*Quercus robur* L.) stands and their response to climate. *Topola*, 195/196: 85-96

dataset_MVA_individual

Example of dataset with individual chronologies of MVA and mean April temperature

Description

A dataset of individual tree-ring chronologies from a lowland forest in Slovenia. The first row represents a value of a year in 2015.

Usage

dataset_MVA_individual

Format

A data frame with 56 rows and 54 columns :

T_Apr mean April temperature for Ljubljana

MVA_1 Mean vessel area chronology for tree 1

MVA_2 Mean vessel area chronology for tree 2 [mm²]

MVA_3 Mean vessel area chronology for tree 3 [mm²]

MVA_4 Mean vessel area chronology for tree 4 [mm²]

MVA_5 Mean vessel area chronology for tree 5 [mm²]

MVA_6 Mean vessel area chronology for tree 6 [mm²]

MVA_7 Mean vessel area chronology for tree 7 [mm²]

MVA_8 Mean vessel area chronology for tree 8 [mm²]

MVA_9 Mean vessel area chronology for tree 9 [mm²]

MVA_10 Mean vessel area chronology for tree 10 [mm²]

Source

Slovenian Forestry Institute, Večna pot 2, Ljubljana, Slovenia

dataset_TRW

TRW and mean June - July temperature from Albania

Description

A dataset with a tree-ring width (TRW) chronology of *Pinus nigra* from Albania and mean June-July temperature. This TRW chronology has a span of 59 years (period 2009 - 1951) and was already used to reconstruct summer temperatures by Levanič et al. (2015). In this paper, all the details about sample replication, site description and correlation statistics are described.

Usage

dataset_TRW

Format

A data frame with 59 rows and 2 variables:

TRW Standardised tree-ring width chronology of *Pinus nigra* from Albania

T_Jun_Jul Mean June - July temperature for Albania downloaded from KNMI Climate Explorer

Source

Levanič, T., Poljanšek, S., Toromani, E., 2015. Early summer temperatures reconstructed from black pine (*Pinus nigra* Arnold) tree-ring widths from Albania. *The Holocene* 25, 469-481.

dataset_TRW_complete	<i>The complete dataset of standardized tree-ring chronology from Albania</i>
----------------------	-------------------------------------------------------------------------------

Description

A dataset with a tree-ring width (TRW) chronology of *Pinus nigra* from Albania. This TRW chronology has a span of 551 years (period 2009 - 1459) and was already used to reconstruct summer temperatures by Levanič et al. (2015). In this paper, all the details about sample replication, site description and correlation statistics are described.

Usage

dataset_TRW_complete

Format

A data frame with 551 rows and 1 variable:

TRW Standardised tree-ring width chronology of *Pinus nigra* from Albania

Source

Levanič, T., Poljanšek, S., Toromani, E., 2015. Early summer temperatures reconstructed from black pine (*Pinus nigra* Arnold) tree-ring widths from Albania. *The Holocene* 25, 469-481.

data_MVA	<i>Mean vessel area example proxy from 2012 - 1940</i>
----------	--------------------------------------------------------

Description

A dataset with MVA proxy records from a lowland forest Mlače in Slovenia. The first row represents a value of a year in 2012. Row names represent years.

Usage

data_MVA

Format

A data frame with 73 rows and 1 variable:

MVA Mean vessel area [mm²] indices from 2012 - 1940

Source

Jernej Jevšenak, Slovenian Forestry Institute, Večna pot 2, Ljubljana, Slovenia

data_transform	<i>data_transform</i>
----------------	-----------------------

Description

Transforms daily data with two columns (date and variable) into data frame suitable for daily or monthly analysis with dendroTools.

Usage

```
data_transform(
  input,
  format = "daily",
  monthly_aggregate_function = "auto",
  date_format = "ymd"
)
```

Arguments

input	typical daily data format: Data frame with two columns, first column represents date, second column represents variable, such as mean temperature, precipitation, etc. Date should be in format Year-Month-Day (e.g. "2019-05-15")
format	character string indicating the desired output format. Should be "daily" or "monthly". Daily format returns a data frame with 366 columns (days), while monthly format returns data frame with 12 columns (months). Years are indicated as row names.
monthly_aggregate_function	character string indicating, how to aggregate daily into monthly data. It can be "mean" or "sum". Third option is "auto" (default). In this case function will try to guess whether input is temperature or precipitation data. For temperature, it will use "mean", for precipitation "sum".
date_format	Describe the format of date. It should be one of "ymd", "ydm", "myd", "mdy", "dmy", "dym".

Value

env_data suitable for daily or monthly analysis with dendroTools.

Examples

```
data(swit272_daily_temperatures)
proper_daily_data <- data_transform(swit272_daily_temperatures, format = "daily",
  date_format = "ymd")

proper_monthly_data <- data_transform(swit272_daily_temperatures, format = "monthly",
  date_format = "ymd")
```

```

data(swit272_daily_precipitation)
proper_daily_data <- data_transform(swit272_daily_precipitation, format = "daily",
  date_format = "ymd")

proper_monthly_data <- data_transform(swit272_daily_precipitation, format = "monthly",
  date_format = "ymd")

```

data_TRW

Tree-ring width (TRW) example proxy from 1981 - 1757

Description

A dataset with TRW proxy records from a site in Slovenian Alps - Vrsic. The first row represents a TRW value in a year 1757. Row names represent years.

Usage

```
data_TRW
```

Format

A data frame with 225 rows and 1 variable:

TRW residual TRW indices from 1981 - 1757

Source

- Schweingruber, F.H., 1981. Vrsic Krajnska Gora - PCAB - ITRDB YUGO001.
- <https://www.ncei.noaa.gov/access/paleo-search/study/4728>

data_TRW_1

Tree-ring width (TRW) data from 2012 - 1961

Description

A dataset of tree-ring widths (TRW) from a site in Krakovo forest (Slovenia). The first row represents a value of a year in 1961.

Usage

```
data_TRW_1
```

Format

A data frame with 52 rows and 1 variable:

TRW Standardized tree-ring width indices from 2012 - 1961

Source

Tom Levanič, Slovenian Forestry Institute, Večna pot 2, Ljubljana, Slovenia

example_dataset_1 *Example of dataset as required for compare_methods()*

Description

A dataset of Mean Vessel Area (MVA) tree-ring parameter from a lowland forest in Slovenia. The first row represents a value of a year in 2012.

Usage

example_dataset_1

Format

A data frame with 58 rows and 3 columns :

MVA Mean Vessel Area measurements from 2012 - 1955

T_APR Mean April temperatures from 2012 - 1955

T_aug_sep Mean August-September temperatures from preceding growing season from 2012 - 1955

Source

Jernej Jevšenak, Slovenian Forestry Institute, Večna pot 2, Ljubljana, Slovenia

example_proxies_1 *Tree-ring example proxies 1 from 2015 - 1961*

Description

A dataset with three tree-ring proxy records from a site near Ljubljana (Slovenia). The first row represents a value of a year in 1961. The three proxy records are MVA (Mean vessel area [mm²]), O (stable oxygen isotope ratios) and TRW (Tree-ring widths)

Usage

example_proxies_1

Format

A data frame with 55 rows and 3 variables:

MVA Mean vessel area [mm²] indices from 2015 - 1961

O18 Scaled Stable oxygen isotope ratios from 2015 - 1961

TRW Tree-ring widths from 2015 - 1961

Source

Jernej Jevšenak, Slovenian Forestry Institute, Večna pot 2, Ljubljana, Slovenia

example_proxies_individual

Example of dataset with individual chronologies of MVA.

Description

A dataset of individual tree-ring chronologies from a lowland forest in Slovenia. The first row represents a value of a year in 2015.

Usage

example_proxies_individual

Format

A data frame with 56 rows and 54 columns :

MVA_1 Mean vessel area chronology for tree 1

MVA_2 Mean vessel area chronology for tree 2

MVA_3 Mean vessel area chronology for tree 3

MVA_4 Mean vessel area chronology for tree 4

MVA_5 Mean vessel area chronology for tree 5

MVA_6 Mean vessel area chronology for tree 6

MVA_7 Mean vessel area chronology for tree 7

MVA_8 Mean vessel area chronology for tree 8

MVA_9 Mean vessel area chronology for tree 9

MVA_10 Mean vessel area chronology for tree 10

Source

Jernej Jevšenak, Slovenian Forestry Institute, Večna pot 2, Ljubljana, Slovenia

`glimpse_daily_data` *glimpse_daily_data*

Description

Visual presentation of daily data to spot missing values.

Usage

```
glimpse_daily_data(  
  env_data,  
  na.color = "red",  
  low_color = "blue",  
  high_color = "green",  
  tidy_env_data = FALSE  
)
```

Arguments

<code>env_data</code>	a data frame of daily sequences of environmental data as columns and years as row names. Each row represents a year and each column represents a day of a year. Alternatively, <code>env_data</code> could be a tidy data with three columns, i.e. Year, DOY and third column representing values of mean temperatures, sum of precipitation etc. If tidy data is passed to the function, set the argument <code>tidy_env_data</code> to TRUE.
<code>na.color</code>	color to use for missing values
<code>low_color</code>	colours for low end of the gradient
<code>high_color</code>	colours for high end of the gradient
<code>tidy_env_data</code>	if set to TRUE, <code>env_data</code> should be inserted as a data frame with three columns: "Year", "DOY", "Precipitation/Temperature/etc."

Examples

```
library(dendroTools)  
data("LJ_daily_temperatures")  
# glimpse_daily_data(env_data = LJ_daily_temperatures,  
# tidy_env_data = FALSE, na.color = "white")  
  
data("LJ_daily_precipitation")  
# glimpse_daily_data(env_data = LJ_daily_precipitation,  
#   tidy_env_data = TRUE, na.color = "white")
```

KRE_daily_temperatures

*Daily mean temperatures for Kredarica (Alps in Slovenia) from 2017
- 1955*

Description

A dataset of daily mean temperatures in Kredarica (Slovenia). The first row represents temperatures in 1955. The first column represents the first day of a year, the second column represents the second day of a year, etc. Row names represent years.

Usage

```
KRE_daily_temperatures
```

Format

A data frame with 63 rows and 366 variables:

- X1** Temperatures on the day 1 of a year
- X2** Temperatures on the day 2 of a year
- X3** Temperatures on the day 3 of a year
- X4** Temperatures on the day 4 of a year
- X5** Temperatures on the day 5 of a year
- X6** Temperatures on the day 6 of a year
- X7** Temperatures on the day 7 of a year
- X8** Temperatures on the day 8 of a year
- X9** Temperatures on the day 9 of a year
- X10** Temperatures on the day 10 of a year
- X11** Temperatures on the day 11 of a year
- X12** Temperatures on the day 12 of a year
- X13** Temperatures on the day 13 of a year
- X14** Temperatures on the day 14 of a year
- X15** Temperatures on the day 15 of a year
- X16** Temperatures on the day 16 of a year
- X17** Temperatures on the day 17 of a year
- X18** Temperatures on the day 18 of a year
- X19** Temperatures on the day 19 of a year
- X20** Temperatures on the day 20 of a year
- X21** Temperatures on the day 21 of a year
- X22** Temperatures on the day 22 of a year

- X23** Temperatures on the day 23 of a year
- X24** Temperatures on the day 24 of a year
- X25** Temperatures on the day 25 of a year
- X26** Temperatures on the day 26 of a year
- X27** Temperatures on the day 27 of a year
- X28** Temperatures on the day 28 of a year
- X29** Temperatures on the day 29 of a year
- X30** Temperatures on the day 30 of a year
- X31** Temperatures on the day 31 of a year
- X32** Temperatures on the day 32 of a year
- X33** Temperatures on the day 33 of a year
- X34** Temperatures on the day 34 of a year
- X35** Temperatures on the day 35 of a year
- X36** Temperatures on the day 36 of a year
- X37** Temperatures on the day 37 of a year
- X38** Temperatures on the day 38 of a year
- X39** Temperatures on the day 39 of a year
- X40** Temperatures on the day 40 of a year
- X41** Temperatures on the day 41 of a year
- X42** Temperatures on the day 42 of a year
- X43** Temperatures on the day 43 of a year
- X44** Temperatures on the day 44 of a year
- X45** Temperatures on the day 45 of a year
- X46** Temperatures on the day 46 of a year
- X47** Temperatures on the day 47 of a year
- X48** Temperatures on the day 48 of a year
- X49** Temperatures on the day 49 of a year
- X50** Temperatures on the day 50 of a year
- X51** Temperatures on the day 51 of a year
- X52** Temperatures on the day 52 of a year
- X53** Temperatures on the day 53 of a year
- X54** Temperatures on the day 54 of a year
- X55** Temperatures on the day 55 of a year
- X56** Temperatures on the day 56 of a year
- X57** Temperatures on the day 57 of a year
- X58** Temperatures on the day 58 of a year
- X59** Temperatures on the day 59 of a year

- X60** Temperatures on the day 60 of a year
- X61** Temperatures on the day 61 of a year
- X62** Temperatures on the day 62 of a year
- X63** Temperatures on the day 63 of a year
- X64** Temperatures on the day 64 of a year
- X65** Temperatures on the day 65 of a year
- X66** Temperatures on the day 66 of a year
- X67** Temperatures on the day 67 of a year
- X68** Temperatures on the day 68 of a year
- X69** Temperatures on the day 69 of a year
- X70** Temperatures on the day 70 of a year
- X71** Temperatures on the day 71 of a year
- X72** Temperatures on the day 72 of a year
- X73** Temperatures on the day 73 of a year
- X74** Temperatures on the day 74 of a year
- X75** Temperatures on the day 75 of a year
- X76** Temperatures on the day 76 of a year
- X77** Temperatures on the day 77 of a year
- X78** Temperatures on the day 78 of a year
- X79** Temperatures on the day 79 of a year
- X80** Temperatures on the day 80 of a year
- X81** Temperatures on the day 81 of a year
- X82** Temperatures on the day 82 of a year
- X83** Temperatures on the day 83 of a year
- X84** Temperatures on the day 84 of a year
- X85** Temperatures on the day 85 of a year
- X86** Temperatures on the day 86 of a year
- X87** Temperatures on the day 87 of a year
- X88** Temperatures on the day 88 of a year
- X89** Temperatures on the day 89 of a year
- X90** Temperatures on the day 90 of a year
- X91** Temperatures on the day 91 of a year
- X92** Temperatures on the day 92 of a year
- X93** Temperatures on the day 93 of a year
- X94** Temperatures on the day 94 of a year
- X95** Temperatures on the day 95 of a year
- X96** Temperatures on the day 96 of a year

- X97** Temperatures on the day 97 of a year
- X98** Temperatures on the day 98 of a year
- X99** Temperatures on the day 99 of a year
- X100** Temperatures on the day 100 of a year
- X101** Temperatures on the day 101 of a year
- X102** Temperatures on the day 102 of a year
- X103** Temperatures on the day 103 of a year
- X104** Temperatures on the day 104 of a year
- X105** Temperatures on the day 105 of a year
- X106** Temperatures on the day 106 of a year
- X107** Temperatures on the day 107 of a year
- X108** Temperatures on the day 108 of a year
- X109** Temperatures on the day 109 of a year
- X110** Temperatures on the day 110 of a year
- X111** Temperatures on the day 111 of a year
- X112** Temperatures on the day 112 of a year
- X113** Temperatures on the day 113 of a year
- X114** Temperatures on the day 114 of a year
- X115** Temperatures on the day 115 of a year
- X116** Temperatures on the day 116 of a year
- X117** Temperatures on the day 117 of a year
- X118** Temperatures on the day 118 of a year
- X119** Temperatures on the day 119 of a year
- X120** Temperatures on the day 120 of a year
- X121** Temperatures on the day 121 of a year
- X122** Temperatures on the day 122 of a year
- X123** Temperatures on the day 123 of a year
- X124** Temperatures on the day 124 of a year
- X125** Temperatures on the day 125 of a year
- X126** Temperatures on the day 126 of a year
- X127** Temperatures on the day 127 of a year
- X128** Temperatures on the day 128 of a year
- X129** Temperatures on the day 129 of a year
- X130** Temperatures on the day 130 of a year
- X131** Temperatures on the day 131 of a year
- X132** Temperatures on the day 132 of a year
- X133** Temperatures on the day 133 of a year

X134 Temperatures on the day 134 of a year
X135 Temperatures on the day 135 of a year
X136 Temperatures on the day 136 of a year
X137 Temperatures on the day 137 of a year
X138 Temperatures on the day 138 of a year
X139 Temperatures on the day 139 of a year
X140 Temperatures on the day 140 of a year
X141 Temperatures on the day 141 of a year
X142 Temperatures on the day 142 of a year
X143 Temperatures on the day 143 of a year
X144 Temperatures on the day 144 of a year
X145 Temperatures on the day 145 of a year
X146 Temperatures on the day 146 of a year
X147 Temperatures on the day 147 of a year
X148 Temperatures on the day 148 of a year
X149 Temperatures on the day 149 of a year
X150 Temperatures on the day 150 of a year
X151 Temperatures on the day 151 of a year
X152 Temperatures on the day 152 of a year
X153 Temperatures on the day 153 of a year
X154 Temperatures on the day 154 of a year
X155 Temperatures on the day 155 of a year
X156 Temperatures on the day 156 of a year
X157 Temperatures on the day 157 of a year
X158 Temperatures on the day 158 of a year
X159 Temperatures on the day 159 of a year
X160 Temperatures on the day 160 of a year
X161 Temperatures on the day 161 of a year
X162 Temperatures on the day 162 of a year
X163 Temperatures on the day 163 of a year
X164 Temperatures on the day 164 of a year
X165 Temperatures on the day 165 of a year
X166 Temperatures on the day 166 of a year
X167 Temperatures on the day 167 of a year
X168 Temperatures on the day 168 of a year
X169 Temperatures on the day 169 of a year
X170 Temperatures on the day 170 of a year

- X171** Temperatures on the day 171 of a year
- X172** Temperatures on the day 172 of a year
- X173** Temperatures on the day 173 of a year
- X174** Temperatures on the day 174 of a year
- X175** Temperatures on the day 175 of a year
- X176** Temperatures on the day 176 of a year
- X177** Temperatures on the day 177 of a year
- X178** Temperatures on the day 178 of a year
- X179** Temperatures on the day 179 of a year
- X180** Temperatures on the day 180 of a year
- X181** Temperatures on the day 181 of a year
- X182** Temperatures on the day 182 of a year
- X183** Temperatures on the day 183 of a year
- X184** Temperatures on the day 184 of a year
- X185** Temperatures on the day 185 of a year
- X186** Temperatures on the day 186 of a year
- X187** Temperatures on the day 187 of a year
- X188** Temperatures on the day 188 of a year
- X189** Temperatures on the day 189 of a year
- X190** Temperatures on the day 190 of a year
- X191** Temperatures on the day 191 of a year
- X192** Temperatures on the day 192 of a year
- X193** Temperatures on the day 193 of a year
- X194** Temperatures on the day 194 of a year
- X195** Temperatures on the day 195 of a year
- X196** Temperatures on the day 196 of a year
- X197** Temperatures on the day 197 of a year
- X198** Temperatures on the day 198 of a year
- X199** Temperatures on the day 199 of a year
- X200** Temperatures on the day 200 of a year
- X201** Temperatures on the day 201 of a year
- X202** Temperatures on the day 202 of a year
- X203** Temperatures on the day 203 of a year
- X204** Temperatures on the day 204 of a year
- X205** Temperatures on the day 205 of a year
- X206** Temperatures on the day 206 of a year
- X207** Temperatures on the day 207 of a year

X208 Temperatures on the day 208 of a year
X209 Temperatures on the day 209 of a year
X210 Temperatures on the day 210 of a year
X211 Temperatures on the day 211 of a year
X212 Temperatures on the day 212 of a year
X213 Temperatures on the day 213 of a year
X214 Temperatures on the day 214 of a year
X215 Temperatures on the day 215 of a year
X216 Temperatures on the day 216 of a year
X217 Temperatures on the day 217 of a year
X218 Temperatures on the day 218 of a year
X219 Temperatures on the day 219 of a year
X220 Temperatures on the day 220 of a year
X221 Temperatures on the day 221 of a year
X222 Temperatures on the day 222 of a year
X223 Temperatures on the day 223 of a year
X224 Temperatures on the day 224 of a year
X225 Temperatures on the day 225 of a year
X226 Temperatures on the day 226 of a year
X227 Temperatures on the day 227 of a year
X228 Temperatures on the day 228 of a year
X229 Temperatures on the day 229 of a year
X230 Temperatures on the day 230 of a year
X231 Temperatures on the day 231 of a year
X232 Temperatures on the day 232 of a year
X233 Temperatures on the day 233 of a year
X234 Temperatures on the day 234 of a year
X235 Temperatures on the day 235 of a year
X236 Temperatures on the day 236 of a year
X237 Temperatures on the day 237 of a year
X238 Temperatures on the day 238 of a year
X239 Temperatures on the day 239 of a year
X240 Temperatures on the day 240 of a year
X241 Temperatures on the day 241 of a year
X242 Temperatures on the day 242 of a year
X243 Temperatures on the day 243 of a year
X244 Temperatures on the day 244 of a year

- X245** Temperatures on the day 245 of a year
- X246** Temperatures on the day 246 of a year
- X247** Temperatures on the day 247 of a year
- X248** Temperatures on the day 248 of a year
- X249** Temperatures on the day 249 of a year
- X250** Temperatures on the day 250 of a year
- X251** Temperatures on the day 251 of a year
- X252** Temperatures on the day 252 of a year
- X253** Temperatures on the day 253 of a year
- X254** Temperatures on the day 254 of a year
- X255** Temperatures on the day 255 of a year
- X256** Temperatures on the day 256 of a year
- X257** Temperatures on the day 257 of a year
- X258** Temperatures on the day 258 of a year
- X259** Temperatures on the day 259 of a year
- X260** Temperatures on the day 260 of a year
- X261** Temperatures on the day 261 of a year
- X262** Temperatures on the day 262 of a year
- X263** Temperatures on the day 263 of a year
- X264** Temperatures on the day 264 of a year
- X265** Temperatures on the day 265 of a year
- X266** Temperatures on the day 266 of a year
- X267** Temperatures on the day 267 of a year
- X268** Temperatures on the day 268 of a year
- X269** Temperatures on the day 269 of a year
- X270** Temperatures on the day 270 of a year
- X271** Temperatures on the day 271 of a year
- X272** Temperatures on the day 272 of a year
- X273** Temperatures on the day 273 of a year
- X274** Temperatures on the day 274 of a year
- X275** Temperatures on the day 275 of a year
- X276** Temperatures on the day 276 of a year
- X277** Temperatures on the day 277 of a year
- X278** Temperatures on the day 278 of a year
- X279** Temperatures on the day 279 of a year
- X280** Temperatures on the day 280 of a year
- X281** Temperatures on the day 281 of a year

X282 Temperatures on the day 282 of a year
X283 Temperatures on the day 283 of a year
X284 Temperatures on the day 284 of a year
X285 Temperatures on the day 285 of a year
X286 Temperatures on the day 286 of a year
X287 Temperatures on the day 287 of a year
X288 Temperatures on the day 288 of a year
X289 Temperatures on the day 289 of a year
X290 Temperatures on the day 290 of a year
X291 Temperatures on the day 291 of a year
X292 Temperatures on the day 292 of a year
X293 Temperatures on the day 293 of a year
X294 Temperatures on the day 294 of a year
X295 Temperatures on the day 295 of a year
X296 Temperatures on the day 296 of a year
X297 Temperatures on the day 297 of a year
X298 Temperatures on the day 298 of a year
X299 Temperatures on the day 299 of a year
X300 Temperatures on the day 300 of a year
X301 Temperatures on the day 301 of a year
X302 Temperatures on the day 302 of a year
X303 Temperatures on the day 303 of a year
X304 Temperatures on the day 304 of a year
X305 Temperatures on the day 305 of a year
X306 Temperatures on the day 306 of a year
X307 Temperatures on the day 307 of a year
X308 Temperatures on the day 308 of a year
X309 Temperatures on the day 309 of a year
X310 Temperatures on the day 310 of a year
X311 Temperatures on the day 311 of a year
X312 Temperatures on the day 312 of a year
X313 Temperatures on the day 313 of a year
X314 Temperatures on the day 314 of a year
X315 Temperatures on the day 315 of a year
X316 Temperatures on the day 316 of a year
X317 Temperatures on the day 317 of a year
X318 Temperatures on the day 318 of a year

- X319** Temperatures on the day 319 of a year
- X320** Temperatures on the day 320 of a year
- X321** Temperatures on the day 321 of a year
- X322** Temperatures on the day 322 of a year
- X323** Temperatures on the day 323 of a year
- X324** Temperatures on the day 324 of a year
- X325** Temperatures on the day 325 of a year
- X326** Temperatures on the day 326 of a year
- X327** Temperatures on the day 327 of a year
- X328** Temperatures on the day 328 of a year
- X329** Temperatures on the day 329 of a year
- X330** Temperatures on the day 330 of a year
- X331** Temperatures on the day 331 of a year
- X332** Temperatures on the day 332 of a year
- X333** Temperatures on the day 333 of a year
- X334** Temperatures on the day 334 of a year
- X335** Temperatures on the day 335 of a year
- X336** Temperatures on the day 336 of a year
- X337** Temperatures on the day 337 of a year
- X338** Temperatures on the day 338 of a year
- X339** Temperatures on the day 339 of a year
- X340** Temperatures on the day 340 of a year
- X341** Temperatures on the day 341 of a year
- X342** Temperatures on the day 342 of a year
- X343** Temperatures on the day 343 of a year
- X344** Temperatures on the day 344 of a year
- X345** Temperatures on the day 345 of a year
- X346** Temperatures on the day 346 of a year
- X347** Temperatures on the day 347 of a year
- X348** Temperatures on the day 348 of a year
- X349** Temperatures on the day 349 of a year
- X350** Temperatures on the day 350 of a year
- X351** Temperatures on the day 351 of a year
- X352** Temperatures on the day 352 of a year
- X353** Temperatures on the day 353 of a year
- X354** Temperatures on the day 354 of a year
- X355** Temperatures on the day 355 of a year

X356 Temperatures on the day 356 of a year
X357 Temperatures on the day 357 of a year
X358 Temperatures on the day 358 of a year
X359 Temperatures on the day 359 of a year
X360 Temperatures on the day 360 of a year
X361 Temperatures on the day 361 of a year
X362 Temperatures on the day 362 of a year
X363 Temperatures on the day 363 of a year
X364 Temperatures on the day 364 of a year
X365 Temperatures on the day 365 of a year
X366 Temperatures on the day 366 of a year

Source

<https://meteo.arso.gov.si/met/sl/archive/>

LJ_daily_precipitation

Daily precipitation for Ljubljana from 2017 - 1900

Description

A dataset of daily sum of precipitation [mm] in Ljubljana (Slovenia). The first row represents precipitation in 1900 on DOY 1.

Usage

LJ_daily_precipitation

Format

A data frame with 43067 rows and 3 variables:

Year year

DOY day of year

Precipitation Sum of precipitation in mm

Source

<http://climexp.knmi.nl/start.cgi>

LJ_daily_temperatures *Daily mean temperatures for Ljubljana from 2016 - 1930*

Description

A dataset of daily mean temperatures in Ljubljana (Slovenia). The first row represents temperatures in 1930. The first column represents the first day of a year, the second column represents the second day of a year, etc.

Usage

LJ_daily_temperatures

Format

A data frame with 87 rows and 366 variables:

- X1** Temperatures on the day 1 of a year
- X2** Temperatures on the day 2 of a year
- X3** Temperatures on the day 3 of a year
- X4** Temperatures on the day 4 of a year
- X5** Temperatures on the day 5 of a year
- X6** Temperatures on the day 6 of a year
- X7** Temperatures on the day 7 of a year
- X8** Temperatures on the day 8 of a year
- X9** Temperatures on the day 9 of a year
- X10** Temperatures on the day 10 of a year
- X11** Temperatures on the day 11 of a year
- X12** Temperatures on the day 12 of a year
- X13** Temperatures on the day 13 of a year
- X14** Temperatures on the day 14 of a year
- X15** Temperatures on the day 15 of a year
- X16** Temperatures on the day 16 of a year
- X17** Temperatures on the day 17 of a year
- X18** Temperatures on the day 18 of a year
- X19** Temperatures on the day 19 of a year
- X20** Temperatures on the day 20 of a year
- X21** Temperatures on the day 21 of a year
- X22** Temperatures on the day 22 of a year
- X23** Temperatures on the day 23 of a year

- X24** Temperatures on the day 24 of a year
- X25** Temperatures on the day 25 of a year
- X26** Temperatures on the day 26 of a year
- X27** Temperatures on the day 27 of a year
- X28** Temperatures on the day 28 of a year
- X29** Temperatures on the day 29 of a year
- X30** Temperatures on the day 30 of a year
- X31** Temperatures on the day 31 of a year
- X32** Temperatures on the day 32 of a year
- X33** Temperatures on the day 33 of a year
- X34** Temperatures on the day 34 of a year
- X35** Temperatures on the day 35 of a year
- X36** Temperatures on the day 36 of a year
- X37** Temperatures on the day 37 of a year
- X38** Temperatures on the day 38 of a year
- X39** Temperatures on the day 39 of a year
- X40** Temperatures on the day 40 of a year
- X41** Temperatures on the day 41 of a year
- X42** Temperatures on the day 42 of a year
- X43** Temperatures on the day 43 of a year
- X44** Temperatures on the day 44 of a year
- X45** Temperatures on the day 45 of a year
- X46** Temperatures on the day 46 of a year
- X47** Temperatures on the day 47 of a year
- X48** Temperatures on the day 48 of a year
- X49** Temperatures on the day 49 of a year
- X50** Temperatures on the day 50 of a year
- X51** Temperatures on the day 51 of a year
- X52** Temperatures on the day 52 of a year
- X53** Temperatures on the day 53 of a year
- X54** Temperatures on the day 54 of a year
- X55** Temperatures on the day 55 of a year
- X56** Temperatures on the day 56 of a year
- X57** Temperatures on the day 57 of a year
- X58** Temperatures on the day 58 of a year
- X59** Temperatures on the day 59 of a year
- X60** Temperatures on the day 60 of a year

- X61** Temperatures on the day 61 of a year
- X62** Temperatures on the day 62 of a year
- X63** Temperatures on the day 63 of a year
- X64** Temperatures on the day 64 of a year
- X65** Temperatures on the day 65 of a year
- X66** Temperatures on the day 66 of a year
- X67** Temperatures on the day 67 of a year
- X68** Temperatures on the day 68 of a year
- X69** Temperatures on the day 69 of a year
- X70** Temperatures on the day 70 of a year
- X71** Temperatures on the day 71 of a year
- X72** Temperatures on the day 72 of a year
- X73** Temperatures on the day 73 of a year
- X74** Temperatures on the day 74 of a year
- X75** Temperatures on the day 75 of a year
- X76** Temperatures on the day 76 of a year
- X77** Temperatures on the day 77 of a year
- X78** Temperatures on the day 78 of a year
- X79** Temperatures on the day 79 of a year
- X80** Temperatures on the day 80 of a year
- X81** Temperatures on the day 81 of a year
- X82** Temperatures on the day 82 of a year
- X83** Temperatures on the day 83 of a year
- X84** Temperatures on the day 84 of a year
- X85** Temperatures on the day 85 of a year
- X86** Temperatures on the day 86 of a year
- X87** Temperatures on the day 87 of a year
- X88** Temperatures on the day 88 of a year
- X89** Temperatures on the day 89 of a year
- X90** Temperatures on the day 90 of a year
- X91** Temperatures on the day 91 of a year
- X92** Temperatures on the day 92 of a year
- X93** Temperatures on the day 93 of a year
- X94** Temperatures on the day 94 of a year
- X95** Temperatures on the day 95 of a year
- X96** Temperatures on the day 96 of a year
- X97** Temperatures on the day 97 of a year

X98 Temperatures on the day 98 of a year
X99 Temperatures on the day 99 of a year
X100 Temperatures on the day 100 of a year
X101 Temperatures on the day 101 of a year
X102 Temperatures on the day 102 of a year
X103 Temperatures on the day 103 of a year
X104 Temperatures on the day 104 of a year
X105 Temperatures on the day 105 of a year
X106 Temperatures on the day 106 of a year
X107 Temperatures on the day 107 of a year
X108 Temperatures on the day 108 of a year
X109 Temperatures on the day 109 of a year
X110 Temperatures on the day 110 of a year
X111 Temperatures on the day 111 of a year
X112 Temperatures on the day 112 of a year
X113 Temperatures on the day 113 of a year
X114 Temperatures on the day 114 of a year
X115 Temperatures on the day 115 of a year
X116 Temperatures on the day 116 of a year
X117 Temperatures on the day 117 of a year
X118 Temperatures on the day 118 of a year
X119 Temperatures on the day 119 of a year
X120 Temperatures on the day 120 of a year
X121 Temperatures on the day 121 of a year
X122 Temperatures on the day 122 of a year
X123 Temperatures on the day 123 of a year
X124 Temperatures on the day 124 of a year
X125 Temperatures on the day 125 of a year
X126 Temperatures on the day 126 of a year
X127 Temperatures on the day 127 of a year
X128 Temperatures on the day 128 of a year
X129 Temperatures on the day 129 of a year
X130 Temperatures on the day 130 of a year
X131 Temperatures on the day 131 of a year
X132 Temperatures on the day 132 of a year
X133 Temperatures on the day 133 of a year
X134 Temperatures on the day 134 of a year

- X135** Temperatures on the day 135 of a year
- X136** Temperatures on the day 136 of a year
- X137** Temperatures on the day 137 of a year
- X138** Temperatures on the day 138 of a year
- X139** Temperatures on the day 139 of a year
- X140** Temperatures on the day 140 of a year
- X141** Temperatures on the day 141 of a year
- X142** Temperatures on the day 142 of a year
- X143** Temperatures on the day 143 of a year
- X144** Temperatures on the day 144 of a year
- X145** Temperatures on the day 145 of a year
- X146** Temperatures on the day 146 of a year
- X147** Temperatures on the day 147 of a year
- X148** Temperatures on the day 148 of a year
- X149** Temperatures on the day 149 of a year
- X150** Temperatures on the day 150 of a year
- X151** Temperatures on the day 151 of a year
- X152** Temperatures on the day 152 of a year
- X153** Temperatures on the day 153 of a year
- X154** Temperatures on the day 154 of a year
- X155** Temperatures on the day 155 of a year
- X156** Temperatures on the day 156 of a year
- X157** Temperatures on the day 157 of a year
- X158** Temperatures on the day 158 of a year
- X159** Temperatures on the day 159 of a year
- X160** Temperatures on the day 160 of a year
- X161** Temperatures on the day 161 of a year
- X162** Temperatures on the day 162 of a year
- X163** Temperatures on the day 163 of a year
- X164** Temperatures on the day 164 of a year
- X165** Temperatures on the day 165 of a year
- X166** Temperatures on the day 166 of a year
- X167** Temperatures on the day 167 of a year
- X168** Temperatures on the day 168 of a year
- X169** Temperatures on the day 169 of a year
- X170** Temperatures on the day 170 of a year
- X171** Temperatures on the day 171 of a year

X172 Temperatures on the day 172 of a year
X173 Temperatures on the day 173 of a year
X174 Temperatures on the day 174 of a year
X175 Temperatures on the day 175 of a year
X176 Temperatures on the day 176 of a year
X177 Temperatures on the day 177 of a year
X178 Temperatures on the day 178 of a year
X179 Temperatures on the day 179 of a year
X180 Temperatures on the day 180 of a year
X181 Temperatures on the day 181 of a year
X182 Temperatures on the day 182 of a year
X183 Temperatures on the day 183 of a year
X184 Temperatures on the day 184 of a year
X185 Temperatures on the day 185 of a year
X186 Temperatures on the day 186 of a year
X187 Temperatures on the day 187 of a year
X188 Temperatures on the day 188 of a year
X189 Temperatures on the day 189 of a year
X190 Temperatures on the day 190 of a year
X191 Temperatures on the day 191 of a year
X192 Temperatures on the day 192 of a year
X193 Temperatures on the day 193 of a year
X194 Temperatures on the day 194 of a year
X195 Temperatures on the day 195 of a year
X196 Temperatures on the day 196 of a year
X197 Temperatures on the day 197 of a year
X198 Temperatures on the day 198 of a year
X199 Temperatures on the day 199 of a year
X200 Temperatures on the day 200 of a year
X201 Temperatures on the day 201 of a year
X202 Temperatures on the day 202 of a year
X203 Temperatures on the day 203 of a year
X204 Temperatures on the day 204 of a year
X205 Temperatures on the day 205 of a year
X206 Temperatures on the day 206 of a year
X207 Temperatures on the day 207 of a year
X208 Temperatures on the day 208 of a year

- X209** Temperatures on the day 209 of a year
- X210** Temperatures on the day 210 of a year
- X211** Temperatures on the day 211 of a year
- X212** Temperatures on the day 212 of a year
- X213** Temperatures on the day 213 of a year
- X214** Temperatures on the day 214 of a year
- X215** Temperatures on the day 215 of a year
- X216** Temperatures on the day 216 of a year
- X217** Temperatures on the day 217 of a year
- X218** Temperatures on the day 218 of a year
- X219** Temperatures on the day 219 of a year
- X220** Temperatures on the day 220 of a year
- X221** Temperatures on the day 221 of a year
- X222** Temperatures on the day 222 of a year
- X223** Temperatures on the day 223 of a year
- X224** Temperatures on the day 224 of a year
- X225** Temperatures on the day 225 of a year
- X226** Temperatures on the day 226 of a year
- X227** Temperatures on the day 227 of a year
- X228** Temperatures on the day 228 of a year
- X229** Temperatures on the day 229 of a year
- X230** Temperatures on the day 230 of a year
- X231** Temperatures on the day 231 of a year
- X232** Temperatures on the day 232 of a year
- X233** Temperatures on the day 233 of a year
- X234** Temperatures on the day 234 of a year
- X235** Temperatures on the day 235 of a year
- X236** Temperatures on the day 236 of a year
- X237** Temperatures on the day 237 of a year
- X238** Temperatures on the day 238 of a year
- X239** Temperatures on the day 239 of a year
- X240** Temperatures on the day 240 of a year
- X241** Temperatures on the day 241 of a year
- X242** Temperatures on the day 242 of a year
- X243** Temperatures on the day 243 of a year
- X244** Temperatures on the day 244 of a year
- X245** Temperatures on the day 245 of a year

X246 Temperatures on the day 246 of a year
X247 Temperatures on the day 247 of a year
X248 Temperatures on the day 248 of a year
X249 Temperatures on the day 249 of a year
X250 Temperatures on the day 250 of a year
X251 Temperatures on the day 251 of a year
X252 Temperatures on the day 252 of a year
X253 Temperatures on the day 253 of a year
X254 Temperatures on the day 254 of a year
X255 Temperatures on the day 255 of a year
X256 Temperatures on the day 256 of a year
X257 Temperatures on the day 257 of a year
X258 Temperatures on the day 258 of a year
X259 Temperatures on the day 259 of a year
X260 Temperatures on the day 260 of a year
X261 Temperatures on the day 261 of a year
X262 Temperatures on the day 262 of a year
X263 Temperatures on the day 263 of a year
X264 Temperatures on the day 264 of a year
X265 Temperatures on the day 265 of a year
X266 Temperatures on the day 266 of a year
X267 Temperatures on the day 267 of a year
X268 Temperatures on the day 268 of a year
X269 Temperatures on the day 269 of a year
X270 Temperatures on the day 270 of a year
X271 Temperatures on the day 271 of a year
X272 Temperatures on the day 272 of a year
X273 Temperatures on the day 273 of a year
X274 Temperatures on the day 274 of a year
X275 Temperatures on the day 275 of a year
X276 Temperatures on the day 276 of a year
X277 Temperatures on the day 277 of a year
X278 Temperatures on the day 278 of a year
X279 Temperatures on the day 279 of a year
X280 Temperatures on the day 280 of a year
X281 Temperatures on the day 281 of a year
X282 Temperatures on the day 282 of a year

- X283** Temperatures on the day 283 of a year
- X284** Temperatures on the day 284 of a year
- X285** Temperatures on the day 285 of a year
- X286** Temperatures on the day 286 of a year
- X287** Temperatures on the day 287 of a year
- X288** Temperatures on the day 288 of a year
- X289** Temperatures on the day 289 of a year
- X290** Temperatures on the day 290 of a year
- X291** Temperatures on the day 291 of a year
- X292** Temperatures on the day 292 of a year
- X293** Temperatures on the day 293 of a year
- X294** Temperatures on the day 294 of a year
- X295** Temperatures on the day 295 of a year
- X296** Temperatures on the day 296 of a year
- X297** Temperatures on the day 297 of a year
- X298** Temperatures on the day 298 of a year
- X299** Temperatures on the day 299 of a year
- X300** Temperatures on the day 300 of a year
- X301** Temperatures on the day 301 of a year
- X302** Temperatures on the day 302 of a year
- X303** Temperatures on the day 303 of a year
- X304** Temperatures on the day 304 of a year
- X305** Temperatures on the day 305 of a year
- X306** Temperatures on the day 306 of a year
- X307** Temperatures on the day 307 of a year
- X308** Temperatures on the day 308 of a year
- X309** Temperatures on the day 309 of a year
- X310** Temperatures on the day 310 of a year
- X311** Temperatures on the day 311 of a year
- X312** Temperatures on the day 312 of a year
- X313** Temperatures on the day 313 of a year
- X314** Temperatures on the day 314 of a year
- X315** Temperatures on the day 315 of a year
- X316** Temperatures on the day 316 of a year
- X317** Temperatures on the day 317 of a year
- X318** Temperatures on the day 318 of a year
- X319** Temperatures on the day 319 of a year

X320 Temperatures on the day 320 of a year
X321 Temperatures on the day 321 of a year
X322 Temperatures on the day 322 of a year
X323 Temperatures on the day 323 of a year
X324 Temperatures on the day 324 of a year
X325 Temperatures on the day 325 of a year
X326 Temperatures on the day 326 of a year
X327 Temperatures on the day 327 of a year
X328 Temperatures on the day 328 of a year
X329 Temperatures on the day 329 of a year
X330 Temperatures on the day 330 of a year
X331 Temperatures on the day 331 of a year
X332 Temperatures on the day 332 of a year
X333 Temperatures on the day 333 of a year
X334 Temperatures on the day 334 of a year
X335 Temperatures on the day 335 of a year
X336 Temperatures on the day 336 of a year
X337 Temperatures on the day 337 of a year
X338 Temperatures on the day 338 of a year
X339 Temperatures on the day 339 of a year
X340 Temperatures on the day 340 of a year
X341 Temperatures on the day 341 of a year
X342 Temperatures on the day 342 of a year
X343 Temperatures on the day 343 of a year
X344 Temperatures on the day 344 of a year
X345 Temperatures on the day 345 of a year
X346 Temperatures on the day 346 of a year
X347 Temperatures on the day 347 of a year
X348 Temperatures on the day 348 of a year
X349 Temperatures on the day 349 of a year
X350 Temperatures on the day 350 of a year
X351 Temperatures on the day 351 of a year
X352 Temperatures on the day 352 of a year
X353 Temperatures on the day 353 of a year
X354 Temperatures on the day 354 of a year
X355 Temperatures on the day 355 of a year
X356 Temperatures on the day 356 of a year

X357 Temperatures on the day 357 of a year
X358 Temperatures on the day 358 of a year
X359 Temperatures on the day 359 of a year
X360 Temperatures on the day 360 of a year
X361 Temperatures on the day 361 of a year
X362 Temperatures on the day 362 of a year
X363 Temperatures on the day 363 of a year
X364 Temperatures on the day 364 of a year
X365 Temperatures on the day 365 of a year
X366 Temperatures on the day 366 of a year

Source

<http://climexp.knmi.nl/start.cgi>

LJ_monthly_precipitation

Monthly sums of precipitation for Ljubljana from 2018 - 1900. Tidy format.

Description

A dataset of monthly sums of precipitations in Ljubljana (Slovenia). The first row represents precipitation sum for January 1900.

Usage

```
LJ_monthly_precipitation
```

Format

A data frame with 1417 rows and 3 variables:

Year year

Month Month

Precipitation Sum of precipitation

Source

<http://climexp.knmi.nl/start.cgi>

LJ_monthly_temperatures

Monthly mean air temperatures for Ljubljana from 2015 - 1900

Description

A dataset of monthly mean air temperatures in Ljubljana (Slovenia). The first row represents temperatures in 2015. The first column represents mean January temperature, the second column represents mean February temperature. etc. Row names represent year.

Usage

```
LJ_monthly_temperatures
```

Format

A data frame with 116 rows and 12 variables:

Jan Mean monthly air temperature for January from 1900 to 2015

Feb Mean monthly air temperature for February from 1900 to 2015

Mar Mean monthly air temperature for March from 1900 to 2015

Apr Mean monthly air temperature for April from 1900 to 2015

May Mean monthly air temperature for May from 1900 to 2015

Jun Mean monthly air temperature for June from 1900 to 2015

Jul Mean monthly air temperature for July from 1900 to 2015

Aug Mean monthly air temperature for August from 1900 to 2015

Sep Mean monthly air temperature for September from 1900 to 2015

Oct Mean monthly air temperature for October from 1900 to 2015

Nov Mean monthly air temperature for November from 1900 to 2015

Dec Mean monthly air temperature for December from 1900 to 2015

Source

<https://meteo.arso.gov.si/met/sl/archive/>

monthly_response	<i>monthly_response</i>
------------------	-------------------------

Description

Function calculates all possible values of a selected statistical metric between one or more response variables and monthly sequences of environmental data. Calculations are based on moving window which slides through monthly environmental data. All calculated metrics are stored in a matrix. The location of stored calculated metric in the matrix is indicating a window width (row names) and a location in a matrix of monthly sequences of environmental data (column names).

Usage

```
monthly_response(  
  response,  
  env_data,  
  method = "cor",  
  metric = "r.squared",  
  cor_method = "pearson",  
  previous_year = FALSE,  
  number_previous_years = NULL,  
  neurons = 1,  
  lower_limit = 1,  
  upper_limit = 12,  
  fixed_width = 0,  
  brnn_smooth = TRUE,  
  remove_insignificant = TRUE,  
  alpha = 0.05,  
  row_names_subset = FALSE,  
  reference_window = "start",  
  aggregate_function = "mean",  
  quantile_prob = 0.5,  
  temporal_stability_check = "sequential",  
  k = 2,  
  k_running_window = 30,  
  cross_validation_type = "blocked",  
  subset_years = NULL,  
  ylimits = NULL,  
  seed = NULL,  
  tidy_env_data = FALSE,  
  boot = FALSE,  
  boot_n = 1000,  
  boot_ci_type = "norm",  
  boot_conf_int = 0.95,  
  month_interval = NULL,  
  dc_method = NULL,  
  cor_na_use = "everything"
```

)

Arguments

response	a data frame with tree-ring proxy variables as columns and (optional) years as row names. Row.names should be matched with those from a env_data data frame. If not, set row_names_subset = TRUE.
env_data	a data frame of monthly sequences of environmental data as columns and years as row names. Each row represents a year and each column represents a day of a year (or month). Row.names should be matched with those from a response data frame. If not, set row_names_subset = TRUE. Alternatively, env_data could be a tidy data with three columns, i.e. Year, DOY (Month) and third column representing values of mean temperatures, sum of precipitation etc. If tidy data is passed to the function, set the argument tidy_env_data to TRUE.
method	a character string specifying which method to use. Current possibilities are "cor" (default), "lm" and "brnn".
metric	a character string specifying which metric to use. Current possibilities are "r.squared" and "adj.r.squared". If method = "cor", metric is not relevant.
cor_method	a character string indicating which correlation coefficient is to be computed. One of "pearson" (default), "kendall", or "spearman".
previous_year	logical. If TRUE, previous-year climate data are included in the analysis. If FALSE, no previous-year climate data are included and number_previous_years is ignored.
number_previous_years	integer between 1 and 5 specifying how many previous years should be included in the environmental matrix when previous_year = TRUE. For example, number_previous_years = 2 uses monthly climate data from years t - 2, t - 1 and t for response year t. If NULL and previous_year = TRUE, one previous year is included.
neurons	positive integer that indicates the number of neurons used for brnn method
lower_limit	lower limit of window width (i.e. number of consecutive months to be used for calculations)
upper_limit	upper limit of window width (i.e. number of consecutive months to be used for calculations)
fixed_width	fixed width used for calculations (i.e. number of consecutive months to be used for calculations)
brnn_smooth	if set to TRUE, a smoothing algorithm is applied that removes unrealistic calculations which are a result of neural net failure.
remove_ insignificant	if set to TRUE, removes all correlations bellow the significant threshold level, based on a selected alpha. For "lm" and "brnn" method, squared threshold is used, which corresponds to R squared statistics.
alpha	significance level used to remove insignificant calculations.
row_names_subset	if set to TRUE, row.names are used to subset env_data and response data frames. Only years from both data frames are kept.

reference_window	character string, the reference_window argument describes, how each calculation is referred. There are two different options: 'start' (default) and 'end'. If the reference_window argument is set to 'start', then each calculation is related to the starting month of window. If the reference_window argument is set to 'end', then each calculation is related to the ending day of window calculation.
aggregate_function	character string specifying how the monthly data should be aggregated. The default is 'mean', the other options are 'median', 'sum' and 'quantile'.
quantile_prob	numeric value between 0 and 1 specifying the quantile probability used when aggregate_function = 'quantile'. For example, quantile_prob = 0.95 calculates the 95th percentile. The default is 0.5.
temporal_stability_check	character string, specifying, how temporal stability between the optimal selection and response variable(s) will be analysed. Current possibilities are "sequential", "progressive" and "running_window". Sequential check will split data into k splits and calculate selected metric for each split. Progressive check will split data into k splits, calculate metric for the first split and then progressively add 1 split at a time and calculate selected metric. For running window, select the length of running window with the k_running_window argument.
k	integer, number of breaks (splits) for temporal stability and cross validation analysis.
k_running_window	the length of running window for temporal stability check. Applicable only if temporal_stability argument is set to running window.
cross_validation_type	character string, specifying, how to perform cross validation between the optimal selection and response variables. If the argument is set to "blocked", years will not be shuffled. If the argument is set to "randomized", years will be shuffled.
subset_years	a subset of years to be analyzed. Should be given in the form of subset_years = c(1980, 2005)
ylimits	limit of the y axes for plot_extreme. It should be given in the form of: ylimits = c(0,1)
seed	optional seed argument for reproducible results
tidy_env_data	if set to TRUE, env_data should be inserted as a data frame with three columns: "Year", "Month", "Precipitation/Temperature/etc."
boot	logical, if TRUE, bootstrap procedure will be used to calculate estimates correlation coefficients, R squared or adjusted R squared metrics
boot_n	The number of bootstrap replicates
boot_ci_type	A character string representing the type of bootstrap intervals required. The value should be any subset of the values c("norm", "basic", "stud", "perc", "bca").
boot_conf_int	A scalar or vector containing the confidence level(s) of the required interval(s)

month_interval	a vector of two values defining the interval of months used for calculations. Positive values indicate months in the current year. Negative values indicate months in the previous-year block and are only used when previous_year = TRUE. If previous_year = FALSE and negative values are supplied, month_interval is ignored and the analysis is performed for the current year only using month_interval = c(1, 12). If number_previous_years > 1, the previous-year block starts with the earliest included previous year. For example, previous_year = TRUE, number_previous_years = 2 and month_interval = c(-1, 12) analyses the full sequence from January of year t - 2 to December of year t.
dc_method	a character string to determine the method to detrend climate data. Possible values are "none" (default) and "SLD" which refers to Simple Linear Detrending
cor_na_use	an optional character string giving a method for computing covariances in the presence of missing values for correlation coefficients. This must be (an abbreviation of) one of the strings "everything" (default), "all.obs", "complete.obs", "na.or.complete", or "pairwise.complete.obs". See also the documentation for the base cor() function.

Value

a list with 19 elements:

1. \$calculations - a matrix with calculated metrics
2. \$method - the character string of a method
3. \$metric - the character string indicating the metric used for calculations
4. \$analysed_period - the character string specifying the analysed period based on the information from row names. If there are no row names, this argument is given as NA
5. \$optimized_return - data frame with two columns, response variable and aggregated (averaged) monthly data that return the optimal results. This data.frame could be directly used to calibrate a model for climate reconstruction
6. \$optimized_return_all - a data frame with aggregated monthly data, that returned the optimal result for the entire env_data (and not only subset of analysed years)
7. \$transfer_function - a ggplot object: scatter plot of optimized return and a transfer line of the selected method
8. \$temporal_stability - a data frame with calculations of selected metric for different temporal subsets
9. \$cross_validation - a data frame with cross validation results
10. \$plot_heatmap - ggplot2 object: a heatmap of calculated metrics
11. \$plot_extreme - ggplot2 object: line or bar plot of a row with the highest value in a matrix of calculated metrics
12. \$type - the character string describing type of analysis: daily or monthly
13. \$reference_window - character string, which reference window was used for calculations
14. \$boot_lower - matrix with lower limit of confidence intervals of bootstrap calculations
15. \$boot_upper - matrix with upper limit of confidence intervals of bootstrap calculations
16. \$aggregated_climate - matrix with all aggregated climate series
17. \$previous_year - logical indicating whether previous-year climate data were used
18. \$number_previous_years - integer indicating how many previous years were used

Examples

```
# The examples below are enclosed within donttest{} to minimize the execution
# time during R package checks.

# Load the dendroTools R package
library(dendroTools)

# Load data used for examples
data(data_MVA)
data(data_TRW)
data(data_TRW_1)
data(example_proxies_individual)
data(example_proxies_1)
data(LJ_monthly_temperatures)
data(LJ_monthly_precipitation)

# 1 Example with tidy precipitation data
example_tidy_data <- monthly_response(response = data_MVA,
  lower_limit = 1, upper = 24, dc_method = "SLD",
  env_data = LJ_monthly_precipitation, fixed_width = 0,
  method = "cor", row_names_subset = TRUE,
  remove_insignificant = FALSE, previous_year = FALSE,
  reference_window = "end",
  alpha = 0.05, aggregate_function = 'sum', boot = FALSE,
  tidy_env_data = TRUE, boot_n = 100, month_interval = c(-5, 10))

# summary(example_tidy_data)
# plot(example_tidy_data, type = 1)
# plot(example_tidy_data, type = 2)

# 2 Example with split data for early and late
example_MVA_early <- monthly_response(response = data_MVA,
  env_data = LJ_monthly_temperatures,
  method = "cor", row_names_subset = TRUE, previous_year = TRUE,
  remove_insignificant = TRUE, alpha = 0.05,
  subset_years = c(1940, 1980), aggregate_function = 'mean')

example_MVA_late <- monthly_response(response = data_MVA,
  env_data = LJ_monthly_temperatures,
  method = "cor", row_names_subset = TRUE, alpha = 0.05,
  previous_year = TRUE, remove_insignificant = TRUE,
  subset_years = c(1981, 2010), aggregate_function = 'mean')

# summary(example_MVA_late)
# plot(example_MVA_early, type = 1)
# plot(example_MVA_late, type = 1)
# plot(example_MVA_early, type = 2)
# plot(example_MVA_late, type = 2)

# 3 Example negative correlations
example_neg_cor <- monthly_response(response = data_TRW_1, alpha = 0.05,
```

```

env_data = LJ_monthly_temperatures,
method = "cor", row_names_subset = TRUE,
remove_insignificant = TRUE, boot = FALSE)

# summary(example_neg_cor)
# plot(example_neg_cor, type = 1)
# plot(example_neg_cor, type = 2)
# example_neg_cor$temporal_stability

# 4 Example of multiproxy analysis
# summary(example_proxies_1)
# cor(example_proxies_1)

example_multiproxy <- monthly_response(response = example_proxies_1,
  env_data = LJ_monthly_temperatures,
  method = "lm", metric = "adj.r.squared",
  row_names_subset = TRUE, previous_year = FALSE,
  remove_insignificant = TRUE, alpha = 0.05)

# summary(example_multiproxy)
# plot(example_multiproxy, type = 1)

# 5 Example to test the temporal stability
example_MVA_ts <- monthly_response(response = data_MVA,
  env_data = LJ_monthly_temperatures,
  method = "lm", metric = "adj.r.squared", row_names_subset = TRUE,
  remove_insignificant = TRUE, alpha = 0.05,
  temporal_stability_check = "running_window", k_running_window = 10)

# summary(example_MVA_ts)
# example_MVA_ts$temporal_stability

# 6 Example using quantiles for the aggregation
example_q95 <- monthly_response(
  response = data_MVA,
  env_data = LJ_monthly_temperatures,
  method = "cor",
  fixed_width = 3,
  row_names_subset = TRUE,
  previous_year = TRUE,
  aggregate_function = "quantile",
  quantile_prob = 0.95
)

# summary(example_q95)
# example_q95$temporal_stability

# Example using two previous years plus the current year
example_two_previous_years <- monthly_response(
  response = data_MVA,
  env_data = LJ_monthly_temperatures,
  method = "cor",
  fixed_width = 3,

```

```

row_names_subset = TRUE,
previous_year = TRUE,
number_previous_years = 2,
month_interval = c(-1, 10),
aggregate_function = "mean"
)

```

```

monthly_response_seascorr
      monthly_response_seascorr

```

Description

Function calculates all possible partial correlation coefficients between tree-ring chronology and monthly environmental (usually climate) data. All calculated (partial) correlation coefficients are stored in a matrix. The location of stored correlation in the matrix is indicating a window width (row names) and a location in a matrix of monthly sequences of environmental data (column names).

Usage

```

monthly_response_seascorr(
  response,
  env_data_primary,
  env_data_control,
  previous_year = FALSE,
  number_previous_years = NULL,
  pcor_method = "pearson",
  remove_insignificant = TRUE,
  lower_limit = 1,
  upper_limit = 12,
  fixed_width = 0,
  alpha = 0.05,
  row_names_subset = FALSE,
  reference_window = "start",
  aggregate_function_env_data_primary = "mean",
  quantile_prob_env_data_primary = 0.5,
  aggregate_function_env_data_control = "mean",
  quantile_prob_env_data_control = 0.5,
  temporal_stability_check = "sequential",
  k = 2,
  k_running_window = 30,
  subset_years = NULL,
  ylimits = NULL,
  seed = NULL,
  tidy_env_data_primary = FALSE,

```

```

tidy_env_data_control = FALSE,
boot = FALSE,
boot_n = 1000,
boot_ci_type = "norm",
boot_conf_int = 0.95,
month_interval = NULL,
dc_method = NULL,
pcor_na_use = "pairwise.complete"
)

```

Arguments

- response** a data frame with tree-ring proxy variable and (optional) years as row names. Row.names should be matched with those from env_data_primary and env_data_control data frame. If not, set the row_names_subset argument to TRUE.
- env_data_primary** primary data frame of monthly sequences of environmental data as columns and years as row names. Each row represents a year and each column represents a day of a year. Row.names should be matched with those from the response data frame. If not, set the argument row_names_subset to TRUE. Alternatively, env_data_primary could be a tidy data with three columns, i.e. Year, Month and third column representing values of mean temperatures, sum of precipitation etc. If tidy data is passed to the function, set the argument tidy_env_data_primary to TRUE.
- env_data_control** a data frame of monthly sequences of environmental data as columns and years as row names. This data is used as control for calculations of partial correlation coefficients. Each row represents a year and each column represents a day of a year. Row.names should be matched with those from the response data frame. If not, set the row_names_subset argument to TRUE. Alternatively, env_data_control could be a tidy data with three columns, i.e. Year, Month and third column representing values of mean temperatures, sum of precipitation etc. If tidy data is passed to the function, set the argument tidy_env_data_control to TRUE.
- previous_year** logical. If TRUE, previous-year climate data are included in the analysis. If FALSE, no previous-year climate data are included and number_previous_years is ignored.
- number_previous_years** integer between 1 and 5 specifying how many previous years should be included in the environmental matrices when previous_year = TRUE. For example, number_previous_years = 2 uses climate data from years t - 2, t - 1 and t for response year t. If NULL and previous_year = TRUE, one previous year is included.
- pcor_method** a character string indicating which partial correlation coefficient is to be computed. One of "pearson" (default), "kendall", or "spearman", can be abbreviated.
- remove_insignificant** if set to TRUE, removes all correlations below the significant threshold level, based on a selected alpha.

lower_limit	lower limit of window width (i.e. number of consecutive months to be used for calculations)
upper_limit	upper limit of window width (i.e. number of consecutive months to be used for calculations)
fixed_width	fixed width used for calculations (i.e. number of consecutive months to be used for calculations)
alpha	significance level used to remove insignificant calculations.
row_names_subset	if set to TRUE, row.names are used to subset env_data_primary, env_data_control and response data frames. Only years from all three data frames are kept.
reference_window	character string, the reference_window argument describes, how each calculation is referred. There are two different options: 'start' (default) and 'end'. If the reference_window argument is set to 'start', then each calculation is related to the starting month of window. If the reference_window argument is set to 'end', then each calculation is related to the ending day of window calculation.
aggregate_function_env_data_primary	character string specifying how the monthly data from env_data_primary should be aggregated. The default is 'mean', the other options are 'median', 'sum' and 'quantile'.
quantile_prob_env_data_primary	numeric value between 0 and 1 specifying the quantile probability used when aggregate_function_env_data_primary = 'quantile'. For example, 0.95 calculates the 95th percentile. The default is 0.5.
aggregate_function_env_data_control	character string specifying how the monthly data from env_data_control should be aggregated. The default is 'mean', the other options are 'median', 'sum' and 'quantile'.
quantile_prob_env_data_control	numeric value between 0 and 1 specifying the quantile probability used when aggregate_function_env_data_control = 'quantile'. For example, 0.95 calculates the 95th percentile. The default is 0.5.
temporal_stability_check	character string, specifying, how temporal stability between the optimal selection and response variable(s) will be analysed. Current possibilities are "sequential", "progressive" and "running_window". Sequential check will split data into k splits and calculate selected metric for each split. Progressive check will split data into k splits, calculate metric for the first split and then progressively add 1 split at a time and calculate selected metric. For running window, select the length of running window with the k_running_window argument.
k	integer, number of breaks (splits) for temporal stability
k_running_window	the length of running window for temporal stability check. Applicable only if temporal_stability argument is set to running window.
subset_years	a subset of years to be analyzed. Should be given in the form of subset_years = c(1980, 2005)

<code>ylimits</code>	limit of the y axes for <code>plot_extreme</code> . It should be given in the form of: <code>ylimits = c(0,1)</code>
<code>seed</code>	optional seed argument for reproducible results
<code>tidy_env_data_primary</code>	if set to <code>TRUE</code> , <code>env_data_primary</code> should be inserted as a data frame with three columns: "Year", "Month", "Precipitation/Temperature/etc."
<code>tidy_env_data_control</code>	if set to <code>TRUE</code> , <code>env_data_control</code> should be inserted as a data frame with three columns: "Year", "Month", "Precipitation/Temperature/etc."
<code>boot</code>	logical, if <code>TRUE</code> , bootstrap procedure will be used to calculate partial correlation coefficients
<code>boot_n</code>	The number of bootstrap replicates
<code>boot_ci_type</code>	A character string representing the type of bootstrap intervals required. The value should be any subset of the values <code>c("norm", "basic", "stud", "perc", "bca")</code> .
<code>boot_conf_int</code>	A scalar or vector containing the confidence level(s) of the required interval(s)
<code>month_interval</code>	a vector of two values defining the interval of months used for calculations. Positive values indicate months in the current year. Negative values indicate months in the previous-year block and are used only when <code>previous_year = TRUE</code> . If <code>previous_year = FALSE</code> and negative values are supplied, <code>month_interval</code> is ignored and the analysis is performed for the current year only using <code>month_interval = c(1, 12)</code> . If <code>number_previous_years > 1</code> , the previous-year block starts with the earliest included previous year. For example, <code>previous_year = TRUE</code> , <code>number_previous_years = 2</code> and <code>month_interval = c(-1, 12)</code> analyses the full sequence from January of year <code>t - 2</code> to December of year <code>t</code> .
<code>dc_method</code>	a character string to determine the method to detrend climate data. Possible values are "none" (default) and "SLD" which refers to Simple Linear Detrending
<code>pcor_na_use</code>	an optional character string giving a method for computing covariances in the presence of missing values for partial correlation coefficients. This must be (an abbreviation of) one of the strings "all.obs", "everything", "complete.obs", "na.or.complete", or "pairwise.complete.obs" (default). See also the documentation for the base <code>partial.r</code> in <code>psych</code> R package

Value

a list with 17 elements:

1. `$calculations` - a matrix with calculated metrics
2. `$method` - the character string of a method
3. `$metric` - the character string indicating the metric used for calculations
4. `$analysed_period` - the character string specifying the analysed period based on the information from row names. If there are no row names, this argument is given as `NA`
5. `$optimized_return` - data frame with two columns, response variable and aggregated (averaged) monthly data that return the optimal results. This data.frame could be directly used to calibrate a model for climate reconstruction

6. \$optimized_return_all - a data frame with aggregated monthly data, that returned the optimal result for the entire env_data_primary (and not only subset of analysed years)
7. \$transfer_function - a ggplot object: scatter plot of optimized return and a transfer line of the selected method
8. \$temporal_stability - a data frame with calculations of selected metric for different temporal subsets
9. \$cross_validation - not available for partial correlation method
10. \$plot_heatmap - ggplot2 object: a heatmap of calculated metrics
11. \$plot_extreme - ggplot2 object: line plot of a row with the highest value in a matrix of calculated metrics
12. \$type - the character string describing type of analysis: monthly or monthly
13. \$reference_window - character string, which reference window was used for calculations
14. \$aggregated_climate_primary - matrix with all aggregated climate series of primary data
15. \$aggregated_climate_control - matrix with all aggregated climate series of control data
16. \$previous_year - logical indicating whether previous-year climate data were used
17. \$number_previous_years - integer indicating how many previous years were used

Examples

```
# Load the dendroTools R package
library(dendroTools)

# Load data
data(data_MVA)
data(data_TRW)
data(data_TRW_1)
data(example_proxies_individual)
data(example_proxies_1)
data(LJ_monthly_temperatures)
data(LJ_monthly_precipitation)

# 1 Basic example
example_basic <- monthly_response_seascorr(response = data_MVA,
  fixed_width = 11,
  env_data_primary = LJ_monthly_temperatures,
  env_data_control = LJ_monthly_precipitation,
  row_names_subset = TRUE,
  remove_insignificant = TRUE,
  reference_window = "start",
  aggregate_function_env_data_primary = 'median',
  aggregate_function_env_data_control = 'median',
  alpha = 0.05, pcor_method = "spearman",
  tidy_env_data_primary = FALSE,
  tidy_env_data_control = TRUE,
  previous_year = TRUE)

# summary(example_basic)
# plot(example_basic, type = 1)
```

```

# plot(example_basic, type = 2)
# example_basic$optimized_return
# example_basic$optimized_return_all
# example_basic$temporal_stability

# 2 Extended example
example_extended <- monthly_response_seascorr(response = data_MVA,
  env_data_primary = LJ_monthly_temperatures,
  env_data_control = LJ_monthly_precipitation,
  row_names_subset = TRUE, dc_method = "SLD",
  remove_insignificant = FALSE,
  aggregate_function_env_data_primary = 'mean',
  aggregate_function_env_data_control = 'mean',
  alpha = 0.05, pcor_na_use = "pairwise.complete",
  reference_window = "end",
  tidy_env_data_primary = FALSE,
  tidy_env_data_control = TRUE)

# summary(example_extended)
# plot(example_extended, type = 1)
# plot(example_extended, type = 2)
# example_extended$optimized_return
# example_extended$optimized_return_all

# 3 Example using quantiles for primary and control variables
example_quantile <- monthly_response_seascorr(
  response = data_MVA,
  env_data_primary = LJ_monthly_temperatures,
  env_data_control = LJ_monthly_precipitation,
  row_names_subset = TRUE,
  fixed_width = 3,
  previous_year = TRUE,
  aggregate_function_env_data_primary = "quantile",
  quantile_prob_env_data_primary = 0.50,
  aggregate_function_env_data_control = "quantile",
  quantile_prob_env_data_control = 0.50,
  tidy_env_data_primary = FALSE,
  tidy_env_data_control = TRUE)

# summary(example_quantile)

```

swit272

Standardised tree-ring width chronology swit272, Larix decidua Mill.

Description

A TRW chronology swit272 Investigators: Bigler, C.; Claluna, A. Site_Name: Sils-Maria GR Blais dal Fo Location: Switzerland Northernmost_Latitude: 46.4333 Southernmost_Latitude: 46.4333 Easternmost_Longitude: 9.7833 Westernmost_Longitude: 9.7833 Elevation: 2100

Usage

swit272

Format

A data frame with 273 rows and 1 variable:

TRWi Standardised tree-ring width chronology

Source

<https://www.ncei.noaa.gov/access/paleo-search/study/14108>

swit272_daily_precipitation

Daily precipitation for swit272 chronology

Description

Sum of daily precipitation in millimeters for the period 1950 - 2019. This gridded E-OBS data on 0.1° regular grid, version 20e. Extracted data is for the grid point with lon = 9.75 and lat = 46.45.

Usage

swit272_daily_precipitation

Format

A data frame with 25414 rows and 2 variables:

date character string describing date

p_sum mean temperature

Details

We acknowledge the E-OBS dataset from the EU-FP6 project UERRA (<http://www.uerra.eu>) and the Copernicus Climate Change Service, and the data providers in the ECA&D project (<https://www.ecad.eu>). Cornes, R., G. van der Schrier, E.J.M. van den Besselaar, and P.D. Jones. 2018: An Ensemble Version of the E-OBS Temperature and Precipitation Datasets, *J. Geophys. Res. Atmos.*, 123. doi:10.1029/2017JD028200

Source

<https://www.ecad.eu/download/ensembles/download.php>

 swit272_daily_temperatures

Daily temperatures for swit272 chronology

Description

Mean daily temperature in Celsius for the period 1950 - 2019. This gridded E-OBS data on 0.1° regular grid, version 20e. Extracted data is for the grid point with lon = 9.75 and lat = 46.45.

Usage

```
swit272_daily_temperatures
```

Format

A data frame with 25414 rows and 2 variables:

date character string describing date

t_avg mean temperature

Details

We acknowledge the E-OBS dataset from the EU-FP6 project UERRA (<http://www.uerra.eu>) and the Copernicus Climate Change Service, and the data providers in the ECA&D project (<https://www.ecad.eu>). Cornes, R., G. van der Schrier, E.J.M. van den Besselaar, and P.D. Jones. 2018: An Ensemble Version of the E-OBS Temperature and Precipitation Datasets, *J. Geophys. Res. Atmos.*, 123. doi:10.1029/2017JD028200

Source

<https://www.ecad.eu/download/ensembles/download.php>

 years_to_rownames

Function returns a data frame with row names as years

Description

Function returns a data frame with row names as years

Usage

```
years_to_rownames(data, column_year)
```

Arguments

data a data frame to be manipulated

column_year string specifying a column with years

Value

a data frame with years as row names

Examples

```
data <- data.frame(years = seq(1950, 2015), observations = rnorm(66))
new_data <- years_to_rownames(data = data, column_year = "years")
```

```
data <- data.frame(observations1 = rnorm(66), years = seq(1950, 2015),
observations2 = rnorm(66), observations3 = rnorm(66))
new_data <- years_to_rownames(data = data, column_year = "years")
```

Index

* datasets

- data_MVA, [28](#)
 - data_TRW, [30](#)
 - data_TRW_1, [30](#)
 - dataset_MVA, [25](#)
 - dataset_MVA_individual, [26](#)
 - dataset_TRW, [27](#)
 - dataset_TRW_complete, [28](#)
 - example_dataset_1, [31](#)
 - example_proxies_1, [31](#)
 - example_proxies_individual, [32](#)
 - KRE_daily_temperatures, [34](#)
 - LJ_daily_precipitation, [44](#)
 - LJ_daily_temperatures, [45](#)
 - LJ_monthly_precipitation, [55](#)
 - LJ_monthly_temperatures, [56](#)
 - swit272, [68](#)
 - swit272_daily_precipitation, [69](#)
 - swit272_daily_temperatures, [70](#)
- [calculate_metrics, 2](#)
- [compare_methods, 4](#)
- [critical_r, 10](#)
- [daily_response, 11](#)
- [daily_response_seascorr, 19](#)
- data_MVA, [28](#)
 - data_transform, [29](#)
 - data_TRW, [30](#)
 - data_TRW_1, [30](#)
 - dataset_MVA, [25](#)
 - dataset_MVA_individual, [26](#)
 - dataset_TRW, [27](#)
 - dataset_TRW_complete, [28](#)
- example_dataset_1, [31](#)
 - example_proxies_1, [31](#)
 - example_proxies_individual, [32](#)
- [glimpse_daily_data, 33](#)
- [LJ_daily_temperatures, 34](#)
- [LJ_daily_precipitation, 44](#)
- [LJ_daily_temperatures, 45](#)
- [LJ_monthly_precipitation, 55](#)
- [LJ_monthly_temperatures, 56](#)
- [monthly_response, 57](#)
- [monthly_response_seascorr, 63](#)
- [swit272, 68](#)
- [swit272_daily_precipitation, 69](#)
- [swit272_daily_temperatures, 70](#)
- [years_to_rownames, 70](#)