

Package ‘dodgr’

January 9, 2019

Title Distances on Directed Graphs

Version 0.1.2

Description Distances on dual-weighted directed graphs using priority-queue shortest paths. Weighted directed graphs have weights from A to B which may differ from those from B to A. Dual-weighted directed graphs have two sets of such weights. A canonical example is a street network to be used for routing in which routes are calculated by weighting distances according to the type of way and mode of transport, yet lengths of routes must be calculated from direct distances.

Depends R (>= 3.2.0)

License GPL-3

Imports igraph, magrittr, methods, osmdata, rbenchmark, sp, Rcpp (>= 0.12.6), RcppParallel

Suggests devtools, ggplot2, igraphdata, knitr, purrr, RColorBrewer, rmarkdown, roxygen2, scales, testthat, tidygraph

LinkingTo Rcpp, RcppParallel

SystemRequirements C++11, GNU make

VignetteBuilder knitr

NeedsCompilation yes

Encoding UTF-8

LazyData true

URL <https://github.com/ATFutures/dodgr>

BugReports <https://github.com/ATFutures/dodgr/issues>

RoxygenNote 6.1.1

Author Mark Padgham [aut, cre],
Andreas Petutschnig [aut],
Robin Lovelace [ctb],
Andrew Smith [ctb],
Malcolm Morgan [ctb],
Shane Saunders [cph] (Original author of included code for priority
heaps)

Maintainer Mark Padgham <mark.padgham@email.com>

Repository CRAN

Date/Publication 2019-01-09 13:20:03 UTC

R topics documented:

compare_heaps	2
dodgr	3
dodgr_components	4
dodgr_contract_graph	4
dodgr_distances	5
dodgr_dists	7
dodgr_flowmap	9
dodgr_flows_aggregate	10
dodgr_flows_disperse	12
dodgr_paths	13
dodgr_sample	14
dodgr_streetnet	15
dodgr_to_igraph	16
dodgr_to_sfc	17
dodgr_to_tidygraph	18
dodgr_vertices	18
hampi	19
match_points_to_graph	19
match_pts_to_graph	20
merge_directed_flows	21
os_roads_bristol	22
weighting_profiles	23
weight_railway	23
weight_streetnet	24
Index	27

compare_heaps	<i>compare_heaps</i>
---------------	----------------------

Description

Perform timing comparison between different kinds of heaps as well as with equivalent igraph routine distances. To do this, a random sub-graph containing a defined number of vertices is first selected. Alternatively, this random sub-graph can be pre-generated with the `dodgr_sample` function and passed directly.

Usage

```
compare_heaps(graph, nverts = 100, replications = 2)
```

Arguments

graph	data.frame object representing the network graph (or a sub-sample selected with codedodgr_sample)
nverts	Number of vertices used to generate random sub-graph. If a non-numeric value is given, the whole graph will be used.
replications	Number of replications to be used in comparison

Value

Result of `rbenachmar::benchmark` comparison in data.frame form.

Note

igraph caches intermediate results of graph processing, so the **igraph** comparisons will be faster on subsequent runs. To obtain fair comparisons, run only once or re-start the current R session.

Examples

```
graph <- weight_streetnet (hampi)
compare_heaps (graph, nverts = 100, replications = 1)
```

dodgr

dodgr.

Description

Distances on dual-weighted directed graphs using priority-queue shortest paths. Weighted directed graphs have weights from A to B which may differ from those from B to A. Dual-weighted directed graphs have two sets of such weights. A canonical example is a street network to be used for routing in which routes are calculated by weighting distances according to the type of way and mode of transport, yet lengths of routes must be calculated from direct distances.

The Main Function

- `dodgr_dists()`: Calculate pair-wise distances between specified pairs of points in a graph.

Functions to Obtain Graphs

- `dodgr_streetnet()`: Extract a street network in Simple Features (sf) form.
- `weight_streetnet()`: Convert an sf-formatted street network to a dodgr graph through applying specified weights to all edges.

Functions to Modify Graphs

- `dodgr_components()`: Number all graph edges according to their presence in distinct connected components.
- `dodgr_contract_graph()`: Contract a graph by removing redundant edges.

Miscellaneous Functions

- `dodgr_sample()`: Randomly sample a graph, returning a single connected component of a defined number of vertices.
- `dodgr_vertices()`: Extract all vertices of a graph.
- `compare_heaps()`: Compare the performance of different priority queue heap structures for a given type of graph.

`dodgr_components` *dodgr_components*

Description

Identify connected components of graph and add corresponding component column to `data.frame`.

Usage

```
dodgr_components(graph)
```

Arguments

`graph` A `data.frame` of edges

Value

Equivalent graph with additional component column, sequentially numbered from 1 = largest component.

Examples

```
graph <- weight_streetnet (hampi)
graph <- dodgr_components (graph)
```

`dodgr_contract_graph` *dodgr_contract_graph*

Description

Removes redundant (straight-line) vertices from graph, leaving only junction vertices.

Usage

```
dodgr_contract_graph(graph, verts = NULL)
```

Arguments

graph	A flat table of graph edges. Must contain columns labelled from and to, or start and stop. May also contain similarly labelled columns of spatial coordinates (for example from_x) or stop_lon).
verts	Optional list of vertices to be retained as routing points. These must match the from_id and to_id columns of graph.

Value

A list of two items: graph containing contracted version of the original graph, converted to a standardised format, and edge_map, a two-column matrix mapping all newly contracted edges onto corresponding edges in original (uncontracted) graph.

Examples

```
graph <- weight_streetnet (hampi)
nrow (graph) # 5,742
graph <- dodgr_contract_graph (graph)
nrow (graph$graph) # 2,878
```

dodgr_distances	<i>dodgr_distances</i>
-----------------	------------------------

Description

Alias for [dodgr_dists](#)

Usage

```
dodgr_distances(graph, from, to, wt_profile = "bicycle", expand = 0,
  heap = "BHeap", parallel = TRUE, quiet = TRUE)
```

Arguments

graph	data.frame or equivalent object representing the network graph (see Details)
from	Vector or matrix of points from which route distances are to be calculated (see Details)
to	Vector or matrix of points to which route distances are to be calculated (see Details)
wt_profile	Name of weighting profile for street networks (one of foot, horse, wheelchair, bicycle, moped, motorcycle, motorcar, goods, hgv, psv).
expand	Only when graph not given, the multiplicative factor by which to expand the street network surrounding the points defined by from and/or to.
heap	Type of heap to use in priority queue. Options include Fibonacci Heap (default; FHeap), Binary Heap (BHeap), Radix, Trinomial Heap (TriHeap), Extended Trinomial Heap (TriHeapExt, and 2-3 Heap (Heap23).

parallel If TRUE, perform routing calculation in parallel (see details)
 quiet If FALSE, display progress messages on screen.

Value

square matrix of distances between nodes

Examples

```
# A simple graph
graph <- data.frame (from = c ("A", "B", "B", "B", "C", "C", "D", "D"),
                    to = c ("B", "A", "C", "D", "B", "D", "C", "A"),
                    d = c (1, 2, 1, 3, 2, 1, 2, 1))

dodgr_dists (graph)

# A larger example from the included [hampi()] data.
graph <- weight_streetnet (hampi)
from <- sample (graph$from_id, size = 100)
to <- sample (graph$to_id, size = 50)
d <- dodgr_dists (graph, from = from, to = to)
# d is a 100-by-50 matrix of distances between `from` and `to`

## Not run:
# a more complex street network example, thanks to @chrijo; see
# https://github.com/ATFutures/dodgr/issues/47

xy <- rbind (c (7.005994, 51.45774), # limbeckerplatz 1 essen germany
            c (7.012874, 51.45041)) # hauptbahnhof essen germany
xy <- data.frame (lon = xy [, 1], lat = xy [, 2])
essen <- dodgr_streetnet (pts = xy, expand = 0.2, quiet = FALSE)
graph <- weight_streetnet (essen, wt_profile = "foot")
d <- dodgr_dists (graph, from = xy, to = xy)
# First reason why this does not work is because the graph has multiple,
# disconnected components.
table (graph$component)
# reduce to largest connected component, which is always number 1
graph <- graph [which (graph$component == 1), ]
d <- dodgr_dists (graph, from = xy, to = xy)
# should work, but even then note that
table (essen$level)
# There are parts of the network on different building levels (because of
# shopping malls and the like). These may or may not be connected, so it may be
# necessary to filter out particular levels
levs <- paste0 (essen$level) # because sf data are factors
index <- which (! (levs == "-1" | levs == "1")) # for example
library (sf) # needed for following sub-select operation
essen <- essen [index, ]
graph <- weight_streetnet (essen, wt_profile = "foot")
d <- dodgr_dists (graph, from = xy, to = xy)

## End(Not run)
```

dodgr_dists	<i>dodgr_dists</i>
-------------	--------------------

Description

Calculate matrix of pair-wise distances between points.

Usage

```
dodgr_dists(graph, from, to, wt_profile = "bicycle", expand = 0,
            heap = "BHeap", parallel = TRUE, quiet = TRUE)
```

Arguments

graph	data.frame or equivalent object representing the network graph (see Details)
from	Vector or matrix of points from which route distances are to be calculated (see Details)
to	Vector or matrix of points to which route distances are to be calculated (see Details)
wt_profile	Name of weighting profile for street networks (one of foot, horse, wheelchair, bicycle, moped, motorcycle, motorcar, goods, hgv, psv).
expand	Only when graph not given, the multiplicative factor by which to expand the street network surrounding the points defined by from and/or to.
heap	Type of heap to use in priority queue. Options include Fibonacci Heap (default; FHeap), Binary Heap (BHeap), Radix, Trinomial Heap (TriHeap), Extended Trinomial Heap (TriHeapExt, and 2-3 Heap (Heap23).
parallel	If TRUE, perform routing calculation in parallel (see details)
quiet	If FALSE, display progress messages on screen.

Value

square matrix of distances between nodes

Note

graph must minimally contain three columns of from, to, dist. If an additional column named weight or wt is present, shortest paths are calculated according to values specified in that column; otherwise according to dist values. Either way, final distances between from and to points are calculated according to values of dist. That is, paths between any pair of points will be calculated according to the minimal total sum of weight values (if present), while reported distances will be total sums of dist values.

The from and to columns of graph may be either single columns of numeric or character values specifying the numbers or names of graph vertices, or combinations to two columns specifying geographical (longitude and latitude) coordinates. In the latter case, almost any sensible combination of names will be accepted (for example, from_x, from_y, from_x, from_y, or fr_{lat}, fr_{lon}.)

from and to values can be either two-column matrices of equivalent of longitude and latitude coordinates, or else single columns precisely matching node numbers or names given in graph\$from or graph\$to. If to is missing, pairwise distances are calculated between all points specified in from. If neither from nor to are specified, pairwise distances are calculated between all nodes in graph.

Calculations in parallel (parallel = TRUE) ought very generally be advantageous. For small graphs, Calculating distances in parallel is likely to offer relatively little gain in speed, but increases from parallel computation will generally markedly increase with increasing graph sizes.

Examples

```
# A simple graph
graph <- data.frame (from = c ("A", "B", "B", "B", "C", "C", "D", "D"),
                    to = c ("B", "A", "C", "D", "B", "D", "C", "A"),
                    d = c (1, 2, 1, 3, 2, 1, 2, 1))

dodgr_dists (graph)

# A larger example from the included [hampi()] data.
graph <- weight_streetnet (hampi)
from <- sample (graph$from_id, size = 100)
to <- sample (graph$to_id, size = 50)
d <- dodgr_dists (graph, from = from, to = to)
# d is a 100-by-50 matrix of distances between `from` and `to`

## Not run:
# a more complex street network example, thanks to @chrijo; see
# https://github.com/ATFutures/dodgr/issues/47

xy <- rbind (c (7.005994, 51.45774), # limbeckerplatz 1 essen germany
            c (7.012874, 51.45041)) # hauptbahnhof essen germany
xy <- data.frame (lon = xy [, 1], lat = xy [, 2])
essen <- dodgr_streetnet (pts = xy, expand = 0.2, quiet = FALSE)
graph <- weight_streetnet (essen, wt_profile = "foot")
d <- dodgr_dists (graph, from = xy, to = xy)
# First reason why this does not work is because the graph has multiple,
# disconnected components.
table (graph$component)
# reduce to largest connected component, which is always number 1
graph <- graph [which (graph$component == 1), ]
d <- dodgr_dists (graph, from = xy, to = xy)
# should work, but even then note that
table (essen$level)
# There are parts of the network on different building levels (because of
# shopping malls and the like). These may or may not be connected, so it may be
# necessary to filter out particular levels
levs <- paste0 (essen$level) # because sf data are factors
index <- which (! (levs == "-1" | levs == "1")) # for example
library (sf) # needed for following sub-select operation
essen <- essen [index, ]
graph <- weight_streetnet (essen, wt_profile = "foot")
d <- dodgr_dists (graph, from = xy, to = xy)

## End(Not run)
```

dodgr_flowmap	<i>dodgr_flowmap</i>
---------------	----------------------

Description

Map the output of [dodgr_flows_aggregate](#) or [dodgr_flows_disperse](#)

Usage

```
dodgr_flowmap(net, bbox = NULL, linescale = 1)
```

Arguments

net	A street network with a flow column obtained from dodgr_flows_aggregate or dodgr_flows_disperse
bbox	If given, scale the map to this bbox, otherwise use entire extend of net
linescale	Maximal thickness of plotted lines

Note

net should be first passed through `merge_directed_flows` prior to plotting, otherwise lines for different directions will be overlaid.

Examples

```
graph <- weight_streetnet (hampi)
from <- sample (graph$from_id, size = 10)
to <- sample (graph$to_id, size = 5)
to <- to [!to %in% from]
flows <- matrix (10 * runif (length (from) * length (to)),
                 nrow = length (from))
graph <- dodgr_flows_aggregate (graph, from = from, to = to, flows = flows)
# graph then has an additional 'flows` column of aggregate flows along all
# edges. These flows are directed, and can be aggregated to equivalent
# undirected flows on an equivalent undirected graph with:
graph_undir <- merge_directed_flows (graph)
## Not run:
dodgr_flowmap (graph_undir)

## End(Not run)
```

dodgr_flows_aggregate *dodgr_flows_aggregate*

Description

Aggregate flows throughout a network based on an input matrix of flows between all pairs of from and to points.

Usage

```
dodgr_flows_aggregate(graph, from, to, flows, wt_profile = "bicycle",
  contract = FALSE, heap = "BHeap", quiet = TRUE)
```

Arguments

graph	data.frame or equivalent object representing the network graph (see Details)
from	Vector or matrix of points from which aggregate flows are to be calculated (see Details)
to	Vector or matrix of points to which aggregate flows are to be calculated (see Details)
flows	Matrix of flows with <code>nrow(flows)==length(from)</code> and <code>ncol(flows)==length(to)</code> .
wt_profile	Name of weighting profile for street networks (one of foot, horse, wheelchair, bicycle, moped, motorcycle, motorcar, goods, hgv, psv; only used if graph is not provided, in which case a street network is downloaded and correspondingly weighted).
contract	If TRUE, calculate flows on contracted graph before mapping them back on to the original full graph (recommended as this will generally be much faster).
heap	Type of heap to use in priority queue. Options include Fibonacci Heap (default; FHeap), Binary Heap (BHeap), Radix, Trinomial Heap (TriHeap), Extended Trinomial Heap (TriHeapExt, and 2-3 Heap (Heap23).
quiet	If FALSE, display progress messages on screen.

Value

Modified version of graph with additional flow column added.

Examples

```
graph <- weight_streetnet (hampi)
from <- sample (graph$from_id, size = 10)
to <- sample (graph$to_id, size = 5)
to <- to [!to %in% from]
flows <- matrix (10 * runif (length (from) * length (to)),
  nrow = length (from))
graph <- dodgr_flows_aggregate (graph, from = from, to = to, flows = flows)
# graph then has an additional 'flows' column of aggregate flows along all
```

```

# edges. These flows are directed, and can be aggregated to equivalent
# undirected flows on an equivalent undirected graph with:
graph_undir <- merge_directed_flows (graph)
# This graph will only include those edges having non-zero flows, and so:
nrow (graph); nrow (graph_undir) # the latter is much smaller

# The following code can be used to convert the resultant graph to an `sf`
# object suitable for plotting
## Not run:
geoms <- dodgr_to_sfc (graph_undir)
gc <- dodgr_contract_graph (graph_undir)
gsf <- sf::st_sf (geoms)
gsf$flow <- gc$graph$flow

# example of plotting with the 'mapview' package
library (mapview)
flow <- gsf$flow / max (gsf$flow)
ncols <- 30
cols <- colorRampPalette (c ("lawngreen", "red")) (ncols) [ceiling (ncols * flow)]
mapview (gsf, color = cols, lwd = 10 * flow)

## End(Not run)

# An example of flow aggregation across a generic (non-OSM) highway,
# represented as the `routes_fast` object of the \pkg{stplanr} package,
# which is a SpatialLinesDataFrame containing commuter densities along
# components of a street network.
## Not run:
library (stplanr)
# merge all of the 'routes_fast' lines into a single network
r <- overline (routes_fast, attrib = "length", buff_dist = 1)
r <- sf::st_as_sf (r)
# then extract the start and end points of each of the original 'routes_fast'
# lines and use these for routing with `dodgr`
l <- lapply (routes_fast@lines, function (i)
  c (sp::coordinates (i) [[1]] [1, ],
    tail (sp::coordinates (i) [[1]], 1)))
l <- do.call (rbind, l)
xy_start <- l [, 1:2]
xy_end <- l [, 3:4]
# Then just specify a generic OD matrix with uniform values of 1:
flows <- matrix (1, nrow = nrow (l), ncol = nrow (l))
# We need to specify both a `type` and `id` column for the
# \link{weight_streetnet} function.
r$type <- 1
r$id <- seq (nrow (r))
graph <- weight_streetnet (r, type_col = "type", id_col = "id",
  wt_profile = 1)
f <- dodgr_flows_aggregate (graph, from = xy_start, to = xy_end, flows = flows)
# Then merge directed flows and convert to \pkg{sf} for plotting as before:
f <- merge_directed_flows (f)
geoms <- dodgr_to_sfc (f)
gc <- dodgr_contract_graph (f)

```

```
gsf <- sf::st_sf (geoms)
gsf$flow <- gc$graph$flow
# sf plot:
plot (gsf ["flow"])

## End(Not run)
```

dodgr_flows_disperse *dodgr_flows_disperse*

Description

Disperse flows throughout a network based on a input vectors of origin points and associated densities

Usage

```
dodgr_flows_disperse(graph, from, dens, wt_profile = "bicycle",
  contract = FALSE, k = 2, heap = "BHeap", quiet = TRUE)
```

Arguments

graph	data.frame or equivalent object representing the network graph (see Details)
from	Vector or matrix of points from which aggregate dispersed flows are to be calculated (see Details)
dens	Vectors of densities corresponding to the from points
wt_profile	Name of weighting profile for street networks (one of foot, horse, wheelchair, bicycle, moped, motorcycle, motorcar, goods, hgv, psv).
contract	If TRUE, calculate flows on contracted graph before mapping them back on to the original full graph (recommended as this will generally be much faster).
k	Width coefficient of exponential diffusion function defined as $\exp(-d/k)$. If value of $k < 0$ is given, a standard logistic polynomial will be used.
heap	Type of heap to use in priority queue. Options include Fibonacci Heap (default; FHeap), Binary Heap (BHeap), Radix, Trinomial Heap (TriHeap), Extended Trinomial Heap (TriHeapExt, and 2-3 Heap (Heap23).
quiet	If FALSE, display progress messages on screen.

Value

Modified version of graph with additional flow column added.

Examples

```
graph <- weight_streetnet (hampi)
from <- sample (graph$from_id, size = 10)
dens <- rep (1, length (from)) # Uniform densities
graph <- dodgr_flows_disperse (graph, from = from, dens = dens)
# graph then has an additional 'flows` column of aggregate flows along all
# edges. These flows are directed, and can be aggregated to equivalent
# undirected flows on an equivalent undirected graph with:
graph_undir <- merge_directed_flows (graph)
```

dodgr_paths

dodgr_paths

Description

Calculate lists of pair-wise shortest paths between points.

Usage

```
dodgr_paths(graph, from, to, vertices = TRUE, wt_profile = "bicycle",
  pairwise = FALSE, heap = "BHeap", quiet = TRUE)
```

Arguments

graph	data.frame or equivalent object representing the network graph (see Details)
from	Vector or matrix of points from which route paths are to be calculated (see Details)
to	Vector or matrix of points to which route paths are to be calculated (see Details)
vertices	If TRUE, return lists of lists of vertices for each path, otherwise return corresponding lists of edge numbers from graph.
wt_profile	Name of weighting profile for street networks (one of foot, horse, wheelchair, bicycle, moped, motorcycle, motorcar, goods, hgv, psv; only used if graph is not provided, in which case a street network is downloaded and correspondingly weighted).
pairwise	If TRUE, calculate paths only between the ordered pairs of from and to. In this case, each of these must be the same length, and the output will contain paths the i-th members of each, and thus also be of that length.
heap	Type of heap to use in priority queue. Options include Fibonacci Heap (default; FHeap), Binary Heap (BHeap), Radix, Trinomial Heap (TriHeap), Extended Trinomial Heap (TriHeapExt, and 2-3 Heap (Heap23).
quiet	If FALSE, display progress messages on screen.

Value

List of list of paths tracing all connections between nodes such that if `x <- dodgr_paths (graph, from, to)`, then the path between `from[i]` and `to[j]` is `x [[i]] [[j]]`.

Note

graph must minimally contain four columns of from, to, dist. If an additional column named weight or wt is present, shortest paths are calculated according to values specified in that column; otherwise according to dist values. Either way, final distances between from and to points are calculated according to values of dist. That is, paths between any pair of points will be calculated according to the minimal total sum of weight values (if present), while reported distances will be total sums of dist values.

The from and to columns of graph may be either single columns of numeric or character values specifying the numbers or names of graph vertices, or combinations to two columns specifying geographical (longitude and latitude) coordinates. In the latter case, almost any sensible combination of names will be accepted (for example, from_x, from_y, from_x, from_y, or fr_lat, fr_lon.)

from and to values can be either two-column matrices of equivalent of longitude and latitude coordinates, or else single columns precisely matching node numbers or names given in graph\$from or graph\$to. If to is missing, pairwise distances are calculated between all points specified in from. If neither from nor to are specified, pairwise distances are calculated between all nodes in graph.

Examples

```
graph <- weight_streetnet (hampi)
from <- sample (graph$from_id, size = 100)
to <- sample (graph$to_id, size = 50)
dp <- dodgr_paths (graph, from = from, to = to)
# dp is a list with 100 items, and each of those 100 items has 30 items, each
# of which is a single path listing all vertiex IDs as taken from `graph`.

# it is also possible to calculate paths between pairwise start and end
# points
from <- sample (graph$from_id, size = 5)
to <- sample (graph$to_id, size = 5)
dp <- dodgr_paths (graph, from = from, to = to, pairwise = TRUE)
# dp is a list of 5 items, each of which just has a single path between each
# pairwise from and to point.
```

dodgr_sample

dodgr_sample

Description

Sample a random but connected sub-component of a graph

Usage

```
dodgr_sample(graph, nverts = 1000)
```

Arguments

graph	A flat table of graph edges. Must contain columns labelled from and to, or start and stop. May also contain similarly labelled columns of spatial coordinates (for example from_x) or stop_lon).
nverts	Number of vertices to sample

Value

A connected sub-component of graph

Note

Graphs may occasionally have `nverts + 1` vertices, rather than the requested `nverts`.

Examples

```
graph <- weight_streetnet (hampi)
nrow (graph) # 5,742
graph <- dodgr_sample (graph, nverts = 200)
nrow (graph) # generally around 400 edges
nrow (dodgr_vertices (graph)) # 200
```

dodgr_streetnet *dodgr_streetnet*

Description

Use the `osmdata` package to extract the street network for a given location. For routing between a given set of points (passed as `pts`), the `bbox` argument may be omitted, in which case a bounding box will be constructed by expanding the range of `pts` by the relative amount of `expand`.

Usage

```
dodgr_streetnet(bbox, pts, expand = 0.05, quiet = TRUE)
```

Arguments

bbox	Bounding box as vector or matrix of coordinates, or location name. Passed to <code>osmdata::getbb</code> .
pts	List of points presumably containing spatial coordinates
expand	Relative factor by which street network should extend beyond limits defined by <code>pts</code> (only if <code>bbox</code> not given).
quiet	If <code>FALSE</code> , display progress messages

Value

A Simple Features (`sf`) object with coordinates of all lines in the street network.

Examples

```
## Not run:
streetnet <- dodgr_streetnet ("hampi india", expand = 0)
# convert to form needed for `dodgr` functions:
graph <- weight_streetnet (streetnet)
nrow (graph) # 5,742 edges
# Alternative ways of extracting street networks by using a small selection of
# graph vertices to define bounding box:
verts <- dodgr_vertices (graph)
verts <- verts [sample (nrow (verts), size = 200), ]
streetnet <- dodgr_streetnet (pts = verts, expand = 0)
graph <- weight_streetnet (streetnet)
nrow (graph)
# This will generally have many more rows because most street networks include
# streets that extend considerably beyond the specified bounding box.

# bbox can also be a polygon:
bb <- osmdata::getbb ("gent belgium") # rectangular bbox
nrow (dodgr_streetnet (bbox = bb)) # 28,742
bb <- osmdata::getbb ("gent belgium", format_out = "polygon")
nrow (dodgr_streetnet (bbox = bb)) # 15,969
# The latter has fewer rows because only edges within polygon are returned

## End(Not run)
```

dodgr_to_igraph

dodgr_to_igraph

Description

Convert a dodgr graph to an **igraph**.

Usage

```
dodgr_to_igraph(graph)
```

Arguments

graph A dodgr graph

Value

The igraph equivalent of the input

Examples

```
graph <- weight_streetnet (hampi)
graphi <- dodgr_to_igraph (graph)
```

dodgr_to_sfc	<i>dodgr_to_sfc</i>
--------------	---------------------

Description

Convert a `dodgr` graph into a list composed of two objects: `dat`, a `data.frame`; and `geometry`, an `sfc` object from the (`sf`) package. Works by aggregating edges into `LINestring` objects representing longest sequences between all junction nodes. The resultant objects will generally contain more `LINestring` objects than the original `sf` object, because the former will be bisected at every junction point.

Usage

```
dodgr_to_sfc(net)
```

Arguments

<code>net</code>	A dodgr network
------------------	------------------------

Value

A list containing (i) A `data.frame` of data associated with the `sf` geometries; and (ii) A Simple Features Collection (`sfc`) list of `LINestring` objects.

Note

The output of this function corresponds to the edges obtained from `dodgr_contract_graph`. An `sf` `data.frame` may be created by appending any data from the latter to the `sfc` output of this function - see `sf` for details.

Examples

```
hw <- weight_streetnet (hampi)
nrow(hw)
xy <- dodgr_to_sfc (hw)
dim (hw) # 5.845 edges
length (xy$geometry) # more linestrings aggregated from those edges
nrow (hampi) # than the 191 linestrings in original sf object
dim (xy$dat) # same number of rows as there are geometries
# sf::st_sf(xy$dat, geometry = xy$geometry, crs = 4326)
```

dodgr_to_tidygraph *dodgr_to_tidygraph*

Description

Convert a dodgr graph to an **tidygraph**.

Usage

```
dodgr_to_tidygraph(graph)
```

Arguments

graph A dodgr graph

Value

The tidygraph equivalent of the input

Examples

```
graph <- weight_streetnet (hampi)
graph_t <- dodgr_to_tidygraph (graph)
```

dodgr_vertices *dodgr_vertices*

Description

Extract vertices of graph, including spatial coordinates if included

Usage

```
dodgr_vertices(graph)
```

Arguments

graph A flat table of graph edges. Must contain columns labelled from and to, or start and stop. May also contain similarly labelled columns of spatial coordinates (for example from_x) or stop_lon).

Value

A data.frame of vertices with unique numbers (n).

Note

Values of n are 0-indexed

Examples

```
graph <- weight_streetnet (hampi)
v <- dodgr_vertices (graph)
```

hampi

hampi

Description

A sample street network from the township of Hampi, Karnataka, India.

Format

A Simple Features sf data.frame containing the street network of Hampi.

Note

Can be re-created with the following command, which also removes extraneous columns to reduce size:

Examples

```
## Not run:
hampi <- dodgr_streetnet("hampi india")
cols <- c ("osm_id", "highway", "oneway", "geometry")
hampi <- hampi [, which (names (hampi) %in% cols)]

## End(Not run)
# this 'sf data.frame' can be converted to a 'dodgr' network with
net <- weight_streetnet (hampi, wt_profile = 'foot')
```

match_points_to_graph *match_points_to_graph*

Description

Alias for [match_points_to_graph](#)

Usage

```
match_points_to_graph(verts, xy, connected = FALSE)
```

Arguments

verts	A data.frame of vertices obtained from <code>dodgr_vertices(graph)</code> .
xy	coordinates of points to be matched to the vertices, either as matrix or sf -formatted data.frame.
connected	Should points be matched to the same (largest) connected component of graph? If FALSE and these points are to be used for a dodgr routine routine (<code>dodgr_dists</code> , <code>dodgr_paths</code> , or <code>dodgr_flows_aggregate</code>), then results may not be returned if points are not part of the same connected component. On the other hand, forcing them to be part of the same connected component may decrease the spatial accuracy of matching.

Value

A vector index into verts

Examples

```
net <- weight_streetnet (hampi, wt_profile = "foot")
verts <- dodgr_vertices (net)
# Then generate some random points to match to graph
npts <- 10
xy <- data.frame (
  x = min (verts$x) + runif (npts) * diff (range (verts$x)),
  y = min (verts$y) + runif (npts) * diff (range (verts$y))
)
pts <- match_pts_to_graph (verts, xy)
pts # an index into verts
pts <- verts$id [pts]
pts # names of those vertices
```

match_pts_to_graph *match_pts_to_graph*

Description

Match spatial points to a spatial graph which contains vertex coordinates

Usage

```
match_pts_to_graph(verts, xy, connected = FALSE)
```

Arguments

verts	A data.frame of vertices obtained from <code>dodgr_vertices(graph)</code> .
xy	coordinates of points to be matched to the vertices, either as matrix or sf -formatted data.frame.

`connected` Should points be matched to the same (largest) connected component of graph? If FALSE and these points are to be used for a `dodgr` routine routine (`dodgr_dists`, `dodgr_paths`, or `dodgr_flows_aggregate`), then results may not be returned if points are not part of the same connected component. On the other hand, forcing them to be part of the same connected component may decrease the spatial accuracy of matching.

Value

A vector index into `verts`

Examples

```
net <- weight_streetnet (hampi, wt_profile = "foot")
verts <- dodgr_vertices (net)
# Then generate some random points to match to graph
npts <- 10
xy <- data.frame (
  x = min (verts$x) + runif (npts) * diff (range (verts$x)),
  y = min (verts$y) + runif (npts) * diff (range (verts$y))
)
pts <- match_pts_to_graph (verts, xy)
pts # an index into verts
pts <- verts$id [pts]
pts # names of those vertices
```

`merge_directed_flows` *merge_directed_flows*

Description

The `dodgr_flows_aggregate` and `dodgr_flows_disperse` functions return a column of aggregated flows directed along each edge of a graph, so the aggregated flow from vertex A to vertex B will not necessarily equal that from B to A, and the total flow in both directions will be the sum of flow from A to B plus that from B to A. This function converts a directed graph to undirected form through reducing all pairs of directed edges to a single edge, and aggregating flows from both directions.

Usage

```
merge_directed_flows(graph)
```

Arguments

`graph` A graph containing a flow column as returned from `dodgr_flows_aggregate` or `dodgr_flows_disperse`

Value

An equivalent graph in which all directed edges have been reduced to single, undirected edges, and all directed flows aggregated to undirected flows.

Examples

```
graph <- weight_streetnet (hampi)
from <- sample (graph$from_id, size = 10)
to <- sample (graph$to_id, size = 5)
to <- to [!to %in% from]
flows <- matrix (10 * runif (length (from) * length (to)),
                 nrow = length (from))
graph <- dodgr_flows_aggregate (graph, from = from, to = to, flows = flows)
# graph then has an additional 'flows' column of aggregate flows along all
# edges. These flows are directed, and can be aggregated to equivalent
# undirected flows on an equivalent undirected graph with:
graph_undir <- merge_directed_flows (graph)
# This graph will only include those edges having non-zero flows, and so:
nrow (graph); nrow (graph_undir) # the latter is much smaller
```

os_roads_bristol

os_roads_bristol

Description

A sample street network for Bristol, U.K., from the Ordnance Survey.

Format

A Simple Features sf data.frame representing motorways in Bristol, UK.

Note

Input data downloaded from <https://www.ordnancesurvey.co.uk/opendatadownload/products.html>. To download the data from that page click on the tick box next to 'OS Open Roads', scroll to the bottom, click 'Continue' and complete the form on the subsequent page. This dataset is open access and can be used under the [Open Government License](#) and must be cited as follows: Contains OS data © Crown copyright and database right (2017)

Examples

```
## Not run:
library(sf)
library(dplyr)
os_roads <- sf::read_sf("~/data/ST_RoadLink.shp") # data must be unzipped here
u <- "https://opendata.arcgis.com/datasets/686603e943f948acaa13fb5d2b0f1275_4.kml"
lads <- sf::read_sf(u)
mapview::mapview(lads)
bristol_pol <- dplyr::filter(lads, grepl("Bristol", lad16nm))
os_roads <- st_transform(os_roads, st_crs(lads))
os_roads_bristol <- os_roads[bristol_pol, ] %>%
  dplyr::filter(class == "Motorway" & roadNumber != "M32") %>%
  st_zm(drop = TRUE)
mapview::mapview(os_roads_bristol)
```

```
## End(Not run)
# Converting this 'sf data.frame' to a 'dodgr' network requires manual
# specification of weighting profile:
colnm <- "formOfWay" # name of column used to determine weights
wts <- c(0.1, 0.2, 0.8, 1)
names(wts) <- unique(os_roads_bristol[[colnm]])
net <- weight_streetnet(os_roads_bristol, wt_profile = wts,
                        type_col = colnm, id_col = "identifier")
# 'id_col' tells the function which column to use to attribute IDs of ways
```

weighting_profiles	<i>weighting_profiles</i>
--------------------	---------------------------

Description

Collection of weighting profiles used to adjust the routing process to different means of transport. Original data taken from the Routino project.

Format

data.frame with profile names, means of transport and weights.

References

<https://www.routino.org/xml/routino-profiles.xml>

weight_railway	<i>weight_railway</i>
----------------	-----------------------

Description

Weight (or re-weight) an sf-formatted OSM street network for routing along railways.

Usage

```
weight_railway(sf_lines, type_col = "railway", id_col = "osm_id",
               keep_cols = c("maxspeed"), excluded = c("abandoned", "disused",
               "proposed", "razed"))
```

Arguments

<code>sf_lines</code>	A street network represented as <code>sf</code> <code>LINESTRING</code> objects, typically extracted with <code>dodgr_streetnet</code>
<code>type_col</code>	Specify column of the <code>sf</code> <code>data.frame</code> object which designates different types of railways to be used for weighting (default works with <code>osmdata</code> objects).
<code>id_col</code>	Specify column of the <code>codesf</code> <code>data.frame</code> object which provides unique identifiers for each railway (default works with <code>osmdata</code> objects).
<code>keep_cols</code>	Vectors of columns from <code>sf_lines</code> to be kept in the resultant <code>dodgr</code> network; vector can be either names or indices of desired columns.
<code>excluded</code>	Types of railways to exclude from routing.

Value

A `data.frame` of edges representing the rail network, along with a column of graph component numbers.

Note

Default railway weighting is by distance. Other weighting schemes, such as by maximum speed, can be implemented simply by modifying the `d_weighted` column returned by this function accordingly.

Examples

```
## Not run:
# sample railway extraction with the 'osmdata' package
library(osmdata)
dat <- opq("shinjuku") %>%
  add_osm_feature(key = "railway") %>%
  osmdata_sf(quiet = FALSE)
graph <- weight_railway(dat$osm_lines)

## End(Not run)
```

`weight_streetnet`
`weight_streetnet`

Description

Weight (or re-weight) an `sf`-formatted OSM street network according to a named routino profile, selected from (`foot`, `horse`, `wheelchair`, `bicycle`, `moped`, `motorcycle`, `motorcar`, `goods`, `hgv`, `psv`).

Usage

```
weight_streetnet(x, wt_profile = "bicycle", type_col = "highway",
  id_col = "osm_id", keep_cols = NULL)

## Default S3 method:
weight_streetnet(x, wt_profile = "bicycle",
  type_col = "highway", id_col = "osm_id", keep_cols = NULL)

## S3 method for class 'sf'
weight_streetnet(x, wt_profile = "bicycle",
  type_col = "highway", id_col = "osm_id", keep_cols = NULL)

## S3 method for class 'sc'
weight_streetnet(x, wt_profile = "bicycle",
  type_col = "highway", id_col = "osm_id", keep_cols = NULL)
```

Arguments

x	A street network represented as sf LINESTRING objects, typically extracted with <code>dodgr_streetnet</code>
wt_profile	Name of weighting profile, or vector of values with names corresponding to names in <code>type_col</code> (see Details)
type_col	Specify column of the sf data.frame object which designates different types of highways to be used for weighting (default works with osmdata objects).
id_col	Specify column of the codesf data.frame object which provides unique identifiers for each highway (default works with osmdata objects).
keep_cols	Vectors of columns from <code>sf_lines</code> to be kept in the resultant <code>dodgr</code> network; vector can be either names or indices of desired columns.

Value

A data.frame of edges representing the street network, along with a column of graph component numbers.

Note

Names for the `wt_profile` parameter are taken from [weighting_profiles](#), which is a data.frame of weights for different modes of transport. Current modes included there are "bicycle", "foot", "goods", "hgv", "horse", "moped", "motorcar", "motorcycle", "psv", and "wheelchair". Railway routing can be implemented with the separate function [weight_railway](#).

Examples

```
# hampi is included with package as an 'osmdata' sf-formatted street network
net <- weight_streetnet (hampi)
class(net) # data.frame
dim(net) # 6096 11; 6096 streets
# os_roads_bristol is also included as an sf data.frame, but in a different
```


Index

*Topic **datasets**

- hampi, [19](#)
- os_roads_bristol, [22](#)
- weighting_profiles, [23](#)

- compare_heaps, [2](#)
- compare_heaps(), [4](#)

- dodgr, [3](#)
- dodgr-package (dodgr), [3](#)
- dodgr_components, [4](#)
- dodgr_components(), [3](#)
- dodgr_contract_graph, [4](#)
- dodgr_contract_graph(), [3](#)
- dodgr_distances, [5](#)
- dodgr_dists, [5](#), [7](#), [20](#), [21](#)
- dodgr_dists(), [3](#)
- dodgr_flowmap, [9](#)
- dodgr_flows_aggregate, [9](#), [10](#), [20](#), [21](#)
- dodgr_flows_disperse, [9](#), [12](#), [21](#)
- dodgr_paths, [13](#), [20](#), [21](#)
- dodgr_sample, [14](#)
- dodgr_sample(), [4](#)
- dodgr_streetnet, [15](#)
- dodgr_streetnet(), [3](#)
- dodgr_to_igraph, [16](#)
- dodgr_to_sfc, [17](#)
- dodgr_to_tidygraph, [18](#)
- dodgr_vertices, [18](#)
- dodgr_vertices(), [4](#)

- hampi, [19](#)

- match_points_to_graph, [19](#), [19](#)
- match_pts_to_graph, [20](#)
- merge_directed_flows, [21](#)

- os_roads_bristol, [22](#)

- weight_railway, [23](#), [25](#)
- weight_streetnet, [24](#)

- weight_streetnet(), [3](#)
- weighting_profiles, [23](#), [25](#)