

Package ‘ethnobotanyR’

August 6, 2019

Type Package

Title Calculate Quantitative Ethnobotany Indices

Version 0.1.5

Author Cory Whitney

Maintainer Cory Whitney <whitney.cory@gmail.com>

Date 2019-08-05

Description Calculate common quantitative ethnobotany indices to assess the cultural significance of plant species based on informant consensus. The package closely follows the paper by Tardio and Pardo-de-Santayana (2008). Tardio, J., and M. Pardo-de-Santayana, 2008. Cultural Importance Indices: A Comparative Analysis Based on the Useful Wild Plants of Southern Cantabria (Northern Spain) 1. Economic Botany, 62(1), 24-39. <doi:10.1007/s12231-007-9004-5>.

Depends R (>= 2.10)

Imports dplyr, reshape, circlize, magrittr, assertthat, ggplot2, cowplot

License GPL

Encoding UTF-8

LazyData true

RoxygenNote 6.1.1

Suggests knitr, rmarkdown

VignetteBuilder knitr

NeedsCompilation no

Repository CRAN

Date/Publication 2019-08-06 06:50:02 UTC

R topics documented:

CIs	2
CVe	3
ethnobotanyChord	4

ethnobotanydata	4
ethnoChord	5
ethnoChordUser	6
FCs	7
FLs	7
NUs	8
Radial_plot	9
RFCs	10
RIs	11
simple_UVs	11
URs	12
URsum	13
UVs	14

Index	16
--------------	-----------

CIs	<i>Cultural Importance index (CI)</i>
-----	---------------------------------------

Description

Calculates the Cultural Importance Index (CI) per species.

Usage

```
CIs(data)
```

Arguments

data	is an ethnobotany data set with column 1 'informant' and 2 'sp_name' as row identifiers of informants and of species names respectively. The rest of the columns are the identified ethnobotany use categories. The data should be populated with counts of uses per person (should be 0 or 1 values).
------	--

Source

Tardio, J., and M. Pardo-de-Santayana, 2008. Cultural Importance Indices: A Comparative Analysis Based on the Useful Wild Plants of Southern Cantabria (Northern Spain) 1. *Economic Botany*, 62(1), 24-39. <<https://doi.org/10.1007/s12231-007-9004-5>>

Examples

```
#Use built-in ethnobotany data example
CIs(ethnobotanydata)

#Generate random dataset of three informants uses for four species
eb_data <- data.frame(replicate(10, sample(0:1, 20, rep=TRUE)))
names(eb_data) <- gsub(x = names(eb_data), pattern = "X", replacement = "Use_")
```

```
eb_data$informant<-sample(c('User_1', 'User_2', 'User_3'), 20, replace=TRUE)
eb_data$sp_name<-sample(c('sp_1', 'sp_2', 'sp_3', 'sp_4'), 20, replace=TRUE)
CIs(eb_data)
```

CVe

*Cultural Value of ethnospecies (CVe)***Description**

Calculates the Cultural Value (CVe) per ethnospecies.

Usage

```
CVe(data)
```

Arguments

`data` is an ethnobotany data set with column 1 'informant' and 2 'sp_name' as row identifiers of informants and of species names respectively.

Source

Reyes-Garcia, V., T. Huanca, V. Vadez, and W. Leonard. "Cultural, Practical, and Economic Value of Wild Plants: A Quantitative Study in the Bolivian Amazon." *Economic Botany*, 2006. <<https://doi.org/10.2307/4257061>>

Examples

```
#Use built-in ethnobotany data example
CVe(ethnobotanydata)

#Generate random dataset of three informants uses for four species
eb_data <- data.frame(replicate(10,sample(0:1,20,rep=TRUE)))
names(eb_data) <- gsub(x = names(eb_data), pattern = "X", replacement = "Use_")
eb_data$informant<-sample(c('User_1', 'User_2', 'User_3'), 20, replace=TRUE)
eb_data$sp_name<-sample(c('sp_1', 'sp_2', 'sp_3', 'sp_4'), 20, replace=TRUE)
CVe(eb_data)
```

ethnobotanyChord *Chord diagram of ethnobotany uses and species*

Description

Creates a chord diagram of species and uses for ethnobotany studies.

Usage

```
ethnobotanyChord(data)
```

Arguments

`data` is an ethnobotany data set with column 1 'informant' and 2 'sp_name' as row identifiers of informants and of species names respectively. The rest of the columns are the identified ethnobotany use categories. The data should be populated with counts of uses per person (should be 0 or 1 values).

Source

Whitney, C. W., Bahati, J., and Gebauer, J. (2018), Ethnobotany and agrobiodiversity; valuation of plants in the homegardens of southwestern Uganda. *Ethnobiology Letters*, 9(2), 90-100. <<https://doi.org/10.14237/eb1.9.2.2018.503>>

Examples

```
#Use built-in ethnobotany data example
ethnobotanyChord(ethnobotanydata)

#Generate random dataset of three informants uses for four species
eb_data <- data.frame(replicate(10,sample(0:1,20,rep=TRUE)))
names(eb_data) <- gsub(x = names(eb_data), pattern = "X", replacement = "Use_")
eb_data$informant<-sample(c('User_1', 'User_2', 'User_3'), 20, replace=TRUE)
eb_data$sp_name<-sample(c('sp_1', 'sp_2', 'sp_3', 'sp_4'), 20, replace=TRUE)
ethnobotanyChord(eb_data)
```

ethnobotanydata *Ethnobotany data set.*

Description

An ethnobotany dataset from 20 informants, four species and 10 uses column 1 'informant' lists the names or id's of knowledge holders column 2 'sp_name' lists the names or id's of species The other 10 columns are the identified ethnobotany use categories. The data is populated with counts of uses per person (0 and 1 values).

Usage

```
ethnobotanydata
```

Format

A data frame with 80 rows and 12 variables:

informant anonymized id's of 20 knowledge holders

sp_name id's of four species

Use_1 one of the categorized uses of species, 0 and 1 values

Use_2 one of the categorized uses of species, 0 and 1 values

Use_3 one of the categorized uses of species, 0 and 1 values

Use_4 one of the categorized uses of species, 0 and 1 values

Use_5 one of the categorized uses of species, 0 and 1 values

Use_6 one of the categorized uses of species, 0 and 1 values

Use_7 one of the categorized uses of species, 0 and 1 values

Use_8 one of the categorized uses of species, 0 and 1 values

Use_9 one of the categorized uses of species, 0 and 1 values

Use_10 one of the categorized uses of species, 0 and 1 values ...

ethnoChord

Chord diagram of ethnobotany uses and species

Description

Creates a chord diagram of species and uses for ethnobotany studies.

Usage

```
ethnoChord(data)
```

Arguments

data is an ethnobotany data set with column 1 'informant' and 2 'sp_name' as row identifiers of informants and of species names respectively. The rest of the columns are the identified ethnobotany use categories. The data should be populated with counts of uses per person (should be 0 or 1 values).

Source

Whitney, C. W., Bahati, J., and Gebauer, J. (2018), Ethnobotany and agrobiodiversity; valuation of plants in the homegardens of southwestern Uganda. *Ethnobiology Letters*, 9(2), 90-100. <<https://doi.org/10.14237/ebl.9.2.2018.503>>

Examples

```
#Use built-in ethnobotany data example
ethnoChord(ethnobotanydata)

#Generate random dataset of three informants uses for four species
eb_data <- data.frame(replicate(10,sample(0:1,20,rep=TRUE)))
names(eb_data) <- gsub(x = names(eb_data), pattern = "X", replacement = "Use_")
eb_data$informant<-sample(c('User_1', 'User_2', 'User_3'), 20, replace=TRUE)
eb_data$sp_name<-sample(c('sp_1', 'sp_2', 'sp_3', 'sp_4'), 20, replace=TRUE)
ethnoChord(eb_data)
```

ethnoChordUser

Chord diagram of informants and species uses

Description

Creates a chord diagram of informants and species uses for ethnobotany studies.

Usage

```
ethnoChordUser(data)
```

Arguments

data is an ethnobotany data set with column 1 'informant' and 2 'sp_name' as row identifiers of informants and of species names respectively. The rest of the columns are the identified ethnobotany use categories. The data should be populated with counts of uses per person (should be 0 or 1 values).

Source

Whitney, C. W., Bahati, J., and Gebauer, J. (2018), Ethnobotany and agrobiodiversity; valuation of plants in the homegardens of southwestern Uganda. *Ethnobiology Letters*, 9(2), 90-100. <<https://doi.org/10.14237/ebl.9.2.2018.503>>

Examples

```
#Use built-in ethnobotany data example
ethnoChordUser(ethnobotanydata)

#Generate random dataset of three informants uses for four species
eb_data <- data.frame(replicate(10,sample(0:1,20,rep=TRUE)))
names(eb_data) <- gsub(x = names(eb_data), pattern = "X", replacement = "Use_")
eb_data$informant<-sample(c('User_1', 'User_2', 'User_3'), 20, replace=TRUE)
eb_data$sp_name<-sample(c('sp_1', 'sp_2', 'sp_3', 'sp_4'), 20, replace=TRUE)
ethnoChordUser(eb_data)
```

FCs *Frequency of Citation (FC)*

Description

Calculates the frequency of citation (FC) per species.

Usage

```
FCs(data)
```

Arguments

`data` is an ethnobotany data set with column 1 'informant' and 2 'sp_name' as row identifiers of informants and of species names respectively. The rest of the columns are the identified ethnobotany use categories. The data should be populated with counts of uses per person (should be 0 or 1 values).

Source

Prance, G. T., W. Baleé, B. M. Boom, and R. L. Carneiro. "Quantitative Ethnobotany and the Case for Conservation in Amazonia." *Conservation Biology* 1, no. 4 (1987): 296–310.

Examples

```
#Use built-in ethnobotany data example
FCs(ethnobotanydata)

#Generate random dataset of three informants uses for four species
eb_data <- data.frame(replicate(10, sample(0:1, 20, rep=TRUE)))
names(eb_data) <- gsub(x = names(eb_data), pattern = "X", replacement = "Use_")
eb_data$informant <- sample(c('User_1', 'User_2', 'User_3'), 20, replace=TRUE)
eb_data$sp_name <- sample(c('sp_1', 'sp_2', 'sp_3', 'sp_4'), 20, replace=TRUE)
FCs(eb_data)
```

FLs *Fidelity Level (FL)*

Description

Calculates the fidelity level (FL) of species uses, i.e. the ratio between the number of informants who independently cite the use of a species for the same major purposes (URs) and the total number of informants who mentioned the plant for any use (FCs).

Usage

```
FLs(data)
```

Arguments

`data` is an ethnobotany data set with column 1 'informant' and 2 'sp_name' as row identifiers of informants and of species names respectively. The rest of the columns are the identified ethnobotany use categories. The data should be populated with counts of uses per person (should be 0 or 1 values).

Source

Friedman, J., Yaniv, Z., Dafni, A., Palewitch, D., 1986. A preliminary classification of the healing potential of medicinal plants, based on a rational analysis of an ethnopharmacological field survey among Bedouins in the Negev Desert, Israel. *Journal of Ethnopharmacology* 16, 275-287.

Examples

```
#Use built-in ethnobotany data example
FLs(ethnobotanydata)
#returns the primary use category (Primary.use) and the FLs value

#Generate random dataset of three informants uses for four species
eb_data <- data.frame(replicate(10,sample(0:1,20,rep=TRUE)))
names(eb_data) <- gsub(x = names(eb_data), pattern = "X", replacement = "Use_")
eb_data$informant<-sample(c('User_1', 'User_2', 'User_3'), 20, replace=TRUE)
eb_data$sp_name<-sample(c('sp_1', 'sp_2', 'sp_3', 'sp_4'), 20, replace=TRUE)

FLs(eb_data)
```

NUs	<i>Number of Uses (NU)</i>
-----	----------------------------

Description

Calculates the number of uses (NU) per species.

Usage

```
NUs(data)
```

Arguments

`data` is an ethnobotany data set with column 1 'informant' and 2 'sp_name' as row identifiers of informants and of species names respectively. The rest of the columns are the identified ethnobotany use categories. The data should be populated with counts of uses per person (should be 0 or 1 values).

Source

Prance, G. T., W. Baleé, B. M. Boom, and R. L. Carneiro. "Quantitative Ethnobotany and the Case for Conservation in Amazonia." *Conservation Biology* 1, no. 4 (1987): 296–310.

Examples

```
#Use built-in ethnobotany data example
NUs(ethnobotanydata)

#Generate random dataset of three informants uses for four species
eb_data <- data.frame(replicate(10,sample(0:1,20,rep=TRUE)))
names(eb_data) <- gsub(x = names(eb_data), pattern = "X", replacement = "Use_")
eb_data$informant<-sample(c('User_1', 'User_2', 'User_3'), 20, replace=TRUE)
eb_data$sp_name<-sample(c('sp_1', 'sp_2', 'sp_3', 'sp_4'), 20, replace=TRUE)
NUs(eb_data)
```

Radial_plot

Radial bar plot of use reports (UR) per species

Description

Creates a radial bar plot of use reports (UR) per species based on the 'UR function'.

Usage

```
Radial_plot(data, analysis)
```

Arguments

data	is an ethnobotany data set with column 1 'informant' and 2 'sp_name' as row identifiers of informants and of species names respectively. The rest of the columns are the identified ethnobotany use categories. The data should be populated with counts of uses per person (should be 0 or 1 values).
analysis	is one of the quantitative ethnobotany functions from ethnobotanyR, i.e. ethnobotanyR::FCs.

Examples

```
#Use built-in ethnobotany data example and Frequency of Citation function FCs()
Radial_plot(ethnobotanydata, analysis = FCs)

#Generate random dataset of three informants uses for four species
eb_data <- data.frame(replicate(10,sample(0:1,20,rep=TRUE)))
names(eb_data) <- gsub(x = names(eb_data), pattern = "X", replacement = "Use_")
eb_data$informant<-sample(c('User_1', 'User_2', 'User_3'), 20, replace=TRUE)
```

```
eb_data$sp_name<-sample(c('sp_1', 'sp_2', 'sp_3', 'sp_4'), 20, replace=TRUE)
Radial_plot(data = eb_data, analysis = FCs)
```

 RFCs

Relative Frequency of Citation (RFC)

Description

Calculates the relative frequency of citation (RFC) per species published by Pardo-de-Santayana (2003).

Usage

```
RFCs(data)
```

Arguments

`data` is an ethnobotany data set with column 1 'informant' and 2 'sp_name' as row identifiers of informants and of species names respectively. The rest of the columns are the identified ethnobotany use categories. The data should be populated with counts of uses per person (should be 0 or 1 values).

Source

Tardio, J., and M. Pardo-de-Santayana, 2008. Cultural Importance Indices: A Comparative Analysis Based on the Useful Wild Plants of Southern Cantabria (Northern Spain) 1. *Economic Botany*, 62(1), 24-39. <<https://doi.org/10.1007/s12231-007-9004-5>>

Examples

```
#Use built-in ethnobotany data example
RFCs(ethnobotanydata)

#Generate random dataset of three informants uses for four species
eb_data <- data.frame(replicate(10,sample(0:1,20,rep=TRUE)))
names(eb_data) <- gsub(x = names(eb_data), pattern = "X", replacement = "Use_")
eb_data$informant<-sample(c('User_1', 'User_2', 'User_3'), 20, replace=TRUE)
eb_data$sp_name<-sample(c('sp_1', 'sp_2', 'sp_3', 'sp_4'), 20, replace=TRUE)
RFCs(eb_data)
```

RIs *Relative Importance index (RI)*

Description

Calculates the relative importance index (RI) per species, published by Pardo-de-Santayana (2003).

Usage

```
RIs(data)
```

Arguments

`data` is an ethnobotany data set with column 1 'informant' and 2 'sp_name' as row identifiers of informants and of species names respectively. The rest of the columns are the identified ethnobotany use categories. The data should be populated with counts of uses per person (should be 0 or 1 values).

Source

Tardio, J., and M. Pardo-de-Santayana, 2008. Cultural Importance Indices: A Comparative Analysis Based on the Useful Wild Plants of Southern Cantabria (Northern Spain) 1. *Economic Botany*, 62(1), 24-39. <<https://doi.org/10.1007/s12231-007-9004-5>>

Examples

```
#Use built-in ethnobotany data example
RIs(ethnobotanydata)

#Generate random dataset of three informants uses for four species
eb_data <- data.frame(replicate(10,sample(0:1,20,rep=TRUE)))
names(eb_data) <- gsub(x = names(eb_data), pattern = "X", replacement = "Use_")
eb_data$informant<-sample(c('User_1', 'User_2', 'User_3'), 20, replace=TRUE)
eb_data$sp_name<-sample(c('sp_1', 'sp_2', 'sp_3', 'sp_4'), 20, replace=TRUE)
RIs(eb_data)
```

simple_UVs *Use Value (UV) index per species*

Description

Calculates the simplified use value (UV) index for each species in the data set (see Albuquerque et al. 2006).

Usage

```
simple_UVs(data)
```

Arguments

`data` is an ethnobotany data set with column 1 'informant' and 2 'sp_name' as row identifiers of informants and of species names respectively. The rest of the columns are the identified ethnobotany use categories. The data should be populated with counts of uses per person (should be 0 or 1 values).

Source

Albuquerque, U. P., R. F. P. Lucena, J. M. Monteiro, A. T. N. Florentino, and C. F. C. B. R. Almeida. 2006. Evaluating Two Quantitative Ethnobotanical Techniques. *Ethnobotany Research and Applications* 4:51–60. <<http://hdl.handle.net/10125/237>>

Examples

```
#Use built-in ethnobotany data example
simple_UVs(ethnobotanydata)

#Generate random dataset of three informants uses for four species
eb_data <- data.frame(replicate(10,sample(0:1,20,rep=TRUE)))
names(eb_data) <- gsub(x = names(eb_data), pattern = "X", replacement = "Use_")
eb_data$informant<-sample(c('User_1', 'User_2', 'User_3'), 20, replace=TRUE)
eb_data$sp_name<-sample(c('sp_1', 'sp_2', 'sp_3', 'sp_4'), 20, replace=TRUE)
simple_UVs(eb_data)
```

URs

Use Report (UR)

Description

Calculates the use reports (UR) per species, a common metric for ethnobotany studies.

Usage

```
URs(data)
```

Arguments

`data` is an ethnobotany data set with column 1 'informant' and 2 'sp_name' as row identifiers of informants and of species names respectively. The rest of the columns are the identified ethnobotany use categories. The data should be populated with counts of uses per person (should be 0 or 1 values).

Source

Prance, G. T., W. Baleé, B. M. Boom, and R. L. Carneiro. “Quantitative Ethnobotany and the Case for Conservation in Amazonia.” *Conservation Biology* 1, no. 4 (1987): 296–310.

Examples

```
#Use built-in ethnobotany data example
URs(ethnobotanydata)

#Generate random dataset of three informants uses for four species
eb_data <- data.frame(replicate(10,sample(0:1,20,rep=TRUE)))
names(eb_data) <- gsub(x = names(eb_data), pattern = "X", replacement = "Use_")
eb_data$informant<-sample(c('User_1', 'User_2', 'User_3'), 20, replace=TRUE)
eb_data$sp_name<-sample(c('sp_1', 'sp_2', 'sp_3', 'sp_4'), 20, replace=TRUE)
URs(eb_data)
```

URsum

Sum of all Use Reports (UR) for all species

Description

Calculates the sum of all ethnobotany use reports (UR) for all species, a common metric for ethnobotany studies.

Usage

```
URsum(data)
```

Arguments

`data` is an ethnobotany data set with column 1 'informant' and 2 'sp_name' as row identifiers of informants and of species names respectively. The rest of the columns are the identified ethnobotany use categories. The data should be populated with counts of uses per person (should be 0 or 1 values).

Source

Prance, G. T., W. Baleé, B. M. Boom, and R. L. Carneiro. “Quantitative Ethnobotany and the Case for Conservation in Amazonia.” *Conservation Biology* 1, no. 4 (1987): 296–310.

Examples

```
#Use built-in ethnobotany data example
URsum(ethnobotanydata)

#Generate random dataset of three informants uses for four species
eb_data <- data.frame(replicate(10,sample(0:1,20,rep=TRUE)))
names(eb_data) <- gsub(x = names(eb_data), pattern = "X", replacement = "Use_")
eb_data$informant<-sample(c('User_1', 'User_2', 'User_3'), 20, replace=TRUE)
eb_data$sp_name<-sample(c('sp_1', 'sp_2', 'sp_3', 'sp_4'), 20, replace=TRUE)
URsum(eb_data)
```

 UVs

Use Value (UV) index per species

Description

Calculates the use value (UV) index for each species in the data set (see Tardio and Pardo-de-Santayana 2008).

Usage

```
UVs(data)
```

Arguments

data is an ethnobotany data set with column 1 'informant' and 2 'sp_name' as row identifiers of informants and of species names respectively. The rest of the columns are the identified ethnobotany use categories. The data should be populated with counts of uses per person (should be 0 or 1 values).

Source

Tardio, Javier, and Manuel Pardo-de-Santayana. "Cultural Importance Indices: A Comparative Analysis Based on the Useful Wild Plants of Southern Cantabria (Northern Spain)1." *Economic Botany* 62, no. 1 (May 2008): 24–39. <<https://doi.org/10.1007/s12231-007-9004-5>>

Examples

```
#Use built-in ethnobotany data example
UVs(ethnobotanydata)

#Generate random dataset of three informants uses for four species
eb_data <- data.frame(replicate(10,sample(0:1,20,rep=TRUE)))
names(eb_data) <- gsub(x = names(eb_data), pattern = "X", replacement = "Use_")
eb_data$informant<-sample(c('User_1', 'User_2', 'User_3'), 20, replace=TRUE)
eb_data$sp_name<-sample(c('sp_1', 'sp_2', 'sp_3', 'sp_4'), 20, replace=TRUE)
```

UVs(eb_data)

Index

- *Topic **bar**
 - Radial_plot, 9
- *Topic **chord**
 - ethnoChord, 5
 - ethnoChordUser, 6
- *Topic **citation**
 - FCs, 7
 - RFCs, 10
- *Topic **cultural**
 - CIs, 2
 - CVe, 3
 - ethnoChord, 5
 - ethnoChordUser, 6
 - FLs, 7
 - simple_UVs, 11
 - URs, 12
 - UVs, 14
- *Topic **datasets**
 - ethnobotanydata, 4
- *Topic **diagram**
 - ethnoChord, 5
 - ethnoChordUser, 6
- *Topic **ethnobotany**
 - CIs, 2
 - CVe, 3
 - ethnobotanyChord, 4
 - ethnobotanydata, 4
 - ethnoChord, 5
 - ethnoChordUser, 6
 - FCs, 7
 - FLs, 7
 - NUs, 8
 - Radial_plot, 9
 - RFCs, 10
 - RIIs, 11
 - simple_UVs, 11
 - URs, 12
 - URsum, 13
 - UVs, 14
- *Topic **fidelity**
 - FLs, 7
- *Topic **frequency**
 - FCs, 7
 - RFCs, 10
- *Topic **importance**
 - CIs, 2
 - CVe, 3
 - RIIs, 11
 - simple_UVs, 11
 - UVs, 14
- *Topic **number**
 - NUs, 8
- *Topic **of**
 - NUs, 8
- *Topic **plot**
 - Radial_plot, 9
- *Topic **quantitative**
 - CIs, 2
 - CVe, 3
 - ethnoChord, 5
 - ethnoChordUser, 6
 - FCs, 7
 - NUs, 8
 - RFCs, 10
 - RIIs, 11
 - simple_UVs, 11
 - URs, 12
 - URsum, 13
 - UVs, 14
- *Topic **radial**
 - Radial_plot, 9
- *Topic **relative**
 - RFCs, 10
 - RIIs, 11
- *Topic **report**
 - ethnoChord, 5
 - ethnoChordUser, 6
 - FLs, 7

- URs, [12](#)
- URsum, [13](#)
- *Topic **uses**
 - NUs, [8](#)
- *Topic **use**
 - ethnoChord, [5](#)
 - ethnoChordUser, [6](#)
 - FLs, [7](#)
 - simple_UVs, [11](#)
 - URs, [12](#)
 - URsum, [13](#)
 - UVs, [14](#)
- *Topic **value**
 - ethnoChord, [5](#)
 - ethnoChordUser, [6](#)
 - FLs, [7](#)
 - simple_UVs, [11](#)
 - URs, [12](#)
 - UVs, [14](#)
- *Topic **visualuzation**
 - Radial_plot, [9](#)

CIIs, [2](#)

CVe, [3](#)

ethnobotanyChord, [4](#)

ethnobotanydata, [4](#)

ethnoChord, [5](#)

ethnoChordUser, [6](#)

FCs, [7](#)

FLs, [7](#)

NUs, [8](#)

Radial_plot, [9](#)

RFCs, [10](#)

RIIs, [11](#)

simple_UVs, [11](#)

URs, [12](#)

URsum, [13](#)

UVs, [14](#)