

# Package ‘freesurfer’

October 10, 2017

**Type** Package

**Title** Wrapper Functions for 'Freesurfer'

**Version** 1.6.1

**Author** John Muschelli <muschellij2@gmail.com>

**Maintainer** John Muschelli <muschellij2@gmail.com>

**Description** Wrapper functions that interface with 'Freesurfer' <<https://surfer.nmr.mgh.harvard.edu/>>, a powerful and commonly-used 'neuroimaging' software, using system commands. The goal is to be able to interface with 'Freesurfer' completely in R, where you pass R objects of class 'nifti', implemented by package 'oro.nifti', and the function executes an 'Freesurfer' command and returns an R object of class 'nifti' or necessary output.

**LazyData** true

**LazyLoad** true

**Imports** methods, neurobase, tools, R.utils, reshape2

**Depends** R (>= 3.2.0)

**License** GPL-3

**Suggests** magrittr, knitr, oro.nifti (>= 0.7), rgl, rmarkdown, pander, fslr (>= 2.9.2)

**BugReports** <https://github.com/muschellij2/freesurfer/issues>

**SystemRequirements** Freesurfer (<https://surfer.nmr.mgh.harvard.edu/>)

**RoxygenNote** 6.0.1.9000

**VignetteBuilder** knitr

**Encoding** UTF-8

**NeedsCompilation** no

**Repository** CRAN

**Date/Publication** 2017-10-10 14:20:36 UTC

**R topics documented:**

aparcstats2table . . . . .	3
aparcstats2table.help . . . . .	4
aparc_to_bg . . . . .	5
asegstats2table . . . . .	5
asegstats2table.help . . . . .	6
checkmnc-methods . . . . .	7
check_fs_result . . . . .	7
construct_subj_dir . . . . .	8
convert_surface . . . . .	9
freesurferdir . . . . .	10
freesurfer_read3 . . . . .	10
freesurfer_read3_con . . . . .	11
freesurfer_read_curv . . . . .	12
freesurfer_read_surf . . . . .	12
fs_cmd . . . . .	13
fs_help . . . . .	14
fs_imgext . . . . .	14
fs_lut . . . . .	15
fs_subj_dir . . . . .	15
fs_version . . . . .	16
get_fs . . . . .	16
get_fs_output . . . . .	17
have_fs . . . . .	17
mnc2nii . . . . .	18
mnc2nii.help . . . . .	19
mrisc_convert . . . . .	19
mrisc_convert.help . . . . .	20
mrisc_convert_annot . . . . .	20
mrisc_convert_curv . . . . .	21
mrisc_convert_normals . . . . .	22
mrisc_convert_vertex . . . . .	22
mrisc_euler_number . . . . .	23
mrisc_euler_number.help . . . . .	24
mri_convert . . . . .	24
mri_convert.help . . . . .	25
mri_info . . . . .	25
mri_info.help . . . . .	26
mri_mask . . . . .	26
mri_mask.help . . . . .	27
mri_normalize . . . . .	27
mri_normalize.help . . . . .	28
mri_segment . . . . .	28
mri_segment.help . . . . .	29
mri_surf2surf . . . . .	29
mri_surf2surf.help . . . . .	30
mri_watershed . . . . .	31

mri_watershed.help . . . . .	31
nii2mnc . . . . .	32
nii2mnc.help . . . . .	32
nu_correct . . . . .	33
nu_correct.help . . . . .	33
readmgz . . . . .	34
readmnc . . . . .	34
read_aseg_stats . . . . .	35
read_fs_label . . . . .	35
read_fs_table . . . . .	36
recon . . . . .	37
reconner . . . . .	40
recon_all . . . . .	41
recon_con1 . . . . .	41
run_check_fs_cmd . . . . .	42
set_fs_subj_dir . . . . .	43
surface_to_obj . . . . .	43
surface_to_triangles . . . . .	44
surf_convert . . . . .	45
tracker . . . . .	46
trac_all . . . . .	46
trac_prep . . . . .	47

<b>Index</b>	<b>48</b>
--------------	-----------

---

aparcstats2table	<i>Parcellation Stats to Table</i>
------------------	------------------------------------

---

## Description

This function calls `aparcstats2table` to convert parcellation statistics to a table

## Usage

```
aparcstats2table(subjects, outfile = NULL, hemi = c("lh", "rh"),
  measure = c("area", "volume", "thickness", "thicknessstd", "meancurv",
    "gauscurv", "foldind", "curvind"), sep = c("tab", "space", "comma",
    "semicolon"), parc = c("aparc", "aparc.a2009s"), skip = FALSE,
  subj_dir = NULL, opts = "", verbose = TRUE)
```

## Arguments

subjects	(character) vector of subjects
outfile	(character) output filename
hemi	(character) hemisphere to run statistics
measure	(character) measure to be calculated
sep	(character) separator for the output file. This will be an attribute of outfile

parc	(character) parcellation to compute on
skip	(logical) if subject does not have parcellation, should the command skip that subject (TRUE) or error (FALSE)
subj_dir	(character path) if a different subjects directory is to be used other than SUBJECTS_DIR from shell, it can be specified here. Use with care as if the command fail, it may not reset the SUBJECTS_DIR back correctly after the error
opts	(character) additional options to aparcstats2table
verbose	(logical) print diagnostic messages

**Value**

Character filename of output file, with the attribute of the separator

**Examples**

```
if (have_fs()) {
  fs_subj_dir()
  outfile = aparcstats2table(subjects = "bert",
                             hemi = "lh",
                             meas = "thickness")
}
```

---

aparcstats2table.help *Parcellation Stats to Table Help*

---

**Description**

This calls Freesurfer's aparcstats2table help

**Usage**

```
aparcstats2table.help()
```

**Value**

Result of fs\_help

---

aparcs_to_bg	<i>Convert Freesurfer aparcs Table to brainGraph</i>
--------------	------------------------------------------------------

---

**Description**

Converts Freesurfer aparcs table to brainGraph naming convention, relying on [aparstats2table](#)

**Usage**

```
aparcs_to_bg(subjects, measure, ...)
```

**Arguments**

subjects	subjects to analyze, passed to <a href="#">aparstats2table</a>
measure	measure to be analyzed, passed to <a href="#">aparstats2table</a>
...	additional arguments passed to <a href="#">aparstats2table</a>

**Value**

Long data.frame

**Examples**

```
if (have_fs()) {
  fs_subj_dir()
  df = aparcs_to_bg(subjects = "bert", measure = "thickness")
  print(head(df))
}
```

---

asegstats2table	<i>Parcellation Stats to Table</i>
-----------------	------------------------------------

---

**Description**

This function calls `asegstats2table` to convert parcellation statistics to a table

**Usage**

```
asegstats2table(subjects = NULL, inputs = NULL, outfile = NULL,
  measure = c("volume", "mean", "std"), sep = c("tab", "space", "comma",
  "semicolon"), skip = FALSE, subj_dir = NULL, opts = "",
  verbose = TRUE)
```

**Arguments**

subjects	(character) vector of subjects
inputs	(character paths) vector of input filenames, e.g. aseg.stats.
outfile	(character) output filename
measure	(character) measure to be calculated
sep	(character) separator for the output file. This will be an attribute of outfile
skip	(logical) if subject does not have parcellation, should the command skip that subject (TRUE) or error (FALSE)
subj_dir	(character path) if a different subjects directory is to be used other than SUBJECTS_DIR from shell, it can be specified here. Use with care as if the command fail, it may not reset the SUBJECTS_DIR back correctly after the error
opts	(character) additional options to asegstats2table
verbose	(logical) print diagnostic messages

**Value**

Character filename of output file, with the attribute of the separator

**Examples**

```
if (have_fs()) {
  outfile = asegstats2table(subjects = "bert",
                           meas = "mean")
}
```

---

asegstats2table.help *Parcellation Stats to Table Help*

---

**Description**

This calls Freesurfer's asegstats2table help

**Usage**

```
asegstats2table.help()
```

**Value**

Result of fs\_help

---

checkmnc-methods	<i>Force object to filename with .mnc extension</i>
------------------	-----------------------------------------------------

---

**Description**

Ensures the output to be a character filename (or vector) from an input image or nifti to have .mnc extension and be converted to MNC when necessary

**Usage**

```
checkmnc(file, ...)  
  
## S4 method for signature 'nifti'  
checkmnc(file, ...)  
  
## S4 method for signature 'character'  
checkmnc(file, ...)  
  
## S4 method for signature 'list'  
checkmnc(file, ...)  
  
ensure_mnc(file, ...)
```

**Arguments**

file	character or nifti object
...	options passed to <a href="#">checking</a>

**Value**

Character filename of mnc image

**Author(s)**

John Muschelli <muschellij2@gmail.com>

---

check_fs_result	<i>Check Freesurfer Result</i>
-----------------	--------------------------------

---

**Description**

Checks the Freesurfer system command result and will stop or warning based on whether output files exist.

**Usage**

```
check_fs_result(res, fe_before, fe_after)
```

**Arguments**

res	(numeric) Result from system command
fe_before	(logical) did the output file exist before the command ran
fe_after	(logical) did the output file exist after the command ran

---

construct\_subj\_dir      *Construct Subject Directory*

---

**Description**

This function copies files specified by the types of data, determined by the folder Freesurfer put them in, into a temporary directory for easier separation of data and different structuring of data.

**Usage**

```
construct_subj_dir(label = NULL, mri = NULL, stats = NULL, surf = NULL,
  touch = NULL, subj = NULL, subj_root_dir = tempdir())
```

**Arguments**

label	Files to copy to subj_root_dir/subj/label folder
mri	Files to copy to subj_root_dir/subj/mri folder
stats	Files to copy to subj_root_dir/subj/stats folder
surf	Files to copy to subj_root_dir/subj/surf folder
touch	Files to copy to subj_root_dir/subj/touch folder
subj	Name of subject to make folder for to use for Freesurfer functions. If NULL, a temporary id will be generated
subj_root_dir	Directory to put folder with contents of subj

**Value**

List with the subject name, the SUBJECTS\_DIR to use (the directory that contains the subject name), and the types of objects copied



## Examples

```
## Not run:
library(freesurfer)
label = "/Applications/freesurfer/subjects/bert/label/aparc.annot.a2009s.ctab"
mri = c(
  "/Applications/freesurfer/subjects/bert/mri/aparc.a2009s+aseg.mgz",
  "/Applications/freesurfer/subjects/bert/mri/aseg.auto.mgz")
stats = c("/Applications/freesurfer/subjects/bert/stats/lh.aparc.stats",
          "/Applications/freesurfer/subjects/bert/stats/aseg.stats")
surf = "/Applications/freesurfer/subjects/bert/surf/lh.thickness"
touch = NULL

## End(Not run)
```

---

convert_surface	<i>Convert Freesurfer Surface</i>
-----------------	-----------------------------------

---

## Description

Reads in a surface file from Freesurfer and separates into vertices and faces

## Usage

```
convert_surface(infile, ...)
```

## Arguments

infile	Input surface file
...	additional arguments to pass to <a href="#">mris_convert</a>

## Value

List of 3 elements: a header indicating the number of vertices and faces, the vertices, and the faces

## Note

This was adapted from the gist: <https://gist.github.com/mm--/4a4fc7badacfad874102>

## Examples

```
if (have_fs()) {
  infile = file.path(fs_subj_dir(),
                    "bert", "surf", "rh.pial")
  res = convert_surface(infile = infile)
}
```

---

freesurferdir	<i>Get Freesurfer's Directory</i>
---------------	-----------------------------------

---

**Description**

Finds the FREESURFER\_HOME from system environment or getopt("freesurfer.path") for location of Freesurfer fuctions and returns it

**Usage**

freesurferdir()

freesurfer\_dir()

fs\_dir()

**Value**

Character path

**Examples**

```
if (have_fs()) {
  freesurferdir()
  freesurfer_dir()
  fs_dir()
}
```

---

freesurfer_read3	<i>Freesurfer Read 3 records</i>
------------------	----------------------------------

---

**Description**

Reads first 3 records of file and returns the rotated value, for checking for other functions.

**Usage**

freesurfer\_read3(file)

**Arguments**

file                    thickness file or anything in surf/ directory from Freesurfer subject

**Value**

Numeric

## Examples

```
if (have_fs()) {  
  bert_dir = file.path(fs_subj_dir(), "bert", "surf")  
  file = file.path(bert_dir, "lh.thickness")  
  out = freesurfer_read3(file)  
}
```

---

freesurfer\_read3\_con *Freesurfer Read 3 records*

---

## Description

Reads first 3 records from a connection and returns the rotated value, for checking for other functions.

## Usage

```
freesurfer_read3_con(fid)
```

## Arguments

fid	connection to a thickness file or anything in surf/ directory from Freesurfer subject
-----	---------------------------------------------------------------------------------------

## Value

Numeric

## Examples

```
if (have_fs()) {  
  bert_dir = file.path(fs_subj_dir(), "bert", "surf")  
  file = file.path(bert_dir, "lh.thickness")  
  fid = file(file, open = "rb")  
  out = freesurfer_read3_con(fid)  
}
```

freesurfer\_read\_curv *Read Freesurfer Curv file*

---

**Description**

Reads a Freesurfer curvature file according to the FREESURFER\_HOME/matlab/read\_curv.m file.

**Usage**

```
freesurfer_read_curv(file)
```

**Arguments**

file                    file name of a curvature file

**Value**

Numeric vector

**Examples**

```
if (have_fs()) {  
    bert_dir = file.path(fs_subj_dir(), "bert", "surf")  
    file = file.path(bert_dir, "lh.thickness")  
    fid = file(file, open = "rb")  
    out = freesurfer_read_curv(file)  
}
```

---

freesurfer\_read\_surf *Read Freesurfer Surface file*

---

**Description**

Reads a Freesurfer Surface file from the surf/ directory from recon-all

**Usage**

```
freesurfer_read_surf(file)
```

**Arguments**

file                    surface file (e.g. lh.inflated)

**Value**

List of length 2: vertices and faces are the elements

**Examples**

```

if (have_fs()) {
  fname = file.path(fs_subj_dir(), "bert", "surf", "lh.inflated")
  out = freesurfer_read_surf(fname)
}

```

fs\_cmd

*FS Command Wrapper***Description**

This function calls Freesurfer command passed to func

**Usage**

```

fs_cmd(func, file, outfile = NULL, retimg = TRUE, reorient = FALSE,
intern = FALSE, opts = "", verbose = TRUE, samefile = FALSE,
opts_after_outfile = FALSE, frontopts = "", add_ext = TRUE,
bin_app = "bin", ...)

```

**Arguments**

func	(character) Freesurfer function
file	(character) image to be manipulated
outfile	(character) resultant image name (optional)
retimg	(logical) return image of class nifti
reorient	(logical) If retimg, should file be reoriented when read in? Passed to <a href="#">readnii</a> .
intern	(logical) to be passed to <a href="#">system</a>
opts	(character) operations to be passed to func
verbose	(logical) print out command before running
samefile	(logical) is the output the same file?
opts_after_outfile	(logical) should opts come after the outfile in the Freesurfer command?
frontopts	(character) options/character to put in before filename
add_ext	(logical) should the extension be added to the outfile
bin_app	(character) appendix to add to <a href="#">get_fs</a>
...	additional arguments passed to <a href="#">system</a> .

**Value**

If retimg then object of class nifti. Otherwise, Result from system command, depends if intern is TRUE or FALSE.

---

fs_help	<i>Wrapper for getting Freesurfer help</i>
---------	--------------------------------------------

---

**Description**

This function takes in the function and returns the help from Freesurfer for that function

**Usage**

```
fs_help(func_name, help.arg = "--help", extra.args = "", ...)
```

**Arguments**

func_name	Freesurfer function name
help.arg	Argument to print help, usually "-help"
extra.args	Extra arguments to be passed other than --help
...	additional arguments to <a href="#">get_fs</a>

**Value**

Prints help output and returns output as character vector

**Examples**

```
if (have_fs()) {
  fs_help(func_name = "mri_watershed")
}
```

---

fs_imgext	<i>Determine extension of image based on FSLOUTPUTTYPE</i>
-----------	------------------------------------------------------------

---

**Description**

Runs `get_fs_output()` to extract FSLOUTPUTTYPE and then gets corresponding extension (such as .nii.gz)

**Usage**

```
fs_imgext()
```

**Value**

Extension for output type

**Examples**

```
fs_imgext()
```

---

fs_lut	<i>Freesurfer look up table (LUT)</i>
--------	---------------------------------------

---

**Description**

A `data.frame` with the index, label, and RGBA (red, blue, green, alpha) specification for the segmentations

**Usage**

```
fs_lut
```

**Format**

An object of class `data.frame` with 1266 rows and 6 columns.

---

fs_subj_dir	<i>Determine Freesurfer Subjects Directory</i>
-------------	------------------------------------------------

---

**Description**

Finds the `SUBJECTS_DIR` from system environment or `getOption("fs.subj_dir")` for subjects dir

**Usage**

```
fs_subj_dir()
```

**Value**

`SUBJECTS_DIR`, such as `${FREESURFER_HOME}/subjects`

**Examples**

```
if (have_fs()) {  
  fs_subj_dir()  
}
```

---

fs_version	<i>Find Freesurfer Version</i>
------------	--------------------------------

---

**Description**

Finds the Freesurfer version from FREESURFER\_HOME/build-stamp.txt

**Usage**

```
fs_version()
```

**Value**

If the version file does not exist, it will throw a warning, but it will return an empty string. Otherwise it will be a string of the version.

**Note**

This will use fs\_dir() to get the directory of FREESURFER

**Examples**

```
if (have_fs()) {
  fs_version()
}
```

---

get_fs	<i>Create command declaring FREESURFER_HOME</i>
--------	-------------------------------------------------

---

**Description**

Finds the Freesurfer from system environment or getopt("freesurfer.path") for location of Freesurfer functions

**Usage**

```
get_fs(bin_app = c("bin", "mni/bin", ""))
```

**Arguments**

bin_app	Should bin be added to the freesurfer path? All executables are assumed to be in FREESURFER_HOME/bin/. If not, and bin_app = "", they will be assumed to be in FREESURFER_HOME/.
---------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

**Value**

NULL if Freesurfer in path, or bash code for setting up Freesurfer DIR



**Note**

This will use `Sys.getenv("FREESURFER_HOME")` before `getOption("freesurfer.path")`. If the directory is not found for Freesurfer in `Sys.getenv("FreesurferDIR")` and `getOption("freesurfer.path")`, it will try the default directory `/usr/local/freesurfer`.

**Examples**

```
if (have_fs()) {
  get_fs()
}
```

---

get_fs_output	<i>Determine Freesurfer output type</i>
---------------	-----------------------------------------

---

**Description**

Finds the `FSF_OUTPUT_FORMAT` from system environment or `getOption("fs.outputtype")` for output type (nii.gz, nii, ANALYZE, etc)

**Usage**

```
get_fs_output()
```

**Value**

`FSF_OUTPUT_FORMAT`, such as `nii.gz`. If none found, uses `nii.gz` as default

**Examples**

```
get_fs_output()
```

---

have_fs	<i>Logical check if Freesurfer is accessible</i>
---------	--------------------------------------------------

---

**Description**

Uses `get_fs` to check if `FreesurferDIR` is accessible or the option `freesurfer.path` is set and returns logical

**Usage**

```
have_fs(...)
```

**Arguments**

... options to pass to `get_fs`

**Value**

Logical TRUE if Freesurfer is accessible, FALSE if not

**Examples**

```
have_fs()
```

---

mnc2nii	<i>Convert MNC to NIFTI</i>
---------	-----------------------------

---

**Description**

This function calls `mnc2nii` to convert MNC files to NIFTI

**Usage**

```
mnc2nii(file, outfile = NULL)
```

**Arguments**

file	(character) input filename
outfile	(character) output filename

**Value**

Character filename of output

**Examples**

```
if (have_fs()) {  
  img = oro.nifti::nifti(array(rnorm(5*5*5), dim = c(5,5,5)))  
  mnc = nii2mnc(img)  
  img_file = mnc2nii(mnc, outfile = tempfile(fileext = ".nii"))  
  neurobase::readnii(img_file, verbose = TRUE)  
}
```

---

mnc2nii.help	<i>MNC to NIfTI Help</i>
--------------	--------------------------

---

**Description**

This calls Freesurfer's mnc2nii help

**Usage**

```
mnc2nii.help()
```

**Value**

Result of fs\_help

---

mris_convert	<i>Use Freesurfer's MRIs Converter</i>
--------------	----------------------------------------

---

**Description**

This function call mris\_convert, a general conversion program for converting between cortical surface file formats

**Usage**

```
mris_convert(infile, outfile = NULL, ext = ".asc", opts = "",
  verbose = TRUE)
```

**Arguments**

infile	(character) file path for input file
outfile	(character) output file path
ext	(character) output file extension, default is set to .asc
opts	(character) additional options to add to front of command
verbose	(logical) print diagnostic messages

**Value**

Name of output file

**Examples**

```
if (have_fs()) {
  bert_surf_dir = file.path(fs_subj_dir(), "bert", "surf")
  asc_file = mris_convert(
    infile = file.path(bert_surf_dir, "lh.white")
  )
}
```

---

mris\_convert.help      *Help file for Freesurfer's MRIs Converter*

---

### Description

This calls Freesurfer's `mris_convert help`

### Usage

```
mris_convert.help()
```

### Value

Result of `fs_help`

---

mris\_convert\_annot      *Convert Annotation file*

---

### Description

This function call `mris_convert`, using the `--annot` option

### Usage

```
mris_convert_annot(annot, opts = "", ...)
```

### Arguments

<code>annot</code>	(character) annotation or gifti label data
<code>opts</code>	(character) additional options to <code>mris_convert</code>
<code>...</code>	additional arguments to <code>mris_convert</code>

### Value

Result of `mris_convert`

### Examples

```
if (have_fs()) {
  bert_dir = file.path(fs_subj_dir(), "bert")
  gii_file = mris_convert_annot(
    infile = file.path(bert_dir, "surf", "lh.white"),
    annot = file.path(bert_dir, "label", "lh.aparc.annot"),
    ext = ".gii"
  )
  gii = mris_convert_annot(
```

```
infile = file.path(bert_dir, "surf", "lh.white"),
annot = gii_file,
ext = ".gii"
)
}
```

---

mris\_convert\_curv      *Convert Curvature file*

---

## Description

This function call `mris_convert`, using the `-c` option

## Usage

```
mris_convert_curv(curv, opts = "", ...)
```

## Arguments

curv	(character) scalar curv overlay file
opts	(character) additional options to <code>mris_convert</code>
...	additional arguments to <code>mris_convert</code>

## Value

Result of `mris_convert`

## Examples

```
if (have_fs()) {
  bert_surf_dir = file.path(fs_subj_dir(), "bert", "surf")
  asc_file = mris_convert_curv(
    infile = file.path(bert_surf_dir, "lh.white"),
    curv = file.path(bert_surf_dir, "lh.thickness")
  )
  res = read_fs_table(asc_file, header = FALSE)
  colnames(res) = c("index", "coord_1", "coord_2", "coord_3", "value")
  head(res)
}
```

mris\_convert\_normals *Convert Surface to Surface normals*

---

### Description

This function call `mris_convert`, using the `-n` option

### Usage

```
mris_convert_normals(opts = "", ...)
```

### Arguments

`opts` (character) additional options to `mris_convert`  
`...` additional arguments to `mris_convert`

### Value

Result of `mris_convert`

### Examples

```
if (have_fs()) {  
  bert_dir = file.path(fs_subj_dir(), "bert")  
  asc_file = mris_convert_normals(  
    infile = file.path(bert_dir, "surf", "lh.white")  
  )  
  readLines(asc_file, n = 6)  
}
```

---

mris\_convert\_vertex *Convert Surface to vertex file*

---

### Description

This function call `mris_convert`, using the `-v` option

### Usage

```
mris_convert_vertex(opts = "", ...)
```

### Arguments

`opts` (character) additional options to `mris_convert`  
`...` additional arguments to `mris_convert`

**Value**

Result of `mris_convert`

**Examples**

```
if (have_fs()) {  
  bert_surf_dir = file.path(fs_subj_dir(), "bert", "surf")  
  asc_file = mris_convert_vertex(  
    infile = file.path(bert_surf_dir, "lh.white")  
  )  
  readLines(asc_file, n = 6)  
}
```

---

mris_euler_number	<i>MRI Euler Number</i>
-------------------	-------------------------

---

**Description**

This function calls `mris_euler_number` to calculate the Euler Number

**Usage**

```
mris_euler_number(file, outfile = NULL, opts = "")
```

**Arguments**

file	(character) input filename
outfile	(character) output filename
opts	(character) additional options to <code>mris_euler_number</code>

**Value**

Result of system command

**Examples**

```
## Not run:  
if (have_fs()) {  
  img = oro.nifti::nifti(array(rnorm(5*5*5), dim = c(5,5,5)))  
  res = mris_euler_number(img, outfile = tempfile(fileext = ".mgz"))  
}  
  
## End(Not run)
```

---

`mris_euler_number.help`*MRI Euler Number Help*

---

**Description**

This calls Freesurfer's `mris_euler_number help`

**Usage**

```
mris_euler_number.help()
```

**Value**

Result of `fs_help`

---

`mri_convert`*Use Freesurfer's MRI Converter*

---

**Description**

This function calls `mri_convert` to convert an image

**Usage**

```
mri_convert(file, outfile, opts = "")
```

**Arguments**

<code>file</code>	(character) input filename
<code>outfile</code>	(character) output filename
<code>opts</code>	(character) additional options to <code>mri_convert</code>

**Value**

Result of system command

**Examples**

```
if (have_fs()) {  
  img = oro.nifti::nifti(array(rnorm(5*5*5), dim = c(5,5,5)))  
  res = mri_convert(img, outfile = tempfile(fileext = ".mgz"))  
}
```



---

mri_convert.help	<i>MRI Normalize Help</i>
------------------	---------------------------

---

**Description**

This calls Freesurfer's `mri_convert help`

**Usage**

```
mri_convert.help()
```

**Value**

Result of `fs_help`

---

mri_info	<i>MRI information</i>
----------	------------------------

---

**Description**

This calls Freesurfer's `mri_info`

**Usage**

```
mri_info(file, ...)
```

**Arguments**

file	File to pass to <code>mri_info</code>
...	Additional arguments to pass to <a href="#">fs_cmd</a>

**Value**

Result of `fs_cmd`, which type depends on arguments to ...

**Examples**

```
if (have_fs()){  
  img = oro.nifti::nifti(array(rnorm(5*5*5), dim = c(5,5,5)))  
  mri_info(img)  
}
```

---

mri_info.help	<i>MRI information Help</i>
---------------	-----------------------------

---

**Description**

This calls Freesurfer's `mri_info help`

**Usage**

```
mri_info.help()
```

**Value**

Result of `fs_help`

---

mri_mask	<i>Use Freesurfer's MRI Mask</i>
----------	----------------------------------

---

**Description**

This function calls `mri_mask` to mask an image

**Usage**

```
mri_mask(file, mask, outfile = NULL, retimg = TRUE, opts = "", ...)
```

**Arguments**

<code>file</code>	(character) input filename
<code>mask</code>	(character) mask filename
<code>outfile</code>	(character) output filename
<code>retimg</code>	(logical) return image of class nifti
<code>opts</code>	(character) additional options to <code>mri_mask</code>
<code>...</code>	additional arguments passed to <code>fs_cmd</code> .

**Value**

Character or nifti depending on `retimg`

**Examples**

```
if (have_fs()) {
  img = oro.nifti::nifti(array(rnorm(5*5*5), dim = c(5,5,5)))
  mask = img > 1
  res = mri_mask(img, mask)
}
```

---

mri_mask.help	<i>MRI Normalize Help</i>
---------------	---------------------------

---

**Description**

This calls Freesurfer's mri\_mask help

**Usage**

```
mri_mask.help()
```

**Value**

Result of fs\_help

---

mri_normalize	<i>Use Freesurfer's MRI Normalize Algorithm</i>
---------------	-------------------------------------------------

---

**Description**

This function calls mri\_normalize to normalize the values of the image, with white matter voxels around 110.

**Usage**

```
mri_normalize(file, outfile = NULL, retimg = TRUE, opts = "", ...)
```

**Arguments**

file	(character) input filename
outfile	(character) output filename
retimg	(logical) return image of class nifti
opts	(character) additional options to mri_normalize
...	additional arguments passed to <a href="#">fs_cmd</a> .

**Value**

Character or nifti depending on retimg

**Examples**

```
## Not run:
if (have_fs()){
  mri_normalize("/path/to/T1.nii.gz")
}

## End(Not run)
```

---

mri\_normalize.help      *MRI Normalize Help*

---

**Description**

This calls Freesurfer's mri\_normalize help

**Usage**

mri\_normalize.help()

**Value**

Result of fs\_help

---

mri\_segment              *Use Freesurfers MRI Segmentation Algorithm*

---

**Description**

This function calls mri\_segment to segment tissues from an image

**Usage**

mri\_segment(file, outfile = NULL, retimg = TRUE, opts = "", ...)

**Arguments**

file	(character) input filename
outfile	(character) output filename
retimg	(logical) return image of class nifti
opts	(character) additional options to mri_segment
...	additional arguments passed to <a href="#">fs_cmd</a> .

**Value**

Character or nifti depending on retimg

**Note**

NOT COMPLETE

**Examples**

```
## Not run:
if (have_fs()){
  mri_segment("/path/to/T1.nii.gz")
}

## End(Not run)
```

---

mri_segment.help	<i>MRI Segment Help</i>
------------------	-------------------------

---

**Description**

This calls Freesurfer's `mri_segment help`

**Usage**

```
mri_segment.help()
```

**Value**

Result of `fs_help`

---

mri_surf2surf	<i>Use Freesurfer's mri_surf2surf function to resamples one cortical surface onto another</i>
---------------	-----------------------------------------------------------------------------------------------

---

**Description**

This function calls Freesurfer `mri_surf2surf` to resample one cortical surface onto another

**Usage**

```
mri_surf2surf(subject = NULL, target_subject = NULL, trg_type = c("curv",
  "w", "mgh", "nii"), src_type = c("curv", "w"), outfile = NULL,
  hemi = c("lh", "rh"), sval = c("thickness"), subj_dir = NULL,
  opts = "", verbose = TRUE)
```

**Arguments**

subject	(character) vector of subject name
target_subject	(character) vector of target subject name
trg_type	(character) target file type, can be curv, paint (w), mgh, or nii
src_type	(character) source file type, can be curv or paint (w)
outfile	(character) output filename
hemi	(character) hemisphere to run statistics
sval	(character) source file
subj_dir	(character path) if a different subjects directory is to be used other than SUBJECTS_DIR from shell, it can be specified here. Use with care as if the command fail, it may not reset the SUBJECTS_DIR back correctly after the error
opts	(character) additional options to mri_surf2surf
verbose	(logical) print diagnostic messages

**Value**

Name of output file

**Examples**

```
if (have_fs()) {
  out = mri_surf2surf(
    subject = 'bert',
    target_subject = 'fsaverage',
    trg_type = 'curv',
    src_type = 'curv',
    hemi = "rh",
    sval = "thickness")
}
```

---

mri\_surf2surf.help      *Freesurfer's mri\_surf2surf Help*

---

**Description**

This calls Freesurfer's mri\_surf2surf help

**Usage**

```
mri_surf2surf.help()
```

**Value**

Result of fs\_help

---

mri_watershed	<i>Use Freesurfer's MRI Watershed Algorithm</i>
---------------	-------------------------------------------------

---

**Description**

This function calls `mri_watershed` to extract a brain from an image, usually for skull stripping.

**Usage**

```
mri_watershed(file, outfile = NULL, retimg = TRUE, opts = "", ...)
```

**Arguments**

<code>file</code>	(character) input filename
<code>outfile</code>	(character) output filename
<code>retimg</code>	(logical) return image of class nifti
<code>opts</code>	(character) additional options to <code>mri_watershed</code>
<code>...</code>	additional arguments passed to <code>fs_cmd</code> .

**Value**

Character or nifti depending on `retimg`

**Examples**

```
## Not run:
if (have_fs()){
  mri_watershed("/path/to/T1.nii.gz")
}

## End(Not run)
```

---

<code>mri_watershed.help</code>	<i>MRI Watershed Help</i>
---------------------------------	---------------------------

---

**Description**

This calls Freesurfer's `mri_watershed help`

**Usage**

```
mri_watershed.help()
```

**Value**

Result of `fs_help`

nii2mnc

*Convert NIfTI to MNC*

---

**Description**

This function calls nii2mnc to convert NIfTI to MNC files

**Usage**

```
nii2mnc(file, outfile = NULL)
```

**Arguments**

file            (character) input filename  
outfile        (character) output filename

**Value**

Character filename of output

**Examples**

```
if (have_fs()) {  
  img = oro.nifti::nifti(array(rnorm(5*5*5), dim = c(5,5,5)))  
  mnc = nii2mnc(img)  
  img_file = mnc2nii(mnc)  
}
```

---

nii2mnc.help*Convert NIfTI to MNC Help*

---

**Description**

This calls Freesurfer's mnc2nii help

**Usage**

```
nii2mnc.help()
```

**Value**

Result of fs\_help



---

nu_correct	<i>Use Freesurfer's Non-Uniformity Correction</i>
------------	---------------------------------------------------

---

**Description**

This function calls nu\_correct to correct for non-uniformity

**Usage**

```
nu_correct(file, mask = NULL, opts = "", verbose = TRUE, ...)
```

**Arguments**

file	(character) input filename
mask	(character or nifti) Mask to use for correction.
opts	(character) additional options to mri_segment
verbose	print diagnostic messages
...	additional arguments passed to <a href="#">fs_cmd</a> .

**Value**

Object of class nifti depending on retimg

**Examples**

```
## Not run:
if (have_fs()){
  nu_correct("/path/to/T1.nii.gz")
}

## End(Not run)
```

---

nu_correct.help	<i>Non-Uniformity Correction Help</i>
-----------------	---------------------------------------

---

**Description**

This calls Freesurfer's nu\_correct help

**Usage**

```
nu_correct.help()
```

**Value**

Result of fs\_help

---

readmgz	<i>Read MGH or MGZ File</i>
---------	-----------------------------

---

**Description**

This function calls `mri_convert` to convert MGH/MGZ files to NIfTI, then reads it in using [readnii](#)

**Usage**

```
readmgz(file)
```

```
readmgh(file)
```

**Arguments**

`file` (character) input filename

**Value**

Object of class `nifti`

---

readmnc	<i>Read MNC File</i>
---------	----------------------

---

**Description**

This function calls `mnc2nii` to convert MNC files to NIfTI, then reads it in using [readnii](#)

**Usage**

```
readmnc(file)
```

**Arguments**

`file` (character) input filename

**Value**

Object of class `nifti`

---

read_aseg_stats	<i>Read Anatomical Segmentation Statistics</i>
-----------------	------------------------------------------------

---

**Description**

Reads an aseg.stats file from an individual subject

**Usage**

```
read_aseg_stats(file)
```

**Arguments**

file                    aseg.stats file from Freesurfer

**Value**

List of 2 data.frames, one with the global measures and one with the structure-specific measures.

**Examples**

```
if (have_fs()) {  
  file = file.path(fs_subj_dir(), "bert", "stats", "aseg.stats")  
  out = read_aseg_stats(file)  
}
```

---

read_fs_label	<i>Read Label File</i>
---------------	------------------------

---

**Description**

Reads an label file from an individual subject

**Usage**

```
read_fs_label(file)
```

**Arguments**

file                    label file from Freesurfer

**Value**

data.frame with 5 columns:

vertex\_num: Vertex Number

r\_coord: Coordinate in RL direction

a\_coord: Coordinate in AP direction

s\_coord: Coordinate in SI direction

value: Value of label (depends on file)

**Examples**

```
if (have_fs()) {
  file = file.path(fs_subj_dir(), "bert", "label", "lh.BA1.label")
  out = read_fs_label(file)
}
```

---

read\_fs\_table

*Read Freesurfer Table Output*

---

**Description**

This function reads output from a Freesurfer table command, e.g. `aparstats2table`, `asegstats2table`

**Usage**

```
read_fs_table(file, sep = NULL, stringsAsFactors = FALSE, header = TRUE,
  ...)
```

**Arguments**

`file` (character path) filename of text file

`sep` separator to override attribute of file, to pass to [read.table](#).

`stringsAsFactors` (logical) passed to [read.table](#)

`header` Is there a header in the data

`...` additional arguments to [read.table](#)

**Value**

data.frame from the file

**Examples**

```

if (have_fs()) {
  outfile = aparstats2table(subjects = "bert",
                           hemi = "lh",
                           meas = "thickness")
  df = read_fs_table(outfile)
  seg_outfile = asegstats2table(subjects = "bert", meas = "mean")
  df_seg = read_fs_table(seg_outfile)
}
## Not run:
### using the pipe
df_seg = asegstats2table(subjects = "bert", meas = "mean") %>%
  read_fs_table

## End(Not run)

```

recon

*Reconstruction from Freesurfer***Description**

Reconstruction from Freesurfer with most of the options implemented.

**Usage**

```

recon(infile, outdir = NULL, subjid, motioncor = TRUE,
       nuintensitycor = TRUE, talairach = TRUE, normalization = TRUE,
       skullstrip = TRUE, gcareg = TRUE, canorm = TRUE, careg = TRUE,
       rmneck = TRUE, skull_lta = TRUE, calabel = TRUE,
       normalization2 = TRUE, segmentation = TRUE, fill = TRUE,
       tessellate = TRUE, smooth1 = TRUE, inflate1 = TRUE, qsphere = TRUE,
       fix = TRUE, finalsurfs = TRUE, smooth2 = TRUE, inflate2 = TRUE,
       cortribbon = TRUE, sphere = TRUE, surfreg = TRUE,
       contrasurfreg = TRUE, avgcurv = TRUE, cortparc = TRUE,
       parcstats = TRUE, cortparc2 = TRUE, parcstats2 = TRUE,
       aparc2aseg = TRUE, verbose = TRUE, opts = "")

```

**Arguments**

<code>infile</code>	Input filename (dcm or nii)
<code>outdir</code>	Output directory
<code>subjid</code>	subject id
<code>motioncor</code>	When there are multiple source volumes, this step will correct for small motions between them and then average them together. The input are the volumes found in file(s) <code>mri/orig/XXX.mgz</code> . The output will be the volume <code>mri/orig.mgz</code> . If no runs are found, then it looks for a volume in <code>mri/orig</code> (or <code>mri/orig.mgz</code> ). If that volume is there, then it is used in subsequent processes as if it was the motion corrected volume. If no volume is found, then the process exits with errors.

nuintensitycor	Non-parametric Non-uniform intensity Normalization (N3), corrects for intensity non-uniformity in MR data, making relatively few assumptions about the data. This runs the MINC tool 'nu_correct'. By default, four iterations of nu_correct are run. The flag '-nuitations' specification of some other number of iterations.
talairach	computes the affine transform from the orig volume to the MNI305 atlas using the MINC program mritotal. Creates the files mri/transform/talairach.auto.xfm and talairach.xfm.
normalization	Performs intensity normalization of the orig volume and places the result in mri/T1.mgz
skullstrip	Removes the skull from mri/T1.mgz and stores the result in mri/brainmask.auto.mgz and mri/brainmask.mgz. Runs the mri_watershed program.
gcareg	Computes transform to align the mri/nu.mgz volume to the default GCA atlas found in FREESURFER_HOME/average. Creates the file mri/transforms/talairach.lta.
canorm	Further normalization, based on GCA model. Creates mri/norm.mgz.
careg	Computes a nonlinear transform to align with GCA atlas. Creates the file mri/transform/talairach.m3z.
rmneck	The neck region is removed from the NU-corrected volume mri/nu.mgz. Makes use of transform computed from prior CA Register stage. Creates the file mri/nu_noneck.mgz.
skull_lta	Computes transform to align volume mri/nu_noneck.mgz with GCA volume possessing the skull. Creates the file mri/transforms/talairach_with_skull.lta.
calabel	Labels subcortical structures, based in GCA model. Creates the files mri/aseg.auto.mgz and mri/aseg.mgz.
normalization2	Performs a second (major) intensity correction using only the brain volume as the input (so that it has to be done after the skull strip). Intensity normalization works better when the skull has been removed. Creates a new brain.mgz volume. If -noaseg flag is used, then aseg.mgz is not used by mri_normalize.
segmentation	Attempts to separate white matter from everything else. The input is mri/brain.mgz, and the output is mri/wm.mgz. Uses intensity, neighborhood, and smoothness constraints. This is the volume that is edited when manually fixing defects. Calls mri_segment, mri_edit_wm_with_aseg, and mri_preteess. To keep previous edits, run with -keepwmedits. If -noaseg is used, then mri_edit_wm_aseg is skipped.
fill	This creates the subcortical mass from which the orig surface is created. The mid brain is cut from the cerebrum, and the hemispheres are cut from each other. The left hemisphere is binarized to 255. The right hemisphere is binarized to 127. The input is mri/wm.mgz and the output is mri/filled.mgz. Calls mri_fill. If the cut fails, then seed points can be supplied (see -cc-crs, -pons-crs, -lh-crs, -rh-crs). The actual points used for the cutting planes in the corpus callosum and pons can be found in scripts/ponscut.cut.log. This is the last stage of volumetric processing. If -noaseg is used, then aseg.mgz is not used by mri_fill.
tessellate	This is the step where the orig surface (ie, surf/?h.orig.nofix) is created. The surface is created by covering the filled hemisphere with triangles. Runs mri_tessellate. The places where the points of the triangles meet are called vertices. Creates the file surf/?h.orig.nofix Note: the topology fixer will create the surface ?h.orig.

smooth1	Calls mris_smooth. Smooth1 is the step just after tessellation
inflate1	Inflation of the surf/?h.smoothwm(.nofix) surface to create surf/?h.inflated.
qsphere	automatic topology fixing. It is a quasi-homeomorphic spherical transformation of the inflated surface designed to localize topological defects for the subsequent automatic topology fixer.
fix	Finds topological defects (ie, holes in a filled hemisphere) using surf/?h.qsphere.nofix, and changes the orig surface (surf/?h.orig.nofix) to remove the defects. Changes the number of vertices. All the defects will be removed, but the user should check the orig surface in the volume to make sure that it looks appropriate. Calls mris_fix_topology.
finalsurfs	Creates the ?h.white and ?h.pial surfaces as well as the thickness file (?h.thickness) and curvature file (?h.curv). The white surface is created by "nudging" the orig surface so that it closely follows the white-gray intensity gradient as found in the T1 volume. The pial surface is created by expanding the white surface so that it closely follows the gray-CSF intensity gradient as found in the T1 volume. Calls mris_make_surfaces.
smooth2	the step just after topology fixing.
inflate2	inflate2 is the step just after topology fixing
cortribbon	Creates binary volume masks of the cortical ribbon, ie, each voxel is either a 1 or 0 depending upon whether it falls in the ribbon or not. Saved as ?h.ribbon.mgz. Uses mgz regardless of whether the -mgz option is used.
sphere	Inflates the orig surface into a sphere while minimizing metric distortion. This step is necessary in order to register the surface to the spherical atlas. (also known as the spherical morph). Calls mris_sphere. Creates surf/?h.sphere.
surfreg	Registers the orig surface to the spherical atlas through surf/?h.sphere. The surfaces are first coarsely registered by aligning the large scale folding patterns found in ?h.sulc and then fine tuned using the small-scale patterns as in ?h.curv. Calls mris_register. Creates surf/?h.sphere.reg.
contrasurfreg	Same as ipsilateral but registers to the contralateral atlas. Creates lh.rh.sphere.reg and rh.lh.sphere.reg.
avgcurv	Resamples the average curvature from the atlas to that of the subject. Allows the user to display activity on the surface of an individual with the folding pattern (ie, anatomy) of a group. Calls mrisp_paint. Creates surf/?h.avg_curv.
cortparc	Assigns a neuroanatomical label to each location on the cortical surface. Incorporates both geometric information derived from the cortical model (sulcus and curvature), and neuroanatomical convention. Calls mris_ca_label. -cortparc creates label/?h.aparc.annot, and -cortparc2 creates /label/?h.aparc.a2005s.annot.
parcstats	Runs mris_anatomical_stats to create a summary table of cortical parcellation statistics for each structure, including 1. structure name 2. number of vertices 3. total surface area (mm <sup>2</sup> ) 4. total gray matter volume (mm <sup>3</sup> ) 5. average cortical thickness (mm) 6. standard error of cortical thickness (mm) 7. integrated rectified mean curvature 8. integrated rectified Gaussian curvature 9. folding index 10. intrinsic curvature index. For -parcstats, the file is saved in stats/?h.aparc.stats. For -parcstats2, the file is saved in stats/?h.aparc.a2005s.stats.

cortparc2	see cortparc argument
parcstats2	see cortparc2 argument
aparc2aseg	Maps the cortical labels from the automatic cortical parcellation (aparc) to the automatic segmentation volume (aseg). The result can be used as the aseg would.
verbose	print diagnostic messages
opts	Additional options

**Value**

Result of `system`

---

reconner	<i>Reconstruction Helper for recon from Freesurfer</i>
----------	--------------------------------------------------------

---

**Description**

Wrapper for the recon-all function in Freesurfer

**Usage**

```
reconner(infile = NULL, outdir = NULL, subjid = NULL, verbose = TRUE,
         opts = "-all", force = FALSE)
```

**Arguments**

infile	Input filename (dcm or nii)
outdir	Output directory
subjid	subject id
verbose	print diagnostic messages
opts	Additional options
force	Force running of the reconstruction

**Value**

Result of `system`

**Note**

If you set `infile = NULL`, then you can omit the `-i` flag in `recon-all`



---

`recon_all`*Reconstruction from Freesurfer for All Steps*

---

**Description**

Reconstruction from Freesurfer for All Steps

**Usage**

```
recon_all(infile = NULL, outdir = NULL, subjid = NULL, verbose = TRUE,  
          opts = "-all", ...)
```

**Arguments**

<code>infile</code>	Input filename (dcm or nii)
<code>outdir</code>	Output directory
<code>subjid</code>	subject id
<code>verbose</code>	print diagnostic messages
<code>opts</code>	Additional options
<code>...</code>	arguments passed to <a href="#">reconner</a>

**Value**

Result of [system](#)

**Note**

If you would like to restart a recon-all run, change opts so that opts = "-make all"

---

`recon_con1`*Reconstruction from Motion Correction to Skull Strip*

---

**Description**

Reconstruction from Freesurfer for Step 1-5 (Motion Correction to Skull Strip), which calls `-autorecon1` in recon-all

**Usage**

```

recon_con1(infile, outdir = NULL, subjid, verbose = TRUE)

autorecon1(infile, outdir = NULL, subjid, verbose = TRUE)

recon_con2(infile, outdir = NULL, subjid, verbose = TRUE)

autorecon2(infile, outdir = NULL, subjid, verbose = TRUE)

recon_con3(infile, outdir = NULL, subjid, verbose = TRUE)

autorecon3(infile, outdir = NULL, subjid, verbose = TRUE)

```

**Arguments**

infile	Input filename (dcm or nii)
outdir	Output directory
subjid	subject id
verbose	print diagnostic messages

**Value**

Result of `system`

**Note**

See <https://surfer.nmr.mgh.harvard.edu/fswiki/recon-all> for the steps of each autorecon1-3. If you set `infile = NULL`, then you can omit the `-i` flag in recon-all.

---

run\_check\_fs\_cmd      *Run and Check a Freesurfer Command*

---

**Description**

Checks whether an output filename exists before a command has run, prints and runs the command, and then checks the output from the result.

**Usage**

```
run_check_fs_cmd(cmd, outfile, verbose = TRUE)
```

**Arguments**

cmd	Command to be run
outfile	Output file to be produced
verbose	print diagnostic messages

**Value**

Invisible NULL

**See Also**

[check\\_fs\\_result](#)

---

set_fs_subj_dir	<i>Set Freesurfer Subjects Directory</i>
-----------------	------------------------------------------

---

**Description**

Sets the SUBJECTS\_DIR variable in the system environment or options("fs.subj\_dir" = x)

**Usage**

```
set_fs_subj_dir(x = file.path(fs_dir(), "subjects"))
```

**Arguments**

x	path to SUBJECTS_DIR defaults to file.path(fs_dir(), "subjects")
---	------------------------------------------------------------------

---

surface_to_obj	<i>Convert Freesurfer Surface to Wavefront OBJ</i>
----------------	----------------------------------------------------

---

**Description**

Reads in a surface file from Freesurfer and converts it to a Wavefront OBJ file

**Usage**

```
surface_to_obj(infile, outfile = NULL, ...)
```

**Arguments**

infile	Input surface file
outfile	output Wavefront OBJ file. If NULL, a temporary file will be created
...	additional arguments to pass to <a href="#">convert_surface</a>

**Value**

Character filename of output file

**Examples**

```

if (have_fs()) {
infile = file.path(fs_subj_dir(),
                  "bert", "surf", "rh.pial")
res = surface_to_obj(infile = infile)
}

```

---

surface\_to\_triangles *Convert Freesurfer Surface to Triangles*

---

**Description**

Reads in a surface file from Freesurfer and converts it into triangles

**Usage**

```
surface_to_triangles(infile, ...)
```

**Arguments**

infile	Input surface file
...	additional arguments to pass to <a href="#">convert_surface</a>

**Value**

Matrix of triangles with the number of rows equal to the number of faces (not the triplets - total faces)

**Examples**

```

if (have_fs()) {
infile = file.path(fs_subj_dir(),
                  "bert", "surf", "rh.pial")
right_triangles = surface_to_triangles(infile = infile)
infile = file.path(fs_subj_dir(),
                  "bert", "surf", "lh.pial")
left_triangles = surface_to_triangles(infile = infile)
if (requireNamespace("rgl", quietly = TRUE)) {
  rgl::rgl.open()
  rgl::rgl.triangles(right_triangles,
                    color = rainbow(nrow(right_triangles)))
  rgl::rgl.triangles(left_triangles,
                    color = rainbow(nrow(left_triangles)))
}
infile = file.path(fs_subj_dir(),
                  "bert", "surf", "rh.inflated")
right_triangles = surface_to_triangles(infile = infile)
infile = file.path(fs_subj_dir(),
                  "bert", "surf", "lh.inflated")

```

```
left_triangles = surface_to_triangles(infile = infile)
if (requireNamespace("rgl", quietly = TRUE)) {
  rgl::rgl.open()
  rgl::rgl.triangles(left_triangles,
    color = rainbow(nrow(left_triangles)))
  rgl::rgl.triangles(right_triangles,
    color = rainbow(nrow(right_triangles)))
}
}
```

---

surf\_convert

*Convert Surface Data to ASCII*

---

## Description

This function calls `mri_convert` to convert a measure from surfaces to an ASCII file and reads it in.

## Usage

```
surf_convert(file, outfile = NULL)
```

## Arguments

`file` (character) input filename of curvature measure  
`outfile` (character) output filename (if wanted to be saved)

## Value

data.frame

## Examples

```
if (have_fs()) {
  fname = file.path(fs_subj_dir(), "bert", "surf", "lh.thickness")
  out = surf_convert(fname)
}
```

---

tracker	<i>Tract Reconstruction Helper for trac-all from Freesurfer</i>
---------	-----------------------------------------------------------------

---

**Description**

Wrapper for the trac-all function in Freesurfer

**Usage**

```
tracker(infile, outdir = NULL, subjid, verbose = TRUE, opts = "")
```

**Arguments**

infile	Input filename (dcm or nii)
outdir	Output directory
subjid	subject id, if NULL, the basename of the infile will be used
verbose	print diagnostic messages
opts	Additional options

**Value**

Result of [system](#)

---

trac_all	<i>Tract Reconstruction Helper for trac-all from Freesurfer for All Steps</i>
----------	-------------------------------------------------------------------------------

---

**Description**

Wrapper for the trac-all function in Freesurfer for All Steps

**Usage**

```
trac_all(infile, outdir = NULL, subjid, verbose = TRUE, opts = "")
```

**Arguments**

infile	Input filename (dcm or nii)
outdir	Output directory
subjid	subject id
verbose	print diagnostic messages
opts	Additional options

**Value**

Result of [system](#)

---

`trac_prep`*Tract Reconstruction for Each Step*

---

**Description**

Reconstruction from Freesurfer for Preprocessing, Bedpost, and Path reconstruction

**Usage**

```
trac_prep(infile, outdir = NULL, subjid, verbose = TRUE)
```

```
trac_bedpost(infile, outdir = NULL, subjid, verbose = TRUE)
```

```
trac_path(infile, outdir = NULL, subjid, verbose = TRUE)
```

**Arguments**

<code>infile</code>	Input filename (dcm or nii)
<code>outdir</code>	Output directory
<code>subjid</code>	subject id
<code>verbose</code>	print diagnostic messages

**Value**

Result of `system`

# Index

## \*Topic **datasets**

- fs\_lut, 15
  
- aparcs\_to\_bg, 5
- aparcsstats2table, 3, 5
- aparcsstats2table.help, 4
- asegstats2table, 5
- asegstats2table.help, 6
- autorecon1 (recon\_con1), 41
- autorecon2 (recon\_con1), 41
- autorecon3 (recon\_con1), 41
  
- check\_fs\_result, 7, 43
- checking, 7
- checkmnc (checkmnc-methods), 7
- checkmnc, character-method  
    (checkmnc-methods), 7
- checkmnc, list-method  
    (checkmnc-methods), 7
- checkmnc, nifti-method  
    (checkmnc-methods), 7
- checkmnc-methods, 7
- construct\_subj\_dir, 8
- convert\_surface, 9, 43, 44
  
- ensure\_mnc (checkmnc-methods), 7
  
- freesurfer\_dir (freesurferdir), 10
- freesurfer\_read3, 10
- freesurfer\_read3\_con, 11
- freesurfer\_read\_curv, 12
- freesurfer\_read\_surf, 12
- freesurferdir, 10
- fs\_cmd, 13, 25–28, 31, 33
- fs\_dir (freesurferdir), 10
- fs\_help, 14
- fs\_imgext, 14
- fs\_lut, 15
- fs\_subj\_dir, 15
- fs\_version, 16
  
- get\_fs, 13, 14, 16, 17
- get\_fs\_output, 17
  
- have\_fs, 17
  
- mnc2nii, 18
- mnc2nii.help, 19
- mri\_convert, 24
- mri\_convert.help, 25
- mri\_info, 25
- mri\_info.help, 26
- mri\_mask, 26
- mri\_mask.help, 27
- mri\_normalize, 27
- mri\_normalize.help, 28
- mri\_segment, 28
- mri\_segment.help, 29
- mri\_surf2surf, 29
- mri\_surf2surf.help, 30
- mri\_watershed, 31
- mri\_watershed.help, 31
- mrisc\_convert, 9, 19, 20–23
- mrisc\_convert.help, 20
- mrisc\_convert\_annot, 20
- mrisc\_convert\_curv, 21
- mrisc\_convert\_normals, 22
- mrisc\_convert\_vertex, 22
- mrisc\_euler\_number, 23
- mrisc\_euler\_number.help, 24
  
- nii2mnc, 32
- nii2mnc.help, 32
- nu\_correct, 33
- nu\_correct.help, 33
  
- read.table, 36
- read\_aseg\_stats, 35
- read\_fs\_label, 35
- read\_fs\_table, 36
- readmgh (readmgz), 34



readmgz, 34  
readmnc, 34  
readnii, 13, 34  
recon, 37  
recon\_all, 41  
recon\_con1, 41  
recon\_con1, recon\_con2, recon\_con3  
    (recon\_con1), 41  
recon\_con2 (recon\_con1), 41  
recon\_con3 (recon\_con1), 41  
reconner, 40, 41  
run\_check\_fs\_cmd, 42  
  
set\_fs\_subj\_dir, 43  
surf\_convert, 45  
surface\_to\_obj, 43  
surface\_to\_triangles, 44  
system, 13, 40–42, 46, 47  
  
trac\_all, 46  
trac\_bedpost (trac\_prep), 47  
trac\_path (trac\_prep), 47  
trac\_prep, 47  
tracker, 46