

Package ‘ggnewscale’

October 6, 2019

Title Multiple Fill and Color Scales in 'ggplot2'

Version 0.4.0

Description Use multiple fill and color scales in 'ggplot2'.

License GPL-3

Encoding UTF-8

LazyData true

Imports ggplot2 (>= 3.0.0), stringi

RoxygenNote 6.1.1

NeedsCompilation no

Author Elio Campitelli [cre, aut] (<<https://orcid.org/0000-0002-7742-9230>>)

Maintainer Elio Campitelli <elio.campitelli@cima.fcen.uba.ar>

Repository CRAN

Date/Publication 2019-10-06 04:40:02 UTC

R topics documented:

new_scale 1

Index 3

new_scale *Adds a new scale to a plot*

Description

Creates a new scale "slot". Geoms added to a plot after this function will use a new scale definition.

Usage

```
new_scale(new_aes)

new_scale_fill()

new_scale_color()

new_scale_colour()
```

Arguments

`new_aes` A string with the name of the aesthetic for which a new scale will be created.

Details

`new_scale_color()`, `new_scale_colour()` and `new_scale_fill()` are just aliases to `new_scale("color")`, etc...

Examples

```
library(ggplot2)

# Equivalent to melt(volcano), but we don't want to depend on reshape2
topography <- expand.grid(x = 1:nrow(volcano),
                        y = 1:ncol(volcano))
topography$z <- c(volcano)

# point measurements of something at a few locations
measurements <- data.frame(x = runif(30, 1, 80),
                          y = runif(30, 1, 60),
                          thing = rnorm(30))

ggplot(mapping = aes(x, y)) +
  geom_contour(data = topography, aes(z = z, color = stat(level))) +
  # Color scale for topography
  scale_color_viridis_c(option = "D") +
  # geoms below will use another color scale
  new_scale_color() +
  geom_point(data = measurements, size = 3, aes(color = thing)) +
  # Color scale applied to geoms added after new_scale_color()
  scale_color_viridis_c(option = "A")
```

Index

`new_scale`, 1
`new_scale_color` (`new_scale`), 1
`new_scale_colour` (`new_scale`), 1
`new_scale_fill` (`new_scale`), 1