

# Package ‘ggrepel’

February 3, 2023

**Version** 0.9.3

**Title** Automatically Position Non-Overlapping Text Labels with  
'ggplot2'

**Description** Provides text and label geoms for 'ggplot2' that help to avoid overlapping text labels. Labels repel away from each other and away from the data points.

**Depends** R (>= 3.0.0), ggplot2 (>= 2.2.0)

**Imports** grid, Rcpp, rlang (>= 0.3.0), scales (>= 0.5.0), withr (>= 2.5.0)

**Suggests** knitr, rmarkdown, testthat, svglite, vdiff, gridExtra, devtools, prettydoc, ggbeeswarm, dplyr, magrittr, readr, stringr

**VignetteBuilder** knitr

**License** GPL-3 | file LICENSE

**URL** <https://github.com/slowkow/ggrepel>

**BugReports** <https://github.com/slowkow/ggrepel/issues>

**RoxygenNote** 7.1.2

**LinkingTo** Rcpp

**Encoding** UTF-8

**NeedsCompilation** yes

**Author** Kamil Slowikowski [aut, cre] (<<https://orcid.org/0000-0002-2843-6370>>),  
Alicia Schep [ctb] (<<https://orcid.org/0000-0002-3915-0618>>),  
Sean Hughes [ctb] (<<https://orcid.org/0000-0002-9409-9405>>),  
Trung Kien Dang [ctb] (<<https://orcid.org/0000-0001-7562-6495>>),  
Saulius Lukauskas [ctb],  
Jean-Olivier Irisson [ctb] (<<https://orcid.org/0000-0003-4920-3880>>),  
Zhian N Kamvar [ctb] (<<https://orcid.org/0000-0003-1458-7108>>),  
Thompson Ryan [ctb] (<<https://orcid.org/0000-0002-0450-8181>>),  
Dervieux Christophe [ctb] (<<https://orcid.org/0000-0003-4474-2498>>),  
Yutani Hiroaki [ctb],  
Pierre Gramme [ctb],

Amir Masoud Abdol [ctb],  
 Malcolm Barrett [ctb] (<<https://orcid.org/0000-0003-0299-5825>>),  
 Robrecht Cannoodt [ctb] (<<https://orcid.org/0000-0003-3641-729X>>),  
 Michał Krassowski [ctb] (<<https://orcid.org/0000-0002-9638-7785>>),  
 Michael Chirico [ctb] (<<https://orcid.org/0000-0003-0787-087X>>),  
 Pedro Aphalo [ctb] (<<https://orcid.org/0000-0003-3385-972X>>)

**Maintainer** Kamil Slowikowski <[kslowikowski@gmail.com](mailto:kslowikowski@gmail.com)>

**Repository** CRAN

**Date/Publication** 2023-02-03 09:00:02 UTC

## R topics documented:

geom_label_repel . . . . .	2
position_nudge_repel . . . . .	6

**Index** 9

---

geom_label_repel	<i>Repulsive textual annotations.</i>
------------------	---------------------------------------

---

## Description

geom\_text\_repel adds text directly to the plot. geom\_label\_repel draws a rectangle underneath the text, making it easier to read. The text labels repel away from each other and away from the data points.

## Usage

```
geom_label_repel(
  mapping = NULL,
  data = NULL,
  stat = "identity",
  position = "identity",
  parse = FALSE,
  ...,
  box.padding = 0.25,
  label.padding = 0.25,
  point.padding = 1e-06,
  label.r = 0.15,
  label.size = 0.25,
  min.segment.length = 0.5,
  arrow = NULL,
  force = 1,
  force_pull = 1,
  max.time = 0.5,
  max.iter = 10000,
```

```

    max.overlaps = getOption("ggrepel.max.overlaps", default = 10),
    nudge_x = 0,
    nudge_y = 0,
    xlim = c(NA, NA),
    ylim = c(NA, NA),
    na.rm = FALSE,
    show.legend = NA,
    direction = c("both", "y", "x"),
    seed = NA,
    verbose = FALSE,
    inherit.aes = TRUE
  )

geom_text_repel(
  mapping = NULL,
  data = NULL,
  stat = "identity",
  position = "identity",
  parse = FALSE,
  ...,
  box.padding = 0.25,
  point.padding = 1e-06,
  min.segment.length = 0.5,
  arrow = NULL,
  force = 1,
  force_pull = 1,
  max.time = 0.5,
  max.iter = 10000,
  max.overlaps = getOption("ggrepel.max.overlaps", default = 10),
  nudge_x = 0,
  nudge_y = 0,
  xlim = c(NA, NA),
  ylim = c(NA, NA),
  na.rm = FALSE,
  show.legend = NA,
  direction = c("both", "y", "x"),
  seed = NA,
  verbose = FALSE,
  inherit.aes = TRUE
)

```

### Arguments

mapping	Set of aesthetic mappings created by <code>aes</code> or <code>aes_</code> . If specified and <code>inherit.aes</code> = <code>TRUE</code> (the default), is combined with the default mapping at the top level of the plot. You only need to supply mapping if there isn't a mapping defined for the plot.
data	A data frame. If specified, overrides the default data frame defined at the top

	level of the plot.
<code>stat</code>	The statistical transformation to use on the data for this layer, as a string.
<code>position</code>	Position adjustment, either as a string, or the result of a call to a position adjustment function.
<code>parse</code>	If TRUE, the labels will be parsed into expressions and displayed as described in <code>?plotmath</code>
<code>...</code>	other arguments passed on to <code>layer</code> . There are three types of arguments you can use here: <ul style="list-style-type: none"> <li>• Aesthetics: to set an aesthetic to a fixed value, like <code>colour = "red"</code> or <code>size = 3</code>.</li> <li>• Other arguments to the layer, for example you override the default <code>stat</code> associated with the layer.</li> <li>• Other arguments passed on to the <code>stat</code>.</li> </ul>
<code>box.padding</code>	Amount of padding around bounding box, as unit or number. Defaults to 0.25. (Default unit is lines, but other units can be specified by passing <code>unit(x, "units")</code> ).
<code>label.padding</code>	Amount of padding around label, as unit or number. Defaults to 0.25. (Default unit is lines, but other units can be specified by passing <code>unit(x, "units")</code> ).
<code>point.padding</code>	Amount of padding around labeled point, as unit or number. Defaults to 0. (Default unit is lines, but other units can be specified by passing <code>unit(x, "units")</code> ).
<code>label.r</code>	Radius of rounded corners, as unit or number. Defaults to 0.15. (Default unit is lines, but other units can be specified by passing <code>unit(x, "units")</code> ).
<code>label.size</code>	Size of label border, in mm.
<code>min.segment.length</code>	Skip drawing segments shorter than this, as unit or number. Defaults to 0.5. (Default unit is lines, but other units can be specified by passing <code>unit(x, "units")</code> ).
<code>arrow</code>	specification for arrow heads, as created by <code>arrow</code>
<code>force</code>	Force of repulsion between overlapping text labels. Defaults to 1.
<code>force_pull</code>	Force of attraction between a text label and its corresponding data point. Defaults to 1.
<code>max.time</code>	Maximum number of seconds to try to resolve overlaps. Defaults to 0.5.
<code>max.iter</code>	Maximum number of iterations to try to resolve overlaps. Defaults to 10000.
<code>max.overlaps</code>	Exclude text labels that overlap too many things. Defaults to 10.
<code>nudge_x, nudge_y</code>	Horizontal and vertical adjustments to nudge the starting position of each text label. The units for <code>nudge_x</code> and <code>nudge_y</code> are the same as for the data units on the x-axis and y-axis.
<code>xlim, ylim</code>	Limits for the x and y axes. Text labels will be constrained to these limits. By default, text labels are constrained to the entire plot area.
<code>na.rm</code>	If FALSE (the default), removes missing values with a warning. If TRUE silently removes missing values.
<code>show.legend</code>	logical. Should this layer be included in the legends? NA, the default, includes if any aesthetics are mapped. FALSE never includes, and TRUE always includes.

direction	"both", "x", or "y" – direction in which to adjust position of labels
seed	Random seed passed to <code>set.seed</code> . Defaults to NA, which means that <code>set.seed</code> will not be called.
verbose	If TRUE, some diagnostics of the repel algorithm are printed
inherit.aes	If FALSE, overrides the default aesthetics, rather than combining with them. This is most useful for helper functions that define both data and aesthetics and shouldn't inherit behaviour from the default plot specification, e.g. <code>borders</code> .

## Details

These geoms are based on `geom_text` and `geom_label`. See the documentation for those functions for more details. Differences from those functions are noted here.

Text labels have height and width, but they are physical units, not data units. The amount of space they occupy on that plot is not constant in data units: when you resize a plot, labels stay the same size, but the size of the axes changes. The text labels are repositioned after resizing a plot.

## geom\_label\_repel

Currently `geom_label_repel` does not support the `rot` argument and is considerably slower than `geom_text_repel`. The `fill` aesthetic controls the background colour of the label.

## Alignment with `hjust` or `vjust`

The arguments `hjust` and `vjust` are supported, but they only control the initial positioning, so repulsive forces may disrupt alignment. Alignment with `hjust` will be preserved if labels only move up and down by using `direction="y"`. For `vjust`, use `direction="x"`.

## Examples

```
p <- ggplot(mtcars,
  aes(wt, mpg, label = rownames(mtcars), colour = factor(cyl))) +
  geom_point()

# Avoid overlaps by repelling text labels
p + geom_text_repel()
# Labels with background
p + geom_label_repel()

## Not run:
p + geom_text_repel(family = "Times New Roman",
  box.padding = 0.5)

# Add aesthetic mappings
p + geom_text_repel(aes(alpha=wt, size=mpg))
p + geom_label_repel(aes(fill=factor(cyl)), colour="white", segment.colour="black")

# Draw all line segments
p + geom_text_repel(min.segment.length = 0)
```

```

# Omit short line segments (default behavior)
p + geom_text_repel(min.segment.length = 0.5)

# Omit all line segments
p + geom_text_repel(segment.colour = NA)

# Repel just the labels and totally ignore the data points
p + geom_text_repel(point.size = NA)

# Hide some of the labels, but repel from all data points
mtcars$label <- rownames(mtcars)
mtcars$label[1:15] <- ""
p + geom_text_repel(data = mtcars, aes(wt, mpg, label = label))

# Nudge the starting positions
p + geom_text_repel(nudge_x = ifelse(mtcars$cyl == 6, 1, 0),
                    nudge_y = ifelse(mtcars$cyl == 6, 8, 0))

# Change the text size
p + geom_text_repel(aes(size = wt))
# Scale height of text, rather than sqrt(height)
p + geom_text_repel(aes(size = wt)) + scale_radius(range = c(3,6))

# You can display expressions by setting parse = TRUE. The
# details of the display are described in ?plotmath, but note that
# geom_text_repel uses strings, not expressions.
p + geom_text_repel(aes(label = paste(wt, "^(", cyl, ")", sep = "")),
  parse = TRUE)

# Add a text annotation
p +
  geom_text_repel() +
  annotate(
    "text", label = "plot mpg vs. wt",
    x = 2, y = 15, size = 8, colour = "red"
  )

# Add arrows
p +
  geom_point(colour = "red") +
  geom_text_repel(
    arrow = arrow(length = unit(0.02, "npc")),
    box.padding = 1
  )

## End(Not run)

```

**Description**

`position_nudge_repel` is useful for adjusting the starting position of text labels before they are repelled from data points.

**Usage**

```
position_nudge_repel(x = 0, y = 0)
```

**Arguments**

`x, y` Amount of horizontal and vertical distance to move. Same units as the data on the x and y axes.

**Examples**

```
df <- data.frame(
  x = c(1,3,2,5),
  y = c("a","c","d","c")
)

ggplot(df, aes(x, y)) +
  geom_point() +
  geom_text_repel(aes(label = y))

ggplot(df, aes(x, y)) +
  geom_point() +
  geom_text_repel(
    aes(label = y),
    min.segment.length = 0,
    position = position_nudge_repel(x = 0.1, y = 0.15)
  )

# The values for x and y can be vectors
ggplot(df, aes(x, y)) +
  geom_point() +
  geom_text_repel(
    aes(label = y),
    min.segment.length = 0,
    position = position_nudge_repel(
      x = c(0.1, 0, -0.1, 0),
      y = c(0.1, 0.2, -0.1, -0.2)
    )
  )

# We can also use geom_text_repel() with arguments nudge_x, nudge_y
ggplot(df, aes(x, y)) +
  geom_point() +
  geom_text_repel(
    aes(label = y),
    min.segment.length = 0,
    nudge_x = 0.1,
```

```
    nudge_y = 0.15
  )

# The arguments nudge_x, nudge_y also accept vectors
ggplot(df, aes(x, y)) +
  geom_point() +
  geom_text_repel(
    aes(label = y),
    min.segment.length = 0,
    nudge_x = c(0.1, 0, -0.1, 0),
    nudge_y = c(0.1, 0.2, -0.1, -0.2)
  )
```



# Index

## \* position adjustments

position\_nudge\_repel, 6

aes, 3

aes\_, 3

arrow, 4

borders, 5

geom\_label, 5

geom\_label\_repel, 2

geom\_text, 5

geom\_text\_repel (geom\_label\_repel), 2

layer, 4

position\_nudge\_repel, 6

set.seed, 5