

Package ‘gpboost’

November 29, 2023

Type Package

Title Combining Tree-Boosting with Gaussian Process and Mixed Effects Models

Version 1.2.7

Date 2023-11-29

Description An R package that allows for combining tree-boosting with Gaussian process and mixed effects models. It also allows for independently doing tree-boosting as well as inference and prediction for Gaussian process and mixed effects models. See <<https://github.com/fabsig/GPBoost>> for more information on the software and Sigrist (2022, JMLR) <<https://www.jmlr.org/papers/v23/20-322.html>> and Sigrist (2023, TPAMI) <[doi:10.1109/TPAMI.2022.3168152](https://doi.org/10.1109/TPAMI.2022.3168152)> for more information on the methodology.

Encoding UTF-8

License Apache License (== 2.0) | file LICENSE

URL <https://github.com/fabsig/GPBoost>

BugReports <https://github.com/fabsig/GPBoost/issues>

NeedsCompilation yes

Biarch true

Suggests testthat

Depends R (>= 3.5), R6 (>= 2.0)

Imports data.table (>= 1.9.6), graphics, RJSONIO, Matrix (>= 1.1-0), methods, utils

SystemRequirements C++17

RoxygenNote 6.0.1

Author Fabio Sigrist [aut, cre],
Pascal Kuendig [aut],
Benoit Jacob [cph],
Gael Guennebaud [cph],
Nicolas Carre [cph],
Pierre Zoppitelli [cph],

Gauthier Brun [cph],
 Jean Ceccato [cph],
 Jitse Niesen [cph],
 Other authors of Eigen for the included version of Eigen [ctb, cph],
 Timothy A. Davis [cph],
 Guolin Ke [ctb],
 Damien Soukhavong [ctb],
 James Lamb [ctb],
 Other authors of LightGBM for the included version of LightGBM [ctb],
 Microsoft Corporation [cph],
 Dropbox, Inc. [cph],
 Jay Loden [cph],
 Dave Daeschler [cph],
 Giampaolo Rodola [cph],
 Alberto Ferreira [ctb],
 Daniel Lemire [ctb],
 Victor Zverovich [cph],
 IBM Corporation [ctb],
 Keith O'Hara [cph],
 Stephen L. Moshier [cph]

Maintainer Fabio Sigrist <fabiosigrist@gmail.com>

Repository CRAN

Date/Publication 2023-11-29 16:20:02 UTC

R topics documented:

agaricus.test	4
agaricus.train	4
bank	5
coords	5
coords_test	6
dim.gpb.Dataset	6
dimnames.gpb.Dataset	7
fit	8
fit.GPModel	10
fitGPModel	13
getinfo	19
get_nested_categories	20
gpb.convert_with_rules	21
gpb.cv	23
gpb.Dataset	26
gpb.Dataset.construct	28
gpb.Dataset.create.valid	28
gpb.Dataset.save	29
gpb.Dataset.set.categorical	30
gpb.Dataset.set.reference	30
gpb.dump	31

gpb.get.eval.result	32
gpb.grid.search.tune.parameters	33
gpb.importance	37
gpb.interprete	38
gpb.load	39
gpb.model.dt.tree	40
gpb.plot.importance	41
gpb.plot.interpretation	42
gpb.plot.part.dep.interact	44
gpb.plot.partial.dependence	45
gpb.save	47
gpb.train	48
gpboost	53
GPBoost_data	57
GPMModel	58
GPMModel_shared_params	61
group_data	67
group_data_test	67
loadGPMModel	67
neg_log_likelihood	68
neg_log_likelihood.GPMModel	69
predict.gpb.Booster	70
predict.GPMModel	73
predict_training_data_random_effects	76
predict_training_data_random_effects.GPMModel	77
readRDS.gpb.Booster	78
saveGPMModel	79
saveRDS.gpb.Booster	80
setinfo	81
set_optim_params	82
set_optim_params.GPMModel	84
set_prediction_data	87
set_prediction_data.GPMModel	89
slice	91
summary.GPMModel	92
X	93
X_test	93
y	93

agaricus.test

Test part from Mushroom Data Set

Description

This data set is originally from the Mushroom data set, UCI Machine Learning Repository. This data set includes the following fields:

- label: the label for each record
- data: a sparse Matrix of dgCMatrx class, with 126 columns.

Usage

```
data(agaricus.test)
```

Format

A list containing a label vector, and a dgCMatrx object with 1611 rows and 126 variables

References

<https://archive.ics.uci.edu/ml/datasets/Mushroom>

Bache, K. & Lichman, M. (2013). UCI Machine Learning Repository [<http://archive.ics.uci.edu/ml>]. Irvine, CA: University of California, School of Information and Computer Science.

agaricus.train*Training part from Mushroom Data Set*

Description

This data set is originally from the Mushroom data set, UCI Machine Learning Repository. This data set includes the following fields:

- label: the label for each record
- data: a sparse Matrix of dgCMatrx class, with 126 columns.

Usage

```
data(agaricus.train)
```

Format

A list containing a label vector, and a dgCMatrx object with 6513 rows and 127 variables

References

<https://archive.ics.uci.edu/ml/datasets/Mushroom>

Bache, K. & Lichman, M. (2013). UCI Machine Learning Repository [<http://archive.ics.uci.edu/ml>]. Irvine, CA: University of California, School of Information and Computer Science.

bank

Bank Marketing Data Set

Description

This data set is originally from the Bank Marketing data set, UCI Machine Learning Repository.

It contains only the following: bank.csv with 10 randomly selected from 3 (older version of this dataset with less inputs).

Usage

```
data(bank)
```

Format

A data.table with 4521 rows and 17 variables

References

<http://archive.ics.uci.edu/ml/datasets/Bank+Marketing>

S. Moro, P. Cortez and P. Rita. (2014) A Data-Driven Approach to Predict the Success of Bank Telemarketing. Decision Support Systems

coords

Example data for the GPBoost package

Description

A matrix with spatial coordinates for the example data of the GPBoost package

Usage

```
data(GPBoost_data)
```

coords_test	<i>Example data for the GPBoost package</i>
-------------	---

Description

A matrix with spatial coordinates for predictions for the example data of the GPBoost package

Usage

```
data(GPBoost_data)
```

dim.gpb.Dataset	<i>Dimensions of an gpb.Dataset</i>
-----------------	-------------------------------------

Description

Returns a vector of numbers of rows and of columns in an gpb.Dataset.

Usage

```
## S3 method for class 'gpb.Dataset'
dim(x, ...)
```

Arguments

x	Object of class gpb.Dataset
...	other parameters

Details

Note: since nrow and ncol internally use dim, they can also be directly used with an gpb.Dataset object.

Value

a vector of numbers of rows and of columns

Examples

```
data(agaricus.train, package = "gpboost")
train <- agaricus.train
dtrain <- gpb.Dataset(train$data, label = train$label)

stopifnot(nrow(dtrain) == nrow(train$data))
stopifnot(ncol(dtrain) == ncol(train$data))
stopifnot(all(dim(dtrain) == dim(train$data)))
```

dimnames.gpb.Dataset *Handling of column names of gpb.Dataset*

Description

Only column names are supported for `gpb.Dataset`, thus setting of row names would have no effect and returned row names would be `NULL`.

Usage

```
## S3 method for class 'gpb.Dataset'
dimnames(x)

## S3 replacement method for class 'gpb.Dataset'
dimnames(x) <- value
```

Arguments

<code>x</code>	object of class <code>gpb.Dataset</code>
<code>value</code>	a list of two elements: the first one is ignored and the second one is column names

Details

Generic `dimnames` methods are used by `colnames`. Since row names are irrelevant, it is recommended to use `colnames` directly.

Value

A list with the dimension names of the dataset

A list with the dimension names of the dataset

Examples

```
data(agaricus.train, package = "gpboost")
train <- agaricus.train
dtrain <- gpb.Dataset(train$data, label = train$label)
gpb.Dataset.construct(dtrain)
dimnames(dtrain)
colnames(dtrain)
colnames(dtrain) <- make.names(seq_len(ncol(train$data)))
print(dtrain, verbose = TRUE)
```

fit	<i>Generic 'fit' method for a GPMoDel</i>
-----	---

Description

Generic 'fit' method for a GPMoDel

Usage

```
fit(gp_model, y, X, params, fixed_effects = NULL)
```

Arguments

- | | |
|----------|---|
| gp_model | a GPMoDel |
| y | A vector with response variable data |
| X | A matrix with numeric covariate data for the fixed effects linear regression term (if there is one) |
| params | <p>A list with parameters for the estimation / optimization</p> <ul style="list-style-type: none"> • optimizer_cov: string (default = "gradient_descent"). Optimizer used for estimating covariance parameters. Options: "gradient_descent", "fisher_scoring", "nelder_mead", "bfgs", "adam". If there are additional auxiliary parameters for non-Gaussian likelihoods, 'optimizer_cov' is also used for those • optimizer_coef: string (default = "wls" for Gaussian likelihoods and "gradient_descent" for other likelihoods). Optimizer used for estimating linear regression coefficients, if there are any (for the GPBoost algorithm there are usually none). Options: "gradient_descent", "wls", "nelder_mead", "bfgs", "adam". Gradient descent steps are done simultaneously with gradient descent steps for the covariance parameters. "wls" refers to doing coordinate descent for the regression coefficients using weighted least squares. If 'optimizer_cov' is set to "nelder_mead", "bfgs", or "adam", 'optimizer_coef' is automatically also set to the same value. • maxit: integer (default = 1000). Maximal number of iterations for optimization algorithm • delta_rel_conv: numeric (default = 1E-6 except for "nelder_mead" for which the default is 1E-8). Convergence tolerance. The algorithm stops if the relative change in either the (approximate) log-likelihood or the parameters is below this value. For "bfgs" and "adam", the L2 norm of the gradient is used instead of the relative change in the log-likelihood. If < 0, internal default values are used • convergence_criterion: string (default = "relative_change_in_log_likelihood"). The convergence criterion used for terminating the optimization algorithm. Options: "relative_change_in_log_likelihood" or "relative_change_in_parameters" • init_coef: vector with numeric elements (default = NULL). Initial values for the regression coefficients (if there are any, can be NULL) |

- `init_cov_pars`: vector with numeric elements (default = NULL). Initial values for covariance parameters of Gaussian process and random effects (can be NULL)
- `lr_coef`: numeric (default = 0.1). Learning rate for fixed effect regression coefficients if gradient descent is used
- `lr_cov`: numeric (default = 0.1 for "gradient_descent" and 1. for "fisher_scoring"). Initial learning rate for covariance parameters. If `lr_cov < 0`, internal default values are used. If there are additional auxiliary parameters for non-Gaussian likelihoods, 'lr_cov' is also used for those
- `use_nesterov_acc`: boolean (default = TRUE). If TRUE Nesterov acceleration is used. This is used only for gradient descent
- `acc_rate_coef`: numeric (default = 0.5). Acceleration rate for regression coefficients (if there are any) for Nesterov acceleration
- `acc_rate_cov`: numeric (default = 0.5). Acceleration rate for covariance parameters for Nesterov acceleration
- `momentum_offset`: integer (Default = 2). Number of iterations for which no momentum is applied in the beginning.
- `trace`: boolean (default = FALSE). If TRUE, information on the progress of the parameter optimization is printed
- `std_dev`: boolean (default = TRUE). If TRUE, approximate standard deviations are calculated for the covariance and linear regression parameters (= square root of diagonal of the inverse Fisher information for Gaussian likelihoods and square root of diagonal of a numerically approximated inverse Hessian for non-Gaussian likelihoods)
- `init_aux_pars`: vector with numeric elements (default = NULL). Initial values for additional parameters for non-Gaussian likelihoods (e.g., shape parameter of gamma likelihood)
- `estimate_aux_pars`: boolean (default = TRUE). If TRUE, additional parameters for non-Gaussian likelihoods are also estimated (e.g., shape parameter of gamma likelihood)
- `cg_max_num_it`: integer (default = 1000). Maximal number of iterations for conjugate gradient algorithms
- `cg_max_num_it_tridiag`: integer (default = 1000). Maximal number of iterations for conjugate gradient algorithm when being run as Lanczos algorithm for tridiagonalization
- `cg_delta_conv`: numeric (default = 1E-2). Tolerance level for L2 norm of residuals for checking convergence in conjugate gradient algorithm when being used for parameter estimation
- `num_rand_vec_trace`: integer (default = 50). Number of random vectors (e.g., Rademacher) for stochastic approximation of the trace of a matrix
- `reuse_rand_vec_trace`: boolean (default = TRUE). If true, random vectors (e.g., Rademacher) for stochastic approximation of the trace of a matrix are sampled only once at the beginning of Newton's method for finding the mode in the Laplace approximation and are then reused in later trace approximations. Otherwise they are sampled every time a trace is calculated
- `seed_rand_vec_trace`: integer (default = 1). Seed number to generate random vectors (e.g., Rademacher)

- `piv_chol_rank`: integer (default = 50). Rank of the pivoted Cholesky decomposition used as preconditioner in conjugate gradient algorithms
- `cg_preconditioner_type`: string (default = "Sigma_inv_plus_BtWB" for non-Gaussian likelihoods and a Vecchia-Laplace approximation). Type of preconditioner used for conjugate gradient algorithms. Options for non-Gaussian likelihoods and a Vecchia-Laplace approximation:
 - "piv_chol_on_Sigma": $(L_k * L_k^T + W^{-1})$ as preconditioner for inverting $(B^{-1} * D * B^{-T} + W^{-1})$, where L_k is a low-rank pivoted Cholesky approximation for Sigma and $B^{-1} * D * B^{-T} \approx$ Sigma
 - "Sigma_inv_plus_BtWB": $(B^T * (D^{-1} + W) * B)$ as preconditioner for inverting $(B^T * D^{-1} * B + W)$, where $B^T * D^{-1} * B \approx$ Sigma⁻¹

`fixed_effects` A vector of optional external fixed effects (length = number of data points)

Author(s)

Fabio Sigrist

fit.GPModel

Fits a GPModel

Description

Estimates the parameters of a GPModel using maximum likelihood estimation

Usage

```
## S3 method for class 'GPModel'
fit(gp_model, y, X = NULL, params = list(),
    fixed_effects = NULL)
```

Arguments

- | | |
|-----------------------|--|
| <code>gp_model</code> | a GPModel |
| <code>y</code> | A vector with response variable data |
| <code>X</code> | A matrix with numeric covariate data for the fixed effects linear regression term (if there is one) |
| <code>params</code> | A list with parameters for the estimation / optimization <ul style="list-style-type: none"> • <code>optimizer_cov</code>: string (default = "gradient_descent"). Optimizer used for estimating covariance parameters. Options: "gradient_descent", "fisher_scoring", "nelder_mead", "bfgs", "adam". If there are additional auxiliary parameters for non-Gaussian likelihoods, 'optimizer_cov' is also used for those |

- `optimizer_coef`: `string` (default = "wls" for Gaussian likelihoods and "gradient_descent" for other likelihoods). Optimizer used for estimating linear regression coefficients, if there are any (for the GPBoost algorithm there are usually none). Options: "gradient_descent", "wls", "nelder_mead", "bfgs", "adam". Gradient descent steps are done simultaneously with gradient descent steps for the covariance parameters. "wls" refers to doing coordinate descent for the regression coefficients using weighted least squares. If 'optimizer_cov' is set to "nelder_mead", "bfgs", or "adam", 'optimizer_coef' is automatically also set to the same value.
- `maxit`: `integer` (default = 1000). Maximal number of iterations for optimization algorithm
- `delta_rel_conv`: `numeric` (default = 1E-6 except for "nelder_mead" for which the default is 1E-8). Convergence tolerance. The algorithm stops if the relative change in either the (approximate) log-likelihood or the parameters is below this value. For "bfgs" and "adam", the L2 norm of the gradient is used instead of the relative change in the log-likelihood. If < 0, internal default values are used
- `convergence_criterion`: `string` (default = "relative_change_in_log_likelihood"). The convergence criterion used for terminating the optimization algorithm. Options: "relative_change_in_log_likelihood" or "relative_change_in_parameters"
- `init_coef`: `vector` with `numeric` elements (default = NULL). Initial values for the regression coefficients (if there are any, can be NULL)
- `init_cov_pars`: `vector` with `numeric` elements (default = NULL). Initial values for covariance parameters of Gaussian process and random effects (can be NULL)
- `lr_coef`: `numeric` (default = 0.1). Learning rate for fixed effect regression coefficients if gradient descent is used
- `lr_cov`: `numeric` (default = 0.1 for "gradient_descent" and 1. for "fisher_scoring"). Initial learning rate for covariance parameters. If `lr_cov` < 0, internal default values are used. If there are additional auxiliary parameters for non-Gaussian likelihoods, 'lr_cov' is also used for those
- `use_nesterov_acc`: `boolean` (default = TRUE). If TRUE Nesterov acceleration is used. This is used only for gradient descent
- `acc_rate_coef`: `numeric` (default = 0.5). Acceleration rate for regression coefficients (if there are any) for Nesterov acceleration
- `acc_rate_cov`: `numeric` (default = 0.5). Acceleration rate for covariance parameters for Nesterov acceleration
- `momentum_offset`: `integer` (Default = 2). Number of iterations for which no momentum is applied in the beginning.
- `trace`: `boolean` (default = FALSE). If TRUE, information on the progress of the parameter optimization is printed
- `std_dev`: `boolean` (default = TRUE). If TRUE, approximate standard deviations are calculated for the covariance and linear regression parameters (= square root of diagonal of the inverse Fisher information for Gaussian likelihoods and square root of diagonal of a numerically approximated inverse Hessian for non-Gaussian likelihoods)

- `init_aux_pars`: vector with numeric elements (default = NULL). Initial values for additional parameters for non-Gaussian likelihoods (e.g., shape parameter of gamma likelihood)
- `estimate_aux_pars`: boolean (default = TRUE). If TRUE, additional parameters for non-Gaussian likelihoods are also estimated (e.g., shape parameter of gamma likelihood)
- `cg_max_num_it`: integer (default = 1000). Maximal number of iterations for conjugate gradient algorithms
- `cg_max_num_it_tridiag`: integer (default = 1000). Maximal number of iterations for conjugate gradient algorithm when being run as Lanczos algorithm for tridiagonalization
- `cg_delta_conv`: numeric (default = 1E-2). Tolerance level for L2 norm of residuals for checking convergence in conjugate gradient algorithm when being used for parameter estimation
- `num_rand_vec_trace`: integer (default = 50). Number of random vectors (e.g., Rademacher) for stochastic approximation of the trace of a matrix
- `reuse_rand_vec_trace`: boolean (default = TRUE). If true, random vectors (e.g., Rademacher) for stochastic approximation of the trace of a matrix are sampled only once at the beginning of Newton's method for finding the mode in the Laplace approximation and are then reused in later trace approximations. Otherwise they are sampled every time a trace is calculated
- `seed_rand_vec_trace`: integer (default = 1). Seed number to generate random vectors (e.g., Rademacher)
- `piv_chol_rank`: integer (default = 50). Rank of the pivoted Cholesky decomposition used as preconditioner in conjugate gradient algorithms
- `cg_preconditioner_type`: string (default = "Sigma_inv_plus_BtWB" for non-Gaussian likelihoods and a Vecchia-Laplace approximation). Type of preconditioner used for conjugate gradient algorithms. Options for non-Gaussian likelihoods and a Vecchia-Laplace approximation:
 - "piv_chol_on_Sigma": $(L_k * L_k^T + W^{-1})$ as preconditioner for inverting $(B^{-1} * D * B^{-T} + W^{-1})$, where L_k is a low-rank pivoted Cholesky approximation for Sigma and $B^{-1} * D * B^{-T} \approx$ Sigma
 - "Sigma_inv_plus_BtWB": $(B^T * (D^{-1} + W) * B)$ as preconditioner for inverting $(B^T * D^{-1} * B + W)$, where $B^T * D^{-1} * B \approx$ Sigma⁻¹

`fixed_effects` A vector of optional external fixed effects (length = number of data points)

Value

A fitted GPModel

Author(s)

Fabio Sigrist

Examples

```
# See https://github.com/fabsig/GPBoost/tree/master/R-package for more examples

data(GPBoost_data, package = "gpboost")
# Add intercept column
X1 <- cbind(rep(1,dim(X)[1]),X)
X_test1 <- cbind(rep(1,dim(X_test)[1]),X_test)

#-----Grouped random effects model: single-level random effect-----
gp_model <- GPModel(group_data = group_data[,1], likelihood="gaussian")
fit(gp_model, y = y, X = X1, params = list(std_dev = TRUE))
summary(gp_model)
# Make predictions
pred <- predict(gp_model, group_data_pred = group_data_test[,1],
               X_pred = X_test1, predict_var = TRUE)
pred$mu # Predicted mean
pred$var # Predicted variances
# Also predict covariance matrix
pred <- predict(gp_model, group_data_pred = group_data_test[,1],
               X_pred = X_test1, predict_cov_mat = TRUE)
pred$mu # Predicted mean
pred$cov # Predicted covariance

#-----Gaussian process model-----
gp_model <- GPModel(gp_coords = coords, cov_function = "exponential",
                  likelihood="gaussian")
fit(gp_model, y = y, X = X1, params = list(std_dev = TRUE))
summary(gp_model)
# Make predictions
pred <- predict(gp_model, gp_coords_pred = coords_test,
               X_pred = X_test1, predict_cov_mat = TRUE)
pred$mu # Predicted (posterior) mean of GP
pred$cov # Predicted (posterior) covariance matrix of GP
```

fitGPModel

Fits a GPModel

Description

Estimates the parameters of a GPModel using maximum likelihood estimation

Usage

```
fitGPModel(likelihood = "gaussian", group_data = NULL,
           group_rand_coef_data = NULL, ind_effect_group_rand_coef = NULL,
           drop_intercept_group_rand_effect = NULL, gp_coords = NULL,
```

```
gp_rand_coef_data = NULL, cov_function = "exponential",
cov_fct_shape = 0.5, gp_approx = "none", cov_fct_taper_range = 1,
cov_fct_taper_shape = 0, num_neighbors = 20L,
vecchia_ordering = "random", num_ind_points = 500L,
matrix_inversion_method = "cholesky", seed = 0L, cluster_ids = NULL,
free_raw_data = FALSE, y, X = NULL, params = list(),
vecchia_approx = NULL, vecchia_pred_type = NULL,
num_neighbors_pred = NULL)
```

Arguments

likelihood	<p>A string specifying the likelihood function (distribution) of the response variable. Available options:</p> <ul style="list-style-type: none"> • "gaussian" • "bernoulli_probit": binary data with Bernoulli likelihood and a probit link function • "bernoulli_logit": binary data with Bernoulli likelihood and a logit link function • "gamma" • "poisson"
group_data	<p>A vector or matrix whose columns are categorical grouping variables. The elements being group levels defining grouped random effects. The elements of 'group_data' can be integer, double, or character. The number of columns corresponds to the number of grouped (intercept) random effects</p>
group_rand_coef_data	<p>A vector or matrix with numeric covariate data for grouped random coefficients</p>
ind_effect_group_rand_coef	<p>A vector with integer indices that indicate the corresponding categorical grouping variable (=columns) in 'group_data' for every covariate in 'group_rand_coef_data'. Counting starts at 1. The length of this index vector must equal the number of covariates in 'group_rand_coef_data'. For instance, c(1,1,2) means that the first two covariates (=first two columns) in 'group_rand_coef_data' have random coefficients corresponding to the first categorical grouping variable (=first column) in 'group_data', and the third covariate (=third column) in 'group_rand_coef_data' has a random coefficient corresponding to the second grouping variable (=second column) in 'group_data'</p>
drop_intercept_group_rand_effect	<p>A vector of type logical (boolean). Indicates whether intercept random effects are dropped (only for random coefficients). If drop_intercept_group_rand_effect[k] is TRUE, the intercept random effect number k is dropped / not included. Only random effects with random slopes can be dropped.</p>
gp_coords	<p>A matrix with numeric coordinates (= inputs / features) for defining Gaussian processes</p>
gp_rand_coef_data	<p>A vector or matrix with numeric covariate data for Gaussian process random coefficients</p>

cov_function	<p>A string specifying the covariance function for the Gaussian process. Available options: "exponential", "gaussian", "matern", "powered_exponential", "wendland"</p> <ul style="list-style-type: none"> • For "exponential", "gaussian", and "powered_exponential", we use parametrization of Diggle and Ribeiro (2007) • For "matern", we use the parametrization of Rasmussen and Williams (2006) • For "wendland", we use the parametrization of Bevilacqua et al. (2019, AOS)
cov_fct_shape	<p>A numeric specifying the shape parameter of the covariance function (=smoothness parameter for Matern covariance) This parameter is irrelevant for some covariance functions such as the exponential or Gaussian</p>
gp_approx	<p>A string specifying the large data approximation for Gaussian processes. Available options:</p> <ul style="list-style-type: none"> • "none": No approximation • "vecchia": A Vecchia approximation; see Sigrist (2022, JMLR for more details) • "tapering": The covariance function is multiplied by a compactly supported Wendland correlation function
cov_fct_taper_range	<p>A numeric specifying the range parameter of the Wendland covariance function and Wendland correlation taper function. We follow the notation of Bevilacqua et al. (2019, AOS)</p>
cov_fct_taper_shape	<p>A numeric specifying the shape (=smoothness) parameter of the Wendland covariance function and Wendland correlation taper function. We follow the notation of Bevilacqua et al. (2019, AOS)</p>
num_neighbors	<p>An integer specifying the number of neighbors for the Vecchia approximation. Note: for prediction, the number of neighbors can be set through the 'num_neighbors_pred' parameter in the 'set_prediction_data' function. By default, num_neighbors_pred = 2 * num_neighbors. Further, the type of Vecchia approximation used for making predictions is set through the 'vecchia_pred_type' parameter in the 'set_prediction_data' function</p>
vecchia_ordering	<p>A string specifying the ordering used in the Vecchia approximation. Available options:</p> <ul style="list-style-type: none"> • "none": the default ordering in the data is used • "random": a random ordering
num_ind_points	<p>An integer specifying the number of inducing points / knots for, e.g., a predictive process approximation</p>
matrix_inversion_method	<p>A string specifying the method used for inverting covariance matrices. Available options:</p> <ul style="list-style-type: none"> • "cholesky": Cholesky factorization • "iterative": iterative methods. Only supported for non-Gaussian likelihoods with a Vecchia-Laplace approximation. This a combination of conjugate gradient, Lanczos algorithm, and other methods

seed	An integer specifying the seed used for model creation (e.g., random ordering in Vecchia approximation)
cluster_ids	A vector with elements indicating independent realizations of random effects / Gaussian processes (same values = same process realization). The elements of 'cluster_ids' can be integer, double, or character.
free_raw_data	A boolean. If TRUE, the data (groups, coordinates, covariate data for random coefficients) is freed in R after initialization
y	A vector with response variable data
X	A matrix with numeric covariate data for the fixed effects linear regression term (if there is one)
params	<p>A list with parameters for the estimation / optimization</p> <ul style="list-style-type: none"> • optimizer_cov: string (default = "gradient_descent"). Optimizer used for estimating covariance parameters. Options: "gradient_descent", "fisher_scoring", "nelder_mead", "bfgs", "adam". If there are additional auxiliary parameters for non-Gaussian likelihoods, 'optimizer_cov' is also used for those • optimizer_coef: string (default = "wls" for Gaussian likelihoods and "gradient_descent" for other likelihoods). Optimizer used for estimating linear regression coefficients, if there are any (for the GPBoost algorithm there are usually none). Options: "gradient_descent", "wls", "nelder_mead", "bfgs", "adam". Gradient descent steps are done simultaneously with gradient descent steps for the covariance parameters. "wls" refers to doing coordinate descent for the regression coefficients using weighted least squares. If 'optimizer_cov' is set to "nelder_mead", "bfgs", or "adam", 'optimizer_coef' is automatically also set to the same value. • maxit: integer (default = 1000). Maximal number of iterations for optimization algorithm • delta_rel_conv: numeric (default = 1E-6 except for "nelder_mead" for which the default is 1E-8). Convergence tolerance. The algorithm stops if the relative change in either the (approximate) log-likelihood or the parameters is below this value. For "bfgs" and "adam", the L2 norm of the gradient is used instead of the relative change in the log-likelihood. If < 0, internal default values are used • convergence_criterion: string (default = "relative_change_in_log_likelihood"). The convergence criterion used for terminating the optimization algorithm. Options: "relative_change_in_log_likelihood" or "relative_change_in_parameters" • init_coef: vector with numeric elements (default = NULL). Initial values for the regression coefficients (if there are any, can be NULL) • init_cov_pars: vector with numeric elements (default = NULL). Initial values for covariance parameters of Gaussian process and random effects (can be NULL) • lr_coef: numeric (default = 0.1). Learning rate for fixed effect regression coefficients if gradient descent is used • lr_cov: numeric (default = 0.1 for "gradient_descent" and 1. for "fisher_scoring"). Initial learning rate for covariance parameters. If lr_cov < 0, internal default values are used. If there are additional auxiliary parameters for non-Gaussian likelihoods, 'lr_cov' is also used for those

- `use_nesterov_acc`: `boolean` (default = `TRUE`). If `TRUE` Nesterov acceleration is used. This is used only for gradient descent
- `acc_rate_coef`: `numeric` (default = 0.5). Acceleration rate for regression coefficients (if there are any) for Nesterov acceleration
- `acc_rate_cov`: `numeric` (default = 0.5). Acceleration rate for covariance parameters for Nesterov acceleration
- `momentum_offset`: `integer` (Default = 2). Number of iterations for which no momentum is applied in the beginning.
- `trace`: `boolean` (default = `FALSE`). If `TRUE`, information on the progress of the parameter optimization is printed
- `std_dev`: `boolean` (default = `TRUE`). If `TRUE`, approximate standard deviations are calculated for the covariance and linear regression parameters (= square root of diagonal of the inverse Fisher information for Gaussian likelihoods and square root of diagonal of a numerically approximated inverse Hessian for non-Gaussian likelihoods)
- `init_aux_pars`: `vector` with `numeric` elements (default = `NULL`). Initial values for additional parameters for non-Gaussian likelihoods (e.g., shape parameter of gamma likelihood)
- `estimate_aux_pars`: `boolean` (default = `TRUE`). If `TRUE`, additional parameters for non-Gaussian likelihoods are also estimated (e.g., shape parameter of gamma likelihood)
- `cg_max_num_it`: `integer` (default = 1000). Maximal number of iterations for conjugate gradient algorithms
- `cg_max_num_it_tridiag`: `integer` (default = 1000). Maximal number of iterations for conjugate gradient algorithm when being run as Lanczos algorithm for tridiagonalization
- `cg_delta_conv`: `numeric` (default = 1E-2). Tolerance level for L2 norm of residuals for checking convergence in conjugate gradient algorithm when being used for parameter estimation
- `num_rand_vec_trace`: `integer` (default = 50). Number of random vectors (e.g., Rademacher) for stochastic approximation of the trace of a matrix
- `reuse_rand_vec_trace`: `boolean` (default = `TRUE`). If true, random vectors (e.g., Rademacher) for stochastic approximation of the trace of a matrix are sampled only once at the beginning of Newton's method for finding the mode in the Laplace approximation and are then reused in later trace approximations. Otherwise they are sampled every time a trace is calculated
- `seed_rand_vec_trace`: `integer` (default = 1). Seed number to generate random vectors (e.g., Rademacher)
- `piv_chol_rank`: `integer` (default = 50). Rank of the pivoted Cholesky decomposition used as preconditioner in conjugate gradient algorithms
- `cg_preconditioner_type`: `string` (default = "Sigma_inv_plus_BtWB" for non-Gaussian likelihoods and a Vecchia-Laplace approximation). Type of preconditioner used for conjugate gradient algorithms. Options for non-Gaussian likelihoods and a Vecchia-Laplace approximation:
 - "piv_chol_on_Sigma": $(L_k * L_k^T + W^{-1})$ as preconditioner for inverting $(B^{-1} * D * B^{-T} + W^{-1})$, where L_k is a low-rank pivoted

Cholesky approximation for Σ and $B^{-1} * D * B^{-T}$ approx=
 Σ
 - "Sigma_inv_plus_BtWB": $(B^T * (D^{-1} + W) * B)$ as preconditioner
 for inverting $(B^T * D^{-1} * B + W)$, where $B^T * D^{-1} * B$ approx=
 Σ^{-1}

vecchia_approx Discontinued. Use the argument gp_approx instead
 vecchia_pred_type
 A string specifying the type of Vecchia approximation used for making pre-
 dictions. This is discontinued here. Use the function 'set_prediction_data' to
 specify this
 num_neighbors_pred
 an integer specifying the number of neighbors for making predictions. This is
 discontinued here. Use the function 'set_prediction_data' to specify this

Value

A fitted GPModel

Author(s)

Fabio Sigrist

Examples

```
# See https://github.com/fabsig/GPBoost/tree/master/R-package for more examples

data(GPBoost_data, package = "gpboost")
# Add intercept column
X1 <- cbind(rep(1,dim(X)[1]),X)
X_test1 <- cbind(rep(1,dim(X_test)[1]),X_test)

#-----Grouped random effects model: single-level random effect-----
gp_model <- fitGPModel(group_data = group_data[,1], y = y, X = X1,
                      likelihood="gaussian", params = list(std_dev = TRUE))
summary(gp_model)
# Make predictions
pred <- predict(gp_model, group_data_pred = group_data_test[,1],
               X_pred = X_test1, predict_var = TRUE)
pred$mu # Predicted mean
pred$var # Predicted variances
# Also predict covariance matrix
pred <- predict(gp_model, group_data_pred = group_data_test[,1],
               X_pred = X_test1, predict_cov_mat = TRUE)
pred$mu # Predicted mean
pred$cov # Predicted covariance

#-----Two crossed random effects and a random slope-----
gp_model <- fitGPModel(group_data = group_data, likelihood="gaussian",
                      group_rand_coef_data = X[,2],
                      ind_effect_group_rand_coef = 1,
```

```

y = y, X = X1, params = list(std_dev = TRUE))
summary(gp_model)

#-----Gaussian process model-----
gp_model <- fitGPModel(gp_coords = coords, cov_function = "exponential",
                      likelihood="gaussian", y = y, X = X1, params = list(std_dev = TRUE))
summary(gp_model)
# Make predictions
pred <- predict(gp_model, gp_coords_pred = coords_test,
               X_pred = X_test1, predict_cov_mat = TRUE)
pred$mu # Predicted (posterior) mean of GP
pred$cov # Predicted (posterior) covariance matrix of GP

#-----Gaussian process model with Vecchia approximation-----
gp_model <- fitGPModel(gp_coords = coords, cov_function = "exponential",
                      gp_approx = "vecchia", num_neighbors = 20,
                      likelihood="gaussian", y = y)
summary(gp_model)

#-----Gaussian process model with random coefficients-----
gp_model <- fitGPModel(gp_coords = coords, cov_function = "exponential",
                      gp_rand_coef_data = X[,2], y=y,
                      likelihood = "gaussian", params = list(std_dev = TRUE))
summary(gp_model)

#-----Combine Gaussian process with grouped random effects-----
gp_model <- fitGPModel(group_data = group_data,
                      gp_coords = coords, cov_function = "exponential",
                      likelihood = "gaussian", y = y, X = X1, params = list(std_dev = TRUE))
summary(gp_model)

```

getinfo

Get information of an gpb.Dataset object

Description

Get one attribute of a gpb.Dataset

Usage

```

getinfo(dataset, ...)

## S3 method for class 'gpb.Dataset'
getinfo(dataset, name, ...)

```

Arguments

dataset	Object of class <code>gpb.Dataset</code>
...	other parameters
name	the name of the information field to get (see details)

Details

The name field can be one of the following:

- `label`: label gboost learn from ;
- `weight`: to do a weight rescale ;
- `group`: used for learning-to-rank tasks. An integer vector describing how to group rows together as ordered results from the same set of candidate results to be ranked. For example, if you have a 100-document dataset with `group = c(10, 20, 40, 10, 10, 10)`, that means that you have 6 groups, where the first 10 records are in the first group, records 11-30 are in the second group, etc.
- `init_score`: initial score is the base prediction gboost will boost from.

Value

info data
info data

Examples

```
data(agaricus.train, package = "gboost")
train <- agaricus.train
dtrain <- gpb.Dataset(train$data, label = train$label)
gpb.Dataset.construct(dtrain)

labels <- gboost::getinfo(dtrain, "label")
gboost::setinfo(dtrain, "label", 1 - labels)

labels2 <- gboost::getinfo(dtrain, "label")
stopifnot(all(labels2 == 1 - labels))
```

`get_nested_categories` *Auxiliary function to create categorical variables for nested grouped random effects*

Description

Auxiliary function to create categorical variables for nested grouped random effects

Usage

```
get_nested_categories(outer_var, inner_var)
```

Arguments

`outer_var` A vector containing the outer categorical grouping variable within which the `inner_var` is nested in. Can be of type integer, double, or character.

`inner_var` A vector containing the inner nested categorical grouping variable

Value

A vector containing a categorical variable such that `inner_var` is nested in `outer_var`

Author(s)

Fabio Sigrist

Examples

```
# Fit a model with Time as categorical fixed effects variables and Diet and Chick
# as random effects, where Chick is nested in Diet using lme4
chick_nested_diet <- get_nested_categories(ChickWeight$Diet, ChickWeight$Chick)
fixed_effects_matrix <- model.matrix(weight ~ as.factor(Time), data = ChickWeight)
mod_gpb <- fitGPModel(X = fixed_effects_matrix,
                     group_data = cbind(diet=ChickWeight$Diet, chick_nested_diet),
                     y = ChickWeight$weight, params = list(std_dev = TRUE))
summary(mod_gpb)
# This does (almost) the same thing as the following code using lme4:
# mod_lme4 <- lmer(weight ~ as.factor(Time) + (1 | Diet/Chick), data = ChickWeight, REML = FALSE)
# summary(mod_lme4)
```

`gpb.convert_with_rules`

Data preparator for GPBoost datasets with rules (integer)

Description

Attempts to prepare a clean dataset to prepare to put in a `gpb.Dataset`. Factor, character, and logical columns are converted to integer. Missing values in factors and characters will be filled with 0L. Missing values in logicals will be filled with -1L.

This function returns and optionally takes in "rules" the describe exactly how to convert values in columns.

Columns that contain only NA values will be converted by this function but will not show up in the returned rules.

Usage

```
gpb.convert_with_rules(data, rules = NULL)
```

Arguments

<code>data</code>	A data.frame or data.table to prepare.
<code>rules</code>	A set of rules from the data preparator, if already used. This should be an R list, where names are column names in data and values are named character vectors whose names are column values and whose values are new values to replace them with.

Value

A list with the cleaned dataset (`data`) and the rules (`rules`). Note that the data must be converted to a matrix format (`as.matrix`) for input in `gpb.Dataset`.

Examples

```
data(iris)

str(iris)

new_iris <- gpb.convert_with_rules(data = iris)
str(new_iris$data)

data(iris) # Erase iris dataset
iris$Species[1L] <- "NEW FACTOR" # Introduce junk factor (NA)

# Use conversion using known rules
# Unknown factors become 0, excellent for sparse datasets
newer_iris <- gpb.convert_with_rules(data = iris, rules = new_iris$rules)

# Unknown factor is now zero, perfect for sparse datasets
newer_iris$data[1L, ] # Species became 0 as it is an unknown factor

newer_iris$data[1L, 5L] <- 1.0 # Put back real initial value

# Is the newly created dataset equal? YES!
all.equal(new_iris$data, newer_iris$data)

# Can we test our own rules?
data(iris) # Erase iris dataset

# We remapped values differently
personal_rules <- list(
  Species = c(
    "setosa" = 3L
    , "versicolor" = 2L
    , "virginica" = 1L
  )
)
```

```
)
newest_iris <- gpb.convert_with_rules(data = iris, rules = personal_rules)
str(newest_iris$data) # SUCCESS!
```

gpb.cv

CV function for number of boosting iterations

Description

Cross validation function for determining number of boosting iterations

Usage

```
gpb.cv(params = list(), data, nrounds = 100L, gp_model = NULL,
  use_gp_model_for_validation = TRUE, fit_GP_cov_pars_OOS = FALSE,
  train_gp_model_cov_pars = TRUE, folds = NULL, nfold = 4L,
  label = NULL, weight = NULL, obj = NULL, eval = NULL, verbose = 1L,
  record = TRUE, eval_freq = 1L, showsd = FALSE, stratified = TRUE,
  init_model = NULL, colnames = NULL, categorical_feature = NULL,
  early_stopping_rounds = NULL, callbacks = list(), reset_data = FALSE,
  delete_boosters_folds = FALSE, ...)
```

Arguments

- | | |
|--------|---|
| params | <p>list of "tuning" parameters. See the parameter documentation for more information. A few key parameters:</p> <ul style="list-style-type: none"> • <code>learning_rate</code>: The learning rate, also called shrinkage or damping parameter (default = 0.1). An important tuning parameter for boosting. Lower values usually lead to higher predictive accuracy but more boosting iterations are needed • <code>num_leaves</code>: Number of leaves in a tree. Tuning parameter for tree-boosting (default = 31) • <code>max_depth</code>: Maximal depth of a tree. Tuning parameter for tree-boosting (default = no limit) • <code>min_data_in_leaf</code>: Minimal number of samples per leaf. Tuning parameter for tree-boosting (default = 20) • <code>lambda_l2</code>: L2 regularization (default = 0) • <code>lambda_l1</code>: L1 regularization (default = 0) • <code>max_bin</code>: Maximal number of bins that feature values will be bucketed in (default = 255) • <code>train_gp_model_cov_pars</code>: If TRUE, the covariance parameters of the Gaussian process are estimated in every boosting iterations, otherwise the <code>gp_model</code> parameters are not estimated. In the latter case, you need to either estimate them beforehand or provide the values via the <code>'init_cov_pars'</code> parameter when creating the <code>gp_model</code> (default = TRUE). |
|--------|---|

- `use_gp_model_for_validation`: If TRUE, the Gaussian process is also used (in addition to the tree model) for calculating predictions on the validation data (default = TRUE)
- `leaves_newton_update`: Set this to TRUE to do a Newton update step for the tree leaves after the gradient step. Applies only to Gaussian process boosting (GPBoost algorithm)
- `num_threads`: Number of threads. For the best speed, set this to the number of real CPU cores(`parallel::detectCores(logical = FALSE)`), not the number of threads (most CPU using hyper-threading to generate 2 threads per CPU core).

<code>data</code>	a <code>gpb.Dataset</code> object, used for training. Some functions, such as <code>gpb.cv</code> , may allow you to pass other types of data like <code>matrix</code> and then separately supply label as a keyword argument.
<code>nrounds</code>	number of boosting iterations (= number of trees). This is the most important tuning parameter for boosting
<code>gp_model</code>	A <code>GPMoel</code> object that contains the random effects (Gaussian process and / or grouped random effects) model
<code>use_gp_model_for_validation</code>	Boolean. If TRUE, the <code>gp_model</code> (Gaussian process and/or random effects) is also used (in addition to the tree model) for calculating predictions on the validation data. If FALSE, the <code>gp_model</code> (random effects part) is ignored for making predictions and only the tree ensemble is used for making predictions for calculating the validation / test error.
<code>fit_GP_cov_pars_OOS</code>	Boolean (default = FALSE). If TRUE, the covariance parameters of the <code>gp_model</code> model are estimated using the out-of-sample (OOS) predictions on the validation data using the optimal number of iterations (after performing the CV). This corresponds to the GPBoostOOS algorithm.
<code>train_gp_model_cov_pars</code>	Boolean. If TRUE, the covariance parameters of the <code>gp_model</code> (Gaussian process and/or random effects) are estimated in every boosting iterations, otherwise the <code>gp_model</code> parameters are not estimated. In the latter case, you need to either estimate them beforehand or provide the values via the <code>init_cov_pars</code> parameter when creating the <code>gp_model</code>
<code>folds</code>	<code>list</code> provides a possibility to use a list of pre-defined CV folds (each element must be a vector of test fold's indices). When folds are supplied, the <code>nfold</code> and <code>stratified</code> parameters are ignored.
<code>nfold</code>	the original dataset is randomly partitioned into <code>nfold</code> equal size subsamples.
<code>label</code>	Vector of labels, used if data is not an <code>gpb.Dataset</code>
<code>weight</code>	vector of response values. If not NULL, will set to dataset
<code>obj</code>	(character) The distribution of the response variable (=label) conditional on fixed and random effects. This only needs to be set when doing independent boosting without random effects / Gaussian processes.
<code>eval</code>	evaluation function(s). This can be a character vector, function, or list with a mixture of strings and functions.

- **a. character vector:** If you provide a character vector to this argument, it should contain strings with valid evaluation metrics. See [the "metric" section of the parameter documentation](#) for a list of valid metrics.
- **b. function:** You can provide a custom evaluation function. This should accept the keyword arguments `preds` and `dtrain` and should return a named list with three elements:
 - `name`: A string with the name of the metric, used for printing and storing results.
 - `value`: A single number indicating the value of the metric for the given predictions and true values
 - `higher_better`: A boolean indicating whether higher values indicate a better fit. For example, this would be `FALSE` for metrics like MAE or RMSE.
- **c. list:** If a list is given, it should only contain character vectors and functions. These should follow the requirements from the descriptions above.

<code>verbose</code>	verbosity for output, if ≤ 0 , also will disable the print of evaluation during training
<code>record</code>	Boolean, <code>TRUE</code> will record iteration message to <code>booster\$record_evals</code>
<code>eval_freq</code>	evaluation output frequency, only effect when <code>verbose > 0</code>
<code>showsd</code>	boolean, whether to show standard deviation of cross validation. This parameter defaults to <code>TRUE</code> .
<code>stratified</code>	a boolean indicating whether sampling of folds should be stratified by the values of outcome labels.
<code>init_model</code>	path of model file of <code>gpb.Booster</code> object, will continue training from this model
<code>colnames</code>	feature names, if not null, will use this to overwrite the names in dataset
<code>categorical_feature</code>	categorical features. This can either be a character vector of feature names or an integer vector with the indices of the features (e.g. <code>c(1L, 10L)</code> to say "the first and tenth columns").
<code>early_stopping_rounds</code>	int. Activates early stopping. Requires at least one validation data and one metric. When this parameter is non-null, training will stop if the evaluation of any metric on any validation set fails to improve for <code>early_stopping_rounds</code> consecutive boosting rounds. If training stops early, the returned model will have attribute <code>best_iter</code> set to the iteration number of the best iteration.
<code>callbacks</code>	List of callback functions that are applied at each iteration.
<code>reset_data</code>	Boolean, setting it to <code>TRUE</code> (not the default value) will transform the booster model into a predictor model which frees up memory and the original datasets
<code>delete_boosters_folds</code>	Boolean, setting it to <code>TRUE</code> (not the default value) will delete the boosters of the individual folds
<code>...</code>	other parameters, see <code>Parameters.rst</code> for more information.

Value

a trained model `gpb.CVBooster`.

Early Stopping

"early stopping" refers to stopping the training process if the model's performance on a given validation set does not improve for several consecutive iterations.

If multiple arguments are given to `eval`, their order will be preserved. If you enable early stopping by setting `early_stopping_rounds` in `params`, by default all metrics will be considered for early stopping.

If you want to only consider the first metric for early stopping, pass `first_metric_only = TRUE` in `params`. Note that if you also specify `metric` in `params`, that metric will be considered the "first" one. If you omit `metric`, a default metric will be used based on your choice for the parameter `obj` (keyword argument) or `objective` (passed into `params`).

Author(s)

Authors of the LightGBM R package, Fabio Sigrist

Examples

See <https://github.com/fabsig/GPBoost/tree/master/R-package> for more examples

```
library(gpboost)
data(GPBoost_data, package = "gpboost")

# Create random effects model and dataset
gp_model <- GPModel(group_data = group_data[,1], likelihood="gaussian")
dtrain <- gpb.Dataset(X, label = y)
params <- list(learning_rate = 0.05,
              max_depth = 6,
              min_data_in_leaf = 5)

# Run CV
cvbst <- gpb.cv(params = params,
               data = dtrain,
               gp_model = gp_model,
               nrounds = 100,
               nfold = 4,
               eval = "l2",
               early_stopping_rounds = 5,
               use_gp_model_for_validation = TRUE)
print(paste0("Optimal number of iterations: ", cvbst$best_iter,
            ", best test error: ", cvbst$best_score))
```

gpb.Dataset

Construct gpb.Dataset object

Description

Construct `gpb.Dataset` object from dense matrix, sparse matrix or local file (that was created previously by saving an `gpb.Dataset`).

Usage

```
gpb.Dataset(data, params = list(), reference = NULL, colnames = NULL,
  categorical_feature = NULL, free_raw_data = FALSE, info = list(), ...)
```

Arguments

data	a matrix object, a dgCMatix object or a character representing a filename
params	a list of parameters. See the "Dataset Parameters" section of the parameter documentation for a list of parameters and valid values.
reference	reference dataset. When GPBoost creates a Dataset, it does some preprocessing like binning continuous features into histograms. If you want to apply the same bin boundaries from an existing dataset to new data, pass that existing Dataset to this argument.
colnames	names of columns
categorical_feature	categorical features. This can either be a character vector of feature names or an integer vector with the indices of the features (e.g. c(1L, 10L) to say "the first and tenth columns").
free_raw_data	GPBoost constructs its data format, called a "Dataset", from tabular data. By default, this Dataset object on the R side does keep a copy of the raw data. If you set free_raw_data = TRUE, no copy of the raw data is kept (this reduces memory usage)
info	a list of information of the gpb.Dataset object
...	other information to pass to info or parameters pass to params

Value

constructed dataset

Examples

```
data(agaricus.train, package = "gpboost")
train <- agaricus.train
dtrain <- gpb.Dataset(train$data, label = train$label)
data_file <- tempfile(fileext = ".data")
gpb.Dataset.save(dtrain, data_file)
dtrain <- gpb.Dataset(data_file)
gpb.Dataset.construct(dtrain)
```

`gpb.Dataset.construct` *Construct Dataset explicitly*

Description

Construct Dataset explicitly

Usage

```
gpb.Dataset.construct(dataset)
```

Arguments

dataset Object of class gpb.Dataset

Value

constructed dataset

Examples

```
data(agaricus.train, package = "gpboost")
train <- agaricus.train
dtrain <- gpb.Dataset(train$data, label = train$label)
gpb.Dataset.construct(dtrain)
```

`gpb.Dataset.create.valid`
Construct validation data

Description

Construct validation data according to training data

Usage

```
gpb.Dataset.create.valid(dataset, data, info = list(), ...)
```

Arguments

dataset gpb.Dataset object, training data
data a matrix object, a dgCMatix object or a character representing a filename
info a list of information of the gpb.Dataset object
... other information to pass to info.

Value

constructed dataset

Examples

```
data(agaricus.train, package = "gpboost")
train <- agaricus.train
dtrain <- gpb.Dataset(train$data, label = train$label)
data(agaricus.test, package = "gpboost")
test <- agaricus.test
dtest <- gpb.Dataset.create.valid(dtrain, test$data, label = test$label)
```

gpb.Dataset.save	<i>Save gpb.Dataset to a binary file</i>
------------------	--

Description

Please note that `init_score` is not saved in binary file. If you need it, please set it again after loading Dataset.

Usage

```
gpb.Dataset.save(dataset, fname)
```

Arguments

dataset	object of class <code>gpb.Dataset</code>
fname	object filename of output file

Value

the dataset you passed in

Examples

```
data(agaricus.train, package = "gpboost")
train <- agaricus.train
dtrain <- gpb.Dataset(train$data, label = train$label)
gpb.Dataset.save(dtrain, tempfile(fileext = ".bin"))
```

`gpb.Dataset.set.categorical`
Set categorical feature of gpb.Dataset

Description

Set the categorical features of an `gpb.Dataset` object. Use this function to tell GPBoost which features should be treated as categorical.

Usage

```
gpb.Dataset.set.categorical(dataset, categorical_feature)
```

Arguments

`dataset` object of class `gpb.Dataset`
`categorical_feature`
 categorical features. This can either be a character vector of feature names or an integer vector with the indices of the features (e.g. `c(1L, 10L)` to say "the first and tenth columns").

Value

the dataset you passed in

Examples

```
data(agaricus.train, package = "gpboost")  
train <- agaricus.train  
dtrain <- gpb.Dataset(train$data, label = train$label)  
data_file <- tempfile(fileext = ".data")  
gpb.Dataset.save(dtrain, data_file)  
dtrain <- gpb.Dataset(data_file)  
gpb.Dataset.set.categorical(dtrain, 1L:2L)
```

`gpb.Dataset.set.reference`
Set reference of gpb.Dataset

Description

If you want to use validation data, you should set reference to training data

Usage

```
gpb.Dataset.set.reference(dataset, reference)
```

Arguments

dataset	object of class gpb.Dataset
reference	object of class gpb.Dataset

Value

the dataset you passed in

Examples

```
data(agaricus.train, package = "gpboost")
train <- agaricus.train
dtrain <- gpb.Dataset(train$data, label = train$label)
data(agaricus.test, package = "gpboost")
test <- agaricus.test
dtest <- gpb.Dataset(test$data, test = train$label)
gpb.Dataset.set.reference(dtest, dtrain)
```

gpb.dump

Dump GPBoost model to json

Description

Dump GPBoost model to json

Usage

```
gpb.dump(booster, num_iteration = NULL)
```

Arguments

booster	Object of class gpb.Booster
num_iteration	number of iteration want to predict with, NULL or <= 0 means use best iteration

Value

json format of model

Examples

```

library(gpboost)
data(agaricus.train, package = "gpboost")
train <- agaricus.train
dtrain <- gpb.Dataset(train$data, label = train$label)
data(agaricus.test, package = "gpboost")
test <- agaricus.test
dtest <- gpb.Dataset.create.valid(dtrain, test$data, label = test$label)
params <- list(objective = "regression", metric = "l2")
valids <- list(test = dtest)
model <- gpb.train(
  params = params
  , data = dtrain
  , nrounds = 10L
  , valids = valids
  , min_data = 1L
  , learning_rate = 1.0
  , early_stopping_rounds = 5L
)
json_model <- gpb.dump(model)

```

`gpb.get.eval.result` *Get record evaluation result from booster*

Description

Given a `gpb.Booster`, return evaluation results for a particular metric on a particular dataset.

Usage

```
gpb.get.eval.result(booster, data_name, eval_name, iters = NULL,
  is_err = FALSE)
```

Arguments

<code>booster</code>	Object of class <code>gpb.Booster</code>
<code>data_name</code>	Name of the dataset to return evaluation results for.
<code>eval_name</code>	Name of the evaluation metric to return results for.
<code>iters</code>	An integer vector of iterations you want to get evaluation results for. If <code>NULL</code> (the default), evaluation results for all iterations will be returned.
<code>is_err</code>	<code>TRUE</code> will return evaluation error instead

Value

numeric vector of evaluation result

Examples

```

# train a regression model
data(agaricus.train, package = "gboost")
train <- agaricus.train
dtrain <- gpb.Dataset(train$data, label = train$label)
data(agaricus.test, package = "gboost")
test <- agaricus.test
dtest <- gpb.Dataset.create.valid(dtrain, test$data, label = test$label)
params <- list(objective = "regression", metric = "l2")
valids <- list(test = dtest)
model <- gpb.train(
  params = params
  , data = dtrain
  , nrounds = 5L
  , valids = valids
  , min_data = 1L
  , learning_rate = 1.0
)

# Examine valid data_name values
print(setdiff(names(model$record_evals), "start_iter"))

# Examine valid eval_name values for dataset "test"
print(names(model$record_evals[["test"]]))

# Get L2 values for "test" dataset
gpb.get.eval.result(model, "test", "l2")

```

gpb.grid.search.tune.parameters

Function for choosing tuning parameters

Description

Function that allows for choosing tuning parameters from a grid in a deterministic or random way using cross validation or validation data sets.

Usage

```

gpb.grid.search.tune.parameters(param_grid, data, params = list(),
  num_try_random = NULL, nrounds = 100L, gp_model = NULL,
  use_gp_model_for_validation = TRUE, train_gp_model_cov_pars = TRUE,
  folds = NULL, nfold = 4L, label = NULL, weight = NULL, obj = NULL,
  eval = NULL, verbose_eval = 1L, stratified = TRUE, init_model = NULL,
  colnames = NULL, categorical_feature = NULL,
  early_stopping_rounds = NULL, callbacks = list(), ...)

```

Arguments

param_grid	list with candidate parameters defining the grid over which a search is done
data	a gpb.Dataset object, used for training. Some functions, such as <code>gpb.cv</code> , may allow you to pass other types of data like matrix and then separately supply label as a keyword argument.
params	list with other parameters not included in param_grid
num_try_random	integer with number of random trial on parameter grid. If NULL, a deterministic search is done
nrounds	number of boosting iterations (= number of trees). This is the most important tuning parameter for boosting
gp_model	A GPModel object that contains the random effects (Gaussian process and / or grouped random effects) model
use_gp_model_for_validation	Boolean. If TRUE, the gp_model (Gaussian process and/or random effects) is also used (in addition to the tree model) for calculating predictions on the validation data. If FALSE, the gp_model (random effects part) is ignored for making predictions and only the tree ensemble is used for making predictions for calculating the validation / test error.
train_gp_model_cov_pars	Boolean. If TRUE, the covariance parameters of the gp_model (Gaussian process and/or random effects) are estimated in every boosting iterations, otherwise the gp_model parameters are not estimated. In the latter case, you need to either estimate them beforehand or provide the values via the <code>init_cov_pars</code> parameter when creating the gp_model
folds	list provides a possibility to use a list of pre-defined CV folds (each element must be a vector of test fold's indices). When folds are supplied, the <code>nfold</code> and <code>stratified</code> parameters are ignored.
nfold	the original dataset is randomly partitioned into <code>nfold</code> equal size subsamples.
label	Vector of labels, used if data is not an <code>gpb.Dataset</code>
weight	vector of response values. If not NULL, will set to dataset
obj	(character) The distribution of the response variable (=label) conditional on fixed and random effects. This only needs to be set when doing independent boosting without random effects / Gaussian processes.
eval	evaluation function(s). This can be a character vector, function, or list with a mixture of strings and functions. <ul style="list-style-type: none"> • a. character vector: If you provide a character vector to this argument, it should contain strings with valid evaluation metrics. See the "metric" section of the parameter documentation for a list of valid metrics. • b. function: You can provide a custom evaluation function. This should accept the keyword arguments <code>preds</code> and <code>dtrain</code> and should return a named list with three elements: <ul style="list-style-type: none"> – <code>name</code>: A string with the name of the metric, used for printing and storing results.

- **value:** A single number indicating the value of the metric for the given predictions and true values
- **higher_better:** A boolean indicating whether higher values indicate a better fit. For example, this would be `FALSE` for metrics like MAE or RMSE.
- **c. list:** If a list is given, it should only contain character vectors and functions. These should follow the requirements from the descriptions above.

<code>verbose_eval</code>	integer. Whether to display information on the progress of tuning parameter choice. If <code>None</code> or <code>0</code> , verbose is off. If <code>= 1</code> , summary progress information is displayed for every parameter combination. If <code>>= 2</code> , detailed progress is displayed at every boosting stage for every parameter combination.
<code>stratified</code>	a boolean indicating whether sampling of folds should be stratified by the values of outcome labels.
<code>init_model</code>	path of model file of gpb. <code>Booster</code> object, will continue training from this model
<code>colnames</code>	feature names, if not null, will use this to overwrite the names in dataset
<code>categorical_feature</code>	categorical features. This can either be a character vector of feature names or an integer vector with the indices of the features (e.g. <code>c(1L, 10L)</code> to say "the first and tenth columns").
<code>early_stopping_rounds</code>	int. Activates early stopping. Requires at least one validation data and one metric. When this parameter is non-null, training will stop if the evaluation of any metric on any validation set fails to improve for <code>early_stopping_rounds</code> consecutive boosting rounds. If training stops early, the returned model will have attribute <code>best_iter</code> set to the iteration number of the best iteration.
<code>callbacks</code>	List of callback functions that are applied at each iteration.
<code>...</code>	other parameters, see <code>Parameters.rst</code> for more information.

Value

A list with the best parameter combination and score The list has the following format: `list("best_params" = best_params, "best_iter" = best_iter, "best_score" = best_score)`

Early Stopping

"early stopping" refers to stopping the training process if the model's performance on a given validation set does not improve for several consecutive iterations.

If multiple arguments are given to `eval`, their order will be preserved. If you enable early stopping by setting `early_stopping_rounds` in `params`, by default all metrics will be considered for early stopping.

If you want to only consider the first metric for early stopping, pass `first_metric_only = TRUE` in `params`. Note that if you also specify `metric` in `params`, that metric will be considered the "first" one. If you omit `metric`, a default metric will be used based on your choice for the parameter `obj` (keyword argument) or `objective` (passed into `params`).

Author(s)

Fabio Sigrist

Examples

```
# See https://github.com/fabsig/GPBoost/tree/master/R-package for more examples

library(gpboost)
data(GPBoost_data, package = "gpboost")

# Create random effects model, dataset, and define parameter grid
gp_model <- GPModel(group_data = group_data[,1], likelihood="gaussian")
dataset <- gpb.Dataset(X, label = y)
param_grid = list("learning_rate" = c(1,0.1,0.01),
                  "min_data_in_leaf" = c(10,100,1000),
                  "max_depth" = c(1,2,3,5,10),
                  "lambda_l2" = c(0,1,10))
other_params <- list(num_leaves = 2^10)
# Note: here we try different values for 'max_depth' and thus set 'num_leaves' to a large value.
#       An alternative strategy is to impose no limit on 'max_depth',
#       and try different values for 'num_leaves' as follows:
# param_grid = list("learning_rate" = c(1,0.1,0.01),
#                  "min_data_in_leaf" = c(10,100,1000),
#                  "num_leaves" = 2^(1:10),
#                  "lambda_l2" = c(0,1,10))
# other_params <- list(max_depth = -1)
set.seed(1)
opt_params <- gpb.grid.search.tune.parameters(param_grid = param_grid, params = other_params,
                                           num_try_random = NULL, nfold = 4,
                                           data = dataset, gp_model = gp_model,
                                           use_gp_model_for_validation=TRUE, verbose_eval = 1,
                                           nrounds = 1000, early_stopping_rounds = 10)

print(paste0("Best parameters: ",
            paste0(unlist(lapply(seq_along(opt_params$best_params),
                              function(y, n, i) { paste0(n[[i]],": ", y[[i]] }),
                              y=opt_params$best_params,
                              n=names(opt_params$best_params))), collapse=", "))

print(paste0("Best number of iterations: ", opt_params$best_iter))
print(paste0("Best score: ", round(opt_params$best_score, digits=3)))
# Note: other scoring / evaluation metrics can be chosen using the
#       'metric' argument, e.g., metric = "l1"

# Using manually defined validation data instead of cross-validation
valid_tune_idx <- sample.int(length(y), as.integer(0.2*length(y)))
folds = list(valid_tune_idx)
opt_params <- gpb.grid.search.tune.parameters(param_grid = param_grid, params = other_params,
                                           num_try_random = NULL, folds = folds,
                                           data = dataset, gp_model = gp_model,
                                           use_gp_model_for_validation=TRUE, verbose_eval = 1,
                                           nrounds = 1000, early_stopping_rounds = 10)
```

gpb.importance	<i>Compute feature importance in a model</i>
----------------	--

Description

Creates a `data.table` of feature importances in a model.

Usage

```
gpb.importance(model, percentage = TRUE)
```

Arguments

<code>model</code>	object of class <code>gpb.Booster</code> .
<code>percentage</code>	whether to show importance in relative percentage.

Value

For a tree model, a `data.table` with the following columns:

- `Feature`: Feature names in the model.
- `Gain`: The total gain of this feature's splits.
- `Cover`: The number of observation related to this feature.
- `Frequency`: The number of times a feature splitted in trees.

Examples

```
data(agaricus.train, package = "gpboost")
train <- agaricus.train
dtrain <- gpb.Dataset(train$data, label = train$label)

params <- list(
  objective = "binary"
  , learning_rate = 0.1
  , max_depth = -1L
  , min_data_in_leaf = 1L
  , min_sum_hessian_in_leaf = 1.0
)
model <- gpb.train(
  params = params
  , data = dtrain
  , nrounds = 5L
)

tree_imp1 <- gpb.importance(model, percentage = TRUE)
tree_imp2 <- gpb.importance(model, percentage = FALSE)
```

`gpb.interprete` *Compute feature contribution of prediction*

Description

Computes feature contribution components of rawscore prediction.

Usage

```
gpb.interprete(model, data, idxset, num_iteration = NULL)
```

Arguments

`model` object of class `gpb.Booster`.
`data` a matrix object or a `dgCMatrix` object.
`idxset` an integer vector of indices of rows needed.
`num_iteration` number of iteration want to predict with, `NULL` or `<= 0` means use best iteration.

Value

For regression, binary classification and lambdarank model, a list of `data.table` with the following columns:

- `Feature`: Feature names in the model.
- `Contribution`: The total contribution of this feature's splits.

For multiclass classification, a list of `data.table` with the `Feature` column and `Contribution` columns to each class.

Examples

```
Logit <- function(x) log(x / (1.0 - x))
data(agaricus.train, package = "gpboost")
train <- agaricus.train
dtrain <- gpb.Dataset(train$data, label = train$label)
setinfo(dtrain, "init_score", rep(Logit(mean(train$label)), length(train$label)))
data(agaricus.test, package = "gpboost")
test <- agaricus.test

params <- list(
  objective = "binary"
  , learning_rate = 0.1
  , max_depth = -1L
  , min_data_in_leaf = 1L
  , min_sum_hessian_in_leaf = 1.0
)
model <- gpb.train(
```

```

      params = params
      , data = dtrain
      , nrounds = 3L
    )

    tree_interpretation <- gpb.interprete(model, test$data, 1L:5L)

```

gpb.load

Load GPBoost model

Description

Load GPBoost takes in either a file path or model string. If both are provided, Load will default to loading from file Boosters with gp_models can only be loaded from file.

Usage

```
gpb.load(filename = NULL, model_str = NULL)
```

Arguments

filename	path of model file
model_str	a str containing the model

Value

gpb.Booster

Author(s)

Fabio Sigrist, authors of the LightGBM R package

Examples

```

library(gpboost)
data(GPBoost_data, package = "gpboost")

# Train model and make prediction
gp_model <- GPModel(group_data = group_data[,1], likelihood = "gaussian")
bst <- gpboost(data = X, label = y, gp_model = gp_model, nrounds = 16,
              learning_rate = 0.05, max_depth = 6, min_data_in_leaf = 5,
              verbose = 0)
pred <- predict(bst, data = X_test, group_data_pred = group_data_test[,1],
               predict_var= TRUE, pred_latent = TRUE)
# Save model to file
filename <- tempfile(fileext = ".json")
gpb.save(bst,filename = filename)

```

```
# Load from file and make predictions again
bst_loaded <- gpb.load(filename = filename)
pred_loaded <- predict(bst_loaded, data = X_test, group_data_pred = group_data_test[,1],
                      predict_var= TRUE, pred_latent = TRUE)
# Check equality
pred$fixed_effect - pred_loaded$fixed_effect
pred$random_effect_mean - pred_loaded$random_effect_mean
pred$random_effect_cov - pred_loaded$random_effect_cov
```

`gpb.model.dt.tree` *Parse a GPBoost model json dump*

Description

Parse a GPBoost model json dump into a `data.table` structure.

Usage

```
gpb.model.dt.tree(model, num_iteration = NULL)
```

Arguments

<code>model</code>	object of class <code>gpb.Booster</code>
<code>num_iteration</code>	number of iterations you want to predict with. <code>NULL</code> or <code><= 0</code> means use best iteration

Value

A `data.table` with detailed information about model trees' nodes and leaves.

The columns of the `data.table` are:

- `tree_index`: ID of a tree in a model (integer)
- `split_index`: ID of a node in a tree (integer)
- `split_feature`: for a node, it's a feature name (character); for a leaf, it simply labels it as "NA"
- `node_parent`: ID of the parent node for current node (integer)
- `leaf_index`: ID of a leaf in a tree (integer)
- `leaf_parent`: ID of the parent node for current leaf (integer)
- `split_gain`: Split gain of a node
- `threshold`: Splitting threshold value of a node
- `decision_type`: Decision type of a node
- `default_left`: Determine how to handle NA value, `TRUE` -> Left, `FALSE` -> Right
- `internal_value`: Node value
- `internal_count`: The number of observation collected by a node
- `leaf_value`: Leaf value
- `leaf_count`: The number of observation collected by a leaf

Examples

```

data(agaricus.train, package = "gboost")
train <- agaricus.train
dtrain <- gpb.Dataset(train$data, label = train$label)

params <- list(
  objective = "binary"
  , learning_rate = 0.01
  , num_leaves = 63L
  , max_depth = -1L
  , min_data_in_leaf = 1L
  , min_sum_hessian_in_leaf = 1.0
)
model <- gpb.train(params, dtrain, 10L)

tree_dt <- gpb.model.dt.tree(model)

```

`gpb.plot.importance` *Plot feature importance as a bar graph*

Description

Plot previously calculated feature importance: Gain, Cover and Frequency, as a bar graph.

Usage

```

gpb.plot.importance(tree_imp, top_n = 10L, measure = "Gain",
  left_margin = 10L, cex = NULL, ...)

```

Arguments

<code>tree_imp</code>	a data.table returned by gpb.importance .
<code>top_n</code>	maximal number of top features to include into the plot.
<code>measure</code>	the name of importance measure to plot, can be "Gain", "Cover" or "Frequency".
<code>left_margin</code>	(base R barplot) allows to adjust the left margin size to fit feature names.
<code>cex</code>	(base R barplot) passed as <code>cex.names</code> parameter to barplot . Set a number smaller than 1.0 to make the bar labels smaller than R's default and values greater than 1.0 to make them larger.
<code>...</code>	other parameters passed to <code>graphics::barplot</code>

Details

The graph represents each feature as a horizontal bar of length proportional to the defined importance of a feature. Features are shown ranked in a decreasing importance order.

Value

The `gpb.plot.importance` function creates a barplot and silently returns a processed `data.table` with `top_n` features sorted by defined importance.

Examples

```
data(agaricus.train, package = "gboost")
train <- agaricus.train
dtrain <- gpb.Dataset(train$data, label = train$label)

params <- list(
  objective = "binary"
  , learning_rate = 0.1
  , min_data_in_leaf = 1L
  , min_sum_hessian_in_leaf = 1.0
)

model <- gpb.train(
  params = params
  , data = dtrain
  , nrounds = 5L
)

tree_imp <- gpb.importance(model, percentage = TRUE)
gpb.plot.importance(tree_imp, top_n = 5L, measure = "Gain")
```

`gpb.plot.interpretation`

Plot feature contribution as a bar graph

Description

Plot previously calculated feature contribution as a bar graph.

Usage

```
gpb.plot.interpretation(tree_interpretation_dt, top_n = 10L, cols = 1L,
  left_margin = 10L, cex = NULL)
```

Arguments

<code>tree_interpretation_dt</code>	a <code>data.table</code> returned by gpb.interprete .
<code>top_n</code>	maximal number of top features to include into the plot.
<code>cols</code>	the column numbers of layout, will be used only for multiclass classification feature contribution.

`left_margin` (base R barplot) allows to adjust the left margin size to fit feature names.
`cex` (base R barplot) passed as `cex.names` parameter to `barplot`.

Details

The graph represents each feature as a horizontal bar of length proportional to the defined contribution of a feature. Features are shown ranked in a decreasing contribution order.

Value

The `gpb.plot.interpretation` function creates a barplot.

Examples

```
Logit <- function(x) {
  log(x / (1.0 - x))
}
data(agaricus.train, package = "gboost")
labels <- agaricus.train$label
dtrain <- gpb.Dataset(
  agaricus.train$data
  , label = labels
)
setinfo(dtrain, "init_score", rep(Logit(mean(labels)), length(labels)))

data(agaricus.test, package = "gboost")

params <- list(
  objective = "binary"
  , learning_rate = 0.1
  , max_depth = -1L
  , min_data_in_leaf = 1L
  , min_sum_hessian_in_leaf = 1.0
)
model <- gpb.train(
  params = params
  , data = dtrain
  , nrounds = 5L
)

tree_interpretation <- gpb.interprete(
  model = model
  , data = agaricus.test$data
  , idxset = 1L:5L
)
gpb.plot.interpretation(
  tree_interpretation_dt = tree_interpretation[[1L]]
  , top_n = 3L
)
```

gpb.plot.part.dep.interact

Plot interaction partial dependence plots

Description

Plot interaction partial dependence plots

Usage

```
gpb.plot.part.dep.interact(model, data, variables, n.pt.per.var = 20,
  subsample = pmin(1, n.pt.per.var^2 * 100/nrow(data)),
  discrete.variables = c(FALSE, FALSE), which.class = NULL,
  type = "filled.contour", nlevels = 20, xlab = variables[1],
  ylab = variables[2], zlab = "", main = "", return_plot_data = FALSE,
  ...)
```

Arguments

model	A gpb.Booster model object
data	A matrix with data for creating partial dependence plots
variables	A vector of length two of type string with names of the columns or integer with indices of the columns in data for which an interaction dependence plot is created
n.pt.per.var	Number of grid points per variable (used only if a variable is not discrete) For continuous variables, the two-dimensional grid for the interaction plot has dimension $c(n.pt.per.var, n.pt.per.var)$
subsample	Fraction of random samples in data to be used for calculating the partial dependence plot
discrete.variables	A vector of length two of type boolean. If an entry is TRUE, the evaluation grid of the corresponding variable is set to the unique values of the variable
which.class	An integer indicating the class in multi-class classification (value from 0 to num_class - 1)
type	A character string indicating the type of the plot. Supported values: "filled.contour" and "contour"
nlevels	Parameter passed to the filled.contour or contour function
xlab	Parameter passed to the filled.contour or contour function
ylab	Parameter passed to the filled.contour or contour function
zlab	Parameter passed to the filled.contour or contour function
main	Parameter passed to the filled.contour or contour function
return_plot_data	A boolean. If TRUE, the data for creating the partial dependence plot is returned
...	Additional parameters passed to the filled.contour or contour function

Value

A list with three entries for creating the partial dependence plot: the first two entries are vectors with x and y coordinates. The third is a two-dimensional matrix of dimension $c(\text{length}(x), \text{length}(y))$ with z-coordinates. This is only returned if `return_plot_data==TRUE`

Author(s)

Fabio Sigrist

Examples

```
library(gpboost)
data(GPBoost_data, package = "gpboost")
gp_model <- GPModel(group_data = group_data[,1], likelihood = "gaussian")
gpboost_model <- gpboost(data = X,
                        label = y,
                        gp_model = gp_model,
                        nrounds = 16,
                        learning_rate = 0.05,
                        max_depth = 6,
                        min_data_in_leaf = 5,
                        verbose = 0)
gpb.plot.part.dep.interact(gpboost_model, X, variables = c(1,2))
```

`gpb.plot.partial.dependence`

Plot partial dependence plots

Description

Plot partial dependence plots

Usage

```
gpb.plot.partial.dependence(model, data, variable, n.pt = 100,
                          subsample = pmin(1, n.pt * 100/nrow(data)), discrete.x = FALSE,
                          which.class = NULL, xlab = deparse(substitute(variable)), ylab = "",
                          type = if (discrete.x) "p" else "b", main = "",
                          return_plot_data = FALSE, ...)
```

Arguments

<code>model</code>	A <code>gpb.Booster</code> model object
<code>data</code>	A matrix with data for creating partial dependence plots
<code>variable</code>	A string with a name of the column or an integer with an index of the column in data for which a dependence plot is created

<code>n.pt</code>	Evaluation grid size (used only if <code>x</code> is not discrete)
<code>subsample</code>	Fraction of random samples in data to be used for calculating the partial dependence plot
<code>discrete.x</code>	A boolean. If TRUE, the evaluation grid is set to the unique values of <code>x</code>
<code>which.class</code>	An integer indicating the class in multi-class classification (value from 0 to <code>num_class - 1</code>)
<code>xlab</code>	Parameter passed to plot
<code>ylab</code>	Parameter passed to plot
<code>type</code>	Parameter passed to plot
<code>main</code>	Parameter passed to plot
<code>return_plot_data</code>	A boolean. If TRUE, the data for creating the partial dependence plot is returned
<code>...</code>	Additional parameters passed to plot

Value

A two-dimensional matrix with data for creating the partial dependence plot. This is only returned if `return_plot_data==TRUE`

Author(s)

Fabio Sigrist (adapted from a version by Michael Mayer)

Examples

```
library(gpboost)
data(GPBoost_data, package = "gpboost")

gp_model <- GPModel(group_data = group_data[,1], likelihood = "gaussian")
gpboost_model <- gpboost(data = X,
                        label = y,
                        gp_model = gp_model,
                        nrounds = 16,
                        learning_rate = 0.05,
                        max_depth = 6,
                        min_data_in_leaf = 5,
                        verbose = 0)
gpb.plot.partial.dependence(gpboost_model, X, variable = 1)
```

gpb.save	<i>Save GPBoost model</i>
----------	---------------------------

Description

Save GPBoost model

Usage

```
gpb.save(booster, filename, start_iteration = NULL, num_iteration = NULL,
         save_raw_data = FALSE, ...)
```

Arguments

booster	Object of class <code>gpb.Booster</code>
filename	saved filename
start_iteration	int or NULL, optional (default=NULL) Start index of the iteration to predict. If NULL or ≤ 0 , starts from the first iteration.
num_iteration	int or NULL, optional (default=NULL) Limit number of iterations in the prediction. If NULL, if the best iteration exists and start_iteration is NULL or ≤ 0 , the best iteration is used; otherwise, all iterations from start_iteration are used. If ≤ 0 , all iterations from start_iteration are used (no limits).
save_raw_data	If TRUE, the raw data (predictor / covariate data) for the Booster is also saved. Enable this option if you want to change start_iteration or num_iteration at prediction time after loading.
...	Additional named arguments passed to the <code>predict()</code> method of the <code>gpb.Booster</code> object passed to object. This is only used when there is a <code>gp_model</code> and when <code>save_raw_data=FALSE</code>

Value

`gpb.Booster`

Author(s)

Fabio Sigrist, authors of the LightGBM R package

Examples

```
library(gpboost)
data(GPBoost_data, package = "gpboost")

# Train model and make prediction
gp_model <- GPModel(group_data = group_data[,1], likelihood = "gaussian")
bst <- gpboost(data = X, label = y, gp_model = gp_model, nrounds = 16,
```

```

        learning_rate = 0.05, max_depth = 6, min_data_in_leaf = 5,
        verbose = 0)
pred <- predict(bst, data = X_test, group_data_pred = group_data_test[,1],
               predict_var= TRUE, pred_latent = TRUE)
# Save model to file
filename <- tempfile(fileext = ".json")
gpb.save(bst,filename = filename)
# Load from file and make predictions again
bst_loaded <- gpb.load(filename = filename)
pred_loaded <- predict(bst_loaded, data = X_test, group_data_pred = group_data_test[,1],
                     predict_var= TRUE, pred_latent = TRUE)
# Check equality
pred$fixed_effect - pred_loaded$fixed_effect
pred$random_effect_mean - pred_loaded$random_effect_mean
pred$random_effect_cov - pred_loaded$random_effect_cov

```

gpb.train

Main training logic for GBPoost

Description

Logic to train with GBPoost

Usage

```

gpb.train(params = list(), data, nrounds = 100L, gp_model = NULL,
          use_gp_model_for_validation = TRUE, train_gp_model_cov_pars = TRUE,
          valids = list(), obj = NULL, eval = NULL, verbose = 1L,
          record = TRUE, eval_freq = 1L, init_model = NULL, colnames = NULL,
          categorical_feature = NULL, early_stopping_rounds = NULL,
          callbacks = list(), reset_data = FALSE, ...)

```

Arguments

- | | |
|--------|---|
| params | <p>list of "tuning" parameters. See the parameter documentation for more information. A few key parameters:</p> <ul style="list-style-type: none"> • <code>learning_rate</code>: The learning rate, also called shrinkage or damping parameter (default = 0.1). An important tuning parameter for boosting. Lower values usually lead to higher predictive accuracy but more boosting iterations are needed • <code>num_leaves</code>: Number of leaves in a tree. Tuning parameter for tree-boosting (default = 31) • <code>max_depth</code>: Maximal depth of a tree. Tuning parameter for tree-boosting (default = no limit) • <code>min_data_in_leaf</code>: Minimal number of samples per leaf. Tuning parameter for tree-boosting (default = 20) • <code>lambda_l2</code>: L2 regularization (default = 0) |
|--------|---|

- `lambda_l1`: L1 regularization (default = 0)
- `max_bin`: Maximal number of bins that feature values will be bucketed in (default = 255)
- `train_gp_model_cov_pars`: If TRUE, the covariance parameters of the Gaussian process are estimated in every boosting iterations, otherwise the `gp_model` parameters are not estimated. In the latter case, you need to either estimate them beforehand or provide the values via the `'init_cov_pars'` parameter when creating the `gp_model` (default = TRUE).
- `use_gp_model_for_validation`: If TRUE, the Gaussian process is also used (in addition to the tree model) for calculating predictions on the validation data (default = TRUE)
- `leaves_newton_update`: Set this to TRUE to do a Newton update step for the tree leaves after the gradient step. Applies only to Gaussian process boosting (GPBoost algorithm)
- `num_threads`: Number of threads. For the best speed, set this to the number of real CPU cores (`parallel::detectCores(logical = FALSE)`), not the number of threads (most CPU using hyper-threading to generate 2 threads per CPU core).

<code>data</code>	a <code>gpb.Dataset</code> object, used for training. Some functions, such as <code>gpb.cv</code> , may allow you to pass other types of data like <code>matrix</code> and then separately supply <code>label</code> as a keyword argument.
<code>nrounds</code>	number of boosting iterations (= number of trees). This is the most important tuning parameter for boosting
<code>gp_model</code>	A <code>GPMModel</code> object that contains the random effects (Gaussian process and / or grouped random effects) model
<code>use_gp_model_for_validation</code>	Boolean. If TRUE, the <code>gp_model</code> (Gaussian process and/or random effects) is also used (in addition to the tree model) for calculating predictions on the validation data. If FALSE, the <code>gp_model</code> (random effects part) is ignored for making predictions and only the tree ensemble is used for making predictions for calculating the validation / test error.
<code>train_gp_model_cov_pars</code>	Boolean. If TRUE, the covariance parameters of the <code>gp_model</code> (Gaussian process and/or random effects) are estimated in every boosting iterations, otherwise the <code>gp_model</code> parameters are not estimated. In the latter case, you need to either estimate them beforehand or provide the values via the <code>init_cov_pars</code> parameter when creating the <code>gp_model</code>
<code>valids</code>	a list of <code>gpb.Dataset</code> objects, used for validation
<code>obj</code>	(character) The distribution of the response variable (=label) conditional on fixed and random effects. This only needs to be set when doing independent boosting without random effects / Gaussian processes.
<code>eval</code>	evaluation function(s). This can be a character vector, function, or list with a mixture of strings and functions. <ul style="list-style-type: none"> • a. character vector: If you provide a character vector to this argument, it should contain strings with valid evaluation metrics. See the "metric" section of the parameter documentation for a list of valid metrics.

- **b. function:** You can provide a custom evaluation function. This should accept the keyword arguments `preds` and `dtrain` and should return a named list with three elements:
 - `name`: A string with the name of the metric, used for printing and storing results.
 - `value`: A single number indicating the value of the metric for the given predictions and true values
 - `higher_better`: A boolean indicating whether higher values indicate a better fit. For example, this would be `FALSE` for metrics like MAE or RMSE.
- **c. list:** If a list is given, it should only contain character vectors and functions. These should follow the requirements from the descriptions above.

<code>verbose</code>	verbosity for output, if ≤ 0 , also will disable the print of evaluation during training
<code>record</code>	Boolean, <code>TRUE</code> will record iteration message to <code>booster\$record_evals</code>
<code>eval_freq</code>	evaluation output frequency, only effect when <code>verbose > 0</code>
<code>init_model</code>	path of model file of <code>gpb.Booster</code> object, will continue training from this model
<code>colnames</code>	feature names, if not null, will use this to overwrite the names in dataset
<code>categorical_feature</code>	categorical features. This can either be a character vector of feature names or an integer vector with the indices of the features (e.g. <code>c(1L, 10L)</code> to say "the first and tenth columns").
<code>early_stopping_rounds</code>	int. Activates early stopping. Requires at least one validation data and one metric. When this parameter is non-null, training will stop if the evaluation of any metric on any validation set fails to improve for <code>early_stopping_rounds</code> consecutive boosting rounds. If training stops early, the returned model will have attribute <code>best_iter</code> set to the iteration number of the best iteration.
<code>callbacks</code>	List of callback functions that are applied at each iteration.
<code>reset_data</code>	Boolean, setting it to <code>TRUE</code> (not the default value) will transform the booster model into a predictor model which frees up memory and the original datasets
<code>...</code>	other parameters, see the parameter documentation for more information.

Value

a trained booster model `gpb.Booster`.

Early Stopping

"early stopping" refers to stopping the training process if the model's performance on a given validation set does not improve for several consecutive iterations.

If multiple arguments are given to `eval`, their order will be preserved. If you enable early stopping by setting `early_stopping_rounds` in `params`, by default all metrics will be considered for early stopping.

If you want to only consider the first metric for early stopping, pass `first_metric_only = TRUE` in `params`. Note that if you also specify `metric` in `params`, that metric will be considered the "first" one. If you omit `metric`, a default metric will be used based on your choice for the parameter `obj` (keyword argument) or `objective` (passed into `params`).

Author(s)

Fabio Sigrist, authors of the LightGBM R package

Examples

```
# See https://github.com/fabsig/GPBoost/tree/master/R-package for more examples

library(gpboost)
data(GPBoost_data, package = "gpboost")

#-----Combine tree-boosting and grouped random effects model-----
# Create random effects model
gp_model <- GPModel(group_data = group_data[,1], likelihood = "gaussian")
# The default optimizer for covariance parameters (hyperparameters) is
# Nesterov-accelerated gradient descent.
# This can be changed to, e.g., Nelder-Mead as follows:
# re_params <- list(optimizer_cov = "nelder_mead")
# gp_model$set_optim_params(params=re_params)
# Use trace = TRUE to monitor convergence:
# re_params <- list(trace = TRUE)
# gp_model$set_optim_params(params=re_params)
dtrain <- gpb.Dataset(data = X, label = y)
# Train model
bst <- gpb.train(data = dtrain, gp_model = gp_model, nrounds = 16,
                 learning_rate = 0.05, max_depth = 6, min_data_in_leaf = 5,
                 verbose = 0)
# Estimated random effects model
summary(gp_model)
# Make predictions
pred <- predict(bst, data = X_test, group_data_pred = group_data_test[,1],
               predict_var= TRUE)
pred$random_effect_mean # Predicted mean
pred$random_effect_cov # Predicted variances
pred$fixed_effect # Predicted fixed effect from tree ensemble
# Sum them up to obtain a single prediction
pred$random_effect_mean + pred$fixed_effect

#-----Combine tree-boosting and Gaussian process model-----
# Create Gaussian process model
gp_model <- GPModel(gp_coords = coords, cov_function = "exponential",
                   likelihood = "gaussian")
# Train model
dtrain <- gpb.Dataset(data = X, label = y)
bst <- gpb.train(data = dtrain, gp_model = gp_model, nrounds = 16,
                 learning_rate = 0.05, max_depth = 6, min_data_in_leaf = 5,
```

```

        verbose = 0)
# Estimated random effects model
summary(gp_model)
# Make predictions
pred <- predict(bst, data = X_test, gp_coords_pred = coords_test,
               predict_cov_mat =TRUE)
pred$random_effect_mean # Predicted (posterior) mean of GP
pred$random_effect_cov # Predicted (posterior) covariance matrix of GP
pred$fixed_effect # Predicted fixed effect from tree ensemble
# Sum them up to obtain a single prediction
pred$random_effect_mean + pred$fixed_effect

#-----Using validation data-----
set.seed(1)
train_ind <- sample.int(length(y),size=250)
dtrain <- gpb.Dataset(data = X[train_ind,], label = y[train_ind])
dtest <- gpb.Dataset.create.valid(dtrain, data = X[-train_ind,], label = y[-train_ind])
valids <- list(test = dtest)
gp_model <- GPModel(group_data = group_data[train_ind,1], likelihood="gaussian")
# Need to set prediction data for gp_model
gp_model$set_prediction_data(group_data_pred = group_data[-train_ind,1])
# Training with validation data and use_gp_model_for_validation = TRUE
bst <- gpb.train(data = dtrain, gp_model = gp_model, nrounds = 100,
                learning_rate = 0.05, max_depth = 6, min_data_in_leaf = 5,
                verbose = 1, valids = valids,
                early_stopping_rounds = 10, use_gp_model_for_validation = TRUE)
print(paste0("Optimal number of iterations: ", bst$best_iter,
            ", best test error: ", bst$best_score))
# Plot validation error
val_error <- unlist(bst$record_evals$test$l2$eval)
plot(1:length(val_error), val_error, type="l", lwd=2, col="blue",
     xlab="iteration", ylab="Validation error", main="Validation error vs. boosting iteration")

#-----Do Newton updates for tree leaves-----
# Note: run the above examples first
bst <- gpb.train(data = dtrain, gp_model = gp_model, nrounds = 100,
                learning_rate = 0.05, max_depth = 6, min_data_in_leaf = 5,
                verbose = 1, valids = valids,
                early_stopping_rounds = 5, use_gp_model_for_validation = FALSE,
                leaves_newton_update = TRUE)
print(paste0("Optimal number of iterations: ", bst$best_iter,
            ", best test error: ", bst$best_score))
# Plot validation error
val_error <- unlist(bst$record_evals$test$l2$eval)
plot(1:length(val_error), val_error, type="l", lwd=2, col="blue",
     xlab="iteration", ylab="Validation error", main="Validation error vs. boosting iteration")

#-----GPBoostOOS algorithm: GP parameters estimated out-of-sample-----
# Create random effects model and dataset
gp_model <- GPModel(group_data = group_data[,1], likelihood="gaussian")

```

```

dtrain <- gpb.Dataset(X, label = y)
params <- list(learning_rate = 0.05,
              max_depth = 6,
              min_data_in_leaf = 5)
# Stage 1: run cross-validation to (i) determine to optimal number of iterations
#           and (ii) to estimate the GPModel on the out-of-sample data
cvbst <- gpb.cv(params = params,
               data = dtrain,
               gp_model = gp_model,
               nrounds = 100,
               nfold = 4,
               eval = "l2",
               early_stopping_rounds = 5,
               use_gp_model_for_validation = TRUE,
               fit_GP_cov_pars_OOS = TRUE)
print(paste0("Optimal number of iterations: ", cvbst$best_iter))
# Estimated random effects model
# Note: ideally, one would have to find the optimal combination of
#       other tuning parameters such as the learning rate, tree depth, etc.)
summary(gp_model)
# Stage 2: Train tree-boosting model while holding the GPModel fix
bst <- gpb.train(data = dtrain,
                 gp_model = gp_model,
                 nrounds = cvbst$best_iter,
                 learning_rate = 0.05,
                 max_depth = 6,
                 min_data_in_leaf = 5,
                 verbose = 0,
                 train_gp_model_cov_pars = FALSE)
# The GPModel has not changed:
summary(gp_model)

```

gpboost

Train a GPBoost model

Description

Simple interface for training a GPBoost model.

Usage

```

gpboost(data, label = NULL, weight = NULL, params = list(),
        nrounds = 100L, gp_model = NULL, use_gp_model_for_validation = TRUE,
        train_gp_model_cov_pars = TRUE, valids = list(), obj = NULL,
        eval = NULL, verbose = 1L, record = TRUE, eval_freq = 1L,
        early_stopping_rounds = NULL, init_model = NULL, colnames = NULL,
        categorical_feature = NULL, callbacks = list(), ...)

```

Arguments

data	a <code>gpb.Dataset</code> object, used for training. Some functions, such as <code>gpb.cv</code> , may allow you to pass other types of data like <code>matrix</code> and then separately supply <code>label</code> as a keyword argument.
label	Vector of response values / labels, used if data is not an <code>gpb.Dataset</code>
weight	Vector of weights. The GPBoost algorithm currently does not support weights
params	list of "tuning" parameters. See the parameter documentation for more information. A few key parameters: <ul style="list-style-type: none"> • <code>learning_rate</code>: The learning rate, also called shrinkage or damping parameter (default = 0.1). An important tuning parameter for boosting. Lower values usually lead to higher predictive accuracy but more boosting iterations are needed • <code>num_leaves</code>: Number of leaves in a tree. Tuning parameter for tree-boosting (default = 31) • <code>max_depth</code>: Maximal depth of a tree. Tuning parameter for tree-boosting (default = no limit) • <code>min_data_in_leaf</code>: Minimal number of samples per leaf. Tuning parameter for tree-boosting (default = 20) • <code>lambda_l2</code>: L2 regularization (default = 0) • <code>lambda_l1</code>: L1 regularization (default = 0) • <code>max_bin</code>: Maximal number of bins that feature values will be bucketed in (default = 255) • <code>train_gp_model_cov_pars</code>: If TRUE, the covariance parameters of the Gaussian process are estimated in every boosting iterations, otherwise the <code>gp_model</code> parameters are not estimated. In the latter case, you need to either estimate them beforehand or provide the values via the <code>'init_cov_pars'</code> parameter when creating the <code>gp_model</code> (default = TRUE). • <code>use_gp_model_for_validation</code>: If TRUE, the Gaussian process is also used (in addition to the tree model) for calculating predictions on the validation data (default = TRUE) • <code>leaves_newton_update</code>: Set this to TRUE to do a Newton update step for the tree leaves after the gradient step. Applies only to Gaussian process boosting (GPBoost algorithm) • <code>num_threads</code>: Number of threads. For the best speed, set this to the number of real CPU cores (<code>parallel::detectCores(logical = FALSE)</code>), not the number of threads (most CPU using hyper-threading to generate 2 threads per CPU core).
nrounds	number of boosting iterations (= number of trees). This is the most important tuning parameter for boosting
gp_model	A <code>GPMModel</code> object that contains the random effects (Gaussian process and / or grouped random effects) model
use_gp_model_for_validation	Boolean. If TRUE, the <code>gp_model</code> (Gaussian process and/or random effects) is also used (in addition to the tree model) for calculating predictions on the

	validation data. If FALSE, the <code>gp_model</code> (random effects part) is ignored for making predictions and only the tree ensemble is used for making predictions for calculating the validation / test error.
<code>train_gp_model_cov_pars</code>	Boolean. If TRUE, the covariance parameters of the <code>gp_model</code> (Gaussian process and/or random effects) are estimated in every boosting iterations, otherwise the <code>gp_model</code> parameters are not estimated. In the latter case, you need to either estimate them beforehand or provide the values via the <code>init_cov_pars</code> parameter when creating the <code>gp_model</code>
<code>valids</code>	a list of <code>gpb.Dataset</code> objects, used for validation
<code>obj</code>	(character) The distribution of the response variable (=label) conditional on fixed and random effects. This only needs to be set when doing independent boosting without random effects / Gaussian processes.
<code>eval</code>	evaluation function(s). This can be a character vector, function, or list with a mixture of strings and functions. <ul style="list-style-type: none"> • a. character vector: If you provide a character vector to this argument, it should contain strings with valid evaluation metrics. See the "metric" section of the parameter documentation for a list of valid metrics. • b. function: You can provide a custom evaluation function. This should accept the keyword arguments <code>preds</code> and <code>dtrain</code> and should return a named list with three elements: <ul style="list-style-type: none"> – <code>name</code>: A string with the name of the metric, used for printing and storing results. – <code>value</code>: A single number indicating the value of the metric for the given predictions and true values – <code>higher_better</code>: A boolean indicating whether higher values indicate a better fit. For example, this would be FALSE for metrics like MAE or RMSE. • c. list: If a list is given, it should only contain character vectors and functions. These should follow the requirements from the descriptions above.
<code>verbose</code>	verbosity for output, if ≤ 0 , also will disable the print of evaluation during training
<code>record</code>	Boolean, TRUE will record iteration message to <code>booster\$record_evals</code>
<code>eval_freq</code>	evaluation output frequency, only effect when <code>verbose > 0</code>
<code>early_stopping_rounds</code>	int. Activates early stopping. Requires at least one validation data and one metric. When this parameter is non-null, training will stop if the evaluation of any metric on any validation set fails to improve for <code>early_stopping_rounds</code> consecutive boosting rounds. If training stops early, the returned model will have attribute <code>best_iter</code> set to the iteration number of the best iteration.
<code>init_model</code>	path of model file of <code>gpb.Booster</code> object, will continue training from this model
<code>colnames</code>	feature names, if not null, will use this to overwrite the names in dataset
<code>categorical_feature</code>	categorical features. This can either be a character vector of feature names or an integer vector with the indices of the features (e.g. <code>c(1L, 10L)</code> to say "the first and tenth columns").

callbacks	List of callback functions that are applied at each iteration.
...	Additional arguments passed to <code>gpb.train</code> . For example <ul style="list-style-type: none"> • <code>valids</code>: a list of <code>gpb.Dataset</code> objects, used for validation • <code>eval</code>: evaluation function, can be (a list of) character or custom eval function • <code>record</code>: Boolean, TRUE will record iteration message to <code>booster\$record_evals</code> • <code>colnames</code>: feature names, if not null, will use this to overwrite the names in dataset • <code>categorical_feature</code>: categorical features. This can either be a character vector of feature names or an integer vector with the indices of the features (e.g. <code>c(1L, 10L)</code> to say "the first and tenth columns"). • <code>reset_data</code>: Boolean, setting it to TRUE (not the default value) will transform the booster model into a predictor model which frees up memory and the original datasets

Value

a trained `gpb.Booster`

Early Stopping

"early stopping" refers to stopping the training process if the model's performance on a given validation set does not improve for several consecutive iterations.

If multiple arguments are given to `eval`, their order will be preserved. If you enable early stopping by setting `early_stopping_rounds` in `params`, by default all metrics will be considered for early stopping.

If you want to only consider the first metric for early stopping, pass `first_metric_only = TRUE` in `params`. Note that if you also specify `metric` in `params`, that metric will be considered the "first" one. If you omit `metric`, a default metric will be used based on your choice for the parameter `obj` (keyword argument) or `objective` (passed into `params`).

Author(s)

Fabio Sigrist, authors of the LightGBM R package

Examples

```
# See https://github.com/fabsig/GPBoost/tree/master/R-package for more examples

library(gpboost)
data(GPBoost_data, package = "gpboost")

#-----Combine tree-boosting and grouped random effects model-----
# Create random effects model
gp_model <- GPModel(group_data = group_data[,1], likelihood = "gaussian")
# The default optimizer for covariance parameters (hyperparameters) is
# Nesterov-accelerated gradient descent.
```



```

# This can be changed to, e.g., Nelder-Mead as follows:
# re_params <- list(optimizer_cov = "nelder_mead")
# gp_model$set_optim_params(params=re_params)
# Use trace = TRUE to monitor convergence:
# re_params <- list(trace = TRUE)
# gp_model$set_optim_params(params=re_params)

# Train model
bst <- gpboost(data = X, label = y, gp_model = gp_model, nrounds = 16,
              learning_rate = 0.05, max_depth = 6, min_data_in_leaf = 5,
              verbose = 0)
# Estimated random effects model
summary(gp_model)

# Make predictions
# Predict latent variables
pred <- predict(bst, data = X_test, group_data_pred = group_data_test[,1],
               predict_var = TRUE, pred_latent = TRUE)
pred$random_effect_mean # Predicted latent random effects mean
pred$random_effect_cov # Predicted random effects variances
pred$fixed_effect # Predicted fixed effects from tree ensemble
# Predict response variable
pred_resp <- predict(bst, data = X_test, group_data_pred = group_data_test[,1],
                   predict_var = TRUE, pred_latent = FALSE)
pred_resp$response_mean # Predicted response mean
# For Gaussian data: pred$random_effect_mean + pred$fixed_effect = pred_resp$response_mean
pred$random_effect_mean + pred$fixed_effect - pred_resp$response_mean

#-----Combine tree-boosting and Gaussian process model-----
# Create Gaussian process model
gp_model <- GPModel(gp_coords = coords, cov_function = "exponential",
                  likelihood = "gaussian")
# Train model
bst <- gpboost(data = X, label = y, gp_model = gp_model, nrounds = 8,
              learning_rate = 0.1, max_depth = 6, min_data_in_leaf = 5,
              verbose = 0)
# Estimated random effects model
summary(gp_model)
# Make predictions
pred <- predict(bst, data = X_test, gp_coords_pred = coords_test,
               predict_var = TRUE, pred_latent = TRUE)
pred$random_effect_mean # Predicted latent random effects mean
pred$random_effect_cov # Predicted random effects variances
pred$fixed_effect # Predicted fixed effects from tree ensemble
# Predict response variable
pred_resp <- predict(bst, data = X_test, gp_coords_pred = coords_test,
                   predict_var = TRUE, pred_latent = FALSE)
pred_resp$response_mean # Predicted response mean

```

Description

Simulated example data for the GPBoost package This data set includes the following fields:

- `y`: response variable
- `X`: a matrix with covariate information
- `group_data`: a matrix with categorical grouping variables
- `coords`: a matrix with spatial coordinates
- `X_test`: a matrix with covariate information for predictions
- `group_data_test`: a matrix with categorical grouping variables for predictions
- `coords_test`: a matrix with spatial coordinates for predictions

Usage

```
data(GPBoost_data)
```

GPModel	<i>Create a GPModel object</i>
---------	--------------------------------

Description

Create a GPModel which contains a Gaussian process and / or mixed effects model with grouped random effects

Usage

```
GPModel(likelihood = "gaussian", group_data = NULL,
        group_rand_coef_data = NULL, ind_effect_group_rand_coef = NULL,
        drop_intercept_group_rand_effect = NULL, gp_coords = NULL,
        gp_rand_coef_data = NULL, cov_function = "exponential",
        cov_fct_shape = 0.5, gp_approx = "none", cov_fct_taper_range = 1,
        cov_fct_taper_shape = 0, num_neighbors = 20L,
        vecchia_ordering = "random", num_ind_points = 500L,
        matrix_inversion_method = "cholesky", seed = 0L, cluster_ids = NULL,
        free_raw_data = FALSE, vecchia_approx = NULL, vecchia_pred_type = NULL,
        num_neighbors_pred = NULL)
```

Arguments

<code>likelihood</code>	A string specifying the likelihood function (distribution) of the response variable. Available options: <ul style="list-style-type: none"> • "gaussian" • "bernoulli_probit": binary data with Bernoulli likelihood and a probit link function • "bernoulli_logit": binary data with Bernoulli likelihood and a logit link function
-------------------------	--

	<ul style="list-style-type: none"> • "gamma" • "poisson"
group_data	A vector or matrix whose columns are categorical grouping variables. The elements being group levels defining grouped random effects. The elements of 'group_data' can be integer, double, or character. The number of columns corresponds to the number of grouped (intercept) random effects
group_rand_coef_data	A vector or matrix with numeric covariate data for grouped random coefficients
ind_effect_group_rand_coef	A vector with integer indices that indicate the corresponding categorical grouping variable (=columns) in 'group_data' for every covariate in 'group_rand_coef_data'. Counting starts at 1. The length of this index vector must equal the number of covariates in 'group_rand_coef_data'. For instance, c(1,1,2) means that the first two covariates (=first two columns) in 'group_rand_coef_data' have random coefficients corresponding to the first categorical grouping variable (=first column) in 'group_data', and the third covariate (=third column) in 'group_rand_coef_data' has a random coefficient corresponding to the second grouping variable (=second column) in 'group_data'
drop_intercept_group_rand_effect	A vector of type logical (boolean). Indicates whether intercept random effects are dropped (only for random coefficients). If drop_intercept_group_rand_effect[k] is TRUE, the intercept random effect number k is dropped / not included. Only random effects with random slopes can be dropped.
gp_coords	A matrix with numeric coordinates (= inputs / features) for defining Gaussian processes
gp_rand_coef_data	A vector or matrix with numeric covariate data for Gaussian process random coefficients
cov_function	A string specifying the covariance function for the Gaussian process. Available options: "exponential", "gaussian", "matern", "powered_exponential", "wendland" <ul style="list-style-type: none"> • For "exponential", "gaussian", and "powered_exponential", we use parametrization of Diggle and Ribeiro (2007) • For "matern", we use the parametrization of Rasmussen and Williams (2006) • For "wendland", we use the parametrization of Bevilacqua et al. (2019, AOS)
cov_fct_shape	A numeric specifying the shape parameter of the covariance function (=smoothness parameter for Matern covariance) This parameter is irrelevant for some covariance functions such as the exponential or Gaussian
gp_approx	A string specifying the large data approximation for Gaussian processes. Available options: <ul style="list-style-type: none"> • "none": No approximation • "vecchia": A Vecchia approximation; see Sigrist (2022, JMLR for more details)

- "tapering": The covariance function is multiplied by a compactly supported Wendland correlation function

`cov_fct_taper_range` A numeric specifying the range parameter of the Wendland covariance function and Wendland correlation taper function. We follow the notation of Bevilacqua et al. (2019, AOS)

`cov_fct_taper_shape` A numeric specifying the shape (=smoothness) parameter of the Wendland covariance function and Wendland correlation taper function. We follow the notation of Bevilacqua et al. (2019, AOS)

`num_neighbors` An integer specifying the number of neighbors for the Vecchia approximation. Note: for prediction, the number of neighbors can be set through the 'num_neighbors_pred' parameter in the 'set_prediction_data' function. By default, `num_neighbors_pred = 2 * num_neighbors`. Further, the type of Vecchia approximation used for making predictions is set through the 'vecchia_pred_type' parameter in the 'set_prediction_data' function

`vecchia_ordering` A string specifying the ordering used in the Vecchia approximation. Available options:

- "none": the default ordering in the data is used
- "random": a random ordering

`num_ind_points` An integer specifying the number of inducing points / knots for, e.g., a predictive process approximation

`matrix_inversion_method` A string specifying the method used for inverting covariance matrices. Available options:

- "cholesky": Cholesky factorization
- "iterative": iterative methods. Only supported for non-Gaussian likelihoods with a Vecchia-Laplace approximation. This a combination of conjugate gradient, Lanczos algorithm, and other methods

`seed` An integer specifying the seed used for model creation (e.g., random ordering in Vecchia approximation)

`cluster_ids` A vector with elements indicating independent realizations of random effects / Gaussian processes (same values = same process realization). The elements of 'cluster_ids' can be integer, double, or character.

`free_raw_data` A boolean. If TRUE, the data (groups, coordinates, covariate data for random coefficients) is freed in R after initialization

`vecchia_approx` Discontinued. Use the argument `gp_approx` instead

`vecchia_pred_type` A string specifying the type of Vecchia approximation used for making predictions. This is discontinued here. Use the function 'set_prediction_data' to specify this

`num_neighbors_pred` an integer specifying the number of neighbors for making predictions. This is discontinued here. Use the function 'set_prediction_data' to specify this

Value

A GPMoDel containing contains a Gaussian process and / or mixed effects model with grouped random effects

Author(s)

Fabio Sigrist

Examples

```
# See https://github.com/fabsig/GPBoost/tree/master/R-package for more examples

data(GPBoost_data, package = "gpboost")

#-----Grouped random effects model: single-level random effect-----
gp_model <- GPMoDel(group_data = group_data[,1], likelihood="gaussian")

#-----Gaussian process model-----
gp_model <- GPMoDel(gp_coords = coords, cov_function = "exponential",
                  likelihood="gaussian")

#-----Combine Gaussian process with grouped random effects-----
gp_model <- GPMoDel(group_data = group_data,
                  gp_coords = coords, cov_function = "exponential",
                  likelihood="gaussian")
```

GPMoDel_shared_params *Documentation for parameters shared by GPMoDel, gpb.cv, and gpboost*

Description

Documentation for parameters shared by GPMoDel, gpb.cv, and gpboost

Arguments

likelihood	<p>A string specifying the likelihood function (distribution) of the response variable. Available options:</p> <ul style="list-style-type: none"> • "gaussian" • "bernoulli_probit": binary data with Bernoulli likelihood and a probit link function • "bernoulli_logit": binary data with Bernoulli likelihood and a logit link function • "gamma" • "poisson"
------------	---

group_data	A vector or matrix whose columns are categorical grouping variables. The elements being group levels defining grouped random effects. The elements of 'group_data' can be integer, double, or character. The number of columns corresponds to the number of grouped (intercept) random effects
group_rand_coef_data	A vector or matrix with numeric covariate data for grouped random coefficients
ind_effect_group_rand_coef	A vector with integer indices that indicate the corresponding categorical grouping variable (=columns) in 'group_data' for every covariate in 'group_rand_coef_data'. Counting starts at 1. The length of this index vector must equal the number of covariates in 'group_rand_coef_data'. For instance, c(1,1,2) means that the first two covariates (=first two columns) in 'group_rand_coef_data' have random coefficients corresponding to the first categorical grouping variable (=first column) in 'group_data', and the third covariate (=third column) in 'group_rand_coef_data' has a random coefficient corresponding to the second grouping variable (=second column) in 'group_data'
drop_intercept_group_rand_effect	A vector of type logical (boolean). Indicates whether intercept random effects are dropped (only for random coefficients). If drop_intercept_group_rand_effect[k] is TRUE, the intercept random effect number k is dropped / not included. Only random effects with random slopes can be dropped.
gp_coords	A matrix with numeric coordinates (= inputs / features) for defining Gaussian processes
gp_rand_coef_data	A vector or matrix with numeric covariate data for Gaussian process random coefficients
cov_function	A string specifying the covariance function for the Gaussian process. Available options: "exponential", "gaussian", "matern", "powered_exponential", "wendland" <ul style="list-style-type: none"> • For "exponential", "gaussian", and "powered_exponential", we use parametrization of Diggle and Ribeiro (2007) • For "matern", we use the parametrization of Rasmussen and Williams (2006) • For "wendland", we use the parametrization of Bevilacqua et al. (2019, AOS)
cov_fct_shape	A numeric specifying the shape parameter of the covariance function (=smoothness parameter for Matern covariance) This parameter is irrelevant for some covariance functions such as the exponential or Gaussian
gp_approx	A string specifying the large data approximation for Gaussian processes. Available options: <ul style="list-style-type: none"> • "none": No approximation • "vecchia": A Vecchia approximation; see Sigrist (2022, JMLR for more details) • "tapering": The covariance function is multiplied by a compactly supported Wendland correlation function

cov_fct_taper_range	A numeric specifying the range parameter of the Wendland covariance function and Wendland correlation taper function. We follow the notation of Bevilacqua et al. (2019, AOS)
cov_fct_taper_shape	A numeric specifying the shape (=smoothness) parameter of the Wendland covariance function and Wendland correlation taper function. We follow the notation of Bevilacqua et al. (2019, AOS)
num_neighbors	An integer specifying the number of neighbors for the Vecchia approximation. Note: for prediction, the number of neighbors can be set through the 'num_neighbors_pred' parameter in the 'set_prediction_data' function. By default, num_neighbors_pred = 2 * num_neighbors. Further, the type of Vecchia approximation used for making predictions is set through the 'vecchia_pred_type' parameter in the 'set_prediction_data' function
vecchia_ordering	A string specifying the ordering used in the Vecchia approximation. Available options: <ul style="list-style-type: none"> • "none": the default ordering in the data is used • "random": a random ordering
num_ind_points	An integer specifying the number of inducing points / knots for, e.g., a predictive process approximation
matrix_inversion_method	A string specifying the method used for inverting covariance matrices. Available options: <ul style="list-style-type: none"> • "cholesky": Cholesky factorization • "iterative": iterative methods. Only supported for non-Gaussian likelihoods with a Vecchia-Laplace approximation. This a combination of conjugate gradient, Lanczos algorithm, and other methods
seed	An integer specifying the seed used for model creation (e.g., random ordering in Vecchia approximation)
vecchia_pred_type	A string specifying the type of Vecchia approximation used for making predictions. Default value if vecchia_pred_type = NULL: "order_obs_first_cond_obs_only". Available options: <ul style="list-style-type: none"> • "order_obs_first_cond_obs_only": Vecchia approximation for the observable process and observed training data is ordered first and the neighbors are only observed training data points • "order_obs_first_cond_all": Vecchia approximation for the observable process and observed training data is ordered first and the neighbors are selected among all points (training + prediction) • "latent_order_obs_first_cond_obs_only": Vecchia approximation for the latent process and observed data is ordered first and neighbors are only observed points • "latent_order_obs_first_cond_all": Vecchia approximation for the latent process and observed data is ordered first and neighbors are selected among all points

- "order_pred_first": Vecchia approximation for the observable process and prediction data is ordered first for making predictions. This option is only available for Gaussian likelihoods

num_neighbors_pred	an integer specifying the number of neighbors for the Vecchia approximation for making predictions. Default value if NULL: $\text{num_neighbors_pred} = 2 * \text{num_neighbors}$
cg_delta_conv_pred	a numeric specifying the tolerance level for L2 norm of residuals for checking convergence in conjugate gradient algorithms when being used for prediction Default value if NULL: 1e-3
nsim_var_pred	an integer specifying the number of samples when simulation is used for calculating predictive variances Default value if NULL: 1000
rank_pred_approx_matrix_lanczos	an integer specifying the rank of the matrix for approximating predictive covariances obtained using the Lanczos algorithm Default value if NULL: 1000
cluster_ids	A vector with elements indicating independent realizations of random effects / Gaussian processes (same values = same process realization). The elements of 'cluster_ids' can be integer, double, or character.
free_raw_data	A boolean. If TRUE, the data (groups, coordinates, covariate data for random coefficients) is freed in R after initialization
y	A vector with response variable data
X	A matrix with numeric covariate data for the fixed effects linear regression term (if there is one)
params	A list with parameters for the estimation / optimization <ul style="list-style-type: none"> • optimizer_cov: string (default = "gradient_descent"). Optimizer used for estimating covariance parameters. Options: "gradient_descent", "fisher_scoring", "nelder_mead", "bfgs", "adam". If there are additional auxiliary parameters for non-Gaussian likelihoods, 'optimizer_cov' is also used for those • optimizer_coef: string (default = "wls" for Gaussian likelihoods and "gradient_descent" for other likelihoods). Optimizer used for estimating linear regression coefficients, if there are any (for the GPBoost algorithm there are usually none). Options: "gradient_descent", "wls", "nelder_mead", "bfgs", "adam". Gradient descent steps are done simultaneously with gradient descent steps for the covariance parameters. "wls" refers to doing coordinate descent for the regression coefficients using weighted least squares. If 'optimizer_cov' is set to "nelder_mead", "bfgs", or "adam", 'optimizer_coef' is automatically also set to the same value. • maxit: integer (default = 1000). Maximal number of iterations for optimization algorithm • delta_rel_conv: numeric (default = 1E-6 except for "nelder_mead" for which the default is 1E-8). Convergence tolerance. The algorithm stops if the relative change in either the (approximate) log-likelihood or the parameters is below this value. For "bfgs" and "adam", the L2 norm of the gradient is used instead of the relative change in the log-likelihood. If < 0, internal default values are used

- `convergence_criterion`: string (default = "relative_change_in_log_likelihood"). The convergence criterion used for terminating the optimization algorithm. Options: "relative_change_in_log_likelihood" or "relative_change_in_parameters"
- `init_coef`: vector with numeric elements (default = NULL). Initial values for the regression coefficients (if there are any, can be NULL)
- `init_cov_pars`: vector with numeric elements (default = NULL). Initial values for covariance parameters of Gaussian process and random effects (can be NULL)
- `lr_coef`: numeric (default = 0.1). Learning rate for fixed effect regression coefficients if gradient descent is used
- `lr_cov`: numeric (default = 0.1 for "gradient_descent" and 1. for "fisher_scoring"). Initial learning rate for covariance parameters. If `lr_cov < 0`, internal default values are used. If there are additional auxiliary parameters for non-Gaussian likelihoods, 'lr_cov' is also used for those
- `use_nesterov_acc`: boolean (default = TRUE). If TRUE Nesterov acceleration is used. This is used only for gradient descent
- `acc_rate_coef`: numeric (default = 0.5). Acceleration rate for regression coefficients (if there are any) for Nesterov acceleration
- `acc_rate_cov`: numeric (default = 0.5). Acceleration rate for covariance parameters for Nesterov acceleration
- `momentum_offset`: integer (Default = 2). Number of iterations for which no momentum is applied in the beginning.
- `trace`: boolean (default = FALSE). If TRUE, information on the progress of the parameter optimization is printed
- `std_dev`: boolean (default = TRUE). If TRUE, approximate standard deviations are calculated for the covariance and linear regression parameters (= square root of diagonal of the inverse Fisher information for Gaussian likelihoods and square root of diagonal of a numerically approximated inverse Hessian for non-Gaussian likelihoods)
- `init_aux_pars`: vector with numeric elements (default = NULL). Initial values for additional parameters for non-Gaussian likelihoods (e.g., shape parameter of gamma likelihood)
- `estimate_aux_pars`: boolean (default = TRUE). If TRUE, additional parameters for non-Gaussian likelihoods are also estimated (e.g., shape parameter of gamma likelihood)
- `cg_max_num_it`: integer (default = 1000). Maximal number of iterations for conjugate gradient algorithms
- `cg_max_num_it_tridiag`: integer (default = 1000). Maximal number of iterations for conjugate gradient algorithm when being run as Lanczos algorithm for tridiagonalization
- `cg_delta_conv`: numeric (default = 1E-2). Tolerance level for L2 norm of residuals for checking convergence in conjugate gradient algorithm when being used for parameter estimation
- `num_rand_vec_trace`: integer (default = 50). Number of random vectors (e.g., Rademacher) for stochastic approximation of the trace of a matrix

- reuse_rand_vec_trace: boolean (default = TRUE). If true, random vectors (e.g., Rademacher) for stochastic approximation of the trace of a matrix are sampled only once at the beginning of Newton's method for finding the mode in the Laplace approximation and are then reused in later trace approximations. Otherwise they are sampled every time a trace is calculated
- seed_rand_vec_trace: integer (default = 1). Seed number to generate random vectors (e.g., Rademacher)
- piv_chol_rank: integer (default = 50). Rank of the pivoted Cholesky decomposition used as preconditioner in conjugate gradient algorithms
- cg_preconditioner_type: string (default = "Sigma_inv_plus_BtWB" for non-Gaussian likelihoods and a Vecchia-Laplace approximation). Type of preconditioner used for conjugate gradient algorithms. Options for non-Gaussian likelihoods and a Vecchia-Laplace approximation:
 - "piv_chol_on_Sigma": $(Lk * Lk^T + W^{-1})$ as preconditioner for inverting $(B^{-1} * D * B^{-T} + W^{-1})$, where Lk is a low-rank pivoted Cholesky approximation for Σ and $B^{-1} * D * B^{-T} \approx \Sigma$
 - "Sigma_inv_plus_BtWB": $(B^T * (D^{-1} + W) * B)$ as preconditioner for inverting $(B^T * D^{-1} * B + W)$, where $B^T * D^{-1} * B \approx \Sigma^{-1}$

fixed_effects	A vector of optional external fixed effects (length = number of data points)
group_data_pred	A vector or matrix with elements being group levels for which predictions are made (if there are grouped random effects in the GPModel)
group_rand_coef_data_pred	A vector or matrix with covariate data for grouped random coefficients (if there are some in the GPModel)
gp_coords_pred	A matrix with prediction coordinates (=features) for Gaussian process (if there is a GP in the GPModel)
gp_rand_coef_data_pred	A vector or matrix with covariate data for Gaussian process random coefficients (if there are some in the GPModel)
cluster_ids_pred	A vector with elements indicating the realizations of random effects / Gaussian processes for which predictions are made (set to NULL if you have not specified this when creating the GPModel)
X_pred	A matrix with prediction covariate data for the fixed effects linear regression term (if there is one in the GPModel)
predict_cov_mat	A boolean. If TRUE, the (posterior) predictive covariance is calculated in addition to the (posterior) predictive mean
predict_var	A boolean. If TRUE, the (posterior) predictive variances are calculated
vecchia_approx	Discontinued. Use the argument gp_approx instead

group_data	<i>Example data for the GPBoost package</i>
------------	---

Description

A matrix with categorical grouping variables for the example data of the GPBoost package

Usage

```
data(GPBoost_data)
```

group_data_test	<i>Example data for the GPBoost package</i>
-----------------	---

Description

A matrix with categorical grouping variables for predictions for the example data of the GPBoost package

Usage

```
data(GPBoost_data)
```

loadGPModel	<i>Load a GPModel from a file</i>
-------------	-----------------------------------

Description

Load a GPModel from a file

Usage

```
loadGPModel(filename)
```

Arguments

filename	filename for loading
----------	----------------------

Value

A GPModel

Author(s)

Fabio Sigrist

Examples

```

data(GPBoost_data, package = "gpboost")
# Add intercept column
X1 <- cbind(rep(1,dim(X)[1]),X)
X_test1 <- cbind(rep(1,dim(X_test)[1]),X_test)

gp_model <- fitGPModel(group_data = group_data[,1], y = y, X = X1, likelihood="gaussian")
pred <- predict(gp_model, group_data_pred = group_data_test[,1],
               X_pred = X_test1, predict_var = TRUE)
# Save model to file
filename <- tempfile(fileext = ".json")
saveGPModel(gp_model,filename = filename)
# Load from file and make predictions again
gp_model_loaded <- loadGPModel(filename = filename)
pred_loaded <- predict(gp_model_loaded, group_data_pred = group_data_test[,1],
                     X_pred = X_test1, predict_var = TRUE)

# Check equality
pred$mu - pred_loaded$mu
pred$var - pred_loaded$var

```

neg_log_likelihood *Evaluate the negative log-likelihood*

Description

Evaluate the negative log-likelihood. If there is a linear fixed effects predictor term, this needs to be calculated "manually" prior to calling this function (see example below)

Usage

```
neg_log_likelihood(gp_model, cov_pars, y, fixed_effects = NULL,
                 aux_pars = NULL)
```

Arguments

gp_model	A GPModel
cov_pars	A vector with numeric elements. Covariance parameters of Gaussian process and random effects
y	A vector with response variable data
fixed_effects	A vector of optional external fixed effects (length = number of data points)
aux_pars	A vector with numeric elements. Additional parameters for non-Gaussian likelihoods (e.g., shape parameter of gamma likelihood)

Author(s)

Fabio Sigrist

Examples

```
data(GPBoost_data, package = "gpboost")
gp_model <- GPModel(group_data = group_data, likelihood="gaussian")
X1 <- cbind(rep(1,dim(X)[1]), X)
coef <- c(0.1, 0.1, 0.1)
fixed_effects <- as.numeric(X1 %**% coef)
neg_log_likelihood(gp_model, y = y, cov_pars = c(0.1,1,1),
                  fixed_effects = fixed_effects)
```

neg_log_likelihood.GPModel

Evaluate the negative log-likelihood

Description

Evaluate the negative log-likelihood. If there is a linear fixed effects predictor term, this needs to be calculated "manually" prior to calling this function (see example below)

Usage

```
## S3 method for class 'GPModel'
neg_log_likelihood(gp_model, cov_pars, y,
                  fixed_effects = NULL, aux_pars = NULL)
```

Arguments

gp_model	A GPModel
cov_pars	A vector with numeric elements. Covariance parameters of Gaussian process and random effects
y	A vector with response variable data
fixed_effects	A vector of optional external fixed effects (length = number of data points)
aux_pars	A vector with numeric elements. Additional parameters for non-Gaussian likelihoods (e.g., shape parameter of gamma likelihood)

Value

A GPModel

Author(s)

Fabio Sigrist

Examples

```
data(GPBoost_data, package = "gpboost")
gp_model <- GPModel(group_data = group_data, likelihood="gaussian")
X1 <- cbind(rep(1,dim(X)[1]), X)
coef <- c(0.1, 0.1, 0.1)
fixed_effects <- as.numeric(X1 %*% coef)
neg_log_likelihood(gp_model, y = y, cov_pars = c(0.1,1,1),
                  fixed_effects = fixed_effects)
```

predict.gpb.Booster *Prediction function for gpb.Booster objects*

Description

Prediction function for gpb.Booster objects

Usage

```
## S3 method for class 'gpb.Booster'
predict(object, data, start_iteration = NULL,
        num_iteration = NULL, pred_latent = FALSE, predleaf = FALSE,
        predcontrib = FALSE, header = FALSE, reshape = FALSE,
        group_data_pred = NULL, group_rand_coef_data_pred = NULL,
        gp_coords_pred = NULL, gp_rand_coef_data_pred = NULL,
        cluster_ids_pred = NULL, predict_cov_mat = FALSE, predict_var = FALSE,
        cov_pars = NULL, ignore_gp_model = FALSE, rawscore = NULL,
        vecchia_pred_type = NULL, num_neighbors_pred = NULL, ...)
```

Arguments

object	Object of class gpb.Booster
data	a matrix object, a dgCMatrix object or a character representing a filename
start_iteration	int or NULL, optional (default=NULL) Start index of the iteration to predict. If NULL or <= 0, starts from the first iteration.
num_iteration	int or NULL, optional (default=NULL) Limit number of iterations in the prediction. If NULL, if the best iteration exists and start_iteration is NULL or <= 0, the best iteration is used; otherwise, all iterations from start_iteration are used. If <= 0, all iterations from start_iteration are used (no limits).
pred_latent	If TRUE latent variables, both fixed effects (tree-ensemble) and random effects (gp_model) are predicted. Otherwise, the response variable (label) is predicted. Depending on how the argument 'pred_latent' is set, different values are returned from this function; see the 'Value' section for more details. If there is no gp_model, this argument corresponds to 'raw_score' in LightGBM.

predleaf	whether predict leaf index instead.
predcontrib	return per-feature contributions for each record.
header	only used for prediction for text file. True if text file has header
reshape	whether to reshape the vector of predictions to a matrix form when there are several prediction outputs per case.
group_data_pred	A vector or matrix with elements being group levels for which predictions are made (if there are grouped random effects in the GPMoDel)
group_rand_coef_data_pred	A vector or matrix with covariate data for grouped random coefficients (if there are some in the GPMoDel)
gp_coords_pred	A matrix with prediction coordinates (=features) for Gaussian process (if there is a GP in the GPMoDel)
gp_rand_coef_data_pred	A vector or matrix with covariate data for Gaussian process random coefficients (if there are some in the GPMoDel)
cluster_ids_pred	A vector with elements indicating the realizations of random effects / Gaussian processes for which predictions are made (set to NULL if you have not specified this when creating the GPMoDel)
predict_cov_mat	A boolean. If TRUE, the (posterior) predictive covariance is calculated in addition to the (posterior) predictive mean
predict_var	A boolean. If TRUE, the (posterior) predictive variances are calculated
cov_pars	A vector containing covariance parameters which are used if the gp_model has not been trained or if predictions should be made for other parameters than the trained ones
ignore_gp_model	A boolean. If TRUE, predictions are only made for the tree ensemble part and the gp_model is ignored
rawscore	This is discontinued. Use the renamed equivalent argument pred_latent instead
vecchia_pred_type	A string specifying the type of Vecchia approximation used for making predictions. This is discontinued here. Use the function 'set_prediction_data' to specify this
num_neighbors_pred	an integer specifying the number of neighbors for making predictions. This is discontinued here. Use the function 'set_prediction_data' to specify this
...	Additional named arguments passed to the predict() method of the gpb.Booster object passed to object.

Value

either a list with vectors or a single vector / matrix depending on whether there is a `gp_model` or not. If there is a `gp_model`, the result dict contains the following entries. 1. If `pred_latent` is TRUE, the dict contains the following 3 entries: - `result["fixed_effect"]` are the predictions from the tree-ensemble. - `result["random_effect_mean"]` are the predicted means of the `gp_model`. - `result["random_effect_cov"]` are the predicted covariances or variances of the `gp_model` (only if `'predict_var'` or `'predict_cov'` is TRUE). 2. If `pred_latent` is FALSE, the dict contains the following 2 entries: - `result["response_mean"]` are the predicted means of the response variable (Label) taking into account both the fixed effects (tree-ensemble) and the random effects (`gp_model`) - `result["response_var"]` are the predicted covariances or variances of the response variable (only if `'predict_var'` or `'predict_cov'` is TRUE). If there is no `gp_model` or `predcontrib` or `ignore_gp_model` are TRUE, the result contains predictions from the tree-boosters only.

Author(s)

Fabio Sigrist, authors of the LightGBM R package

Examples

```
# See https://github.com/fabsig/GPBoost/tree/master/R-package for more examples

library(gpboost)
data(GPBoost_data, package = "gpboost")

#-----Combine tree-boosting and grouped random effects model-----
# Create random effects model
gp_model <- GPModel(group_data = group_data[,1], likelihood = "gaussian")
# The default optimizer for covariance parameters (hyperparameters) is
# Nesterov-accelerated gradient descent.
# This can be changed to, e.g., Nelder-Mead as follows:
# re_params <- list(optimizer_cov = "nelder_mead")
# gp_model$set_optim_params(params=re_params)
# Use trace = TRUE to monitor convergence:
# re_params <- list(trace = TRUE)
# gp_model$set_optim_params(params=re_params)

# Train model
bst <- gpboost(data = X, label = y, gp_model = gp_model, nrounds = 16,
               learning_rate = 0.05, max_depth = 6, min_data_in_leaf = 5,
               verbose = 0)
# Estimated random effects model
summary(gp_model)

# Make predictions
# Predict latent variables
pred <- predict(bst, data = X_test, group_data_pred = group_data_test[,1],
               predict_var = TRUE, pred_latent = TRUE)
pred$random_effect_mean # Predicted latent random effects mean
pred$random_effect_cov # Predicted random effects variances
```



```

pred$fixed_effect # Predicted fixed effects from tree ensemble
# Predict response variable
pred_resp <- predict(bst, data = X_test, group_data_pred = group_data_test[,1],
                    predict_var = TRUE, pred_latent = FALSE)
pred_resp$response_mean # Predicted response mean
# For Gaussian data: pred$random_effect_mean + pred$fixed_effect = pred_resp$response_mean
pred$random_effect_mean + pred$fixed_effect - pred_resp$response_mean

#-----Combine tree-boosting and Gaussian process model-----
# Create Gaussian process model
gp_model <- GPModel(gp_coords = coords, cov_function = "exponential",
                   likelihood = "gaussian")
# Train model
bst <- gpboost(data = X, label = y, gp_model = gp_model, nrounds = 8,
              learning_rate = 0.1, max_depth = 6, min_data_in_leaf = 5,
              verbose = 0)
# Estimated random effects model
summary(gp_model)
# Make predictions
pred <- predict(bst, data = X_test, gp_coords_pred = coords_test,
               predict_var = TRUE, pred_latent = TRUE)
pred$random_effect_mean # Predicted latent random effects mean
pred$random_effect_cov # Predicted random effects variances
pred$fixed_effect # Predicted fixed effects from tree ensemble
# Predict response variable
pred_resp <- predict(bst, data = X_test, gp_coords_pred = coords_test,
                   predict_var = TRUE, pred_latent = FALSE)
pred_resp$response_mean # Predicted response mean

```

predict.GPModel

Make predictions for a GPModel

Description

Make predictions for a GPModel

Usage

```

## S3 method for class 'GPModel'
predict(object, y = NULL, group_data_pred = NULL,
        group_rand_coef_data_pred = NULL, gp_coords_pred = NULL,
        gp_rand_coef_data_pred = NULL, cluster_ids_pred = NULL,
        predict_cov_mat = FALSE, predict_var = FALSE, cov_pars = NULL,
        X_pred = NULL, use_saved_data = FALSE, predict_response = TRUE,
        fixed_effects = NULL, fixed_effects_pred = NULL,
        vecchia_pred_type = NULL, num_neighbors_pred = NULL, ...)

```

Arguments

object	a GPModel
y	Observed data (can be NULL, e.g. when the model has been estimated already and the same data is used for making predictions)
group_data_pred	A vector or matrix with elements being group levels for which predictions are made (if there are grouped random effects in the GPModel)
group_rand_coef_data_pred	A vector or matrix with covariate data for grouped random coefficients (if there are some in the GPModel)
gp_coords_pred	A matrix with prediction coordinates (=features) for Gaussian process (if there is a GP in the GPModel)
gp_rand_coef_data_pred	A vector or matrix with covariate data for Gaussian process random coefficients (if there are some in the GPModel)
cluster_ids_pred	A vector with elements indicating the realizations of random effects / Gaussian processes for which predictions are made (set to NULL if you have not specified this when creating the GPModel)
predict_cov_mat	A boolean. If TRUE, the (posterior) predictive covariance is calculated in addition to the (posterior) predictive mean
predict_var	A boolean. If TRUE, the (posterior) predictive variances are calculated
cov_pars	A vector containing covariance parameters which are used if the GPModel has not been trained or if predictions should be made for other parameters than the trained ones
X_pred	A matrix with prediction covariate data for the fixed effects linear regression term (if there is one in the GPModel)
use_saved_data	A boolean. If TRUE, predictions are done using a priory set data via the function '\$set_prediction_data' (this option is not used by users directly)
predict_response	A boolean. If TRUE, the response variable (label) is predicted, otherwise the latent random effects
fixed_effects	(usually not used) A numeric vector with additional external training data fixed effects. The length of this vector needs to equal the number of training data points. Used only for non-Gaussian data. For Gaussian data, this is ignored
fixed_effects_pred	(usually not used) A numeric vector with additional external prediction fixed effects. The length of this vector needs to equal the number of prediction points. Used only for non-Gaussian data. For Gaussian data, this is ignored
vecchia_pred_type	A string specifying the type of Vecchia approximation used for making predictions. This is discontinued here. Use the function 'set_prediction_data' to specify this

```

num_neighbors_pred
    an integer specifying the number of neighbors for making predictions. This is
    discontinued here. Use the function 'set_prediction_data' to specify this
...
    (not used, ignore this, simply here that there is no CRAN warning)

```

Value

Predictions from a GPModel. A list with three entries is returned:

- "mu" (first entry): predictive (=posterior) mean. For (generalized) linear mixed effects models, i.e., models with a linear regression term, this consists of the sum of fixed effects and random effects predictions
- "cov" (second entry): predictive (=posterior) covariance matrix. This is NULL if 'predict_cov_mat=FALSE'
- "var" (third entry) : predictive (=posterior) variances. This is NULL if 'predict_var=FALSE'

Author(s)

Fabio Sigrist

Examples

```

# See https://github.com/fabsig/GPBoost/tree/master/R-package for more examples

data(GPBoost_data, package = "gpboost")
# Add intercept column
X1 <- cbind(rep(1,dim(X)[1]),X)
X_test1 <- cbind(rep(1,dim(X_test)[1]),X_test)

#-----Grouped random effects model: single-level random effect-----
gp_model <- fitGPModel(group_data = group_data[,1], y = y, X = X1,
                      likelihood="gaussian", params = list(std_dev = TRUE))
summary(gp_model)
# Make predictions
pred <- predict(gp_model, group_data_pred = group_data_test[,1],
              X_pred = X_test1, predict_var = TRUE)
pred$mu # Predicted mean
pred$var # Predicted variances
# Also predict covariance matrix
pred <- predict(gp_model, group_data_pred = group_data_test[,1],
              X_pred = X_test1, predict_cov_mat = TRUE)
pred$mu # Predicted mean
pred$cov # Predicted covariance

#-----Gaussian process model-----
gp_model <- fitGPModel(gp_coords = coords, cov_function = "exponential",
                      likelihood="gaussian", y = y, X = X1, params = list(std_dev = TRUE))
summary(gp_model)
# Make predictions
pred <- predict(gp_model, gp_coords_pred = coords_test,

```

```

      X_pred = X_test1, predict_cov_mat = TRUE)
pred$mu # Predicted (posterior) mean of GP
pred$cov # Predicted (posterior) covariance matrix of GP

```

```

predict_training_data_random_effects
      Predict ("estimate") training data random effects for a GPModel

```

Description

Predict ("estimate") training data random effects for a GPModel

Usage

```
predict_training_data_random_effects(gp_model, predict_var = FALSE)
```

Arguments

gp_model	A GPModel
predict_var	A boolean. If TRUE, the (posterior) predictive variances are calculated

Value

A GPModel

Author(s)

Fabio Sigrist

Examples

```

data(GPBoost_data, package = "gpboost")
# Add intercept column
X1 <- cbind(rep(1,dim(X)[1]),X)
X_test1 <- cbind(rep(1,dim(X_test)[1]),X_test)

gp_model <- fitGPModel(group_data = group_data[,1], y = y, X = X1, likelihood="gaussian")
all_training_data_random_effects <- predict_training_data_random_effects(gp_model)
first_occurences <- match(unique(group_data[,1]), group_data[,1])
unique_training_data_random_effects <- all_training_data_random_effects[first_occurences]
head(unique_training_data_random_effects)

```

```
predict_training_data_random_effects.GPModel  
  Predict ("estimate") training data random effects for a GPModel
```

Description

Predict ("estimate") training data random effects for a GPModel

Usage

```
## S3 method for class 'GPModel'  
predict_training_data_random_effects(gp_model,  
  predict_var = FALSE)
```

Arguments

gp_model	A GPModel
predict_var	A boolean. If TRUE, the (posterior) predictive variances are calculated

Value

A GPModel

Author(s)

Fabio Sigrist

Examples

```
data(GPBoost_data, package = "gpboost")  
# Add intercept column  
X1 <- cbind(rep(1,dim(X)[1]),X)  
X_test1 <- cbind(rep(1,dim(X_test)[1]),X_test)  
  
gp_model <- fitGPModel(group_data = group_data[,1], y = y, X = X1, likelihood="gaussian")  
all_training_data_random_effects <- predict_training_data_random_effects(gp_model)  
first_occurrences <- match(unique(group_data[,1]), group_data[,1])  
unique_training_data_random_effects <- all_training_data_random_effects[first_occurrences]  
head(unique_training_data_random_effects)
```

readRDS.gpb.Booster *readRDS for gpb.Booster models*

Description

Attempts to load a model stored in a .rds file, using [readRDS](#)

Usage

```
readRDS.gpb.Booster(file, refhook = NULL)
```

Arguments

`file` a connection or the name of the file where the R object is saved to or read from.
`refhook` a hook function for handling reference objects.

Value

`gpb.Booster`

Examples

```
library(gpboost)
data(agaricus.train, package = "gpboost")
train <- agaricus.train
dtrain <- gpb.Dataset(train$data, label = train$label)
data(agaricus.test, package = "gpboost")
test <- agaricus.test
dtest <- gpb.Dataset.create.valid(dtrain, test$data, label = test$label)
params <- list(objective = "regression", metric = "l2")
valids <- list(test = dtest)
model <- gpb.train(
  params = params
  , data = dtrain
  , nrounds = 10L
  , valids = valids
  , min_data = 1L
  , learning_rate = 1.0
  , early_stopping_rounds = 5L
)
model_file <- tempfile(fileext = ".rds")
saveRDS.gpb.Booster(model, model_file)
new_model <- readRDS.gpb.Booster(model_file)
```

saveGPModel	<i>Save a GPModel</i>
-------------	-----------------------

Description

Save a GPModel

Usage

```
saveGPModel(gp_model, filename)
```

Arguments

gp_model	a GPModel
filename	filename for saving

Value

A GPModel

Author(s)

Fabio Sigrist

Examples

```
data(GPBoost_data, package = "gpboost")
# Add intercept column
X1 <- cbind(rep(1,dim(X)[1]),X)
X_test1 <- cbind(rep(1,dim(X_test)[1]),X_test)

gp_model <- fitGPModel(group_data = group_data[,1], y = y, X = X1, likelihood="gaussian")
pred <- predict(gp_model, group_data_pred = group_data_test[,1],
               X_pred = X_test1, predict_var = TRUE)

# Save model to file
filename <- tempfile(fileext = ".json")
saveGPModel(gp_model,filename = filename)
# Load from file and make predictions again
gp_model_loaded <- loadGPModel(filename = filename)
pred_loaded <- predict(gp_model_loaded, group_data_pred = group_data_test[,1],
                     X_pred = X_test1, predict_var = TRUE)

# Check equality
pred$mu - pred_loaded$mu
pred$var - pred_loaded$var
```

saveRDS.gpb.Booster *saveRDS for gpb.Booster models*

Description

Attempts to save a model using RDS. Has an additional parameter (`raw`) which decides whether to save the raw model or not.

Usage

```
saveRDS.gpb.Booster(object, file, ascii = FALSE, version = NULL,
  compress = TRUE, refhook = NULL, raw = TRUE)
```

Arguments

<code>object</code>	R object to serialize.
<code>file</code>	a connection or the name of the file where the R object is saved to or read from.
<code>ascii</code>	a logical. If TRUE or NA, an ASCII representation is written; otherwise (default), a binary one is used. See the comments in the help for save.
<code>version</code>	the workspace format version to use. NULL specifies the current default version (2). Versions prior to 2 are not supported, so this will only be relevant when there are later versions.
<code>compress</code>	a logical specifying whether saving to a named file is to use "gzip" compression, or one of "gzip", "bzip2" or "xz" to indicate the type of compression to be used. Ignored if file is a connection.
<code>refhook</code>	a hook function for handling reference objects.
<code>raw</code>	whether to save the model in a raw variable or not, recommended to leave it to TRUE.

Value

NULL invisibly.

Examples

```
library(gpboost)
data(agaricus.train, package = "gpboost")
train <- agaricus.train
dtrain <- gpb.Dataset(train$data, label = train$label)
data(agaricus.test, package = "gpboost")
test <- agaricus.test
dtest <- gpb.Dataset.create.valid(dtrain, test$data, label = test$label)
params <- list(objective = "regression", metric = "l2")
valids <- list(test = dtest)
model <- gpb.train(
```



```

    params = params
    , data = dtrain
    , nrounds = 10L
    , valids = valids
    , min_data = 1L
    , learning_rate = 1.0
    , early_stopping_rounds = 5L
  )
  model_file <- tempfile(fileext = ".rds")
  saveRDS.gpb.Booster(model, model_file)

```

setinfo

Set information of an gpb.Dataset object

Description

Set one attribute of a gpb.Dataset

Usage

```

setinfo(dataset, ...)

## S3 method for class 'gpb.Dataset'
setinfo(dataset, name, info, ...)

```

Arguments

dataset	Object of class gpb.Dataset
...	other parameters
name	the name of the field to get
info	the specific field of information to set

Details

The name field can be one of the following:

- `label`: vector of labels to use as the target variable
- `weight`: to do a weight rescale
- `init_score`: initial score is the base prediction gboost will boost from
- `group`: used for learning-to-rank tasks. An integer vector describing how to group rows together as ordered results from the same set of candidate results to be ranked. For example, if you have a 100-document dataset with `group = c(10, 20, 40, 10, 10, 10)`, that means that you have 6 groups, where the first 10 records are in the first group, records 11-30 are in the second group, etc.

Value

the dataset you passed in
 the dataset you passed in

Examples

```
data(agaricus.train, package = "gpboost")
train <- agaricus.train
dtrain <- gpb.Dataset(train$data, label = train$label)
gpb.Dataset.construct(dtrain)

labels <- gpboost::getinfo(dtrain, "label")
gpboost::setinfo(dtrain, "label", 1 - labels)

labels2 <- gpboost::getinfo(dtrain, "label")
stopifnot(all.equal(labels2, 1 - labels))
```

 set_optim_params

Set parameters for estimation of the covariance parameters

Description

Set parameters for optimization of the covariance parameters of a GPModel

Usage

```
set_optim_params(gp_model, params = list())
```

Arguments

- | | |
|----------|--|
| gp_model | A GPModel |
| params | A list with parameters for the estimation / optimization <ul style="list-style-type: none"> • optimizer_cov: string (default = "gradient_descent"). Optimizer used for estimating covariance parameters. Options: "gradient_descent", "fisher_scoring", "nelder_mead", "bfgs", "adam". If there are additional auxiliary parameters for non-Gaussian likelihoods, 'optimizer_cov' is also used for those • optimizer_coef: string (default = "wls" for Gaussian likelihoods and "gradient_descent" for other likelihoods). Optimizer used for estimating linear regression coefficients, if there are any (for the GPBoost algorithm there are usually none). Options: "gradient_descent", "wls", "nelder_mead", "bfgs", "adam". Gradient descent steps are done simultaneously with gradient descent steps for the covariance parameters. "wls" refers to doing coordinate descent for the regression coefficients using weighted least squares. If 'optimizer_cov' is set to "nelder_mead", "bfgs", or "adam", 'optimizer_coef' is automatically also set to the same value. |

- `maxit`: integer (default = 1000). Maximal number of iterations for optimization algorithm
- `delta_rel_conv`: numeric (default = 1E-6 except for "nelder_mead" for which the default is 1E-8). Convergence tolerance. The algorithm stops if the relative change in either the (approximate) log-likelihood or the parameters is below this value. For "bfgs" and "adam", the L2 norm of the gradient is used instead of the relative change in the log-likelihood. If < 0, internal default values are used
- `convergence_criterion`: string (default = "relative_change_in_log_likelihood"). The convergence criterion used for terminating the optimization algorithm. Options: "relative_change_in_log_likelihood" or "relative_change_in_parameters"
- `init_coef`: vector with numeric elements (default = NULL). Initial values for the regression coefficients (if there are any, can be NULL)
- `init_cov_pars`: vector with numeric elements (default = NULL). Initial values for covariance parameters of Gaussian process and random effects (can be NULL)
- `lr_coef`: numeric (default = 0.1). Learning rate for fixed effect regression coefficients if gradient descent is used
- `lr_cov`: numeric (default = 0.1 for "gradient_descent" and 1. for "fisher_scoring"). Initial learning rate for covariance parameters. If `lr_cov` < 0, internal default values are used. If there are additional auxiliary parameters for non-Gaussian likelihoods, 'lr_cov' is also used for those
- `use_nesterov_acc`: boolean (default = TRUE). If TRUE Nesterov acceleration is used. This is used only for gradient descent
- `acc_rate_coef`: numeric (default = 0.5). Acceleration rate for regression coefficients (if there are any) for Nesterov acceleration
- `acc_rate_cov`: numeric (default = 0.5). Acceleration rate for covariance parameters for Nesterov acceleration
- `momentum_offset`: integer (Default = 2). Number of iterations for which no momentum is applied in the beginning.
- `trace`: boolean (default = FALSE). If TRUE, information on the progress of the parameter optimization is printed
- `std_dev`: boolean (default = TRUE). If TRUE, approximate standard deviations are calculated for the covariance and linear regression parameters (= square root of diagonal of the inverse Fisher information for Gaussian likelihoods and square root of diagonal of a numerically approximated inverse Hessian for non-Gaussian likelihoods)
- `init_aux_pars`: vector with numeric elements (default = NULL). Initial values for additional parameters for non-Gaussian likelihoods (e.g., shape parameter of gamma likelihood)
- `estimate_aux_pars`: boolean (default = TRUE). If TRUE, additional parameters for non-Gaussian likelihoods are also estimated (e.g., shape parameter of gamma likelihood)
- `cg_max_num_it`: integer (default = 1000). Maximal number of iterations for conjugate gradient algorithms

- `cg_max_num_it_tridiag`: integer (default = 1000). Maximal number of iterations for conjugate gradient algorithm when being run as Lanczos algorithm for tridiagonalization
- `cg_delta_conv`: numeric (default = 1E-2). Tolerance level for L2 norm of residuals for checking convergence in conjugate gradient algorithm when being used for parameter estimation
- `num_rand_vec_trace`: integer (default = 50). Number of random vectors (e.g., Rademacher) for stochastic approximation of the trace of a matrix
- `reuse_rand_vec_trace`: boolean (default = TRUE). If true, random vectors (e.g., Rademacher) for stochastic approximation of the trace of a matrix are sampled only once at the beginning of Newton's method for finding the mode in the Laplace approximation and are then reused in later trace approximations. Otherwise they are sampled every time a trace is calculated
- `seed_rand_vec_trace`: integer (default = 1). Seed number to generate random vectors (e.g., Rademacher)
- `piv_chol_rank`: integer (default = 50). Rank of the pivoted Cholesky decomposition used as preconditioner in conjugate gradient algorithms
- `cg_preconditioner_type`: string (default = "Sigma_inv_plus_BtWB" for non-Gaussian likelihoods and a Vecchia-Laplace approximation). Type of preconditioner used for conjugate gradient algorithms. Options for non-Gaussian likelihoods and a Vecchia-Laplace approximation:
 - "piv_chol_on_Sigma": $(L_k * L_k^T + W^{-1})$ as preconditioner for inverting $(B^{-1} * D * B^{-T} + W^{-1})$, where L_k is a low-rank pivoted Cholesky approximation for Σ and $B^{-1} * D * B^{-T} \approx \Sigma$
 - "Sigma_inv_plus_BtWB": $(B^T * (D^{-1} + W) * B)$ as preconditioner for inverting $(B^T * D^{-1} * B + W)$, where $B^T * D^{-1} * B \approx \Sigma^{-1}$

Author(s)

Fabio Sigrist

Examples

```
data(GPBoost_data, package = "gpboost")
gp_model <- GPModel(group_data = group_data, likelihood="gaussian")
set_optim_params(gp_model, params=list(optimizer_cov="nelder_mead"))
```

set_optim_params.GPModel

Set parameters for estimation of the covariance parameters

Description

Set parameters for optimization of the covariance parameters of a GPModel

Usage

```
## S3 method for class 'GPModel'
set_optim_params(gp_model, params = list())
```

Arguments

- | | |
|----------|---|
| gp_model | A GPModel |
| params | <p>A list with parameters for the estimation / optimization</p> <ul style="list-style-type: none"> • optimizer_cov: string (default = "gradient_descent"). Optimizer used for estimating covariance parameters. Options: "gradient_descent", "fisher_scoring", "nelder_mead", "bfgs", "adam". If there are additional auxiliary parameters for non-Gaussian likelihoods, 'optimizer_cov' is also used for those • optimizer_coef: string (default = "wls" for Gaussian likelihoods and "gradient_descent" for other likelihoods). Optimizer used for estimating linear regression coefficients, if there are any (for the GPBoost algorithm there are usually none). Options: "gradient_descent", "wls", "nelder_mead", "bfgs", "adam". Gradient descent steps are done simultaneously with gradient descent steps for the covariance parameters. "wls" refers to doing coordinate descent for the regression coefficients using weighted least squares. If 'optimizer_cov' is set to "nelder_mead", "bfgs", or "adam", 'optimizer_coef' is automatically also set to the same value. • maxit: integer (default = 1000). Maximal number of iterations for optimization algorithm • delta_rel_conv: numeric (default = 1E-6 except for "nelder_mead" for which the default is 1E-8). Convergence tolerance. The algorithm stops if the relative change in either the (approximate) log-likelihood or the parameters is below this value. For "bfgs" and "adam", the L2 norm of the gradient is used instead of the relative change in the log-likelihood. If < 0, internal default values are used • convergence_criterion: string (default = "relative_change_in_log_likelihood"). The convergence criterion used for terminating the optimization algorithm. Options: "relative_change_in_log_likelihood" or "relative_change_in_parameters" • init_coef: vector with numeric elements (default = NULL). Initial values for the regression coefficients (if there are any, can be NULL) • init_cov_pars: vector with numeric elements (default = NULL). Initial values for covariance parameters of Gaussian process and random effects (can be NULL) • lr_coef: numeric (default = 0.1). Learning rate for fixed effect regression coefficients if gradient descent is used • lr_cov: numeric (default = 0.1 for "gradient_descent" and 1. for "fisher_scoring"). Initial learning rate for covariance parameters. If lr_cov < 0, internal default values are used. If there are additional auxiliary parameters for non-Gaussian likelihoods, 'lr_cov' is also used for those |

- use_nesterov_acc: boolean (default = TRUE). If TRUE Nesterov acceleration is used. This is used only for gradient descent
- acc_rate_coef: numeric (default = 0.5). Acceleration rate for regression coefficients (if there are any) for Nesterov acceleration
- acc_rate_cov: numeric (default = 0.5). Acceleration rate for covariance parameters for Nesterov acceleration
- momentum_offset: integer (Default = 2). Number of iterations for which no momentum is applied in the beginning.
- trace: boolean (default = FALSE). If TRUE, information on the progress of the parameter optimization is printed
- std_dev: boolean (default = TRUE). If TRUE, approximate standard deviations are calculated for the covariance and linear regression parameters (= square root of diagonal of the inverse Fisher information for Gaussian likelihoods and square root of diagonal of a numerically approximated inverse Hessian for non-Gaussian likelihoods)
- init_aux_pars: vector with numeric elements (default = NULL). Initial values for additional parameters for non-Gaussian likelihoods (e.g., shape parameter of gamma likelihood)
- estimate_aux_pars: boolean (default = TRUE). If TRUE, additional parameters for non-Gaussian likelihoods are also estimated (e.g., shape parameter of gamma likelihood)
- cg_max_num_it: integer (default = 1000). Maximal number of iterations for conjugate gradient algorithms
- cg_max_num_it_tridiag: integer (default = 1000). Maximal number of iterations for conjugate gradient algorithm when being run as Lanczos algorithm for tridiagonalization
- cg_delta_conv: numeric (default = 1E-2). Tolerance level for L2 norm of residuals for checking convergence in conjugate gradient algorithm when being used for parameter estimation
- num_rand_vec_trace: integer (default = 50). Number of random vectors (e.g., Rademacher) for stochastic approximation of the trace of a matrix
- reuse_rand_vec_trace: boolean (default = TRUE). If true, random vectors (e.g., Rademacher) for stochastic approximation of the trace of a matrix are sampled only once at the beginning of Newton's method for finding the mode in the Laplace approximation and are then reused in later trace approximations. Otherwise they are sampled every time a trace is calculated
- seed_rand_vec_trace: integer (default = 1). Seed number to generate random vectors (e.g., Rademacher)
- piv_chol_rank: integer (default = 50). Rank of the pivoted Cholesky decomposition used as preconditioner in conjugate gradient algorithms
- cg_preconditioner_type: string (default = "Sigma_inv_plus_BtWB" for non-Gaussian likelihoods and a Vecchia-Laplace approximation). Type of preconditioner used for conjugate gradient algorithms. Options for non-Gaussian likelihoods and a Vecchia-Laplace approximation:
 - "piv_chol_on_Sigma": $(L_k * L_k^T + W^{-1})$ as preconditioner for inverting $(B^{-1} * D * B^{-T} + W^{-1})$, where L_k is a low-rank pivoted

- Cholesky approximation for Σ and $B^{-1} * D * B^{-T}$ approx=
 Σ
- "Sigma_inv_plus_BtWB": $(B^T * (D^{-1} + W) * B)$ as preconditioner for inverting $(B^T * D^{-1} * B + W)$, where $B^T * D^{-1} * B$ approx=
 Σ^{-1}

Value

A GPMoel

Author(s)

Fabio Sigrist

Examples

```
data(GPBoost_data, package = "gpboost")
gp_model <- GPMoel(group_data = group_data, likelihood="gaussian")
set_optim_params(gp_model, params=list(optimizer_cov="nelder_mead"))
```

set_prediction_data *Set prediction data for a GPMoel*

Description

Set the data required for making predictions with a GPMoel

Usage

```
set_prediction_data(gp_model, vecchia_pred_type = NULL,
  num_neighbors_pred = NULL, cg_delta_conv_pred = NULL,
  nsim_var_pred = NULL, rank_pred_approx_matrix_lanczos = NULL,
  group_data_pred = NULL, group_rand_coef_data_pred = NULL,
  gp_coords_pred = NULL, gp_rand_coef_data_pred = NULL,
  cluster_ids_pred = NULL, X_pred = NULL)
```

Arguments

gp_model A GPMoel

vecchia_pred_type

A string specifying the type of Vecchia approximation used for making predictions. Default value if vecchia_pred_type = NULL: "order_obs_first_cond_obs_only".

Available options:

- "order_obs_first_cond_obs_only": Vecchia approximation for the observable process and observed training data is ordered first and the neighbors are only observed training data points

- "order_obs_first_cond_all": Vecchia approximation for the observable process and observed training data is ordered first and the neighbors are selected among all points (training + prediction)
- "latent_order_obs_first_cond_obs_only": Vecchia approximation for the latent process and observed data is ordered first and neighbors are only observed points
- "latent_order_obs_first_cond_all": Vecchia approximation for the latent process and observed data is ordered first and neighbors are selected among all points
- "order_pred_first": Vecchia approximation for the observable process and prediction data is ordered first for making predictions. This option is only available for Gaussian likelihoods

num_neighbors_pred	an integer specifying the number of neighbors for the Vecchia approximation for making predictions. Default value if NULL: $\text{num_neighbors_pred} = 2 * \text{num_neighbors}$
cg_delta_conv_pred	a numeric specifying the tolerance level for L2 norm of residuals for checking convergence in conjugate gradient algorithms when being used for prediction Default value if NULL: 1e-3
nsim_var_pred	an integer specifying the number of samples when simulation is used for calculating predictive variances Default value if NULL: 1000
rank_pred_approx_matrix_lanczos	an integer specifying the rank of the matrix for approximating predictive covariances obtained using the Lanczos algorithm Default value if NULL: 1000
group_data_pred	A vector or matrix with elements being group levels for which predictions are made (if there are grouped random effects in the GPModel)
group_rand_coef_data_pred	A vector or matrix with covariate data for grouped random coefficients (if there are some in the GPModel)
gp_coords_pred	A matrix with prediction coordinates (=features) for Gaussian process (if there is a GP in the GPModel)
gp_rand_coef_data_pred	A vector or matrix with covariate data for Gaussian process random coefficients (if there are some in the GPModel)
cluster_ids_pred	A vector with elements indicating the realizations of random effects / Gaussian processes for which predictions are made (set to NULL if you have not specified this when creating the GPModel)
X_pred	A matrix with prediction covariate data for the fixed effects linear regression term (if there is one in the GPModel)

Author(s)

Fabio Sigrist

Examples

```

data(GPBoost_data, package = "gpboost")
set.seed(1)
train_ind <- sample.int(length(y),size=250)
gp_model <- GPModel(group_data = group_data[train_ind,1], likelihood="gaussian")
set_prediction_data(gp_model, group_data_pred = group_data[-train_ind,1])

```

```
set_prediction_data.GPModel
```

Set prediction data for a GPModel

Description

Set the data required for making predictions with a GPModel

Usage

```

## S3 method for class 'GPModel'
set_prediction_data(gp_model, vecchia_pred_type = NULL,
  num_neighbors_pred = NULL, cg_delta_conv_pred = NULL,
  nsim_var_pred = NULL, rank_pred_approx_matrix_lanczos = NULL,
  group_data_pred = NULL, group_rand_coef_data_pred = NULL,
  gp_coords_pred = NULL, gp_rand_coef_data_pred = NULL,
  cluster_ids_pred = NULL, X_pred = NULL)

```

Arguments

gp_model A GPModel
vecchia_pred_type

A string specifying the type of Vecchia approximation used for making predictions. Default value if vecchia_pred_type = NULL: "order_obs_first_cond_obs_only".

Available options:

- "order_obs_first_cond_obs_only": Vecchia approximation for the observable process and observed training data is ordered first and the neighbors are only observed training data points
- "order_obs_first_cond_all": Vecchia approximation for the observable process and observed training data is ordered first and the neighbors are selected among all points (training + prediction)
- "latent_order_obs_first_cond_obs_only": Vecchia approximation for the latent process and observed data is ordered first and neighbors are only observed points
- "latent_order_obs_first_cond_all": Vecchia approximation for the latent process and observed data is ordered first and neighbors are selected among all points

- "order_pred_first": Vecchia approximation for the observable process and prediction data is ordered first for making predictions. This option is only available for Gaussian likelihoods
- num_neighbors_pred
an integer specifying the number of neighbors for the Vecchia approximation for making predictions. Default value if NULL: $2 * \text{num_neighbors}$
- cg_delta_conv_pred
a numeric specifying the tolerance level for L2 norm of residuals for checking convergence in conjugate gradient algorithms when being used for prediction Default value if NULL: 1e-3
- nsim_var_pred
an integer specifying the number of samples when simulation is used for calculating predictive variances Default value if NULL: 1000
- rank_pred_approx_matrix_lanczos
an integer specifying the rank of the matrix for approximating predictive covariances obtained using the Lanczos algorithm Default value if NULL: 1000
- group_data_pred
A vector or matrix with elements being group levels for which predictions are made (if there are grouped random effects in the GPModel)
- group_rand_coef_data_pred
A vector or matrix with covariate data for grouped random coefficients (if there are some in the GPModel)
- gp_coords_pred
A matrix with prediction coordinates (=features) for Gaussian process (if there is a GP in the GPModel)
- gp_rand_coef_data_pred
A vector or matrix with covariate data for Gaussian process random coefficients (if there are some in the GPModel)
- cluster_ids_pred
A vector with elements indicating the realizations of random effects / Gaussian processes for which predictions are made (set to NULL if you have not specified this when creating the GPModel)
- X_pred
A matrix with prediction covariate data for the fixed effects linear regression term (if there is one in the GPModel)

Value

A GPModel

Author(s)

Fabio Sigrist

Examples

```
data(GPBoost_data, package = "gpboost")
set.seed(1)
```

```
train_ind <- sample.int(length(y),size=250)
gp_model <- GPModel(group_data = group_data[train_ind,1], likelihood="gaussian")
set_prediction_data(gp_model, group_data_pred = group_data[-train_ind,1])
```

 slice

Slice a dataset

Description

Get a new `gpb.Dataset` containing the specified rows of original `gpb.Dataset` object

Usage

```
slice(dataset, ...)

## S3 method for class 'gpb.Dataset'
slice(dataset, idxset, ...)
```

Arguments

dataset	Object of class <code>gpb.Dataset</code>
...	other parameters (currently not used)
idxset	an integer vector of indices of rows needed

Value

constructed sub dataset

Examples

```
data(agaricus.train, package = "gpboost")
train <- agaricus.train
dtrain <- gpb.Dataset(train$data, label = train$label)

dsub <- gpboost::slice(dtrain, seq_len(42L))
gpb.Dataset.construct(dsub)
labels <- gpboost::getinfo(dsub, "label")
```

summary.GPModel	<i>Summary for a GPModel</i>
-----------------	------------------------------

Description

Summary for a GPModel

Usage

```
## S3 method for class 'GPModel'
summary(object, ...)
```

Arguments

```
object      a GPModel
...         (not used, ignore this, simply here that there is no CRAN warning)
```

Value

Summary of a (fitted) GPModel

Author(s)

Fabio Sigrist

Examples

```
# See https://github.com/fabsig/GPBoost/tree/master/R-package for more examples

data(GPBoost_data, package = "gpboost")
# Add intercept column
X1 <- cbind(rep(1,dim(X)[1]),X)
X_test1 <- cbind(rep(1,dim(X_test)[1]),X_test)

#-----Grouped random effects model: single-level random effect-----
gp_model <- fitGPModel(group_data = group_data[,1], y = y, X = X1,
                      likelihood="gaussian", params = list(std_dev = TRUE))
summary(gp_model)

#-----Gaussian process model-----
gp_model <- fitGPModel(gp_coords = coords, cov_function = "exponential",
                      likelihood="gaussian", y = y, X = X1, params = list(std_dev = TRUE))
summary(gp_model)
```

X	<i>Example data for the GPBoost package</i>
---	---

Description

A matrix with covariate data for the example data of the GPBoost package

Usage

```
data(GPBoost_data)
```

X_test	<i>Example data for the GPBoost package</i>
--------	---

Description

A matrix with covariate information for the predictions for the example data of the GPBoost package

Usage

```
data(GPBoost_data)
```

y	<i>Example data for the GPBoost package</i>
---	---

Description

Response variable for the example data of the GPBoost package

Usage

```
data(GPBoost_data)
```

Index

* datasets

- agaricus.test, 4
- agaricus.train, 4
- bank, 5
- coords, 5
- coords_test, 6
- GPBoost_data, 58
- group_data, 67
- group_data_test, 67
- X, 93
- X_test, 93
- y, 93

- agaricus.test, 4
- agaricus.train, 4

- bank, 5
- barplot, 41

- coords, 5
- coords_test, 6

- dim.gpb.Dataset, 6
- dimnames.gpb.Dataset, 7
- dimnames<- .gpb.Dataset
(dimnames.gpb.Dataset), 7

- fit, 8
- fit.GPModel, 10
- fitGPModel, 13

- get_nested_categories, 20
- getinfo, 19
- gpb.convert_with_rules, 21
- gpb.cv, 23, 24, 34, 49, 54
- gpb.Dataset, 24, 26, 34, 54
- gpb.Dataset.construct, 28
- gpb.Dataset.create.valid, 28
- gpb.Dataset.save, 29
- gpb.Dataset.set.categorical, 30
- gpb.Dataset.set.reference, 30

- gpb.dump, 31
- gpb.get.eval.result, 32
- gpb.grid.search.tune.parameters, 33
- gpb.importance, 37, 41
- gpb.interprete, 38, 42
- gpb.load, 39
- gpb.model.dt.tree, 40
- gpb.plot.importance, 41
- gpb.plot.interpretation, 42
- gpb.plot.part.dep.interact, 44
- gpb.plot.partial.dependence, 45
- gpb.save, 47
- gpb.train, 48, 56
- gpboost, 53
- GPBoost_data, 57
- GPModel, 58
- GPModel_shared_params, 61
- group_data, 67
- group_data_test, 67

- loadGPModel, 67

- neg_log_likelihood, 68
- neg_log_likelihood.GPModel, 69

- predict.gpb.Booster, 70
- predict.GPModel, 73
- predict_training_data_random_effects,
76
- predict_training_data_random_effects.GPModel,
77

- readRDS, 78
- readRDS.gpb.Booster, 78

- saveGPModel, 79
- saveRDS.gpb.Booster, 80
- set_optim_params, 82
- set_optim_params.GPModel, 84
- set_prediction_data, 87
- set_prediction_data.GPModel, 89

setinfo, [81](#)
slice, [91](#)
summary.GPModel, [92](#)

X, [93](#)
X_test, [93](#)

y, [93](#)