

Package ‘gprofiler2’

August 26, 2019

Type Package

Title Interface to the 'g:Profiler' Toolset

Version 0.1.6

Author Liis Kolberg <liis.kolberg@ut.ee>, Uku Raudvere <uku.raudvere@ut.ee>

Maintainer Liis Kolberg <liis.kolberg@ut.ee>

Description A toolset for functional enrichment analysis and visualization, gene/protein/SNP identifier conversion and mapping orthologous genes across species via 'g:Profiler' (<<https://biit.cs.ut.ee/gprofiler>>).

The main tools are:

- (1) 'g:GOST' - functional enrichment analysis and visualization of gene lists;
- (2) 'g:Convert' - gene/protein/transcript identifier conversion across various namespaces;
- (3) 'g:Orth' - orthology search across species;
- (4) 'g:SNPense' - mapping SNP rs identifiers to chromosome positions, genes and variant effects

This package is an R interface corresponding to the 2019 update of 'g:Profiler' and provides access to 'g:Profiler' for versions 'e94_eg41_p11' and higher. See the package 'gProfileR' for accessing older versions from the 'g:Profiler' toolset.

BugReports <https://biit.cs.ut.ee/gprofiler/page/contact>

License GPL (>= 2)

Encoding UTF-8

LazyData true

RoxygenNote 6.1.1

Imports jsonlite, RCurl, ggplot2, plotly, tidyr, crosstalk, plyr,
grDevices, gridExtra, grid, viridisLite, dplyr

Depends R (>= 3.5)

NeedsCompilation no

Repository CRAN

Date/Publication 2019-08-26 13:40:02 UTC

R topics documented:

gconvert	2
get_base_url	3
get_tls_version	3
get_user_agent	3
gorth	4
gost	5
gostplot	6
gsnpense	7
mapViridis	8
publish_gostplot	9
publish_gosttable	10
set_base_url	11
set_tls_version	11
set_user_agent	11
upload_GMT_file	12

Index	14
--------------	-----------

gconvert	<i>Gene ID conversion.</i>
----------	----------------------------

Description

Interface to the g:Profiler tool g:Convert that uses the information in Ensembl databases to handle hundreds of types of identifiers for genes, proteins, transcripts, microarray probesets, etc, for many species, experimental platforms and biological databases. The input is flexible: it accepts a mixed list of IDs and recognises their types automatically. It can also serve as a service to get all genes belonging to a particular functional category.

Usage

```
gconvert(query, organism = "hsapiens", target = "ENSG",
         numeric_ns = "", mthreshold = Inf, filter_na = TRUE)
```

Arguments

query	vector that can consist of mixed types of gene IDs (proteins, transcripts, microarray IDs, etc), SNP IDs, chromosomal intervals or term IDs.
organism	organism name. Organism names are constructed by concatenating the first letter of the name and the family name. Example: human - 'hsapiens', mouse - 'mmusculus'.
target	target namespace.
numeric_ns	namespace to use for fully numeric IDs.
mthreshold	maximum number of results per initial alias to show. Shows all by default.
filter_na	logical indicating whether to filter out results without a corresponding target.

Value

The output is a data.frame which is a table closely corresponding to the web interface output.

Author(s)

Liis Kolberg <liis.kolberg@ut.ee>, Uku Raudvere <uku.raudvere@ut.ee>

Examples

```
gconvert(c("POU5F1", "SOX2", "NANOG"), organism = "hsapiens", target="AFFY_HG_U133_PLUS_2")
```

get_base_url	<i>Get the current base URL.</i>
--------------	----------------------------------

Description

Get the current base URL.

Usage

```
get_base_url()
```

get_tls_version	<i>Get the TLS version for SSL</i>
-----------------	------------------------------------

Description

Get the TLS version for SSL

Usage

```
get_tls_version()
```

get_user_agent	<i>Get current user agent string.</i>
----------------	---------------------------------------

Description

Get the HTTP User-Agent string.

Usage

```
get_user_agent()
```

gorth *Orthology search.*

Description

Interface to the g:Profiler tool g:Orth that, given a target organism, retrieves the genes of the target organism that are similar in sequence to the source organism genes in the input.

Usage

```
gorth(query, source_organism = "hsapiens",
      target_organism = "mmusculus", numeric_ns = "", mthreshold = Inf,
      filter_na = TRUE)
```

Arguments

query	vector of gene IDs to be translated.
source_organism	name of the source organism. Organism names are constructed by concatenating the first letter of the name and the family name. Example: human - 'hsapiens', mouse - 'mmusculus'.
target_organism	name of the target organism. Organism names are constructed by concatenating the first letter of the name and the family name. Example: human - 'hsapiens', mouse - 'mmusculus'.
numeric_ns	namespace to use for fully numeric IDs.
mthreshold	maximum number of ortholog names per gene to show.
filter_na	logical indicating whether to filter out results without a corresponding target name.

Value

The output is a data.frame which is a table closely corresponding to the web interface output.

Author(s)

Liis Kolberg <liis.kolberg@ut.ee>, Uku Raudvere <uku.raudvere@ut.ee>

Examples

```
gorth(c("K1f4", "Pax5", "Sox2", "Nanog"), source_organism="mmusculus", target_organism="hsapiens")
```

gost

*Gene list functional enrichment.***Description**

Interface to the g:Profiler tool g:GOST for functional enrichments analysis of gene lists. In case the input 'query' is a list of gene vectors, results for multiple queries will be returned in the same data frame with column 'query' indicating the corresponding query name. If 'multi_query' is selected, the result is a data frame for comparing multiple input lists, just as in the web tool.

Usage

```
gost(query, organism = "hsapiens", ordered_query = FALSE,
      multi_query = FALSE, significant = TRUE, exclude_iea = FALSE,
      measure_underrepresentation = FALSE, evcodes = FALSE,
      user_threshold = 0.05, correction_method = c("g_SCS", "bonferroni",
      "fdr", "false_discovery_rate", "gSCS", "analytical"),
      domain_scope = c("annotated", "known", "custom"), custom_bg = NULL,
      numeric_ns = "", sources = NULL)
```

Arguments

query	vector, or a (named) list of vectors for multiple queries, that can consist of mixed types of gene IDs (proteins, transcripts, microarray IDs, etc), SNP IDs, chromosomal intervals or term IDs.
organism	organism name. Organism names are constructed by concatenating the first letter of the name and the family name. Example: human - 'hsapiens', mouse - 'mmusculus'.
ordered_query	in case input gene lists are ranked this option may be used to get GSEA style p-values.
multi_query	in case of multiple gene lists, returns comparison table of these lists. If enabled, the result data frame has columns named 'p_values', 'query_sizes', 'intersection_sizes' with vectors showing values in the order of input queries. To get the results in a long format set 'multi_query' to FALSE and just input query list of multiple gene vectors.
significant	whether all or only statistically significant results should be returned.
exclude_iea	exclude GO electronic annotations (IEA).
measure_underrepresentation	measure underrepresentation.
evcodes	include evidence codes to the results. Note that this can decrease performance and make the query slower. In addition, a column 'intersection' is created that contains the gene id-s that intersect between the query and term. This parameter does not work if 'multi_query' is set to TRUE.
user_threshold	custom p-value threshold, results with a larger p-value are excluded.

correction_method	the algorithm used for multiple testing correction, one of "gSCS" (synonyms: "analytical", "g_SCS"), "fdr" (synonyms: "false_discovery_rate"), "bonferroni".
domain_scope	how to define statistical domain, one of "annotated", "known" or "custom".
custom_bg	vector of gene names to use as a statistical background. If given, the domain_scope is set to 'custom'.
numeric_ns	namespace to use for fully numeric IDs.
sources	a vector of data sources to use. Currently, these include GO (GO:BP, GO:MF, GO:CC to select a particular GO branch), KEGG, REAC, TF, MIRNA, CORUM, HP, HPA, WP. Please see the g:GOSt web tool for the comprehensive list and details on incorporated data sources.

Value

A named list where 'result' contains data.frame with the enrichment analysis results and 'meta' contains metadata needed for Manhattan plot. If the input consisted of several lists the corresponding list is indicated with a variable 'query'. When requesting a 'multi_query', either TRUE or FALSE, the columns of the resulting data frame differ. If 'evcodes' is set, the return value includes columns 'evidence_codes' and 'intersection'. The latter conveys info about the intersecting genes between the corresponding query and term.

Author(s)

Liis Kolberg <liis.kolberg@ut.ee>, Uku Raudvere <uku.raudvere@ut.ee>

Examples

```
gostres <- gost(c("X:1000:1000000", "rs17396340", "GO:0005005", "ENSG00000156103", "NLRP1"))
```

gostplot

Manhattan plot of functional enrichment results.

Description

This function creates a Manhattan plot out of the results from gprofiler2::gost(). The plot is very similar to the one shown in the g:GOSt web tool.

Usage

```
gostplot(gostres, capped = TRUE, interactive = TRUE, pal = c(`GO:MF` = "#dc3912", `GO:BP` = "#ff9900", `GO:CC` = "#109618", KEGG = "#dd4477", REAC = "#3366cc", WP = "#0099c6", TF = "#5574a6", MIRNA = "#22aa99", HPA = "#6633cc", CORUM = "#66aa00", HP = "#990099"))
```

Arguments

<code>gostres</code>	named list from <code>gost()</code> function (with names 'result' and 'meta')
<code>capped</code>	whether the $-\log_{10}(\text{p-values})$ would be capped if ≥ 16 , just as in the web options.
<code>interactive</code>	if enabled, returns interactive plot using 'plotly'. If disabled, static 'ggplot()' object is returned.
<code>pal</code>	values mapped to relevant colors for data sources.

Value

The output is either a plotly object (if `interactive = TRUE`) or a ggplot object (if `interactive = FALSE`).

Author(s)

Liis Kolberg <liis.kolberg@ut.ee>

Examples

```
gostres <- gost(c("Klf4", "Pax5", "Sox2", "Nanog"), organism = "mmusculus")
gostplot(gostres)
```

`gsnpense` *Convert SNP rs numbers to genes.*

Description

Interface to the g:Profiler tool g:SNPense that maps SNP rs identifiers to chromosome positions, genes and variant effects. Available only for human SNPs.

Usage

```
gsnpense(query, filter_na = TRUE)
```

Arguments

<code>query</code>	vector of SNP IDs to be translated (should start with prefix 'rs').
<code>filter_na</code>	logical indicating whether to filter out results without a corresponding target name.

Value

The output is a data.frame which is a table closely corresponding to the web interface output. Columns 'ensgs' and 'gene_names' can contain list of multiple values.

Author(s)

Liis Kolberg <liis.kolberg@ut.ee>, Uku Raudvere <uku.raudvere@ut.ee>

Examples

```
gsnpense(c("rs11734132", "rs7961894", "rs4305276", "rs17396340", "rs3184504"))
```

mapViridis

Map vector of numeric values to Viridis color scale.

Description

Map vector of numeric values to Viridis color scale.

Usage

```
mapViridis(values, domain_min = 0, domain_max = 50, n = 256)
```

Arguments

values	vector of numeric values (mostly $-\log_{10}(\text{p-values})$)
domain_min	numeric value that corresponds to the 'yellow' in the color scale
domain_max	numeric value that corresponds to the 'dark blue' in the color scale
n	number of bins to generate from the color scale

Value

The output is a corresponding vector of colors from the Viridis color scale with domain in range(domain_min, domain_max).

Author(s)

Liis Kolberg <liis.kolberg@ut.ee>

publish_gostplot	<i>Create and save an annotated Manhattan plot of enrichment results.</i>
------------------	---

Description

This function allows to highlight a list of selected terms on the Manhattan plot created with the `gprofiler2::gostplot()` function. The resulting plot is saved to a publication ready image if 'filename' is specified. The plot is very similar to the one shown in the `g:GOSt` web tool after clicking on circles.

Usage

```
publish_gostplot(p, highlight_terms = NULL, filename = NULL)
```

Arguments

<code>p</code>	ggplot object from <code>gostplot(gostres, interactive = FALSE)</code> function
<code>highlight_terms</code>	vector of selected term IDs from the analysis or a (subset) data.frame that has a column called 'term_id'. No annotation is added if set to NULL.
<code>filename</code>	file name to create on disk and save the annotated plot. Filename extension should be from <code>c("png", "pdf", "jpeg", "tiff", "bmp")</code> .

Value

The output is a ggplot object.

Author(s)

Liis Kolberg <liis.kolberg@ut.ee>

Examples

```
gostres <- gost(c("Klf4", "Pax5", "Sox2", "Nanog"), organism = "mmusculus")
p <- gostplot(gostres, interactive = FALSE)
publish_gostplot(p, highlight_terms = c("GO:0001010", "WP:WP1763"))
```

publish_gosttable *Create and save a table with the functional enrichment analysis results.*

Description

This function creates a table mainly for the results from gost() function. However, if the input at least contains columns named 'term_id' and 'p_value' then any enrichment results data frame can be visualised in a table with this function.

Usage

```
publish_gosttable(gostres, highlight_terms = NULL, use_colors = TRUE,
  show_columns = c("source", "term_name", "term_size",
    "intersection_size"), filename = NULL)
```

Arguments

gostres	named list from gost() function (with names 'result' and 'meta') or a data frame that has columns named "term_id" and "p_value(s)".
highlight_terms	vector of selected term IDs from the analysis or a (subset) data.frame that has a column called 'term_id'. All data is shown if set to NULL.
use_colors	if enabled, the p-values are highlighted in the viridis colorscale just as in g:Profiler, otherwise the table has no background colors.
show_columns	names of additional columns to show besides term_id and p_value. By default the output table shows additional columns named "source", "term_name", "term_size", "intersection_size"
filename	file name to create on disk and save the annotated plot. Filename extension should be from c("png", "pdf", "jpeg", "tiff", "bmp").

Details

The output table is very similar to the one shown under the Manhattan plot.

Value

The output is a ggplot object.

Author(s)

Liis Kolberg <liis.kolberg@ut.ee>

Examples

```
gostres <- gost(c("Klf4", "Pax5", "Sox2", "Nanog"), organism = "mmusculus")
publish_gosttable(gostres, highlight_terms = c("GO:0001010", "WP:WP1763"))
```

set_base_url	<i>Set the base URL.</i>
--------------	--------------------------

Description

Function to change the g:Profiler base URL. Useful for overriding the default URL (<http://biit.cs.ut.ee/gprofiler>) with the beta (http://biit.cs.ut.ee/gprofiler_beta) or an archived version (available starting from the version e94_eg41_p11, e.g. http://biit.cs.ut.ee/gprofiler_archive3/e94_eg41_p11).

Usage

```
set_base_url(url)
```

Arguments

url	the base URL.
-----	---------------

set_tls_version	<i>Set the TLS version to use for SSL</i>
-----------------	---

Description

Set the TLS version. Could be useful at environments where SSL was built without TLS 1.2 support

Usage

```
set_tls_version(v)
```

Arguments

v	version: "1.2" (default), "1.1" (fallback)
---	--

set_user_agent	<i>Set custom user agent string.</i>
----------------	--------------------------------------

Description

Set the HTTP User-Agent string. Useful for overriding the default user agent for packages that depend on gprofiler2 functionality.

Usage

```
set_user_agent(ua, append = F)
```

Arguments

ua	the user agent string.
append	logical indicating whether to append the passed string to the default user agent string.

upload_GMT_file	<i>Upload custom annotations for functional enrichment analysis in g:GOSt.</i>
-----------------	--

Description

Upload your own annotation data using files in the Gene Matrix Transposed file format (GMT) for functional enrichment analysis in g:GOSt. The accepted file is either a single annotations file (with the extension .gmt) or a compressed directory of multiple annotation GMT files (with the extension .zip). The GMT format is a tab-separated list of gene annotation sets where every line represents a separate gene set/functional term. The first column defines the function ID, second defines a short name/description of the function and the following columns are the list of genes related to the specific function in that row.

Usage

```
upload_GMT_file(gmtfile)
```

Arguments

gmtfile	the filepath of the GMT file to be uploaded. The file extension should be .gmt or .zip in case of multiple GMT files. If the filepath does not contain an absolute path, the filename is relative to the current working directory.
---------	---

Details

The uploaded filename is used to define 'source' name in the g:GOSt results.

Value

A string that denotes the ID of the uploaded custom annotations in the g:Profiler database. After the GMT file upload this unique ID can be used as a value for the argument 'organism' in the gost() function to perform functional enrichment analysis based on these custom data.

No need to repeatedly upload the same custom GMT file(s) every time you want to do the enrichment analysis. The custom ID can also be used in the web tool as a token under the Custom GMT options.

Author(s)

Liis Kolberg <liis.kolberg@ut.ee>

Examples

```
## Not run: custom_id <- upload_GMT_file("path/to/file.gmt")
```

Index

[gconvert](#), 2
[get_base_url](#), 3
[get_tls_version](#), 3
[get_user_agent](#), 3
[gorth](#), 4
[gost](#), 5
[gostplot](#), 6
[gsnpense](#), 7

[mapViridis](#), 8

[publish_gostplot](#), 9
[publish_gosttable](#), 10

[set_base_url](#), 11
[set_tls_version](#), 11
[set_user_agent](#), 11

[upload_GMT_file](#), 12