

Package ‘intsvy’

October 13, 2022

Version 2.6

Type Package

Title International Assessment Data Manager

Date 2022-08-06

Author Daniel Caro <dcarov@gmail.com>, Przemyslaw Biecek <przemyslaw.biecek@gmail.com>

Maintainer Daniel Caro <dcarov@gmail.com>

Description Provides tools for importing, merging, and analysing data from international assessment studies (TIMSS, PIRLS, PISA, ICILS, and PIAAC).

License GPL-2

URL <https://daniel-caro.com/r-intsvy/>,
<https://github.com/eldafani/intsvy>

BugReports <https://github.com/eldafani/intsvy/issues>

Imports dplyr, foreign, ggplot2, Hmisc, memisc, plyr, reshape, stats,
utils

LazyData yes

NeedsCompilation no

Repository CRAN

Depends R (>= 3.5.0)

Date/Publication 2022-08-06 14:00:13 UTC

R topics documented:

intsvy-package	3
configs	4
intsvy.ben.pv	4
intsvy.config	5
intsvy.log	7
intsvy.log.pv	8
intsvy.mean	9
intsvy.mean.pv	10

intsvy.per.pv	11
intsvy.reg	12
intsvy.reg.pv	13
intsvy.rho	14
intsvy.rho.pv	15
intsvy.select.merge	16
intsvy.table	17
intsvy.var.label	18
piaac.ben.pv	19
piaac.mean	20
piaac.mean.pv	21
piaac.reg	22
piaac.reg.pv	23
piaac.table	24
pirls.ben.pv	25
pirls.log	26
pirls.log.pv	27
pirls.mean	28
pirls.mean.pv	29
pirls.per.pv	30
pirls.reg	31
pirls.reg.pv	32
pirls.rho	33
pirls.rho.pv	34
pirls.select.merge	35
pirls.table	36
pirls.var.label	37
pisa.ben.pv	37
pisa.log	38
pisa.log.pv	39
pisa.mean	40
pisa.mean.pv	41
pisa.per.pv	42
pisa.reg	43
pisa.reg.pv	44
pisa.rho	45
pisa.select.merge	46
pisa.table	47
pisa.var.label	48
plot.intsvy.mean	49
plot.intsvy.reg	50
plot.intsvy.table	51
timss.ben.pv	53
timss.log	54
timss.log.pv	55
timss.mean	56
timss.mean.pv	57
timss.per.pv	58

intsvy-package 3

timss.reg	59
timss.reg.pv	60
timss.rho	61
timss.rho.pv	62
timss.table	63
timssg4.select.merge	64
timssg4.var.label	65
timssg8.select.merge	65
timssg8.var.label	66

Index 68

intsvy-package *International Assessment Data Manager*

Description

Provides tools for importing, merging, and analysing data from international assessment studies (TIMSS, PIRLS, PISA, and PIAAC and others)

Details

Package: intsvy
Type: Package
Version: 2.6
Date: 2022-08-06
License: GPL-2

intsvy allows useRs to work with international assessment data (e.g., TIMSS, PIRLS, PISA, ICILS, and PIAAC). Data and merge functions print variable labels and the name of participating countries in international assessments as well as import data directly into R for the variables in student, parent, school, and teacher instruments and countries selected by the useR. Analysis functions, including mean statistics, standard deviations, regression estimates, correlation coefficients, and frequency tables, calculate point estimates and standard errors that take into account the complex sample design (i.e., replicate weights) and rotated test forms (i.e., plausible achievement values).

Author(s)

Daniel Caro <dcarov@gmail.com>, Przemyslaw Biecek <przemyslaw.biecek@gmail.com>

References

PISA, PIAAC, PIRLS, and TIMSS Technical Reports

configs	<i>Config files for intsvy studies</i>
---------	--

Description

Each config file describes detailed study meta-data. Such meta data defined names of columns with weights, type of weighting, number of plausible values and other study parameters. Most of intsvy functions require such config objects.

Usage

pisa_conf

Format

A list with three components - input, variables and parameters.

intsvy.ben.pv	<i>Performance international benchmarks and proficiency levels</i>
---------------	--

Description

intsvy.ben.pv calculates the percentage of students performing at or above the cut-off points (scores) given by the useR. The default are the benchmarks established by official reports.

Usage

```
intsvy.ben.pv(pvnames, by, cutoff, data, atlevel=FALSE, export = FALSE, name = "output",
             folder = getwd(), config)
```

Arguments

pvnames	The label corresponding to the achievement variable, for example, "ASRREA", for overall reading performance.
cutoff	The cut-off points for the assessment benchmarks (e.g., cutoff= c(357.77, 420.07, 482.38, 544.68, 606.99, 669.30)).
by	The label for the grouping variable, usually the countries (i.e., by="IDCOUNTRYL"), but could be any other categorical variable.
data	An R object, normally a data frame, containing the data from PIRLS.
atlevel	A logical value. If TRUE, percentages at each level are calculated. Otherwise (FALSE), percentages at or above levels are reported.
export	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
name	The name of the exported file.

folder	The folder where the exported file is located.
config	Object with configuration of a given study. Should contain the slot 'prefixes' with prefixes of filenames with the student, home, school, and teacher data.

Value

pirls.ben.pv returns a data frame with the percentage of students at or above the benchmark and the corresponding standard error.

See Also

timss.ben.pv, pirls.ben.pv, pisa.ben.pv

Examples

```
## Not run:
pisa.ben.pv(pvlabel="MATH", by="CNT", data=pisa, atlevel = TRUE)
intsvy.ben.pv(pvnames="MATH", by="CNT", data=pisa, atlevel= TRUE, config=pisa_conf)

piaac.ben.pv(pvlabel="LIT", by="CNTRYID", data=piaac)
intsvy.ben.pv(pvnames="LIT", by="CNTRYID", data=piaac, config=piaac_conf)

timss.ben.pv(pvlabel="ASMMAT", by="IDCNTRYL", data=timss4)
intsvy.ben.pv(pvnames="ASMMAT", by="IDCNTRYL", data=timss4, config=timss4_conf)

## End(Not run)
```

intsvy.config *Config files for intsvy studies*

Description

intsvy.config set non standard parameters for intsvy functions. It also allow to apply intsvy functions to new studies that are similar to PIRLS, TIMSS, PISA, PIAAC, ICILS.

Usage

```
intsvy.config(variables.pvlabelpref,
              variables.pvlabelsuff,
              variables.weight,
              variables.jackknifeZone,
              variables.jackknifeRep,
              parameters.cutoffs,
              parameters.cutoffs2,
              parameters.percentiles,
              parameters.weights,
              parameters.PVreps,
              parameters.varpv1,
```

```

input.type,
input.prefixes,
input.student,
input.student_colnames1,
input.student_colnames2,
input.student_pattern,
input.homeinput,
input.home_colnames,
input.school,
input.school_colnames,
input.teacher,
input.teacher_colnames,
input.student_ids,
input.school_ids,
input.type_part,
input.cnt_part, base.config = pirls_conf)

```

Arguments

`parameters.weights`
 Weighting scheme. It may be "JK" for studies like PIRLS, ICLS, TIMSS, or "BRR" for studies like PISA or "mixed_piaac" for studies with mixed design like PIAAC.

`parameters.cutoffs2`, `parameters.cutoffs`
 Cut offs for plausible values, either for benchmark or for logistic regression.

`parameters.percentiles`, `parameters.PVreps`
 Other parameters for weighting schemes, like number of PVs.

`parameters.varpv1`
 Logical value, TRUE if only 1 plausible value for within variance estimation.

`variables.pvlabelpref`, `variables.pvlabelsuff`, `variables.weight`, `variables.jackknifeZone`, `variables.ja`
 Names of variables that are used for jack-knife replicates.

`input.type`, `input.prefixes`, `input.student`, `input.student_colnames1`, `input.student_colnames2`, `input.stu`
 Parameters to correctly read data from files downloaded from `iea.nl` website.

`base.config` Base config structure, either `pirls_conf`, `pisa_conf`, `piaac_conf`, `timss4_conf`, `timss8_conf`, `icils_conf`.

Value

`intsvy.config` returns new object with parameters. It is a list with three components - `input`, `variables` and `parameters`.

Examples

```

## Not run:
icils_conf <- intsvy.config(input.student_pattern = "^PV[0-5]CIL$" ,
                           parameters.cutoffs2 = 550, intsvy:::pirls_conf)

icils_conf

## End(Not run)

```

Description

intsvy.log performs logistic regression analysis for an observed dependent variable (NOT for plausible values)

Usage

```
intsvy.log(y, x, by, data, export = FALSE, name = "output",
          folder = getwd(), config)
```

Arguments

y	Label for dependent variable
x	Data labels of independent variables (e.g., x = c("ASDHEHLA", "ITSEX")).
by	The label for the grouping variable, usually the countries (i.e., by="IDCNTRYL"), but could be any other categorical variable.
data	An R object, normally a data frame, containing the data from PIRLS.
export	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
name	The name of the exported file.
folder	The folder where the exported file is located.
config	Object with configuration of a given study. Should contain the slot 'prefixes' with prefixes of filenames with the student, home, school, and teacher data.

Value

pirls.log prints a data frame with coefficients, standard errors, t-values, and odds ratios. Results are stored in a list object of class "intsvy.reg".

See Also

timss.log, pirls.log, pisa.log

Examples

```
## Not run:

pisa$SKIP[!(pisa$ST09Q01=="None" & pisa$ST115Q01=="None")] <- 1
pisa$SKIP[pisa$ST09Q01=="None" & pisa$ST115Q01=="None"] <- 0

pisa$LATE[!pisa$ST08Q01=="None"] <- 1
pisa$LATE[pisa$ST08Q01=="None"] <- 0
```

```
pisa.log(y="SKIP", x="LATE", by="IDCNTRYL", data = pisa)
```

```
## End(Not run)
```

intsvy.log.pv

Logistic regression analysis with plausible values

Description

intsvy.log.pv performs logistic regression with plausible values and replicate weights.

Usage

```
intsvy.log.pv(pvnames, x, cutoff, by, data, export=FALSE, name= "output",
folder=getwd(), config)
```

Arguments

pvnames	The label corresponding to the achievement variable, for example, "ASRREA", for overall reading performance.
x	Data labels of independent variables.
cutoff	The cut-off point at which the dependent plausible values scores are dichotomised (1 is larger than the cut-off)
by	The label for the categorical grouping variable (i.e., by="IDCNTRYL") or variables (e.g., x= c("IDCNTRYL", "ITSEX")).
data	An R object, normally a data frame, containing the data from PIRLS.
export	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
name	The name of the exported file.
folder	The folder where the exported file is located.
config	Object with configuration of a given study. Should contain the slot 'prefixes' with prefixes of filenames with the student, home, school, and teacher data.

Value

intsvy.log.pv returns a data frame with coefficients, standard errors, t-values, and odds ratios. If "by" is specified, results are reported in a list. Weights, e.g. "TOTWGT" for PIRLS, are defined in the config argument.

See Also

pisa.log.pv, pirls.log.pv, timss.log.pv

Examples

```
## Not run:
intsvy.log.pv(pvnames="MATH", cutoff= 606.99, x="ESCS", by="IDCNTRYL",
data=pisa, config=pisa_conf)
intsvy.log.pv(pvnames="BSMMAT", cutoff= 550, x="ITSEX", by="IDCNTRYL",
data=timss8g, config=timss8_conf)

## End(Not run)
```

intsvy.mean	<i>Calculates mean of variable</i>
-------------	------------------------------------

Description

Calculates mean and standard error of observed variable (NOT one with plausible values).

Usage

```
intsvy.mean(variable, by, data, export = FALSE,
name = "output", folder = getwd(), config)
```

Arguments

variable	The label corresponding to the observed variable, for example, "AGE_R" for age of respondent.
by	The label for the grouping variable, usually the countries (i.e., by="CNTRYID"), but could be any other categorical variable.
data	An R object, normally a data frame, containing the data from PIAAC.
export	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
name	The name of the exported file.
folder	The folder where the exported file is located.
config	Object with configuration of a given study. Should contain the slot 'prefixes' with prefixes of filenames with the student, home, school, and teacher data.

Value

intsvy.mean returns a data frame with means and standard errors.

See Also

pisa.mean, timss.mean, pirls.mean

Examples

```
## Not run:
intsvy.mean(variable="READHOME", by="CNTRYID", data=piaac, config=piaac_conf)
intsvy.mean(variable="PARED", by="IDCNTRYL", data=pisa, config=pisa_conf)
intsvy.mean(variable="BSBGSLM", by='IDCNTRYL', data=timss8g, config=timss8_conf)
intsvy.mean(variable='ASBELA', by= 'IDCNTRYL', data=pirls,config=pirls_conf)

## End(Not run)
```

intsvy.mean.pv

Calculates mean achievement score

Description

The function `intsvy.mean.pv` uses plausible values to calculate the mean achievement score and its standard error.

Usage

```
intsvy.mean.pv(pvnames, by, data, export=FALSE, name= "output", folder=getwd(), config)
```

Arguments

<code>pvnames</code>	The names of columns corresponding to the achievement score, for example, <code>paste0("PV",1:5,"MATH")</code> for PISA.
<code>by</code>	The label for the grouping variable, usually the countries (e.g., <code>by="CNTRYID"</code>), but could be any other categorical variable.
<code>data</code>	An R object, normally a data frame.
<code>export</code>	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
<code>name</code>	The name of the exported file.
<code>folder</code>	The folder where the exported file is located.
<code>config</code>	Object with configuration of a given study. Should contain the slot 'prefixes' with prefixes of filenames with the student, home, school, and teacher data.

Value

`intsvy.mean.pv` returns a data frame with means and standard errors.

See Also

`pisa.mean.pv`, `timss.mean.pv`, `pirls.mean.pv`

Examples

```
## Not run:
intsvy.mean.pv(pvnames = "ASRREA0", by= "IDCNTRYL",
  data=pirls, config=pirls_conf)

intsvy.mean.pv(pvnames = "MATH", by="CNT", data=pisa,
  config=pisa_conf)

intsvy.mean.pv(pvnames = "BSMMAT0", by= "IDCNTRYL", data=timss8g,
  config=timss8_conf)

intsvy.mean.pv(pvnames = paste0("PVNUM", 1:10), by="CNTRYID", data=piaac,
  config=piaac_conf)

## End(Not run)
```

intsvy.per.pv	<i>Calculates percentiles</i>
---------------	-------------------------------

Description

Calculates percentiles for plausible values

Usage

```
intsvy.per.pv(pvnames, by, per, data, export=FALSE, name= "output",
  folder=getwd(), config)
```

Arguments

pvnames	The label corresponding to the achievement variable, for example, "BSMMAT", for overall mathematics performance.
per	User-defined percentiles (e.g., per = c(5, 10, 25, 75, 90, 95)).
by	The label of the categorical grouping variable (e.g., by="IDCNTRYL") or variables (e.g., by=c("IDCNTRYL", "ITSEX")).
data	An R object, normally a data frame, containing the data from intsvy studies.
export	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
name	The name of the exported file.
folder	The folder where the exported file is located.
config	Object with configuration of a given study. Should contain the slot 'prefixes' with prefixes of filenames with the student, home, school, and teacher data.

Value

intsvy.per.pv returns a data frame with percentiles and associated standard errors. Default weights (e.g. "TOTWGT" in TIMSS) and percentiles are specified in the config parameter.

See Also

pisa.per.pv, pirls.per.pv, timss.per.pv

Examples

```
## Not run:
timss.per.pv(pvlabel="BSMMAT", per = c(5, 10, 25, 50, 75, 90, 95), by="IDCNTRYL", data=timss8)
intsvy.per.pv(pvnames="BSMMAT", by="IDCNTRYL", data=timss8, config=timss8_conf)

pirls.per.pv(pvlabel="ASRREA", by="IDCNTRYL", data=pirls)
intsvy.per.pv(pvnames="ASRREA", per = c(5, 10, 25, 50, 75, 90, 95), by="IDCNTRYL", data=pirls,
config=pirls_conf)

pisa.per.pv(pvlabel="MATH", per=c(10, 25, 75, 90), by="CNT", data=pisa)
intsvy.per.pv(pvnames="MATH", by="CNT", data=pisa, config=pisa_conf)

## End(Not run)
```

intsvy.reg

Regression analysis without plausible values

Description

intsvy.reg performs linear regression analysis (OLS) for an observed dependent variable (NOT for plausible values)

Usage

```
intsvy.reg(y, x, by, data, export = FALSE, name = "output", folder = getwd(),
config)
```

Arguments

y	Label for dependent variable.
x	Data labels of independent variables.
by	The label for the grouping variable, usually the countries (i.e., by="CNTRYID"), but could be any other categorical variable.
data	An R object, normally a data frame, containing the data.
export	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
name	The name of the exported file.
folder	The folder where the exported file is located.
config	Object with configuration of a given study. Should contain the slot 'prefixes' with prefixes of filenames with the student, home, school, and teacher data.

Value

intsvy.reg returns a data frame with coefficients, standard errors and t-values. If "by" is specified, results are reported in a list. If the "by" argument is set, then the returning object is of the class "intsvy.reg" with overloaded function plot().

See Also

pisa.reg, pirls.reg, timss.reg

Examples

```
## Not run:
# install pbierek/PIAAC package from github to have access to piaac data
piaac.reg(y="AGE_R", x="GENDER_R", by="CNTRYID", data=piaac)

## End(Not run)
```

intsvy.reg.pv

Regression analysis with plausible values

Description

intsvy.reg.pv performs linear regression analysis (OLS) with plausible values and replicate weights.

Usage

```
intsvy.reg.pv(x, pvnames, by,
data, std=FALSE, export = FALSE, name = "output", folder = getwd(), config)
```

Arguments

pvnames	The label corresponding to the achievement variable, for example, "BSMMAT", for overall math performance in TIMSS Grade 8.
x	Data labels of independent variables.
by	The label for the grouping variable, usually the countries (i.e., by="IDCNTRYL"), but could be any other categorical variable.
data	An R object, normally a data frame, containing the data from TIMSS.
std	A logical value. If TRUE standardised regression coefficients are calculated.
export	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
name	The name of the exported file.
folder	The folder where the exported file is located.
config	Object with configuration of a given study. Should contain the slot 'prefixes' with prefixes of filenames with the student, home, school, and teacher data.

Value

intsvy.reg.pv prints a data.frame with regression results (i.e., coefficients, standard errors, t-values, R-squared) and stores different regression output including residuals, replicate coefficients, variance within and between, and the regression data.frame in a list object of class "intsvy.reg".

See Also

piaac.reg.pv, pirls.reg.pv, pisa.reg.pv, timss.reg.pv

Examples

```
## Not run:
intsvy.reg.pv(pvnames="MATH", x="ST04Q01", by = "IDCNTRYL", data=pisa, config=pisa_conf)
intsvy.reg.pv(pvnames="LIT", x="GENDER_R", by = "CNTRYID", data=piaac, config=piaac_conf)
intsvy.reg.pv(pvnames="BSMMAT", by="IDCNTRYL", x="ITSEX", data=timss8g, config=timss8_conf)
intsvy.reg.pv(pvnames="ASRREA", by="IDCNTRYL", x="ITSEX", data=pirls, config=pirls_conf)

## End(Not run)
```

intsvy.rho

Correlation matrix

Description

intsvy.rho produces a correlation matrix for observed variables (NOT for plausible values)

Usage

```
intsvy.rho(variables, by, data,
export = FALSE, name = "output", folder = getwd(), config)
```

Arguments

variables	Data labels for the variables in the correlation matrix (e.g., variables=c("ASRREA01", "ASDAGE"))
by	The label for the grouping variable, usually the countries (i.e., by="IDCNTRYL"), but could be any other categorical variable.
data	An R object, normally a data frame, containing the data from PIRLS.
export	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
name	The name of the exported file.
folder	The folder where the exported file is located.
config	Object with configuration of a given study. Should contain the slot 'prefixes' with prefixes of filenames with the student, home, school, and teacher data.

Value

intsvy.rho returns a matrix including correlation and standard error values.

See Also

timss.rho, pirls.rho.pv, timss.rho.pv

Examples

```
## Not run:
pirls.rho(variables=c("ASRREA01", "ASDAGE"), by="IDCNTRYL", data=pirls)

## End(Not run)
```

intsvy.rho.pv

Two-way weighted correlation with plausible values

Description

intsvy.rho.pv calculates the correlation and standard error among two achievement variables each based on 5 plausible values or one achievement variable and an observed variable (i.e., with observed scores rather than plausible values).

Usage

```
intsvy.rho.pv(variable, pvnames, by, data, export=FALSE,
name= "output", folder=getwd(), config)
```

Arguments

variable	A data label for the observed variable
pvnames	One or two labels describing the achievement variables.
by	The label for the grouping variable, usually the countries (i.e., by="IDCNTRYL"), but could be any other categorical variable.
data	An R object, normally a data frame, containing the data.
export	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
name	The name of the exported file.
folder	The folder where the exported file is located.
config	Object with configuration of a given study. Should contain the slot 'prefixes' with prefixes of filenames with the student, home, school, and teacher data.

Value

intsvy.rho returns a matrix including correlation and standard error values.

See Also

timss.rho, pirls.rho.pv, timss.rho.pv

Examples

```
## Not run:
timss.rho.pv(variable="BSDGEDUP", pvlabel="BSMMAT", by="IDCNTYRL", data=timss)

## End(Not run)
```

intsvy.select.merge *Select and merge data*

Description

intsvy.select.merge selects and merges data from different international assessment studies. It was developed and it is particularly handy for importing IEA data since original files are organised by instrument, country, grade, etc., in a large number of files. Achievement and weight variables (all of them) are selected by default.

Usage

```
intsvy.select.merge(folder = getwd(), countries, student = c(), home,
  school, teacher, config)
```

Arguments

folder	Directory path where the data are located. The data could be organised within folders but duplicated files should be avoided.
countries	The selected countries, supplied with the abbreviation (e.g., countries=c("AUT", "BGR")) or codes (countries=c(40, 100)). If no countries are selected, all are selected.
student	The data labels for the selected student variables.
home	The data labels for the selected home background variables.
school	The data labels for the selected school variables.
teacher	The data labels for the selected teacher data.
config	Object with configuration of a given study. Should contain the slot 'prefixes' with prefixes of filenames with the student, home, school, and teacher data.

Value

intsvy.select.merge returns a data frame with the selected data from study defined in config file.

See Also

timssg4.select.merge, timssg8.select.merge, pisa.select.merge

Examples

```
## Not run:
pirls <- intsvy.select.merge(folder= getwd(),
  countries= c("AUS", "AUT", "AZE", "BFR"),
  student= c("ITSEX", "ASDAGE", "ASBGSMR"),
  home= c("ASDHEDUP", "ASDHOCCP", "ASDHELA", "ASBHELA"),
  school= c("ACDGDAS", "ACDGCMP", "ACDG03"),
  config = pirls_conf)

pirls <- intsvy.select.merge(folder= getwd(),
  countries= c(36, 40, 31, 957),
  student= c("ITSEX", "ASDAGE", "ASBGSMR"),
  home= c("ASDHEDUP", "ASDHOCCP", "ASDHELA", "ASBHELA"),
  school= c("ACDGDAS", "ACDGCMP", "ACDG03"),
  config = pirls_conf)

timss8g <- intsvy.select.merge(folder= getwd(),
  countries=c("AUS", "BHR", "ARM", "CHL"),
  student =c("BSDGEDUP", "ITSEX", "BSDAGE", "BSBGSLM", "BSDGSLM"),
  school=c("BCBGDAS", "BCDG03"), config = timss8_conf)

icils <- intsvy.select.merge(folder= getwd(),
  countries=c("AUS", "POL", "SVK"),
  student =c("S_SEX", "S_TLANG", "S_MISEI"),
  school =c("IP1G02J", "IP1G03A"),
  config = icils_conf)

pisa <- pisa.select.merge(folder= getwd(),
  school.file="INT_SCQ12_DEC03.sav",
  student.file="INT_STU12_DEC03.sav",
  student= c("ST01Q01", "ST04Q01", "ESCS", "PARED"),
  school = c("CLSIZ", "TCSHORT"),
  countries = c("HKG", "USA", "SWE", "POL", "PER"))

## End(Not run)
```

intsvy.table

*Frequency table***Description**

intsvy.table produces a frequency table for a categorical variable printing percentages and standard errors.

Usage

```
intsvy.table(variable, by, data, config)
```

Arguments

variable	The data label with the variable to be analysed.
by	The label for the grouping variable, usually the countries (i.e., by="IDCNTRYL"), but could be any other categorical variable.
data	An R object, normally a data frame, containing the data from PISA.
config	Object with configuration of a given study. Should contain the slot 'prefixes' with prefixes of filenames with the student, home, school, and teacher data.

Value

`intsvy.table` returns a data frame with percentages and standard errors.

See Also

`timss.table`, `pirls.table`

Examples

```
## Not run:
intsvy.table(variable="ASDGSLM", by="IDCNTRYL", data=timss4,
  config = intsvy::timss_conf)
intsvy.table(variable="ST08Q01", by="CNT", data=pisa, config=pisa_conf)

## End(Not run)
```

<code>intsvy.var.label</code>	<i>Data labels</i>
-------------------------------	--------------------

Description

`intsvy.var.labels` prints and saves variable labels and names of participating countries in a text file. The function is called by `timssg4.var.label`, `timssg8.var.label`, `pirls.var.label` and `pisa.var.label`.

Usage

```
intsvy.var.label(folder = getwd(), name = "Variable labels", output = getwd(),
  config)
```

Arguments

folder	Directory path where the data files are located. The data could be organized within folders but duplicated files should be avoided. It is assumed that data is in 'sav' files. For TIMSS, PIRLS and ICILS studies the data can be downloaded from http://rms.iea-dpc.org/ .
name	Name of the output file.

output	Folder where the output file is located.
config	Object with configuration of a given study. Should contain the slot 'prefixes' with prefixes of filenames with the student, home, school, and teacher data.

Value

intsvy.var.label returns a list with variable labels for the student, home, school, and teacher data (if applied).

See Also

timssg4.var.label, timssg8.var.label, pirls.var.label, pisa.var.label

Examples

```
## Not run:
intsvy.var.label(folder= getwd(), config = pirls_conf)
intsvy.var.label(folder= getwd(), config = timss8_conf)
intsvy.var.label(folder= getwd(), config = icils_conf)
intsvy.var.label(folder= getwd(), config = piaac_conf)

## End(Not run)
```

piaac.ben.pv

PIAAC proficiency levels

Description

Calculates percentage of population at each proficiency level defined by PIAAC. Or at proficiency levels provided by the user.

Usage

```
piaac.ben.pv(pvlabel, by, data, cutoff, atlevel, export=FALSE,
            name= "output", folder=getwd())
```

Arguments

pvlabel	The label corresponding to the achievement variable, for example, "LIT", for overall reading performance.
by	The label for the grouping variable, usually the countries (i.e., by="CNTRYID"), but could be any other categorical variable.
cutoff	The cut-off points for the assessment benchmarks (e.g., cutoff= c(357.77, 420.07, 482.38, 544.68, 606.99, 669.30)).
data	An R object, normally a data frame, containing the data from PIAAC.
atlevel	A logical value. If TRUE, percentages at each level are calculated. Otherwise (FALSE), percentages at or above levels are reported.

export	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
name	The name of the exported file.
folder	The folder where the exported file is located.

Value

piaac.ben.pv returns a data frame with the percentage of students at each proficiency level and its corresponding standard error.

The total weight, "TOTWGT" and the cut-off points or benchmarks are defined in the config object.

See Also

timss.ben.pv, pirls.ben.pv, pisa.ben.pv

Examples

```
## Not run:
#Table A2.5
#Percentage of adults scoring at each proficiency level in numeracy
piaac.ben.pv(pvlabel="NUM", by="CNTRYID", data=piaac)
#Table A2.1
#Percentage of adults scoring at each proficiency level in literacy
piaac.ben.pv(pvlabel="LIT", by="CNTRYID", data=piaac)

## End(Not run)
```

piaac.mean

Calculates mean of variable in PIAAC data

Description

Calculates the mean of an observed variable (NOT one with plausible values) and its standard error.

Usage

```
piaac.mean(variable, by, data, export = FALSE,
name = "output", folder = getwd())
```

Arguments

variable	The label corresponding to the observed variable, for example, "AGE_R" for age of respondent.
by	The label for the grouping variable, usually the countries (i.e., by="CNTRYID"), but could be any other categorical variable.
data	An R object, normally a data frame, containing the data from PIAAC.

export	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
name	The name of the exported file.
folder	The folder where the exported file is located.

Value

piaac.mean returns a data frame with means and standard errors.

See Also

pisa.mean, timss.mean, pirls.mean

Examples

```
## Not run:
# install pbierek/PIAAC package from github to have access to piaac data
piaac.mean(variable="AGE_R", by="CNTRYID", data=piaac)

## End(Not run)
```

piaac.mean.pv

Calculates mean achievement score for PIAAC data

Description

piaac.mean.pv uses ten plausible values to calculate the mean achievement score and its standard error

Usage

```
piaac.mean.pv(pvlabel, by, data, export = FALSE, name = "output", folder = getwd())
```

Arguments

pvlabel	The label corresponding to the achievement variable, for example, "LIT", for overall literacy performance, "NUM" for numeracy, "PSL" for problem solving.
by	The label for the grouping variable, usually the countries (i.e., by="CNTRYID"), but could be any other categorical variable.
data	An R object, normally a data frame, containing the data from PIAAC.
export	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
name	The name of the exported file.
folder	The folder where the exported file is located.

Value

`piaac.mean.pv` returns a data frame with the mean values and standard errors.

See Also

`pisa.mean.pv`, `timss.mean.pv`, `pirls.mean.pv`

Examples

```
## Not run:
# install pbierek/PIAAC package from github to have access to piaac data
piaac.mean.pv(pvlabel = "LIT", by = "CNTRYID", data = piaac)
piaac.mean.pv(pvlabel = "NUM", by=c("CNTRYID", "GENDER_R"), data=piaac)

## End(Not run)
```

`piaac.reg`

Regression analysis for PIAAC

Description

`piaac.reg` performs linear regression analysis (OLS) for an observed dependent variable (NOT for plausible values)

Usage

```
piaac.reg(y, x, by, data, export = FALSE, name = "output", folder = getwd())
```

Arguments

<code>y</code>	Label for dependent variable.
<code>x</code>	Data labels of independent variables.
<code>by</code>	The label for the grouping variable, usually the countries (i.e., <code>by="CNTRYID"</code>), but could be any other categorical variable.
<code>data</code>	An R object, normally a data frame, containing the data from PIAAC.
<code>export</code>	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
<code>name</code>	The name of the exported file.
<code>folder</code>	The folder where the exported file is located.

Value

`piaac.reg` returns a data frame with coefficients, standard errors and t-values. If "by" is specified, results are reported in a list. If the "by" argument is set, then the returning object is of the class "intsy.reg" with overloaded function `plot()`.

See Also

pisa.reg, pirls.reg, timss.reg

Examples

```
## Not run:
# install pbierek/PIAAC package from github to have access to piaac data
piaac.reg(y="AGE_R", x="GENDER_R", by="CNTRYID", data=piaac)

## End(Not run)
```

piaac.reg.pv

Regression analysis with plausible values for PIAAC

Description

piaac.reg.pv performs linear regression analysis (OLS) with plausible values and replicate weights.

Usage

```
piaac.reg.pv(x, pvlabel = "LIT", by, data,
export = FALSE, name = "output", std=FALSE, folder = getwd())
```

Arguments

x	Data labels of independent variables.
pvlabel	The label corresponding to the achievement variable, for example, "LIT", for overall literacy performance, "NUM" for numeracy, "PSL" for problem solving.
by	The label for the grouping variable, usually the countries (i.e., by="CNTRYID"), but could be any other categorical variable.
data	An R object, normally a data frame, containing the data from PIAAC.
export	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
name	The name of the exported file.
std	A logical value. If TRUE standardised regression coefficients are calculated.
folder	The folder where the exported file is located.

Value

piaac.reg.pv returns a data frame with coefficients, standard errors and t-values. If "by" is specified, results are reported in a list. If the "by" argument is set, then the returning object is of the class "intsvy.reg" with overloaded function plot().

See Also

pisa.reg.pv, timss.reg.pv, pirls.reg.pv

Examples

```
## Not run:
# install pbiemek/PIAAC package from github to have access to piaac data
piaac.reg.pv(pvlabel="LIT", x="GENDER_R", by = "CNTRYID", data=piaac)

## End(Not run)
```

piaac.table	<i>Frequency table</i>
-------------	------------------------

Description

piaac.table produces a frequency table for a categorical variable printing percentages and standard errors.

Usage

```
piaac.table(variable, by, data, export = FALSE, name = "output", folder = getwd())
```

Arguments

variable	The data label with the variable to be analysed.
by	The label for the grouping variable, usually the countries (i.e., by="CNTRYID"), but could be any other categorical variable.
data	An R object, normally a data frame, containing the data from PIAAC.
export	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
name	The name of the exported file.
folder	The folder where the exported file is located.

Value

piaac.table returns a data frame with percentages and standard errors.

See Also

pisa.table, timss.table, pirls.table

Examples

```
## Not run:
# install pbiemek/PIAAC package from github to have access to piaac data
piaac.table(variable="I_Q06A", by="CNTRYID", data=piaac)
piaac.table(variable="GENDER_R", by="CNTRYID", data=piaac)

## End(Not run)
```

pirls.ben.pv *PIRLS international benchmarks*

Description

pirls.ben.pv calculates the percentage of students performing at or above the cut-off points (scores) given by the useR. The default are the benchmarks established by PIRLS/TIMSS.

Usage

```
pirls.ben.pv(pvlabel, by, cutoff, data, atlevel=FALSE,
export = FALSE, name = "output", folder = getwd())
```

Arguments

pvlabel	The label corresponding to the achievement variable, for example, "ASRREA", for overall reading performance.
cutoff	The cut-off points for the assessment benchmarks (e.g., cutoff = c(400, 475, 550, 625).
by	The label for the grouping variable, usually the countries (i.e., by="IDCNTRYL"), but could be any other categorical variable.
data	An R object, normally a data frame, containing the data from PIRLS.
atlevel	A logical value. If TRUE, percentages at each level are calculated. Otherwise (FALSE), percentages at or above levels are reported.
export	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
name	The name of the exported file.
folder	The folder where the exported file is located.

Value

pirls.ben.pv returns a data frame with the percentage of students at or above the benchmark and the corresponding standard error.

The total weight, "TOTWGT" and the cut-off points or benchmarks are defined in the config object.

See Also

timss.ben.pv, pisa.ben.pv

Examples

```
## Not run:
pirls.ben.pv(pvlabel="ASRREA", by="IDCNTRYL", data=pirls)

## End(Not run)
```

pirls.log

*Logistic regression analysis***Description**

pirls.log performs logistic regression analysis for an observed dependent variable (NOT for plausible values)

Usage

```
pirls.log(y, x, by, data, export = FALSE,
name = "output", folder = getwd())
```

Arguments

y	Label for dependent variable
x	Data labels of independent variables (e.g., x = c("ASDHEHLA", "ITSEX")).
by	The label for the grouping variable, usually the countries (i.e., by="IDCNTRYL"), but could be any other categorical variable.
data	An R object, normally a data frame, containing the data from PIRLS.
export	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
name	The name of the exported file.
folder	The folder where the exported file is located.

Value

pirls.log prints a data frame with coefficients, standard errors, t-values, and odds ratios. Results are stored in a list object of class "intsvy.reg".

See Also

timss.log, pisa.log

Examples

```
## Not run:

pisa$SKIP[!(pisa$ST09Q01 == "None" & pisa$ST115Q01 == "None")] <- 1
pisa$SKIP[pisa$ST09Q01 == "None" & pisa$ST115Q01 == "None"] <- 0

pisa$LATE[!pisa$ST08Q01 == "None"] <- 1
pisa$LATE[pisa$ST08Q01 == "None"] <- 0

pisa.log(y="SKIP", x="LATE", by="IDCNTRYL", data = pisa)

## End(Not run)
```

pirls.log.pv

*Logistic regression analysis with plausible values***Description**

pirls.log.pv performs logistic regression with plausible values and replicate weights.

Usage

```
pirls.log.pv(pvlabel="ASRREA", x, cutoff, by,
            data, export=FALSE, name= "output", folder=getwd())
```

Arguments

pvlabel	The label corresponding to the achievement variable, for example, "ASRREA", for overall reading performance.
x	Data labels of independent variables.
cutoff	The cut-off point at which the dependent plausible values scores are dichotomised (1 is larger than the cut-off)
by	The label for the categorical grouping variable (i.e., by="IDCNTRYL") or variables (e.g., x= c("IDCNTRYL", "ITSEX")).
data	An R object, normally a data frame, containing the data from PIRLS.
export	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
name	The name of the exported file.
folder	The folder where the exported file is located.

Value

pirls.log.pv returns a data frame with coefficients, standard errors, t-values, and odds ratios. If "by" is specified, results are reported in a list.

See Also

pisa.log.pv, timss.log.pv

Examples

```
## Not run:
timss.log.pv(pvlabel="BSMMAT", cutoff= 550, x=c("ITSEX", "BSBGSLM"), by="IDCNTRYL", data=timss8g)
intsvy.log.pv(pvlabel="BSMMAT", cutoff= 550, x="ITSEX", by="IDCNTRYL",
             data=timss8g, config=timss8_conf)

## End(Not run)
```

pirls.mean	<i>Calculates mean of variable</i>
------------	------------------------------------

Description

Calculates the mean of an observed variable (NOT one with plausible values) and its standard error.

Usage

```
pirls.mean(variable, by, data,  
export = FALSE, name = "output", folder = getwd())
```

Arguments

variable	The label corresponding to the observed variable, for example, "ASDAGE", for the age of the student.
by	The label for the grouping variable, usually the countries (i.e., by="IDCNTRYL"), but could be any other categorical variable.
data	An R object, normally a data frame, containing the data from PIRLS.
export	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
name	The name of the exported file.
folder	The folder where the exported file is located.

Value

pirls.mean returns a data frame with means and standard errors.

See Also

timss.mean, pisa.mean

Examples

```
## Not run:  
pirls.mean(variable='ASBHELA', by= 'IDCNTRYL', data=pirls)  
  
## End(Not run)
```

pirls.mean.pv

Calculates mean achievement score

Description

pirls.mean.pv uses five plausible values to calculate the mean achievement score and its standard error

Usage

```
pirls.mean.pv(pvlabel = "ASRREA", by,  
data, export = FALSE, name = "output", folder = getwd())
```

Arguments

pvlabel	The label corresponding to the achievement variable, for example, "ASRREA", for overall reading performance.
by	The label for the grouping variable, usually the countries (i.e., by="IDCNTRYL"), but could be any other categorical variable.
data	An R object, normally a data frame, containing the data from PIRLS.
export	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
name	The name of the exported file.
folder	The folder where the exported file is located.

Value

pirls.mean.pv returns a data frame with the mean values and standard errors.

See Also

timss.mean.pv, pisa.mean.pv

Examples

```
## Not run:  
pirls.mean.pv(pvlabel="ASRREA", by= "IDCNTRYL", data=pirls)  
pirls.mean.pv(pvlabel="ASRREA", by= c("IDCNTRYL", "ITSEX"), data=pirls)  
  
## End(Not run)
```

pirls.per.pv

PIRLS percentiles

Description

Calculates percentiles for plausible values

Usage

```
pirls.per.pv(pvlabel="ASRREA", by, per, data, export=FALSE,
name= "output", folder=getwd())
```

Arguments

pvlabel	The label corresponding to the achievement variable, for example, "ASRREA", for overall reading performance.
per	User-defined percentiles (e.g., per = c(5, 10, 25, 75, 90, 95)).
by	The label of the categorical grouping variable (e.g., by="IDCNTRYL") or variables (e.g., by=c("IDCNTRYL", "ITSEX")).
data	An R object, normally a data frame, containing the data from PIRLS.
export	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
name	The name of the exported file.
folder	The folder where the exported file is located.

Value

pirls.per.pv returns a data frame with percentiles and associated standard errors. Default weights (e.g. "TOTWGT" in TIMSS) and percentiles are specified in the config parameter.

See Also

pisa.per.pv, timss.per.pv

Examples

```
## Not run:
pirls.per.pv(pvlabel="ASRREA", per = c(5, 10, 25, 50, 75, 90, 95), by="IDCNTRYL", data=pirls)

## End(Not run)
```

pirls.reg

*Regression analysis***Description**

pirls.reg performs linear regression analysis (OLS) for an observed dependent variable (NOT for plausible values)

Usage

```
pirls.reg(y, x, by, data, export = FALSE,
name = "output", folder = getwd())
```

Arguments

y	Label for dependent variable
x	Data labels of independent variables (e.g., x = c("ASDHEHLA", "ITSEX")).
by	The label for the grouping variable, usually the countries (i.e., by="IDCNTRYL"), but could be any other categorical variable.
data	An R object, normally a data frame, containing the data from PIRLS.
export	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
name	The name of the exported file.
folder	The folder where the exported file is located.

Value

pirls.reg prints a data.frame with regression results (i.e., coefficients, standard errors, t-values, R-squared) and stores different regression output including residuals and replicate coefficients in a list object of class "intsvy.reg".

See Also

timss.reg

Examples

```
## Not run:

# Recode ASBGB00K
table(as.numeric(pirls$ASBGB00K), pirls$ASBGB00K)
pirls$BOOK[as.numeric(pirls$ASBGB00K)==1] <- 5
pirls$BOOK[as.numeric(pirls$ASBGB00K)==2] <- 18
pirls$BOOK[as.numeric(pirls$ASBGB00K)==3] <- 63
pirls$BOOK[as.numeric(pirls$ASBGB00K)==4] <- 151
pirls$BOOK[as.numeric(pirls$ASBGB00K)==5] <- 251
```

```
table(pirls$BOOK)

pirls.reg(y= "BOOK", x= "ITSEX", by="IDCNTRYL", data=pirls)

## End(Not run)
```

pirls.reg.pv

Regression analysis with plausible values

Description

pirls.reg.pv performs linear regression analysis (OLS) with plausible values and replicate weights.

Usage

```
pirls.reg.pv(x, pvlabel = "ASRREA", by,
data, std=FALSE, export = FALSE, name = "output", folder = getwd())
```

Arguments

x	Data labels of independent variables (e.g., x = c("ASDHEHLA", "ITSEX")).
pvlabel	The label corresponding to the achievement variable, for example, "ASRREA", for overall reading performance.
by	The label for the grouping variable, usually the countries (i.e., by="IDCNTRYL"), but could be any other categorical variable.
data	An R object, normally a data frame, containing the data from PIRLS.
std	A logical value. If TRUE standardised regression coefficients are calculated.
export	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
name	The name of the exported file.
folder	The folder where the exported file is located.

Value

pirls.reg.pv prints a data.frame with regression results (i.e., coefficients, standard errors, t-values, R-squared) and stores different regression output including residuals, replicate coefficients, variance within and between, and the regression data.frame in a list object of class "intsvy.reg".

See Also

timss.reg.pv, pisa.reg.pv

Examples

```
## Not run:
pirls$SEX[pirls$ITSEX=="BOY"]=1
pirls$SEX[pirls$ITSEX=="GIRL"]=0
pirls.reg.pv(pvlabel="ASRREA", by="IDCNTRYL", x="SEX", data=pirls)

## End(Not run)
```

pirls.rho *Correlation matrix*

Description

pirls.rho produces a correlation matrix for observed variables (NOT for plausible values)

Usage

```
pirls.rho(variables, by, data,
export = FALSE, name = "output", folder = getwd())
```

Arguments

variables	Data labels for the variables in the correlation matrix (e.g., variables=c("ASRREA01", "ASDAGE"))
by	The label for the grouping variable, usually the countries (i.e., by="IDCNTRYL"), but could be any other categorical variable.
data	An R object, normally a data frame, containing the data from PIRLS.
export	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
name	The name of the exported file.
folder	The folder where the exported file is located.

Value

pirls.rho returns a matrix including correlation and standard error values.

See Also

timss.rho, pirls.rho.pv, timss.rho.pv

Examples

```
## Not run:
pirls.rho(variables=c("ASRREA01", "ASDAGE"), by="IDCNTRYL", data=pirls)

## End(Not run)
```

pirls.rho.pv

Two-way weighted correlation with plausible values

Description

pirls.rho.pv calculates the correlation and standard error among two achievement variables each based on 5 plausible values or one achievement variable and an observed variable (i.e., with observed scores rather than plausible values).

Usage

```
pirls.rho.pv(variable, pvlabel, by,
data, export = FALSE, name = "output", folder = getwd())
```

Arguments

variable	A data label for the observed variable (e.g., variable="ASDAGE")
pvlabel	One or two labels describing the achievement variables (e.g., pvlabels = c("ASRLIT", "ASRINF"))
by	The label for the grouping variable, usually the countries (i.e., by="IDCOUNTRYL"), but could be any other categorical variable.
data	An R object, normally a data frame, containing the data from PIRLS.
export	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
name	The name of the exported file.
folder	The folder where the exported file is located.

Value

pirls.rho.pv returns a matrix with correlations and standard errors.

See Also

timss.rho.pv, pirls.rho, timss.rho

Examples

```
## Not run:
pirls.rho.pv(pvlabels=c("ASRLIT", "ASRINF"), by="IDCOUNTRYL", data=pirls)

## End(Not run)
```

pirls.select.merge *Select and merge data*

Description

pirls.select.merge selects and merges data from PIRLS. Achievement and weight variables (all of them) are selected by default.

Usage

```
pirls.select.merge(folder = getwd(), countries, student = c(),
  home, school, teacher)
```

Arguments

folder	Directory path where the data are located. The data could be organized within folders but it should not be duplicated.
countries	The selected countries, supplied with the abbreviation (e.g., countries=c("AUT", "BGR")) or codes (countries=c(40, 100)). If no countries are selected, all are selected.
student	The data labels for the selected student variables.
home	The data labels for the selected home background variables.
school	The data labels for the selected school variables.
teacher	The data labels for the selected teacher data.

Value

pirls.select.merge returns a data frame with the selected data from PIRLS.

See Also

timssg4.select.merge, timssg8.select.merge, pisa.select.merge

Examples

```
## Not run:
pirls <- pirls.select.merge(folder= getwd(),
  countries= c(36, 40, 31, 957),
  student= c("ITSEX", "ASDAGE", "ASBGSMR"),
  home= c("ASDHEDUP", "ASDHOCPP", "ASDHELA", "ASBHELA"),
  school= c("ACGDAS", "ACDGCMP", "ACDG03"))

## End(Not run)
```

pirls.table	<i>Frequency table</i>
-------------	------------------------

Description

pirls.table produces a frequency table for a categorical variable printing percentages and standard errors. Information about weight is extracted from `intsvy::pirls_conf`.

Usage

```
pirls.table(variable, by, data,  
export = FALSE, name = "output", folder = getwd())
```

Arguments

variable	The data label with the variable to be analysed.
by	The label for the grouping variable, usually the countries (i.e., <code>by="IDCNTRYL"</code>), but could be any other categorical variable.
data	An R object, normally a data frame, containing the data from PIRLS.
export	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
name	The name of the exported file.
folder	The folder where the exported file is located.

Value

pirls.table returns a data frame with percentages and standard errors.

See Also

`timss.table`, `pisa.table`

Examples

```
## Not run:  
pirls.table(variable="ASDHELA", by="IDCNTRYL", data=pirls)  
  
## End(Not run)
```

pirls.var.label	<i>Data labels</i>
-----------------	--------------------

Description

pirls.var.labels prints and saves variable labels and names of participating countries in a text file

Usage

```
pirls.var.label(folder = getwd(), name = "Variable labels", output = getwd())
```

Arguments

folder	Directory path where the PIRLS data are located. The data could be organized within folders but it should not be duplicated.
name	Name of output file.
output	Folder where output file is located.

Value

pirls.var.label returns a list with variable labels for the student, home, school, and teacher data.

See Also

timssg4.var.label, timssg8.var.label, pisa.var.label

Examples

```
## Not run:  
pirls.var.label(folder= getwd())  
  
## End(Not run)
```

pisa.ben.pv	<i>PISA proficiency levels</i>
-------------	--------------------------------

Description

Calculates percentage of students at each proficiency level defined by PISA. Or at proficiency levels provided by the user.

Usage

```
pisa.ben.pv(pvlabel, by, cutoff, data, atlevel=FALSE,  
export=FALSE, name= "output", folder=getwd())
```

Arguments

pvlabel	The label corresponding to the achievement variable, for example, "READ", for overall reading performance.
cutoff	The cut-off points for the assessment benchmarks (e.g., cutoff= c(357.77, 420.07, 482.38, 544.68, 606.99, 669.30)).
by	The label for the grouping variable, usually the countries (i.e., by="IDCNTRYL"), but could be any other categorical variable.
data	An R object, normally a data frame, containing the data from PISA.
atlevel	A logical value. If TRUE, percentages at each level are calculated. Otherwise (FALSE), percentages at or above levels are reported.
export	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
name	The name of the exported file.
folder	The folder where the exported file is located.

Value

pisa.ben.pv returns a data frame with the percentage of students at each proficiency level and its corresponding standard error.

The total weight, "TOTWGT" and the cut-off points or benchmarks are defined in the config object.

See Also

timss.ben.pv, pirls.ben.pv

Examples

```
## Not run:
pisa.ben.pv(pvlabel="MATH", by="IDCNTRYL", atlevel=TRUE, data=pisa)

## End(Not run)
```

pisa.log

Logistic regression analysis

Description

pisa.log performs logistic regression analysis (OLS) for an observed dependent variable (NOT for plausible values)

Usage

```
pisa.log(y, x, by, data, export=FALSE, name= "output", folder=getwd())
```

Arguments

y	Label for dependent variable.
x	Data labels of independent variables.
by	The label for the grouping variable, usually the countries (i.e., by="CNT"), but could be any other categorical variable.
data	An R object, normally a data frame, containing the data from PISA.
export	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
name	The name of the exported file.
folder	The folder where the exported file is located.

Value

pisa.log prints a data.frame with regression results (i.e., coefficients, standard errors, t-values, R-squared) and stores replicate estimates and other regression output in a list object of class "intsvy.reg".

See Also

pirls.log, timss.log

Examples

```
## Not run:

pisa$SKIP[!(pisa$ST09Q01=="None" & pisa$ST115Q01=="None")] <- 1
pisa$SKIP[pisa$ST09Q01=="None" & pisa$ST115Q01=="None"] <- 0

pisa$LATE[!pisa$ST08Q01=="None"] <- 1
pisa$LATE[pisa$ST08Q01=="None"] <- 0

pisa.log(y="SKIP", x="LATE", by="IDCNTRYL", data = pisa)

## End(Not run)
```

pisa.log.pv

Logistic regression analysis with plausible values

Description

pisa.log.pv performs logistic regression with plausible values and replicate weights.

Usage

```
pisa.log.pv(pvlabel="READ", x, by, cutoff,
            data, export=FALSE, name= "output", folder=getwd())
```

Arguments

pvlabel	The label corresponding to the achievement variable, for example, "READ", for overall reading performance.
x	Data labels of independent variables.
cutoff	The cut-off point at which the dependent plausible values scores are dichotomised (1 is larger than the cut-off)
by	The label for the categorical grouping variable (i.e., by="IDCNTRYL") or variables (e.g., x= c("IDCNTRYL", "ST79Q03")).
data	An R object, normally a data frame, containing the data from PISA.
export	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
name	The name of the exported file.
folder	The folder where the exported file is located.

Value

pisa.log.pv returns a data frame with coefficients, standard errors, t-values, and odds ratios. If "by" is specified, results are reported in a list.

See Also

timss.log.pv, pirls.log.pv

Examples

```
## Not run:
timss.log.pv(pvlabel="BSMMAT", cutoff= 550, x=c("ITSEX", "BSBGSLM"), by="IDCNTRYL", data=timss8g)
intsvy.log.pv(pvlabel="BSMMAT", cutoff= 550, x="ITSEX", by="IDCNTRYL",
data=timss8g, config=timss8_conf)

## End(Not run)
```

pisa.mean

Calculates mean of variable

Description

Calculates the mean of an observed variable (NOT one with plausible values) and its standard error.

Usage

```
pisa.mean(variable, by, data, export = FALSE,
name = "output", folder = getwd())
```


Arguments

variable	The label corresponding to the observed variable, for example, ""ESCS"", for the student SES.
by	The label for the grouping variable, usually the countries (i.e., by="IDCNTRYL"), but could be any other categorical variable.
data	An R object, normally a data frame, containing the data from PISA.
export	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
name	The name of the exported file.
folder	The folder where the exported file is located.

Value

pisa.mean returns a data frame with means and standard errors.

See Also

timss.mean, pirls.mean, piaac.mean

Examples

```
## Not run:
pisa.mean(variable="ESCS", by="IDCNTRYL", data=pisa)
pisa.mean(variable="PARED", by="IDCNTRYL", data=pisa)

pisa.mean(variable="BELONG", by="IDCNTRYL", data=pisa)
pisa.mean(variable="BELONG", by=c("IDCNTRYL", "ST04Q01"), data=pisa)

## End(Not run)
```

pisa.mean.pv

Calculates mean achievement score

Description

pisa.mean.pv uses five plausible values to calculate the mean achievement score and its standard error

Usage

```
pisa.mean.pv(pvlabel, by, data, export = FALSE, name = "output",
             folder = getwd())
```

Arguments

pvlabel	The label corresponding to the achievement variable, for example, "READ", for overall reading performance.
by	The label for the grouping variable, usually the countries (i.e., by="IDCNTRYL"), but could be any other categorical variable.
data	An R object, normally a data frame, containing the data from PIRLS.
export	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
name	The name of the exported file.
folder	The folder where the exported file is located.

Value

pisa.mean.pv returns a data frame with the mean values and standard errors.

See Also

timss.mean.pv, pirls.mean.pv, pиаac.mean.pv

Examples

```
## Not run:
pisa.mean.pv(pvlabel = "MATH", by = "IDCNTRYL", data = pisa)
pisa.mean.pv(pvlabel = "MATH", by = c("IDCNTRYL", "ST04Q01"), data = pisa)
pisa.mean.pv(pvlabel = "READ", by = "IDCNTRYL", data = pisa)

## End(Not run)
```

pisa.per.pv

PISA percentiles

Description

Calculates percentiles for plausible values.

Usage

```
pisa.per.pv(pvlabel="READ", by, per, data, export=FALSE, name= "output",
folder=getwd())
```

Arguments

pvlabel	The label corresponding to the achievement variable, for example, "READ", for overall reading performance.
per	User-defined percentiles (e.g., per = c(5, 10, 25, 75, 90, 95)).
by	The label of the categorical grouping variable (e.g., by="IDCNTRYL") or variables (e.g., by=c("IDCNTRYL", "ST79Q03")).
data	An R object, normally a data frame, containing the data from PISA.
export	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
name	The name of the exported file.
folder	The folder where the exported file is located.

Value

pisa.per.pv returns a data frame with percentiles and associated standard errors. Default weights (e.g. "TOTWGT" in TIMSS) and percentiles are specified in the config parameter.

See Also

timss.per.pv, pirls.per.pv

Examples

```
## Not run:  
pisa.per.pv(pvlabel="MATH", per=c(10, 25, 75, 90), by="IDCNTRYL", data=pisa)  
  
## End(Not run)
```

pisa.reg

Regression analysis

Description

pisa.reg performs linear regression analysis (OLS) for an observed dependent variable (NOT for plausible values)

Usage

```
pisa.reg(y, x, by, data, export = FALSE, name = "output", folder = getwd())
```

Arguments

y	Label for dependent variable.
x	Data labels of independent variables.
by	The label for the grouping variable, usually the countries (i.e., by="IDCNTRYL"), but could be any other categorical variable.
data	An R object, normally a data frame, containing the data from PISA.
export	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
name	The name of the exported file.
folder	The folder where the exported file is located.

Value

pisa.reg prints a data.frame with regression results (i.e., coefficients, standard errors, t-values, R-squared) and stores different regression output including residuals and replicate coefficients in a list object of class "intsvy.reg".

See Also

pirls.reg, timss.reg, piaac.reg

Examples

```
## Not run:
pisa.reg(y="BELONG", x="ST04Q01", by="IDCNTRYL", data=pisa)

## End(Not run)
```

pisa.reg.pv

Regression analysis with plausible values

Description

pisa.reg.pv performs linear regression analysis (OLS) with plausible values and replicate weights.

Usage

```
pisa.reg.pv(x, pvlabel = "READ", by, data,
export = FALSE, name = "output", folder = getwd(), std=FALSE)
```

Arguments

x	Data labels of independent variables.
pvlabel	The label corresponding to the achievement variable, for example, "READ", for overall reading performance.
by	The label for the grouping variable, usually the countries (i.e., by="IDCNTRYL"), but could be any other categorical variable.
data	An R object, normally a data frame, containing the data from PISA.
export	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
name	The name of the exported file.
folder	The folder where the exported file is located.
std	A logical value. If TRUE standardised regression coefficients are calculated.

Value

pisa.reg.pv prints a data.frame with regression results (i.e., coefficients, standard errors, t-values, R-squared) and stores different regression output including residuals, replicate coefficients, variance within and between, and the regression data.frame in a list object of class "intsvy.reg".

See Also

timss.reg.pv, pirls.reg.pv, piaac.reg.pv

Examples

```
## Not run:
pisa.reg.pv(pvlabel="MATH", x="ST04Q01", by = "IDCNTRYL", data=pisa)

## End(Not run)
```

pisa.rho

Correlation matrix

Description

pisa.rho produces a correlation matrix for observed variables (NOT for plausible values)

Usage

```
pisa.rho(variables, by, data, export=FALSE, name= "output", folder=getwd())
```

Arguments

variables	Data labels for the variables in the correlation matrix (e.g., variables=c("TCHBEHTD", "TCHBEHSO"))
by	The label for the grouping variable, usually the countries (i.e., by="IDCNTRYL"), but could be any other categorical variable.
data	An R object, normally a data frame, containing the data from PISA.
export	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
name	The name of the exported file.
folder	The folder where the exported file is located.

Value

pisa.rho returns a matrix including correlation and standard error values.

See Also

timss.rho, pirls.rho, pirls.rho.pv, timss.rho.pv

Examples

```
## Not run:
pisa.rho(variables=c("COGACT", "TCHBEHTD", "TCHBEHSO", "CLSMAN" ), by="IDCNTRYL", data=pisa)

## End(Not run)
```

pisa.select.merge *Select and merge data*

Description

pisa.select.merge selects and merges data from PISA. Achievement and weight variables (all of them) are selected by default.

Usage

```
pisa.select.merge(folder=getwd(), student.file, parent.file=c(), school.file=c(),
countries, student=c(), parent, school)
```

Arguments

folder	Directory path where the PISA data are located, if all the data are located in the same folder.
student.file	Student file name if 'folder' is provided, otherwise full path name of student dataset (required argument).

parent.file	Parent file name if 'folder' is provided, otherwise full path name of parent dataset.
school.file	School file name if 'folder' is provided, otherwise full path name of school dataset.
countries	The selected countries, supplied with the abbreviation (e.g., countries=c("DEU", "NOR")) or codes. If no countries are selected, all are selected.
student	The data labels for the selected student variables.
parent	The data labels for the selected parental variables.
school	The data labels for the selected school variables.

Value

pisa.select.merge returns a data frame with the selected data from PISA.

See Also

timssg4.select.merge, timssg8.select.merge, pirls.select.merge

Examples

```
## Not run:
pisa <- pisa.select.merge(folder=getwd(),
  school.file="INT_SCQ12_DEC03.sav",
  student.file="INT_STU12_DEC03.sav",
  parent.file="INT_PAQ12_DEC03.sav",
  student= c("IMMIG", "ESCS", "ST04Q01", "ST61Q04", "ST62Q01", "ST08Q01"),
  parent = c("PARINVOL", "PARSUPP"),
  school = c("STRATIO", "SCHAUTON", "CLSIZE"),
  countries = c("HKG", "USA", "SWE", "POL", "PER"))

## End(Not run)
```

pisa.table	<i>Frequency table</i>
------------	------------------------

Description

pisa.table produces a frequency table for a categorical variable printing percentages and standard errors.

Usage

```
pisa.table(variable, by, data, export = FALSE, name = "output", folder = getwd())
```

Arguments

<code>variable</code>	The data label with the variable to be analysed.
<code>by</code>	The label for the grouping variable, usually the countries (i.e., <code>by="IDCNTRYL"</code>), but could be any other categorical variable.
<code>data</code>	An R object, normally a data frame, containing the data from PISA.
<code>export</code>	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
<code>name</code>	The name of the exported file.
<code>folder</code>	The folder where the exported file is located.

Value

`pisa.table` returns a data frame with percentages and standard errors.

See Also

`timss.table`, `pirls.table`

Examples

```
## Not run:
pisa.table(variable="ST01Q01", by="IDCNTRYL", data=pisa)
pisa.table(variable="ST08Q01", by="IDCNTRYL", data=pisa)

## End(Not run)
```

`pisa.var.label`

Data labels

Description

`pisa.var.labels` prints and saves variable labels and names of participating countries in a text file

Usage

```
pisa.var.label(folder=getwd(), student.file, parent.file=c(), school.file=c(),
name="Variable labels", output=getwd())
```

Arguments

<code>folder</code>	Directory path where the PISA data are located, if all the data are located in the same folder.
<code>student.file</code>	Student file name if 'folder' is provided, otherwise full path name of student dataset (required argument).
<code>parent.file</code>	Parent file name if 'folder' is provided, otherwise full path name of parent dataset.

school.file	School file name if 'folder' is provided, otherwise full path name of school dataset.
name	Name of output file.
output	Folder where output file is located.

Value

pisa.var.label returns a list with variable labels for the student, parent, and school data.

See Also

timssg4.var.label, timssg8.var.label, pirls.var.label

Examples

```
## Not run:
pisa.var.label(folder=getwd(), school.file="INT_SCQ12_DEC03.sav",
student.file="INT_STU12_DEC03.sav", parent.file="INT_PAQ12_DEC03.sav")

## End(Not run)
```

plot.intsvy.mean *Graphical representation of means in groups*

Description

Functions pisa.mean, pisa.mean.pv, piae.mean, piae.mean.pv produce object of the class intsvy.mean. The function plot.intsvy.mean presents these means graphically.

Usage

```
## S3 method for class 'intsvy.mean'
plot(x, se = TRUE, sort = FALSE, ...)
```

Arguments

x	An object of the class intsvy.mean returned by pisa.mean, pisa.mean.pv, piae.mean or piae.mean.pv functions.
se	If TRUE add whiskers for standard errors.
sort	If TRUE groups are sorted along averages.
...	Not used. Required for cran-check.

Value

Returns object of ggplot class with dotplot. Works for one way, two-way and three-way effects.

See Also

plot.intsvy.table, plot.intsvy.reg

Examples

```
## Not run:
# Country averages
head(pmeansNC <- piaac.mean.pv(pvlabel="NUM", by="CNTRYID", data=piaac, export=FALSE))

# plotting country average NUM performance
plot(pmeansNC) + ggtitle("Country performance in NUM")
# without se bars, not good idea
plot(pmeansNC, se=FALSE)
# sorted, thats better
plot(pmeansNC, sort=TRUE)

# Country averages for different age groups
head(pmeansNCA <- piaac.mean.pv(pvlabel="NUM", by=c("CNTRYID", "AGEG10LFS"),
                                data=piaac, export=FALSE))
#
# plotting country average within
# age groups NUM performance
plot(pmeansNCA, sort=TRUE)

# Country averages for different age and gender groups (changed order)
head(pmeansNCGA <- piaac.mean.pv(pvlabel="NUM", by=c("CNTRYID", "GENDER_R", "AGEG10LFS"),
                                data=piaac, export=FALSE))
#
# plotting country average within
# age and gender groups NUM performance
plot(na.omit(pmeansNCGA), sort=TRUE)

## End(Not run)
```

plot.intsvy.reg

Graphical representation of regression models in groups

Description

Functions pisa.reg, pisa.reg.pv, piaac.reg and piaac.reg.pv produce object of the class intsvy.reg. The function plot.intsvy.reg presents this list of regression models graphically.

Usage

```
## S3 method for class 'intsvy.reg'
plot(x, ..., vars, se = TRUE, sort = FALSE)
```

Arguments

x	An object of the class intsvy.reg returned by pisa.reg, pisa.reg.pv, piaac.reg and piaac.reg.pv functions.
...	Other arguments
vars	Variable labels of coefficients to be plotted. If none selected all coefficients are plotted including the R-squared
se	If TRUE add whiskers for standard errors.
sort	If TRUE groups are sorted in alphabetical order.

Value

Returns object of ggplot class with barplot. As with other ggplot objects the plus sign "+" can be used outside this function to modify graph parameters of the returning ggplot object. Works for one way, two-way and three-way contingency tables.

See Also

plot.intsvy.table, plot.intsvy.mean

Examples

```
## Not run:
# Independent variables
x.vars <- c("ESCS", "COGACT", "TCHBEHTD", "TCHBEHSO")
# Model estimation
my.mod <- pisa.reg.pv(pvlabel="MATH", x=x.vars, by="IDCNTRYL", data=pisa12)
# Plot
plot(gen.mod, vars = c("COGACT", "TCHBEHTD", "TCHBEHSO"), sort=TRUE)

## End(Not run)
```

plot.intsvy.table *Graphical representation of frequency tables*

Description

Functions pisa.table and piaac.table produce object of the class intsvy.table. The function plot.intsvy.table presents this table graphically.

Usage

```
## S3 method for class 'intsvy.table'
plot(x, se=FALSE, stacked=FALSE, centered = FALSE, midpoint = NA, ...)
```

Arguments

x	An object of the class intsvy.table returned by pisa.table or piaeac.table functions.
se	If TRUE add whiskers for standard errors (only for stacked=FALSE).
stacked	If TRUE plot bars stacked one over another.
centered	If TRUE then bars will be centered around midpoint.
midpoint	A single number, which specifies the segment around which bars are centered. By default it's the middle segment calculated as $(n.levels + 1)/2$. If n.levels is odd then bars are centered around the beginning of the selected segment. If n.levels is even then bars are centered around the middle of the selected segment.
...	Not used. Required for cran-check.

Value

Returns object of ggplot class with barplot. Works for one way, two-way and three-way contingency tables.

See Also

plot.intsvy.mean, plot.intsvy.reg

Examples

```
## Not run:
# install pbiecek/PIAAC package from github to have access to piaeac data
# age distribution in whole dataset
(ptable <- piaeac.table(variable="AGEG10LFS", data=pieaac))

# age distribution in whole dataset
plot(ptable)
plot(ptable, centered=TRUE)

# age distribution within countries
head(ptableC <- piaeac.table(variable="AGEG10LFS", by="CNTRYID", data=pieaac))

# age distribution within countries
plot(ptableC, stacked=TRUE)
plot(na.omit(ptableC), centered=TRUE)

# age distribution within countries and gender segments
head(ptableCA <- piaeac.table(variable="AGEG10LFS", by=c("CNTRYID", "GENDER_R"), data=pieaac))

# age distribution within countries and gender segments
plot(na.omit(ptableCA), stacked=TRUE)
plot(na.omit(ptableCA), centered=TRUE)

## End(Not run)
```

timss.ben.pv	<i>TIMSS international benchmarks</i>
--------------	---------------------------------------

Description

timss.ben.pv calculates the percentage of students performing at or above the cut-off points (scores) given by the user. The default are the benchmarks established by PIRLS/TIMSS

Usage

```
timss.ben.pv(pvlabel, by, cutoff, data, atlevel=FALSE,
export = FALSE, name = "output", folder = getwd())
```

Arguments

pvlabel	The label corresponding to the achievement variable, for example, "BSMMAT", for overall math performance.
cutoff	The cut-off points for the assessment benchmarks (e.g., cutoff = c(400, 475, 550, 625)).
by	The label for the grouping variable, usually the countries (i.e., by="IDCNTRYL"), but could be any other categorical variable.
data	An R object, normally a data frame, containing the data from TIMSS.
atlevel	A logical value. If TRUE, percentages at each level are calculated. Otherwise (FALSE), percentages at or above levels are reported.
export	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
name	The name of the exported file.
folder	The folder where the exported file is located.

Value

timss.ben.pv returns a data frame with the percentage of students at or above the benchmark and the corresponding standard error.

The total weight, "TOTWGT" and the cut-off points or benchmarks are defined in the config object.

See Also

pirls.ben.pv, pisa.ben.pv

Examples

```
## Not run:
timss.ben.pv(pvlabel="BSMMAT", by="IDCNTRYL", cutoff = c(400, 475, 550, 625), data=timss8g)
timss.ben.pv(pvlabel="ASMMAT", by="IDCNTRYL", data=timss4g)

## End(Not run)
```

timss.log

*Logistic regression analysis***Description**

timss.log performs logistic regression analysis for an observed dependent variable (NOT for plausible values)

Usage

```
timss.log(y, x, by, data, export = FALSE,
name = "output", folder = getwd())
```

Arguments

y	Label for dependent variable
x	Data labels of independent variables (e.g., x = c("ASDHEHLA", "ITSEX")).
by	The label for the grouping variable, usually the countries (i.e., by="IDCNTRYL"), but could be any other categorical variable.
data	An R object, normally a data frame, containing the data from PIRLS.
export	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
name	The name of the exported file.
folder	The folder where the exported file is located.

Value

timss.log prints a data frame with coefficients, standard errors, t-values, and odds ratios. Results are stored in a list object of class "intsvy.reg".

See Also

pirls.log, pisa.log

Examples

```
## Not run:

pisa$SKIP[!(pisa$ST09Q01 == "None" & pisa$ST115Q01 == "None")] <- 1
pisa$SKIP[pisa$ST09Q01 == "None" & pisa$ST115Q01 == "None"] <- 0

pisa$LATE[!pisa$ST08Q01 == "None"] <- 1
pisa$LATE[pisa$ST08Q01 == "None"] <- 0

pisa.log(y="SKIP", x="LATE", by="IDCNTRYL", data = pisa)

## End(Not run)
```

timss.log.pv

*Logistic regression analysis with plausible values***Description**

timss.log.pv performs logistic regression with plausible values and replicate weights.

Usage

```
timss.log.pv(pvlabel="BSMMAT", x, by, cutoff,
            data, export=FALSE, name= "output", folder=getwd())
```

Arguments

pvlabel	The label corresponding to the achievement variable, for example, "BSMMAT", for overall mathematics performance.
x	Data labels of independent variables.
cutoff	The cut-off point at which the dependent plausible values scores are dichotomised (1 is larger than the cut-off)
by	The label for the categorical grouping variable (i.e., by="IDCNTRYL") or variables (e.g., x= c("IDCNTRYL", "ITSEX")).
data	An R object, normally a data frame, containing the data from TIMSS.
export	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
name	The name of the exported file.
folder	The folder where the exported file is located.

Value

timss.log.pv returns a data frame with coefficients, standard errors, t-values, and odds ratios. If "by" is specified, results are reported in a list.

See Also

pisa.log.pv, pirls.log.pv

Examples

```
## Not run:
timss.log.pv(pvlabel="BSMMAT", cutoff= 550, x=c("ITSEX", "BSBGSLM"), by="IDCNTRYL", data=timss8g)
intsvy.log.pv(pvlabel="BSMMAT", cutoff= 550, x="ITSEX", by="IDCNTRYL",
             data=timss8g, config=timss8_conf)

## End(Not run)
```

timss.mean	<i>Calculates mean of variable</i>
------------	------------------------------------

Description

Calculates the mean of an observed variable (NOT one with plausible values) and its standard error.

Usage

```
timss.mean(variable, by, data,  
export = FALSE, name = "output", folder = getwd())
```

Arguments

variable	The label corresponding to the observed variable, for example, "ASDAGE", for the age of the student.
by	The label for the grouping variable, usually the countries (i.e., by="IDCNTRYL"), but could be any other categorical variable.
data	An R object, normally a data frame, containing the data from TIMSS.
export	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
name	The name of the exported file.
folder	The folder where the exported file is located.

Value

timss.mean returns a data frame with means and standard errors.

See Also

pirls.mean, pisa.mean

Examples

```
## Not run:  
timss.mean(variable='ASBGSLM', by='IDCNTRYL', data=timss4g)  
timss.mean(variable='BSBGSLM', by='IDCNTRYL', data=timss8g)  
  
## End(Not run)
```

`timss.mean.pv`*Calculates mean achievement score*

Description

`timss.mean.pv` uses five plausible values to calculate the mean achievement score and its standard error

Usage

```
timss.mean.pv(pvlabel = "BSMMAT", by, data,
export = FALSE, name = "output", folder = getwd())
```

Arguments

<code>pvlabel</code>	The label corresponding to the achievement variable, for example, "BSMMAT", for overall math performance in Grade 8.
<code>by</code>	The label for the grouping variable, usually the countries (i.e., <code>by="IDCOUNTRYL"</code>), but could be any other categorical variable.
<code>data</code>	An R object, normally a data frame, containing the data from TIMSS.
<code>export</code>	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
<code>name</code>	The name of the exported file.
<code>folder</code>	The folder where the exported file is located.

Value

`timss.mean.pv` returns a data frame with the mean values and standard errors.

See Also

`girls.mean.pv`, `pisa.mean.pv`

Examples

```
## Not run:
timss.mean.pv(pvlabel="ASMMAT", by= "IDCOUNTRYL", data=timss4g)
timss.mean.pv(pvlabel="BSMMAT", by= c("IDCOUNTRYL", "ITSEX"), data=timss8g)

## End(Not run)
```

timss.per.pv

TIMSS percentiles

Description

Calculates percentiles for plausible values

Usage

```
timss.per.pv(pvlabel="BSMMAT", by, per, data, export=FALSE, name= "output",
            folder=getwd())
```

Arguments

pvlabel	The label corresponding to the achievement variable, for example, "BSMMAT", for overall mathematics performance.
per	User-defined percentiles (e.g., per = c(5, 10, 25, 75, 90, 95)).
by	The label of the categorical grouping variable (e.g., by="IDCNTRYL") or variables (e.g., by=c("IDCNTRYL", "ITSEX")).
data	An R object, normally a data frame, containing the data from TIMSS.
export	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
name	The name of the exported file.
folder	The folder where the exported file is located.

Value

timss.per.pv returns a data frame with percentiles and associated standard errors. Default weights (e.g. "TOTWGT" in TIMSS) and percentiles are specified in the config parameter.

See Also

pisa.per.pv, girls.per.pv

Examples

```
## Not run:
timss.per.pv(pvlabel="BSMMAT", per = c(5, 10, 25, 50, 75, 90, 95), by="IDCNTRYL", data=timssg8)

## End(Not run)
```

`timss.reg`*Regression analysis*

Description

`timss.reg` performs linear regression analysis (OLS) for an observed dependent variable (NOT for plausible values)

Usage

```
timss.reg(y, x, by, data,  
export = FALSE, name = "output", folder = getwd())
```

Arguments

<code>y</code>	Label for dependent variable.
<code>x</code>	Data labels of independent variables.
<code>by</code>	The label for the grouping variable, usually the countries (i.e., <code>by="IDCNTRYL"</code>), but could be any other categorical variable.
<code>data</code>	An R object, normally a data frame, containing the data from TIMSS.
<code>export</code>	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
<code>name</code>	The name of the exported file.
<code>folder</code>	The folder where the exported file is located.

Value

`timss.reg` prints a `data.frame` with regression results (i.e., coefficients, standard errors, t-values, R-squared) and stores different regression output including residuals and replicate coefficients in a list object of class `"intsvy.reg"`.

See Also

`pirls.reg`

Examples

```
## Not run:  
timss.reg(y="BSDAGE", x="ITSEX", by="IDCNTRYL", data=timss8g)  
  
## End(Not run)
```

timss.reg.pv

Regression analysis with plausible values

Description

timss.reg.pv performs linear regression analysis (OLS) with plausible values and replicate weights.

Usage

```
timss.reg.pv(x, pvlabel = "BSMMAT", by,
data, std=FALSE, export = FALSE, name = "output", folder = getwd())
```

Arguments

x	Data labels of independent variables.
pvlabel	The label corresponding to the achievement variable, for example, "BSMMAT", for overall math performance in Grade 8.
by	The label for the grouping variable, usually the countries (i.e., by="IDCNTRYL"), but could be any other categorical variable.
data	An R object, normally a data frame, containing the data from TIMSS.
std	A logical value. If TRUE standardised regression coefficients are calculated.
export	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
name	The name of the exported file.
folder	The folder where the exported file is located.

Value

timss.reg.pv prints a data.frame with regression results (i.e., coefficients, standard errors, t-values, R-squared) and stores different regression output including residuals, replicate coefficients, variance within and between, and the regression data.frame in a list object of class "intsvy.reg".

See Also

pirls.reg.pv, pisa.reg.pv

Examples

```
## Not run:
timss8g$SEX[timss8g$ITSEX=="BOY"]=1
timss8g$SEX[timss8g$ITSEX=="GIRL"]=0
timss.reg.pv(pvlabel="BSMMAT", by=c("IDCNTRYL"), x="SEX", data=timss8g)

## End(Not run)
```

timss.rho	<i>Correlation matrix</i>
-----------	---------------------------

Description

timss.rho produces a correlations matrix for observed variables (NOT for plausible values)

Usage

```
timss.rho(variables, by, data,  
export = FALSE, name = "output", folder = getwd())
```

Arguments

variables	Data labels for the variables in the correlation matrix.
by	The label for the grouping variable, usually the countries (i.e., by="IDCNTRYL"), but could be any other categorical variable.
data	An R object, normally a data frame, containing the data from TIMSS.
export	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
name	The name of the exported file.
folder	The folder where the exported file is located.

Value

timss.rho returns a matrix including correlation and standard error values.

See Also

pirls.rho, pirls.rho.pv, timss.rho.pv

Examples

```
## Not run:  
timss.rho(variables=c("BSMMAT01", "BSDGEDUP"), data=timss)  
  
## End(Not run)
```

`timss.rho.pv`*Two-way weighted correlation with plausible values*

Description

`timss.rho.pv` calculates the correlation and standard error among two achievement variables each based on 5 plausible values or one achievement variable and an observed variable (i.e., with observed scores rather than plausible values).

Usage

```
timss.rho.pv(variable, pvlabel, by,
data, export = FALSE, name = "output", folder = getwd())
```

Arguments

<code>variable</code>	A data label for the observed variable
<code>pvlabel</code>	One or two labels describing the achievement variables.
<code>by</code>	The label for the grouping variable, usually the countries (i.e., <code>by="IDCNTRYL"</code>), but could be any other categorical variable.
<code>data</code>	An R object, normally a data frame, containing the data from TIMSS.
<code>export</code>	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
<code>name</code>	The name of the exported file.
<code>folder</code>	The folder where the exported file is located.

Value

`timss.rho.pv` returns a matrix with correlations and standard errors.

See Also

`pirls.rho.pv`, `pirls.rho`, `timss.rho`

Examples

```
## Not run:
timss.rho.pv(variable="BSDGEDUP", pvlabel="BSMMAT", by="IDCNTRYL", data=timss)

## End(Not run)
```

timss.table	<i>Frequency table</i>
-------------	------------------------

Description

timss.table produces a frequency table for a categorical variable printing percentages and standard errors. Information about weight is extracted from `intsvy::pirls_conf`.

Usage

```
timss.table(variable, by, data,  
export = FALSE, name = "output", folder = getwd())
```

Arguments

variable	The data label with the variable to be analysed.
by	The label for the grouping variable, usually the countries (i.e., <code>by="IDCNTRYL"</code>), but could be any other categorical variable.
data	An R object, normally a data frame, containing the data from TIMSS.
export	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
name	The name of the exported file.
folder	The folder where the exported file is located.

Value

timss.table returns a data frame with percentages and standard errors.

See Also

`pirls.table`, `pisa.table`

Examples

```
## Not run:  
timss.table(variable="ASDGSLM", by="IDCNTRYL", data=timss4g)  
timss.table(variable="BSDGSLM", by="IDCNTRYL", data=timss8g)  
  
## End(Not run)
```

timssg4.select.merge *Select and merge data*

Description

timssg4.select.merge selects and merges data from TIMSS G4. Achievement and weight variables (all of them) are selected by default.

Usage

```
timssg4.select.merge(folder = getwd(), countries, student = c(), home, school, teacher)
```

Arguments

folder	Directory path where the data are located. The data could be organized within folders but it should not be duplicated.
countries	The selected countries, supplied with the abbreviation (e.g., countries=c("AUT", "BGR") or codes (countries=c(40, 100)). If no countries are selected, all are selected.
student	The data labels for the selected student variables.
home	The data labels for the selected home background variables.
school	The data labels for the selected school variables.
teacher	The data labels for the selected teacher variables.

Value

timssg4.select.merge returns a data frame with the selected data from TIMSS G4.

See Also

timssg8.select.merge, pirls.select.merge, pisa.select.merge

Examples

```
## Not run:
timss4g <- timssg4.select.merge(folder=getwd(),
  countries=c("AUS", "BHR", "ARM", "CHL"),
  student =c("ITSEX", "ASDAGE", "ASBGSLM", "ASDGSLM"),
  home = c("ASDHEDUP", "ASDHENA"),
  school =c("ACDG03", "ACDGENS"))

## End(Not run)
```

timssg4.var.label *Data labels*

Description

timssg4.var.labels prints and saves variable labels and names of participating countries in a text file

Usage

```
timssg4.var.label(folder = getwd(), name = "Variable labels", output = getwd())
```

Arguments

folder	Directory path where the TIMSS G4 data are located. The data could be organized within folders but it should not be duplicated.
name	Name of output file.
output	Folder where output file is located.

Value

timssg4.var.label returns a list with variable labels for the student, home, school, and teacher data.

See Also

timssg8.var.label, pirls.var.label, pisa.var.label

Examples

```
## Not run:  
timssg4.var.label(folder= getwd())  
  
## End(Not run)
```

timssg8.select.merge *Select and merge data*

Description

timssg8.select.merge selects and merges data from TIMSS G8.

Usage

```
timssg8.select.merge(folder = getwd(), countries, student = c(), school,  
math.teacher, science.teacher)
```

Arguments

folder	Directory path where the data are located. The data could be organized within folders but it should not be duplicated.
countries	The selected countries, supplied with the abbreviation (e.g., countries=c("AUT", "BGR")) or codes (countries=c(40, 100)). If no countries are selected, all are selected.
student	The data labels for the selected student variables.
school	The data labels for the selected school variables.
math.teacher	The data labels for the selected math teacher variables.
science.teacher	The data labels for the selected science teacher variables.

Value

timssg8.select.merge returns a data frame with the selected data from TIMSS G8.

See Also

timssg4.select.merge, pirls.select.merge, pisa.select.merge

Examples

```
## Not run:
timss8g <- timssg8.select.merge(folder=getwd(),
                               countries=c("AUS", "BHR", "ARM", "CHL"),
                               student =c("BSDGEDUP", "ITSEX", "BSDAGE", "BSBGSLM", "BSDGSLM"),
                               school =c("BCBGDAS", "BCDG03"))

## End(Not run)
```

timssg8.var.label	<i>Data labels</i>
-------------------	--------------------

Description

timssg8.var.labels prints and saves variable labels and names of participating countries in a text file

Usage

```
timssg8.var.label(folder = getwd(), name = "Variable labels", output = getwd())
```

Arguments

folder	Directory path where the TIMSS G8 data are located. The data could be organized within folders but it should not be duplicated.
name	Name of output file.
output	Folder where output file is located.

Value

`timssg8.var.label` returns a list with variable labels for the student, home, school, and teacher data.

See Also

`timssg4.var.label`, `pirls.var.label`, `pisa.var.label`

Examples

```
## Not run:  
timssg8.var.label(folder= getwd())  
  
## End(Not run)
```

Index

* datasets

- configs, 4
- configs, 4
- icils_conf (configs), 4
- intsvy (intsvy-package), 3
- intsvy-package, 3
- intsvy.ben.pv, 4
- intsvy.config, 5
- intsvy.log, 7
- intsvy.log.pv, 8
- intsvy.mean, 9
- intsvy.mean.pv, 10
- intsvy.per.pv, 11
- intsvy.reg, 12
- intsvy.reg.pv, 13
- intsvy.rho, 14
- intsvy.rho.pv, 15
- intsvy.select.merge, 16
- intsvy.table, 17
- intsvy.var.label, 18
- llece_conf (configs), 4
- pasec_conf (configs), 4
- piaac.ben.pv, 19
- piaac.mean, 20
- piaac.mean.pv, 21
- piaac.reg, 22
- piaac.reg.pv, 23
- piaac.table, 24
- piaac_conf (configs), 4
- pirls.ben.pv, 25
- pirls.log, 26
- pirls.log.pv, 27
- pirls.mean, 28
- pirls.mean.pv, 29
- pirls.per.pv, 30
- pirls.reg, 31
- pirls.reg.pv, 32
- pirls.rho, 33
- pirls.rho.pv, 34
- pirls.select.merge, 35
- pirls.table, 36
- pirls.var.label, 37
- pirls_conf (configs), 4
- pisa.ben.pv, 37
- pisa.log, 38
- pisa.log.pv, 39
- pisa.mean, 40
- pisa.mean.pv, 41
- pisa.per.pv, 42
- pisa.reg, 43
- pisa.reg.pv, 44
- pisa.rho, 45
- pisa.select.merge, 46
- pisa.table, 47
- pisa.var.label, 48
- pisa_conf (configs), 4
- plot.intsvy.mean, 49
- plot.intsvy.reg, 50
- plot.intsvy.table, 51
- sea_conf (configs), 4
- timss.ben.pv, 53
- timss.log, 54
- timss.log.pv, 55
- timss.mean, 56
- timss.mean.pv, 57
- timss.per.pv, 58
- timss.reg, 59
- timss.reg.pv, 60
- timss.rho, 61
- timss.rho.pv, 62
- timss.table, 63
- timss4_conf (configs), 4
- timss8_conf (configs), 4
- timssg4.select.merge, 64

timssg4.var.label, [65](#)
timssg8.select.merge, [65](#)
timssg8.var.label, [66](#)