Package 'iteratoR'

May 8, 2026

Type Package

Title Print Loop Iterations at Exponentially Disparate Intervals

Version 0.1.1

Maintainer Steve Condylios <steve.condylios@gmail.com>

BugReports https://github.com/stevecondylios/iteratoR/issues

License MIT + file LICENSE

URL https://github.com/stevecondylios/iteratoR

Description Know which loop iteration the code execution is up to by including a single, convenient function call inside the loop.

Encoding UTF-8

RoxygenNote 7.1.2

NeedsCompilation no

Author Steve Condylios [aut, cre, cph] (ORCID: <https://orcid.org/0000-0003-0599-844X>), Zane Dax [ctb]

Repository CRAN

Date/Publication 2022-08-30 15:20:02 UTC

Contents

iteration 2

Index **4**

`iteration` *Conveniently print loop iterations to console*

Description

Place inside a loop to automatically and conveniently print the current loop iteration at exponentially disparate (or custom) intervals.

Usage

```
iteration(iterator_name, iteration_values)
```

Arguments

`iterator_name`	The name of the loop iterator (e.g. "i")
`iteration_values`	An integer vector specifying loop iterations (defaults to the sequence 1, 2, 5, 10, 20, 50, 100, 200, 500 ....)

Value

iteration() is a non-value-returning function. As such, it will not return anything, and instead print to console the value representing the current loop iteration.

Examples

```
# For a loop that would otherwise give no feedback as to where it is up to,
# simply include iteration() anywhere inside the loop to show progress

for(i in 1:10000) {
  2 * 2
  iteration()
}
# 10
# 20
# 50
# 100
# 200
# 500
# 1,000
# 2,000
# 5,000
# 10,000
# 20,000
# 50,000



# To use an iterator other than 'i' (example: 'page')
```

```
for(page in 1:10000) {
  2 * 2
  iteration("page")
}
# 10
# 20
# 50
# 100
# 200
# 500
# 1,000
# 2,000
# 5,000
# 10,000

# Use custom iteration intervals
for(i in 1:10000) {
  2 * 2
  iteration(iteration_values = seq(0, 1e4, 1e3))
}

# 1,000
# 2,000
# 3,000
# 4,000
# 5,000
# 6,000
# 7,000
# 8,000
# 9,000
# 10,000
```

Index

iteration, 2