

Package ‘magickGUI’

January 8, 2021

Type Package

Title GUI Tools for Interactive Image Processing with 'magick'

Version 1.2.2

Maintainer Shota Ochi <shotaochi1990@gmail.com>

Description Enables us to use the functions of the package 'magick' interactively.

License GPL-3

Depends R (>= 3.1.2), magick (>= 2.2)

Imports tcltk

Suggests testthat (>= 2.0.0), knitr, rmarkdown

URL <https://github.com/ShotaOchi/magickGUI>

BugReports <https://github.com/ShotaOchi/magickGUI/issues>

NeedsCompilation no

SystemRequirements ImageMagick (>= 6.9.5.4)

RoxygenNote 7.1.0

Encoding UTF-8

Author Shota Ochi [aut, cre]

Repository CRAN

Date/Publication 2021-01-08 07:10:03 UTC

R topics documented:

interactive_annotate	2
interactive_blur	3
interactive_canny	4
interactive_charcoal	5
interactive_composite	6
interactive_crop	7
interactive_despeckle	8
interactive_emboss	9

<code>interactive_fill</code>	10
<code>interactive_implode</code>	11
<code>interactive_modulate</code>	12
<code>interactive_oilpaint</code>	13
<code>interactive_quantize</code>	14
<code>interactive_reducenoise</code>	15
<code>interactive_threshold</code>	16
<code>magickGUI</code>	17

Index	18
--------------	-----------

`interactive_annotate` *interactive annotation*

Description

Using `image_annotate` of 'magick' interactively. location, degrees, size, weight, and kerning are parameters of `image_annotate`. See reference manual of 'magick' for detail.

Usage

```
interactive_annotate(
  image,
  text,
  gravity = "northwest",
  font = "",
  style = "normal",
  decoration = NULL,
  color = NULL,
  strokecolor = NULL,
  boxcolor = NULL,
  range_max_size = 1000,
  range_max_weight = 850,
  range_max_kerning = 300,
  resolution = 0.1,
  return_param = FALSE,
  scale
)
```

Arguments

<code>image</code>	a magick image object
<code>text</code>	character vector of length equal to 'image' or length 1
<code>gravity</code>	string with gravity value from <code>gravity_types</code> .
<code>font</code>	string with font family such as "sans", "mono", "serif", "Times", "Helvetica", "Trebuchet", "Georgia", "Palatino" or "Comic Sans".
<code>style</code>	value of <code>style_types</code> for example "italic"

decoration	value of decoration_types for example "underline"
color	a valid color string such as "navyblue" or "#000080". Use "none" for transparency.
strokecolor	a color string adds a stroke (border around the text)
boxcolor	a color string for background color that annotation text is rendered on.
range_max_size	define maximum of size in slider. must be positive.
range_max_weight	define maximum of weight in slider. must be positive.
range_max_kerning	define maximum of kerning in slider. must be positive.
resolution	resolution of slider
return_param	If return_param is TRUE, returns a list of values of location, degrees, size, weight, and kerning. If return_param is FALSE, returns a magick image object.
scale	geometry to be passed to image_scale function of magick package. image is scaled just for preview and result image is not scaled if scale is given.

Value

a magick image object or a list of values of location, degrees, size, weight, and kerning

Author(s)

Shota Ochi

Examples

```
interactive_annotate(wizard, "hello")
```

interactive_blur	<i>interactive blurring</i>
------------------	-----------------------------

Description

Using image_blur of 'magick' interactively. radius and sigma are parameters of image_blur. See reference manual of 'magick' for detail.

Usage

```
interactive_blur(
  image,
  range_max_radius = 5,
  range_max_sigma = 5,
  resolution = 0.1,
  return_param = FALSE,
  scale
)
```

Arguments

image	a magick image object
range_max_radius	define maximum in slider of radius. must be positive.
range_max_sigma	define maximum in slider of sigma. must be positive.
resolution	resolution of slider
return_param	If return_param is TRUE, returns values of radius and sigma. If return_param is FALSE, returns a magick image object.
scale	geometry to be passed to image_scale function of magick package. image is scaled just for preview and result image is not scaled if scale is given.

Value

a magick image object or values of radius and sigma

Author(s)

Shota Ochi

Examples

```
interactive_blur(wizard)
```

interactive_canny *interactive canny edge detection*

Description

Using image_canny of 'magick' interactively. radius, sigma, lower%, and upper% are parameters of image_canny. See reference manual of 'magick' for detail.

Usage

```
interactive_canny(  
  image,  
  range_max_radius = 30,  
  range_max_sigma = 2,  
  resolution = 0.1,  
  return_param = FALSE,  
  scale  
)
```

Arguments

image	a magick image object
range_max_radius	define maximum in slider of radius. must be positive.
range_max_sigma	define maximum in slider of sigma. must be positive.
resolution	resolution of slider
return_param	If return_param is TRUE, returns values of radius, sigma, lower%, and upper% represented in the format of 'magick'. If return_param is FALSE, returns a magick image object.
scale	geometry to be passed to image_scale function of magick package. image is scaled just for preview and result image is not scaled if scale is given.

Value

a magick image object or values of radius, sigma, lower%, and upper% represented in the format of 'magick'

Author(s)

Shota Ochi

Examples

```
interactive_canny(wizard)
```

interactive_charcoal *interactive charcoal filtering*

Description

Using image_charcoal of 'magick' interactively. radius and sigma are parameters of image_charcoal. See reference manual of 'magick' for detail.

Usage

```
interactive_charcoal(  
    image,  
    range_max_radius = 5,  
    range_max_sigma = 5,  
    resolution = 0.1,  
    return_param = FALSE,  
    scale  
)
```

Arguments

image	a magick image object
range_max_radius	define maximum in slider of radius. must be positive.
range_max_sigma	define maximum in slider of sigma. must be positive.
resolution	resolution of slider
return_param	If return_param is TRUE, returns values of radius and sigma. If return_param is FALSE, returns a magick image object.
scale	geometry to be passed to image_scale function of magick package. image is scaled just for preview and result image is not scaled if scale is given.

Value

a magick image object or values of radius and sigma

Author(s)

Shota Ochi

Examples

```
interactive_charcoal(wizard)
```

interactive_composite *interactive image compositing*

Description

Using image_composite of 'magick' interactively. operator, compose_args, and offset are parameters of image_composite. see reference manual of 'magick' for detail.

Usage

```
interactive_composite(  
    image,  
    composite_image,  
    operator = "atop",  
    compose_args = "",  
    resolution = 1,  
    return_param = FALSE,  
    scale  
)
```

Arguments

image	a magick image object
composite_image	composition image
operator	string with a composite operator
compose_args	additional arguments needed for some composite operations
resolution	resolution of slider
return_param	If return_param is TRUE, returns values of offset. If return_param is FALSE, returns a magick image object.
scale	geometry to be passed to image_scale function of magick package. image is scaled just for preview and result image is not scaled if scale is given.

Value

magick a image object or values of offset

Author(s)

Shota Ochi

Examples

```
interactive_composite(wizard, rose)
```

interactive_crop *interactive cropping*

Description

Using image_crop of 'magick' interactively.

Usage

```
interactive_crop(image, color = "white", return_param = FALSE, scale)
```

Arguments

<code>image</code>	a magick image object
<code>color</code>	color of background. a valid color string such as "navyblue" or "#000080". "none" is not allowed.
<code>return_param</code>	If <code>return_param</code> is TRUE, returns a value of geometry. If <code>return_param</code> is FALSE, returns a magick image object.
<code>scale</code>	geometry to be passed to <code>image_scale</code> function of magick package. image is scaled just for preview and result image is not scaled if scale is given.

Value

a magick image object or a value of geometry.

Author(s)

Shota Ochi

Examples

```
interactive_crop(wizard)
```

`interactive_despeckle` *interactive despeckling*

Description

Using `image_despeckle` of 'magick' interactively. `times` is a parameter of `image_despeckle`. See reference manual of 'magick' for detail.

Usage

```
interactive_despeckle(  
  image,  
  range_max = 50,  
  resolution = 1,  
  return_param = FALSE,  
  scale  
)
```


Arguments

image	a magick image object
range_max	define maximum in slider. must be positive.
resolution	resolution of slider
return_param	If return_param is TRUE, returns value of times. If return_param is FALSE, returns a magick image object.
scale	geometry to be passed to image_scale function of magick package. image is scaled just for preview and result image is not scaled if scale is given.

Value

a magick image object or value of times

Author(s)

Shota Ochi

Examples

```
interactive_despeckle(wizard)
```

interactive_emboss *interactive embossing*

Description

Using image_emboss of 'magick' interactively. radius and sigma are parameters of image_emboss. See reference manual of 'magick' for detail.

Usage

```
interactive_emboss(  
  image,  
  range_max_radius = 5,  
  range_max_sigma = 5,  
  resolution = 0.1,  
  return_param = FALSE,  
  scale  
)
```

Arguments

<code>image</code>	a magick image object
<code>range_max_radius</code>	define maximum in slider of radius. must be positive.
<code>range_max_sigma</code>	define maximum in slider of sigma. must be positive.
<code>resolution</code>	resolution of slider
<code>return_param</code>	If <code>return_param</code> is TRUE, returns values of radius and sigma. If <code>return_param</code> is FALSE, returns a magick image object.
<code>scale</code>	geometry to be passed to <code>image_scale</code> function of magick package. image is scaled just for preview and result image is not scaled if scale is given.

Value

a magick image object or values of radius and sigma

Author(s)

Shota Ochi

Examples

```
interactive_emboss(wizard)
```

`interactive_fill` *interactive_filling*

Description

Using `image_fill` of 'magick' interactively. `point` and `fuzz` are parameters of `image_fill`. See reference manual of 'magick' for detail.

Usage

```
interactive_fill(  
  image,  
  color,  
  refcolor = NULL,  
  resolution = 0.1,  
  return_param = FALSE,  
  scale  
)
```

Arguments

image	a magick image object
color	a valid color string such as "navyblue" or "#000080". Use "none" for transparency.
refcolor	if set, fuzz color distance will be measured against this color, not the color of the starting point. Any color (within fuzz color distance of the given refcolor), connected to starting point will be replaced with the color. If the pixel at the starting point does not itself match the given refcolor (according to fuzz) then no action will be taken.
resolution	resolution of slider of fuzz
return_param	If return_param is TRUE, returns a list values of point and fuzz. If return_param is FALSE, returns a magick image object.
scale	geometry to be passed to image_scale function of magick package. image is scaled just for preview and result image is not scaled if scale is given.

Value

a magick image object or a list of values of point and fuzz

Author(s)

Shota Ochi

Examples

```
interactive_fill(wizard, "black")
```

interactive_implode *interactive imploding*

Description

Using image_implode of 'magick' interactively. factor is a parameter of image_implode. See reference manual of 'magick' for detail.

Usage

```
interactive_implode(  
  image,  
  range_max = 1,  
  resolution = 0.1,  
  return_param = FALSE,  
  scale  
)
```

Arguments

image	a magick image object
range_max	define maximum in slider. must be positive.
resolution	resolution of slider
return_param	If return_param is TRUE, returns value of factor. If return_param is FALSE, returns a magick image object.
scale	geometry to be passed to image_scale function of magick package. image is scaled just for preview and result image is not scaled if scale is given.

Value

a magick image object or value of factor

Author(s)

Shota Ochi

Examples

```
interactive_implode(wizard)
```

interactive_modulate *interactive modulating*

Description

Using image_modulate of 'magick' interactively. brightness and saturation and hue are parameters of image_modulate. See reference manual of 'magick' for detail.

Usage

```
interactive_modulate(  
  image,  
  range_max_brightness = 200,  
  range_max_saturation = 200,  
  range_max_hue = 200,  
  resolution = 0.1,  
  return_param = FALSE,  
  scale  
)
```

Arguments

image	a magick image object
range_max_brightness	define maximum in slider of brightness. must be positive.
range_max_saturation	define maximum in slider of saturation. must be positive.
range_max_hue	define maximum in slider of hue. must be positive.
resolution	resolution of slider
return_param	If return_param is TRUE, returns values of brightness and saturation and hue. If return_param is FALSE, returns a magick image object.
scale	geometry to be passed to image_scale function of magick package. image is scaled just for preview and result image is not scaled if scale is given.

Value

a magick image object or values of brightness and saturation

Author(s)

Shota Ochi

Examples

```
interactive_modulate(wizard)
```

interactive_oilpaint *interactive oil painting*

Description

Using image_oilpaint of 'magick' interactively. radius is a parameter of image_oilpaint. See reference manual of 'magick' for detail.

Usage

```
interactive_oilpaint(  
  image,  
  range_max = 10,  
  resolution = 0.1,  
  return_param = FALSE,  
  scale  
)
```

Arguments

<code>image</code>	a magick image object
<code>range_max</code>	define maximum in slider. must be positive.
<code>resolution</code>	resolution of slider
<code>return_param</code>	If <code>return_param</code> is TRUE, returns value of radius. If <code>return_param</code> is FALSE, returns a magick image object.
<code>scale</code>	geometry to be passed to <code>image_scale</code> function of magick package. image is scaled just for preview and result image is not scaled if scale is given.

Value

a magick image object or value of radius

Author(s)

Shota Ochi

Examples

```
interactive_oilpaint(wizard)
```

`interactive_quantize` *interactive quantization*

Description

Using `image_quantize` of 'magick' interactively. `max`, `colorspace`, `dither`, and `treedepth` are parameters of `image_quantize`. See reference manual of 'magick' for detail.

Usage

```
interactive_quantize(  
  image,  
  colorspace = "rgb",  
  dither = NULL,  
  treedepth = NULL,  
  range_max = 256,  
  resolution = 1,  
  return_param = FALSE,  
  scale  
)
```

Arguments

image	a magick image object
colorspace	specify colorspace. for example, "rgb", "gray", or "cmyk".
dither	apply Floyd/Steinberg error diffusion to the image
treedepth	depth of the quantization color classification tree
range_max	define maximum in slider. must be positive.
resolution	resolution of slider
return_param	If return_param is TRUE, returns value of max. If return_param is FALSE, returns a magick image object.
scale	geometry to be passed to image_scale function of magick package. image is scaled just for preview and result image is not scaled if scale is given.

Value

a magick image object or value of max

Author(s)

Shota Ochi

Examples

```
interactive_quantize(wizard)
```

```
interactive_reducenoise  
    interactive denoising
```

Description

Using image_reducenoise of 'magick' interactively. radius is a parameter of image_reducenoise. See reference manual of 'magick' for detail.

Usage

```
interactive_reducenoise(  
  image,  
  range_max = 30,  
  resolution = 1,  
  return_param = FALSE,  
  scale  
)
```

Arguments

<code>image</code>	a magick image object
<code>range_max</code>	define maximum in slider. must be positive.
<code>resolution</code>	resolution of slider
<code>return_param</code>	If <code>return_param</code> is TRUE, returns value of radius. If <code>return_param</code> is FALSE, returns a magick image object.
<code>scale</code>	geometry to be passed to <code>image_scale</code> function of magick package. image is scaled just for preview and result image is not scaled if scale is given.

Value

a magick image object or value of radius

Author(s)

Shota Ochi

Examples

```
interactive_reducenoise(wizard)
```

`interactive_threshold` *interactive thresholding*

Description

Using `image_threshold` of 'magick' interactively. `type` and `channel` are parameters of `image_threshold`. See reference manual of 'magick' for detail.

Usage

```
interactive_threshold(  
  image,  
  type = c("black", "white"),  
  channel = NULL,  
  resolution = 0.1,  
  return_param = FALSE,  
  scale  
)
```


Arguments

image	a magick image object
type	type of thresholding, either one of lat, black or white
channel	a value specifying which channel(s) to set
resolution	resolution of slider
return_param	If return_param is TRUE, returns threshold value. If return_param is FALSE, returns a magick image object.
scale	geometry to be passed to image_scale function of magick package. image is scaled just for preview and result image is not scaled if scale is given.

Value

a magick image object or threshold value

Author(s)

Shota Ochi

Examples

```
interactive_threshold(wizard)
```

magickGUI

magickGUI: GUI tools for interactive image processing with 'magick'

Description

magickGUI enables us to use the functions of the package 'magick' interactively.

Index

[interactive_annotate](#), 2
[interactive_blur](#), 3
[interactive_canny](#), 4
[interactive_charcoal](#), 5
[interactive_composite](#), 6
[interactive_crop](#), 7
[interactive_despeckle](#), 8
[interactive_emboss](#), 9
[interactive_fill](#), 10
[interactive_implode](#), 11
[interactive_modulate](#), 12
[interactive_oilpaint](#), 13
[interactive_quantize](#), 14
[interactive_reducenoise](#), 15
[interactive_threshold](#), 16

[magickGUI](#), 17