

Package ‘modeldata’

July 14, 2021

Title Data Sets Used Useful for Modeling Packages

Version 0.1.1

Description Data sets used for demonstrating or testing model-related packages are contained in this package.

License MIT + file LICENSE

URL <https://modeldata.tidymodels.org>,
<https://github.com/tidymodels/modeldata>

BugReports <https://github.com/tidymodels/modeldata/issues>

Depends R (>= 2.10)

Suggests covr

Encoding UTF-8

LazyData false

RoxygenNote 7.1.1.9000

NeedsCompilation no

Author Max Kuhn [aut, cre],
RStudio [cph]

Maintainer Max Kuhn <max@rstudio.com>

Repository CRAN

Date/Publication 2021-07-14 16:20:02 UTC

R topics documented:

ad_data	2
ames	3
attrition	4
biomass	5
bivariate	5
car_prices	6
cells	6
check_times	7

Chicago	8
concrete	9
covers	9
credit_data	10
crickets	10
drinks	11
grants	11
hpc_cv	12
hpc_data	13
lending_club	13
meats	14
mlc_churn	14
oils	15
okc	15
parabolic	16
pathology	17
pd_speech	17
penguins	18
Sacramento	19
scat	19
small_fine_foods	20
Smithsonian	20
solubility_test	21
stackoverflow	22
tate_text	22
two_class_dat	23
two_class_example	23
wa_churn	24

Index 25

ad_data	<i>Alzheimer's disease data</i>
---------	---------------------------------

Description

Alzheimer's disease data

Details

Craig-Schapiro et al. (2011) describe a clinical study of 333 patients, including some with mild (but well-characterized) cognitive impairment as well as healthy individuals. CSF samples were taken from all subjects. The goal of the study was to determine if subjects in the early states of impairment could be differentiated from cognitively healthy individuals. Data collected on each subject included:

- Demographic characteristics such as age and gender
- Apolipoprotein E genotype

- Protein measurements of Abeta, Tau, and a phosphorylated version of Tau (called pTau)
- Protein measurements of 124 exploratory biomarkers, and
- Clinical dementia scores

For these analyses, we have converted the scores to two classes: impaired and healthy. The goal of this analysis is to create classification models using the demographic and assay data to predict which patients have early stages of disease.

Value

ad_data a tibble

Source

Kuhn, M., Johnson, K. (2013) *Applied Predictive Modeling*, Springer.

Craig-Schapiro R, Kuhn M, Xiong C, Pickering EH, Liu J, Misko TP, et al. (2011) Multiplexed Immunoassay Panel Identifies Novel CSF Biomarkers for Alzheimer's Disease Diagnosis and Prognosis. PLoS ONE 6(4): e18850.

Examples

```
data(ad_data)
str(ad_data)
```

ames

Ames Housing Data

Description

A data set from De Cock (2011) has 82 fields were recored for 2,930 properties in Ames IA. This version is copies from the *AmesHousing* package but does not include a few quality columns that appear to be outcomes rather than predictors.

Details

See this links for the sources below for more information as well as `?AmesHousing::make_ames`.

For these data, the training materials typically use:

```
library(tidymodels)

set.seed(4595)
data_split <- initial_split(ames, strata = "Sale_Price")
ames_train <- training(data_split)
ames_test  <- testing(data_split)

set.seed(2453)
ames_folds<- vfold_cv(ames_train)
```

Value

ames a tibble

Source

De Cock, D. (2011). "Ames, Iowa: Alternative to the Boston Housing Data as an End of Semester Regression Project," *Journal of Statistics Education*, Volume 19, Number 3.

<http://jse.amstat.org/v19n3/decock/DataDocumentation.txt>

<http://jse.amstat.org/v19n3/decock.pdf>

attrition

Job attrition

Description

Job attrition

Details

These data are from the IBM Watson Analytics Lab. The website describes the data with “Uncover the factors that lead to employee attrition and explore important questions such as ‘show me a breakdown of distance from home by job role and attrition’ or ‘compare average monthly income by education and attrition’. This is a fictional data set created by IBM data scientists.”. There are 1470 rows.

Value

attrition a data frame

Source

The IBM Watson Analytics Lab website <https://www.ibm.com/communities/analytics/watson-analytics-blog/hr-employee-attrition/>

Examples

```
data(attrition)
str(attrition)
```

biomass	<i>Biomass data</i>
---------	---------------------

Description

Ghugare et al (2014) contains a data set where different biomass fuels are characterized by the amount of certain molecules (carbon, hydrogen, oxygen, nitrogen, and sulfur) and the corresponding higher heating value (HHV). These data are from their Table S.2 of the Supplementary Materials

Value

biomass a data frame

Source

Ghugare, S. B., Tiwary, S., Elangovan, V., and Tambe, S. S. (2013). Prediction of Higher Heating Value of Solid Biomass Fuels Using Artificial Intelligence Formalisms. *BioEnergy Research*, 1-12.

Examples

```
data(biomass)
str(biomass)
```

bivariate	<i>Example bivariate classification data</i>
-----------	----------------------------------------------

Description

Example bivariate classification data

Details

These data are a simplified version of the segmentation data contained in caret. There are three columns: A and B are predictors and the column Class is a factor with levels "One" and "Two". There are three data sets: one for training (n = 1009), validation (n = 300), and testing (n = 710).

Value

bivariate_train, bivariate_test, bivariate_val
tibbles

Examples

```
data(bivariate)
```

 car_prices

Kelly Blue Book resale data for 2005 model year GM cars

Description

Kuiper (2008) collected data on Kelly Blue Book resale data for 804 GM cars (2005 model year).

Value

cars data frame of the suggested retail price (column Price) and various characteristics of each car (columns Mileage, Cylinder, Doors, Cruise, Sound, Leather, Buick, Cadillac, Chevy, Pontiac, Saab, Saturn, convertible, coupe, hatchback, sedan and wagon)

Source

Kuiper, S. (2008). Introduction to Multiple Regression: How Much Is Your Car Worth?, *Journal of Statistics Education*, Vol. 16 http://jse.amstat.org/jse_archive.htm#2008.

 cells

Cell body segmentation

Description

Hill, LaPan, Li and Haney (2007) develop models to predict which cells in a high content screen were well segmented. The data consists of 119 imaging measurements on 2019. The original analysis used 1009 for training and 1010 as a test set (see the column called case).

Details

The outcome class is contained in a factor variable called class with levels "PS" for poorly segmented and "WS" for well segmented.

The raw data used in the paper can be found at the Biomedcentral website. The version contained in cells is modified. First, several discrete versions of some of the predictors (with the suffix "Status") were removed. Second, there are several skewed predictors with minimum values of zero (that would benefit from some transformation, such as the log). A constant value of 1 was added to these fields: avg_inten_ch_2, fiber_align_2_ch_3, fiber_align_2_ch_4, spot_fiber_count_ch_4 and total_inten_ch_2.

Value

cells a tibble

Source

Hill, LaPan, Li and Haney (2007). Impact of image segmentation on high-content screening data quality for SK-BR-3 cells, *BMC Bioinformatics*, Vol. 8, pg. 340, <https://bmcbioinformatics.biomedcentral.com/articles/10.1186/1471-2105-8-340>.

check_times

Execution time data

Description

These data were collected from the CRAN web page for 13,626 R packages. The time to complete the standard package checking routine was collected. In some cases, the package checking process is stopped due to errors and these data are treated as censored. It is less than 1 percent.

Details

As predictors, the associated package source code were downloaded and parsed to create predictors, including

- authors: The number of authors in the author field.
- imports: The number of imported packages.
- suggests: The number of packages suggested.
- depends: The number of hard dependencies.
- Roxygen: a binary indicator for whether Roxygen was used for documentation.
- gh: a binary indicator for whether the URL field contained a GitHub link.
- rforge: a binary indicator for whether the URL field contained a link to R-forge.
- descr: The number of characters (or, in some cases, bytes) in the description field.
- r_count: The number of R files in the R directory.
- r_size: The total disk size of the R files.
- ns_import: Estimated number of imported functions or methods.
- ns_export: Estimated number of exported functions or methods.
- s3_methods: Estimated number of S3 methods.
- s4_methods: Estimated number of S4 methods.
- doc_count: How many Rmd or Rnw files in the vignettes directory.
- doc_size: The disk size of the Rmd or Rnw files.
- src_count: The number of files in the src directory.
- src_size: The size on disk of files in the src directory.
- data_count: The number of files in the data directory.
- data_size: The size on disk of files in the data directory.
- testthat_count: The number of files in the testthat directory.

- `testthat_size`: The size on disk of files in the `testthat` directory.
- `check_time`: The time (in seconds) to run R CMD check using the "r-devel-windows-ix86+x86_64" flavor.
- `status`: An indicator for whether the tests completed.

Data were collected on 2019-01-20.

Value

`check_times` a data frame

Source

CRAN

Examples

```
data(check_times)
str(check_times)
```

Chicago

Chicago ridership data

Description

Chicago ridership data

Details

These data are from Kuhn and Johnson (2020) and contain an *abbreviated* training set for modeling the number of people (in thousands) who enter the Clark and Lake L station.

The date column corresponds to the current date. The columns with station names (Austin through California) are a *sample* of the columns used in the original analysis (for file size reasons). These are 14 day lag variables (i.e. `date - 14 days`). There are columns related to weather and sports team schedules.

The station at 35th and Archer is contained in the column `Archer_35th` to make it a valid R column name.

Value

`Chicago` a tibble
`stations` a vector of station names

Source

Kuhn and Johnson (2020), *Feature Engineering and Selection*, Chapman and Hall/CRC . <https://bookdown.org/max/FES/> and <https://github.com/topepo/FES>

Examples

```
data(Chicago)
str(Chicago)
stations
```

concrete	<i>Compressive strength of concrete mixtures</i>
----------	--------------------------------------------------

Description

Yeh (2006) describes an aggregated data set for experimental designs used to test the compressive strength of concrete mixtures. The data are used by Kuhn and Johnson (2013).

Value

concrete a tibble

Source

Yeh I (2006). "Analysis of Strength of Concrete Using Design of Experiments and Neural Networks." *Journal of Materials in Civil Engineering*, 18, 597-604.

Kuhn, M., Johnson, K. (2013) *Applied Predictive Modeling*, Springer.

Examples

```
data(concrete)
```

covers	<i>Raw cover type data</i>
--------	----------------------------

Description

These data are raw data describing different types of forest cover-types from the UCI Machine Learning Database (see link below). There is one column in the data that has a few difference pieces of textual information (of variable lengths).

Value

covers a data frame

Source

<https://archive.ics.uci.edu/ml/machine-learning-databases/covtype/covtype.info>

Examples

```
data(covers)
str(covers)
```

`credit_data`*Credit data*

Description

These data are from the website of Dr. Lluís A. Belanche Muñoz by way of a github repository of Dr. Gaston Sanchez. One data point is a missing outcome was removed from the original data.

Value

`credit_data` a data frame

Source

<https://github.com/gastonstat/CreditScoring>, <http://bit.ly/2kkBFrk>

Examples

```
data(credit_data)
str(credit_data)
```

`crickets`*Rates of Cricket Chirps*

Description

These data are from from McDonald (2009), by way of Mangiafico (2015), on the relationship between the ambient temperature and the rate of cricket chirps per minute. Data were collected for two species: *O. exclamationis* and *O. niveus*. The data are contained in a data frame called `crickets` with a total of 31 data points.

Value

`crickets` a tibble

Source

Mangiafico, S. 2015. "An R Companion for the Handbook of Biological Statistics." <https://rcompanion.org/handbook/>.

McDonald, J. 2009. *Handbook of Biological Statistics*. Sparky House Publishing.

drinks *Sample time series data*

Description

Sample time series data

Details

Drink sales. The exact name of the series from FRED is: "Merchant Wholesalers, Except Manufacturers' Sales Branches and Offices Sales: Nondurable Goods: Beer, Wine, and Distilled Alcoholic Beverages Sales"

Value

drinks a tibble

Source

The Federal Reserve Bank of St. Louis website <https://fred.stlouisfed.org/series/S4248SM144NCEN>

Examples

```
data(drinks)
str(drinks)
```

grants *Grant acceptance data*

Description

A data set related to the success or failure of academic grants.

Details

The data are discussed in Kuhn and Johnson (2013):

"These data are from a 2011 Kaggle competition sponsored by the University of Melbourne where there was interest in predicting whether or not a grant application would be accepted. Since public funding of grants had decreased over time, triaging grant applications based on their likelihood of success could be important for estimating the amount of potential funding to the university. In addition to predicting grant success, the university sought to understand factors that were important in predicting success."

The data ranged from 2005 and 2008 and the data spending strategy was driven by the date of the grant. Kuhn and Johnson (2013) describe:

"The compromise taken here is to build models on the pre-2008 data and tune them by evaluating a random sample of 2,075 grants from 2008. Once the optimal parameters are determined, final model is built using these parameters and the entire training set (i.e., the data prior to 2008 and the additional 2,075 grants). A small holdout set of 518 grants from 2008 will be used to ensure that no gross methodology errors occur from repeatedly evaluating the 2008 data during model tuning. In the text, this set of samples is called the 2 0 0 8 holdout set. This small set of year 2008 grants will be referred to as the test set and will not be evaluated until set of candidate models are identified."

To emulate this, `grants_other` contains the training (pre-2008, $n = 6,633$) and holdout/validation data (2008, $n = 1,557$). `grants_test` has 518 grant samples from 2008. The object `grants_2008` is an integer vector that can be used to separate the modeling with the holdout/validation sets.

Value

`grants_other`, `grants_other`, `grants_2008`
two tibbles and an integer vector of data points used for training

Source

Kuhn and Johnson (2013). *Applied Predictive Modeling*. Springer.

hpc_cv	<i>Class probability predictions</i>
--------	--------------------------------------

Description

Class probability predictions

Details

This data frame contains the predicted classes and class probabilities for a linear discriminant analysis model fit to the HPC data set from Kuhn and Johnson (2013). These data are the assessment sets from a 10-fold cross-validation scheme. The data column columns for the true class (`obs`), the class prediction (`pred`) and columns for each class probability (columns `VF`, `F`, `M`, and `L`). Additionally, a column for the resample indicator is included.

Value

`hpc_cv` a data frame

Source

Kuhn, M., Johnson, K. (2013) *Applied Predictive Modeling*, Springer

Examples

```
data(hpc_cv)
str(hpc_cv)
```

hpc_data	<i>High-performance computing system data</i>
----------	-----------------------------------------------

Description

Kuhn and Johnson (2013) describe a data set where characteristics of unix jobs were used to classify their completion times as either very fast (1 min or less, VF), fast (1–50 min, F), moderate (5–30 min, M), or long (greater than 30 min, L).

Value

hpc_data a tibble

Source

Kuhn, M., Johnson, K. (2013) *Applied Predictive Modeling*, Springer.

Examples

```
data(hpc_data)
```

lending_club	<i>Loan data</i>
--------------	------------------

Description

Loan data

Details

These data were downloaded from the Lending Club access site (see below) and are from the first quarter of 2016. A subset of the rows and variables are included here. The outcome is in the variable `Class` and is either "good" (meaning that the loan was fully paid back or currently on-time) or "bad" (charged off, defaulted, or 21-120 days late). A data dictionary can be found on the source website.

Value

lending_club a data frame

Source

Lending Club Statistics <https://www.lendingclub.com/info/download-data.action>

Examples

```
data(lending_club)
str(lending_club)
```

meats	<i>Fat, water and protein content of meat samples</i>
-------	-------------------------------------------------------

Description

"These data are recorded on a Tecator Infratec Food and Feed Analyzer working in the wavelength range 850 - 1050 nm by the Near Infrared Transmission (NIT) principle. Each sample contains finely chopped pure meat with different moisture, fat and protein contents.

Details

If results from these data are used in a publication we want you to mention the instrument and company name (Tecator) in the publication. In addition, please send a preprint of your article to Karin Thente, Tecator AB, Box 70, S-263 21 Hoganas, Sweden

The data are available in the public domain with no responsibility from the original data source. The data can be redistributed as long as this permission note is attached."

"For each meat sample the data consists of a 100 channel spectrum of absorbances and the contents of moisture (water), fat and protein. The absorbance is $-\log_{10}$ of the transmittance measured by the spectrometer. The three contents, measured in percent, are determined by analytic chemistry."

Included here are the training, monitoring and test sets.

Value

meats	a tibble
-------	----------

Examples

```
data(meats)
```

mlc_churn	<i>Customer churn data</i>
-----------	----------------------------

Description

A data set from the MLC++ machine learning software for modeling customer churn. There are 19 predictors, mostly numeric: state (categorical), account_length area_code international_plan (yes/no), voice_mail_plan (yes/no), number_vmail_messages total_day_minutes total_day_calls total_day_charge total_eve_minutes total_eve_calls total_eve_charge total_night_minutes total_night_calls total_night_charge total_intl_minutes total_intl_calls total_intl_charge, and number_customer_service_calls.

Details

The outcome is contained in a column called churn (also yes/no). A note in one of the source files states that the data are "artificial based on claims similar to real world".

Value

mlc_churn a tibble

SourceOriginally at <http://www.sgi.com/tech/mlc/>

oils

*Fatty acid composition of commercial oils***Description**

Fatty acid concentrations of commercial oils were measured using gas chromatography. The data is used to predict the type of oil. Note that only the known oils are in the data set. Also, the authors state that there are 95 samples of known oils. However, we count 96 in Table 1 (pgs. 33-35).

Value

oils a tibble

Source

Brodnjak-Voncina et al. (2005). Multivariate data analysis in classification of vegetable oils characterized by the content of fatty acids, *Chemometrics and Intelligent Laboratory Systems*, Vol. 75:31-45.

okc

*OkCupid data***Description****[Deprecated]**

These are a sample of columns and users from the OkCupid dating website. The data are from Kim and Escobedo-Land (2015). Permission to use this data set was explicitly granted by OkCupid, but since that time, concerns have been raised about the ethics of using this or similar data sets, for example to identify individuals (see the original journal article as well as letter below). This data set will be removed entirely from this package in a future release.

Value

okc, okc_text data frames

Source

Kim, A. Y., and A. Escobedo-Land. 2015. "OkCupid Data for Introductory Statistics and Data Science Courses." *Journal of Statistics Education: An International Journal on the Teaching and Learning of Statistics*. doi: [10.1080/26939169.2021.1924516](https://doi.org/10.1080/26939169.2021.1924516)

Tiffany Xiao & Yifan Ma. 2021. "A Letter to the *Journal of Statistics and Data Science Education* — A Call for Review of 'OkCupid Data for Introductory Statistics and Data Science Courses' by Albert Y. Kim and Adriana Escobedo-Land." *Journal of Statistics Education: An International Journal on the Teaching and Learning of Statistics*. doi: [10.1080/26939169.2021.1930812](https://doi.org/10.1080/26939169.2021.1930812)

Examples

```
data(okc)
str(okc)

data(okc_text)
str(okc_text)
```

parabolic

Parabolic class boundary data

Description

Parabolic class boundary data

Details

These data were simulated. There are two correlated predictors and two classes in the factor outcome.

Value

parabolic a data frame

Examples

```
data(parabolic)
```

pathology	<i>Liver pathology data</i>
-----------	-----------------------------

Description

Liver pathology data

Details

These data have the results of a *x*-ray examination to determine whether liver is abnormal or not (in the scan column) versus the more extensive pathology results that approximate the truth (in pathology).

Value

pathology a data frame

Source

Altman, D.G., Bland, J.M. (1994) "Diagnostic tests 1: sensitivity and specificity," *British Medical Journal*, vol 308, 1552.

Examples

```
data(pathology)
str(pathology)
```

pd_speech	<i>Parkinson's disease speech classification data set</i>
-----------	-----------------------------------------------------------

Description

Parkinson's disease speech classification data set

Details

From the UCI ML archive, the description is "The data used in this study were gathered from 188 patients with PD (107 men and 81 women) with ages ranging from 33 to 87 (65.1 p/m 10.9) at the Department of Neurology in Cerrahpaşa Faculty of Medicine, Istanbul University. The control group consists of 64 healthy individuals (23 men and 41 women) with ages varying between 41 and 82 (61.1 p/m 8.9). During the data collection process, the microphone is set to 44.1 KHz and following the physician's examination, the sustained phonation of the vowel /a/ was collected from each subject with three repetitions."

The data here are averaged over the replicates.

Value

pd_speech a data frame

Source

UCI ML repository (data) <https://archive.ics.uci.edu/ml/datasets/Parkinson%27s+Disease+Classification#>,

Sakar et al (2019), "A comparative analysis of speech signal processing algorithms for Parkinson's disease classification and the use of the tunable Q-factor wavelet transform", *Applied Soft Computing*, V74, pg 255-263.

Examples

```
data(pd_speech)
str(pd_speech)
```

penguins

Palmer Station penguin data

Description

A data set from Gorman, Williams, and Fraser (2014) containing measurements from different types of penguins. This version of the data was retrieved from Allison Horst's palmerpenguins package on 2020-06-22.

Value

penguins a tibble

Source

Gorman KB, Williams TD, Fraser WR (2014) Ecological Sexual Dimorphism and Environmental Variability within a Community of Antarctic Penguins (*Genus Pygoscelis*). PLoS ONE 9(3): e90081. doi: [10.1371/journal.pone.0090081](https://doi.org/10.1371/journal.pone.0090081)

<https://github.com/allisonhorst/palmerpenguins>

Sacramento	<i>Sacramento CA home prices</i>
------------	----------------------------------

Description

This data frame contains house and sale price data for 932 homes in Sacramento CA. The original data were obtained from the website for the SpatialKey software. From their website: "The Sacramento real estate transactions file is a list of 985 real estate transactions in the Sacramento area reported over a five-day period, as reported by the Sacramento Bee." Google was used to fill in missing/incorrect data.

Value

Sacramento a tibble

Source

SpatialKey website: <https://support.spatialkey.com/spatialkey-sample-csv-data/>

Examples

```
data(Sacramento)
```

scat	<i>Morphometric data on scat</i>
------	----------------------------------

Description

Reid (2015) collected data on animal feces in coastal California. The data consist of DNA verified species designations as well as fields related to the time and place of the collection and the scat itself. The data are on the three main species.

Value

scat a tibble

Source

Reid, R. E. B. (2015). A morphometric modeling approach to distinguishing among bobcat, coyote and gray fox scats. *Wildlife Biology*, 21(5), 254-262

small_fine_foods *Fine foods example data*

Description

Fine foods example data

Details

These data are from Amazon, who describe it as "This dataset consists of reviews of fine foods from amazon. The data span a period of more than 10 years, including all ~500,000 reviews up to October 2012. Reviews include product and user information, ratings, and a plaintext review."

A subset of the data are contained here and are split into a training and test set. The training set sampled 10 products and retained all of their individual reviews. Since the reviews within these products are correlated, we recommend resampling the data using a leave-one-product-out approach. The test set sampled 500 products that were not included in the training set and selected a single review at random for each.

There is a column for the product, a column for the text of the review, and a factor column for a class variable. The outcome is whether the reviewer gave the product a 5-star rating or not.

Value

training_data, testing_data
tibbles

Source

<https://snap.stanford.edu/data/web-FineFoods.html>

Examples

```
data(small_fine_foods)
str(training_data)
```

Smithsonian *Smithsonian museums*

Description

Geocodes for the Smithsonian museums (circa 2018).

Value

Smithsonian a tibble

Source

https://en.wikipedia.org/wiki/List_of_Smithsonian_museums

Examples

```
data(Smithsonian)
Smithsonian
```

solubility_test	<i>Solubility predictions from MARS model</i>
-----------------	-----------------------------------------------

Description

Solubility predictions from MARS model

Details

For the solubility data in Kuhn and Johnson (2013), these data are the test set results for the MARS model. The observed solubility (in column solubility) and the model results (prediction) are contained in the data.

Value

```
solubility_test
a data frame
```

Source

Kuhn, M., Johnson, K. (2013) *Applied Predictive Modeling*, Springer

Examples

```
data(solubility_test)
str(solubility_test)
```

`stackoverflow`*Annual Stack Overflow Developer Survey Data*

Description

Annual Stack Overflow Developer Survey Data

Details

These data are a collection of 5,594 data points collected on developers. These data could be used to try to predict who works remotely (as used in the source listed below).

Value

`stackoverflow` a tibble

Source

Julia Silge, *Supervised Machine Learning Case Studies in R*

<https://supervised-ml-course.netlify.com/chapter2>

Raw data: <https://insights.stackoverflow.com/survey/>

Examples

```
data(stackoverflow)
```

`tate_text`*Tate Gallery modern artwork metadata*

Description

Metadata such as artist, title, and year created for recent artworks owned by the Tate Gallery. Only artworks created during or after 1990 are included, and the metadata source was last updated in 2014. The Tate Gallery provides these data but requests users to be respectful of their [guidelines for use](#).

Value

`tate_text` a tibble

Source

- <https://github.com/tategallery/collection>
- <https://www.tate.org.uk/>

Examples

```
data(tate_text)
str(tate_text)
```

two_class_dat	<i>Two class data</i>
---------------	-----------------------

Description

Two class data

Details

There are artificial data with two predictors (A and B) and a factor outcome variable (Class).

Value

two_class_dat a data frame

Examples

```
data(two_class_dat)
str(two_class_dat)
```

two_class_example	<i>Two class predictions</i>
-------------------	------------------------------

Description

Two class predictions

Details

These data are a test set from a model built for two classes ("Class1" and "Class2"). There are columns for the true and predicted classes and column for the probabilities for each class.

Value

two_class_example
a data frame

Examples

```
data(two_class_example)
str(two_class_example)
```

wa_churn	<i>Watson churn data</i>
----------	--------------------------

Description

Watson churn data

Details

These data were downloaded from the IBM Watson site (see below) in September 2018. The data contain a factor for whether a customer churned or not. Alternatively, the tenure column presumably contains information on how long the customer has had an account. A survival analysis can be done on this column using the churn outcome as the censoring information. A data dictionary can be found on the source website.

Value

wa_churn a data frame

Source

IBM Watson Analytics <https://ibm.co/2sOvyvy>

Examples

```
data(wa_churn)
str(wa_churn)
```


Index

* datasets

- ad_data, 2
 - ames, 3
 - attrition, 4
 - biomass, 5
 - bivariate, 5
 - car_prices, 6
 - cells, 6
 - check_times, 7
 - Chicago, 8
 - concrete, 9
 - covers, 9
 - credit_data, 10
 - crickets, 10
 - drinks, 11
 - grants, 11
 - hpc_cv, 12
 - hpc_data, 13
 - lending_club, 13
 - meats, 14
 - mlc_churn, 14
 - oils, 15
 - okc, 15
 - parabolic, 16
 - pathology, 17
 - pd_speech, 17
 - penguins, 18
 - Sacramento, 19
 - scat, 19
 - small_fine_foods, 20
 - Smithsonian, 20
 - solubility_test, 21
 - stackoverflow, 22
 - tate_text, 22
 - two_class_dat, 23
 - two_class_example, 23
 - wa_churn, 24
-
- ad_data, 2
 - ames, 3
 - attrition, 4
 - biomass, 5
 - bivariate, 5
 - bivariate_test (bivariate), 5
 - bivariate_train (bivariate), 5
 - bivariate_val (bivariate), 5
 - car_prices, 6
 - cells, 6
 - check_times, 7
 - Chicago, 8
 - concrete, 9
 - covers, 9
 - credit_data, 10
 - crickets, 10
 - drinks, 11
 - grants, 11
 - grants_2008 (grants), 11
 - grants_other (grants), 11
 - grants_test (grants), 11
 - hpc_cv, 12
 - hpc_data, 13
 - lending_club, 13
 - meats, 14
 - mlc_churn, 14
 - oils, 15
 - okc, 15
 - okc_text (okc), 15
 - parabolic, 16
 - pathology, 17
 - pd_speech, 17
 - penguins, 18
 - Sacramento, 19

scat, [19](#)
small_fine_foods, [20](#)
Smithsonian, [20](#)
solubility_test, [21](#)
stackoverflow, [22](#)
stations (Chicago), [8](#)

tate_text, [22](#)
testing_data (small_fine_foods), [20](#)
training_data (small_fine_foods), [20](#)
two_class_dat, [23](#)
two_class_example, [23](#)

wa_churn, [24](#)