

# Package ‘moderate.mediation’

March 18, 2023

**Version** 0.0.2

**Date** 2023-03-17

**Title** Causal Moderated Mediation Analysis

**Maintainer** Xu Qin <xuqin@pitt.edu>

**Depends** R (>= 3.5.0)

**Imports** stats, mvtnorm, cowplot, distr, graphics, ggplot2, reshape2,  
doSNOW, scales, foreach

**Description** Causal moderated mediation analysis using the methods proposed by Qin and Wang (2022). Causal moderated mediation analysis is crucial for investigating how, for whom, and where a treatment is effective by assessing the heterogeneity of mediation mechanism across individuals and contexts. This package enables researchers to estimate and test the conditional and moderated mediation effects, assess their sensitivity to unmeasured pre-treatment confounding, and visualize the results. The package is built based on the quasi-Bayesian Monte Carlo method, because it has relatively better performance at small sample sizes, and its running speed is the fastest. The package is applicable to a treatment of any scale, a binary or continuous mediator, a binary or continuous outcome, and one or more moderators of any scale.

**License** GPL-2

**RoxygenNote** 7.2.3

**NeedsCompilation** no

**Author** Xu Qin [aut, cre, cph],  
Lijuan Wang [ctb]

**Repository** CRAN

**Date/Publication** 2023-03-18 08:40:02 UTC

## R topics documented:

modmed . . . . .	2
modmed.plot . . . . .	7
modmed.sens . . . . .	9
newws . . . . .	12
sens.plot . . . . .	13
summary_modmed . . . . .	14

---

modmed	<i>Causal Moderated Mediation Analysis 'modmed' is used to fit mediator and outcome models and estimate and test causal effects for causal moderated mediation analysis. It is applicable to a treatment of any scale, a binary or continuous mediator and outcome, one or more moderators of any scale, and a wide range of scenarios of moderated mediation.</i>
--------	--

---

### Description

Causal Moderated Mediation Analysis 'modmed' is used to fit mediator and outcome models and estimate and test causal effects for causal moderated mediation analysis. It is applicable to a treatment of any scale, a binary or continuous mediator and outcome, one or more moderators of any scale, and a wide range of scenarios of moderated mediation.

### Usage

```
modmed(
  data,
  treatment,
  mediator,
  outcome,
  covariates.disc = NULL,
  covariates.cont = NULL,
  moderators.disc = NULL,
  moderators.cont = NULL,
  m.model,
  y.model,
  comp.treatment.value = 1,
  ref.treatment.value = 0,
  comp.mod.disc.values = NULL,
  ref.mod.disc.values = NULL,
  comp.mod.cont.values = NULL,
  ref.mod.cont.values = NULL,
  m.scale = "continuous",
  y.scale = "continuous",
  method = "mc",
  nmc = 1000,
  nboot = 1000,
  conf.level = 0.95,
  seed = NULL,
  object = NULL,
  is.U = FALSE,
  b.m = NULL,
  b.y = NULL
)
```

**Arguments**

<code>data</code>	A data frame containing the variables in the analysis. Users need to impute any missing values in the data before running the function.
<code>treatment</code>	A character string indicating the name of the treatment variable.
<code>mediator</code>	A character string indicating the name of the mediator variable.
<code>outcome</code>	A character string indicating the name of the outcome variable.
<code>covariates.disc</code>	A name vector of all the discrete pretreatment covariates under study (string). The default is NULL. Users do not need to reformat discrete variables. If treatment is randomized, it should contain confounders of the mediator-outcome relationship. If treatment is not randomized, it should also contain confounders of the treatment-mediator and treatment-outcome relationships. Please do not include moderators here. The main effects of moderators are accounted for by including the moderators in the model of the main model intercept.
<code>covariates.cont</code>	A name vector of all the continuous pretreatment covariates under study (string). The default is NULL. If treatment is randomized, it should contain confounders of the mediator-outcome relationship. If treatment is not randomized, it should also contain confounders of the treatment-mediator and treatment-outcome relationships. Please do not include moderators here. The main effects of moderators are accounted for by including the moderators in the model of the main model intercept.
<code>moderators.disc</code>	A name vector of all the discrete moderator under study (string). The default is NULL.
<code>moderators.cont</code>	A name vector of all the continuous moderator under study (string). The default is NULL.
<code>m.model</code>	A list. The name of each element in the list is a predictor in the main mediator model. The names must include intercept, treatment, and the pretreatment covariates that are confounders of the mediator-outcome relationship but not moderators. If treatment is not randomized, pretreatment covariates that are confounders of the treatment-mediator relationship but not moderators should also be included. Each element of the list is a vector of the names of the moderators (string) of the coefficient of the main model predictor as represented by the name of the element. The moderators of the intercept must include all the moderators in the mediator model. If a main model coefficient is not moderated, then the corresponding vector should be specified as NULL. The set of the moderators contained in this list is a subset of the combination of <code>moderators.disc</code> and <code>moderators.cont</code> . The set of moderators in <code>m.model</code> and that in <code>y.model</code> are not necessarily the same. The union of the two sets of moderators should be contained in the union of <code>moderators.disc</code> , and <code>moderators.cont</code> . If no moderators are specified, only the population average mediation effects are estimated and tested. Check examples for details.
<code>y.model</code>	A list. The name of each element in the list is a predictor in the main outcome model. The names must include intercept, treatment, mediator, and the pretreatment covariates that are confounders of mediator-outcome relationship but not

moderators. If treatment is not randomized, pretreatment covariates that are confounders of the treatment-outcome relationship but not moderators should also be included. If the treatment is assumed to interact with the mediator when affecting the outcome, an additional element should be added to `y.model`, named as "tm". Each element of the list is a vector of the names of the moderators (string) of the coefficient of the main model predictor as represented by the name of the element. The moderators of the intercept must include all the moderators in the mediator model. If a main model coefficient is not moderated, then the corresponding vector should be specified as NULL. The set of the moderators contained in this list is a subset of the combination of `moderators.disc` and `moderators.cont`. The set of moderators in `m.model` and that in `y.model` are not necessarily the same. The union of the two sets of moderators should be contained in the union of `moderators.disc`, and `moderators.cont`. If no moderators are specified, only the population average mediation effects are estimated and tested. Check examples for details.

`comp.treatment.value`

If the total treatment effect for each individual is defined as  $Y(t) - Y(t')$ , `comp.treatment.value` refers to  $t$ . The default is 1.

`ref.treatment.value`

If the total treatment effect for each individual is defined as  $Y(t) - Y(t')$ , `ref.treatment.value` refers to  $t'$ . The default is 0.

`comp.mod.disc.values`

A vector of compare values of the discrete moderators given which the conditional causal effects are estimated. The default is NULL. The length and order of `comp.mod.disc.values` should be the same as `moderators.disc`. If one does not want to condition some moderators on specific values, one may specify their values to be NA. If the discrete moderators take the same compare value, `comp.moderator.disc.values` can be specified as a single value. If not NULL, results contrasting the causal effects given compare moderator values with those given reference moderator values will be reported.

`ref.mod.disc.values`

A vector of reference values of the discrete moderators given which the conditional causal effects are estimated. The default is NULL. The length and order of `ref.mod.disc.values` should be the same as `moderators.disc`. If one does not want to condition some moderators on specific values, one may specify their values to be NA. If the discrete moderators take the same reference value, `ref.moderator.disc.values` can be specified as a single value. The moderators whose reference values are specified must be included in either the mediator model or the outcome model or both.

`comp.mod.cont.values`

A vector of compare values of the continuous moderators given which the conditional causal effects are estimated. The default is NULL. The length and order of `comp.mod.cont.values` should be the same as `moderators.cont`. If one does not want to condition some moderators on specific values, one may specify their values to be NA. If the continuous moderators take the same compare value, `comp.moderator.cont.values` can be specified as a single value. If not NULL, results contrasting the causal effects given compare moderator values with those given reference moderator values will be reported.

ref.mod.cont.values	A vector of reference values of the continuous moderators given which the conditional causal effects are estimated. The default is NULL. The length and order of ref.mod.cont.values should be the same as moderators.cont. If one does not want to condition some moderators on specific values, one may specify their values to be NA. If the continuous moderators take the same reference value, ref.moderator.cont.values can be specified as a single value. The moderators whose reference values are specified must be included in either the mediator model or the outcome model or both.
m.scale	A character string indicating the scale of the mediator. "continuous" if the mediator is continuous. "binary" if the mediator is binary. Logistic regression is fitted in this case. The default is "continuous".
y.scale	A character string indicating the scale of the outcome. "continuous" if the outcome is continuous. "binary" if the outcome is binary. Probit link is used in this case. The default is "continuous".
method	Estimation and inference method. if 'mc', the Monte Carlo method is used; if 'boot', bootstrap is used. Default is 'mc'. When sample size is relatively small and the mediator or binary is binary, 'boot' is preferred. Otherwise, 'mc' is more recommended, mainly because its running speed is much faster.
nmc	Number of simulations involved in the Monte Carlo algorithm. Used if method = 'mc'. The default value is 1000.
nboot	Number of bootstrapped samples involved in the bootstrapping algorithm. Used if method = 'boot'. The default value is 1000.
conf.level	Level of the returned two-sided confidence intervals. The default is 0.95, which returns the 2.5 and 97.5 percentiles.
seed	The seed for the random number generator. The default value is NULL.
object	Output from the original analysis only if is.U = TRUE. NULL in the original analysis. The default is NULL.
is.U	A logical value. 'FALSE' in the original analysis. 'TRUE' in the sensitivity analysis which adjusts for a simulated unmeasured pretreatment confounder U. The default is FALSE.
b.m	Sensitivity parameter that represents the conditional association between the unobserved pretreatment confounder and the mediator. It is NULL in the original analysis. The default is NULL.
b.y	Sensitivity parameter that represents the conditional association between the unobserved pretreatment confounder and the outcome. It is NULL in the original analysis. The default is NULL.

### Value

A list containing

effects	Estimation results of the causal effects. "TIE" indicates the total indirect effect, "PDE" indicates the pure direct effect, and "INT" indicates the natural treatment-by-mediator interaction effect. "TIE.ref", "PDE.ref", and "INT.ref" indicate the corresponding effects when the moderators take the reference values. "TIE.dif",
---------	---

	"PDE.dif", and "INT.dif" each indicates the difference in the corresponding effect between the compare levels and the reference levels of the moderators.
m.model	Estimation results of the mediator model
y.model	Estimation results of the outcome model
results	1000 draws from the sampling distribution of the causal effects.
args	A list of the arguments specified in the function of modmed except for the default ones
args.full	The full list of all the arguments specified in the function of modmed
l.m	The mediator model
l.y	The outcome model
formula.m	The formula for the mediator model
formula.y	The formula for the outcome model
m.predictors	All the original predictors in the main mediator model
y.predictors	All the original predictors in the main outcome model
m.moderators	All the original moderators in the mediator model
y.moderators	All the original moderators in the outcome model
m.predictors.new	All the predictors in the main mediator model, in which the discrete confounders are transformed into multiple indicator codes.
y.predictors.new	All the predictors in the main outcome model, in which the discrete confounders are transformed into multiple indicator codes.
m.moderators.new	All the moderators in the mediator model, in which the discrete confounders are transformed into multiple indicator codes.
y.moderators.new	All the moderators in the outcome model, in which the discrete confounders are transformed into multiple indicator codes.
predict.m.data.ref	Data for prediction of the conditional potential mediator at the reference level of the moderators.
predict.m.data.comp	Data for prediction of the conditional potential mediator at the compare level of the moderators.
predict.m.data	Data for prediction of the marginal potential mediator
predict.y.data.ref	Data for prediction of the conditional potential outcome at the reference level of the moderators.
predict.y.data.comp	Data for prediction of the conditional potential outcome at the compare level of the moderators.
predict.y.data	Data for prediction of the marginal potential outcome
data	The data used in the analysis

**Author(s)**

Xu Qin and Lijuan Wang

**References**

Qin, X., & Wang, L. (2022). Causal Moderated Mediation Analysis.

**Examples**

```
data(newws)
modmed.results = modmed(data = newws, treatment = "treat", mediator = "emp",
  outcome = "depression", covariates.disc = c("emp_prior", "nevmar",
    "hispanic", "nohsdip"), covariates.cont = c("workpref", "attitude",
    "depress_prior"), moderators.disc = "CHCNT", moderators.cont = "ADCPC",
  m.model = list(intercept = c("ADCPC", "CHCNT"), treatment = c("ADCPC",
    "CHCNT"), emp_prior = NULL, nevmar = NULL, hispanic = NULL,
    nohsdip = NULL, workpref = NULL, attitude = NULL, depress_prior = NULL),
  y.model = list(intercept = c("ADCPC", "CHCNT"), treatment = c("ADCPC",
    "CHCNT"), mediator = c("ADCPC", "CHCNT"), tm = c("ADCPC",
    "CHCNT"), emp_prior = NULL, nevmar = NULL, hispanic = NULL,
    nohsdip = NULL, workpref = NULL, attitude = NULL, depress_prior = NULL),
  comp.mod.disc.values = 3, ref.mod.disc.values = 2, comp.mod.cont.values = 5050,
  ref.mod.cont.values = 5050, m.scale = "binary", y.scale = "continuous",
  seed = 1)
```

---

modmed.plot

*Visual Representation of the Causal Moderated Mediation Analysis Results 'modmed.plot' is used to visualize results from modmed function. This applies only if moderators.disc or moderators.cont is not NULL. The plot consists of two parts. The top represents the sampling distribution of the specified causal effect as a function of the specified moderator within the given levels of the other moderators. The bottom represents the distribution of the specified moderator on the x axis.*

---

**Description**

Visual Representation of the Causal Moderated Mediation Analysis Results 'modmed.plot' is used to visualize results from modmed function. This applies only if moderators.disc or moderators.cont is not NULL. The plot consists of two parts. The top represents the sampling distribution of the specified causal effect as a function of the specified moderator within the given levels of the other moderators. The bottom represents the distribution of the specified moderator on the x axis.

**Usage**

```
modmed.plot(
  object,
  effect,
  moderator,
```

```

other.mod.disc.values = NULL,
other.mod.cont.values = NULL,
is.dist.moderator = FALSE,
probs = c(0.1, 0.25, 0.5, 0.75, 0.9)
)

```

### Arguments

object	Output from the modmed function.
effect	A character string indicating which causal effect to be plotted. effect can be specified as "TIE", "PIE", "PDE", "TDE", "INT", "TIE.ref", "PIE.ref", "PDE.ref", "TDE.ref", "INT.ref", "TIE.dif", "PIE.dif", "PDE.dif", "TDE.dif", or "INT.dif".
moderator	A character string indicating which moderator to be plotted. It must be one of the moderators specified in the function of modmed.
other.mod.disc.values	A vector of values of the other discrete moderators given which the conditional effect at each value of the specified moderator is estimated. The order of other.mod.disc.values should be the same as moderators.disc specified in the function of modmed, with the specified moderator removed if the specified moderator is discrete. If one does not want to condition some moderators on specific values, one may specify their values to be NA. NULL if there are no other discrete moderators.
other.mod.cont.values	A vector of values of the other continuous moderators given which the conditional effect at each value of the specified moderator is estimated. The order of other.mod.cont.values should be the same as moderators.cont specified in the function of modmed, with the specified moderator removed if the specified moderator is continuous. If one does not want to condition some moderators on specific values, one may specify their values to be NA. NULL if there are no other continuous moderators.
is.dist.moderator	A logical value. "TRUE" if distribution of the specified moderator is to be plotted at the bottom, and "FALSE" if not. The default is "FALSE".
probs	A vector of percentiles to be plotted on the distribution of the moderator if the moderator is continuous. NULL if is.dist.moderator = FALSE. The default is c(0.1, 0.25, 0.5, 0.75, 0.9).

### Value

modmed returns causal moderated mediation analysis results. The plot.modmed function plots the results.

### Author(s)

Xu Qin and Lijuan Wang

### References

Qin, X., & Wang, L. (2022). Causal Moderated Mediation Analysis.



## Examples

```

data(newws)
modmed.results = modmed(data = newws, treatment = "treat", mediator = "emp",
  outcome = "depression", covariates.disc = c("emp_prior", "nevmar",
    "hispanic", "nohsdip"), covariates.cont = c("workpref", "attitude",
    "depress_prior"), moderators.disc = "CHCNT", moderators.cont = "ADCPC",
  m.model = list(intercept = c("ADCPC", "CHCNT"), treatment = c("ADCPC",
    "CHCNT"), emp_prior = NULL, nevmar = NULL, hispanic = NULL,
    nohsdip = NULL, workpref = NULL, attitude = NULL, depress_prior = NULL),
  y.model = list(intercept = c("ADCPC", "CHCNT"), treatment = c("ADCPC",
    "CHCNT"), mediator = c("ADCPC", "CHCNT"), tm = c("ADCPC",
    "CHCNT"), emp_prior = NULL, nevmar = NULL, hispanic = NULL,
    nohsdip = NULL, workpref = NULL, attitude = NULL, depress_prior = NULL),
  comp.mod.disc.values = 3, ref.mod.disc.values = 2, comp.mod.cont.values = 5050,
  ref.mod.cont.values = 5050, m.scale = "binary", y.scale = "continuous",
  seed = 1)
modmed.plot(modmed.results, effect = "TIE", moderator = "ADCPC",
  other.mod.disc.values = 1, is.dist.moderator = TRUE)

```

---

modmed.sens

*Simulation-Based Sensitivity Analysis Table for Causal Moderated Mediation Analysis modmed.sens' is used to evaluate the sensitivity of the estimated causal effects obtained from modmed function to potential violations of the ignorability assumptions from the frequentist perspective. It estimates the causal effects after adjusting for an unmeasured pretreatment confounder, U, with a specified degree of confounding. In a randomized experiment, the degree of confounding is evaluated via two sensitivity parameters, the coefficient of U in the mediator model and that in the outcome model, given the specified prior distribution of U. When the treatment is not randomized, an additional sensitivity parameter is introduced – the coefficient of U in the treatment model. The treatment, mediator, outcome, and unmeasured pretreatment confounder could be either binary or continuous.*

---

## Description

Simulation-Based Sensitivity Analysis Table for Causal Moderated Mediation Analysis modmed.sens' is used to evaluate the sensitivity of the estimated causal effects obtained from modmed function to potential violations of the ignorability assumptions from the frequentist perspective. It estimates the causal effects after adjusting for an unmeasured pretreatment confounder, U, with a specified degree of confounding. In a randomized experiment, the degree of confounding is evaluated via two sensitivity parameters, the coefficient of U in the mediator model and that in the outcome model, given the specified prior distribution of U. When the treatment is not randomized, an additional sensitivity parameter is introduced – the coefficient of U in the treatment model. The treatment, mediator, outcome, and unmeasured pretreatment confounder could be either binary or continuous.

**Usage**

```

modmed.sens(
  object,
  range.b.m = NULL,
  range.b.y = NULL,
  grid.b.m = 20,
  grid.b.y = 20,
  U.scale = "binary",
  p.u = 0.5,
  sigma.u = 1,
  t.rand = TRUE,
  t.model = NULL,
  t.scale = "binary",
  b.t = NULL,
  iter = 10,
  nsim = 5,
  ncore = detectCores()
)

```

**Arguments**

object	Output from the modmed function.
range.b.m	The range of the sensitivity parameter that represents the slope of the unmeasured pretreatment confounder in the standardized mediator model, in which both the independent and dependent variables are standardized. If the dependent variable is binary, its latent index is standardized instead. E.g., it can be specified as $c(-2, 2)$ . If NULL, the upper bound of the range is determined by 2 times the maximum magnitude of the standardized conditional effect of the existing pretreatment confounders with the mediator. The lower bound is the negative of the upper bound. The default is NULL.
range.b.y	The range of the sensitivity parameter that represents the slope of the unmeasured pretreatment confounder in the standardized outcome model, in which both the independent and dependent variables are standardized. If the dependent variable is binary, its latent index is standardized instead. E.g., it can be specified as $c(-2, 2)$ . If NULL, the upper bound of the range is determined by 2 times the maximum magnitude of the standardized conditional effect of the existing pretreatment confounders with the outcome. The lower bound is the negative of the upper bound. The default is NULL.
grid.b.m	The horizontal dimension of the grid. The default is 20. Increase the number for more smooth curves.
grid.b.y	The vertical dimension of the grid. The default is 20. Increase the number for more smooth curves.
U.scale	The scale of the unobserved pretreatment confounder (string). Can be "continuous" or "binary". The default is "binary".
p.u	This needs to be specified only if U.scale = "binary". The prior probability of the unobserved pretreatment confounder if it is binary. The default is 0.5.

<code>sigma.u</code>	This needs to be specified only if <code>U.scale = "continuous"</code> . The standard deviation of the prior distribution of the unobserved pretreatment confounder if it is continuous. The default is 1.
<code>t.rand</code>	TRUE if the treatment is randomized, and FALSE if not. The default is TRUE.
<code>t.model</code>	A list. The default is NULL. This needs to be specified only if <code>t.rand = FALSE</code> because a treatment model is required for the derivation of the conditional distribution of the unmeasured pretreatment confounder. The names of the list must include intercept and the pretreatment covariates that are predictors but not moderators in the treatment model. The pretreatment covariates should be contained in the union of <code>covariates.disc</code> , and <code>covariates.cont</code> . Each element of the list is a vector of the names of the moderators (string) of the coefficient of the main model predictor as represented by the name of the element. The moderators of the intercept must include all the moderators in the treatment model. If a main model coefficient is not moderated, then the corresponding vector should be specified as NULL. The moderators should be contained in the union of <code>moderators.disc</code> , and <code>moderators.cont</code> .
<code>t.scale</code>	The scale of the treatment (string). Can be "continuous" or "binary". The default is "binary".
<code>b.t</code>	This needs to be specified only if <code>t.rand = FALSE</code> . The value of the sensitivity parameter that represents the slope of the unmeasured pretreatment confounder in the standardized treatment model, in which both the independent and dependent variables are standardized. If the dependent variable is binary, its latent index is standardized instead. When <code>t.rand = TRUE</code> , <code>b.t</code> is NULL, because when the treatment is randomized, there is no need to specify this sensitivity parameter. Hence, the default of <code>b.t</code> is NULL.
<code>iter</code>	The number of iterations in the stochastic EM algorithm for generating the unobserved pretreatment confounder. The default is 10.
<code>nsim</code>	The number of random draws of the unobserved pretreatment confounder in each cell. The default is 5. Increase the number for more smooth curves.
<code>ncore</code>	The number of cores for parallel computing. The default is the number of CPU cores on the current host.

### Value

	A list containing
<code>X.coef.plot</code>	the slopes of the observed pretreatment confounders in the standardized mediator and outcome models (which are used to calibrate the strength of the sensitivity parameters in the sensitivity plots).
<code>b.t</code>	same as specified in the <code>modmed.sens</code> function if <code>b.t</code> is not NULL.
<code>range.b.m</code> , <code>range.b.y</code>	the value range of each sensitivity parameter.
<code>b.m.all</code> , <code>b.y.all</code>	all the specific values of the sensitivity parameters for constructing the grids.
<code>results.new</code>	tables for the causal effect estimates, standard errors, and p values in all the grids, after the adjustment of the unobserved pretreatment confounder.

**Author(s)**

Xu Qin and Fan Yang

**References**

Qin, X., & Yang, F. (2020). Simulation-Based Sensitivity Analysis for Causal Mediation Studies.

**Examples**

```
data(newws)
modmed.results = modmed(data = newws, treatment = "treat", mediator = "emp",
  outcome = "depression", covariates.disc = c("emp_prior", "nevmar",
    "hispanic", "nohsdip"), covariates.cont = c("workpref",
    "attitude", "depress_prior"), moderators.disc = "CHCNT",
  moderators.cont = "ADCPC", m.model = list(intercept = c("ADCPC",
    "CHCNT"), treatment = c("ADCPC", "CHCNT"), emp_prior = NULL,
    nevmar = NULL, hispanic = NULL, nohsdip = NULL, workpref = NULL,
    attitude = NULL, depress_prior = NULL), y.model = list(intercept = c("ADCPC",
    "CHCNT"), treatment = c("ADCPC", "CHCNT"), mediator = c("ADCPC",
    "CHCNT"), tm = c("ADCPC", "CHCNT"), emp_prior = NULL, nevmar = NULL,
    hispanic = NULL, nohsdip = NULL, workpref = NULL, attitude = NULL,
    depress_prior = NULL), comp.mod.disc.values = 3, ref.mod.disc.values = 2,
  comp.mod.cont.values = 5050, ref.mod.cont.values = 5050, m.scale = "binary",
  y.scale = "continuous", seed = 1)
sens.results = modmed.sens(modmed.results, U.scale = "binary",
  grid.b.m = 2, grid.b.y = 2, iter = 2, nsim = 2, ncore = 1)
sens.results = modmed.sens(modmed.results, U.scale = "binary",
  t.model = list(intercept = c("ADCPC", "CHCNT"), emp_prior = "ADCPC",
    nevmar = "CHCNT", hispanic = NULL, nohsdip = NULL, workpref = NULL,
    attitude = NULL, depress_prior = NULL), grid.b.m = 2, grid.b.y = 2,
  iter = 2, nsim = 2, ncore = 1)
```

---

newws

*NEWWS Riverside data*

---

**Description**

The National Evaluation of Welfare-to-Work Strategies (NEWWS) was conducted before the nationwide welfare reform in the mid-1990s. Participants of the study consist of applicants to the Aid to Families with Dependent Children (AFDC) program and current AFDC recipients who were not working for 30 or more hours per week. They were randomly assigned to the labor force attachment (LFA) program, which aimed at moving low-income parents from welfare to work by providing employment-focused incentives and services, and the control group, which received aid from AFDC without requirement for working. The data is from the Riverside sample. It includes 694 participants with preschool-age children, 208 randomly assigned to the LFA program and 486 randomly assigned to the control group. The National Evaluation of Welfare-to-Work Strategies (NEWWS) Riverside study.

**Value**

A list containing

treat	Treatment is a binary variable, taking the value of 1 if a participant was assigned to LFA and 0 otherwise
emp	Mediator is a binary variable, taking the value of 1 if one was ever employed during the two-year period after randomization and 0 if not.
depression	Outcome, maternal depression at the end of the second year after randomization, is a summary score of 12 items measuring depressive symptoms during the past week on a 0-3 scale.
nevmar	1 if never married and 0 otherwise.
emp_prior	1 if employed and 0 otherwise.
hispanic	1 if Hispanic and 0 otherwise.
CHCNT	1 if had 1 child, 2 if had 2 children, and 3 if had 3 or more children before randomization.
ADCPC	welfare amount in the year before randomization
attitude	a composite score of two attitude items - so many family problems that I cannot work at a full time or part time job; so much to do during the day that I cannot go to a school or job training program - measured on the scale of 1-4.
depress_prior	a composite score of three depressive symptom items - sad, depressed, blues, and lonely - in the week before randomization measured on the scale of 1-4.
workpref	one's level of preference for taking care of family full time than working on the scale of 1-4.
nohsdip	1 if had never obtained a high school diploma or a General Educational Development certificate and 0 otherwise.

---

sens.plot	<i>Simulation-Based Sensitivity Analysis Plot for Causal Moderated Mediation Analysis</i>
-----------	---

---

**Description**

Simulation-Based Sensitivity Analysis Plot for Causal Moderated Mediation Analysis

**Usage**

```
sens.plot(object, sens.results, effect)
```

**Arguments**

object	Output from the modmed function.
sens.results	An output from the modmed.sens function.
effect	The name of the effect whose sensitivity analysis results are to be plotted (string). effect can be specified as "TIE", "PIE", "PDE", "TDE", "INT", "TIE.ref", "PIE.ref", "PDE.ref", "TDE.ref", "INT.ref", "TIE.dif", "PIE.dif", "PDE.dif", "TDE.dif", or "INT.dif".

**Value**

Sensitivity analysis plots for the causal effects in the causal moderated mediation analysis.

**Author(s)**

Xu Qin and Fan Yang

**References**

Qin, X., & Yang, F. (2020). Simulation-Based Sensitivity Analysis for Causal Mediation Studies.

**Examples**

```
data(newws)
modmed.results = modmed(data = newws, treatment = "treat", mediator = "emp",
  outcome = "depression", covariates.disc = c("emp_prior", "nevmar",
    "hispanic", "nohsdip"), covariates.cont = c("workpref", "attitude",
    "depress_prior"), moderators.disc = "CHCNT", moderators.cont = "ADCPC",
  m.model = list(intercept = c("ADCPC", "CHCNT"), treatment = c("ADCPC",
    "CHCNT"), emp_prior = NULL, nevmar = NULL, hispanic = NULL,
    nohsdip = NULL, workpref = NULL, attitude = NULL, depress_prior = NULL),
  y.model = list(intercept = c("ADCPC", "CHCNT"), treatment = c("ADCPC",
    "CHCNT"), mediator = c("ADCPC", "CHCNT"), tm = c("ADCPC",
    "CHCNT"), emp_prior = NULL, nevmar = NULL, hispanic = NULL,
    nohsdip = NULL, workpref = NULL, attitude = NULL, depress_prior = NULL),
  comp.mod.disc.values = 3, ref.mod.disc.values = 2, comp.mod.cont.values = 5050,
  ref.mod.cont.values = 5050, m.scale = "binary", y.scale = "continuous",
  seed = 1)
sens.results = modmed.sens(modmed.results, U.scale = "binary", grid.b.m = 2,
  grid.b.y = 2, iter = 2, nsim = 2, ncore = 1)
sens.plot(modmed.results, sens.results, "PIE")
```

---

summary\_modmed

*Summarizing Output for Causal Moderated Mediation Analysis 'summary\_modmed' is used to report from causal moderated mediation analysis*

---

**Description**

Summarizing Output for Causal Moderated Mediation Analysis 'summary\_modmed' is used to report from causal moderated mediation analysis

**Usage**

summary\_modmed(object)

**Arguments**

object                    output from modmed function

**Value**

modmed returns causal moderated mediation analysis results. The summary\_modmed function provides summary tables of the results.

**Author(s)**

Xu Qin and Lijuan Wang

**References**

Qin, X., & Wang, L. (2022). Causal Moderated Mediation Analysis.

**Examples**

```
data(newws)
modmed.results = modmed(data = newws, treatment = "treat", mediator = "emp",
  outcome = "depression", covariates.disc = c("emp_prior", "nevmar",
    "hispanic", "nohsdip"), covariates.cont = c("workpref", "attitude",
    "depress_prior"), moderators.disc = "CHCNT", moderators.cont = "ADCPC",
  m.model = list(intercept = c("ADCPC", "CHCNT"), treatment = c("ADCPC",
    "CHCNT"), emp_prior = NULL, nevmar = NULL, hispanic = NULL,
    nohsdip = NULL, workpref = NULL, attitude = NULL, depress_prior = NULL),
  y.model = list(intercept = c("ADCPC", "CHCNT"), treatment = c("ADCPC",
    "CHCNT"), mediator = c("ADCPC", "CHCNT"), tm = c("ADCPC",
    "CHCNT"), emp_prior = NULL, nevmar = NULL, hispanic = NULL,
    nohsdip = NULL, workpref = NULL, attitude = NULL, depress_prior = NULL),
  comp.mod.disc.values = 3, ref.mod.disc.values = 2, comp.mod.cont.values = 5050,
  ref.mod.cont.values = 5050, m.scale = "binary", y.scale = "continuous",
  seed = 1)
summary_modmed(modmed.results)
```

# Index

`modmed`, [2](#)

`modmed.plot`, [7](#)

`modmed.sens`, [9](#)

`news`, [12](#)

`sens.plot`, [13](#)

`summary_modmed`, [14](#)