

Package ‘ows4R’

May 9, 2026

Version 0.5

Date 2025-06-13

Title Interface to OGC Web-Services (OWS)

Maintainer Emmanuel Blondel <emmanuel.blondel1@gmail.com>

Depends R (>= 3.3.0)

Imports methods, R6, httr, openssl, keyring, XML (>= 3.96-1.1),
geometa (>= 0.9), sf, terra, parallel, crayon

Suggests testthat, knitr, markdown

Description Provides an Interface to Web-Services defined as standards by the Open Geospatial Consortium (OGC), including Web Feature Service (WFS) for vector data, Web Coverage Service (WCS), Catalogue Service (CSW) for ISO/OGC metadata, Web Processing Service (WPS) for data processes, and associated standards such as the common web-service specification (OWS) and OGC Filter Encoding. Partial support is provided for the Web Map Service (WMS). The purpose is to add support for additional OGC service standards such as Web Coverage Processing Service (WCPS), the Sensor Observation Service (SOS), or even new standard services emerging such OGC API or SensorThings.

License MIT + file LICENSE

URL <https://github.com/eblondel/ows4R>,
<https://eblondel.github.io/ows4R/>,
<https://www.ogc.org/standards/>

BugReports <https://github.com/eblondel/ows4R/issues>

LazyLoad yes

RoxygenNote 7.3.1

VignetteBuilder knitr

NeedsCompilation no

Author Emmanuel Blondel [aut, cre] (ORCID:
<<https://orcid.org/0000-0002-5870-5762>>),
Alexandre Bennici [ctb] (ORCID:

<<https://orcid.org/0000-0003-2160-3487>>),
Norbert Billet [ctb]

Repository CRAN

Date/Publication 2025-06-15 00:30:06 UTC

Contents

And	4
BBOX	5
BinaryComparisonOpType	6
BinaryLogicOpType	8
CASClient	9
CSWCapabilities	10
CSWClient	12
CSWConstraint	17
CSWDescribeRecord	19
CSWGetRecordById	20
CSWGetRecords	22
CSWHarvest	24
CSWQuery	25
CSWRecordProperty	28
CSWTransaction	29
getOWSNamespace	31
getOWSNamespace	31
Not	32
OGCAbstractObject	33
OGCExpression	36
OGCFilter	38
Or	39
ows4R	40
OWSBoundingBox	41
OWSCapabilities	43
OWSClient	46
OWSCodeType	49
OWSException	50
OWSGetCapabilities	51
OWSHttpRequest	53
OWSNamespace	56
OWSOperation	57
OWSOperationsMetadata	59
OWSRequest	60
OWSServiceIdentification	61
OWSServiceProvider	63
OWSUtils	65
OWSWG84BoundingBox	66
PropertyIsBetween	67
PropertyIsEqualTo	68

PropertyIsGreaterThan	69
PropertyIsGreaterThanOrEqualTo	70
PropertyIsLessThan	71
PropertyIsLessThanOrEqualTo	72
PropertyIsLike	74
PropertyIsNotEqualTo	75
PropertyIsNull	76
registerOWSNamespace	77
setOWSNamespace	78
UnaryLogicOpType	78
WCSCapabilities	80
WCSClient	81
WCSCoverage	84
WCSCoverageDescription	86
WCSCoverageDomain	88
WCSCoverageFilenameHandler	90
WCSCoverageSpatialDomain	90
WCSCoverageSummary	92
WCSCoverageTemporalDomain	96
WCSDescribeCoverage	97
WCSGetCoverage	99
WCSGridCRS	101
WCSGSElevationDomain	102
WCSGSTimeDomain	103
WFSCapabilities	105
WFSClient	106
WFSDescribeFeatureType	109
WFSFeatureType	110
WFSFeatureTypeElement	114
WFSGetFeature	116
WMSCapabilities	117
WMSClient	119
WMSGetFeatureInfo	122
WMSLayer	124
WPSBoundingBoxData	128
WPSCapabilities	129
WPSClient	131
WPSComplexData	134
WPSComplexInputDescription	136
WPSComplexOutputDescription	137
WPSDescribeProcess	138
WPSDescriptionParameter	140
WPSException	141
WPSExecute	143
WPSExecuteResponse	145
WPSFormat	147
WPSInput	149
WPSInputDescription	150

WPSLiteralData	152
WPSLiteralInputDescription	153
WPSLiteralOutputDescription	155
WPSOutput	156
WPSOutputDescription	158
WPSParameter	159
WPSProcess	160
WPSProcessDescription	162
WPSResponseDocument	165
WPSStatus	166

Index 168

And *And*

Description

And

And

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling an And operator

Super classes

[ows4R::OGCAbstractObject](#) -> [ows4R::OGCExpression](#) -> [ows4R::BinaryLogicOpType](#) -> And

Methods

Public methods:

- [And\\$new\(\)](#)
- [And\\$clone\(\)](#)

Method [new\(\)](#): Initializes an [And](#) expression

Usage:

[And\\$new\(...\)](#)

Arguments:

... list of objects of class [OGCExpression](#)

Method [clone\(\)](#): The objects of this class are cloneable with this method.

Usage:

```
And$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

Examples

```
expr1 <- PropertyIsEqualTo$new(PropertyName = "property1", Literal = "value1")
expr2 <- PropertyIsEqualTo$new(PropertyName = "property2", Literal = "value2")
and <- And$new(expr1,expr2)
and_xml <- and$encode() #see how it looks like in XML
```

BBOX

BBOX

Description

BBOX

BBOX

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling an BBOX

Super classes

[ows4R::OGCAbstractObject](#) -> [ows4R::OGCExpression](#) -> BBOX

Public fields

PropertyName property name field for XML encoding

Envelope envelope as object of class [GMLEnvelope](#) from **geometa**

Methods**Public methods:**

- [BBOX\\$new\(\)](#)
- [BBOX\\$clone\(\)](#)

Method `new()`: Initializes a [BBOX](#) expression

Usage:

```
BBOX$new(bbox, srsName = NULL)
```

Arguments:

`bbox` an object of class `matrix`

`srsName` srs name

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
BBOX$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondell@gmail.com>

Examples

```
bbox <- OWSUtils$toBBOX(-180,-90,180,90)
expr <- BBOX$new(bbox)
expr_xml <- expr$encode() #see how it looks like in XML
```

BinaryComparisonOpType

BinaryComparisonOpType

Description

BinaryComparisonOpType

BinaryComparisonOpType

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling an BinaryComparisonOpType

Super classes

[ows4R::OGCAbstractObject](#) -> [ows4R::OGCEXpression](#) -> BinaryComparisonOpType

Public fields

PropertyName property name field for XML encoding

Literal literal field for XML encoding

attrs attributes for XML encoding

Methods

Public methods:

- [BinaryComparisonOpType\\$new\(\)](#)
- [BinaryComparisonOpType\\$clone\(\)](#)

Method new(): Initializes an object extending [BinaryComparisonOpType](#)

Usage:

```
BinaryComparisonOpType$new(  
  element,  
  namespacePrefix,  
  PropertyName,  
  Literal,  
  matchCase = NA  
)
```

Arguments:

element element name

namespacePrefix XML namespace prefix

PropertyName property name

Literal literal

matchCase match case

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
BinaryComparisonOpType$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Note

abstract super class of all the property operation classes

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

BinaryLogicOpType *BinaryLogicOpType*

Description

BinaryLogicOpType

BinaryLogicOpType

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling an BinaryLogicOpType

Super classes

[ows4R::OGCAbstractObject](#) -> [ows4R::OGCEXpression](#) -> BinaryLogicOpType

Public fields

operations a list OGC expressions

Methods

Public methods:

- [BinaryLogicOpType\\$new\(\)](#)
- [BinaryLogicOpType\\$setExprVersion\(\)](#)
- [BinaryLogicOpType\\$clone\(\)](#)

Method `new()`: Initializes a [BinaryLogicOpType](#) expression

Usage:

```
BinaryLogicOpType$new(..., element, namespacePrefix, exprVersion = "1.1.0")
```

Arguments:

... list of objects of class [OGCEXpression](#)

element element

namespacePrefix namespacePrefix

exprVersion OGC expression version. Default is "1.1.0"

Method `setExprVersion()`: Sets expression version. The methods will control that expression versions are set for each of the operations specified in the expression.

Usage:

```
BinaryLogicOpType$setExprVersion(exprVersion)
```

Arguments:

exprVersion OGC expression version

Method clone(): The objects of this class are cloneable with this method.

Usage:

BinaryLogicOpType\$clone(deep = FALSE)

Arguments:

deep Whether to make a deep clone.

Note

abstract super class of all the binary logical operation classes

CASClient

CASClient

Description

CASClient

CASClient

Format

[R6Class](#) object.

Value

Object of [R6Class](#) with methods for interfacing a Central Authentication Service (CAS).

Methods

Public methods:

- [CASClient\\$new\(\)](#)
- [CASClient\\$getUrl\(\)](#)
- [CASClient\\$login\(\)](#)
- [CASClient\\$logout\(\)](#)
- [CASClient\\$clone\(\)](#)

Method new(): Initializes an object of class [CASClient](#)

Usage:

CASClient\$new(url)

Arguments:

url base URL of the Central Authentication Service (CAS)

Method getUrl(): Get CAS base URL

Usage:

CASClient\$getUrl()

Returns: the base URL

Method login(): Logs in the CAS

Usage:

CASClient\$login(user, pwd)

Arguments:

user user

pwd password

Returns: TRUE if logged in, FALSE otherwise

Method logout(): Logs out from the CAS

Usage:

CASClient\$logout()

Returns: TRUE if logged out, FALSE otherwise

Method clone(): The objects of this class are cloneable with this method.

Usage:

CASClient\$clone(deep = FALSE)

Arguments:

deep Whether to make a deep clone.

Note

Class used internally by **ows4R**

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

CSWCapabilities

CSWCapabilities

Description

CSWCapabilities

CSWCapabilities

Format

[R6Class](#) object.

Value

Object of [R6Class](#) with methods for interfacing an OGC Catalogue Service for the Web (CSW) Get Capabilities document.

Super classes

[ows4R::OGCAbstractObject](#) -> [ows4R::OWSCapabilities](#) -> CSWCapabilities

Methods**Public methods:**

- [CSWCapabilities\\$new\(\)](#)
- [CSWCapabilities\\$clone\(\)](#)

Method new(): Initializes a [CSWCapabilities](#) object

Usage:

```
CSWCapabilities$new(url, version, client = NULL, logger = NULL, ...)
```

Arguments:

url url

version version

client object of class [CSWClient](#)

logger logger type NULL, "INFO" or "DEBUG"

... any other parameter to pass to [OWSGetCapabilities](#) service request

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
CSWCapabilities$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Note

Class used to read a [CSWCapabilities](#) document. The use of [CSWClient](#) is recommended instead to benefit from the full set of capabilities associated to a CSW server.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

CSWClient

CSWClient

Description

CSWClient

CSWClient

Format[R6Class](#) object.**Value**Object of [R6Class](#) with methods for interfacing an OGC Catalogue Service for the Web.**Super classes**[ows4R::OGCAbstractObject](#) -> [ows4R::OWSClient](#) -> CSWClient**Methods****Public methods:**

- [CSWClient\\$new\(\)](#)
- [CSWClient\\$getCapabilities\(\)](#)
- [CSWClient\\$reloadCapabilities\(\)](#)
- [CSWClient\\$describeRecord\(\)](#)
- [CSWClient\\$getRecordById\(\)](#)
- [CSWClient\\$getRecords\(\)](#)
- [CSWClient\\$transaction\(\)](#)
- [CSWClient\\$insertRecord\(\)](#)
- [CSWClient\\$updateRecord\(\)](#)
- [CSWClient\\$deleteRecord\(\)](#)
- [CSWClient\\$deleteRecordById\(\)](#)
- [CSWClient\\$harvestRecord\(\)](#)
- [CSWClient\\$harvestNode\(\)](#)
- [CSWClient\\$clone\(\)](#)

Method new(): This method is used to instantiate a CSWClient with the url of the OGC service. Authentication is supported using basic auth (using user/pwd arguments), bearer token (using token argument), or custom (using headers argument). By default, the logger argument will be set to NULL (no logger). This argument accepts two possible values: INFO: to print only **ows4R** logs, DEBUG: to print more verbose logs

Usage:

```

CSWClient$new(
  url,
  serviceVersion = NULL,
  user = NULL,
  pwd = NULL,
  token = NULL,
  headers = c(),
  config = httr::config(),
  cas_url = NULL,
  logger = NULL
)

```

Arguments:

url url
serviceVersion CSW service version
user user
pwd password
token token
headers headers
config config
cas_url Central Authentication Service (CAS) URL
logger logger

Method getCapabilities(): Get CSW capabilities

Usage:

```
CSWClient$getCapabilities()
```

Returns: an object of class [CSWCapabilities](#)

Method reloadCapabilities(): Reloads CSW capabilities

Usage:

```
CSWClient$reloadCapabilities()
```

Method describeRecord(): Describe records. Retrieves the XML schema for CSW records. By default, returns the XML schema for the CSW records (<http://www.opengis.net/cat/csw/2.0.2>). For other schemas, specify the outputSchema required, e.g. <http://www.isotc211.org/2005/gmd> for ISO 19115/19139 schema

Usage:

```
CSWClient$describeRecord(namespace, ...)
```

Arguments:

namespace namespace
... any other parameter to pass to the [CSWDescribeRecord](#) service request

Returns: the service record description

Method getRecordById(): Get a record by Id. By default, the record will be returned following the CSW schema (<http://www.opengis.net/cat/csw/2.0.2>). For other schemas, specify the outputSchema required, e.g. <http://www.isotc211.org/2005/gmd> for ISO 19115/19139 records.

The parameter `elementSetName` should among values "full", "brief", "summary". The default "full" corresponds to the full metadata sheet returned. "brief" and "summary" will contain only a subset of the metadata content.

Usage:

```
CSWClient$getRecordById(id, elementSetName = "full", ...)
```

Arguments:

`id` record id

`elementSetName` element set name. Default is "full"

... any other parameter to pass to [CSWGetRecordById](#) service request

Returns: the fetched record, NULL otherwise

Method `getRecords()`: Get records based on a query, object of class `CSWQuery`. The maximum number of records can be set either for the full query (`maxRecords`) or per request (`maxRecordsPerRequest`, default set to 10 records) considering this operation is paginated. By default, the record will be returned following the CSW schema (<http://www.opengis.net/cat/csw/2.0.2>). For other schemas, specify the `outputSchema` required, e.g. <http://www.isotc211.org/2005/gmd> for ISO 19115/19139 records.

Usage:

```
CSWClient$getRecords(  
  query = CSWQuery$new(),  
  maxRecords = NULL,  
  maxRecordsPerRequest = 10L,  
  ...  
)
```

Arguments:

`query` an object of class [CSWQuery](#). By default, an empty query is set.

`maxRecords` max number of total records. Default is NULL meaning all records are returned.

`maxRecordsPerRequest` max number of records to return per request. Default set to 10.

... any other parameter to be passed to [CSWGetRecords](#) service request

Returns: the list of records. By default each record will be returned as Dublin Core list object. In case ISO 19115/19139 is set as `outputSchema`, each record will be object of class `ISOMetadata` from **geometa**.

Method `transaction()`: Generic transaction method. Used for inserting, updating or deleting metadata using the transactional CSW service. The `type` gives the type of transaction (Insert, Update, or Delete). The `record`

Usage:

```
CSWClient$transaction(  
  type,  
  record = NULL,  
  recordProperty = NULL,  
  constraint = NULL,  
  ...  
)
```

Arguments:

type of transaction either "Insert", "Update" or "Delete"
 record the record subject of the transaction
 recordProperty record property, object of class [CSWRecordProperty](#)
 constraint constraint, object of class [CSWConstraint](#)
 ... any other parameter to pass to [CSWTransaction](#) service request
Returns: TRUE if transaction succeeded, FALSE otherwise

Method insertRecord(): Inserts a new record

Usage:
 CSWClient\$insertRecord(record, ...)

Arguments:
 record record subject of the Insertion
 ... any other parameter to pass to the transaction

Returns: TRUE if insertion succeeded, FALSE otherwise

Method updateRecord(): Updates an existing record

Usage:
 CSWClient\$updateRecord(
 record = NULL,
 recordProperty = NULL,
 constraint = NULL,
 ...
)

Arguments:
 record record subject of the Insertion
 recordProperty record property, object of class [CSWRecordProperty](#)
 constraint constraint, object of class [CSWConstraint](#)
 ... any other parameter to pass to the transaction

Returns: TRUE if update succeeded, FALSE otherwise

Method deleteRecord(): Deletes an existing (set of) record(s). A constraint (object of class [CSWConstraint](#)) can be specified to limit the deletion to some records.

Usage:
 CSWClient\$deleteRecord(record = NULL, constraint = NULL, ...)

Arguments:
 record record subject of the Insertion
 constraint constraint, object of class [CSWConstraint](#)
 ... any other parameter to pass to the transaction

Returns: TRUE if deletion succeeded, FALSE otherwise

Method deleteRecordById(): Deletes an existing record by identifier (constraint used to identify the record based on its identifier).

Usage:

CSWClient\$deleteRecordById(id)

Arguments:

id record id

Returns: TRUE if deletion succeeded, FALSE otherwise

Method harvestRecord(): Harvests a single record from a sourceUrl, given a resourceType (by default "http://www.isotc211.org/2005/gmd").

Usage:

```
CSWClient$harvestRecord(
  sourceUrl,
  resourceType = "http://www.isotc211.org/2005/gmd"
)
```

Arguments:

sourceUrl source URL

resourceType resource type. Default is "http://www.isotc211.org/2005/gmd"

Returns: TRUE if harvesting succeeded, FALSE otherwise

Method harvestNode(): Harvests a CSW node (having its endpoint defined by an url). A query (object of class CSWQuery) can be specified if needed to restrain the harvesting to a subset. The resourceType defines the type of resources to be harvested (by default "http://www.isotc211.org/2005/gmd")

Usage:

```
CSWClient$harvestNode(
  url,
  query = CSWQuery$new(),
  resourceType = "http://www.isotc211.org/2005/gmd",
  sourceBaseUrl
)
```

Arguments:

url CSW node URL

query a CSW query, object of class [CSWQuery](#)

resourceType resource type. Default is "http://www.isotc211.org/2005/gmd"

sourceBaseUrl source base URL

Returns: an object of class list giving the number of records found and those actually harvested

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
CSWClient$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

Examples

```
## Not run:
#example based on CSW endpoint responding at http://localhost:8000/csw
csw <- CSWClient$new("http://localhost:8000/csw", serviceVersion = "2.0.2")

#get capabilities
caps <- csw$getCapabilities()

#get records
records <- csw$getRecords()

#get record by id
record <- csw$getRecordById("my-metadata-id")

#Advanced examples at https://github.com/eblondel/ows4R/wiki#csw

## End(Not run)
```

CSWConstraint

CSWConstraint

Description

CSWConstraint

CSWConstraint

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling an CSW Constraint

Super class

[ows4R::OGCAbstractObject](#) -> CSWConstraint

Public fields

wrap internal property for object XML encoding

CqlText text to use as CQL filter

filter

Methods

Public methods:

- [CSWConstraint\\$new\(\)](#)
- [CSWConstraint\\$setServiceVersion\(\)](#)
- [CSWConstraint\\$clone\(\)](#)

Method `new()`: Initializes a [CSWConstraint](#) object to be used to constrain CSW operations.

Usage:

```
CSWConstraint$new(cqlText = NULL, filter = NULL, serviceVersion = "2.0.2")
```

Arguments:

`cqlText` `cqlText`, object of class character

`filter` `filter`, object extending [OGCFilter](#)

`serviceVersion` CSW service version. Default is "2.0.2"

Method `setServiceVersion()`: Set service version. This methods ensures that underlying filter property is properly set with the right OGC filter version.

Usage:

```
CSWConstraint$setServiceVersion(serviceVersion)
```

Arguments:

`serviceVersion` service version

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
CSWConstraint$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondell@gmail.com>

Examples

```
filter <- OGCFilter$new( PropertyIsEqualTo$new("apiso:Identifier", "12345") )
cons <- CSWConstraint$new(filter = filter)
cons_xml <- cons$encode() #how it looks like in XML
```

CSWDescribeRecord	<i>CSWDescribeRecord</i>
-------------------	--------------------------

Description

CSWDescribeRecord
CSWDescribeRecord

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling a CSW DescribeRecord request

Super classes

[ows4R::OGCAbstractObject](#) -> [ows4R::OWSHttpRequest](#) -> CSWDescribeRecord

Methods**Public methods:**

- [CSWDescribeRecord\\$new\(\)](#)
- [CSWDescribeRecord\\$clone\(\)](#)

Method `new()`: Initializes a [CSWDescribeRecord](#) service request

Usage:

```
CSWDescribeRecord$new(  
  capabilities,  
  op,  
  url,  
  version,  
  namespace = NULL,  
  user = NULL,  
  pwd = NULL,  
  token = NULL,  
  headers = c(),  
  config = httr::config(),  
  logger = NULL,  
  ...  
)
```

Arguments:

`capabilities` an object of class [CSWCapabilities](#)
`op` object of class [OWSOperation](#) as retrieved from capabilities

url url
 version version
 namespace namespace
 user user
 pwd password
 token token
 headers headers
 config config
 logger logger
 ... any parameter to pass to the service request

Method clone(): The objects of this class are cloneable with this method.

Usage:

CSWDescribeRecord\$clone(deep = FALSE)

Arguments:

deep Whether to make a deep clone.

Note

Class used internally by **ows4R** to trigger a CSW DescribeRecord request

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

CSWGetRecordById

CSWGetRecordById

Description

CSWGetRecordById

CSWGetRecordById

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling a CSW GetRecordById request

Super classes

[ows4R::OGCAbstractObject](#) -> [ows4R::OWSHttpRequest](#) -> CSWGetRecordById

Public fields

Id record Id property for request XML encoding

ElementSetName element set name property for XML encoding

Methods**Public methods:**

- [CSWGetRecordById\\$new\(\)](#)
- [CSWGetRecordById\\$clone\(\)](#)

Method new(): Initializes a [CSWGetRecordById](#) service request

Usage:

```
CSWGetRecordById$new(
  capabilities,
  op,
  url,
  serviceVersion = "2.0.2",
  user = NULL,
  pwd = NULL,
  token = NULL,
  headers = headers,
  config = httr::config(),
  id,
  elementSetName = "full",
  logger = NULL,
  ...
)
```

Arguments:

capabilities an object of class [CSWCapabilities](#)

op object of class [OWSOperation](#) as retrieved from capabilities

url url

serviceVersion serviceVersion. Default is "2.0.2"

user user

pwd password

token token

headers headers

config config

id record id

elementSetName element set name. Default is "full"

logger logger

... any parameter to pass to the service request

Method clone(): The objects of this class are cloneable with this method.

Usage:

CSWGetRecordById\$clone(deep = FALSE)

Arguments:

deep Whether to make a deep clone.

Note

Class used internally by **ows4R** to trigger a CSW GetRecordById request

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

CSWGetRecords

CSWGetRecords

Description

CSWGetRecords

CSWGetRecords

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling a CSW GetRecords request

Super classes

[ows4R::OGCAbstractObject](#) -> [ows4R::OWSHttpRequest](#) -> CSWGetRecords

Public fields

Query query property for request XML encoding

Methods

Public methods:

- [CSWGetRecords\\$new\(\)](#)
- [CSWGetRecords\\$clone\(\)](#)

Method [new\(\)](#): Initializes a [CSWGetRecordById](#) service request

Usage:

```

CSWGetRecords$new(
  capabilities,
  op,
  url,
  serviceVersion = "2.0.2",
  user = NULL,
  pwd = NULL,
  token = NULL,
  headers = list(),
  config = httr::config(),
  query = NULL,
  logger = NULL,
  ...
)

```

Arguments:

`capabilities` an object of class [CSWCapabilities](#)

`op` object of class [OWSOperation](#) as retrieved from `capabilities`

`url` url

`serviceVersion` serviceVersion. Default is "2.0.2"

`user` user

`pwd` password

`token` token

`headers` headers

`config` config

`query` object of class [CSWQuery](#)

`logger` logger

`...` any parameter to pass to the service request, such as `resultType`, `startPosition`, `maxRecords`, `outputFormat`, or `outputSchema`

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
CSWGetRecords$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Note

Class used internally by **ows4R** to trigger a CSW GetRecords request

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

 CSWHarvest

CSWHarvest

Description

CSWHarvest

CSWHarvest

Format[R6Class](#) object.**Value**Object of [R6Class](#) for modelling a CSW Harvest request**Super classes**[ows4R::OGCAbstractObject](#) -> [ows4R::OWSHttpRequest](#) -> CSWHarvest**Public fields**

Source source property for request XML encoding

ResourceType resource type property for request XML encoding

ResourceFormat resource format property for request XML encoding

Methods**Public methods:**

- [CSWHarvest\\$new\(\)](#)
- [CSWHarvest\\$clone\(\)](#)

Method [new\(\)](#): Initializes a [CSWHarvest](#) service request*Usage:*

```

CSWHarvest$new(
  capabilities,
  op,
  url,
  serviceVersion = "2.0.2",
  user = NULL,
  pwd = NULL,
  token = NULL,
  headers = list(),
  config = httr::config(),
  source = NULL,
  resourceType = "http://www.isotc211.org/schemas/2005/gmd/",

```

```

        resourceFormat = "application/xml",
        logger = NULL,
        ...
    )

```

Arguments:

capabilities an object of class [CSWCapabilities](#)
op object of class [OWSOperation](#) as retrieved from capabilities
url url
serviceVersion serviceVersion. Default is "2.0.2"
user user
pwd password
token token
headers headers
config config
source source
resourceType resource type. Default is "http://www.isotc211.org/schemas/2005/gmd/"
resourceFormat resource format. Default is "application/xml"
logger logger
 ... any parameter to pass to the service request

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
CSWHarvest$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Note

Class used internally by **ows4R** to trigger a CSW Harvest request

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

 CSWQuery

CSWQuery

Description

CSWQuery

CSWQuery

Format

R6Class object.

Value

Object of R6Class for modelling an CSW Query

Super class

ows4R: :OGCAbstractObject -> CSWQuery

Public fields

ElementSetName element set name property for request XML encoding
constraint property for request XML encoding

Methods**Public methods:**

- CSWQuery\$new()
- CSWQuery\$setServiceVersion()
- CSWQuery\$clone()

Method new(): This method is used to instantiate an CSWQuery object. The elementSetName can be either "full" (default), "brief" or "summary". A constraint CSWConstraint can be defined for the query. The typeName indicates to query (default "csw:Record"). The serviceVersion gives the CSW service version (default "2.0.2")

Usage:

```
CSWQuery$new(
  elementSetName = "full",
  constraint = NULL,
  typeName = "csw:Record",
  serviceVersion = "2.0.2"
)
```

Arguments:

elementSetName element set name. Default is "full"
constraint object of class CSWConstraint
typeName type names
serviceVersion CSW service version

Method setServiceVersion(): Set service version. The methods ensures property naming of typeName depending on the service version

Usage:

```
CSWQuery$setServiceVersion(serviceVersion)
```

Arguments:

serviceVersion service version

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
CSWQuery$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

Examples

```
#CSWQuery - elementSetName
query_full <- CSWQuery$new()
query_brief <- CSWQuery$new(elementSetName = "brief")
query_summary <- CSWQuery$new(elementSetName = "summary")

#CSWQuery - cqlText with title
cons <- CSWConstraint$new(cqlText = "dc:title like '%ips%'")
query <- CSWQuery$new(constraint = cons)

#CSW 2.0.2 - Query - Filter / AnyText
filter <- OGCFilter$new( PropertyIsLike$new("csw:AnyText", "%Physio%"))
cons <- CSWConstraint$new(filter = filter)
query <- CSWQuery$new(constraint = cons)

#CSW 2.0.2 - Query - Filter / AnyText Equal
filter <- OGCFilter$new( PropertyIsEqualTo$new("csw:AnyText", "species"))
cons <- CSWConstraint$new(filter = filter)
query <- CSWQuery$new(constraint = cons)

#CSW 2.0.2 - Query - Filter / AnyText And Not
filter <- OGCFilter$new(And$new(
  PropertyIsLike$new("csw:AnyText", "%lorem%"),
  PropertyIsLike$new("csw:AnyText", "%ipsum%"),
  Not$new(
    PropertyIsLike$new("csw:AnyText", "%dolor%")
  )
))
cons <- CSWConstraint$new(filter = filter)
query <- CSWQuery$new(constraint = cons)

#CSW 2.0.2 - Query - Filter / AnyText And nested Or
filter <- OGCFilter$new(And$new(
  PropertyIsEqualTo$new("dc:title", "Aliquam fermentum purus quis arcu"),
  PropertyIsEqualTo$new("dc:format", "application/pdf"),
  Or$new(
    PropertyIsEqualTo$new("dc:type", "http://purl.org/dc/dcmitype/Dataset"),
    PropertyIsEqualTo$new("dc:type", "http://purl.org/dc/dcmitype/Service"),
    PropertyIsEqualTo$new("dc:type", "http://purl.org/dc/dcmitype/Image"),
    PropertyIsEqualTo$new("dc:type", "http://purl.org/dc/dcmitype/Text")
  )
))
```

```

    )
  ))
  cons <- CSWConstraint$new(filter = filter)
  query <- CSWQuery$new(elementSetName = "brief", constraint = cons)

#CSW 2.0.2 - Query - Filter / BBOX
bbox <- matrix(c(-180,180,-90,90), nrow = 2, ncol = 2, byrow = TRUE,
              dimnames = list(c("x", "y"), c("min","max")))
filter <- OGCFilter$new( BBOX$new(bbox = bbox) )
cons <- CSWConstraint$new(filter = filter)
query <- CSWQuery$new(elementSetName = "brief", constraint = cons)

```

CSWRecordProperty	<i>CSWRecordProperty</i>
-------------------	--------------------------

Description

CSWRecordProperty

CSWRecordProperty

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling an CSW RecordProperty

Super class

[ows4R::OGCAbstractObject](#) -> CSWRecordProperty

Public fields

wrap internal property for XML encoding

Name name property for request XML encoding

Value property for request XML encoding

Methods

Public methods:

- [CSWRecordProperty\\$new\(\)](#)
- [CSWRecordProperty\\$clone\(\)](#)

Method [new\(\)](#): Initializes an object of class [CSWRecordProperty](#)

Usage:

```
CSWRecordProperty$new(name, value, cswVersion = "2.0.2")
```

Arguments:

name name

value value

cswVersion CSW service version. Default is "2.0.2"

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
CSWRecordProperty$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

Examples

```
rp <- CSWRecordProperty$new(name = "NAME", value = "VALUE")
rp_xml <- rp$encode() #see how it looks in XML
```

CSWTransaction

CSWTransaction

Description

CSWTransaction

CSWTransaction

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling a CSW Transaction request

Super classes

[ows4R::OGCAbstractObject](#) -> [ows4R::OWSHttpRequest](#) -> CSWTransaction

Methods**Public methods:**

- [CSWTransaction\\$new\(\)](#)
- [CSWTransaction\\$clone\(\)](#)

Method `new()`: Initializes a [CSWTransaction](#) service request

Usage:

```
CSWTransaction$new(
  capabilities,
  op,
  url,
  serviceVersion,
  type,
  user = NULL,
  pwd = NULL,
  token = NULL,
  headers = list(),
  record = NULL,
  recordProperty = NULL,
  constraint = NULL,
  logger = NULL,
  ...
)
```

Arguments:

`capabilities` an object of class [CSWCapabilities](#)
`op` object of class [OWSOperation](#) as retrieved from `capabilities`
`url` url
`serviceVersion` serviceVersion. Default is "2.0.2"
`type` type of transaction, either "Insert", "Update", or "Delete"
`user` user
`pwd` password
`token` token
`headers` headers
`record` record
`recordProperty` record property
`constraint` constraint
`logger` logger
`...` any parameter to pass to the service request

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
CSWTransaction$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Note

Class used internally by **ows4R** to trigger a CSW Transaction request

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

getOWSNamespace *getOWSNamespace*

Description

getOWSNamespace gets a namespace given its id

Usage

getOWSNamespace(id)

Arguments

id namespace prefix

Author(s)

Emmanuel Blondel, <emmanuel.blondel1@gmail.com>

Examples

getOWSNamespace("GMD")

*getOWSNamespace*s *getOWSNamespace*s

Description

*getOWSNamespace*s gets the list of namespaces registered

Usage

*getOWSNamespace*s()

Author(s)

Emmanuel Blondel, <emmanuel.blondel1@gmail.com>

Examples

```
getOWSNamespace()
```

Not

Not

Description

Not

Not

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling an Not

Super classes

[ows4R::OGCAbstractObject](#) -> [ows4R::OGCEXpression](#) -> [ows4R::UnaryLogicOpType](#) -> Not

Methods**Public methods:**

- [Not\\$new\(\)](#)
- [Not\\$clone\(\)](#)

Method `new()`: Initializes an [Not](#) expression

Usage:

```
Not$new(...)
```

Arguments:

... list of objects of class [OGCEXpression](#)

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
Not$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

Examples

```

expr <- PropertyIsEqualTo$new(PropertyName = "property", Literal = "value")
not <- Not$new(expr)
not_xml <- not$encode() #see how it looks like in XML

```

OGCAbstractObject *OGCAbstractObject*

Description

OGCAbstractObject
OGCAbstractObject

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling an OGCAbstractObject

Public fields

verbose.info logical property to indicate whether INFO logs have to be displayed
 verbose.debug logical property to indicate whether DEBUG logs have to be displayed
 loggerType logger type, either NULL, "INFO", or "DEBUG"
 wrap internal property for XML encoding
 element element used for XML encoding
 namespace namespace used for XML encoding
 defaults default values to be used for XML encoding
 attrs attributes to be used for XML encoding

Methods**Public methods:**

- [OGCAbstractObject\\$logger\(\)](#)
- [OGCAbstractObject\\$INFO\(\)](#)
- [OGCAbstractObject\\$WARN\(\)](#)
- [OGCAbstractObject\\$ERROR\(\)](#)
- [OGCAbstractObject\\$new\(\)](#)
- [OGCAbstractObject\\$getClassName\(\)](#)
- [OGCAbstractObject\\$getClass\(\)](#)

- [OGCAbstractObject\\$isFieldInheritedFrom\(\)](#)
- [OGCAbstractObject\\$getNamespaceDefinition\(\)](#)
- [OGCAbstractObject\\$encode\(\)](#)
- [OGCAbstractObject\\$print\(\)](#)
- [OGCAbstractObject\\$clone\(\)](#)

Method `logger()`: A basic logger function

Usage:

```
OGCAbstractObject$logger(type, text)
```

Arguments:

type type of logs message.

text log message text to be displayed

Method `INFO()`: a basic INFO logger function

Usage:

```
OGCAbstractObject$INFO(text)
```

Arguments:

text log message text to be displayed

Method `WARN()`: a basic WARN logger function

Usage:

```
OGCAbstractObject$WARN(text)
```

Arguments:

text log message text to be displayed

Method `ERROR()`: a basic ERROR logger function

Usage:

```
OGCAbstractObject$ERROR(text)
```

Arguments:

text log message text to be displayed

Method `new()`: Initializes an object extending [OGCAbstractObject](#)

Usage:

```
OGCAbstractObject$new(  
  xml = NULL,  
  element = NULL,  
  namespacePrefix = NULL,  
  attrs = list(),  
  defaults = list(),  
  wrap = FALSE,  
  logger = NULL  
)
```

Arguments:

xml object of class [XMLInternalNode-class](#) from **XML**
 element element name
 namespacePrefix namespace prefix for XML encoding
 attrs list of attributes
 defaults list of default values
 wrap whether XML element has to be wrapped during XML encoding
 logger logger

Method `getClassName()`: Get class name

Usage:

```
OGCAbstractObject$getClassName()
```

Returns: an object of class character

Method `getClass()`: Get class

Usage:

```
OGCAbstractObject$getClass()
```

Returns: an object of class R6Class

Method `isFieldInheritedFrom()`: Utility to return the parent class in which field is defined

Usage:

```
OGCAbstractObject$isFieldInheritedFrom(field)
```

Arguments:

field field name

Returns: object of class R6Class

Method `getNamespaceDefinition()`: Gets the namespace definition

Usage:

```
OGCAbstractObject$getNamespaceDefinition(recursive = FALSE)
```

Arguments:

recursive Get all namespace recursively

Returns: the namespace definitions as named list

Method `encode()`: Encodes as XML. The `addNS` . Extra parameters related to **geometa** objects: `geometa_validate` (TRUE by default) and `geometa_inspire` (FALSE by default) can be used to perform ISO and INSPIRE validation respectively. In that case on object of class `geometa::INSPIREMetadataValidator`, with a proper user API key, should be specified as `geometa_inspireValidator` argument.

Usage:

```
OGCAbstractObject$encode(  
  addNS = TRUE,  
  geometa_validate = TRUE,  
  geometa_inspire = FALSE,  
  geometa_inspireValidator = NULL  
)
```

Arguments:

addNS addNS controls the addition of XML namespaces

geometa_validate Relates to **geometa** object ISO validation. Default is TRUE

geometa_inspire Relates to **geometa** object INSPIRE validation. Default is FALSE

geometa_inspireValidator Relates to **geometa** object INSPIRE validation. Default is NULL

Returns: an object of class [XMLInternalNode-class](#) from **XML**

Method print(): Provides a custom print output (as tree) of the current class

Usage:

```
OGCAbstractObject$print(..., depth = 1)
```

Arguments:

... args

depth class nesting depth

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
OGCAbstractObject$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Note

abstract class used by **ows4R**

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

OGCEXpression

OGCEXpression

Description

OGCEXpression

OGCEXpression

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling an OGC Expression

Super class

`ows4R:OGCAbstractObject` -> OGCExpression

Methods**Public methods:**

- `OGCExpression$new()`
- `OGCExpression$setExprVersion()`
- `OGCExpression$getExprVersion()`
- `OGCExpression$clone()`

Method `new()`: Initializes an object of class `OGCExpression`

Usage:

```
OGCExpression$new(
  element,
  namespacePrefix,
  attrs = NULL,
  defaults = NULL,
  exprVersion = "1.1.0"
)
```

Arguments:

`element` element name
`namespacePrefix` XML namespace prefix
`attrs` attributes
`defaults` default values
`exprVersion` OGC version for the expression

Method `setExprVersion()`: Sets expression version. The methods will control proper XML namespace prefix setting

Usage:

```
OGCExpression$setExprVersion(exprVersion)
```

Arguments:

`exprVersion` OGC expression version

Method `getExprVersion()`: Gets expression version

Usage:

```
OGCExpression$getExprVersion()
```

Returns: object of class character

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
OGCExpression$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Note

abstract class

Author(s)

Emmanuel Blondel <emmanuel.blondell@gmail.com>

OGCFilter

OGCFilter

Description

OGCFilter

OGCFilter

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling an OGC Filter

Super class

[ows4R::OGCAbstractObject](#) -> OGCFilter

Public fields

expr OGC expression

Methods**Public methods:**

- [OGCFilter\\$new\(\)](#)
- [OGCFilter\\$setFilterVersion\(\)](#)
- [OGCFilter\\$clone\(\)](#)

Method [new\(\)](#): Initializes an object of class [OGCFilter](#).

Usage:

```
OGCFilter$new(expr, filterVersion = "1.1.0")
```

Arguments:

expr object of class [OGCExpression](#)

filterVersion OGC filter version. Default is "1.1.0"

Method [setFilterVersion\(\)](#): Sets the OGC filter version

Usage:

```
OGCFilter$setFilterVersion(filterVersion)
```

Arguments:

```
filterVersion OGC filter version
```

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
OGCFilter$clone(deep = FALSE)
```

Arguments:

```
deep Whether to make a deep clone.
```

Author(s)

Emmanuel Blondel <emmanuel.blondell@gmail.com>

Examples

```
expr <- PropertyIsEqualTo$new(PropertyName = "property", Literal = "value")
not <- Not$new(expr)
not_xml <- not$encode() #see how it looks like in XML
```

Or

Or

Description

Or

Or

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling an Or operator

Super classes

[ows4R::OGCAbstractObject](#) -> [ows4R::OGCExpression](#) -> [ows4R::BinaryLogicOpType](#) -> Or

Methods

Public methods:

- [Or\\$new\(\)](#)
- [Or\\$clone\(\)](#)

Method `new()`: Initializes an [Or](#) expression

Usage:

```
Or$new(...)
```

Arguments:

... list of objects of class [OGCExpression](#)

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
Or$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

Examples

```
expr1 <- PropertyIsEqualTo$new(PropertyName = "property1", Literal = "value1")
expr2 <- PropertyIsEqualTo$new(PropertyName = "property2", Literal = "value2")
or <- Or$new(expr1,expr2)
or_xml <- or$encode() #see how it looks like in XML
```

Description

Provides an Interface to Web-Services defined as standards by the Open Geospatial Consortium (OGC), including Web Feature Service (WFS) for vector data, Web Coverage Service (WCS), Catalogue Service (CSW) for ISO/OGC metadata, and associated standards such as the common web-service specification (OWS) and OGC Filter Encoding. Partial support is provided for the Web Map Service (WMS) and Web Processing Service (WPS). The purpose is to add support for additional OGC service standards such as Web Coverage Processing Service (WCPS) or OGC API.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

See Also

Useful links:

- <https://github.com/eblondel/ows4R>
- <https://eblondel.github.io/ows4R/>
- <https://www.ogc.org/standards/>
- Report bugs at <https://github.com/eblondel/ows4R/issues>

OWSBoundingBox

OWSBoundingBox

Description

OWSBoundingBox

OWSBoundingBox

Format

R6Class object.

Value

Object of R6Class for modelling an OGC Bounding Box

Super class

`ows4R::OGCAbstractObject` -> OWSBoundingBox

Public fields

`attrs` attributes to be associated to XML

`LowerCorner` lower corner coordinates

`UpperCorner` upper corner coordinates

Methods**Public methods:**

- `OWSBoundingBox$new()`
- `OWSBoundingBox$decode()`
- `OWSBoundingBox$getBBOX()`
- `OWSBoundingBox$clone()`

Method `new()`: Initializes an object of class `OWSBoundingBox`

Usage:

```
OWSBoundingBox$new(  
  xml = NULL,  
  element = NULL,  
  namespacePrefix = NULL,  
  owsVersion,  
  serviceVersion,  
  logger = NULL  
)
```

Arguments:

xml an object of class [XMLInternalNode-class](#) to initialize from XML

element element name

namespacePrefix namespace prefix

owsVersion OWS version

serviceVersion service version

logger logger

Method decode(): Decodes an object of class [OWSBoundingBox](#) from XML

Usage:

```
OWSBoundingBox$decode(xml)
```

Arguments:

xml object of class [XMLInternalNode-class](#) from XML

Method getBBOX(): Get BBOX as object of class bbox from **sf** package

Usage:

```
OWSBoundingBox$getBBOX()
```

Returns: a numeric vector of length four, with xmin, ymin, xmax and ymax values

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
OWSBoundingBox$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

OWSCapabilities	<i>OWSGetCapabilities</i>
-----------------	---------------------------

Description

OWSGetCapabilities

OWSGetCapabilities

Format

[R6Class](#) object.

Value

Object of [R6Class](#) with methods for interfacing an abstract OWS Get Capabilities document.

Super class

[ows4R::OGCAbstractObject](#) -> OWSCapabilities

Methods**Public methods:**

- [OWSCapabilities\\$new\(\)](#)
- [OWSCapabilities\\$setClient\(\)](#)
- [OWSCapabilities\\$getClient\(\)](#)
- [OWSCapabilities\\$getUrl\(\)](#)
- [OWSCapabilities\\$getService\(\)](#)
- [OWSCapabilities\\$getServiceVersion\(\)](#)
- [OWSCapabilities\\$getOWSVersion\(\)](#)
- [OWSCapabilities\\$getRequest\(\)](#)
- [OWSCapabilities\\$getServiceIdentification\(\)](#)
- [OWSCapabilities\\$getServiceProvider\(\)](#)
- [OWSCapabilities\\$getOperationsMetadata\(\)](#)
- [OWSCapabilities\\$clone\(\)](#)

Method new(): Initializes a [OWSCapabilities](#) object

Usage:

```
OWSCapabilities$new(  
  element = NULL,  
  namespacePrefix = NULL,  
  url,  
  service,  
  owsVersion,  
  serviceVersion,
```

```

    logger = NULL,
    ...
)

```

Arguments:

element element

namespacePrefix namespace prefix

url url

service service

owsVersion OWS version

serviceVersion service version

logger logger type NULL, "INFO" or "DEBUG"

... any other parameter to pass to [OWSGetCapabilities](#) service request

Method setClient(): Sets the OGC client

Usage:

```
OWSCapabilities$setClient(client)
```

Arguments:

client an object extending [OWSClient](#)

Method getClient(): Get client

Usage:

```
OWSCapabilities$getClient()
```

Arguments:

an object extending [OWSClient](#)

Method getUrl(): Get URL

Usage:

```
OWSCapabilities$getUrl()
```

Returns: an object of class character

Method getService(): Get service

Usage:

```
OWSCapabilities$getService()
```

Returns: an object of class character

Method getServiceVersion(): Get service version

Usage:

```
OWSCapabilities$getServiceVersion()
```

Returns: an object of class character

Method getOWSVersion(): Get OWS version

Usage:

```
OWSCapabilities$getOWSVersion()
```

Returns: an object of class character

Method getRequest(): Get request

Usage:

OWSCapabilities\$request()

Returns: an object of class [OWSGetCapabilities](#)

Method getServiceIdentification(): Get service identification

Usage:

OWSCapabilities\$getServiceIdentification()

Returns: an object of class [OWSServiceIdentification](#)

Method getServiceProvider(): Get service provider

Usage:

OWSCapabilities\$getServiceProvider()

Returns: an object of class [OWSServiceProvider](#)

Method getOperationsMetadata(): Get service operations metadata

Usage:

OWSCapabilities\$getOperationsMetadata()

Returns: an object of class [OWSOperationsMetadata](#)

Method clone(): The objects of this class are cloneable with this method.

Usage:

OWSCapabilities\$clone(deep = FALSE)

Arguments:

deep Whether to make a deep clone.

Note

abstract class used by **ows4R**

Author(s)

Emmanuel Blondel <emmanuel.blondell@gmail.com>

OWSClient

OWSClient

Description

OWSClient

OWSClient

Format

[R6Class](#) object.

Value

Object of [R6Class](#) with methods for interfacing a Common OGC web-service.

Super class

[ows4R::OGCAbstractObject](#) -> OWSClient

Public fields

url Base url of the OWS service

version version of the OWS service

capabilities object giving the OWS service capabilities

Methods

Public methods:

- [OWSClient\\$new\(\)](#)
- [OWSClient\\$getUrl\(\)](#)
- [OWSClient\\$getVersion\(\)](#)
- [OWSClient\\$getCapabilities\(\)](#)
- [OWSClient\\$getUser\(\)](#)
- [OWSClient\\$getPwd\(\)](#)
- [OWSClient\\$getToken\(\)](#)
- [OWSClient\\$getHeaders\(\)](#)
- [OWSClient\\$getConfig\(\)](#)
- [OWSClient\\$getCASUrl\(\)](#)
- [OWSClient\\$clone\(\)](#)

Method new(): This method is used to instantiate a OWSClient with the url of the OGC service. Authentication is supported using basic auth (using user/pwd arguments), bearer token (using token argument), or custom (using headers argument). By default, the logger argument will be set to NULL (no logger). This argument accepts two possible values: INFO: to print only **ows4R** logs, DEBUG: to print more verbose logs

Usage:

```
OWSClient$new(  
  url,  
  service,  
  serviceVersion,  
  user = NULL,  
  pwd = NULL,  
  token = NULL,  
  headers = c(),  
  config = httr::config(),  
  cas_url = NULL,  
  logger = NULL  
)
```

Arguments:

url url
service service name
serviceVersion CSW service version
user user
pwd password
token token
headers headers
config config
cas_url Central Authentication Service (CAS) URL
logger logger

Method getUrl(): Get URL*Usage:*

```
OWSClient$getUrl()
```

Returns: the url of the service, object of class character

Method getVersion(): Get version*Usage:*

```
OWSClient$getVersion()
```

Returns: the version of the service, object of class character

Method getCapabilities(): Get capabilities*Usage:*

```
OWSClient$getCapabilities()
```

Returns: the capabilities, object of class [OWSCapabilities](#)

Method getUser(): Get user*Usage:*

```
OWSClient$getUser()
```

Returns: the user, object of class character

Method getPwd(): Get password

Usage:

OWSClient\$getPwd()

Returns: the password, object of class character

Method getToken(): Get token

Usage:

OWSClient\$getToken()

Returns: the token, object of class character

Method getHeaders(): Get headers

Usage:

OWSClient\$getHeaders()

Returns: the headers, object of class character

Method getConfig(): Get **httr** config

Usage:

OWSClient\$config()

Returns: the **httr** config, if any

Method getCASUrl(): Get CAS URL

Usage:

OWSClient\$CASUrl()

Returns: a CAS URL

Method clone(): The objects of this class are cloneable with this method.

Usage:

OWSClient\$clone(deep = FALSE)

Arguments:

deep Whether to make a deep clone.

Note

Abstract class used internally by **ows4R**

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

OWSCodeType

OWSCodeType

Description

OWSCodeType

OWSCodeType

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling an OWS CodeType

Super class

[ows4R: :OGCAbstractObject](#) -> OWSCodeType

Public fields

value code type

Methods

Public methods:

- [OWSCodeType\\$new\(\)](#)
- [OWSCodeType\\$clone\(\)](#)

Method [new\(\)](#): Initializes an object of class [OWSCodeType](#)

Usage:

```
OWSCodeType$new(xml = NULL, owsVersion = "1.1", value)
```

Arguments:

xml object of class [XMLInternalNode-class](#) from **XML**

owsVersion OWS version. Default is "1.1"

value the code type

Method [clone\(\)](#): The objects of this class are cloneable with this method.

Usage:

```
OWSCodeType$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

OWSEException

OWSEException

Description

OWSEException

OWSEException

Format

[R6Class](#) object.

Value

Object of [R6Class](#) modelling a OWS Service exception

Super class

[ows4R:OGCAbstractObject](#) -> OWSEException

Public fields

ExceptionText exception text

Methods

Public methods:

- [OWSEException\\$new\(\)](#)
- [OWSEException\\$getLocator\(\)](#)
- [OWSEException\\$getCode\(\)](#)
- [OWSEException\\$getText\(\)](#)
- [OWSEException\\$clone\(\)](#)

Method [new\(\)](#): Initializes an object of class [OWSEException](#)

Usage:

[OWSEException\\$new\(xmlObj, logger = NULL\)](#)

Arguments:

xmlObj object of class [XMLInternalNode-class](#) from **XML**

logger logger

Method [getLocator\(\)](#): Get exception locator

Usage:

[OWSEException\\$getLocator\(\)](#)

Returns: the exception locator, object of class character

Method getCode(): Get exception code

Usage:

OWSException\$getCode()

Returns: the exception code, object of class character

Method getText(): Get exception text explanation

Usage:

OWSException\$getText()

Returns: the exception text, object of class character

Method clone(): The objects of this class are cloneable with this method.

Usage:

OWSException\$clone(deep = FALSE)

Arguments:

deep Whether to make a deep clone.

Note

Abstract class used by **ows4R**

Author(s)

Emmanuel Blondel <emmanuel.blondell@gmail.com>

OWSGetCapabilities *OWSGetCapabilities*

Description

OWSGetCapabilities

OWSGetCapabilities

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling a GetCapabilities request

Super classes

[ows4R::OGCAbstractObject](#) -> [ows4R::OWSHttpRequest](#) -> OWSGetCapabilities

Methods**Public methods:**

- [OWSGetCapabilities\\$new\(\)](#)
- [OWSGetCapabilities\\$clone\(\)](#)

Method `new()`: Initializes an [OWSGetCapabilities](#) service request

Usage:

```
OWSGetCapabilities$new(
  element = NULL,
  namespacePrefix = NULL,
  url,
  service,
  version,
  user = NULL,
  pwd = NULL,
  token = NULL,
  headers = c(),
  config = httr::config(),
  ...
)
```

Arguments:

element element
 namespacePrefix namespace prefix
 url url
 service service name
 version service version
 user user
 pwd password
 token token
 headers headers
 config config
 ... any other parameter to pass to the request

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
OWSGetCapabilities$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Note

Class used internally by **ows4R** to trigger a OWS GetCapabilities request

Author(s)

Emmanuel Blondel <emmanuel.blondell@gmail.com>

OWSHttpRequest	<i>OWSHttpRequest</i>
----------------	-----------------------

Description

OWSHttpRequest

OWSHttpRequest

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling a generic OWS http request

Super class

[ows4R::OGCAbstractObject](#) -> OWSHttpRequest

Methods**Public methods:**

- [OWSHttpRequest\\$new\(\)](#)
- [OWSHttpRequest\\$execute\(\)](#)
- [OWSHttpRequest\\$getCapabilities\(\)](#)
- [OWSHttpRequest\\$getRequest\(\)](#)
- [OWSHttpRequest\\$getRequestHeaders\(\)](#)
- [OWSHttpRequest\\$status\(\)](#)
- [OWSHttpRequest\\$response\(\)](#)
- [OWSHttpRequest\\$exception\(\)](#)
- [OWSHttpRequest\\$hasException\(\)](#)
- [OWSHttpRequest\\$result\(\)](#)
- [OWSHttpRequest\\$setResult\(\)](#)
- [OWSHttpRequest\\$clone\(\)](#)

Method new(): Initializes an OWS HTTP request

Usage:

```
OWSHttpRequest$new(  
  element,  
  namespacePrefix,  
  capabilities,  
  op,  
  type,  
  url,
```

```

    request,
    user = NULL,
    pwd = NULL,
    token = NULL,
    headers = c(),
    config = httr::config(),
    namedParams = NULL,
    attrs = NULL,
    contentType = "text/xml",
    mimeType = "text/xml",
    skipXmlComments = TRUE,
    logger = NULL,
    ...
)

```

Arguments:

element element
 namespacePrefix namespace prefix
 capabilities object of class or extending [OWSCapabilities](#)
 op object of class [OWSOperation](#)
 type type of request, eg. GET, POST
 url url
 request request name
 user user
 pwd password
 token token
 headers headers
 config config
 namedParams a named list
 attrs attributes
 contentType content type. Default value is "text/xml"
 mimeType mime type. Default value is "text/xml"
 skipXmlComments Skip XML comments from response
 logger logger
 ... any other parameter

Method `execute()`: Executes the request

Usage:

```
OWSHttpRequest$execute()
```

Method `getCapabilities()`: Get capabilities

Usage:

```
OWSHttpRequest$getCapabilities()
```

Returns: an object of class or extending [OWSCapabilities](#)

Method `getRequest()`: Get request

Usage:

`OWSHttpRequest$request()`

Returns: the request

Method `getRequestHeaders():` Get request headers

Usage:

`OWSHttpRequest$requestHeaders()`

Returns: the request headers

Method `getStatus():` get status code

Usage:

`OWSHttpRequest$status()`

Returns: the request status code

Method `getResponse():` get request response

Usage:

`OWSHttpRequest$response()`

Returns: the request response

Method `getException():` get request exception

Usage:

`OWSHttpRequest$exception()`

Returns: the request exception

Method `hasException():` Indicates if it has an exception

Usage:

`OWSHttpRequest$hasException()`

Returns: TRUE if it has an exception, FALSE otherwise

Method `getResult():` Get the result TRUE if the request is successful, FALSE otherwise

Usage:

`OWSHttpRequest$result()`

Returns: the result, object of class logical

Method `setResult():` Set the result

Usage:

`OWSHttpRequest$result(result)`

Arguments:

result object of class logical

Method `clone():` The objects of this class are cloneable with this method.

Usage:

`OWSHttpRequest$clone(deep = FALSE)`

Arguments:

deep Whether to make a deep clone.

Note

Abstract class used internally by **ows4R**

Author(s)

Emmanuel Blondel <emmanuel.blondell@gmail.com>

OwsNamespace

OwsNamespace

Description

OwsNamespace

OwsNamespace

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling an OWS Namespace

Public fields

id namespace id

uri namespace uri

Methods**Public methods:**

- [OwsNamespace\\$new\(\)](#)
- [OwsNamespace\\$getDefinition\(\)](#)
- [OwsNamespace\\$clone\(\)](#)

Method [new\(\)](#): Initializes an [OwsNamespace](#)

Usage:

[OwsNamespace\\$new](#)(id, uri)

Arguments:

id id

uri uri

Method [getDefinition\(\)](#): Get namespace definition

Usage:

[OwsNamespace\\$getDefinition](#)()

Returns: a named list with id and uri

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
OWSNamespace$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Note

class used internally by ows4R for specifying XML namespaces

Author(s)

Emmanuel Blondel <emmanuel.blondell@gmail.com>

OWSOperation

OWSOperation

Description

OWSOperation

OWSOperation

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling an OGC Operation

Methods

Public methods:

- [OWSOperation\\$new\(\)](#)
- [OWSOperation\\$getName\(\)](#)
- [OWSOperation\\$getParameters\(\)](#)
- [OWSOperation\\$getParameter\(\)](#)
- [OWSOperation\\$clone\(\)](#)

Method `new()`: Initializes an object of class [OWSOperation](#).

Usage:

```
OWSOperation$new(xmlObj, owsVersion, serviceVersion)
```

Arguments:

xmlObj object of class [XMLInternalNode-class](#) from **XML**
owsVersion OWS version
serviceVersion service version

Method getName(): Get operation name

Usage:

OWSOperation\$getName()

Returns: an object of class character

Method getParameters(): Get parameters

Usage:

OWSOperation\$getParameters()

Returns: the parameters

Method getParameter(): Get parameter

Usage:

OWSOperation\$getParameter(name)

Arguments:

name name

Returns: the parameter

Method clone(): The objects of this class are cloneable with this method.

Usage:

OWSOperation\$clone(deep = FALSE)

Arguments:

deep Whether to make a deep clone.

Note

Internal class used internally by **ows4R** when reading capabilities documents

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

OWSOperationsMetadata *OWSOperationsMetadata*

Description

OWSOperationsMetadata
OWSOperationsMetadata

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling an OGC Operations Metadata

Methods**Public methods:**

- [OWSOperationsMetadata\\$new\(\)](#)
- [OWSOperationsMetadata\\$getOperations\(\)](#)
- [OWSOperationsMetadata\\$clone\(\)](#)

Method [new\(\)](#): Initializes an [OWSOperationsMetadata](#) object

Usage:

```
OWSOperationsMetadata$new(xmlObj, owsVersion, serviceVersion)
```

Arguments:

xmlObj object of class [XMLInternalNode-class](#) from **XML**

owsVersion OWS version

serviceVersion service version

Method [getOperations\(\)](#): Get operations

Usage:

```
OWSOperationsMetadata$getOperations()
```

Returns: a list of [OWSOperation](#)

Method [clone\(\)](#): The objects of this class are cloneable with this method.

Usage:

```
OWSOperationsMetadata$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Note

Abstract class used internally by **ows4R**

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

OWSRequest

OWSRequest

Description

OWSRequest

OWSRequest

Format

[R6Class](#) object.

Value

Object of [R6Class](#) modelling a OWS Service Capability Request

Super class

[ows4R: :OGCAbstractObject](#) -> OWSRequest

Methods**Public methods:**

- [OWSRequest\\$new\(\)](#)
- [OWSRequest\\$getName\(\)](#)
- [OWSRequest\\$getFormats\(\)](#)
- [OWSRequest\\$clone\(\)](#)

Method [new\(\)](#): Initializes an object of class [OWSRequest](#)

Usage:

[OWSRequest\\$new](#)(xmlObj, capabilities, version, logger = NULL)

Arguments:

xmlObj object of class [XMLInternalNode-class](#) from **XML**
 capabilities an object of class or extending [OWSCapabilities](#)
 version version
 logger logger

Method [getName\(\)](#): Get request name

Usage:

[OWSRequest\\$getName](#)()

Returns: the name, object of class character

Method getFormats(): Get request formats

Usage:

OWSRequest\$getFormats()

Returns: the formats, object (vector) of class character

Method clone(): The objects of this class are cloneable with this method.

Usage:

OWSRequest\$clone(deep = FALSE)

Arguments:

deep Whether to make a deep clone.

Note

Abstract class used by **ows4R**

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

OWSServiceIdentification

OWSServiceIdentification

Description

OWSServiceIdentification

OWSServiceIdentification

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling an OGC Service Identification

Methods

Public methods:

- [OWSServiceIdentification\\$new\(\)](#)
- [OWSServiceIdentification\\$name\(\)](#)
- [OWSServiceIdentification\\$title\(\)](#)
- [OWSServiceIdentification\\$abstract\(\)](#)
- [OWSServiceIdentification\\$keywords\(\)](#)
- [OWSServiceIdentification\\$onlineResource\(\)](#)

- [OWSServiceIdentification\\$getServiceType\(\)](#)
- [OWSServiceIdentification\\$getServiceTypeVersion\(\)](#)
- [OWSServiceIdentification\\$getFees\(\)](#)
- [OWSServiceIdentification\\$getAccessConstraints\(\)](#)
- [OWSServiceIdentification\\$clone\(\)](#)

Method new(): Initializes an object of class [OWSServiceIdentification](#)

Usage:

```
OWSServiceIdentification$new(xmlObj, owsVersion, serviceVersion)
```

Arguments:

xmlObj object of class [XMLInternalNode-class](#) from **XML**

owsVersion OWS version

serviceVersion service version

Method getName(): Get service identification - name

Usage:

```
OWSServiceIdentification$getName()
```

Returns: the name, object of class character

Method getTitle(): Get service identification - title

Usage:

```
OWSServiceIdentification$getTitle()
```

Returns: the title, object of class character

Method getAbstract(): Get service identification - abstract

Usage:

```
OWSServiceIdentification$getAbstract()
```

Returns: the abstract, object of class character

Method getKeywords(): Get service identification - keywords

Usage:

```
OWSServiceIdentification$getKeywords()
```

Returns: the keywords, object of class character

Method getOnlineResource(): Get service identification - online resource

Usage:

```
OWSServiceIdentification$getOnlineResource()
```

Returns: the online resource, object of class character

Method getServiceType(): Get service identification - service type

Usage:

```
OWSServiceIdentification$getServiceType()
```

Returns: the service type, object of class character

Method getServiceTypeVersion(): Get service identification - service type version

Usage:

OWSServiceIdentification\$getServiceTypeVersion()

Returns: the service type version, object of class character

Method getFees(): Get service identification - fees

Usage:

OWSServiceIdentification\$getFees()

Returns: the fees, object of class character

Method getAccessConstraints(): Get service identification - access constraints

Usage:

OWSServiceIdentification\$getAccessConstraints()

Returns: the access constraints, object of class character

Method clone(): The objects of this class are cloneable with this method.

Usage:

OWSServiceIdentification\$clone(deep = FALSE)

Arguments:

deep Whether to make a deep clone.

Note

Abstract class used internally by **ows4R**

Author(s)

Emmanuel Blondel <emmanuel.blondell@gmail.com>

OWSServiceProvider *OWSServiceProvider*

Description

OWSServiceProvider

OWSServiceProvider

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling an OGC Service Provider

Methods

Public methods:

- [OWSServiceProvider\\$new\(\)](#)
- [OWSServiceProvider\\$getProviderName\(\)](#)
- [OWSServiceProvider\\$getProviderSite\(\)](#)
- [OWSServiceProvider\\$getServiceContact\(\)](#)
- [OWSServiceProvider\\$clone\(\)](#)

Method [new\(\)](#): Initializes an object of class [OWSServiceProvider](#)

Usage:

`OWSServiceProvider$new(xmlObj, owsVersion, serviceVersion)`

Arguments:

`xmlObj` object of class [XMLInternalNode-class](#) from **XML**

`owsVersion` OWS version

`serviceVersion` service version

Method [getProviderName\(\)](#): Get provider name

Usage:

`OWSServiceProvider$getProviderName()`

Arguments:

the provider name, object of class character

Method [getProviderSite\(\)](#): Get provider site

Usage:

`OWSServiceProvider$getProviderSite()`

Arguments:

the provider site, object of class character

Method [getServiceContact\(\)](#): Get provider contact

Usage:

`OWSServiceProvider$getServiceContact()`

Arguments:

the provider contact, object of class [ISOResponsibleParty](#) from **geometa**

Method [clone\(\)](#): The objects of this class are cloneable with this method.

Usage:

`OWSServiceProvider$clone(deep = FALSE)`

Arguments:

`deep` Whether to make a deep clone.

Note

Abstract class used internally by **ows4R**

Author(s)

Emmanuel Blondel <emmanuel.blondell@gmail.com>

OWSUtils

OWSUtils

Description

OWSUtils

Usage

OWSUtils

Format

[R6Class](#) object.

Value

set of OWS Utilities

Static methods

`getNamespaces()` Get the namespaces associated to a given XML object
`findNamespace(namespaces, id, uri)` Finds a namespace by id or by URI
`toBBOX(xmin, xmax, ymin, ymax)` Creates a bbox matrix from min/max x/y coordinates
`findP4s(srsName, morphToESRI)` Finds the PROJ4 string definition for a given srsName
`toCRS(srsName)` Converts a srsName into a CRS object
`toEPSG(crs)` Get the EPSG code from a CRS object
`getAspectRatio(bbox)` Get the aspect ratio for a given bbox

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

Examples

```
#toBBOX
bbox <- OWSUtils$toBBOX(-180,-90,180,90)

#toCRS
crs <- OWSUtils$toCRS("EPSG:4326")
```

OWSWG84BoundingBox *OWSWG84BoundingBox*

Description

OWSWG84BoundingBox

OWSWG84BoundingBox

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling an OGC WS84 BoundingBox

Super classes

[ows4R::OGCAbstractObject](#) -> [ows4R::OWSBoundingBox](#) -> OWSWG84BoundingBox

Methods**Public methods:**

- [OWSWG84BoundingBox\\$new\(\)](#)
- [OWSWG84BoundingBox\\$clone\(\)](#)

Method [new\(\)](#): Initializes an object of class [OWSBoundingBox](#)

Usage:

```
OWSWG84BoundingBox$new(xml = NULL, owsVersion, serviceVersion, logger = NULL)
```

Arguments:

xml an object of class [XMLInternalNode-class](#) to initialize from XML

owsVersion OWS version

serviceVersion service version

logger logger

Method [clone\(\)](#): The objects of this class are cloneable with this method.

Usage:

```
OWSWG84BoundingBox$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Note

Class used internally by **geometa**

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

PropertyIsBetween *PropertyIsBetween*

Description

PropertyIsBetween

PropertyIsBetween

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling an PropertyIsBetween

Super classes

[ows4R::OGCAbstractObject](#) -> [ows4R::OGCEXpression](#) -> PropertyIsBetween

Public fields

PropertyName property name field for XML encoding

lower lower value

upper upper value

Methods**Public methods:**

- [PropertyIsBetween\\$new\(\)](#)
- [PropertyIsBetween\\$clone\(\)](#)

Method `new()`: Initializes an object extending [PropertyIsLike](#)

Usage:

`PropertyIsBetween$new(PropertyName, lower, upper)`

Arguments:

PropertyName property name

lower lower value

upper upper value

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

`PropertyIsBetween$clone(deep = FALSE)`

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

Examples

```
expr <- PropertyIsBetween$new(PropertyName = "property", lower = 1, upper = 10)
expr_xml <- expr$encode() #see how it looks like in XML
```

PropertyIsEqualTo	<i>PropertyIsEqualTo</i>
-------------------	--------------------------

Description

PropertyIsEqualTo

PropertyIsEqualTo

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling an PropertyIsEqualTo

Super classes

[ows4R::OGCAbstractObject](#) -> [ows4R::OGCEXpression](#) -> [ows4R::BinaryComparisonOpType](#)
-> PropertyIsEqualTo

Methods**Public methods:**

- [PropertyIsEqualTo\\$new\(\)](#)
- [PropertyIsEqualTo\\$clone\(\)](#)

Method `new()`: Initializes an object extending [PropertyIsEqualTo](#)

Usage:

```
PropertyIsEqualTo$new(PropertyName, Literal, matchCase = NA)
```

Arguments:

PropertyName property name

Literal literal

matchCase match case

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
PropertyIsGreaterThanOrEqualTo$new(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

Examples

```
expr <- PropertyIsGreaterThanOrEqualTo$new(PropertyName = "property", Literal = "value")
expr_xml <- expr$encode() #see how it looks like in XML
```

PropertyIsGreaterThanOrEqualTo *PropertyIsGreaterThanOrEqualTo*

Description

PropertyIsGreaterThanOrEqualTo

PropertyIsGreaterThanOrEqualTo

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling an PropertyIsGreaterThanOrEqualTo

Super classes

```
ows4R::OGCAbstractObject -> ows4R::OGCExpression -> ows4R::BinaryComparisonOpType
-> PropertyIsGreaterThanOrEqualTo
```

Methods**Public methods:**

- [PropertyIsGreaterThanOrEqualTo\\$new\(\)](#)
- [PropertyIsGreaterThanOrEqualTo\\$clone\(\)](#)

Method `new()`: Initializes an object extending [PropertyIsGreaterThanOrEqualTo](#)

Usage:

```
PropertyIsGreaterThanOrEqualTo$new(PropertyName, Literal, matchCase = NA)
```

Arguments:

PropertyName property name
 Literal literal
 matchCase match case

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
PropertyIsGreaterThanOrEqualTo$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondell@gmail.com>

Examples

```
expr <- PropertyIsGreaterThanOrEqualTo$new(PropertyName = "property", Literal = "value")
expr_xml <- expr$encode() #see how it looks like in XML
```

PropertyIsGreaterThanOrEqualTo
PropertyIsGreaterThanOrEqualTo

Description

PropertyIsGreaterThanOrEqualTo
 PropertyIsGreaterThanOrEqualTo

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling an PropertyIsGreaterThanOrEqualTo

Super classes

```
ows4R::OGCAbstractObject -> ows4R::OGCExpression -> ows4R::BinaryComparisonOpType
-> PropertyIsGreaterThanOrEqualTo
```

Methods**Public methods:**

- [PropertyIsGreaterThanOrEqualTo\\$new\(\)](#)
- [PropertyIsGreaterThanOrEqualTo\\$clone\(\)](#)

Method `new()`: Initializes an object extending [PropertyIsGreaterThanOrEqualTo](#)

Usage:

```
PropertyIsGreaterThanOrEqualTo$new(PropertyName, Literal, matchCase = NA)
```

Arguments:

PropertyName property name

Literal literal

matchCase match case

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
PropertyIsGreaterThanOrEqualTo$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

Examples

```
expr <- PropertyIsGreaterThanOrEqualTo$new(PropertyName = "property", Literal = "value")
expr_xml <- expr$encode() #see how it looks like in XML
```

PropertyIsLessThan *PropertyIsLessThan*

Description

PropertyIsLessThan

PropertyIsLessThan

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling an PropertyIsLessThan

Super classes

ows4R::OGCAbstractObject -> ows4R::OGCExpression -> ows4R::BinaryComparisonOpType
 -> PropertyIsLessThan

Methods**Public methods:**

- [PropertyIsLessThan\\$new\(\)](#)
- [PropertyIsLessThan\\$clone\(\)](#)

Method new(): Initializes an object extending [PropertyIsLessThan](#)

Usage:

```
PropertyIsLessThan$new(PropertyName, Literal, matchCase = NA)
```

Arguments:

PropertyName property name

Literal literal

matchCase match case

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
PropertyIsLessThan$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

Examples

```
expr <- PropertyIsLessThan$new(PropertyName = "property", Literal = "value")
expr_xml <- expr$encode() #see how it looks like in XML
```

PropertyIsLessThanOrEqualTo

PropertyIsLesserThanOrEqualTo

Description

PropertyIsLesserThanOrEqualTo

PropertyIsLesserThanOrEqualTo

Format

R6Class object.

Value

Object of R6Class for modelling an PropertyIsLesserThanOrEqualTo

Super classes

ows4R::OGCAbstractObject -> ows4R::OGCExpression -> ows4R::BinaryComparisonOpType
-> PropertyIsLessThanOrEqualTo

Methods**Public methods:**

- PropertyIsLessThanOrEqualTo\$new()
- PropertyIsLessThanOrEqualTo\$clone()

Method new(): Initializes an object extending PropertyIsLessThanOrEqualTo

Usage:

```
PropertyIsLessThanOrEqualTo$new(PropertyName, Literal, matchCase = NA)
```

Arguments:

PropertyName property name

Literal literal

matchCase match case

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
PropertyIsLessThanOrEqualTo$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

Examples

```
expr <- PropertyIsLessThanOrEqualTo$new(PropertyName = "property", Literal = "value")  
expr_xml <- expr$encode() #see how it looks like in XML
```

PropertyIsLike	<i>PropertyIsLike</i>
----------------	-----------------------

Description

PropertyIsLike

PropertyIsLike

Format

R6Class object.

Value

Object of R6Class for modelling an PropertyIsLike

Super classes

ows4R::OGCAbstractObject -> ows4R::OGCExpression -> PropertyIsLike

Public fields

PropertyName property name field for XML encoding

Literal literal field for XML encoding

attrs attributes for XML encoding

Methods**Public methods:**

- [PropertyIsLike\\$new\(\)](#)
- [PropertyIsLike\\$clone\(\)](#)

Method new(): Initializes an object extending [PropertyIsLike](#)*Usage:*

```
PropertyIsLike$new(
  PropertyName,
  Literal,
  escapeChar = "\\\"",
  singleChar = "_",
  wildCard = "%",
  matchCase = NA
)
```

Arguments:

PropertyName property name

Literal literal

escapeChar escape character. Default is "\"
 singleChar single character. Default is "_"
 wildCard wildcard
 matchCase match case

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
PropertyIsLike$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondell@gmail.com>

Examples

```

expr <- PropertyIsLike$new(PropertyName = "property", Literal = "value")
expr_xml <- expr$encode() #see how it looks like in XML

```

PropertyIsNotEqualTo *PropertyIsNotEqualTo*

Description

PropertyIsNotEqualTo

PropertyIsNotEqualTo

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling an PropertyIsNotEqualTo

Super classes

```

ows4R::OGCAbstractObject -> ows4R::OGCExpression -> ows4R::BinaryComparisonOpType
-> PropertyIsNotEqualTo

```

Methods**Public methods:**

- [PropertyIsNotEqualTo\\$new\(\)](#)
- [PropertyIsNotEqualTo\\$clone\(\)](#)

Method `new()`: Initializes an object extending [PropertyIsNotEqualTo](#)

Usage:

```
PropertyIsNotEqualTo$new(PropertyName, Literal, matchCase = NA)
```

Arguments:

PropertyName property name

Literal literal

matchCase match case

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
PropertyIsNotEqualTo$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

Examples

```
expr <- PropertyIsNotEqualTo$new(PropertyName = "property", Literal = "value")
expr_xml <- expr$encode() #see how it looks like in XML
```

PropertyIsNull

PropertyIsNull

Description

PropertyIsNull

PropertyIsNull

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling an PropertyIsNull

Super classes

[ows4R::OGCAbstractObject](#) -> [ows4R::OGCExpression](#) -> [PropertyIsNull](#)

Public fields

PropertyName property name field for XML encoding

Methods**Public methods:**

- [PropertyIsNull\\$new\(\)](#)
- [PropertyIsNull\\$clone\(\)](#)

Method `new()`: Initializes an object extending [PropertyIsLike](#)

Usage:

```
PropertyIsNull$new(PropertyName)
```

Arguments:

PropertyName property name

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
PropertyIsNull$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondell@gmail.com>

Examples

```
expr <- PropertyIsNull$new(PropertyName = "property")
expr_xml <- expr$encode() #see how it looks like in XML
```

registerOWSNamespace *registerOWSNamespace*

Description

registerOWSNamespace allows to register a new namespace in **ows4R**

Usage

```
registerOWSNamespace(id, uri, force)
```

Arguments

<code>id</code>	prefix of the namespace
<code>uri</code>	URI of the namespace
<code>force</code>	logical parameter indicating if registration has be to be forced in case the identified namespace is already registered

Author(s)

Emmanuel Blondel, <emmanuel.blondel1@gmail.com>

Examples

```
registerOWSNamespace(id = "myprefix", uri = "http://someuri")
```

<code>setOWSNamespace</code>	<i>setOWSNamespace</i>
------------------------------	------------------------

Description

`setOWSNamespace`

Usage

`setOWSNamespace()`

<code>UnaryLogicOpType</code>	<i>UnaryLogicOpType</i>
-------------------------------	-------------------------

Description

`UnaryLogicOpType`

`UnaryLogicOpType`

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling an `UnaryLogicOpType`

Super classes

[ows4R::OGCAbstractObject](#) -> [ows4R::OGCEXpression](#) -> `UnaryLogicOpType`

Public fields

operations a list OGC expressions

Methods**Public methods:**

- [UnaryLogicOpType\\$new\(\)](#)
- [UnaryLogicOpType\\$setExprVersion\(\)](#)
- [UnaryLogicOpType\\$clone\(\)](#)

Method `new()`: Initializes a [UnaryLogicOpType](#) expression

Usage:

```
UnaryLogicOpType$new(..., element, namespacePrefix, exprVersion = "1.1.0")
```

Arguments:

... list of objects of class [OGCExpression](#)

element element

namespacePrefix namespacePrefix

exprVersion OGC expression version. Default is "1.1.0"

Method `setExprVersion()`: Sets expression version. The methods will control that expression versions are set for each of the operations specified in the expression.

Usage:

```
UnaryLogicOpType$setExprVersion(exprVersion)
```

Arguments:

exprVersion OGC expression version

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
UnaryLogicOpType$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Note

abstract super class of all the unary logical operation classes

WCSCapabilities	<i>WCSCapabilities</i>
-----------------	------------------------

Description

WCSCapabilities

WCSCapabilities

Format

[R6Class](#) object.

Value

Object of [R6Class](#) with methods for interfacing an OGC Web Coverage Service Get Capabilities document.

Super classes

[ows4R::OGCAbstractObject](#) -> [ows4R::OWSCapabilities](#) -> WCSCapabilities

Methods

Public methods:

- [WCSCapabilities\\$new\(\)](#)
- [WCSCapabilities\\$getCoverageSummaries\(\)](#)
- [WCSCapabilities\\$findCoverageSummaryById\(\)](#)
- [WCSCapabilities\\$clone\(\)](#)

Method [new\(\)](#): Initializes a [WCSCapabilities](#) object

Usage:

```
WCSCapabilities$new(url, version, client = NULL, logger = NULL, ...)
```

Arguments:

url url

version version

client an object of class [WCSCClient](#)

logger logger type NULL, "INFO" or "DEBUG"

... any other parameter to pass to [OWSGetCapabilities](#) service request

Method [getCoverageSummaries\(\)](#): Get coverage summaries

Usage:

```
WCSCapabilities$getCoverageSummaries()
```

Returns: a list of [WCSCoverageSummary](#) objects

Method findCoverageSummaryById(): Finds a coverage by name

Usage:

WCSCapabilities\$findCoverageSummaryById(expr, exact = FALSE)

Arguments:

expr expr

exact exact matching? Default is TRUE

Method clone(): The objects of this class are cloneable with this method.

Usage:

WCSCapabilities\$clone(deep = FALSE)

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

Examples

```
## Not run:
  WCSCapabilities$new("http://localhost:8080/geoserver/wcs", serviceVersion = "2.0.1")

## End(Not run)
```

WCSClient

WCSClient

Description

WCSClient

WCSClient

Format

[R6Class](#) object.

Value

Object of [R6Class](#) with methods for interfacing an OGC Web Coverage Service.

Super classes

[ows4R::OGCAbstractObject](#) -> [ows4R::OWSClient](#) -> WCSClient

Methods

Public methods:

- [WCSClient\\$new\(\)](#)
- [WCSClient\\$getCapabilities\(\)](#)
- [WCSClient\\$reloadCapabilities\(\)](#)
- [WCSClient\\$describeCoverage\(\)](#)
- [WCSClient\\$getCoverage\(\)](#)
- [WCSClient\\$clone\(\)](#)

Method `new()`: This method is used to instantiate a [WCSClient](#) with the url of the OGC service. Authentication is supported using basic auth (using user/pwd arguments), bearer token (using token argument), or custom (using headers argument). By default, the logger argument will be set to NULL (no logger). This argument accepts two possible values: INFO: to print only **ows4R** logs, DEBUG: to print more verbose logs

Usage:

```
WCSClient$new(
  url,
  serviceVersion = NULL,
  user = NULL,
  pwd = NULL,
  token = NULL,
  headers = c(),
  config = httr::config(),
  cas_url = NULL,
  logger = NULL
)
```

Arguments:

```
url url
serviceVersion WFS service version
user user
pwd password
token token
headers headers
config config
cas_url Central Authentication Service (CAS) URL
logger logger
```

Method `getCapabilities()`: Get WCS capabilities

Usage:

```
WCSClient$getCapabilities()
```

Returns: an object of class [WCSCapabilities](#)

Method `reloadCapabilities()`: Reloads WCS capabilities

Usage:

WCSClient\$reloadCapabilities()

Method describeCoverage(): Describes coverage

Usage:

WCSClient\$describeCoverage(identifier)

Arguments:

identifier identifier

Returns: an object of class [WCSCoverageDescription](#)

Method getCoverage(): Get coverage

Usage:

```
WCSClient$getCoverage(
  identifier,
  bbox = NULL,
  crs = NULL,
  time = NULL,
  format = NULL,
  rangesubset = NULL,
  gridbaseCRS = NULL,
  gridtype = NULL,
  gridCS = NULL,
  gridorigin = NULL,
  gridoffsets = NULL,
  method = "GET",
  filename = NULL,
  ...
)
```

Arguments:

identifier Coverage identifier. Object of class character

bbox bbox. Object of class matrix. Default is NULL. eg. `OWSUtils$toBBOX(-180,180,-90,90)`

crs crs. Object of class character giving the CRS identifier (EPSG prefixed code, or URI/URN). Default is NULL.

time time. Object of class character representing time instant/period. Default is NULL

format format. Object of class character Default will be GeoTIFF, coded differently depending on the WCS version.

rangesubset rangesubset. Default is NULL

gridbaseCRS grid base CRS. Default is NULL

gridtype grid type. Default is NULL

gridCS grid CS. Default is NULL

gridorigin grid origin. Default is NULL

gridoffsets grid offsets. Default is NULL

method method to get coverage, either 'GET' or 'POST' (experimental - under development). Object of class character.

filename filename. Object of class character. Optional filename to download the coverage

... any other argument to [WCSGetCoverage](#)
 elevation elevation. Object of class character or numeric. Default is NULL

Returns: an object of class SpatRaster from **terra**

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
WCSClient$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

Examples

```
## Not run:
  wcs <- WCSClient$new("http://localhost:8080/geoserver/wcs", serviceVersion = "2.0.1")

## End(Not run)
```

WCSCoverage

WCSCoverage

Description

WCSCoverage

WCSCoverage

Format

[R6Class](#) object.

Value

Object of [R6Class](#) modelling a WCS coverage

Super class

[ows4R::OGCAbstractObject](#) -> WCSCoverage

Public fields

description description

Methods**Public methods:**

- [WCSCoverage\\$new\(\)](#)
- [WCSCoverage\\$getIdentifier\(\)](#)
- [WCSCoverage\\$getTitle\(\)](#)
- [WCSCoverage\\$getAbstract\(\)](#)
- [WCSCoverage\\$getReference\(\)](#)
- [WCSCoverage\\$getData\(\)](#)
- [WCSCoverage\\$clone\(\)](#)

Method [new\(\)](#): Initializes an object of class [WCSCoverage](#)

Usage:

```
WCSCoverage$new(xmlObj, serviceVersion, owsVersion, logger = NULL)
```

Arguments:

xmlObj object of class [XMLInternalNode-class](#)

serviceVersion WCS service version

owsVersion OWS version

logger logger

Method [getIdentifier\(\)](#): Get identifier

Usage:

```
WCSCoverage$getIdentifier()
```

Returns: an object of class character

Method [getTitle\(\)](#): Get title

Usage:

```
WCSCoverage$getTitle()
```

Returns: an object of class character

Method [getAbstract\(\)](#): Get abstract

Usage:

```
WCSCoverage$getAbstract()
```

Returns: an object of class character

Method [getReference\(\)](#): Get reference

Usage:

```
WCSCoverage$getReference()
```

Returns: an object of class character

Method [getData\(\)](#): Get data

Usage:

```
WCSCoverage$getData(filename = NULL)
```

Arguments:

filename filename. Optional file name where to download the coverage

Returns: an object of class SpatRaster from **terra**

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
WCSCoverage$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Note

Class used internally by ows4R.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

WCSCoverageDescription

WCSCoverageDescription

Description

WCSCoverageDescription

WCSCoverageDescription

Format

[R6Class](#) object.

Value

Object of [R6Class](#) modelling a WCS coverage summary

Super classes

```
geometa::geometaLogger -> geometa::ISOAbstractObject -> geometa::GMLAbstractObject  
-> geometa::GMLAbstractFeature -> geometa::GMLAbstractCoverage -> geometa::GMLCOVAbstractCoverage  
-> WCSCoverageDescription
```

Public fields

CoverageId coverage ID
SupportedCRS supported CRS
SupportedFormat supported Format
Domain domain
Range range
ServiceParameters service parameters

Methods**Public methods:**

- [WCSCoverageDescription\\$new\(\)](#)
- [WCSCoverageDescription\\$getId\(\)](#)
- [WCSCoverageDescription\\$getSupportedCRS\(\)](#)
- [WCSCoverageDescription\\$getSupportedFormats\(\)](#)
- [WCSCoverageDescription\\$getDomain\(\)](#)
- [WCSCoverageDescription\\$getRange\(\)](#)
- [WCSCoverageDescription\\$clone\(\)](#)

Method [new\(\)](#): Initializes an object of class [WCSCoverageDescription](#)

Usage:

`WCSCoverageDescription$new(xmlObj, serviceVersion, owsVersion, logger = NULL)`

Arguments:

`xmlObj` an object of class [XMLInternalNode-class](#) to initialize from XML
`serviceVersion` service version
`owsVersion` OWS version
`logger` logger

Method [getId\(\)](#): `getId`

Usage:

`WCSCoverageDescription$getId()`

Returns: the coverage id, object of class character

Method [getSupportedCRS\(\)](#): `getSupported CRS`. Applies to WCS 1 coverage descriptions

Usage:

`WCSCoverageDescription$getSupportedCRS()`

Method [getSupportedFormats\(\)](#): `get supported formats`. Applies to WCS 1 coverage descriptions

Usage:

`WCSCoverageDescription$getSupportedFormats()`

Method [getDomain\(\)](#): `get domain`. Applies to WCS 1 coverage descriptions

Usage:

WCSCoverageDescription\$getDomain()

Method getRange(): get range. Applies to WCS 1.0 coverage descriptions

Usage:

WCSCoverageDescription\$getRange()

Method clone(): The objects of this class are cloneable with this method.

Usage:

WCSCoverageDescription\$clone(deep = FALSE)

Arguments:

deep Whether to make a deep clone.

Note

Class used internally by ows4R.

Author(s)

Emmanuel Blondel <emmanuel.blondell@gmail.com>

WCSCoverageDomain

WCSCoverageDomain

Description

WCSCoverageDomain

WCSCoverageDomain

Format

[R6Class](#) object.

Value

Object of [R6Class](#) modelling a WCS coverage domain

Super class

[ows4R::OGCAbstractObject](#) -> WCSCoverageDomain

Public fields

spatialDomain spatial domain

temporalDomain temporal domain

Methods**Public methods:**

- [WCSCoverageDomain\\$new\(\)](#)
- [WCSCoverageDomain\\$getSpatialDomain\(\)](#)
- [WCSCoverageDomain\\$getTemporalDomain\(\)](#)
- [WCSCoverageDomain\\$clone\(\)](#)

Method [new\(\)](#): Initializes an object of class [WCSCoverageDomain](#)

Usage:

```
WCSCoverageDomain$new(xmlObj, serviceVersion, owsVersion, logger = NULL)
```

Arguments:

xmlObj an object of class [XMLInternalNode-class](#) to initialize from XML

serviceVersion service version

owsVersion OWS version

logger logger

Method [getSpatialDomain\(\)](#): Get spatial domain

Usage:

```
WCSCoverageDomain$getSpatialDomain()
```

Returns: object of class [WCSCoverageSpatialDomain](#)

Method [getTemporalDomain\(\)](#): Get spatial domain

Usage:

```
WCSCoverageDomain$getTemporalDomain()
```

Returns: object of class [WCSCoverageTemporalDomain](#)

Method [clone\(\)](#): The objects of this class are cloneable with this method.

Usage:

```
WCSCoverageDomain$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Note

Class used internally by ows4R.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

WCSCoverageFilenameHandler

WCSCoverageFilenameHandler

Description

WCSCoverageFilenameHandler provides a coverage filename handler for coverage download

Usage

WCSCoverageFilenameHandler(identifier, time, elevation, bbox, format)

Arguments

identifier	coverage identifier
time	time
elevation	elevation
bbox	bbox
format	format

Value

the filename to use for coverage download

Author(s)

Emmanuel Blondel, <emmanuel.blondel1@gmail.com>

WCSCoverageSpatialDomain

WCSCoverageSpatialDomain

Description

WCSCoverageSpatialDomain

WCSCoverageSpatialDomain

Format

[R6Class](#) object.

Value

Object of [R6Class](#) modelling a WCS coverage spatial domain

Super class

[ows4R::OGCAbstractObject](#) -> WCSCoverageSpatialDomain

Public fields

envelopes envelopes. For WCS 1.0

BoundingBox bounding box. For WCS 1.1

grids For WCS 1.0

GridCRS grid CRS. For WCS 1.1

Methods**Public methods:**

- [WCSCoverageSpatialDomain\\$new\(\)](#)
- [WCSCoverageSpatialDomain\\$getEnvelopes\(\)](#)
- [WCSCoverageSpatialDomain\\$getBoundingBox\(\)](#)
- [WCSCoverageSpatialDomain\\$getGrids\(\)](#)
- [WCSCoverageSpatialDomain\\$getGridCRS\(\)](#)
- [WCSCoverageSpatialDomain\\$clone\(\)](#)

Method [new\(\)](#): Initializes an object of class [WCSCoverageDomain](#)

Usage:

`WCSCoverageSpatialDomain$new(xmlObj, serviceVersion, owsVersion, logger = NULL)`

Arguments:

xmlObj an object of class [XMLInternalNode-class](#) to initialize from XML

serviceVersion service version

owsVersion OWS version

logger logger

Method [getEnvelopes\(\)](#): Get envelopes. Method that applies to WCS 1.0 only

Usage:

`WCSCoverageSpatialDomain$getEnvelopes()`

Returns: a list of objects of class [GMLEnvelope](#) or [GMLEnvelopeWithTimePeriod](#)

Method [getBoundingBox\(\)](#): Get bounding boxes. Method that applies to WCS 1.1 only

Usage:

`WCSCoverageSpatialDomain$getBoundingBox()`

Returns: a list of objects of class [OWSBoundingBox](#)

Method [getGrids\(\)](#): Get grids. Method that applies to WCS 1.0 only

Usage:

`WCSCoverageSpatialDomain$getGrids()`

Returns: a list of objects of class [GMLGrid](#) or [GMLRectifiedGrid](#)

Method `getGridCRS()`: Get Grid CRS. Method that applies to WCS 1.1 only

Usage:

`WCSCoverageSpatialDomain$getGridCRS()`

Returns: a list of objects of class [WCSGridCRS](#)

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

`WCSCoverageSpatialDomain$clone(deep = FALSE)`

Arguments:

`deep` Whether to make a deep clone.

Note

Class used internally by ows4R.

Author(s)

Emmanuel Blondel <emmanuel.blondell@gmail.com>

WCSCoverageSummary *WCSCoverageSummary*

Description

WCSCoverageSummary

WCSCoverageSummary

Format

[R6Class](#) object.

Value

Object of [R6Class](#) modelling a WCS coverage summary

Super class

[ows4R::OGCAbstractObject](#) -> WCSCoverageSummary

Public fields

CoverageId coverage id

CoverageSubtype coverage subtype

CoverageSubtypeParent coverage subtype parent

WGS84BoundingBox WGS84 bounding box

BoundingBox bounding box

Methods**Public methods:**

- [WCSCoverageSummary\\$new\(\)](#)
- [WCSCoverageSummary\\$getId\(\)](#)
- [WCSCoverageSummary\\$getSubtype\(\)](#)
- [WCSCoverageSummary\\$getSubtypeParent\(\)](#)
- [WCSCoverageSummary\\$getWGS84BoundingBox\(\)](#)
- [WCSCoverageSummary\\$getBoundingBox\(\)](#)
- [WCSCoverageSummary\\$getDescription\(\)](#)
- [WCSCoverageSummary\\$getDimensions\(\)](#)
- [WCSCoverageSummary\\$getCoverage\(\)](#)
- [WCSCoverageSummary\\$getCoverageStack\(\)](#)
- [WCSCoverageSummary\\$clone\(\)](#)

Method new(): Initializes a [WCSCoverageSummary](#) object

Usage:

```
WCSCoverageSummary$new(  
  xmlObj,  
  capabilities,  
  serviceVersion,  
  owsVersion,  
  logger = NULL  
)
```

Arguments:

xmlObj object of class [XMLInternalNode-class](#) from [XML](#)
capabilities object of class [WCSCapabilities](#)
serviceVersion WCS service version
owsVersion version
logger logger type NULL, "INFO" or "DEBUG"

Method getId(): Get coverage ID

Usage:

```
WCSCoverageSummary$getId()
```

Returns: an object of class character

Method getSubtype(): Get sub type

Usage:

```
WCSCoverageSummary$getSubtype()
```

Returns: an object of class character

Method getSubtypeParent(): Get sub type parent

Usage:

```
WCSCoverageSummary$getSubtypeParent()
```

Returns: an object of class character

Method `getWGS84BoundingBox()`: Get bounding box

Usage:

```
WCSCoverageSummary$getWGS84BoundingBox()
```

Returns: an object of class [OWSWGS84BoundingBox](#)

Method `getBoundingBox()`: Get WGS84 bounding box

Usage:

```
WCSCoverageSummary$getBoundingBox()
```

Returns: an object of class [OWSBoundingBox](#)

Method `getDescription()`: Get description

Usage:

```
WCSCoverageSummary$getDescription()
```

Returns: an object of class [WCSCoverageDescription](#)

Method `getDimensions()`: Get dimensions

Usage:

```
WCSCoverageSummary$getDimensions()
```

Returns: the list of dimensions

Method `getCoverage()`: Get coverage data

Usage:

```
WCSCoverageSummary$getCoverage(
  bbox = NULL,
  crs = NULL,
  time = NULL,
  elevation = NULL,
  format = NULL,
  rangesubset = NULL,
  gridbaseCRS = NULL,
  gridtype = NULL,
  gridCS = NULL,
  gridorigin = NULL,
  gridoffsets = NULL,
  method = "GET",
  filename = NULL,
  ...
)
```

Arguments:

`bbox` `bbox`. Object of class `matrix`. Default is `NULL`. eg. `OWSUtils$toBBOX(-180,180,-90,90)`

`crs` `crs`. Object of class character giving the CRS identifier (EPSG prefixed code, or URI/URN). Default is `NULL`.

`time` `time`. Object of class character representing time instant/period. Default is `NULL`

elevation elevation. Object of class character or numeric. Default is NULL
 format format. Object of class character Default will be GeoTIFF, coded differently depending on the WCS version.
 rangesubset rangesubset. Default is NULL
 gridbaseCRS grid base CRS. Default is NULL
 gridtype grid type. Default is NULL
 gridCS grid CS. Default is NULL
 gridorigin grid origin. Default is NULL
 gridoffsets grid offsets. Default is NULL
 method method to get coverage, either 'GET' or 'POST' (experimental - under development).
 Object of class character.
 filename filename. Object of class character. Optional filename to download the coverage
 ... any other argument to [WCSGetCoverage](#)
Returns: an object of class SpatRaster from **terra**

Method `getCoverageStack()`: Get a spatio-temporal coverage data cubes as coverage [stack](#)

Usage:

```
WCSCoverageSummary$getCoverageStack(
  time = NULL,
  elevation = NULL,
  bbox = NULL,
  filename_handler = NULL,
  ...
)
```

Arguments:

time time
 elevation elevation
 bbox bbox
 filename_handler Optional filename handling function with arguments 'identifier', 'time', 'elevation', 'bbox', 'format' See [WCSCoverageFilenameHandler](#) as generic filename handler that can be used.
 ... any other parameter to pass to `getCoverage`
Returns: an object of class [stack](#) from **raster**

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
WCSCoverageSummary$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Note

Class used internally by ows4R.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

WCSCoverageTemporalDomain
WCSCoverageTemporalDomain

Description

WCSCoverageTemporalDomain
WCSCoverageTemporalDomain

Format

[R6Class](#) object.

Value

Object of [R6Class](#) modelling a WCS coverage temporal domain

Super class

[ows4R: :OGCAbstractObject](#) -> WCSCoverageTemporalDomain

Public fields

instants instants
periods periods

Methods**Public methods:**

- [WCSCoverageTemporalDomain\\$new\(\)](#)
- [WCSCoverageTemporalDomain\\$getInstants\(\)](#)
- [WCSCoverageTemporalDomain\\$getPeriods\(\)](#)
- [WCSCoverageTemporalDomain\\$clone\(\)](#)

Method [new\(\)](#): Initializes an object of class [WCSCoverageTemporalDomain](#)

Usage:

```
WCSCoverageTemporalDomain$new(  
  xmlObj,  
  serviceVersion,  
  owsVersion,  
  logger = NULL  
)
```

Arguments:

xmlObj an object of class [XMLInternalNode-class](#) to initialize from XML
serviceVersion service version

owsVersion OWS version
logger logger

Method getInstants(): Get time instants

Usage:

WCSCoverageTemporalDomain\$getInstants()

Returns: a list of objects of class POSIXct

Method getPeriods(): Get time periods

Usage:

WCSCoverageTemporalDomain\$getPeriods()

Returns: a list of objects of class [GMLTimePeriod](#)

Method clone(): The objects of this class are cloneable with this method.

Usage:

WCSCoverageTemporalDomain\$clone(deep = FALSE)

Arguments:

deep Whether to make a deep clone.

Note

Class used internally by ows4R.

Author(s)

Emmanuel Blondel <emmanuel.blondell@gmail.com>

WCSDescribeCoverage *WCSDescribeCoverage*

Description

WCSDescribeCoverage

WCSDescribeCoverage

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling a WCS DescribeCoverage request

Super classes

[ows4R::OGCAbstractObject](#) -> [ows4R::OWSHttpRequest](#) -> WCSDescribeCoverage

Methods**Public methods:**

- [WCSDescribeCoverage\\$new\(\)](#)
- [WCSDescribeCoverage\\$clone\(\)](#)

Method `new()`: Initializes a [WCSDescribeCoverage](#) service request

Usage:

```
WCSDescribeCoverage$new(
  capabilities,
  op,
  url,
  serviceVersion,
  coverageId,
  user = NULL,
  pwd = NULL,
  token = NULL,
  headers = c(),
  config = httr::config(),
  logger = NULL,
  ...
)
```

Arguments:

`capabilities` an object of class [WCSCapabilities](#)
`op` object of class [OWSOperation](#) as retrieved from `capabilities`
`url` url
`serviceVersion` serviceVersion
`coverageId` coverage ID
`user` user
`pwd` password
`token` token
`headers` headers
`config` config
`logger` logger
`...` any parameter to pass to the service request

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
WCSDescribeCoverage$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Note

Class used internally by **ows4R** to trigger a WCS DescribeCoverage request

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

WCSGetCoverage

WCSGetCoverage

Description

WCSGetCoverage

WCSGetCoverage

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling a WCS GetCoverage request

Super classes

[ows4R::OGCAbstractObject](#) -> [ows4R::OWSHttpRequest](#) -> WCSGetCoverage

Public fields

CoverageId coverage identifier

format coverage format

Methods**Public methods:**

- [WCSGetCoverage\\$new\(\)](#)
- [WCSGetCoverage\\$clone\(\)](#)

Method new(): Initializes a [WCSGetCoverage](#) service request

Usage:

```
WCSGetCoverage$new(  
  capabilities,  
  op,  
  url,  
  serviceVersion,  
  coverage,  
  envelope = NULL,  
  crs = NULL,  
  time = NULL,  
  elevation = NULL,
```

```

format = NULL,
rangesubset = NULL,
gridbaseCRS = NULL,
gridtype = NULL,
gridCS = NULL,
gridorigin = NULL,
gridoffsets = NULL,
user = NULL,
pwd = NULL,
token = NULL,
headers = c(),
config = httr::config(),
method = "GET",
logger = NULL,
...
)

```

Arguments:

capabilities an object of class [WCSCapabilities](#)
op object of class [OWSOperation](#) as retrieved from capabilities
url url
serviceVersion serviceVersion
coverage coverage, object of class [WCSCoverageSummary](#)
envelope envelope
crs crs
time time
elevation elevation
format format
rangesubset range subset
gridbaseCRS grid base CRS
gridtype grid type
gridCS grid CS
gridorigin grid origin
gridoffsets grid offsets
user user
pwd password
token token
headers headers
config config
method method
logger logger
... any parameter to pass to the service request

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
WCSGetCoverage$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Note

Class used internally by **ows4R** to trigger a WCS GetCoverage request

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

WCSGridCRS

WCSGridCRS

Description

WCSGridCRS

WCSGridCRS

Format

[R6Class](#) object.

Value

Object of [R6Class](#) modelling a WCS grid CRS

Super class

[ows4R::OGCAbstractObject](#) -> WCSGridCRS

Public fields

GridBaseCRS grid base CRS

GridType grid type

GridOrigin grid origin

GridOffsets grid offsets

GridCS grid CS

Methods**Public methods:**

- [WCSGridCRS\\$new\(\)](#)
- [WCSGridCRS\\$clone\(\)](#)

Method `new()`: Initializes an object of class [WCSGridCRS](#)

Usage:

```
WCSGridCRS$new(xmlObj, serviceVersion, owsVersion, logger = NULL)
```

Arguments:

`xmlObj` an object of class [XMLInternalNode-class](#) to initialize from XML
`serviceVersion` service version
`owsVersion` OWS version
`logger` logger

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
WCSGridCRS$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Note

Class used internally by ows4R.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

WCSGSElevationDomain *WCSGSElevationDomain*

Description

WCSGSElevationDomain

WCSGSElevationDomain

Format

[R6Class](#) object.

Value

Object of [R6Class](#) modelling a WCS geoserver elevation domain object

Super classes

[geometa::geometalLogger](#) -> [geometa::ISOAbstractObject](#) -> [WCSGSElevationDomain](#)

Public fields

SingleValue single values

Methods**Public methods:**

- [WCSGSElevationDomain\\$decode\(\)](#)
- [WCSGSElevationDomain\\$clone\(\)](#)

Method [decode\(\)](#): Decodes from XML

Usage:

[WCSGSElevationDomain\\$decode\(xml\)](#)

Arguments:

xml object of class [XMLInternalNode-class](#) from **XML**

Method [clone\(\)](#): The objects of this class are cloneable with this method.

Usage:

[WCSGSElevationDomain\\$clone\(deep = FALSE\)](#)

Arguments:

deep Whether to make a deep clone.

Note

Experimental

Author(s)

Emmanuel Blondel <emmanuel.blondell@gmail.com>

WCSGSTimeDomain

WCSGSTimeDomain

Description

WCSGSTimeDomain

WCSGSTimeDomain

Format

[R6Class](#) object.

Value

Object of [R6Class](#) modelling a WCS geoserver time domain object

Super classes

[geometa::geometaLogger](#) -> [geometa::ISOAbstractObject](#) -> [WCSGSTimeDomain](#)

Public fields

TimeInstant time instants

Methods**Public methods:**

- [WCSGSTimeDomain\\$decode\(\)](#)
- [WCSGSTimeDomain\\$clone\(\)](#)

Method [decode\(\)](#): Decodes from XML

Usage:

[WCSGSTimeDomain\\$decode\(xml\)](#)

Arguments:

xml object of class [XMLInternalNode-class](#) from [XML](#)

Method [clone\(\)](#): The objects of this class are cloneable with this method.

Usage:

[WCSGSTimeDomain\\$clone\(deep = FALSE\)](#)

Arguments:

deep Whether to make a deep clone.

Note

Experimental

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

WFSCapabilities	<i>WFSCapabilities</i>
-----------------	------------------------

Description

WFSCapabilities

WFSCapabilities

Format

[R6Class](#) object.

Value

Object of [R6Class](#) with methods for interfacing an OGC Web Feature Service Get Capabilities document.

Super classes

[ows4R::OGCAbstractObject](#) -> [ows4R::OWSCapabilities](#) -> WFSCapabilities

Methods**Public methods:**

- [WFSCapabilities\\$new\(\)](#)
- [WFSCapabilities\\$getFeatureTypes\(\)](#)
- [WFSCapabilities\\$findFeatureTypeByName\(\)](#)
- [WFSCapabilities\\$clone\(\)](#)

Method [new\(\)](#): Initializes a [WFSCapabilities](#) object

Usage:

```
WFSCapabilities$new(url, version, logger = NULL, ...)
```

Arguments:

url url

version version

logger logger type NULL, "INFO" or "DEBUG"

... any other parameter to pass to [OWSGetCapabilities](#) service request

Method [getFeatureTypes\(\)](#): List the feature types available. If pretty is TRUE, the output will be an object of class data.frame

Usage:

```
WFSCapabilities$getFeatureTypes(pretty = FALSE)
```

Arguments:

pretty whether the output should be summarized as data.frame

Returns: a list of [WFSFeatureType](#) or a `data.frame`

Method `findFeatureTypeByName()`: Finds a feature type by name

Usage:

```
WFSCapabilities$findFeatureTypeByName(expr, exact = TRUE)
```

Arguments:

`expr` `expr`

`exact` exact matching? Default is TRUE

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
WFSCapabilities$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Note

Class used to read a `WFSCapabilities` document. The use of `WFSClient` is recommended instead to benefit from the full set of capabilities associated to a WFS server.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

WFSClient

WFSClient

Description

WFSClient

WFSClient

Format

[R6Class](#) object.

Value

Object of [R6Class](#) with methods for interfacing an OGC Web Feature Service.

Super classes

[ows4R::OGCAbstractObject](#) -> [ows4R::OWSClient](#) -> `WFSClient`

Methods**Public methods:**

- [WFSCClient\\$new\(\)](#)
- [WFSCClient\\$getCapabilities\(\)](#)
- [WFSCClient\\$reloadCapabilities\(\)](#)
- [WFSCClient\\$describeFeatureType\(\)](#)
- [WFSCClient\\$getFeatures\(\)](#)
- [WFSCClient\\$getFeatureTypes\(\)](#)
- [WFSCClient\\$clone\(\)](#)

Method `new()`: This method is used to instantiate a [WFSCClient](#) with the url of the OGC service. Authentication is supported using basic auth (using user/pwd arguments), bearer token (using token argument), or custom (using headers argument). By default, the logger argument will be set to NULL (no logger). This argument accepts two possible values: INFO: to print only **ows4R** logs, DEBUG: to print more verbose logs

Usage:

```
WFSCClient$new(
  url,
  serviceVersion = NULL,
  user = NULL,
  pwd = NULL,
  token = NULL,
  headers = c(),
  config = httr::config(),
  cas_url = NULL,
  logger = NULL
)
```

Arguments:

```
url url
serviceVersion WFS service version
user user
pwd password
token token
headers headers
config config
cas_url Central Authentication Service (CAS) URL
logger logger
```

Method `getCapabilities()`: Get WFS capabilities

Usage:

```
WFSCClient$getCapabilities()
```

Returns: an object of class [WFSCapabilities](#)

Method `reloadCapabilities()`: Reloads WFS capabilities

Usage:

```
WFSCient$reloadCapabilities()
```

Method describeFeatureType(): Describes a feature type

Usage:

```
WFSCient$describeFeatureType(typeName)
```

Arguments:

typeName the name of the feature type

Returns: a list of [WFSFeatureTypeElement](#)

Method getFeatures(): Get features

Usage:

```
WFSCient$getFeatures(typeName, ...)
```

Arguments:

typeName the name of the feature type

... any other parameter to pass to the [WFSGetFeature](#) request

Returns: features as object of class sf

Method getFeatureTypes(): List the feature types available. If pretty is TRUE, the output will be an object of class data.frame

Usage:

```
WFSCient$getFeatureTypes(pretty = FALSE)
```

Arguments:

pretty whether the output should be summarized as data.frame

Returns: a list of [WFSFeatureType](#) or a data.frame

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
WFSCient$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondell@gmail.com>

Examples

```
## Not run:
#example based on a WFS endpoint responding at http://localhost:8080/geoserver/wfs
wfs <- WFSCient$new("http://localhost:8080/geoserver/wfs", serviceVersion = "1.1.1")

#get capabilities
caps <- wfs$getCapabilities()
```

```
#find feature type
ft <- caps$findFeatureTypeByName("mylayer")
if(length(ft)>0){
  data <- ft$getFeatures()
  data_with_filter <- ft$getFeatures(cql_filter = "somefilter")
}

#Advanced examples at https://github.com/eblondel/ows4R/wiki#wfs

## End(Not run)
```

WFSDescribeFeatureType

WFSDescribeFeatureType

Description

WFSDescribeFeatureType

WFSDescribeFeatureType

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling a WFS DescribeFeatureType request

Super classes

[ows4R::OGCAbstractObject](#) -> [ows4R::OWSHttpRequest](#) -> WFSDescribeFeatureType

Methods

Public methods:

- [WFSDescribeFeatureType\\$new\(\)](#)
- [WFSDescribeFeatureType\\$clone\(\)](#)

Method [new\(\)](#): Initializes a [WFSDescribeFeatureType](#) service request

Usage:

```
WFSDescribeFeatureType$new(
  capabilities,
  op,
  url,
  version,
  typeName,
```

```

    user = NULL,
    pwd = NULL,
    token = NULL,
    headers = c(),
    config = httr::config(),
    logger = NULL,
    ...
)

```

Arguments:

capabilities an object of class [WFSCapabilities](#)
op object of class [OWSOperation](#) as retrieved from capabilities
url url
version service version
typeName typeName
user user
pwd pwd
token token
headers headers
config config
logger logger
... any parameter to pass to the service request

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
WFSDescribeFeatureType$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Note

Abstract class used by **ows4R** to trigger a WFS DescribeFeatureType request

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

WFSFeatureType

WFSFeatureType

Description

WFSFeatureType

WFSFeatureType

Format

[R6Class](#) object.

Value

Object of [R6Class](#) modelling a WFS feature type

Super class

[ows4R::OGCAbstractObject](#) -> WFSFeatureType

Public fields

description description

Methods**Public methods:**

- [WFSFeatureType\\$new\(\)](#)
- [WFSFeatureType\\$name\(\)](#)
- [WFSFeatureType\\$title\(\)](#)
- [WFSFeatureType\\$abstract\(\)](#)
- [WFSFeatureType\\$keywords\(\)](#)
- [WFSFeatureType\\$defaultCRS\(\)](#)
- [WFSFeatureType\\$boundingBox\(\)](#)
- [WFSFeatureType\\$description\(\)](#)
- [WFSFeatureType\\$hasGeometry\(\)](#)
- [WFSFeatureType\\$geometryType\(\)](#)
- [WFSFeatureType\\$featuresCRS\(\)](#)
- [WFSFeatureType\\$features\(\)](#)
- [WFSFeatureType\\$clone\(\)](#)

Method new(): Initializes an object of class [WFSFeatureType](#)

Usage:

```
WFSFeatureType$new(xmlObj, capabilities, version, logger = NULL)
```

Arguments:

xmlObj an object of class [XMLInternalNode-class](#) to initialize from XML

capabilities object of class [WFSCapabilities](#)

version service version

logger logger

Method getName(): Get feature type name

Usage:

```
WFSFeatureType$name()
```

Arguments:

object of class character

Method getTitle(): Get feature type title

Usage:

```
WFSFeatureType$title()
```

Arguments:

object of class character

Method getAbstract(): Get feature type abstract

Usage:

```
WFSFeatureType$getAbstract()
```

Arguments:

object of class character

Method getKeywords(): Get feature type keywords

Usage:

```
WFSFeatureType$keywords()
```

Arguments:

object of class character

Method getDefaultCRS(): Get feature type default CRS

Usage:

```
WFSFeatureType$getDefaultCRS()
```

Arguments:

object of class character

Method getBoundingBox(): Get feature type bounding box

Usage:

```
WFSFeatureType$getBoundingBox()
```

Arguments:

object of class matrix

Method getDescription(): Describes a feature type

Usage:

```
WFSFeatureType$getDescription(pretty = FALSE)
```

Arguments:

pretty pretty whether to return a prettified data.frame. Default is FALSE

Returns: a list of [WFSFeatureTypeElement](#) or data.frame

Method hasGeometry(): Indicates with feature type has a geometry

Usage:

```
WFSFeatureType$hasGeometry()
```

Returns: object of class [logical](#)

Method `getGeometryType()`: Get geometry type

Usage:

```
WFSFeatureType$getGeometryType()
```

Returns: object of class [character](#) representing the geometry tpe

Method `getFeaturesCRS()`: Inherits features CRS

Usage:

```
WFSFeatureType$getFeaturesCRS(obj)
```

Arguments:

obj features object

Returns: object of class [integer](#)

Method `getFeatures()`: Get features

Usage:

```
WFSFeatureType$getFeatures(
  ...,
  validate = TRUE,
  outputFormat = NULL,
  paging = FALSE,
  paging_length = 1000,
  parallel = FALSE,
  parallel_handler = NULL,
  cl = NULL
)
```

Arguments:

... any other parameter to pass to the [WFSGetFeature](#) request

validate Whether features have to be validated vs. the feature type description. Default is TRUE

outputFormat output format

paging paging. Default is FALSE

paging_length number of features to request per page. Default is 1000

parallel whether to get features using parallel multicore strategy. Default is FALSE

parallel_handler Handler function to parallelize the code. eg [mclapply](#)

cl optional cluster object for parallel cluster approaches using eg. `parallel::makeCluster`

typeName the name of the feature type

Returns: features as object of class sf

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
WFSFeatureType$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Note

Class used internally by **ows4R** to trigger a WFS DescribeFeatureType request

Author(s)

Emmanuel Blondel <emmanuel.blondell@gmail.com>

WFSFeatureTypeElement *WFSFeatureTypeElement*

Description

WFSFeatureTypeElement

WFSFeatureTypeElement

Format

[R6Class](#) object.

Value

Object of [R6Class](#) modelling a WFS feature type element

Super class

[ows4R::OGCAbstractObject](#) -> WFSFeatureTypeElement

Public fields

minOccurs minOccurs

maxOccurs maxOccurs

nillable nillable

name name

type type

geometry geometry

Methods**Public methods:**

- [WFSFeatureTypeElement\\$new\(\)](#)
- [WFSFeatureTypeElement\\$getMinOccurs\(\)](#)
- [WFSFeatureTypeElement\\$getMaxOccurs\(\)](#)
- [WFSFeatureTypeElement\\$isNillable\(\)](#)
- [WFSFeatureTypeElement\\$getName\(\)](#)
- [WFSFeatureTypeElement\\$getType\(\)](#)

- [WFSFeatureTypeElement\\$isGeometry\(\)](#)
- [WFSFeatureTypeElement\\$clone\(\)](#)

Method `new()`: Initializes a [WFSFeatureTypeElement](#)

Usage:

```
WFSFeatureTypeElement$new(xmlObj, namespaces)
```

Arguments:

xmlObj object of class [XMLInternalNode-class](#) from **XML**

namespaces namespaces definitions inherited from parent XML, as `data.frame`

Method `getMinOccurs()`: get min occurs

Usage:

```
WFSFeatureTypeElement$getMinOccurs()
```

Returns: an object of class character

Method `getMaxOccurs()`: get max occurs

Usage:

```
WFSFeatureTypeElement$getMaxOccurs()
```

Returns: an object of class character

Method `isNillable()`: get if nillable

Usage:

```
WFSFeatureTypeElement$isNillable()
```

Returns: an object of class logical

Method `getName()`: get name

Usage:

```
WFSFeatureTypeElement$getName()
```

Returns: an object of class character

Method `getType()`: get type

Usage:

```
WFSFeatureTypeElement$getType()
```

Returns: an object of class character

Method `isGeometry()`: Is geometry

Usage:

```
WFSFeatureTypeElement$isGeometry()
```

Arguments:

return object of class logical

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
WFSFeatureTypeElement$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Note

Abstract class used by **ows4R**

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

WFSGetFeature

WFSGetFeature

Description

WFSGetFeature

WFSGetFeature

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling a WFS GetFeature request

Super classes

[ows4R::OGCAbstractObject](#) -> [ows4R::OWSHttpRequest](#) -> WFSGetFeature

Methods**Public methods:**

- [WFSGetFeature\\$new\(\)](#)
- [WFSGetFeature\\$clone\(\)](#)

Method new(): Initializes a [WFSGetFeature](#) service request

Usage:

```
WFSGetFeature$new(  
  capabilities,  
  op,  
  url,  
  version,  
  typeName,  
  outputFormat = NULL,  
  user = NULL,  
  pwd = NULL,  
  token = NULL,  
  headers = c(),
```

```

    config = httr::config(),
    logger = NULL,
    ...
)

```

Arguments:

capabilities an object of class [WFSCapabilities](#)
op object of class [OWSOperation](#) as retrieved from capabilities
url url
version service version
typeName typeName
outputFormat output format
user user
pwd password
token token
headers headers
config config
logger logger
... any parameter to pass to the service request

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
WFSGetFeature$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Note

Class used internally by **ows4R** to trigger a WFS GetFeature request

Author(s)

Emmanuel Blondel <emmanuel.blondell@gmail.com>

WMSCapabilities

WMSCapabilities

Description

WMSCapabilities

WMSCapabilities

Format

[R6Class](#) object.

Value

Object of [R6Class](#) with methods for interfacing an OGC Web Map Service Get Capabilities document.

Super classes

[ows4R::OGCAbstractObject](#) -> [ows4R::OWSCapabilities](#) -> WMSCapabilities

Methods**Public methods:**

- [WMSCapabilities\\$new\(\)](#)
- [WMSCapabilities\\$getRequests\(\)](#)
- [WMSCapabilities\\$getRequestNames\(\)](#)
- [WMSCapabilities\\$getLayers\(\)](#)
- [WMSCapabilities\\$findLayerByName\(\)](#)
- [WMSCapabilities\\$clone\(\)](#)

Method [new\(\)](#): Initializes a [WMSCapabilities](#) object

Usage:

```
WMSCapabilities$new(url, version, logger = NULL, ...)
```

Arguments:

url url

version version

logger logger type NULL, "INFO" or "DEBUG"

... any other parameter to pass to [OWSGetCapabilities](#) service request

Method [getRequests\(\)](#): List the requests available. If pretty is TRUE, the output will be an object of class `data.frame`

Usage:

```
WMSCapabilities$getRequests(pretty = FALSE)
```

Arguments:

pretty pretty

Returns: a list of [OWSRequest](#) available, or a `data.frame`

Method [getRequestNames\(\)](#): List the names of requests available.

Usage:

```
WMSCapabilities$getRequestNames()
```

Returns: object of class `character`

Method [getLayers\(\)](#): List the layers available. If pretty is TRUE, the output will be an object of class `data.frame`

Usage:

```
WMSCapabilities$getLayers(pretty = FALSE)
```

Arguments:

pretty pretty

Returns: a list of [WMSLayer](#) available, or a `data.frame`

Method `findLayerByName()`: Finds a layer by name

Usage:

```
WMSCapabilities$findLayerByName(expr, exact = TRUE)
```

Arguments:

expr expr

exact exact matching? Default is TRUE

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
WMSCapabilities$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Note

Class used to read a `WMSCapabilities` document. The use of `WMSClient` is recommended instead to benefit from the full set of capabilities associated to a WMS server.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

WMSClient

WMSClient

Description

WMSClient

WMSClient

Format

[R6Class](#) object.

Value

Object of [R6Class](#) with methods for interfacing an OGC Web Map Service.

Super classes

[ows4R::OGCAbstractObject](#) -> [ows4R::OWSClient](#) -> `WMSClient`

Methods

Public methods:

- [WMSClient\\$new\(\)](#)
- [WMSClient\\$getCapabilities\(\)](#)
- [WMSClient\\$reloadCapabilities\(\)](#)
- [WMSClient\\$getLayers\(\)](#)
- [WMSClient\\$getMap\(\)](#)
- [WMSClient\\$getFeatureInfo\(\)](#)
- [WMSClient\\$getLegendGraphic\(\)](#)
- [WMSClient\\$clone\(\)](#)

Method new(): This method is used to instantiate a [WMSClient](#) with the url of the OGC service. Authentication is supported using basic auth (using user/pwd arguments), bearer token (using token argument), or custom (using headers argument). By default, the logger argument will be set to NULL (no logger). This argument accepts two possible values: INFO: to print only **ows4R** logs, DEBUG: to print more verbose logs

Usage:

```
WMSClient$new(
  url,
  serviceVersion = NULL,
  user = NULL,
  pwd = NULL,
  token = NULL,
  headers = c(),
  config = httr::config(),
  cas_url = NULL,
  logger = NULL
)
```

Arguments:

```
url url
serviceVersion WFS service version
user user
pwd password
token token
headers headers
config config
cas_url Central Authentication Service (CAS) URL
logger logger
```

Method getCapabilities(): Get WMS capabilities

Usage:

```
WMSClient$getCapabilities()
```

Returns: an object of class [WMSCapabilities](#)

Method reloadCapabilities(): Reloads WFS capabilities

Usage:

```
WMSClient$reloadCapabilities()
```

Method getLayers(): List the layers available. If pretty is TRUE, the output will be an object of class data.frame

Usage:

```
WMSClient$getLayers(pretty = FALSE)
```

Arguments:

pretty pretty

Returns: a list of [WMSLayer](#) available, or a data.frame

Method getMap(): Get map. NOT YET IMPLEMENTED

Usage:

```
WMSClient$getMap()
```

Method getFeatureInfo(): Get feature info

Usage:

```
WMSClient$getFeatureInfo(
  layer,
  srs = NULL,
  styles = NULL,
  feature_count = 1,
  x,
  y,
  width,
  height,
  bbox,
  info_format = "application/vnd.ogc.gml",
  ...
)
```

Arguments:

layer layer name

srs srs

styles styles

feature_count feature count. Default is 1

x x

y y

width width

height height

bbox bbox

info_format info format. Default is "application/vnd.ogc.gml"

... any other parameter to pass to a [WMSGetFeatureInfo](#) request

Returns: an object of class sf given the feature(s)

Method getLegendGraphic(): Get legend graphic. NOT YET IMPLEMENTED

Usage:

```
WMSClient$getLegendGraphic()
```

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
WMSClient$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondell@gmail.com>

Examples

```
## Not run:
#example based on a WMS endpoint responding at http://localhost:8080/geoserver/wms
wms <- WMSClient$new("http://localhost:8080/geoserver/wms", serviceVersion = "1.1.1")

#get capabilities
caps <- wms$getCapabilities()

#get feature info

#Advanced examples at https://github.com/eblondel/ows4R/wiki#wms

## End(Not run)
```

WMSGetFeatureInfo

WMSGetFeatureInfo

Description

WMSGetFeatureInfo

WMSGetFeatureInfo

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling a WMS GetFeatureInfo request

Super classes

[ows4R::OGCAbstractObject](#) -> [ows4R::OWSHttpRequest](#) -> WMSGetFeatureInfo

Methods**Public methods:**

- [WMSGetFeatureInfo\\$new\(\)](#)
- [WMSGetFeatureInfo\\$clone\(\)](#)

Method `new()`: Initializes a [WMSGetFeatureInfo](#) service request

Usage:

```
WMSGetFeatureInfo$new(
  capabilities,
  op,
  url,
  version,
  layers,
  srs,
  styles,
  feature_count = 1,
  x,
  y,
  width,
  height,
  bbox,
  info_format = "text/xml",
  user = NULL,
  pwd = NULL,
  token = NULL,
  headers = c(),
  config = httr::config(),
  logger = NULL,
  ...
)
```

Arguments:

`capabilities` an object of class [WMSCapabilities](#)
`op` object of class [OWSOperation](#) as retrieved from `capabilities`
`url` url
`version` version
`layers` layers
`srs` srs
`styles` styles
`feature_count` feature count
`x` x
`y` y

width width
height height
bbox bbox
info_format info format
user user
pwd pwd
token token
headers headers
config config
logger logger
... any parameter to pass to the service request

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
WMSGetFeatureInfo$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Note

Class used internally by **ows4R** to trigger a WMS GetFeatureInfo request

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

WMSLayer

WMSLayer

Description

WMSLayer

WMSLayer

Format

[R6Class](#) object.

Value

Object of [R6Class](#) modelling a WMS layer

Super class

[ows4R::OGCAbstractObject](#) -> WMSLayer

Public fields

description description
features features

Methods**Public methods:**

- [WMSLayer\\$new\(\)](#)
- [WMSLayer\\$getName\(\)](#)
- [WMSLayer\\$getTitle\(\)](#)
- [WMSLayer\\$getAbstract\(\)](#)
- [WMSLayer\\$getKeywords\(\)](#)
- [WMSLayer\\$getDefaultCRS\(\)](#)
- [WMSLayer\\$getBoundingBox\(\)](#)
- [WMSLayer\\$getBoundingBoxSRS\(\)](#)
- [WMSLayer\\$getBoundingBoxCRS\(\)](#)
- [WMSLayer\\$getStyle\(\)](#)
- [WMSLayer\\$getStyleNames\(\)](#)
- [WMSLayer\\$getDimensions\(\)](#)
- [WMSLayer\\$getTimeDimension\(\)](#)
- [WMSLayer\\$getElevationDimension\(\)](#)
- [WMSLayer\\$getFeatureInfo\(\)](#)
- [WMSLayer\\$clone\(\)](#)

Method [new\(\)](#): Initializes an object of class [WMSLayer](#)

Usage:

`WMSLayer$new(xmlObj, capabilities, version, logger = NULL)`

Arguments:

`xmlObj` an object of class [XMLInternalNode-class](#) to initialize from XML
`capabilities` object of class [WMSCapabilities](#)
`version` service version
`logger` logger

Method [getName\(\)](#): Get layer name

Usage:

`WMSLayer$getName()`

Returns: object of class character

Method [getTitle\(\)](#): Get layer title

Usage:

`WMSLayer$getTitle()`

Returns: object of class character

Method getAbstract(): Get layer abstract

Usage:

WMSLayer\$getAbstract()

Returns: object of class character

Method getKeywords(): Get layer keywords

Usage:

WMSLayer\$getKeywords()

Returns: object of class character

Method getDefaultCRS(): Get layer default CRS

Usage:

WMSLayer\$getDefaultCRS()

Returns: object of class character

Method getBoundingBox(): Get layer bounding box

Usage:

WMSLayer\$getBoundingBox()

Returns: object of class matrix

Method getBoundingBoxSRS(): Get layer bounding box SRS

Usage:

WMSLayer\$getBoundingBoxSRS()

Returns: object of class character

Method getBoundingBoxCRS(): Get layer bounding box CRS

Usage:

WMSLayer\$getBoundingBoxCRS()

Returns: object of class character

Method getStyles(): Get layer styles

Usage:

WMSLayer\$getStyles()

Returns: an object of class list

Method getStylenames(): Get layer style names

Usage:

WMSLayer\$getStylenames()

Returns: list of object of class character

Method getDimensions(): Get layer dimensions

Usage:

WMSLayer\$getDimensions(time_format = "character")

Arguments:

time_format time format. Default is character

Returns: a list including default value and listed possible values

Method getTimeDimension(): Get layer TIME dimensions

Usage:

```
WMSLayer$getTimeDimension(time_format = "character")
```

Arguments:

time_format time format. Default is character

Returns: a list including default value and listed possible values

Method getElevationDimension(): Get layer ELEVATION dimensions

Usage:

```
WMSLayer$getElevationDimension()
```

Returns: a list including default value and listed possible values

Method getFeatureInfo(): Get feature info

Usage:

```
WMSLayer$getFeatureInfo(
  srs = NULL,
  styles = NULL,
  feature_count = 1,
  x,
  y,
  width,
  height,
  bbox,
  info_format = "text/xml",
  ...
)
```

Arguments:

srs srs

styles styles

feature_count feature count. Default is 1

x x

y y

width width

height height

bbox bbox

info_format info format. Default is "text/xml"

... any other parameter to pass to a [WMSGetFeatureInfo](#) request

Returns: an object of class sf given the feature(s)

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
WMSLayer$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Note

Abstract class used by **ows4R**

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

WPSBoundingBoxData *WPSBoundingBoxData*

Description

WPSBoundingBoxData

WPSBoundingBoxData

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling an OGC WPS BoundingBox data

Super classes

[ows4R::OGCAbstractObject](#) -> [ows4R::OWSBoundingBox](#) -> WPSBoundingBoxData

Methods**Public methods:**

- [WPSBoundingBoxData\\$new\(\)](#)
- [WPSBoundingBoxData\\$clone\(\)](#)

Method `new()`: Initializes an object of class [WPSBoundingBoxData](#)

Usage:

```
WPSBoundingBoxData$new(  
  xml = NULL,  
  owsVersion,  
  serviceVersion = "1.0.0",  
  logger = NULL,  
  ...  
)
```

Arguments:

xml an object of class [XMLInternalNode-class](#) to initialize from XML
owsVersion OWS version
serviceVersion WPS service version
logger logger
... any other parameter

Method clone(): The objects of this class are cloneable with this method.

Usage:

WPSBoundingBoxData\$clone(deep = FALSE)

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

WPSCapabilities

WPSCapabilities

Description

WPSCapabilities

WPSCapabilities

Format

[R6Class](#) object.

Value

Object of [R6Class](#) with methods for interfacing an OGC Web Processing Service (WPS) Get Capabilities document.

Super classes

[ows4R::OGCAbstractObject](#) -> [ows4R::OWSCapabilities](#) -> WPSCapabilities

Methods**Public methods:**

- [WPSCapabilities\\$new\(\)](#)
- [WPSCapabilities\\$getProcesses\(\)](#)
- [WPSCapabilities\\$describeProcess\(\)](#)
- [WPSCapabilities\\$execute\(\)](#)
- [WPSCapabilities\\$clone\(\)](#)

Method `new()`: Initializes a [WPSCapabilities](#) object

Usage:

```
WPSCapabilities$new(url, version, client = NULL, logger = NULL, ...)
```

Arguments:

url url

version version

client an object of class [WPSClient](#)

logger logger type NULL, "INFO" or "DEBUG"

... any other parameter to pass to [OWSGetCapabilities](#) service request

Method `getProcesses()`: Get the list of processes offered by the service capabilities. `pretty` allows to control the type output. If `TRUE`, a `data.frame` will be returned. When prettified output, it is also possible to get a 'full' description of the process by setting `full = TRUE` in which case a the WPS client will request a process description (with more information about the process) for each process listed in the capabilities.

Usage:

```
WPSCapabilities$getProcesses(pretty = FALSE, full = FALSE)
```

Arguments:

pretty pretty

full full

Returns: a list of [WPSProcessDescription](#) or a `data.frame`

Method `describeProcess()`: Get the description of a process, given its identifier, returning an object of class `WPSProcessDescription`

Usage:

```
WPSCapabilities$describeProcess(identifier)
```

Arguments:

identifier process identifier

Returns: an object of class [WPSProcessDescription](#)

Method `execute()`: Execute a process, given its identifier

Usage:

```

WPSCapabilities$execute(
  identifier,
  dataInputs = list(),
  responseForm = NULL,
  storeExecuteResponse = FALSE,
  lineage = NULL,
  status = NULL,
  update = FALSE,
  updateInterval = 1
)

```

Arguments:

identifier process identifier

dataInputs a named list of data inputs, objects of class [WPSLiteralData](#), [WPSComplexData](#) or [WPSBoundingBoxData](#)

responseForm response form, object of class [WPSResponseDocument](#)

storeExecuteResponse store execute response? object of class logical. FALSE by default

lineage lineage, object of class logical

status status, object of class logical

update update, object of class logical. For asynchronous requests

updateInterval update interval, object of class integer. For asynchronous requests

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
WPSCapabilities$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Note

Class used to read a `WPSCapabilities` document. The use of `WPSClient` is recommended instead to benefit from the full set of capabilities associated to a WPS server.

Author(s)

Emmanuel Blondel <emmanuel.blondell@gmail.com>

WPSClient

WPSClient

Description

WPSClient

WPSClient

Format

R6Class object.

Value

Object of R6Class with methods for interfacing an OGC Web Processing Service.

Super classes

ows4R::OGCAbstractObject -> ows4R::OWSClient -> WPSClient

Methods**Public methods:**

- WPSClient\$new()
- WPSClient\$getCapabilities()
- WPSClient\$reloadCapabilities()
- WPSClient\$getProcesses()
- WPSClient\$describeProcess()
- WPSClient\$execute()
- WPSClient\$clone()

Method new(): This method is used to instantiate a WPSClient with the url of the OGC service. Authentication is supported using basic auth (using user/pwd arguments), bearer token (using token argument), or custom (using headers argument). By default, the logger argument will be set to NULL (no logger). This argument accepts two possible values: INFO: to print only **ows4R** logs, DEBUG: to print more verbose logs

Usage:

```
WPSClient$new(
  url,
  serviceVersion = NULL,
  user = NULL,
  pwd = NULL,
  token = NULL,
  headers = c(),
  config = httr::config(),
  cas_url = NULL,
  logger = NULL
)
```

Arguments:

```
url url
serviceVersion WFS service version
user user
pwd password
token token
headers headers
```

```
config config
cas_url Central Authentication Service (CAS) URL
logger logger
```

Method `getCapabilities()`: Get WPS capabilities

Usage:

```
WPSClient$getCapabilities()
```

Returns: an object of class [WPSCapabilities](#)

Method `reloadCapabilities()`: Reloads WPS capabilities

Usage:

```
WPSClient$reloadCapabilities()
```

Method `getProcesses()`: Get the list of processes offered by the service capabilities. `pretty` allows to control the type output. If `TRUE`, a `data.frame` will be returned. When prettified output, it is also possible to get a 'full' description of the process by setting `full = TRUE` in which case the WPS client will request a process description (with more information about the process) for each process listed in the capabilities.

Usage:

```
WPSClient$getProcesses(pretty = FALSE, full = FALSE)
```

Arguments:

```
pretty pretty
```

```
full full
```

Returns: a list of [WPSProcessDescription](#) or a `data.frame`

Method `describeProcess()`: Get the description of a process, given its identifier, returning an object of class `WPSProcessDescription`

Usage:

```
WPSClient$describeProcess(identifier)
```

Arguments:

```
identifier process identifier
```

Returns: an object of class [WPSProcessDescription](#)

Method `execute()`: Execute a process, given its identifier

Usage:

```
WPSClient$execute(
  identifier,
  dataInputs = list(),
  responseForm = NULL,
  storeExecuteResponse = FALSE,
  lineage = NULL,
  status = NULL,
  update = FALSE,
  updateInterval = 1
)
```

Arguments:

identifier process identifier
 dataInputs a named list of data inputs, objects of class [WPSLiteralData](#), [WPSComplexData](#)
 or [WPSBoundingBoxData](#)
 responseForm response form, object of class [WPSResponseDocument](#)
 storeExecuteResponse store execute response? object of class logical. FALSE by default
 lineage lineage, object of class logical
 status status, object of class logical
 update update, object of class logical. For asynchronous requests
 updateInterval update interval, object of class integer. For asynchronous requests

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
WPSClient$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

Examples

```
## Not run:
#example based on a WPS endpoint responding at http://localhost:8080/geoserver/wps
wps <- WPSClient$new("http://localhost:8080/geoserver/wps", serviceVersion = "1.0.0")

#get capabilities
caps <- wps$getCapabilities()

## End(Not run)
```

WPSComplexData

WPSComplexData

Description

WPSComplexData

WPSComplexData

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling a WPS Complex Data

Super class

[ows4R::OGCAbstractObject](#) -> WPSComplexData

Public fields

value value

Methods**Public methods:**

- [WPSComplexData\\$new\(\)](#)
- [WPSComplexData\\$decode\(\)](#)
- [WPSComplexData\\$checkValidity\(\)](#)
- [WPSComplexData\\$getFeatures\(\)](#)
- [WPSComplexData\\$clone\(\)](#)

Method [new\(\)](#): Initializes an object of class [WPSComplexData](#)

Usage:

```
WPSComplexData$new(  
  xml = NULL,  
  value = NULL,  
  schema = NULL,  
  mimeType = NULL,  
  serviceVersion = "1.0.0",  
  cdata = TRUE  
)
```

Arguments:

xml an object of class [XMLInternalNode-class](#) to initialize from XML

value value

schema schema

mimeType mime type

serviceVersion WPS service version

cdata whether value has to be wrapped in a XML CDATA. Default is TRUE

Method [decode\(\)](#): Decodes an object of class [WPSComplexData](#) from XML

Usage:

```
WPSComplexData$decode(xml)
```

Arguments:

xml an object of class [XMLInternalNode-class](#) to initialize from XML

Method `checkValidity()`: Check the object against a parameter description inherited from a WPS process description, object of class `WPSComplexInputDescription`. If not valid, the function will raise an error.

Usage:

`WPSComplexData$checkValidity(parameterDescription)`

Arguments:

`parameterDescription` object of class [WPSComplexInputDescription](#)

Returns: an error if not valid

Method `getFeatures()`: Get features

Usage:

`WPSComplexData$getFeatures()`

Returns: object of class `sf`

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

`WPSComplexData$clone(deep = FALSE)`

Arguments:

`deep` Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondell@gmail.com>

WPSComplexInputDescription

WPSComplexInputDescription

Description

WPSComplexInputDescription

WPSComplexInputDescription

Format

[R6Class](#) object.

Value

Object of [R6Class](#) modelling a WPS process complex input description

Super classes

[ows4R::OGCAbstractObject](#) -> [ows4R::WPSParameter](#) -> [ows4R::WPSDescriptionParameter](#)
-> [ows4R::WPSInputDescription](#) -> `WPSComplexInputDescription`

Methods**Public methods:**

- [WPSComplexInputDescription\\$new\(\)](#)
- [WPSComplexInputDescription\\$clone\(\)](#)

Method [new\(\)](#): Initializes a [WPSComplexInputDescription](#)

Usage:

```
WPSComplexInputDescription$new(xml = NULL, version, logger = NULL, ...)
```

Arguments:

xml object of class [XMLInternalNode-class](#) from **XML**

version WPS service version

logger logger

... any other parameter

Method [clone\(\)](#): The objects of this class are cloneable with this method.

Usage:

```
WPSComplexInputDescription$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Note

Class used internally by **ows4R**

Author(s)

Emmanuel Blondel <emmanuel.blondell@gmail.com>

WPSComplexOutputDescription

WPSComplexOutputDescription

Description

WPSComplexOutputDescription

WPSComplexOutputDescription

Format

[R6Class](#) object.

Value

Object of [R6Class](#) modelling a WPS process complex input description

Super classes

ows4R::OGCAbstractObject -> ows4R::WPSParameter -> ows4R::WPSDescriptionParameter
 -> ows4R::WPSOutputDescription -> WPSComplexOutputDescription

Methods**Public methods:**

- [WPSComplexOutputDescription\\$new\(\)](#)
- [WPSComplexOutputDescription\\$clone\(\)](#)

Method [new\(\)](#): Initializes a [WPSComplexOutputDescription](#)

Usage:

`WPSComplexOutputDescription$new(xml = NULL, version, logger = NULL, ...)`

Arguments:

xml object of class [XMLInternalNode-class](#) from **XML**

version WPS service version

logger logger

... any other parameter

Method [clone\(\)](#): The objects of this class are cloneable with this method.

Usage:

`WPSComplexOutputDescription$clone(deep = FALSE)`

Arguments:

deep Whether to make a deep clone.

Note

Class used internally by **ows4R**

Author(s)

Emmanuel Blondel <emmanuel.blondell@gmail.com>

WPSDescribeProcess *WPSDescribeProcess*

Description

WPSDescribeProcess

WPSDescribeProcess

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling a WPS DescribeProcess request

Super classes

[ows4R::OGCAbstractObject](#) -> [ows4R::OWSHttpRequest](#) -> WPSDescribeProcess

Methods**Public methods:**

- [WPSDescribeProcess\\$new\(\)](#)
- [WPSDescribeProcess\\$clone\(\)](#)

Method new(): Initializes a [WPSDescribeProcess](#) service request

Usage:

```
WPSDescribeProcess$new(
  capabilities,
  op,
  url,
  serviceVersion,
  identifier,
  user = NULL,
  pwd = NULL,
  token = NULL,
  headers = c(),
  config = httr::config(),
  logger = NULL,
  ...
)
```

Arguments:

capabilities object of class [WPSCapabilities](#)

op object of class [OWSOperation](#)

url url

serviceVersion WPS service version

identifier process identifier

user user

pwd password

token token

headers headers

config config

logger logger

... any other parameter to pass to the request

Method clone(): The objects of this class are cloneable with this method.

Usage:

WPSDescribeProcess\$clone(deep = FALSE)

Arguments:

deep Whether to make a deep clone.

Note

Class used internally by **ows4R** to trigger a WPS DescribeProcess request

Author(s)

Emmanuel Blondel <emmanuel.blondell@gmail.com>

WPSDescriptionParameter

WPSDescriptionParameter

Description

WPSDescriptionParameter

WPSDescriptionParameter

Format

[R6Class](#) object.

Value

Object of [R6Class](#) modelling a WPS process input description parameter

Super classes

[ows4R::OGCAbstractObject](#) -> [ows4R::WSPParameter](#) -> WPSDescriptionParameter

Methods

Public methods:

- [WPSDescriptionParameter\\$new\(\)](#)
- [WPSDescriptionParameter\\$getDataType\(\)](#)
- [WPSDescriptionParameter\\$getFormats\(\)](#)
- [WPSDescriptionParameter\\$clone\(\)](#)

Method [new\(\)](#): Initializes a [WPSDescriptionParameter](#)

Usage:

[WPSDescriptionParameter\\$new](#)(xml = NULL, version, logger = NULL, ...)

Arguments:

xml object of class [XMLInternalNode-class](#) from XML
version WPS service version
logger logger
... any other parameter

Method `getDataType()`: Get data type

Usage:

`WPSDescriptionParameter$getDataType()`

Returns: object of class character

Method `getFormats()`: get formats

Usage:

`WPSDescriptionParameter$getFormats()`

Returns: the formats

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

`WPSDescriptionParameter$clone(deep = FALSE)`

Arguments:

deep Whether to make a deep clone.

Note

Class used internally by **ows4R**

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

WPSException

WPSException

Description

WPSException

WPSException

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling a WPS Exception

Super class

[ows4R: :OGCAbstractObject](#) -> WPSEException

Public fields

value value

percentCompleted percent of completion

Methods**Public methods:**

- [WPSEException\\$new\(\)](#)
- [WPSEException\\$decode\(\)](#)
- [WPSEException\\$clone\(\)](#)

Method [new\(\)](#): Initializes a [WPSEException](#)

Usage:

```
WPSEException$new(xml = NULL, serviceVersion = "1.0.0")
```

Arguments:

xml object of class [XMLInternalNode-class](#) from **XML**
serviceVersion service version. Default "1.0.0"

Method [decode\(\)](#): Decodes an object of class [WPSEException](#) from XML

Usage:

```
WPSEException$decode(xml)
```

Arguments:

xml object of class [XMLInternalNode-class](#) from **XML**

Method [clone\(\)](#): The objects of this class are cloneable with this method.

Usage:

```
WPSEException$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

WPSExecute

WPSExecute

Description

WPSExecute

WPSExecute

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling a WPS Execute request

Super classes

[ows4R::OGCAbstractObject](#) -> [ows4R::OWSHttpRequest](#) -> WPSExecute

Public fields

Identifier process identifier

DataInputs list of [WPSInput](#)

ResponseForm response form

Methods

Public methods:

- [WPSExecute\\$new\(\)](#)
- [WPSExecute\\$getProcessDescription\(\)](#)
- [WPSExecute\\$clone\(\)](#)

Method [new\(\)](#): Initializes a [WPSExecute](#) service request

Usage:

```
WPSExecute$new(  
  capabilities,  
  op,  
  url,  
  serviceVersion,  
  identifier,  
  dataInputs = list(),  
  responseForm = NULL,  
  storeExecuteResponse = FALSE,  
  lineage = NULL,  
  status = NULL,
```

```

    user = NULL,
    pwd = NULL,
    token = NULL,
    headers = c(),
    config = httr::config(),
    logger = NULL,
    ...
)

```

Arguments:

capabilities object of class [WPSCapabilities](#)
op object of class [OWSOperation](#)
url url
serviceVersion WPS service version
identifier process identifier
dataInputs a named list of data inputs, objects of class [WPSLiteralData](#), [WPSComplexData](#)
or [WPSBoundingBoxData](#)
responseForm response form, object of class [WPSResponseDocument](#)
storeExecuteResponse store execute response? object of class logical. FALSE by default
lineage lineage, object of class logical
status status, object of class logical
user user
pwd password
token token
headers headers
config config
logger logger
... any other parameter to pass to the request

Method `getProcessDescription()`: Get process description

Usage:

```
WPSExecute$getProcessDescription()
```

Returns: an object of class [WPSProcessDescription](#)

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
WPSExecute$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Note

Class used internally by **ows4R** to trigger a WPS Execute request

Author(s)

Emmanuel Blondel <emmanuel.blondell@gmail.com>

WPSExecuteResponse *WPSExecuteResponse*

Description

WPSExecuteResponse

WPSExecuteResponse

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling a WPS Execute response

Super class

[ows4R: :OGCAbstractObject](#) -> WPSExecuteResponse

Public fields

process process

status status

statusLocation status location

statusHistory status history

processOutputs process outputs

exception exception

Methods

Public methods:

- [WPSExecuteResponse\\$new\(\)](#)
- [WPSExecuteResponse\\$getProcess\(\)](#)
- [WPSExecuteResponse\\$status\(\)](#)
- [WPSExecuteResponse\\$statusLocation\(\)](#)
- [WPSExecuteResponse\\$statusHistory\(\)](#)
- [WPSExecuteResponse\\$getProcessOutputs\(\)](#)
- [WPSExecuteResponse\\$getException\(\)](#)
- [WPSExecuteResponse\\$decode\(\)](#)
- [WPSExecuteResponse\\$update\(\)](#)
- [WPSExecuteResponse\\$clone\(\)](#)

Method [new\(\)](#): Initializes a [WPSExecuteResponse](#)

Usage:

```
WPSExecuteResponse$new(  
  xml,  
  capabilities,  
  processDescription = NULL,  
  logger = NULL  
)
```

Arguments:

xml object of class [XMLInternalNode-class](#) from [XML](#)
capabilities object of class [WPSCapabilities](#)
processDescription process description
logger logger

Method `getProcess()`: Get process

Usage:

```
WPSExecuteResponse$getProcess()
```

Returns: an object of class [WPSProcess](#)

Method `getStatus()`: Get status

Usage:

```
WPSExecuteResponse$getStatus()
```

Returns: an object of class [WPSStatus](#)

Method `getStatusLocation()`: Get status location

Usage:

```
WPSExecuteResponse$getStatusLocation()
```

Returns: an object of class character

Method `getStatusHistory()`: Get status history

Usage:

```
WPSExecuteResponse$getStatusHistory()
```

Returns: an object of class character

Method `getProcessOutputs()`: Get list of process outputs

Usage:

```
WPSExecuteResponse$getProcessOutputs()
```

Returns: a list of outputs

Method `getException()`: Get exception

Usage:

```
WPSExecuteResponse$getException()
```

Returns: an object of class [WPSException](#)

Method `decode()`: Decodes an object of class [WPSExecuteResponse](#) from XML

Usage:

WPSExecuteResponse\$decode(xml, capabilities, processDescription, logger)

Arguments:

xml object of class [XMLInternalNode-class](#) from **XML**
capabilities object of class [WPSCapabilities](#)
processDescription process description
logger logger

Method update(): Updates status history

Usage:

WPSExecuteResponse\$update(verbose = FALSE)

Arguments:

verbose verbose. Default is FALSE

Method clone(): The objects of this class are cloneable with this method.

Usage:

WPSExecuteResponse\$clone(deep = FALSE)

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

WPSFormat

WPSFormat

Description

WPSFormat

WPSFormat

Format

[R6Class](#) object.

Value

Object of [R6Class](#) modelling a WPS process input description

Super class

[ows4R::OGCAbstractObject](#) -> WPSFormat

Methods**Public methods:**

- [WPSFormat\\$new\(\)](#)
- [WPSFormat\\$getMimeType\(\)](#)
- [WPSFormat\\$getEncoding\(\)](#)
- [WPSFormat\\$getSchema\(\)](#)
- [WPSFormat\\$setIsDefault\(\)](#)
- [WPSFormat\\$isDefault\(\)](#)
- [WPSFormat\\$clone\(\)](#)

Method [new\(\)](#): Initializes an object of class [WPSFormat](#)

Usage:

```
WPSFormat$new(xml = NULL, version, logger = NULL, ...)
```

Arguments:

xml an object of class [XMLInternalNode-class](#) to initialize from XML

version WPS service version

logger logger

... any additional parameter

Method [getMimeType\(\)](#): Get mime type

Usage:

```
WPSFormat$getMimeType()
```

Returns: object of class character

Method [getEncoding\(\)](#): Get encoding

Usage:

```
WPSFormat$getEncoding()
```

Returns: object of class character

Method [getSchema\(\)](#): Get schema

Usage:

```
WPSFormat$getSchema()
```

Returns: object of class character

Method [setIsDefault\(\)](#): set is default

Usage:

```
WPSFormat$setIsDefault(default)
```

Arguments:

default object of class logical

Method [isDefault\(\)](#): is default

Usage:

WPSFormat\$isDefault()

Returns: TRUE if default, FALSE otherwise

Method clone(): The objects of this class are cloneable with this method.

Usage:

WPSFormat\$clone(deep = FALSE)

Arguments:

deep Whether to make a deep clone.

Note

Class used internally by **ows4R**

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

WPSInput

WPSInput

Description

WPSInput

WPSInput

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling a WPS Input

Super class

[ows4R::OGCAbstractObject](#) -> WPSInput

Public fields

Identifier identifier

Data data

Methods**Public methods:**

- [WPSInput\\$new\(\)](#)
- [WPSInput\\$clone\(\)](#)

Method `new()`: Initializes a [WPSInput](#)

Usage:

```
WPSInput$new(xml = NULL, identifier, data, serviceVersion = "1.0.0")
```

Arguments:

`xml` object of class [XMLInternalNode-class](#) from **XML**

`identifier` identifier

`data` data

`serviceVersion` service version. Default "1.0.0"

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
WPSInput$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

WPSInputDescription *WPSInputDescription*

Description

WPSInputDescription

WPSInputDescription

Format

[R6Class](#) object.

Value

Object of [R6Class](#) modelling a WPS process input description

Super classes

[ows4R::OGCAbstractObject](#) -> [ows4R::WPSParameter](#) -> [ows4R::WPSDescriptionParameter](#)
-> [WPSInputDescription](#)

Methods

Public methods:

- [WPSInputDescription\\$new\(\)](#)
- [WPSInputDescription\\$getMinOccurs\(\)](#)
- [WPSInputDescription\\$getMaxOccurs\(\)](#)
- [WPSInputDescription\\$asDataFrame\(\)](#)
- [WPSInputDescription\\$clone\(\)](#)

Method `new()`: Initializes a [WPSInputDescription](#)

Usage:

```
WPSInputDescription$new(xml = NULL, version, logger = NULL, ...)
```

Arguments:

`xml` object of class [XMLInternalNode-class](#) from [XML](#)

`version` WPS service version

`logger` logger

... any other parameter

Method `getMinOccurs()`: Get min occurs

Usage:

```
WPSInputDescription$getMinOccurs()
```

Returns: the min occurs

Method `getMaxOccurs()`: Get max occurs

Usage:

```
WPSInputDescription$getMaxOccurs()
```

Returns: the max occurs

Method `asDataFrame()`: Get input description as data.frame

Usage:

```
WPSInputDescription$asDataFrame()
```

Returns: object of class character

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
WPSInputDescription$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Note

Class used internally by **ows4R**

Author(s)

Emmanuel Blondel <emmanuel.blondell@gmail.com>

WPSLiteralData

WPSLiteralData

Description

WPSLiteralData

WPSLiteralData

Format

R6Class object.

ValueObject of [R6Class](#) for modelling a WPS Literal Data**Super class**[ows4R::OGCAbstractObject](#) -> WPSLiteralData**Public fields**

value value

Methods**Public methods:**

- [WPSLiteralData\\$new\(\)](#)
- [WPSLiteralData\\$decode\(\)](#)
- [WPSLiteralData\\$checkValidity\(\)](#)
- [WPSLiteralData\\$clone\(\)](#)

Method [new\(\)](#): Initializes an object of class [WPSLiteralData](#)*Usage:*

WPSLiteralData\$new(xml = NULL, value = NULL, serviceVersion = "1.0.0")

*Arguments:*xml an object of class [XMLInternalNode-class](#) to initialize from XML

value value

serviceVersion WPS service version

Method [decode\(\)](#): Decodes an object of class [WPSLiteralData](#) from XML*Usage:*

WPSLiteralData\$decode(xml)

*Arguments:*xml an object of class [XMLInternalNode-class](#) to initialize from XML

Method checkValidity(): Check the object against a parameter description inherited from a WPS process description, object of class WPSLiteralInputDescription. If not valid, the function will raise an error.

Usage:

```
WPSLiteralData$checkValidity(parameterDescription)
```

Arguments:

parameterDescription object of class [WPSLiteralInputDescription](#)

Returns: an error if not valid

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
WPSLiteralData$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondell@gmail.com>

WPSLiteralInputDescription

WPSLiteralInputDescription

Description

WPSLiteralInputDescription

WPSLiteralInputDescription

Format

[R6Class](#) object.

Value

Object of [R6Class](#) modelling a WPS process input description

Super classes

```
ows4R::OGCAbstractObject -> ows4R::WPSParameter -> ows4R::WPSDescriptionParameter  
-> ows4R::WPSInputDescription -> WPSLiteralInputDescription
```

Methods**Public methods:**

- [WPSLiteralInputDescription\\$new\(\)](#)
- [WPSLiteralInputDescription\\$getDataType\(\)](#)
- [WPSLiteralInputDescription\\$getDefaultValue\(\)](#)
- [WPSLiteralInputDescription\\$getAllowedValues\(\)](#)
- [WPSLiteralInputDescription\\$clone\(\)](#)

Method `new()`: Initializes a [WPSLiteralInputDescription](#)

Usage:

```
WPSLiteralInputDescription$new(xml = NULL, version, logger = NULL, ...)
```

Arguments:

`xml` object of class [XMLInternalNode-class](#) from [XML](#)

`version` WPS service version

`logger` logger

... any other parameter

Method `getDataType()`: Get data type

Usage:

```
WPSLiteralInputDescription$getDataType()
```

Returns: the data type, object of class character

Method `getDefaultValue()`: Get default value

Usage:

```
WPSLiteralInputDescription$getDefaultValue()
```

Returns: the default value, object of class character

Method `getAllowedValues()`: Get allowed values

Usage:

```
WPSLiteralInputDescription$getAllowedValues()
```

Returns: the allowed values

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
WPSLiteralInputDescription$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Note

Class used internally by **ows4R**

Author(s)

Emmanuel Blondel <emmanuel.blondell@gmail.com>

WPSLiteralOutputDescription
WPSLiteralOutputDescription

Description

WPSLiteralOutputDescription

WPSLiteralOutputDescription

Format

[R6Class](#) object.

Value

Object of [R6Class](#) modelling a WPS process literal output description

Super classes

[ows4R::OGCAbstractObject](#) -> [ows4R::WSPParameter](#) -> [ows4R::WPSDescriptionParameter](#)
-> [ows4R::WPSOutputDescription](#) -> [WPSLiteralOutputDescription](#)

Methods**Public methods:**

- [WPSLiteralOutputDescription\\$new\(\)](#)
- [WPSLiteralOutputDescription\\$clone\(\)](#)

Method [new\(\)](#): Initializes a [WPSLiteralOutputDescription](#)

Usage:

```
WPSLiteralOutputDescription$new(xml = NULL, version, logger = NULL, ...)
```

Arguments:

xml object of class [XMLInternalNode-class](#) from [XML](#)

version WPS service version

logger logger

... any other parameter

Method [clone\(\)](#): The objects of this class are cloneable with this method.

Usage:

```
WPSLiteralOutputDescription$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Note

Class used internally by **ows4R**

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

WPSOutput

WPSOutput

Description

WPSOutput

WPSOutput

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling a WPS Input

Super class

[ows4R::OGCAbstractObject](#) -> WPSOutput

Public fields

Identifier identifier

Title tile

Data data

Methods**Public methods:**

- [WPSOutput\\$new\(\)](#)
- [WPSOutput\\$decode\(\)](#)
- [WPSOutput\\$getData\(\)](#)
- [WPSOutput\\$getDataValue\(\)](#)
- [WPSOutput\\$clone\(\)](#)

Method [new\(\)](#): Initializes a [WPSOutput](#)

Usage:

```
WPSOutput$new(  
  xml = NULL,  
  identifier = NULL,  
  title = NULL,  
  data = NULL,  
  dataType = NULL,  
  serviceVersion = "1.0.0"  
)
```

Arguments:

xml object of class [XMLInternalNode-class](#) from **XML**
identifier identifier
title title
data data
dataType data type
serviceVersion WPS service version

Method decode(): Decodes an object of class [WPSOutput](#) from **XML**

Usage:

```
WPSOutput$decode(xml)
```

Arguments:

xml object of class [XMLInternalNode-class](#) from **XML**

Method getData(): Get data

Usage:

```
WPSOutput$getData()
```

Returns: data

Method getDataValue(): Get data value

Usage:

```
WPSOutput$getDataValue()
```

Returns: data value

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
WPSOutput$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondell@gmail.com>

WPSOutputDescription *WPSOutputDescription*

Description

WPSOutputDescription

WPSOutputDescription

Format

[R6Class](#) object.

Value

Object of [R6Class](#) modelling a WPS process input description

Super classes

[ows4R::OGCAbstractObject](#) -> [ows4R::WPSParameter](#) -> [ows4R::WPSDescriptionParameter](#)
-> [WPSOutputDescription](#)

Methods**Public methods:**

- [WPSOutputDescription\\$new\(\)](#)
- [WPSOutputDescription\\$clone\(\)](#)

Method [new\(\)](#): Initializes a [WPSOutputDescription](#)

Usage:

[WPSOutputDescription\\$new](#)(xml = NULL, version, logger = NULL, ...)

Arguments:

xml object of class [XMLInternalNode-class](#) from [XML](#)

version WPS service version

logger logger

... any other parameter

Method [clone\(\)](#): The objects of this class are cloneable with this method.

Usage:

[WPSOutputDescription\\$clone](#)(deep = FALSE)

Arguments:

deep Whether to make a deep clone.

Note

Class used internally by [ows4R](#)

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

WPSParameter

WPSParameter

Description

WPSParameter

WPSParameter

Format

[R6Class](#) object.

Value

Object of [R6Class](#) modelling a WPS parameter

Super class

[ows4R::OGCAbstractObject](#) -> WPSParameter

Methods**Public methods:**

- [WPSParameter\\$new\(\)](#)
- [WPSParameter\\$getIdentifier\(\)](#)
- [WPSParameter\\$getTitle\(\)](#)
- [WPSParameter\\$getAbstract\(\)](#)
- [WPSParameter\\$clone\(\)](#)

Method [new\(\)](#): Initializes an object of class [WPSParameter](#)

Usage:

```
WPSParameter$new(xml = NULL, version, logger = NULL, ...)
```

Arguments:

xml an object of class [XMLInternalNode-class](#) to initialize from XML

version WPS service version

logger logger

... any additional parameter

Method [getIdentifier\(\)](#): Get identifier

Usage:

```
WPSParameter$getIdentifier()
```

Returns: object of class character

Method getTitle(): Get title

Usage:

WSPParameter\$title()

Returns: object of class character

Method getAbstract(): Get abstract

Usage:

WSPParameter\$getAbstract()

Returns: object of class character

Method clone(): The objects of this class are cloneable with this method.

Usage:

WSPParameter\$clone(deep = FALSE)

Arguments:

deep Whether to make a deep clone.

Note

Abstract class used internally by **ows4R**

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

WPSProcess

WPSProcess

Description

WPSProcess

WPSProcess

Format

[R6Class](#) object.

Value

Object of [R6Class](#) modelling a WPS process

Super class

[ows4R::OGCAbstractObject](#) -> WPSProcess

Methods**Public methods:**

- [WSPProcess\\$new\(\)](#)
- [WSPProcess\\$getIdentifier\(\)](#)
- [WSPProcess\\$getTitle\(\)](#)
- [WSPProcess\\$getVersion\(\)](#)
- [WSPProcess\\$getDescription\(\)](#)
- [WSPProcess\\$execute\(\)](#)
- [WSPProcess\\$clone\(\)](#)

Method [new\(\)](#): Initializes a [WSPProcess](#)

Usage:

`WSPProcess$new(xml, capabilities = NULL, version, logger = NULL, ...)`

Arguments:

`xml` object of class [XMLInternalNode-class](#) from [XML](#)

`capabilities` object of class [WSPCapabilities](#)

`version` service version

`logger` logger

`...` any additional parameter

Method [getIdentifier\(\)](#): Get identifier

Usage:

`WSPProcess$getIdentifier()`

Returns: object of class character

Method [getTitle\(\)](#): Get title

Usage:

`WSPProcess$getTitle()`

Returns: object of class character

Method [getVersion\(\)](#): Get version

Usage:

`WSPProcess$getVersion()`

Returns: object of class character

Method [getDescription\(\)](#): Get description

Usage:

`WSPProcess$getDescription()`

Returns: object of class [WSPProcessDescription](#)

Method [execute\(\)](#): Execute process

Usage:

```

WPSProcess$execute(
  dataInputs = list(),
  responseForm = NULL,
  storeExecuteResponse = FALSE,
  lineage = NULL,
  status = NULL,
  update = FALSE,
  updateInterval = 1
)

```

Arguments:

`dataInputs` a named list of data inputs, objects of class [WPSLiteralData](#), [WPSComplexData](#) or [WPSBoundingBoxData](#)

`responseForm` response form, object of class [WPSResponseDocument](#)

`storeExecuteResponse` store execute response? object of class logical. FALSE by default

`lineage` lineage, object of class logical

`status` status, object of class logical

`update` update, object of class logical. For asynchronous requests

`updateInterval` update interval, object of class integer. For asynchronous requests

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
WPSProcess$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Note

Class used internally by **ows4R**

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

WPSProcessDescription *WPSProcessDescription*

Description

WPSProcessDescription

WPSProcessDescription

Format

[R6Class](#) object.

Value

Object of [R6Class](#) modelling a WPS process description

Super class

[ows4R::OGCAbstractObject](#) -> WPSProcessDescription

Methods**Public methods:**

- [WPSProcessDescription\\$new\(\)](#)
- [WPSProcessDescription\\$getIdentifier\(\)](#)
- [WPSProcessDescription\\$getTitle\(\)](#)
- [WPSProcessDescription\\$getAbstract\(\)](#)
- [WPSProcessDescription\\$getVersion\(\)](#)
- [WPSProcessDescription\\$isStatusSupported\(\)](#)
- [WPSProcessDescription\\$isStoreSupported\(\)](#)
- [WPSProcessDescription\\$getDataInputs\(\)](#)
- [WPSProcessDescription\\$getProcessOutputs\(\)](#)
- [WPSProcessDescription\\$asDataFrame\(\)](#)
- [WPSProcessDescription\\$clone\(\)](#)

Method [new\(\)](#): Initializes an object of class [WPSProcessDescription](#)

Usage:

```
WPSProcessDescription$new(xml, version, logger = NULL, ...)
```

Arguments:

xml object of class [XMLInternalNode-class](#) from [XML](#)

version version

logger logger

... any other parameter

Method [getIdentifier\(\)](#): Get process identifier

Usage:

```
WPSProcessDescription$getIdentifier()
```

Returns: the identifier, object of class character

Method [getTitle\(\)](#): Get process title

Usage:

```
WPSProcessDescription$getTitle()
```

Returns: the title, object of class character

Method [getAbstract\(\)](#): Get process abstract

Usage:

```
WPSProcessDescription$getAbstract()
```

Returns: the abstract, object of class character

Method getVersion(): Get process version

Usage:

WSPProcessDescription\$getVersion()

Arguments:

the version, object of class character

Method isStatusSupported(): Indicates if the status is supported

Usage:

WSPProcessDescription\$isStatusSupported()

Returns: TRUE if supported, FALSE otherwise

Method isStoreSupported(): Indicates if the store is supported

Usage:

WSPProcessDescription\$isStoreSupported()

Returns: TRUE if supported, FALSE otherwise

Method getDataInputs(): Get data inputs

Usage:

WSPProcessDescription\$getDataInputs()

Returns: a list of objects extending [WPSInputDescription](#)

Method getProcessOutputs(): Get process outputs

Usage:

WSPProcessDescription\$getProcessOutputs()

Returns: a list of objects extending [WPSOutputDescription](#)

Method asDataFrame(): Convenience method to export a process description as data.frame

Usage:

WSPProcessDescription\$asDataFrame()

Returns: a data.frame giving the process description

Method clone(): The objects of this class are cloneable with this method.

Usage:

WSPProcessDescription\$clone(deep = FALSE)

Arguments:

deep Whether to make a deep clone.

Note

Class used internally by **ows4R**

Author(s)

Emmanuel Blondel <emmanuel.blondell@gmail.com>

WPSResponseDocument *WPSResponseDocument*

Description

WPSResponseDocument

WPSResponseDocument

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling an OGC WPS response document

Super class

[ows4R: :OGCAbstractObject](#) -> WPSResponseDocument

Public fields

Output output property

Methods

Public methods:

- [WPSResponseDocument\\$new\(\)](#)
- [WPSResponseDocument\\$clone\(\)](#)

Method [new\(\)](#): Initializes a [WPSResponseDocument](#)

Usage:

```
WPSResponseDocument$new(  
  xml = NULL,  
  storeExecuteResponse = FALSE,  
  lineage = NULL,  
  status = NULL,  
  output = NULL,  
  serviceVersion = "1.0.0"  
)
```

Arguments:

xml object of class [XMLInternalNode-class](#) from **XML**
storeExecuteResponse store execute response, object of class logical
lineage lineage, object of class logical
status status, object of class logical

output output
 serviceVersion WPS service version

Method clone(): The objects of this class are cloneable with this method.

Usage:

WPSResponseDocument\$clone(deep = FALSE)

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

WPSStatus

WPSStatus

Description

WPSStatus

WPSStatus

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling a WPS Status

Super class

[ows4R::OGCAbstractObject](#) -> WPSStatus

Public fields

value status value

percentCompleted status percentage of completion

Methods

Public methods:

- [WPSStatus\\$new\(\)](#)
- [WPSStatus\\$decode\(\)](#)
- [WPSStatus\\$getValue\(\)](#)
- [WPSStatus\\$getPercentCompleted\(\)](#)
- [WPSStatus\\$getCreationTime\(\)](#)

- [WPSStatus\\$clone\(\)](#)

Method new(): Initializes a [WPSStatus](#) object

Usage:

```
WPSStatus$new(xml = NULL, serviceVersion = "1.0.0")
```

Arguments:

xml an object of class [XMLInternalNode-class](#) from **XML**
serviceVersion WPS service version. Default is "1.0.0"

Method decode(): Decodes WPS status from XML

Usage:

```
WPSStatus$decode(xml)
```

Arguments:

xml an object of class [XMLInternalNode-class](#) from **XML**

Method getValue(): Get status value, among accepted WPS status values defined in the WPS standard: ProcessAccepted, ProcessStarted, ProcessPaused, ProcessSucceeded, ProcessFailed.

Usage:

```
WPSStatus$getValue()
```

Returns: value, object of class character

Method getPercentCompleted(): Get percentage of completion

Usage:

```
WPSStatus$getPercentCompleted()
```

Returns: the percentage of completion, object of class integer

Method getCreationTime(): Get creation time

Usage:

```
WPSStatus$getCreationTime()
```

Returns: the creation time, object of class POSIXct

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
WPSStatus$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

Index

- * **Abstract**
 - OGCAbstractObject, 33
- * **And**
 - And, 4
- * **Authentication**
 - CASClient, 9
- * **BBOX**
 - BBOX, 5
- * **BinaryComparisonOpType**
 - BinaryComparisonOpType, 6
 - PropertyIsEqualTo, 68
 - PropertyIsGreaterThan, 69
 - PropertyIsGreaterThanOrEqualTo, 70
 - PropertyIsLessThan, 71
 - PropertyIsLessThanOrEqualTo, 72
 - PropertyIsNotEqualTo, 75
- * **BinaryLogicOpType**
 - And, 4
 - BinaryLogicOpType, 8
 - Or, 39
- * **Bounding**
 - WPSBoundingBoxData, 128
- * **Box**
 - WPSBoundingBoxData, 128
- * **CAS**
 - CASClient, 9
- * **CSW**
 - CSWCapabilities, 10
 - CSWClient, 12
 - CSWDescribeRecord, 19
 - CSWGetRecordById, 20
 - CSWGetRecords, 22
 - CSWHarvest, 24
 - CSWRecordProperty, 28
 - CSWTransaction, 29
- * **Capabilities**
 - CSWCapabilities, 10
 - WPSCapabilities, 129
- * **Central**
 - CASClient, 9
- * **CodeType**
 - OWSCodeType, 49
- * **Common**
 - OWSClient, 46
- * **ComplexData**
 - WPSComplexData, 134
- * **Coverage**
 - WCSCClient, 81
 - WSCCoverage, 84
 - WSCCoverageDescription, 86
 - WSCCoverageDomain, 88
 - WSCCoverageSpatialDomain, 90
 - WSCCoverageSummary, 92
 - WSCCoverageTemporalDomain, 96
 - WCSGridCRS, 101
- * **DescribeCoverage**
 - WCSDescribeCoverage, 97
- * **DescribeFeatureType**
 - WFSDescribeFeatureType, 109
- * **DescribeProcess**
 - WPSDescribeProcess, 138
- * **DescribeRecord**
 - CSWDescribeRecord, 19
- * **Exception**
 - WPSException, 141
- * **ExecuteResponse**
 - WPSExecuteResponse, 145
- * **Execute**
 - WPSExecute, 143
- * **Expression**
 - And, 4
 - BBOX, 5
 - BinaryComparisonOpType, 6
 - BinaryLogicOpType, 8
 - Not, 32
 - OGCExpression, 36
 - Or, 39
 - PropertyIsBetween, 67

- PropertyIsEqualTo, 68
- PropertyIsGreaterThan, 69
- PropertyIsGreaterThanOrEqualTo, 70
- PropertyIsLessThan, 71
- PropertyIsLessThanOrEqualTo, 72
- PropertyIsLike, 74
- PropertyIsNotEqualTo, 75
- PropertyIsNull, 76
- UnaryLogicOpType, 78
- * **FeatureType**
 - WFSFeatureType, 110
 - WFSFeatureTypeElement, 114
- * **Feature**
 - WFSCient, 106
- * **Filter**
 - CSWConstraint, 17
 - OGCFilter, 38
- * **GeoServer**
 - WCSGSElevationDomain, 102
 - WCSGSTimeDomain, 103
- * **GetCapabilities**
 - OWSCapabilities, 43
 - OWSGetCapabilities, 51
 - WCSCapabilities, 80
 - WFSCapabilities, 105
 - WMSCapabilities, 117
- * **GetCoverage**
 - WCSGetCoverage, 99
- * **GetFeatureInfo**
 - WMSClient, 119
 - WMSGetFeatureInfo, 122
- * **GetFeature**
 - WFSGetFeature, 116
- * **GetRecordById**
 - CSWGetRecordById, 20
- * **GetRecords**
 - CSWGetRecords, 22
- * **HTTP**
 - OWSHttpRequest, 53
- * **Harvest**
 - CSWHarvest, 24
- * **Identification**
 - OWSServiceIdentification, 61
- * **Input**
 - WPSInput, 149
 - WPSOutput, 156
- * **Layer**
 - WMSLayer, 124
- * **LiteralData**
 - WPSLiteralData, 152
- * **Map**
 - WMSClient, 119
- * **Not**
 - Not, 32
- * **OGC**
 - And, 4
 - BBOX, 5
 - BinaryComparisonOpType, 6
 - BinaryLogicOpType, 8
 - CSWCapabilities, 10
 - CSWClient, 12
 - CSWConstraint, 17
 - CSWDescribeRecord, 19
 - CSWGetRecordById, 20
 - CSWGetRecords, 22
 - CSWHarvest, 24
 - CSWQuery, 25
 - CSWTransaction, 29
 - Not, 32
 - OGCAbstractObject, 33
 - OGCExpression, 36
 - OGCFilter, 38
 - Or, 39
 - OWSBoundingBox, 41
 - OWSCapabilities, 43
 - OWSClient, 46
 - OWSException, 50
 - OWSGetCapabilities, 51
 - OWSHttpRequest, 53
 - OWSOperation, 57
 - OWSOperationsMetadata, 59
 - OWSRequest, 60
 - OWSServiceIdentification, 61
 - OWSServiceProvider, 63
 - OWSUtils, 65
 - OWSWG84BoundingBox, 66
 - PropertyIsBetween, 67
 - PropertyIsEqualTo, 68
 - PropertyIsGreaterThan, 69
 - PropertyIsGreaterThanOrEqualTo, 70
 - PropertyIsLessThan, 71
 - PropertyIsLessThanOrEqualTo, 72
 - PropertyIsLike, 74
 - PropertyIsNotEqualTo, 75
 - PropertyIsNull, 76
 - UnaryLogicOpType, 78

- WCSCapabilities, 80
- WCSClient, 81
- WCSCoverage, 84
- WCSCoverageDescription, 86
- WCSCoverageDomain, 88
- WCSCoverageSpatialDomain, 90
- WCSCoverageSummary, 92
- WCSCoverageTemporalDomain, 96
- WCSDescribeCoverage, 97
- WCSGetCoverage, 99
- WCSGridCRS, 101
- WFSCapabilities, 105
- WFSClient, 106
- WFSDescribeFeatureType, 109
- WFSFeatureType, 110
- WFSFeatureTypeElement, 114
- WFSGetFeature, 116
- WMSCapabilities, 117
- WMSClient, 119
- WMSGetFeatureInfo, 122
- WMSLayer, 124
- WPSBoundingBoxData, 128
- WPSCapabilities, 129
- WPSClient, 131
- WPSComplexData, 134
- WPSComplexInputDescription, 136
- WPSComplexOutputDescription, 137
- WPSDescribeProcess, 138
- WPSDescriptionParameter, 140
- WPSException, 141
- WPSExecute, 143
- WPSExecuteResponse, 145
- WPSFormat, 147
- WPSInput, 149
- WPSInputDescription, 150
- WPSLiteralData, 152
- WPSLiteralInputDescription, 153
- WPSLiteralOutputDescription, 155
- WPSOutput, 156
- WPSOutputDescription, 158
- WPSParameter, 159
- WPSProcess, 160
- WPSProcessDescription, 162
- WPSResponseDocument, 165
- WPSStatus, 166
- * **OWS**
 - OWSBoundingBox, 41
 - OWSCapabilities, 43
 - OWSClient, 46
 - OWSCodeType, 49
 - OWSHttpRequest, 53
 - OWSNamespace, 56
 - OWSOperation, 57
 - OWSOperationsMetadata, 59
 - OWSServiceIdentification, 61
 - OWSServiceProvider, 63
 - OWSUtils, 65
 - OWSWG84BoundingBox, 66
- * **Object**
 - OGCAbstractObject, 33
- * **Or**
 - Or, 39
- * **Parameter**
 - WPSParameter, 159
- * **ProcessDescription**
 - WPSProcessDescription, 162
- * **Processing**
 - WPSClient, 131
- * **Process**
 - WPSClient, 131
 - WPSComplexInputDescription, 136
 - WPSComplexOutputDescription, 137
 - WPSDescriptionParameter, 140
 - WPSFormat, 147
 - WPSInputDescription, 150
 - WPSLiteralInputDescription, 153
 - WPSLiteralOutputDescription, 155
 - WPSOutputDescription, 158
 - WPSProcess, 160
 - WPSProcessDescription, 162
- * **PropertyIsBetween**
 - PropertyIsBetween, 67
- * **PropertyIsEqualTo**
 - PropertyIsEqualTo, 68
- * **PropertyIsGreaterThanOrEqualTo**
 - PropertyIsGreaterThanOrEqualTo, 70
- * **PropertyIsGreaterThan**
 - PropertyIsGreaterThan, 69
- * **PropertyIsLessThan**
 - PropertyIsLessThan, 71
- * **PropertyIsLesserThanOrEqualTo**
 - PropertyIsLessThanOrEqualTo, 72
- * **PropertyIsLike**
 - PropertyIsLike, 74
- * **PropertyIsNotEqualTo**
 - PropertyIsNotEqualTo, 75

- * **PropertyIsNull**
 - PropertyIsNull, 76
- * **Provider**
 - OWSServiceProvider, 63
- * **Query**
 - CSWQuery, 25
- * **RecordProperty**
 - CSWRecordProperty, 28
- * **Request**
 - OWSHttpRequest, 53
 - OWSRequest, 60
- * **ResponseDocument**
 - WPSResponseDocument, 165
- * **Service**
 - CASClient, 9
 - OWSRequest, 60
 - OWSServiceIdentification, 61
 - OWSServiceProvider, 63
- * **Status**
 - WPSStatus, 166
- * **Transaction**
 - CSWTransaction, 29
- * **UnaryLogicOpType**
 - Not, 32
 - UnaryLogicOpType, 78
- * **Utils**
 - OWSUtils, 65
- * **WCS**
 - WCSCapabilities, 80
 - WCSClient, 81
 - WCSCoverage, 84
 - WCSCoverageDescription, 86
 - WCSCoverageDomain, 88
 - WCSCoverageSpatialDomain, 90
 - WCSCoverageSummary, 92
 - WCSCoverageTemporalDomain, 96
 - WCSDescribeCoverage, 97
 - WCSGetCoverage, 99
 - WCSGridCRS, 101
 - WCSGSElevationDomain, 102
 - WCSGSTimeDomain, 103
- * **WFS**
 - WFSCapabilities, 105
 - WFSClient, 106
 - WFSDescribeFeatureType, 109
 - WFSFeatureType, 110
 - WFSFeatureTypeElement, 114
 - WFSGetFeature, 116
- * **WMS**
 - WMSCapabilities, 117
 - WMSClient, 119
 - WMSGetFeatureInfo, 122
 - WMSLayer, 124
- * **WPS**
 - WPSBoundingBoxData, 128
 - WPSCapabilities, 129
 - WPSClient, 131
 - WPSComplexData, 134
 - WPSComplexInputDescription, 136
 - WPSComplexOutputDescription, 137
 - WPSDescribeProcess, 138
 - WPSDescriptionParameter, 140
 - WPSException, 141
 - WPSExecute, 143
 - WPSExecuteResponse, 145
 - WPSFormat, 147
 - WPSInput, 149
 - WPSInputDescription, 150
 - WPSLiteralData, 152
 - WPSLiteralInputDescription, 153
 - WPSLiteralOutputDescription, 155
 - WPSOutput, 156
 - WPSOutputDescription, 158
 - WPSParameter, 159
 - WPSProcess, 160
 - WPSProcessDescription, 162
 - WPSResponseDocument, 165
 - WPSStatus, 166
- * **boundingbox**
 - OWSBoundingBox, 41
 - OWSWG84BoundingBox, 66
- * **catalogue**
 - CSWClient, 12
- * **complex**
 - WPSComplexInputDescription, 136
 - WPSComplexOutputDescription, 137
- * **crs**
 - WCSGridCRS, 101
- * **data**
 - WPSBoundingBoxData, 128
- * **description**
 - WPSComplexInputDescription, 136
 - WPSComplexOutputDescription, 137
 - WPSDescriptionParameter, 140
 - WPSFormat, 147
 - WPSInputDescription, 150

- WPSLiteralInputDescription, [153](#)
- WPSLiteralOutputDescription, [155](#)
- WPSOutputDescription, [158](#)
- * **domain**
 - WCSCoverageDomain, [88](#)
 - WCSCoverageSpatialDomain, [90](#)
 - WCSCoverageTemporalDomain, [96](#)
 - WCSGSElevationDomain, [102](#)
 - WCSGSTimeDomain, [103](#)
- * **elevation**
 - WCSGSElevationDomain, [102](#)
- * **exception**
 - OWSException, [50](#)
- * **grid**
 - WCSGridCRS, [101](#)
- * **input**
 - WPSComplexInputDescription, [136](#)
 - WPSDescriptionParameter, [140](#)
 - WPSFormat, [147](#)
 - WPSInputDescription, [150](#)
 - WPSLiteralInputDescription, [153](#)
- * **literal**
 - WPSLiteralOutputDescription, [155](#)
- * **metadata**
 - OWSOperationsMetadata, [59](#)
- * **namespace**
 - OWSNamespace, [56](#)
- * **operation**
 - OWSOperation, [57](#)
 - OWSOperationsMetadata, [59](#)
- * **output**
 - WPSComplexOutputDescription, [137](#)
 - WPSLiteralOutputDescription, [155](#)
 - WPSOutputDescription, [158](#)
- * **parameter**
 - WPSDescriptionParameter, [140](#)
- * **service**
 - CSWClient, [12](#)
- * **spatial**
 - WCSCoverageSpatialDomain, [90](#)
- * **temporal**
 - WCSCoverageTemporalDomain, [96](#)
- * **time**
 - WCSGSTimeDomain, [103](#)
- * **web**
 - CSWClient, [12](#)
- * **wgs84**
 - OWSWGSS84BoundingBox, [66](#)
- And, [4, 4](#)
- BBOX, [5, 6](#)
- BinaryComparisonOpType, [6, 7](#)
- BinaryLogicOpType, [8, 8](#)
- CASClient, [9, 9](#)
- character, [113](#)
- CSWCapabilities, [10, 11, 13, 19, 21, 23, 25, 30](#)
- CSWClient, [11, 12](#)
- CSWConstraint, [15, 17, 18, 26](#)
- CSWDescribeRecord, [13, 19, 19](#)
- CSWGetRecordById, [14, 20, 21, 22](#)
- CSWGetRecords, [14, 22](#)
- CSWHarvest, [24, 24](#)
- CSWQuery, [14, 16, 23, 25](#)
- CSWRecordProperty, [15, 28, 28](#)
- CSWTransaction, [15, 29, 30](#)
- geometa::geometaLogger, [86, 103, 104](#)
- geometa::GMLAbstractCoverage, [86](#)
- geometa::GMLAbstractFeature, [86](#)
- geometa::GMLAbstractObject, [86](#)
- geometa::GMLCOVAbstractCoverage, [86](#)
- geometa::ISOAbstractObject, [86, 103, 104](#)
- getOWSNamespace, [31](#)
- getOWSNamespace, [31](#)
- getOWSNamespace, [31](#)
- GMLEnvelope, [5, 91](#)
- GMLEnvelopeWithTimePeriod, [91](#)
- GMLGrid, [91](#)
- GMLRectifiedGrid, [91](#)
- GMLTimePeriod, [97](#)
- integer, [113](#)
- ISOResponsibleParty, [64](#)
- logical, [113](#)
- mclapply, [113](#)
- Not, [32, 32](#)
- OGCAbstractObject, [33, 34](#)
- OGCExpression, [4, 8, 32, 36, 37, 38, 40, 79](#)
- OGCFilter, [18, 38, 38](#)
- Or, [39, 40](#)
- ows4R, [40](#)
- ows4R-package (ows4R), [40](#)

- ows4R::BinaryComparisonOpType, [68–70](#), [72](#), [73](#), [75](#)
- ows4R::BinaryLogicOpType, [4](#), [39](#)
- ows4R::OGCAbstractObject, [4](#), [5](#), [7](#), [8](#), [11](#), [12](#), [17](#), [19](#), [20](#), [22](#), [24](#), [26](#), [28](#), [29](#), [32](#), [37–39](#), [41](#), [43](#), [46](#), [49–51](#), [53](#), [60](#), [66–70](#), [72–75](#), [77](#), [78](#), [80](#), [81](#), [84](#), [88](#), [91](#), [92](#), [96](#), [97](#), [99](#), [101](#), [105](#), [106](#), [109](#), [111](#), [114](#), [116](#), [118](#), [119](#), [123](#), [124](#), [128](#), [129](#), [132](#), [135](#), [136](#), [138–140](#), [142](#), [143](#), [145](#), [147](#), [149](#), [150](#), [152](#), [153](#), [155](#), [156](#), [158–160](#), [163](#), [165](#), [166](#)
- ows4R::OGCExpression, [4](#), [5](#), [7](#), [8](#), [32](#), [39](#), [67–70](#), [72–75](#), [77](#), [78](#)
- ows4R::OWSBoundingBox, [66](#), [128](#)
- ows4R::OWSCapabilities, [11](#), [80](#), [105](#), [118](#), [129](#)
- ows4R::OWSClient, [12](#), [81](#), [106](#), [119](#), [132](#)
- ows4R::OWSHttpRequest, [19](#), [20](#), [22](#), [24](#), [29](#), [51](#), [97](#), [99](#), [109](#), [116](#), [123](#), [139](#), [143](#)
- ows4R::UnaryLogicOpType, [32](#)
- ows4R::WPSDescriptionParameter, [136](#), [138](#), [150](#), [153](#), [155](#), [158](#)
- ows4R::WPSInputDescription, [136](#), [153](#)
- ows4R::WPSOutputDescription, [138](#), [155](#)
- ows4R::WPSParameter, [136](#), [138](#), [140](#), [150](#), [153](#), [155](#), [158](#)
- OWSBoundingBox, [41](#), [41](#), [42](#), [66](#), [91](#), [94](#)
- OWSCapabilities, [43](#), [43](#), [47](#), [54](#), [60](#)
- OWSClient, [44](#), [46](#)
- OWSCodeType, [49](#), [49](#)
- OWSException, [50](#), [50](#)
- OWSGetCapabilities, [11](#), [44](#), [45](#), [51](#), [52](#), [80](#), [105](#), [118](#), [130](#)
- OWSHttpRequest, [53](#)
- OWSNamespace, [56](#), [56](#)
- OWSOperation, [19](#), [21](#), [23](#), [25](#), [30](#), [54](#), [57](#), [57](#), [59](#), [98](#), [100](#), [110](#), [117](#), [123](#), [139](#), [144](#)
- OWSOperationsMetadata, [45](#), [59](#), [59](#)
- OWSRequest, [60](#), [60](#), [118](#)
- OWSServiceIdentification, [45](#), [61](#), [62](#)
- OWSServiceProvider, [45](#), [63](#), [64](#)
- OWSUtils, [65](#)
- OWSWGSS84BoundingBox, [66](#), [94](#)
- PropertyIsBetween, [67](#)
- PropertyIsEqualTo, [68](#), [68](#)
- PropertyIsGreaterThan, [69](#), [69](#)
- PropertyIsGreaterThanOrEqualTo, [70](#), [71](#)
- PropertyIsLessThan, [71](#), [72](#)
- PropertyIsLessThanOrEqualTo, [72](#), [73](#)
- PropertyIsLike, [67](#), [74](#), [74](#), [77](#)
- PropertyIsNotEqualTo, [75](#), [76](#)
- PropertyIsNull, [76](#)
- R6Class, [4–6](#), [8–12](#), [17](#), [19](#), [20](#), [22](#), [24](#), [26](#), [28](#), [29](#), [32](#), [33](#), [36](#), [38](#), [39](#), [41](#), [43](#), [46](#), [49–51](#), [53](#), [56](#), [57](#), [59–61](#), [63](#), [65–71](#), [73–76](#), [78](#), [80](#), [81](#), [84](#), [86](#), [88](#), [90](#), [92](#), [96](#), [97](#), [99](#), [101–106](#), [109](#), [111](#), [114](#), [116–119](#), [122](#), [124](#), [128](#), [129](#), [132](#), [134–141](#), [143](#), [145](#), [147](#), [149](#), [150](#), [152](#), [153](#), [155](#), [156](#), [158–160](#), [162](#), [163](#), [165](#), [166](#)
- registerOWSNamespace, [77](#)
- setOWSNamespace, [78](#)
- stack, [95](#)
- UnaryLogicOpType, [78](#), [79](#)
- WSCCapabilities, [80](#), [80](#), [82](#), [93](#), [98](#), [100](#)
- WSCClient, [80](#), [81](#), [82](#)
- WSCCoverage, [84](#), [85](#)
- WSCCoverageDescription, [83](#), [86](#), [87](#), [94](#)
- WSCCoverageDomain, [88](#), [89](#), [91](#)
- WSCCoverageFilenameHandler, [90](#), [95](#)
- WSCCoverageSpatialDomain, [89](#), [90](#)
- WSCCoverageSummary, [80](#), [92](#), [93](#), [100](#)
- WSCCoverageTemporalDomain, [89](#), [96](#), [96](#)
- WCSDescribeCoverage, [97](#), [98](#)
- WCSGetCoverage, [84](#), [95](#), [99](#), [99](#)
- WCSGridCRS, [92](#), [101](#), [102](#)
- WCSGSElevationDomain, [102](#)
- WCSGSTimeDomain, [103](#)
- WFSCapabilities, [105](#), [105](#), [107](#), [110](#), [111](#), [117](#)
- WFSCClient, [106](#), [107](#)
- WFSDescribeFeatureType, [109](#), [109](#)
- WFSFeatureType, [106](#), [108](#), [110](#), [111](#)
- WFSFeatureTypeElement, [108](#), [112](#), [114](#), [115](#)
- WFSGetFeature, [108](#), [113](#), [116](#), [116](#)
- WMSCapabilities, [117](#), [118](#), [120](#), [123](#), [125](#)
- WMSClient, [119](#), [120](#)
- WMSGetFeatureInfo, [121](#), [122](#), [123](#), [127](#)
- WMSLayer, [119](#), [121](#), [124](#), [125](#)
- WPSBoundingBoxData, [128](#), [128](#), [131](#), [134](#), [144](#), [162](#)

WPSCapabilities, [129](#), [130](#), [133](#), [139](#), [144](#),
[146](#), [147](#), [161](#)
WPSClient, [130](#), [131](#), [132](#)
WPSComplexData, [131](#), [134](#), [134](#), [135](#), [144](#), [162](#)
WPSComplexInputDescription, [136](#), [136](#),
[137](#)
WPSComplexOutputDescription, [137](#), [138](#)
WPSDescribeProcess, [138](#), [139](#)
WPSDescriptionParameter, [140](#), [140](#)
WPSException, [141](#), [142](#), [146](#)
WPSExecute, [143](#), [143](#)
WPSExecuteResponse, [145](#), [145](#), [146](#)
WPSFormat, [147](#), [148](#)
WPSInput, [143](#), [149](#), [150](#)
WPSInputDescription, [150](#), [151](#), [164](#)
WPSLiteralData, [131](#), [134](#), [144](#), [152](#), [152](#), [162](#)
WPSLiteralInputDescription, [153](#), [153](#),
[154](#)
WPSLiteralOutputDescription, [155](#), [155](#)
WPSOutput, [156](#), [156](#), [157](#)
WPSOutputDescription, [158](#), [158](#), [164](#)
WPSParameter, [159](#), [159](#)
WPSProcess, [146](#), [160](#), [161](#)
WPSProcessDescription, [130](#), [133](#), [144](#), [161](#),
[162](#), [163](#)
WPSResponseDocument, [131](#), [134](#), [144](#), [162](#),
[165](#), [165](#)
WPSStatus, [146](#), [166](#), [167](#)

XMLInternalNode-class, [35](#), [36](#), [42](#), [49](#), [50](#),
[58–60](#), [62](#), [64](#), [66](#), [85](#), [87](#), [89](#), [91](#), [93](#),
[96](#), [102–104](#), [111](#), [115](#), [125](#), [129](#),
[135](#), [137](#), [138](#), [141](#), [142](#), [146–148](#),
[150–152](#), [154](#), [155](#), [157–159](#), [161](#),
[163](#), [165](#), [167](#)