

Package ‘pkgdepends’

March 16, 2021

Title Package Dependency Resolution and Downloads

Version 0.1.0

Author Gábor Csárdi

Maintainer Gábor Csárdi <csardi.gabor@gmail.com>

Description Find recursive dependencies of 'R' packages from various sources. Solve the dependencies to obtain a consistent set of packages to install. Download packages, and install them. It supports packages on 'CRAN', 'Bioconductor' and other 'CRAN-like' repositories, 'GitHub', package 'URLs', and local package trees and files. It caches metadata and package files via the 'pkgcache' package, and performs all 'HTTP' requests, downloads, builds and installations in parallel. 'pkgdepends' is the workhorse of the 'pak' package.

License MIT + file LICENSE

LazyData true

URL <https://github.com/r-lib/pkgdepends#readme>

BugReports <https://github.com/r-lib/pkgdepends/issues>

RoxygenNote 7.1.1.9001

Imports callr (>= 3.3.1), cli (>= 2.1.0), crayon, curl, desc (>= 1.2.0), filelock (>= 1.0.2), glue, jsonlite, lpSolve, pkgbuild (>= 1.0.2), pkgcache (>= 1.2.0), prettyunits (>= 1.1.1), processx (>= 3.4.2), ps, rematch2, rprojroot, R6, stats, tibble, utils, withr (>= 2.1.1), zip (>= 2.1.0)

Suggests asciicast, debugme, digest, fansi, fs, htmlwidgets, mockery, pingr (>= 2.0.0), rlang, rstudioapi, spelling, testthat, webfakes

Config/testthat/edition 3

Config/Needs/website pkgdown

Config/Needs/coverage covr

Encoding UTF-8

NeedsCompilation no

Repository CRAN

Date/Publication 2021-03-16 09:20:02 UTC

R topics documented:

pkgdepends-package	2
as_pkg_dependencies	6
current_r_platform	7
install_package_plan	7
install_plans	8
is_valid_package_name	9
lib_status	10
new_pkg_deps	10
new_pkg_download_proposal	18
new_pkg_installation_plan	24
new_pkg_installation_proposal	26
parse_pkg_refs	40
pkg_config	40
pkg_dep_types_hard	41
pkg_downloads	42
pkg_name_check	42
pkg_refs	44
pkg_resolution	47
pkg_rx	49
pkg_solution	50
Index	52

pkgdepends-package *pkgdepends: Package Dependency Resolution and Downloads*

Description

pkgdepends is a toolkit for package dependencies, downloads and installations, to be used in other packages. If you are looking for a package manager, see [pak](#).

Features

- Look up package dependencies recursively.
- Visualize package dependencies.
- Download packages and their dependencies.
- Install downloaded packages.
- Includes a dependency solver to find a consistent set of dependencies.
- Supports CRAN and Bioconductor packages automatically.

- Supports packages on GitHub.
- Supports local package file and trees.
- Supports the Remotes entry in the DESCRIPTION file.
- Caches metadata and downloaded packages via `pkgcache`
- Performs all downloads and HTTP queries concurrently.
- Builds and installs packages in parallel.

Install

Once on CRAN, install the package with:

```
install.packages("pkgdepends")
```

Usage

```
library(pkgdepends)
```

Package references:

A package reference (ref) specifies a location from which an R package can be obtained from.

Examples:

```
devtools
cran::devtools
bioc::Biobase
r-lib/pkgdepends
https://github.com/r-lib/pkgdepends
local::~~/works/shiny
```

See “[Package references](#)” for details.

Package dependencies:

Dependencies of the development version of the cli package:

```
pd <- new_pkg_deps("r-lib/pkgcache")
pd$solve()
pd$draw()

#> r-lib/pkgcache 1.1.1.9000 [new][bld][cmp][dl] (unknown size)
#> +-assertthat 0.2.1 [new][dl] (52.47 kB)
#> +-callr 3.5.1 [new]
#> | +-processx 3.4.4 [new]
#> | | +-ps 1.4.0 [new]
#> | | \-R6 2.5.0 [new]
#> | \-R6
#> +-cli 2.1.0 [new]
#> | +-assertthat
#> | +-crayon 1.3.4 [new][dl] (748.25 kB)
#> | +-glue 1.4.2 [new]
#> | \-fansi 0.4.1 [new][dl] (210.40 kB)
```

```

#> +-curl 4.3 [new][dl] (741.06 kB)
#> +-digest 0.6.27 [new]
#> +-filelock 1.0.2 [new][dl] (26.67 kB)
#> +-glue
#> +-prettyunits 1.1.1 [new][dl] (34.79 kB)
#> +-R6
#> +-processx
#> +-rappdirs 0.3.1 [new][dl] (145.56 kB)
#> +-rlang 0.4.8 [new]
#> +-tibble 3.0.4 [new]
#> | +-cli
#> | +-crayon
#> | +-ellipsis 0.3.1 [new][dl] (33.48 kB)
#> | | \-rlang
#> | +-fansI
#> | +-lifecycle 0.2.0 [new][dl] (91.64 kB)
#> | | +-glue
#> | | \-rlang
#> | +-magrittr 2.0.1 [new][dl] (unknown size)
#> | +-pillar 1.4.6 [new]
#> | | +-cli
#> | | +-crayon
#> | | +-ellipsis
#> | | +-fansI
#> | | +-lifecycle
#> | | +-rlang
#> | | +-utf8 1.1.4 [new][dl] (195.28 kB)
#> | | \-vctrs 0.3.5 [new][dl] (unknown size)
#> | |   +-ellipsis
#> | |   +-digest
#> | |   +-glue
#> | |   \-rlang
#> | +-pkgconfig 2.0.3 [new][dl] (17.63 kB)
#> | +-rlang
#> | \-vctrs
#> \-uuid 0.1-4 [new][dl] (27.75 kB)
#>
#> Key: [new] new | [dl] download | [bld] build | [cmp] compile

```

See the [pkg_deps](#) class for details.

Package downloads:

Downloading all dependencies of a package:

```

pdl <- new_pkg_download_proposal("r-lib/cli")
pdl$resolve()
pdl$download()

```

See the [pkg_download_proposal](#) class for details.

Package installation:

Installing or updating a set of package:

```
lib <- tempfile()
pdi <- new_pkg_installation_proposal(
  "r-lib/cli",
  config = list(library = lib)
)
pdi$solve()
pdi$download()
pdi$install()
```

Dependency resolution:

[pkg_deps](#), [pkg_download_proposal](#) and [pkg_installation_proposal](#) all resolve their dependencies recursively, to obtain information about all packages needed for the specified [package references](#). See “[Dependency resolution](#)” for details.

The dependency solver:

The dependency solver takes the resolution information, and works out the exact versions of each package that must be installed, such that version and other requirements are satisfied. See “[The dependency solver](#)” for details.

Installation plans:

[pkg_installation_proposal](#) can create installation plans, and then also install them. It is also possible to import installation plans that were created by other tools. See “[Installation plans](#)” for details.

Configuration:

The details of [pkg_deps](#), [pkg_download_proposal](#) and [pkg_installation_proposal](#) can be tuned with a list of configuration options. See “[Configuration](#)” for details.

Related

- [pak](#) – R package manager
- [pkgcache](#) – Metadata and package cache
- [devtools](#) – Tools for R package developers

License

MIT (c) RStudio

See Also

Useful links:

- <https://github.com/r-lib/pkgdepends#readme>
- Report bugs at <https://github.com/r-lib/pkgdepends/issues>

as_pkg_dependencies *Shorthands for dependency specifications*

Description

Shorthands for dependency specifications

Usage

```
as_pkg_dependencies(deps)
```

Arguments

deps See below.

Details

Supports concise ways of specifying which types of dependencies of a package should be installed. It is similar to how `utils::install.packages()` interprets its `dependencies` argument. Possible values for the `deps` argument are:

- TRUE: This means all hard dependencies plus Suggests for direct installations, and hard dependencies only for dependent packages.
- FALSE: no dependencies are installed at all.
- NA (any atomic type, so `NA_character_`, etc. as well): only hard dependencies are installed. See `pkg_dep_types_hard()`.
- If a list with two entries named `direct` and `indirect`, it is taken as the requested dependency types, for direct installations and dependent packages.
- If a character vector, then it is taken as the dependency types both for direct installations, and the hard dependencies are used for the dependent packages.

If "hard" is included, then it is replaced by the hard dependency types. If "soft" or "all" is included, then it is replaced by all dependency types.

Extra dependencies:

`pkgdepends` supports extra dependency types for direct installations. These are specified with a `Config/Needs/` prefix in `DESCRIPTION` and they can contain package references, separated by commas. For example you can specify packages that are only needed for the pkgdown website of the package:

```
Config/Needs/website: r-lib/pkgdown
```

Value

A named list with two character vectors: `direct`, `indirect`, the dependency types to use for direct installations and dependent packages.

See Also

Other package dependency utilities: [pkg_dep_types_hard\(\)](#)

current_r_platform *The current R platform for packages*

Description

current_r_platform() detects the current platform. default_platforms() prints the default package types that are used on the current platform. See also '[Configuration](#)'.

Usage

```
current_r_platform()
```

```
default_platforms()
```

Value

current_r_platform() returns a string: source, macos or windows.

default_platforms() return a character vector of package types that work on the current system. It is a subset of the possible current_r_platform() return values.

Examples

```
current_r_platform()
default_platforms()
```

install_package_plan *Perform a package installation plan*

Description

See '[Installation plans](#)' for the details and the format.

Usage

```
install_package_plan(
  plan,
  lib = .libPaths()[[1]],
  num_workers = 1,
  cache = NULL
)
```

Arguments

plan	Package plan object, a data frame, see ' Installation plans ' for the format.
lib	Library directory to install to.
num_workers	Number of worker processes to use.
cache	Package cache to use, or NULL.

Value

Information about the installation process.

install_plans	<i>Installation plans</i>
---------------	---------------------------

Description

An installation plan contains all data that is needed to install a set of package files. It is usually created from an [installation proposal](#) with [solving](#) the dependencies and [downloading](#) the package files.

Details

It is also possible to create an installation plan a different way. An installation plan object must be a data frame, with at least the following columns:

- package: The name of the package.
- type: The type of the [package reference](#).
- binary: Whether the package is a binary package.
- file: Full path to the package file or directory.
- dependencies: A list column that lists the names of the dependent packages for each package.
- needscompilation: Whether the package needs compilation. This should be FALSE for binary packages.

For installation plans created via [pkg_installation_proposal](#), the plan contains all columns from [pkg_download_result](#) objects, and some additional ones:

- library: the library the package is supposed to be installed to.
- direct: whether the package was directly requested or it is installed as a dependency.
- vignettes: whether the vignettes need to be (re)built.
- packaged: whether R CMD build was already called for the package.

See Also

[pkg_installation_proposal](#) to create install plans, [install_package_plan\(\)](#) to install plans from any source.

Examples

```
## Not run:
pdi <- new_pkg_installation_proposal(
  "pak",
  config = list(library = tempfile())
)
pdi$resolve()
pdi$solve()
pdi$download()
pdi$get_install_plan()

## End(Not run)
```

is_valid_package_name *Check whether a package name is valid*

Description

Check whether a package name is valid

Usage

```
is_valid_package_name(nm)
```

Arguments

nm Potential package name, string of length 1.

Value

Logical flag. If FALSE, then the reason attribute contains a character string, the explanation why the package name is invalid. See examples below.

Examples

```
is_valid_package_name("pak")
is_valid_package_name("pkg")
is_valid_package_name("pak\u00e1ge")
is_valid_package_name("good-package")
is_valid_package_name("x")
is_valid_package_name("1stpackage")
is_valid_package_name("dots.")
```

lib_status	<i>Status of packages in a library</i>
------------	--

Description

Query data of all packages in a package library.

Usage

```
lib_status(library = .libPaths()[1], packages = NULL)
```

Arguments

library	Path to library.
packages	If not NULL, then only these packages are shown.

Value

Data frame (tibble) the contains data about the packages installed in the library.

new_pkg_deps	<i>R6 class for package dependency lookup</i>
--------------	---

Description

Look up dependencies of R packages from various sources.

Usage

```
new_pkg_deps(refs, ...)
```

Arguments

refs	Package names or references. See 'Package references' for the syntax.
...	Additional arguments, passed to <code>pkg_deps\$new()</code> .

Details

`new_pkg_deps()` creates a new object from the `pkg_deps` class. The advantage of `new_pkg_deps()` compared to using the `pkg_deps` constructor directly is that it avoids making `pkgdepends` a build time dependency.

The usual steps to query package dependencies are:

1. Create a `pkg_deps` object with `new_pkg_deps()`.
2. Resolve all possible dependencies with `pkg_deps$resolve()`.
3. Solve the dependencies, to obtain a subset of all possible dependencies that can be installed together, with `pkg_deps$solve()`.
4. Call `pkg_deps$get_solution()` to list the result of the dependency solver.

Value

new_pkg_deps() returns a new pkg_deps object.

Methods**Public methods:**

- `pkg_deps$new()`
- `pkg_deps$get_refs()`
- `pkg_deps$get_config()`
- `pkg_deps$resolve()`
- `pkg_deps$async_resolve()`
- `pkg_deps$get_resolution()`
- `pkg_deps$get_solve_policy()`
- `pkg_deps$set_solve_policy()`
- `pkg_deps$solve()`
- `pkg_deps$get_solution()`
- `pkg_deps$stop_for_solution_error()`
- `pkg_deps$draw()`
- `pkg_deps$format()`
- `pkg_deps$print()`
- `pkg_deps$clone()`

Method `new()`: Create a new pkg_deps object. Consider using `new_pkg_deps()` instead of calling the constructor directly.

The returned object can be used to look up (recursive) dependencies of R packages from various sources. To perform the actual lookup, you'll need to call the `resolve()` method.

Usage:

```
pkg_deps$new(  
  refs,  
  config = list(),  
  policy = c("lazy", "upgrade"),  
  remote_types = NULL  
)
```

Arguments:

`refs` Package names or references. See '[Package references](#)' for the syntax.

`config` Configuration options, a named list. See '[Configuration](#)'.

`policy` Solution policy. See '[The dependency solver](#)'.

`remote_types` Custom remote ref types, this is for advanced use, and experimental currently.

Returns: A new pkg_deps object.

Examples:

```
pd <- pkg_deps$new("r-lib/pkgdepends")  
pd
```

Method `get_refs()`: The package refs that were used to create the pkg_deps object.

Usage:

```
pkg_deps$get_refs()
```

Returns: A character vector of package refs that were used to create the pkg_deps object.

Examples:

```
pd <- new_pkg_deps(c("pak", "jsonlite"))
pd$get_refs()
```

Method `get_config()`: Configuration options for the pkg_deps object. See '[Configuration](#)' for details.

Usage:

```
pkg_deps$get_config()
```

Returns: Named list. See '[Configuration](#)' for the configuration options.

Examples:

```
pd <- new_pkg_deps("pak")
pd$get_config()
```

Method `resolve()`: Resolve the dependencies of the specified package references. This usually means downloading metadata from CRAN and Bioconductor, unless already cached, and also from GitHub if GitHub refs were included, either directly or indirectly. See '[Dependency resolution](#)' for details.

Usage:

```
pkg_deps$resolve()
```

Returns: The pkg_deps object itself, invisibly.

Examples:

```
\dontrun{
pd <- new_pkg_deps("pak")
pd$resolve()
pd$get_resolution()
}
```

Method `async_resolve()`: The same as `resolve()`, but asynchronous. This method is for advanced use.

Usage:

```
pkg_deps$async_resolve()
```

Returns: A deferred value.

Method `get_resolution()`: Query the result of the dependency resolution. This method can be called after `resolve()` has completed.

Usage:

```
pkg_deps$get_resolution()
```

Returns: A `pkg_resolution_result` object, which is also a tibble. See '[Dependency resolution](#)' for its columns.

Examples:

```

\dontrun{
pd <- new_pkg_deps("r-lib/pkgdepends")
pd$resolve()
pd$get_resolution()
}

```

Method `get_solve_policy()`: Returns the current policy of the dependency solver. See ['The dependency solver'](#) for details.

Usage:

```
pkg_deps$get_solve_policy()
```

Returns: A character vector of length one.

Examples:

```

pdi <- new_pkg_deps("r-lib/pkgdepends")
pdi$get_solve_policy()
pdi$set_solve_policy("upgrade")
pdi$get_solve_policy()

```

Method `set_solve_policy()`: Set the current policy of the dependency solver. If the object already contains a solution and the new policy is different than the old policy, then the solution is deleted. See ['The dependency solver'](#) for details.

Usage:

```
pkg_deps$set_solve_policy(policy = c("lazy", "upgrade"))
```

Arguments:

`policy` Policy to set.

Examples:

```

pdi <- new_pkg_deps("r-lib/pkgdepends")
pdi$get_solve_policy()
pdi$set_solve_policy("upgrade")
pdi$get_solve_policy()

```

Method `solve()`: Solve the package dependencies. Out of the resolved dependencies, it works out a set of packages, that can be installed together to create a functional installation. The set includes all directly specified packages, and all required (or suggested, depending on the configuration) packages as well. It includes every package at most once. See ['The dependency solver'](#) for details.

`solve()` calls `resolve()` automatically, if it hasn't been called yet.

Usage:

```
pkg_deps$solve()
```

Returns: The `pkg_deps` object itself, invisibly.

Examples:

```

\dontrun{
pd <- new_pkg_deps("r-lib/pkgdepends")
pd$resolve()
pd$solve()
pd$get_solution()
}

```

Method `get_solution()`: Returns the solution of the package dependencies.

Usage:

```
pkg_deps$get_solution()
```

Returns: A [pkg_solution_result](#) object, which is a list. See [pkg_solution_result](#) for details.

Examples:

```
\dontrun{
pd <- new_pkg_deps("pkgload")
pd$resolve()
pd$solve()
pd$get_solution()
}
```

Method `stop_for_solution_error()`: Error if the dependency solver failed to find a consistent set of packages that can be installed together.

Usage:

```
pkg_deps$stop_for_solution_error()
```

Examples:

```
\dontrun{
# This is an error, because the packages conflict:
pd <- new_pkg_deps(
  c("r-lib/pak", "cran:pak"),
  config = list(library = tempfile())
)
pd$resolve()
pd$solve()
pd
# This fails:
# pd$stop_for_solution_error()
}
```

Method `draw()`: Draw a tree of package dependencies. It returns a tree object, see [cli::tree\(\)](#). Printing this object prints the dependency tree to the screen.

Usage:

```
pkg_deps$draw()
```

Returns: A tree object from the cli package, see [cli::tree\(\)](#).

Examples:

```
\dontrun{
pd <- new_pkg_deps("pkgload")
pd$solve()
pd$draw()
}
```

Method `format()`: Format a `pkg_deps` object, typically for printing.

Usage:

```
pkg_deps$format(...)
```

Arguments:

... Not used currently.

Returns: A character vector, each element should be a line in the printout.

Method print(): Prints a pkg_deps object to the screen. The printout includes:

- The package refs.
- Whether the object has the resolved dependencies.
- Whether the resolution had errors.
- Whether the object has the solved dependencies.
- Whether the solution had errors.
- Advice on which methods to call next.

See the example below.

Usage:

```
pkg_deps$print(...)
```

Arguments:

... not used currently.

Returns: The pkg_deps object itself, invisibly.

Examples:

```
\dontrun{
pd <- new_pkg_deps("r-lib/pkgdepends")
pd

pd$resolve()
pd

pd$solve()
pd
}
```

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
pkg_deps$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Examples

```
## -----
## Method `pkg_deps$new`
## -----

pd <- pkg_deps$new("r-lib/pkgdepends")
pd
```

```

## -----
## Method `pkg_deps$get_refs`
## -----

pd <- new_pkg_deps(c("pak", "jsonlite"))
pd$get_refs()

## -----
## Method `pkg_deps$get_config`
## -----

pd <- new_pkg_deps("pak")
pd$get_config()

## -----
## Method `pkg_deps$resolve`
## -----

## Not run:
pd <- new_pkg_deps("pak")
pd$resolve()
pd$get_resolution()

## End(Not run)

## -----
## Method `pkg_deps$get_resolution`
## -----

## Not run:
pd <- new_pkg_deps("r-lib/pkgdepends")
pd$resolve()
pd$get_resolution()

## End(Not run)

## -----
## Method `pkg_deps$get_solve_policy`
## -----

pdi <- new_pkg_deps("r-lib/pkgdepends")
pdi$get_solve_policy()
pdi$set_solve_policy("upgrade")
pdi$get_solve_policy()

## -----
## Method `pkg_deps$set_solve_policy`
## -----

pdi <- new_pkg_deps("r-lib/pkgdepends")
pdi$get_solve_policy()
pdi$set_solve_policy("upgrade")
pdi$get_solve_policy()

```



```
## -----
## Method `pkg_deps$solve`
## -----

## Not run:
pd <- new_pkg_deps("r-lib/pkgdepends")
pd$resolve()
pd$solve()
pd$get_solution()

## End(Not run)

## -----
## Method `pkg_deps$get_solution`
## -----

## Not run:
pd <- new_pkg_deps("pkgload")
pd$resolve()
pd$solve()
pd$get_solution()

## End(Not run)

## -----
## Method `pkg_deps$stop_for_solution_error`
## -----

## Not run:
# This is an error, because the packages conflict:
pd <- new_pkg_deps(
  c("r-lib/pak", "cran:pak"),
  config = list(library = tempfile())
)
pd$resolve()
pd$solve()
pd
# This fails:
# pd$stop_for_solution_error()

## End(Not run)

## -----
## Method `pkg_deps$draw`
## -----

## Not run:
pd <- new_pkg_deps("pkgload")
pd$solve()
pd$draw()

## End(Not run)
```

```
## -----  
## Method `pkg_deps$print`  
## -----  
  
## Not run:  
pd <- new_pkg_deps("r-lib/pkgdepends")  
pd  
  
pd$resolve()  
pd  
  
pd$solve()  
pd  
  
## End(Not run)
```

new_pkg_download_proposal
R6 class for package downloads

Description

Download packages with their dependencies, from various sources.

Usage

```
new_pkg_download_proposal(refs, ...)
```

Arguments

refs Package names or references. See ['Package references'](#) for the syntax.
... Additional arguments, passed to `pkg_download_proposal$new()`.

Details

`new_pkg_download_proposal()` creates a new object from the `pkg_download_proposal` class, that can be used to look up and download R packages and their dependencies. The advantage of `new_pkg_download_proposal()` compared to using the `pkg_download_proposal` constructor directly is that it avoids making `pkgdepends` a build time dependency.

Typical workflow to download a set of packages:

1. Create a `pkg_download_proposal` object with `new_pkg_download_proposal()`.
2. Resolve all possible dependencies with `pkg_download_proposal$resolve()`.
3. Download all files with `pkg_download_proposal$download()`.
4. Get the data about the packages and downloads with `pkg_download_proposal$get_downloads()`.

Value

new_pkg_download_proposal() returns a new pkg_download_proposal object.

Methods**Public methods:**

- `pkg_download_proposal$new()`
- `pkg_download_proposal$get_refs()`
- `pkg_download_proposal$get_config()`
- `pkg_download_proposal$resolve()`
- `pkg_download_proposal$async_resolve()`
- `pkg_download_proposal$get_resolution()`
- `pkg_download_proposal$download()`
- `pkg_download_proposal$async_download()`
- `pkg_download_proposal$get_downloads()`
- `pkg_download_proposal$stop_for_download_error()`
- `pkg_download_proposal$format()`
- `pkg_download_proposal$print()`
- `pkg_download_proposal$clone()`

Method new(): Create a new pkg_download_proposal object. Consider using new_pkg_download_proposal() instead of calling the constructor directly.

The returned object can be used to look up (recursive) dependencies of R packages from various sources, and then to download the package files.

Usage:

```
pkg_download_proposal$new(refs, config = list(), remote_types = NULL)
```

Arguments:

refs Package names or references. See ['Package references'](#) for the syntax.

config Configuration options, a named list. See ['Configuration'](#).

remote_types Custom remote ref types, this is for advanced use, and experimental currently.

Examples:

```
pd1 <- pkg_download_proposal$new("r-lib/pkgdepends")
pd1
```

Method get_refs(): The package refs that were used to create the pkg_download_proposal object.

Usage:

```
pkg_download_proposal$get_refs()
```

Returns: A character vector of package refs that were used to create the pkg_download_proposal object.

Examples:

```
pd1 <- new_pkg_download_proposal(c("pak", "jsonlite"))
pd1$get_refs()
```

Method `get_config()`: Configuration options for the `pkg_download_proposal` object. See ['Configuration'](#) for details.

Usage:

```
pkg_download_proposal$get_config()
```

Returns: Named list. See ['Configuration'](#) for the configuration options.

Examples:

```
pdl <- new_pkg_download_proposal("pak")
pdl$get_config()
```

Method `resolve()`: Resolve the dependencies of the specified package references. This usually means downloading metadata from CRAN and Bioconductor, unless already cached, and also from GitHub if GitHub refs were included, either directly or indirectly. See ['Dependency resolution'](#) for details.

Usage:

```
pkg_download_proposal$resolve()
```

Returns: The `pkg_download_proposal` object itself, invisibly.

Examples:

```
\dontrun{
pdl <- new_pkg_download_proposal("pak")
pdl$resolve()
pdl$get_resolution()
}
```

Method `async_resolve()`: The same as `resolve()`, but asynchronous. This method is for advanced use.

Usage:

```
pkg_download_proposal$async_resolve()
```

Returns: A deferred value.

Method `get_resolution()`: Query the result of the dependency resolution. This method can be called after `resolve()` has completed.

Usage:

```
pkg_download_proposal$get_resolution()
```

Returns: A `pkg_resolution_result` object, which is also a tibble. See ['Dependency resolution'](#) for its columns.

Examples:

```
\dontrun{
pdl <- new_pkg_download_proposal("r-lib/pkgdepends")
pdl$resolve()
pdl$get_resolution()
}
```

Method `download()`: Download all resolved packages. It uses the package cache in the `pkg-cache` package by default, to avoid downloads if possible.

Usage:

```
pkg_download_proposal$download()
```

Returns: The `pkg_download_proposal` object, invisibly.

Examples:

```
\dontrun{
pdl <- new_pkg_download_proposal("r-lib/pkgdepends")
pdl$resolve()
pdl$download()
pdl$get_downloads()
}
```

Method `async_download()`: The same as `download()`, but asynchronous. This method is for advanced use.

Usage:

```
pkg_download_proposal$async_download()
```

Returns: A deferred value.

Method `get_downloads()`: Returns the summary of the package downloads.

Usage:

```
pkg_download_proposal$get_downloads()
```

Returns: A `pkg_download_result` object, which is a list. See `pkg_download_result` for details.

Examples:

```
\dontrun{
pdl <- new_pkg_download_proposal("pkgload")
pdl$resolve()
pdl$download()
pdl$get_downloads()
}
```

Method `stop_for_download_error()`: Throw an error if some of the downloads have failed for the most recent `pkg_download_proposal$download()` call.

Usage:

```
pkg_download_proposal$stop_for_download_error()
```

Method `format()`: Format a `pkg_download_proposal` object, typically for printing.

Usage:

```
pkg_download_proposal$format(...)
```

Arguments:

... not used currently.

Returns: Nothing. A character vector, each element should be a line in the printout.

Method `print()`: Prints a `pkg_download_proposal` object to the screen. The printout includes:

- The package refs.
- Whether the object has the resolved dependencies.

- Whether the resolution had errors.
- Whether the downloads were completed.
- Whether the downloads had errors.
- Advice on which methods to call next.

See the example below.

Usage:

```
pkg_download_proposal$print(...)
```

Arguments:

... not used currently.

Returns: The pkg_download_proposal object itself, invisibly.

Examples:

```
\dontrun{
pdl <- new_pkg_download_proposal("r-lib/pkgdepends")
pdl

pdl$resolve()
pdl

pdl$download()
pdl
}
```

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
pkg_download_proposal$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Examples

```
## -----
## Method `pkg_download_proposal$new`
## -----

pdl <- pkg_download_proposal$new("r-lib/pkgdepends")
pdl

## -----
## Method `pkg_download_proposal$get_refs`
## -----

pdl <- new_pkg_download_proposal(c("pak", "jsonlite"))
pdl$get_refs()

## -----
```

```

## Method `pkg_download_proposal$get_config`
## -----

pdl <- new_pkg_download_proposal("pak")
pdl$get_config()

## -----
## Method `pkg_download_proposal$resolve`
## -----

## Not run:
pdl <- new_pkg_download_proposal("pak")
pdl$resolve()
pdl$get_resolution()

## End(Not run)

## -----
## Method `pkg_download_proposal$get_resolution`
## -----

## Not run:
pdl <- new_pkg_download_proposal("r-lib/pkgdepends")
pdl$resolve()
pdl$get_resolution()

## End(Not run)

## -----
## Method `pkg_download_proposal$download`
## -----

## Not run:
pdl <- new_pkg_download_proposal("r-lib/pkgdepends")
pdl$resolve()
pdl$download()
pdl$get_downloads()

## End(Not run)

## -----
## Method `pkg_download_proposal$get_downloads`
## -----

## Not run:
pdl <- new_pkg_download_proposal("pkgload")
pdl$resolve()
pdl$download()
pdl$get_downloads()

## End(Not run)

## -----

```

```
## Method `pkg_download_proposal$print`
## -----

## Not run:
pd1 <- new_pkg_download_proposal("r-lib/pkgdepends")
pd1

pd1$resolve()
pd1

pd1$download()
pd1

## End(Not run)
```

```
new_pkg_installation_plan
```

```
R6 class for installation from a lock file
```

Description

An installation plan is similar to an installation proposal (i.e. [pkg_installation_proposal](#)), but it already contains the solved dependencies, complete with download URLs.

Usage

```
new_pkg_installation_plan(lockfile = "pkg.lock", config = list(), ...)
```

Arguments

lockfile	Path to the lock file to use.
config	Configuration options, a named list. See 'Configuration' . If it does not include library, then <code>.libPaths()[1]</code> is added as library.
...	Additional arguments, passed to pkg_installation_plan\$new() .

Details

Typically you create a `pkg_installation_plan` object with `new_pkg_installation_plan()` and then call its `$download()` method to download the packages and then its `$install()` method to install them.

Value

`new_pkg_installation_plan()` returns a `pkg_installation_plan` object.

Super class

[pkgdepends::pkg_installation_proposal](#) -> `pkg_installation_plan`

Methods

Public methods:

- `pkg_installation_plan$new()`
- `pkg_installation_plan$resolve()`
- `pkg_installation_plan$async_resolve()`
- `pkg_installation_plan$get_solve_policy()`
- `pkg_installation_plan$set_solve_policy()`
- `pkg_installation_plan$solve()`
- `pkg_installation_plan$format()`
- `pkg_installation_plan$clone()`

Method `new()`: Create a new `pkg_installation_plan` object. Consider using `new_pkg_installation_plan()` instead of calling the constructor directly.

The returned object can be used to download and install packages, according to the plan.

Usage:

```
pkg_installation_plan$new(  
  lockfile = "pkg.lock",  
  config = list(),  
  remote_types = NULL  
)
```

Arguments:

`lockfile` Path to the lock file to use.

`config` Configuration options, a named list. See '[Configuration](#)'. It needs to include the package library to install to, in `library`.

`remote_types` Custom remote ref types, this is for advanced use, and experimental currently.

Method `resolve()`: This function is implemented for installation plans, and will error.

Usage:

```
pkg_installation_plan$resolve()
```

Method `async_resolve()`: This function is implemented for installation plans, and will error.

Usage:

```
pkg_installation_plan$async_resolve()
```

Method `get_solve_policy()`: Installation plans are already solved, and this method will return `NA_character_`, always.

Usage:

```
pkg_installation_plan$get_solve_policy()
```

Method `set_solve_policy()`: This function is implemented for installation plans, and will error.

Usage:

```
pkg_installation_plan$set_solve_policy()
```

Method solve(): This function is implemented for installation plans, and will error.

Usage:

```
pkg_installation_plan$solve()
```

Method format(): Format a pkg_installation_plan object, typically for printing.

Usage:

```
pkg_installation_plan$format(...)
```

Arguments:

... not used currently.

Returns: A character vector, each element should be a line in the printout.

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
pkg_installation_plan$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

```
new_pkg_installation_proposal
```

R6 class for package download and installation.

Description

Download and install R packages, with their dependencies, from various sources.

Usage

```
new_pkg_installation_proposal(refs, config = list(), ...)
```

Arguments

refs	Package names or references. See 'Package references' for the syntax.
config	Configuration options, a named list. See 'Configuration' . If it does not include library, then <code>.libPaths()[1]</code> is added as library.
...	Additional arguments, passed to <code>pkg_installation_proposal\$new()</code> .

Details

`new_pkg_installation_proposal()` creates a new object from the `pkg_installation_proposal` class. The advantage of `new_pkg_installation_proposal()` compared to using the `pkg_installation_proposal` constructor directly is that it avoids making `pkgdepends` a build time dependency.

Typical workflow to install a set of packages:

1. Create a `pkg_installation_proposal` object with `new_pkg_installation_proposal()`.

2. Resolve all possible dependencies with `pkg_installation_proposal$resolve()`.
3. Solve the package dependencies, to get an installation plan, with `pkg_installation_proposal$solve()`.
4. Download all files with `pkg_installation_proposal$download()`.
5. Install the downloaded files with `pkg_installation_proposal$install()`.

Value

`new_pkg_installation_proposal()` returns a new `pkg_installation_proposal` object.

Methods

Public methods:

- `pkg_installation_proposal$new()`
- `pkg_installation_proposal$get_refs()`
- `pkg_installation_proposal$get_config()`
- `pkg_installation_proposal$resolve()`
- `pkg_installation_proposal$async_resolve()`
- `pkg_installation_proposal$get_resolution()`
- `pkg_installation_proposal$get_solve_policy()`
- `pkg_installation_proposal$set_solve_policy()`
- `pkg_installation_proposal$solve()`
- `pkg_installation_proposal$get_solution()`
- `pkg_installation_proposal$show_solution()`
- `pkg_installation_proposal$stop_for_solution_error()`
- `pkg_installation_proposal$create_lockfile()`
- `pkg_installation_proposal$draw()`
- `pkg_installation_proposal$download()`
- `pkg_installation_proposal$async_download()`
- `pkg_installation_proposal$get_downloads()`
- `pkg_installation_proposal$stop_for_download_error()`
- `pkg_installation_proposal$install()`
- `pkg_installation_proposal$get_install_plan()`
- `pkg_installation_proposal$format()`
- `pkg_installation_proposal$print()`
- `pkg_installation_proposal$clone()`

Method `new()`: Create a new `pkg_installation_proposal` object. Consider using `new_pkg_installation_proposal()` instead of calling the constructor directly.

The returned object can be used to look up (recursive) dependencies of R packages from various sources, and then download and install the package files.

Usage:

```
pkg_installation_proposal$new(
  refs,
  config = list(),
  policy = c("lazy", "upgrade"),
  remote_types = NULL
)
```

Arguments:

`refs` Package names or references. See ['Package references'](#) for the syntax.

`config` Configuration options, a named list. See ['Configuration'](#). It needs to include the package library to install to, in `library`.

`policy` Solution policy. See ['The dependency solver'](#).

`remote_types` Custom remote ref types, this is for advanced use, and experimental currently.

Examples:

```
pdi <- new_pkg_installation_proposal(
  "r-lib/pkgdepends",
  config = list(library = tempfile()))
pdi
```

Method `get_refs()`: The package refs that were used to create the `pkg_installation_proposal` object.

Usage:

```
pkg_installation_proposal$get_refs()
```

Returns: A character vector of package refs that were used to create the `pkg_installation_proposal` object.

Examples:

```
pdi <- new_pkg_installation_proposal("r-lib/pkgdepends")
pdi$get_refs()
```

Method `get_config()`: Configuration options for the `pkg_installation_proposal` object. See ['Configuration'](#) for details.

Usage:

```
pkg_installation_proposal$get_config()
```

Returns: Named list. See ['Configuration'](#) for the configuration options.

Examples:

```
pdi <- new_pkg_installation_proposal(
  "pak",
  config = list(library = tempfile())
)
pdi$get_config()
```

Method `resolve()`: Resolve the dependencies of the specified package references. This usually means downloading metadata from CRAN and Bioconductor, unless already cached, and also from GitHub if GitHub refs were included, either directly or indirectly. See ['Dependency resolution'](#) for details.

Usage:

```
pkg_installation_proposal$resolve()
```

Returns: The `pkg_installation_proposal` object, invisibly.

Examples:

```
\dontrun{
pdi <- new_pkg_installation_proposal(
  "pak",
  config = list(library = tempfile())
)

pdi$resolve()
pdi$get_resolution()
}
```

Method `async_resolve()`: The same as `resolve()`, but asynchronous. This method is for advanced use.

Usage:

```
pkg_installation_proposal$async_resolve()
```

Returns: A deferred value.

Method `get_resolution()`: Query the result of the dependency resolution. This method can be called after `resolve()` has completed.

Usage:

```
pkg_installation_proposal$get_resolution()
```

Returns: A `pkg_resolution_result` object, which is also a tibble. See ['Dependency resolution'](#) for its columns.

Examples:

```
\dontrun{
pdi <- new_pkg_installation_proposal(
  "r-lib/pkgdepends",
  config = list(library = tempfile())
)
pdi$resolve()
pdi$get_resolution()
}
```

Method `get_solve_policy()`: Returns the current policy of the dependency solver. See ['The dependency solver'](#) for details.

Usage:

```
pkg_installation_proposal$get_solve_policy()
```

Returns: A character vector of length one.

Examples:

```

pdi <- new_pkg_installation_proposal(
  "r-lib/pkgdepends",
  config = list(library = tempfile())
)
pdi$get_solve_policy()
pdi$set_solve_policy("upgrade")
pdi$get_solve_policy()

```

Method `set_solve_policy()`: Set the current policy of the dependency solver. If the object already contains a solution and the new policy is different than the old policy, then the solution is deleted. See ['The dependency solver'](#) for details.

Usage:

```
pkg_installation_proposal$set_solve_policy(policy = c("lazy", "upgrade"))
```

Arguments:

`policy` Policy to set.

Examples:

```

pdi <- new_pkg_installation_proposal(
  "r-lib/pkgdepends",
  config = list(library = tempfile())
)
pdi$get_solve_policy()
pdi$set_solve_policy("upgrade")
pdi$get_solve_policy()

```

Method `solve()`: Solve the package dependencies. Out of the resolved dependencies, it works out a set of packages, that can be installed together to create a functional installation. The set includes all directly specified packages, and all required (or suggested, depending on the configuration) packages as well. It includes every package at most once. See ['The dependency solver'](#) for details.

Usage:

```
pkg_installation_proposal$solve()
```

Returns: The `pkg_installation_proposal` object itself, invisibly.

Examples:

```

\dontrun{
pdi <- new_pkg_installation_proposal(
  "r-lib/pkgdepends",
  config = list(library = tempfile())
)
pdi$resolve()
pdi$solve()
pdi$get_solution()
}

```

Method `get_solution()`: Returns the solution of the package dependencies.

Usage:

```
pkg_installation_proposal$get_solution()
```

Returns: A `pkg_solution_result` object, which is a list. See `pkg_solution_result` for details.

Examples:

```
\dontrun{
pdi <- new_pkg_installation_proposal(
  "r-lib/pkgdepends",
  config = list(library = tempfile())
)
pdi$resolve()
pdi$solve()
pdi$get_solution()
}
```

Method `show_solution()`: Show the solution on the screen.

Usage:

```
pkg_installation_proposal$show_solution(key = FALSE)
```

Arguments:

`key` Whether to show the key to the package list annotation.

Returns: A `pkg_solution_result` object, which is a list. See `pkg_solution_result` for details.

Examples:

```
\dontrun{
pdi <- new_pkg_installation_proposal(
  "r-lib/pkgdepends",
  config = list(library = tempfile())
)
pdi$resolve()
pdi$solve()
pdi$get_solution()
pdi$show_solution()
}
```

Method `stop_for_solution_error()`: Error if the dependency solver failed to find a consistent set of packages that can be installed together.

Usage:

```
pkg_installation_proposal$stop_for_solution_error()
```

Examples:

```
\dontrun{
# This is an error, because the packages conflict:
pdi <- new_pkg_installation_proposal(
  c("r-lib/pak", "cran::pak"),
  config = list(library = tempfile())
)
pdi$resolve()
pdi$solve()
pdi
# This fails:
# pdi$stop_for_solution_error()
}
```

Method `create_lockfile()`: Create a lock file that contains the information to perform the installation later, possibly in another R session.

Usage:

```
pkg_installation_proposal$create_lockfile(path = "pkg.lock", version = 1)
```

Arguments:

`path` Name of the lock file. The default is `pkg.lock` in the current working directory.

`version` Only version 1 is supported currently.

Details: Note, since the URLs of CRAN and most CRAN-like repositories change over time, in practice you cannot perform the plan of the lock file *much* later. For example, binary packages of older package version are removed, and won't be found.

Similarly, for `url::remote` types, the URL might hold an updated version of the package, compared to when the lock file was created. Should this happen, `pkgdepends` prints a warning, but it will try to continue the installation. The installation might fail if the updated package has different (e.g. new) dependencies.

Currently the intended use case of lock files is on CI systems, to facilitate caching. The (hash of the) lock file provides a good key for caching systems.

Method `draw()`: Draw a tree of package dependencies. It returns a tree object, see `cli::tree()`. Printing this object prints the dependency tree to the screen.

Usage:

```
pkg_installation_proposal$draw()
```

Returns: A tree object from the `cli` package, see `cli::tree()`.

Examples:

```
\dontrun{
pdi <- new_pkg_installation_proposal(
  "pak",
  config = list(library = tempfile())
)
pdi$resolve()
pdi$solve()
pdi$draw()
}
```

Method `download()`: Download all packages that are part of the solution. It uses the package cache in the `pkgcache` package by default, to avoid downloads if possible.

Usage:

```
pkg_installation_proposal$download()
```

Returns: The `pkg_installation_proposal` object itself, invisibly.

Examples:

```
\dontrun{
pdi <- new_pkg_installation_proposal(
  c("r-lib/pak", "cran::pak"),
  config = list(library = tempfile())
)
}
```



```

pdi$resolve()
pdi$solve()
pdi$download()
pdi$get_downloads()
}

```

Method `async_download()`: The same as `download()`, but asynchronous. This method is for advanced use.

Usage:

```
pkg_installation_proposal$async_download()
```

Returns: A deferred value.

Method `get_downloads()`: Returns the summary of the package downloads.

Usage:

```
pkg_installation_proposal$get_downloads()
```

Returns: A `pkg_download_result` object, which is a list. See `pkg_download_result` for details.

Examples:

```

\dontrun{
pdi <- new_pkg_installation_proposal(
  c("r-lib/pak", "cran:pak"),
  config = list(library = tempfile())
)
pdi$resolve()
pdi$solve()
pdi$download()
pdi$get_downloads()
}

```

Method `stop_for_download_error()`: Throw an error if some of the downloads have failed for the most recent `pkg_installation_proposal$download()` call.

Usage:

```
pkg_installation_proposal$stop_for_download_error()
```

Method `install()`: Install the downloaded packages. It calls `install_package_plan()`.

Usage:

```
pkg_installation_proposal$install()
```

Returns: The return value of `install_package_plan()`. Create an installation plan for the downloaded packages.

Method `get_install_plan()`:

Usage:

```
pkg_installation_proposal$get_install_plan()
```

Returns: An installation plan, see 'Installation plans' for the format.

Examples:

```

\dontrun{
pdi <- new_pkg_installation_proposal(
  "pak",
  config = list(library = tempfile())
)
pdi$resolve()
pdi$solve()
pdi$download()
pdi$get_install_plan()
}

```

Method `format()`: Format a `pkg_installation_proposal` object, typically for printing.

Usage:

```
pkg_installation_proposal$format(...)
```

Arguments:

... not used currently.

Returns: A character vector, each element should be a line in the printout.

Method `print()`: Prints a `pkg_installation_proposal` object to the screen.

The printout includes:

- The package refs.
- The policy of the dependency solver.
- Whether the object has the solved dependencies.
- Whether the solution had errors.
- Whether the object has downloads.
- Whether the downloads had errors.
- Advice on which methods to call next.

See the example below.

Usage:

```
pkg_installation_proposal$print(...)
```

Arguments:

... not used currently.

Returns: The `pkg_installation_proposal` object itself, invisibly.

Examples:

```

\dontrun{
pdi <- new_pkg_installation_proposal(
  "pak",
  config = list(library = tempfile())
)
pdi

pdi$resolve()
pdi

```

```

pdi$solve()
pdi

pdi$download()
pdi
}

```

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
new_pkg_installation_proposal$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Examples

```

## Not run:
pdi <- new_pkg_installation_proposal(
  "pak",
  config = list(library = tempfile())
)
pdi

pdi$resolve()
pdi

pdi$solve()
pdi

pdi$download()
pdi

## End(Not run)

## -----
## Method `pkg_installation_proposal$new`
## -----

pdi <- new_pkg_installation_proposal(
  "r-lib/pkgdepends",
  config = list(library = tempfile()))
pdi

## -----
## Method `pkg_installation_proposal$get_refs`
## -----

pdi <- new_pkg_installation_proposal("r-lib/pkgdepends")
pdi$get_refs()

## -----
## Method `pkg_installation_proposal$get_config`

```

```

## -----

pdi <- new_pkg_installation_proposal(
  "pak",
  config = list(library = tempfile())
)
pdi$get_config()

## -----
## Method `pkg_installation_proposal$resolve`
## -----

## Not run:
pdi <- new_pkg_installation_proposal(
  "pak",
  config = list(library = tempfile())
)

pdi$resolve()
pdi$get_resolution()

## End(Not run)

## -----
## Method `pkg_installation_proposal$get_resolution`
## -----

## Not run:
pdi <- new_pkg_installation_proposal(
  "r-lib/pkgdepends",
  config = list(library = tempfile())
)
pdi$resolve()
pdi$get_resolution()

## End(Not run)

## -----
## Method `pkg_installation_proposal$get_solve_policy`
## -----

pdi <- new_pkg_installation_proposal(
  "r-lib/pkgdepends",
  config = list(library = tempfile())
)
pdi$get_solve_policy()
pdi$set_solve_policy("upgrade")
pdi$get_solve_policy()

## -----
## Method `pkg_installation_proposal$set_solve_policy`
## -----

```

```

pdi <- new_pkg_installation_proposal(
  "r-lib/pkgdepends",
  config = list(library = tempfile())
)
pdi$get_solve_policy()
pdi$set_solve_policy("upgrade")
pdi$get_solve_policy()

## -----
## Method `pkg_installation_proposal$solve`
## -----

## Not run:
pdi <- new_pkg_installation_proposal(
  "r-lib/pkgdepends",
  config = list(library = tempfile())
)
pdi$resolve()
pdi$solve()
pdi$get_solution()

## End(Not run)

## -----
## Method `pkg_installation_proposal$get_solution`
## -----

## Not run:
pdi <- new_pkg_installation_proposal(
  "r-lib/pkgdepends",
  config = list(library = tempfile())
)
pdi$resolve()
pdi$solve()
pdi$get_solution()

## End(Not run)

## -----
## Method `pkg_installation_proposal$show_solution`
## -----

## Not run:
pdi <- new_pkg_installation_proposal(
  "r-lib/pkgdepends",
  config = list(library = tempfile())
)
pdi$resolve()
pdi$solve()
pdi$get_solution()
pdi$show_solution()

## End(Not run)

```

```

## -----
## Method `pkg_installation_proposal$stop_for_solution_error`
## -----

## Not run:
# This is an error, because the packages conflict:
pdi <- new_pkg_installation_proposal(
  c("r-lib/pak", "cran::pak"),
  config = list(library = tempfile())
)
pdi$resolve()
pdi$solve()
pdi
# This fails:
# pdi$stop_for_solution_error()

## End(Not run)

## -----
## Method `pkg_installation_proposal$draw`
## -----

## Not run:
pdi <- new_pkg_installation_proposal(
  "pak",
  config = list(library = tempfile())
)
pdi$resolve()
pdi$solve()
pdi$draw()

## End(Not run)

## -----
## Method `pkg_installation_proposal$download`
## -----

## Not run:
pdi <- new_pkg_installation_proposal(
  c("r-lib/pak", "cran::pak"),
  config = list(library = tempfile())
)
pdi$resolve()
pdi$solve()
pdi$download()
pdi$get_downloads()

## End(Not run)

## -----
## Method `pkg_installation_proposal$get_downloads`
## -----

```

```
## Not run:
pdi <- new_pkg_installation_proposal(
  c("r-lib/pak", "cran:pak"),
  config = list(library = tempfile())
)
pdi$resolve()
pdi$solve()
pdi$download()
pdi$get_downloads()

## End(Not run)

## -----
## Method `pkg_installation_proposal$get_install_plan`
## -----

## Not run:
pdi <- new_pkg_installation_proposal(
  "pak",
  config = list(library = tempfile())
)
pdi$resolve()
pdi$solve()
pdi$download()
pdi$get_install_plan()

## End(Not run)

## -----
## Method `pkg_installation_proposal$print`
## -----

## Not run:
pdi <- new_pkg_installation_proposal(
  "pak",
  config = list(library = tempfile())
)
pdi

pdi$resolve()
pdi

pdi$solve()
pdi

pdi$download()
pdi

## End(Not run)
```

parse_pkg_refs *Parse package location references*

Description

See [pkg_refs](#) for more about supported package references.

Usage

```
parse_pkg_refs(refs, remote_types = NULL, ...)
```

```
parse_pkg_ref(ref, remote_types = NULL, ...)
```

Arguments

refs	Character vector of references.
remote_types	Custom remote types can be added here, this is for advanced use, and experimental currently.
...	Additional arguments are passed to the individual parser functions.
ref	A package reference, like refs, but a length one vector, for convenience.

Value

parse_pkg_refs() returns a list of parsed references. parse_pkg_ref() returns one parsed reference. A parsed reference is a list, with at least elements:

- ref: The original reference string.
- type: The reference type.
- package: The package name. It typically contains additional data, specific to the various reference types. See [pkg_refs](#) for details. The parsed reference always has class remote_ref_<type> and remote_ref.

pkg_config *Configuration*

Description

Configuration options for several pkgdepends classes. Not all classes use all of these options. E.g. a [pkg_download_proposal](#) is not concerned about package libraries, so it'll ignore the library option.

Details

Options:

- `library`: package library to use for checking already installed packages when considering dependencies in [dependency lookup](#) or [package installation](#). Defaults to the first path in `.libPaths()`.
- `cache_dir`: directory to download the packages to. Defaults to a temporary directory within the R session temporary directory, see `base::tempdir()`.
- `package_cache_dir`: package cache location of `pkgcache::package_cache`. The default is the `pkgcache` default.
- `metadata_cache_dir`: location of metadata replica of `pkgcache::cranlike_metadata_cache`. Defaults to a temporary directory within the R session temporary directory, see `base::tempdir()`.
- `platforms`: Character vector of platforms to *download* or *install* for. Possible platforms are `windows`, `macos` and `source`. Defaults to the current platform, *and* `source`.
- `cran-mirror`: CRAN mirror to use. Defaults to the `repos` option (see `base::options()`), if that's not set then `https://cran.rstudio.com`.
- `dependencies`: Dependencies to consider or download or install. Defaults to the hard dependencies, see `pkg_dep_types_hard()`.
- `r-versions`: Character vector, R versions to download or install packages for. It defaults to the current R version.
- `build-vignettes`: Whether to build vignettes for package trees. This is only used if the package is obtained from a package tree, and not from a source (or binary) package archive. By default vignettes are not built in this case. If you set this to `TRUE`, then you need to make sure that the vignette builder packages are available, as these are not installed by default currently.
- `metadata-update-after`: A time interval as a [difftime](#) object. `pkgdepends` will update the metadata cache if it is older than this. The default is one day.

`pkg_dep_types_hard` *Possible package dependency types*

Description

Hard dependencies are needed for a package to load, soft dependencies are optional.

Usage

```
pkg_dep_types_hard()
```

```
pkg_dep_types_soft()
```

```
pkg_dep_types()
```

Value

A string vector of dependency types, capitalized.

See Also

Other package dependency utilities: [as_pkg_dependencies\(\)](#)

pkg_downloads

Package downloads

Description

The [pkg_download_proposal](#) and [pkg_installation_proposal](#) classes both have download methods, to download package files into a configured directory (see ['Configuration'](#)).

Details

They return a `pkg_download_result` object, which is a data frame (tibble), that adds extra columns to [pkg_resolution_result](#) (for [pkg_download_proposal](#)) or [pkg_solution_result](#) (for [pkg_installation_proposal](#)).

- `fulltarget`: absolute path to the downloaded file. At most one of `fulltarget` and `fulltarget_tree` must exist on the disk.
- `fulltarget_tree`: absolute path to a package tree directory. At most one of `fulltarget` and `fulltarget_tree` must exist on the disk.
- `download_status`: "Had" or "Got", depending on whether the file was obtained from the cache.
- `download_error`: error object for failed downloads.
- `file_size`: Size of the file, or NA. For `installed::` refs, it is NA, and it is also NA for refs that created `fulltarget_tree` instead of `fulltarget`.

`fulltarget`, if it exists, contains a packaged (via R CMD build) source R package. If `fulltarget_tree` exists, it is a package tree directory, that still needs an R CMD build call.

pkg_name_check

Check if an R package name is available.

Description

Additionally, look up the candidate name in a number of dictionaries, to make sure that it does not have a negative meaning.

Usage

```
pkg_name_check(name, dictionaries = NULL)
```

Arguments

name	Package name candidate.
dictionaries	Character vector, the dictionaries to query. Available dictionaries: * wikipedia * wiktionary, * acromine (http://www.nactem.ac.uk/software/acromine/), * sentiment (https://github.com/fnielsen/afinn), * urban (Urban Dictionary). If NULL (by default), the Urban Dictionary is omitted, as it is often offensive.

Details

Valid package name check:

Check the validity of name as a package name. See 'Writing R Extensions' for the allowed package names. Also checked against a list of names that are known to cause problems.

CRAN checks:

Check name against the names of all past and current packages on CRAN, including base and recommended packages.

Bioconductor checks:

Check name against all past and current Bioconductor packages.

Profanity check:

Check name with <https://www.purgomalum.com/service/containsprofanity> to make sure it is not a profanity.

Dictionaries:

See the dictionaries argument.

Value

pkg_name_check object with a custom print method.

Examples

```
## Not run:  
pkg_name_check("cli")  
  
## End(Not run)
```

Description

A package reference (ref) specifies a location from which an R package can be obtained from. The full syntax of a reference is `type: :ref`, but `type` can be often omitted, the common ref types have shortcuts.

Details

Introduction:

The currently supported reference types are:

- `cran`: a CRAN package.
- `bioc`: A Bioconductor package.
- `standard`: a package from CRAN or Bioconductor.
- `github`: A package from GitHub.
- `local`: A local package file or directory.
- `url`: An URL to a package archive.
- `installed`: An installed package.
- `deps`: The dependencies of a local package file or directory.

If a ref does not explicitly specify a type, then the following rules are applied:

- if the ref is a valid `standard` ref type (without the `standard::` prefix), then `standard` is used;
- if the ref is a valid `github` ref type (without the `github::` prefix), then `github` is used;
- if the ref is a GitHub URL, then `github` is used;
- otherwise an error is thrown.

Parameters:

Package refs may have optional parameters, added after a question mark. Different parameters are separated by an ampersand (&) character. Parameters might be binary, or have a string value, assigned with an equal sign (=). If no value is assigned, then we assume the true value. For example these two package refs are the same:

```
cran::testthat?source&nocache
cran::testthat?source=true&nocache=true
```

Currently supported parameters: * `source` is a binary parameter. If specified, then a source R package is requested from a CRAN-like repository. For package installations `source` always triggers a re-install. In other words, `source` implies the `reinstall` parameter. This parameter is supported for `bioc::`, `cran::` and `standard::` remote types, and it is ignore for others. * `reinstall` requests a re-install for package installations. It is supported by the `bioc::`, `cran::`, `github::`, `local::`, `standard::`, and `url::` remote types. * `nocache` will ignore the package cache. It will always download the package file, and it will not add the downloaded (and built) file to the package cache. It is supported by the `bioc::`, `cran::`, `github::`, `standard::` and `url::` remote types.

CRAN packages::

A package from CRAN. Full syntax:

```
[cran::]<package>[@[>=]<version> | current | last]
```

- <package> is a valid package name.
- <version> is a version or a version requirement.

Examples:

```
forecast
forecast@8.8
forecast@>=8.8
cran::forecast
forecast@last
forecast@current
```

Note: pkgdepends currently parses the version specification part (everything after @), but does not use it.

Bioconductor packages::

A package from Bioconductor. The syntax is the same as for CRAN packages, except of the prefix of course:

```
[bioc::]<package>[@[>=]<version> | current | last]
```

Standard packages::

These are packages either from CRAN or Bioconductor, the full syntax is the same as for CRAN packages, except for the prefix:

```
[standard::]<package>[@[>=]<version> | current | last]
```

GitHub packages::

Packages from a GitHub repository. Full syntax:

```
[<package>=][github::]<username>/<repository>[/<subdir>][<detail>]
```

- <package> is the name of the package. If this is missing, then the name of the repository is used.
- <username> is a GitHub username or organization name.
- <repository> is the name of the repository.
- <subdir> optional subdirectory, if the package is within a subdirectory in the repository.
- <detail> specifies a certain version of the package, see below.

<detail> may specify:

- a git branch, tag or (prefix of) a commit hash: @<commitish>;
- a pull request: #<pull-request>; or
- the latest release: @*release.

If <detail> is missing, then the latest commit of the *default* branch is used.

Examples:

```
r-lib/crayon
github::r-lib/crayon
r-lib/crayon@84be6207
r-lib/crayon@branch
r-lib/crayon#41
r-lib/crayon@release
```

For convenience GitHub HTTP URLs can also be used to specify a package from GitHub.

Examples:

```

https://github.com/r-lib/withr
# A branch:
https://github.com/r-lib/withr/tree/ghactions
# A tag:
https://github.com/r-lib/withr/tree/v2.1.1
# A commit:
https://github.com/r-lib/withr/commit/8fbc548e316
# A pull request:
https://github.com/r-lib/withr/pull/76
# A release:
https://github.com/r-lib/withr/releases/tag/v2.1.0

```

A GitHub remote string can also be used instead of an URL, for example: `git@github.com:r-lib/pkgdepends.git`

Local packages::

A path that refers to a package file built with R CMD build, or a directory that contains a package. Full syntax:

```
local::<path>
```

For brevity, you can omit the `local::` prefix, if you specify an absolute path, a path from the user's home directory, starting with `~`, or a relative path starting with `./` or `.\`.

A single dot ("`.`") is considered to be a local package in the current working directory.

Examples:

```

local::/foo/bar/package_1.0.0.tar.gz
local::/foo/bar/pkg
local::.
/absolute/path/package_1.0.0.tar.gz
~/path/from/home
./relative/path
.

```

URLs::

You can use `url::` to refer to URLs that hold R package archives (i.e. properly built with R CMD build), or compressed directories of package trees (i.e. not built with R CMD build). `pkgdepends` will figure out if it needs to run R CMD build on the package first.

This remote type supports `.tar.gz` and `.zip` files.

Note that URLs are not ideal remote types, because `pkgdepends` needs to download the package file to resolve its dependencies. When this happens, it puts the package file in the cache, so no further downloads are needed when installing the package later.

Examples:

```

url::https://cloud.r-project.org/src/contrib/Archive/cli/cli_1.0.0.tar.gz
url::https://github.com/tidyverse/stringr/archive/HEAD.zip

```

Installed packages::

This is usually used internally, but can also be used directly. Full syntax:

```
installed::<path>/<package>
```

- `<path>` is the library the package is installed to.
- `<package>` is the package name.

Example:

```
installed::~~/R/3.6/crayon
```

Package dependencies::

Usually used internally, it specifies the dependencies of a local package. It can be used to download or install the dependencies of a package, without downloading or installing the package itself. Full syntax:

```
deps::<path>
```

Examples:

```
deps::/foo/bar/package_1.0.0.tar.gz
```

```
deps::/foo/bar/pkg
```

```
deps::.
```

pkg_resolution

Dependency resolution

Description

Collect information about dependencies of R packages, recursively.

Details

[pkg_deps](#), [pkg_download_proposal](#) and [pkg_installation_proposal](#) all resolve their dependencies recursively, to obtain information about all packages needed for the specified [package references](#).

CRAN and Bioconductor packages:

Resolution currently start by downloading the CRAN and Bioconductor metadata, if it is out of date. For CRAN, we also download additional metadata, that includes file sizes, SHA hashes, system requirements, and "built" (for binary packages) and "packaged" time stamps. The extra meta information is updated daily currently, so for some packages it might be incorrect or missing.

GitHub packages:

For GitHub packages, we query their download URL to be able to download the package later, and also download their DESCRIPTION file, to learn about their dependencies.

Local packages:

From local package files we extract the DESCRIPTION file, to learn about their dependencies.

The remotes field in DESCRIPTION:

We support the non-standard Remotes field in the package DESCRIPTION file. This field may contain a list of package references for any of the dependencies that are specified in one of the Depends, Includes, Suggests or Enhances fields. The syntax is a comma separated list of [package references](#).

The result:

The result of the resolution is a data frame (tibble) with lots of information about the packages and their dependencies. The columns that are not documented here may be removed or changed, because they are either used internally or experimental.

- **built**: The `Built` field from the `DESCRIPTION` file of binary packages, for which this information is available.
- **cache_status**: Whether the package file is in the package cache. It is `NA` for `installed::package refs`.
- **dep_types**: Character vector of dependency types that were considered for this package. (This is a list column.)
- **deps**: Dependencies of the package, in a data frame (tibble). See 'Package dependency tables' below.
- **direct**: Whether this package (ref, really) was directly specified, or added as a dependency.
- **error**: This is a list column that contains error objects for the refs that `pkgdepends` failed to resolve.
- **filesize**: The file size in bytes, or `NA` if this information is not available.
- **license**: License of the package, or `NA` if not available.
- **md5sum**: MD5 checksum of the package file, if available, or `NA` if not.
- **metadata**: A named character vector. These fields will be (should be) added to the installed `DESCRIPTION` file of the package.
- **mirror**: URL of the CRAN(-like) mirror site where the metadata was obtained from. It is `NA` for non-CRAN-like sources, e.g. local files, installed packages, GitHub, etc.
- **needscompilation**: Whether the package needs compilation.
- **package**: Package name.
- **priority**: This is "base" for base packages, "recommended" for recommended packages, and `NA` otherwise.
- **ref**: Package reference.
- **remote**: The parsed `remote_ref` objects, see `parse_pkg_refs()`. This is a list column.
- **reporidir**: The directory where this package should be in a CRAN-like repository.
- **sha256**: SHA256 hash of the package file, if available, otherwise `NA`.
- **sources**: URLs where this package can be downloaded from. This is a zero length vector for `installed:: refs`.
- **status**: Status of the dependency resolution, "OK" or "FAILED".
- **target**: Path where this package should saved in a CRAN-repository.
- **type**: Ref type.
- **version**: Package version.

Package dependency tables:

A package dependency table has five columns currently:

- **ref**: The package ref of the dependency.
- **type**: The dependency type, in all lowercase. I.e. `imports`, `suggests`, etc.
- **op**: Operator for version requirements, e.g. `>=`.
- **version**: Version number, for version requirements.

Resolution failures:

The resolution process does not stop on error. Instead, failed resolutions return and error object in the error column of the result data frame.

Description

If you use these in R, make sure you specify `perl = TRUE`, see [base::grep\(\)](#).

Usage

```
pkg_rx()
```

Details

Currently included:

- `pkg_name`: A valid package name.
- `type_cran`: A `cran::` package reference.
- `type_bioc`: A `bioc::` package reference.
- `type_standard`: A `standard::` package reference.
- `type_github`: A `github::` package reference.
- `type_local`: A `local::` package reference.
- `type_deps`: A `deps::` package reference.
- `type_installed`: An `installed::` package reference.
- `github_username`: A GitHub username.
- `github_repo`: A GitHub repository name.
- `github_url`: A GitHub URL.

Value

A named list of strings.

Examples

```
pkg_rx()
```

Description

The dependency solver takes the resolution information, and works out the exact versions of each package that must be installed, such that version and other requirements are satisfied.

Details

Solution policies:

The dependency solver currently supports two policies: `lazy` and `upgrade`. The `lazy` policy prefers to minimize installation time, and it does not perform package upgrades, unless version requirements require them. The `upgrade` policy prefers to update all package to their latest possible versions, but it still considers that version requirements.

The integer problem:

Solving the package dependencies requires solving an integer linear problem (ILP). This subsection briefly describes how the problem is represented as an integer problem, and what the solution policies exactly mean.

Every row of the package resolution is a candidate for the dependency solver. In the integer problem, every candidate corresponds to a binary variable. This is 1 if that candidate is selected as part of the solution, and 0 otherwise.

The objective of the ILP minimization is defined differently for different solution policies. The ILP conditions are the same.

1. For the `lazy` policy, installed:: packaged get 0 points, binary packages 1 point, sources packages 5 points.
2. For the `'upgrade'` policy, we rank all candidates for a given package according to their version numbers, and assign more points to older versions. Points are assigned by 100 and candidates with equal versions get equal points. We still prefer installed packages to binaries to source packages, so also add 0 point for already installed candidates, 1 extra points for binaries and 5 points for source packages.
3. For directly specified refs, we aim to install each package exactly once. So for these we require that the variables corresponding to the same package sum up to 1.
4. For non-direct refs (i.e. dependencies), we require that the variables corresponding to the same package sum up to at most one. Since every candidate has at least 1 point in the objective function of the minimization problem, non-needed dependencies will be omitted.
5. For direct refs, we require that their candidates satisfy their references. What this means exactly depends on the ref types. E.g. for CRAN packages, it means that a CRAN candidate must be selected. For a standard ref, a GitHub candidate is OK as well.
6. We rule out candidates for which the dependency resolution failed.
7. We go over all the dependency requirements and rule out packages that do not meet them. For every package A, that requires package B, we select the $B(i, i=1..k)$ candidates of B that satisfy A's requirements and add a $A - B(1) - \dots - B(k) \leq 0$ rule. To satisfy this rule, either we cannot install A, or if A is installed, then one of the good B candidates must be installed as well.

8. We rule out non-installed CRAN and Bioconductor candidates for packages that have an already installed candidate with the same exact version.
9. We also rule out source CRAN and Bioconductor candidates for packages that have a binary candidate with the same exact version.

Explaining why the solver failed:

To be able to explain why a solution attempt failed, we also add a dummy variable for each directly required package. This dummy variable has a very large objective value, and it is only selected if there is no way to install the directly required package.

After a failed solution, we look the dummy variables that were selected, to see which directly required package failed to solve. Then we check which rule(s) ruled out the installation of these packages, and their dependencies, recursively.

The result:

The result of the solution is a `pkg_solution_result` object. It is a named list with entries:

- `status`: Status of the solution attempt, "OK" or "FAILED".
- `data`: The selected candidates. This is very similar to a `pkg_resolution_result` object, but it has two extra columns:
 - `lib_status`: status of the package in the library, after the installation. Possible values: `new` (will be newly installed), `current` (up to date, not installed), `update` (will be updated), `no-update` (could update, but will not).
 - `old_version`: The old (current) version of the package in the library, or NA if the package is currently not installed.
- `problem`: The ILP problem. The exact representation is an implementation detail, but it does have an informative print method.
- `solution`: The return value of the internal solver.

Index

- * **package dependency utilities**
 - as_pkg_dependencies, 6
 - pkg_dep_types_hard, 41
- * **platform functions**
 - current_r_platform, 7
- 'Configuration', 7, 11, 12, 19, 20, 24–26, 28, 42
- 'Dependency resolution', 12, 20, 28, 29
- 'Installation plans', 7, 8, 33
- 'Package references', 10, 11, 18, 19, 26, 28
- 'The dependency solver', 11, 13, 28–30
- .libPaths(), 41
- “Configuration”, 5
- “Dependency resolution”, 5
- “Installation plans”, 5
- “Package references”, 3
- “The dependency solver”, 5
- as_pkg_dependencies, 6, 42
- base::grep(), 49
- base::options(), 41
- base::tempdir(), 41
- cli::tree(), 14, 32
- current_r_platform, 7
- default_platforms(current_r_platform), 7
- dependency lookup, 41
- difftime, 41
- downloading, 8
- install_package_plan, 7
- install_package_plan(), 8, 33
- install_plans, 8
- installation proposal, 8
- is_valid_package_name, 9
- lib_status, 10
- new_pkg_deps, 10
- new_pkg_download_proposal, 18
- new_pkg_installation_plan, 24
- new_pkg_installation_proposal, 26
- package installation, 41
- package reference, 8
- package references, 5, 47
- parse_pkg_ref(parse_pkg_refs), 40
- parse_pkg_refs, 40
- parse_pkg_refs(), 48
- pkg_config, 40
- pkg_dep_types(pkg_dep_types_hard), 41
- pkg_dep_types_hard, 7, 41
- pkg_dep_types_hard(), 6, 41
- pkg_dep_types_soft(pkg_dep_types_hard), 41
- pkg_deps, 4, 5, 10, 47
- pkg_deps(new_pkg_deps), 10
- pkg_download_proposal, 4, 5, 18, 40, 42, 47
- pkg_download_proposal(new_pkg_download_proposal), 18
- pkg_download_result, 8, 21, 33
- pkg_download_result(pkg_downloads), 42
- pkg_downloads, 42
- pkg_installation_plan(new_pkg_installation_plan), 24
- pkg_installation_proposal, 5, 8, 24, 26, 42, 47
- pkg_installation_proposal(new_pkg_installation_proposal), 26
- pkg_name_check, 42
- pkg_refs, 40, 44
- pkg_resolution, 47
- pkg_resolution_result, 12, 20, 29, 42, 51
- pkg_resolution_result(pkg_resolution), 47
- pkg_rx, 49
- pkg_solution, 50

pkg_solution_result, [14](#), [31](#), [42](#)
pkg_solution_result(pkg_solution), [50](#)
pkgcache::cranlike_metadata_cache, [41](#)
pkgcache::package_cache, [41](#)
pkgdepends(pkgdepends-package), [2](#)
pkgdepends-package, [2](#)
pkgdepends::pkg_installation_proposal,
[24](#)

solving, [8](#)

utils::install.packages(), [6](#)