

Package ‘rivnet’

April 21, 2023

Type Package

Title Extract and Analyze Rivers from Elevation Data

Version 0.2.0

Description Seamless extraction of river networks from digital elevation models data. The package allows analysis of digital elevation models that can be either externally provided or downloaded from open source repositories (thus interfacing with the 'elevatr' package). Extraction is performed via the 'D8' flow direction algorithm of TauDEM (Terrain Analysis Using Digital Elevation Models), thus interfacing with the 'traudem' package. Resulting river networks are compatible with functions from the 'OCNet' package.

Imports spam, raster, sf, terra, traudem, elevatr, OCNet (>= 1.0.0), methods, Rcpp (>= 1.0.9)

License MIT + file LICENSE

Encoding UTF-8

Suggests knitr, rmarkdown, bookdown

VignetteBuilder knitr

URL <https://lucarraro.github.io/rivnet/>

LinkingTo Rcpp

NeedsCompilation yes

Author Luca Carraro [cre, aut],
University of Zurich [cph, fnd]

Maintainer Luca Carraro <luca.carraro@hotmail.it>

Repository CRAN

Date/Publication 2023-04-21 10:10:03 UTC

R topics documented:

rivnet-package 2

aggregate_river	2
covariate_river	3
extract_river	5
hydro_river	8
locate_site	11
paths_river	13
path_velocities_river	13
plot	15
river-class	16
river_to_igraph	17
river_to_SSN	18

Index 19

rivnet-package	<i>Extract and Analyze Rivers from Elevation Data.</i>
----------------	--

Description

Seamless extraction of river networks from digital elevation models data. The package allows analysis of digital elevation models that can be either externally provided or downloaded from open source repositories (thus interfacing with the `elevatr` package). Extraction is performed via the 'D8' flow direction algorithm of TauDEM (Terrain Analysis Using Digital Elevation Models), thus interfacing with the `traudem` package. Resulting river networks are compatible with functions from the `OCNet` package.

Author(s)

Luca Carraro (<luca.carraro@hotmail.it>)

aggregate_river	<i>Aggregate a river</i>
-----------------	--------------------------

Description

Aggregates a river

Usage

```
aggregate_river(river, ...)
```

Arguments

river	A river object.
...	Further arguments to be passed to <code>aggregate_OCN</code> .

Details

This is an alias to [aggregate_OCN](#).

Value

A river object. See [aggregate_OCN](#) for description of its structure.

Examples

```
fp <- system.file("extdata/wigger.tif", package="rivnet")
r <- extract_river(outlet=c(637478,237413),
DEM=fp)
r <- aggregate_river(r)
```

covariate_river	<i>Attribute covariates to nodes of a river network</i>
-----------------	---

Description

Attributes covariate values from raster files to subcatchments of a river object. Both local and upstream-averaged covariate values are calculated.

Usage

```
covariate_river(x, river, categorical = TRUE, overwrite = FALSE)
```

Arguments

x	SpatRaster object (obtained via <code>rast</code>) containing categorical or continuous variables from which covariates are computed. Its coordinate system must be the same of <code>river</code> . Consider using <code>terra::project</code> to change coordinate system.
river	river object. It must have been aggregated (via <code>aggregate_river</code>).
categorical	Logical. Is the covariate categorical (e.g. land cover classes)? If <code>x</code> consists of several layers, it is possible to specify <code>categorical</code> as a vector of logicals (one per each layer); alternatively, the single value of <code>categorical</code> is applied to all layers of <code>x</code> .
overwrite	Logical. If TRUE, overwrite previously calculated covariates.

Details

If `categorical = TRUE`, the number of columns of `SC$locCov`, `SC$upsCov` is equal to the number of unique values of `x` within the catchment. Column names are composed as "`y_z`", where `y = names(x)` and `z` are the unique values of `x`. Values correspond to the fraction of pixels (FD nodes) within the local/upstream area that are covered by a given category (e.g., land cover type).

If `categorical = FALSE`, `SC$locCov` and `SC$upsCov` have a single column named `names(x)`. Values correspond to the mean covariate value within the local/upstream reference area.

If `x` has multiple layers, columns in the data frames are added sequentially. The same occurs if `covariate_river` is run repeated times (for instance, to compute covariates for one `SpatRaster` object at a time) when `overwrite = FALSE`.

Value

A river object. The following elements are added:

<code>SC\$locCov</code>	Data frame of covariates evaluated as local values for each subcatchment (i.e., mean covariate value within a catchment).
<code>SC\$upsCov</code>	Data frame of covariates evaluated as upstream-averaged values for each subcatchment (i.e., mean covariate value within the area upstream of a given subcatchment, including the subcatchment itself).

See Also

[rast](#), [project](#)

Examples

```
fp <- system.file("extdata/wigger.tif", package="rivnet")
river <- extract_river(outlet=c(637478,237413),
                      DEM=fp)
river <- aggregate_river(river)

# land cover raster file (categorical)
r1 <- terra::rast(system.file("extdata/landcover.tif", package="rivnet"))
# legend: 1-urban; 2-agriculture; 3-forest; 4-improductive

river <- covariate_river(r1, river)

plot(river$SC$locCov[, 1], river) # fraction of urban area within a subcatchment
plot(river$SC$upsCov[, 1], river) # fraction of upstream-averaged urban area

# mean air temperature raster file (continuous)
r2 <- terra::rast(system.file("extdata/temperature.tif", package="rivnet"))

river <- covariate_river(r2, river, categorical = FALSE)

plot(river$SC$locCov[, 5], river) # the layer has been added after the 4 previous ones
```

```
names(river$SC$locCov)
```

extract_river	<i>Extract a river</i>
---------------	------------------------

Description

Function that extracts a river network from elevation data via TauDEM's D8 flow direction algorithm. It can return a river object and/or output from TauDEM functions as a raster file. Elevation data can be either downloaded from the web or provided externally.

Usage

```
extract_river(outlet, EPSG=NULL, ext=NULL, z=NULL, DEM=NULL,
  as.river=TRUE, as.rast=FALSE, filename=NULL, showPlot=FALSE,
  threshold_parameter=1000, n_processes=1, displayUpdates=FALSE, src="aws")
```

Arguments

outlet	A vector, matrix or data frame expressing the coordinates of the river outlet(s) (in the coordinate system identified by EPSG, or the same as in DEM, if the latter is provided). If a vector, the odd components identify the longitudinal (x) coordinates, and the even components the latitudinal (y) coordinates. If a matrix, it should have 2 columns (for x and y coordinates respectively) and number of rows equal to the number of outlets. If a data frame, it should have components outlet\$x, outlet\$y identifying the respective coordinates.
EPSG	EPSG code identifying the coordinate system used. See https://epsg.org/ . It is required if DEM is not specified, and not used otherwise. It is recommended to use projected coordinate systems, so that lengths and areas in the river object are in metric units.
ext	Vector expressing the extent of the region where elevation data are downloaded. It must be in the form c(xmin, xmax, ymin, ymax). Coordinates must be expressed in the coordinate system identified by EPSG. It is required if DEM is not specified, and not used otherwise.
z	Zoom level at which elevation data should be downloaded. See <code>get_elev_raster</code> for details. It is required if DEM is not specified, and not used otherwise.
DEM	Filename of the Digital Elevation Model raster file to be used.
as.river	Logical. Should a river object be created?
as.rast	Logical. Should a raster file containing results from <code>traudem</code> functions output be created?

filename	Filename of the raster file produced if <code>as.rast=TRUE</code> . Only required if <code>as.rast=TRUE</code> . It can be a single filename, or four filenames, in which case four different raster files are produced. See Details.
showPlot	Logical. Should a plot of the calculated contributing area and extracted catchment contour be produced?
threshold_parameter	Value passed to <code>taudem_threshold</code> . See example and ‘traudem’ documentation for details.
n_processes	Value passed to the <code>traudem</code> functions.
displayUpdates	Logical. If <code>FALSE</code> console output is suppressed (barring some messages from <code>elevatr::get_elev_raster</code> , if DEM is not provided). If <code>TRUE</code> , console output from <code>elevatr::get_elev_raster</code> and <code>traudem</code> functions is displayed.
src	Value passed to <code>get_elev_raster</code> .

Details

This is a wrapper to `elevatr` and `traudem` functions, allowing a seamless extraction of river networks from elevation data. The output river object is compatible with OCN functions (it is equivalent to an OCN produced by `landscape_OCN`).

The workflow of TauDEM commands used is as follows: `PitRemove` -> `D8FlowDir` -> `D8ContributingArea` -> `StreamDefByThreshold` -> `MoveOutletsToStreams` -> `D8ContributingArea`. See <https://hydrology.usu.edu/taudem/taudem5/index.html> for details on TauDEM.

When `as.rast = TRUE`, a raster file is returned. It consists of four layers:

- fel** pit-filled elevation data
- p** D8 flow directions
- ad8** contributing area for the whole region
- ssa** contributing area with respect to the outlet(s) used

The raster file is written via `terra::writeRaster`.

If nested outlets are specified, the function ignores the upstream outlet.

Value

A river object. See `create_OCN`, `landscape_OCN` for description of its structure.

See Also

[get_elev_raster](#), [taudem_threshold](#), [create_OCN](#), [landscape_OCN](#).

Examples

```
# extract the river Wigger (Switzerland) from DEM raster file
# outlet coordinates are expressed in the CH1903/LV03 coordinate system
# (i.e. same as the DEM file)
fp <- system.file("extdata/wigger.tif", package="rivnet")
```

```
r <- extract_river(outlet=c(637478,237413),
DEM=fp)
r

# same as above but download DEM data via elevatr
r <- extract_river(outlet=c(637478,237413),
EPSG=21781, #CH1903/LV03 coordinate system
ext=c(6.2e5,6.6e5,2e5,2.5e5),
z=8)

# enhance resolution by increasing zoom
r2 <- extract_river(outlet=c(637478,237413),
EPSG=21781, #CH1903/LV03 coordinate system
ext=c(6.2e5,6.6e5,2e5,2.5e5),
z=9)
plot(r)
plot(r2)

# specify two outlets as a data frame
r <- extract_river(outlet=data.frame(x=c(637478,629532),y=c(237413,233782)),
EPSG=21781, #CH1903/LV03 coordinate system
ext=c(6.2e5,6.6e5,2e5,2.5e5),
z=10, showPlot=TRUE)

plot(r)

r <- aggregate_river(r)
plot(r, chooseCM = 2) # display only the second catchment
# (i.e. that identified by the second outlet)

# effect of threshold_parameter
r <- extract_river(outlet = c(637478, 237413),
EPSG = 21781, #CH1903/LV03 coordinate system
ext = c(6.2e5, 6.6e5, 2e5, 2.5e5),
z = 8, threshold_parameter = 50,
showPlot = TRUE)
plot(r) # if threshold_parameter is too small, the outlet might be located
# in a smaller river reach, and the extracted river network would be too small
# showPlot = TRUE can help identify what is going on

r <- extract_river(outlet = c(637478, 237413),
EPSG = 21781, #CH1903/LV03 coordinate system
ext = c(6.2e5, 6.6e5, 2e5, 2.5e5),
z = 8, threshold_parameter = 1e5,
showPlot = TRUE)
plot(r) # if threshold_parameter is too large, the outlet pixel might not be
```

```
# located at all (for instance, in this case no cells have contributing area
# above threshold_parameter), hence throwing an error
```

hydro_river

Assign hydraulic variables to a river network

Description

Assign hydraulic variables (width, water depth, discharge, water velocity, ...) across a river object from measured values based on scaling relationships and/or uniform flow equations.

Usage

```
hydro_river(x, river, level = "AG", leopold = TRUE,
  expWidth = 0.5, expDepth = 0.4, expQ = 1,
  crossSection = "natural", ks = 30, minSlope = NULL)
```

Arguments

x	Data frame containing measured hydraulic variables. It must consist of columns data (numeric values of width in m, depth in m or discharge in $m^3 s^{-1}$), type (containing the variable type: width ("w"), depth ("d") or discharge ("Q")), and node (ID of AG or RN nodes to where data have been measured). See details.
river	river object. It must have been aggregated (via <code>aggregate_river</code>).
level	Aggregation level at which the nodes in <code>x\$node</code> are defined and at which hydraulic variables are calculated. Possible values are "RN", "AG". See OCNet for details.
leopold	Logical. Should scaling relationships of hydraulic variables with drainage area (in the spirit of Leopold and Maddock, 1953) be preferred over uniform flow (Gauchler-Strickler/Manning) relationships? See details.
expWidth	Exponent for the scaling relationship of width to drainage area. See details.
expDepth	Exponent for the scaling relationship of depth to drainage area. See details.
expQ	Exponent for the scaling relationship of discharge to drainage area. See details.
crossSection	Shape of the river cross-section (constant across the river network). Possible values are "rectangular", "natural", or a numeric value indicating the exponent of the width-depth relationship. See details.
ks	Roughness coefficient according to Gauchler-Strickler (in $m^{1/3}s^{-1}$). It is the inverse of Manning's roughness coefficient. It can be a single value (thus assumed constant for the whole river network), or a vector of length equal to the number of nodes at the specified level (one roughness coefficient value for each corresponding node).
minSlope	Minimum slope value, replacing null or NaN values of slope in the river object. If NULL, it is assumed equal to either <code>river\$slope0</code> (if the river is an OCN) or to the minimum positive slope value at the selected level.

Details

This function is a more complete version of `rivergeometry_OCN`.

`x` must consist of at least one width value and one value of either depth or discharge. All values included in `x$data` must be referred to the same time point, so that spatial interpolation can be performed. If the goal is assessing spatio-temporal changes in hydraulic variables, then `hydro_river` must be run independently for each time point. For each node, one cannot specify multiple values of the same variable type. Function `locate_site` can be used to attribute `x$node`.

If `level = "AG"`, the drainage area values used for the power law relationships are calculated as $0.5 * (\text{river}\$AG\$A + \text{river}\$AG\$AReach)$. If `level = "RN"`, `river\$RN\$A` is used.

Width values in `x` are assumed to be measured at the water surface. If a single width value is provided, widths are calculated at all nodes from a power-law relationship on drainage area with exponent `expWidth` and such that width at the measured node is equal to the provided value. If multiple values of width are provided, the function fits a width-drainage area power law on the provided values. In this case, `expWidth` is not used and the output (fitted) width values at the measured nodes are generally different than the observed ones.

Depending on the type of depth and discharge data in `x`, the function behaves in eight different ways:

1. If one depth value and zero discharge values are provided, the Gauchler-Strickler uniform flow relationship (hereafter GS) is applied to find discharge at the node where depth was measured. Discharge values are then attributed to all nodes based on a power-law relationship vs. drainage area (hereafter PL) with exponent `expQ`. Finally, depth values at all nodes are derived from GS.
2. If one discharge value and zero depth values are provided, discharge values are attributed to all nodes based on a PL with exponent `expQ`, and such that the value at the measurement node be equal to the observed one. Depth values at all nodes are then derived from GS.
3. If one discharge and one depth value are provided (not necessarily referred to the same node), discharge values are first attributed as in case 2. If `leopold = TRUE`, depth values are derived from a PL with exponent `expDepth`; conversely, GS is applied.
4. If multiple values of discharge and zero values of depth are provided, discharge values are attributed from a power-law fit on measured values vs. drainage area (heareafter PLF). Depth values are then obtained from GS.
5. If multiple values of depth and zero values of discharge are provided, depth values are obtained by PLF. Discharge values are then calculated from GS.
6. If multiple values of discharge and one value of depth are provided, discharge values are first computed as in case 4. Depth values are then obtained by either PF with exponent `expDepth` (if `leopold = TRUE`), or alternatively via GS.
7. If multiple values of depth and one value of discharge are provided, depth values are first computed as in case 5. Discharge values are then obtained as in case 2 (if `leopold = TRUE`), or alternatively computed from GS.
8. If multiple values of both discharge and depth are provided, discharge values are computed as in case 4, and depth values are computed as in case 5.

Cross-sections are assumed as vertically symmetric. If `crossSection = "natural"`, the relationship between width and depth at a cross-section is expressed by $\text{width} \sim \text{depth}^{0.65}$, as suggested by

Leopold and Maddock (1953) (where width \sim discharge^{0.26} and depth \sim discharge^{0.4}). Assuming crossSection = 0 is equivalent to "rectangular" (width does not depend on depth), while crossSection = 1 corresponds to an isosceles triangular cross-section.

Value

A river object. The following elements are added to the list indicated by level:

width, depth, discharge	Values assigned at all nodes (see Details). Units are m, m, m ³ s ⁽⁻¹⁾ , respectively.
velocity	Values in m s ⁽⁻¹⁾ . Calculated by continuity (i.e., ratio between discharge and cross-sectional area).
volume	Values in m ³ . Calculated as cross-sectional area times length.
hydraulicRadius	Values in m. Calculated as the ratio between cross-sectional area and wetted perimeter.
shearStress	Values in N m ⁽⁻²⁾ . Shear stress exerted at the streambed by waterflow. Calculated as $\gamma \cdot \text{hydraulicRadius} \cdot \text{slope}$, where $\gamma = 9806 \text{ N m}^{(-3)}$ is the specific weight of water.

See Also

[aggregate_river](#), [locate_site](#), [rivergeometry_OCN](#).

Examples

```
fp <- system.file("extdata/wigger.tif", package="rivnet")
river <- extract_river(outlet=c(637478,237413),
                      DEM=fp)
river <- aggregate_river(river)

data <- c(12.8, 6.7, 3.3, 1.1, 9.5, 0.8)
type <- c("w", "w", "w", "w", "Q", "d")
node <- c(46, 109, 181, 145, 46, 46) # assume these have been found via locate_site

x <- data.frame(data=data, type=type, node=node)

river1 <- hydro_river(x, river) # case 3
river2 <- hydro_river(x, river, leopold = FALSE) # case 3 (depth calculated via GS)

plot(0.5*(river1$AG$A + river1$AG$AReach), river1$AG$depth) # Power law with exponent 0.4
plot(0.5*(river2$AG$A + river2$AG$AReach),
     river2$AG$depth) # Higher depths in reaches with small slope

river3 <- hydro_river(x, river, leopold = FALSE, minSlope = 0.002)
plot(0.5*(river1$AG$A + river1$AG$AReach), river1$AG$depth) # Variability is reduced
```

```
river <- hydro_river(x[-5, ], river) # case 1
river <- hydro_river(x[-6, ], river) # case 2
```

locate_site

Locate site in a river

Description

Finds location of a site (with coordinates X, Y) within a river object.

Usage

```
locate_site(X, Y=NULL, river, euclidean = TRUE, showPlot = FALSE,
            xlim = NULL, ylim = NULL)
```

Arguments

X	Either a list or a numeric value. If X is a list, it must contain the longitudinal and latitudinal coordinates of the site in columns x (or X) and y (or Y), respectively. If numeric, it represents the longitudinal coordinate of the site. Coordinate values must be given in the same coordinate system as the river object.
Y	Latitudinal coordinate of the site. If X is a list, it can contain the river object.
river	river object where the site is to be located. It must have been aggregated (via aggregate_river).
euclidean	Logical. Should the location of the site in the river be attributed "as the crow flies"? If FALSE, the downstream path from (X, Y) is followed until the river network is met.
showPlot	Logical. Should a close-up of the relocated site be shown?
xlim, ylim	Ranges of x- and y-axis limits for the plot. Only active if showPlots = TRUE.

Details

This function identifies the node in the river network (at the RN and AG levels) that is closest to an arbitrary site of coordinates X, Y. Only a single site can be processed per function call.

Desired coordinates X, Y can be found in an interactive way by clicking on the river map and using function locator.

Nodes at the RN level thus found can be defined as new breakpoints for reaches (see aggregate_OCN and argument breakpoints).

Value

A list with objects:

FDode	index at the FD level of the node that is closest to (X, Y). This is generally not a node that belongs to the river network.
distance	The distance between FDnode and RNnode, expressed either as Euclidean distance (if <code>euclidean = TRUE</code>), or as downstream distance alternatively.
RNode	index at the RN level of the relocated site.
AGode	index at the AG level of the relocated site.

See Also

[aggregate_OCN](#), [locator](#)

Examples

```
fp <- system.file("extdata/wigger.tif", package = "rivnet")
r <- extract_river(outlet = c(637478, 237413),
                  DEM = fp)
r <- aggregate_river(r)

X <- 641329; Y <- 227414
locate_site(X, Y, r, showPlot = TRUE) # as the crow flies
locate_site(X, Y, r, showPlot = TRUE, euclidean = FALSE) # follow downstream path

# define X, Y by clicking on the map
if (interactive()) {
fp <- system.file("extdata/wigger.tif", package = "rivnet")
r <- extract_river(outlet = c(637478, 237413),
                  DEM = fp)
r <- aggregate_river(r)
plot(r)

point <- locator(1) # click on the map to define point
locate_site(point$X, point$Y, r)

# alternative: specify X as a list and pass river as second argument
locate_site(point, r)
}
```

paths_river	<i>Find paths in a river</i>
-------------	------------------------------

Description

Find paths in a river

Usage

```
paths_river(river, ...)
```

Arguments

river	A river object.
...	Further arguments to be passed to paths_OCN.

Details

This is an alias to [paths_OCN](#).

Value

A river object. See paths_OCN for description of its structure.

Examples

```
fp <- system.file("extdata/wigger.tif", package="rivnet")
r <- extract_river(outlet=c(637478,237413),
DEM=fp)
r <- aggregate_river(r)
r <- paths_river(r)
```

path_velocities_river	<i>Calculate velocities along paths in a river</i>
-----------------------	--

Description

Calculate mean water velocities along paths in a river object.

Usage

```
path_velocities_river(river, level = c("RN", "AG"),
displayUpdates = FALSE)
```

Arguments

river	A river object. It must have been aggregated (via <code>aggregate_river</code>), and contain paths (via <code>paths_river</code> with <code>includeDownstreamNode = TRUE</code>) and velocities (via <code>hydro_river</code> or <code>rivergeometry_OCN</code>) at the desired aggregation level(s). See <code>level</code> .
level	Aggregation level(s) at which path velocities should be calculated. Possible values are "RN", "AG", <code>c("RN", "AG")</code> .
displayUpdates	Logical. State if updates are printed on the console while <code>path_velocities_river</code> runs.

Details

Velocities are calculated by dividing the total distance (length of the downstream path joining two nodes) by the total time (sum of times taken to cover all nodes in between the origin and destination nodes; such times are calculated as `length/velocity`).

Note that paths may or may not include the downstream node; this is controlled by option `includeDownstreamNode` in `paths_river`. Path velocities are calculated accordingly. In both cases, diagonal entries of `pathVelocity` are set equal to the respective node velocity. See example.

Value

A river object. The following element is added to the list indicated by `level`:

`pathVelocities` It is a spam object. `pathVelocities[i, j]` is the mean water velocity along the downstream path from nodes `i` to `j`, and is null if the two nodes are not connected by such a path.

See Also

[paths_river](#), [hydro_river](#), [rivergeometry_OCN](#).

Examples

```
fp <- system.file("extdata/wigger.tif", package="rivnet")
river <- extract_river(outlet=c(637478,237413),
                     DEM=fp)
river <- aggregate_river(river)
river <- paths_river(river, includePaths = TRUE)
river <- OCNNet::rivergeometry_OCN(river) # simplified alternative to hydro_river
                                           # to attribute velocities at all RN and AG nodes

river <- path_velocities_river(river, level = "AG") # downstream nodes are not included in paths
river$AG$pathVelocities[176, 176]
river$AG$pathVelocities[176, 174]
# node 174 is immediately downstream of 176; if downstream nodes are not included
# in paths, the two velocities are equal
```

```

river2 <- paths_river(river, includePaths = TRUE, includeDownstreamNode = TRUE)
river2 <- path_velocities_river(river2, level = "AG") # now downstream nodes are included in paths
river2$AG$pathVelocities[176, 176]
river2$AG$pathVelocities[176, 174]

```

plot

Plot a river

Description

Plots a river object

Usage

```

## S4 method for signature 'river,numeric'
plot(x, y, type, ...)
## S4 method for signature 'numeric,river'
plot(x, y, type, ...)
## S4 method for signature 'river,missing'
plot(x, type, ...)

```

Arguments

x	A river object (or a numeric vector if y is a river).
y	A numeric vector to be displayed (or a river if x is a numeric vector). It is equivalent to theme in draw_subcatchments_OCN and draw_thematic_OCN. If y is specified, the river must have been aggregated. See details.
type	Optional argument. If type = "SC" or type = "subcatchments", draw_subcatchments_OCN is used (provided that the river object is aggregated); if type = "elev2D", draw_elev2D_OCN is used; alternatively, draw_thematic_OCN is used.
...	Arguments passed to the plotting functions draw_simple_OCN, draw_contour_OCN, draw_thematic_OCN. See details.

Details

This is an interface to the plotting functions `draw_simple_OCN`, `draw_elev2D_OCN`, `draw_contour_OCN`, `draw_subcatchments_OCN`, `draw_thematic_OCN`. If the river object does not have an elevation field (i.e., it has been generated by `create_OCN` or `create_general_contour_OCN`, but `landscape_OCN` has not been run), the plotting function used is `draw_simple_OCN`. If the elevation field is present, but the river has not been aggregated (via `aggregate_OCN` or `aggregate_river`), the default plotting function used is `draw_contour_OCN`. If the river has been aggregated, `draw_subcatchments_OCN` or `draw_thematic_OCN` are used depending on type. Elevation maps can be produced with type = "elev2D", regardless of whether the river has been aggregated.

See Also

[draw_simple_OCN](#), [draw_elev2D_OCN](#), [draw_contour_OCN](#), [draw_subcatchments_OCN](#), [draw_thematic_OCN](#)

Examples

```
fp <- system.file("extdata/wigger.tif", package="rivnet")
r <- extract_river(outlet=c(637478,237413),
DEM=fp)
plot(r) # equivalent to draw_contour_OCN

r <- aggregate_river(r)
plot(r) # equivalent to draw_thematic_OCN
plot(r, type = "SC") # equivalent to draw_subcatchments_OCN

# equivalent to draw_thematic_OCN with 'theme' specified
plot(r, r$AG$streamOrder, discreteLevels = TRUE)
plot(r$AG$streamOrder, r, discreteLevels = TRUE) # swapping arguments is allowed

# equivalent to draw_subcatchments_OCN with 'theme' specified
plot(r, r$SC$Y, type = "SC", addLegend = FALSE)
plot(r$SC$Y, r, type = "subcatchments", addLegend = FALSE) # swapping arguments is allowed

# plot elevation map
plot(r, type = "elev2D", drawRiver = TRUE)
```

river-class

river class

Description

A river object contains information on river attributes at different aggregation levels. It can represent a real river network (obtained via [extract_river](#)) or an optimal channel network (obtained via [create_OCN](#)).

The content of a river object can be treated as a list, hence its objects and sublists can be accessed with both the \$ and @ operators.

For information on the aggregation levels and on the content of a river object, see [OCNet-package](#).

Examples

```
fp <- system.file("extdata/wigger.tif", package="rivnet")
r <- extract_river(outlet=c(637478,237413),
DEM=fp)
```



```
show(r)
names(r)

# extract or replace parts of a river object
r$dimX
r@dimX
dim <- r[["dimX"]]
r$dimX <- 1
r[["dimX"]]
r[["dimX"]] <- dim
```

river_to_igraph *river_to_igraph*

Description

Transform a river in an igraph object.

Usage

```
river_to_igraph(river, ...)
```

Arguments

river	A river object.
...	Further arguments to be passed to <code>OCN_to_igraph</code> .

Details

This is an alias to [OCN_to_igraph](#).

Value

An igraph object.

Examples

```
fp <- system.file("extdata/wigger.tif", package="rivnet")
r <- extract_river(outlet=c(637478,237413),
DEM=fp)
r <- aggregate_river(r)
g <- river_to_igraph(r, level = "AG")
g
```

river_to_SSN	<i>Transform river into SSN object</i>
--------------	--

Description

Transform a river in a SpatialStreamNetwork object.

Usage

```
river_to_SSN(river, ...)
```

Arguments

river	A river object.
...	Further arguments to be passed to OCN_to_SSN.

Details

This is an alias to [OCN_to_SSN](#).

Value

A SpatialStreamNetwork object if importToR is TRUE, otherwise NULL.

Examples

```
fp <- system.file("extdata/wigger.tif", package="rivnet")
r <- extract_river(outlet=c(637478,237413),
DEM=fp)
r <- aggregate_river(r)
s <- river_to_SSN(r, level = "AG", obsSites = sample(r$AG$nNodes, 10),
path = paste(tempdir(),"/river.ssn", sep = ""), importToR = TRUE)
plot(s)
```

Index

[[,river,character,missing-method (river-class), 16
[[<-,river,character,missing-method (river-class), 16
\$,river-method (river-class), 16
\$<-,river-method (river-class), 16

aggregate_OCN, 3, 12
aggregate_river, 2, 10

covariate_river, 3
create_OCN, 6, 16

draw_contour_OCN, 16
draw_elev2D_OCN, 15, 16
draw_simple_OCN, 16
draw_subcatchments_OCN, 16
draw_thematic_OCN, 16

extract_river, 5, 16

get_elev_raster, 6

hydro_river, 8, 14

landscape_OCN, 6
locate_site, 10, 11
locator, 12

names,river-method (river-class), 16

OCN_to_igraph, 17
OCN_to_SSN, 18
OCNet, 8

path_velocities_river, 13
paths_OCN, 13
paths_river, 13, 14
plot, 15
plot,numeric,river-method (plot), 15
plot,river,missing-method (plot), 15
plot,river,numeric-method (plot), 15
project, 4

rast, 4
river (river-class), 16
river-class, 16
river_to_igraph, 17
river_to_SSN, 18
rivergeometry_OCN, 10, 14
rivnet (rivnet-package), 2
rivnet-package, 2

show,river-method (river-class), 16

taudem_threshold, 6