

Package ‘saemix’

October 10, 2018

Type Package

Title Stochastic Approximation Expectation Maximization (SAEM) Algorithm

Version 2.2

Date 2018-10-05

Author Emmanuelle Comets, Audrey Lavenu, Marc Lavielle (2017) <doi:10.18637/jss.v080.i03>

Maintainer Emmanuelle Comets <emmanuelle.comets@inserm.fr>

Description The SAEMIX package implements the Stochastic Approximation EM algorithm for parameter estimation in (non)linear mixed effects models. The SAEM algorithm: - computes the maximum likelihood estimator of the population parameters, without any approximation of the model (linearisation, quadrature approximation,...), using the Stochastic Approximation Expectation Maximization (SAEM) algorithm, - provides standard errors for the maximum likelihood estimator - estimates the conditional modes, the conditional means and the conditional standard deviations of the individual parameters, using the Hastings-Metropolis algorithm. Several applications of SAEM in agronomy, animal breeding and PKPD analysis have been published by members of the Monolix group (<<http://group.monolix.org/>>).

License GPL (>= 2)

LazyLoad yes

LazyData yes

Suggests testthat (>= 0.3)

Imports graphics, stats, methods

Collate 'aaa_generics.R' 'SaemixData.R' 'SaemixModel.R' 'SaemixRes.R' 'SaemixObject.R' 'compute_LL.R' 'func_FIM.R' 'func_aux.R' 'func_distcond.R' 'func_plots.R' 'func_simulations.R' 'main.R' 'main_estep.R' 'main_initialiseMainAlgo.R' 'main_mstep.R' 'zzz.R'

RoxygenNote 6.1.0

NeedsCompilation no

Repository CRAN

Date/Publication 2018-10-10 16:00:03 UTC

R topics documented:

saemix-package	3
coef.saemix	5
condist.saemix	5
cow.saemix	8
default.saemix.plots	9
fim.saemix	11
fitted.saemix	13
initialize-methods	14
llgq.saemix	17
llis.saemix	19
logLik	20
map.saemix	22
oxboys.saemix	23
PD1.saemix	25
plot,SaemixObject-method	27
plot-methods	30
plot-SaemixData	31
plot-SaemixModel	31
predict-methods	32
print-methods	32
psi-methods	33
resid.saemix	36
saemix	36
saemix.plot.data	38
saemix.plot.select	41
saemix.plot.setoptions	45
saemix.predict	48
saemixControl	49
saemixData	51
SaemixData-class	53
saemixModel	56
SaemixModel-class	58
SaemixObject-class	60
SaemixRes-class	61
show-methods	64
showall-methods	65
simul.saemix	66
subset.SaemixData	67
summary-methods	68
testnpde	69
theo.saemix	70
transformCatCov	72
transformContCov	72
validate.names	73
vcov	74
yield.saemix	74

[.	76
[,SaemixModel-method	77
[,SaemixObject-method	78
[,SaemixRes-method	78
[-methods	79
[<-methods	79

Index	80
--------------	-----------

saemix-package	<i>Stochastic Approximation Expectation Maximization (SAEM) algorithm for non-linear mixed effects models</i>
----------------	---

Description

- Computing the maximum likelihood estimator of the population parameters, without any approximation of the model (linearization, quadrature approximation, . . .), using the Stochastic Approximation Expectation Maximization (SAEM) algorithm
- Estimation of the Fisher Information matrix
- Estimation of the individual parameters
- Estimation of the likelihood
- Plot convergence graphs

Details

Package:	saemix
Type:	Package
Version:	0.9
Date:	2010-09-19
License:	GPL (>=) 1.2
LazyLoad:	yes

The SAEM package includes a number of undocumented functions, which are not meant to be used directly by the user.

default setdefault

computational functions cutoff,cutoff.max, cutoff.eps, cutoff.res, compute.Uy, compute.Uy.nocov, conditional.distribution, gqg.mlx

distributions normcdf, norminv

error model error

sampling trnd.mlx, tpdf.mlx, gammarnd.mlx

parameter transformations transpsi, transphi, dtransphi

Author(s)

Emmanuelle Comets <emmanuelle.comets@inserm.fr>, Audrey Lavenu, Marc Lavielle.

References

Kuhn, E., and Lavielle, M. Maximum likelihood estimation in nonlinear mixed effects models. *Computational Statistics and Data Analysis* 49, 4 (2005), 1020-1038. *Monolix32_UsersGuide.pdf* (<http://software.monolix.org/sdoms/software/>)

See Also

[nlme](#), [SaemixData](#), [SaemixModel](#), [SaemixObject](#), [saemix](#)

Examples

```
data(theo.saemix)

saemix.data<-saemixData(name.data=theo.saemix,header=TRUE,sep=" ",na=NA,
  name.group=c("Id"),name.predictors=c("Dose","Time"),
  name.response=c("Concentration"),name.covariates=c("Weight","Sex"),
  units=list(x="hr",y="mg/L",covariates=c("kg","-")), name.X="Time")

model1cpt<-function(psi,id,xidep) {
  dose<-xidep[,1]
  tim<-xidep[,2]
  ka<-psi[id,1]
  V<-psi[id,2]
  CL<-psi[id,3]
  k<-CL/V
  ypred<-dose*ka/(V*(ka-k))*(exp(-k*tim)-exp(-ka*tim))
  return(ypred)
}

saemix.model<-saemixModel(model=model1cpt,
  description="One-compartment model with first-order absorption",
  psi0=matrix(c(1.,20,0.5,0.1,0,-0.01),ncol=3, byrow=TRUE,dimnames=list(NULL,
  c("ka","V","CL"))),transform.par=c(1,1,1),
  covariate.model=matrix(c(0,1,0,0,0,0),ncol=3,byrow=TRUE),fixed.estim=c(1,1,1),
  covariance.model=matrix(c(1,0,0,0,1,0,0,0,1),ncol=3,byrow=TRUE),
  omega.init=matrix(c(1,0,0,0,1,0,0,0,1),ncol=3,byrow=TRUE), error.model="constant")

saemix.options<-list(seed=632545,save=FALSE,save.graphs=FALSE)

# Not run (strict time constraints for CRAN)
# saemix.fit<-saemix(saemix.model,saemix.data,saemix.options)

# print(saemix.fit)
# plot(saemix.fit)
```

coef.saemix	<i>Extract coefficients from a saemix fit</i>
-------------	---

Description

Extract coefficients from a saemix fit

Usage

```
## S3 method for class 'SaemixObject'
coef(object, ...)
```

Arguments

object	a SaemixObject
...	further arguments to be passed to or from other methods

Value

a list with 3 components:

fixed fixed effects

population a list of population parameters with two elements, a matrix containing the untransformed parameters psi and a matrix containing the transformed parameters phi

individual a list of individual parameters with two elements, a matrix containing the untransformed parameters psi and a matrix containing the transformed parameters phi

condist.saemix	<i>Estimate conditional mean and variance of individual parameters using the MCMC algorithm</i>
----------------	---

Description

When the parameters of the model have been estimated, we can estimate the individual parameters (psi_i).

Usage

```
condist.saemix(saemixObject, nsamp = 1, max.iter = NULL, ...)
```

Arguments

saemixObject	an object returned by the <code>saemix</code> function
nsamp	Number of samples to be drawn in the conditional distribution for each subject. Defaults to 1
max.iter	Maximum number of iterations for the computation of the conditional estimates. Defaults to twice the total number of iterations (<code>sum(saemixObject["options"]\$nbiter.saemix)*2</code>)
...	optional arguments passed to the plots. Plots will appear if the option <code>displayProgress</code> in the <code>saemixObject</code> object is TRUE

Details

Let $\hat{\theta}$ be the estimated value of θ computed with the SAEM algorithm and let $p(\phi_i | y_i; \hat{\theta})$ be the conditional distribution of ϕ_i for $1 \leq i \leq N$. We use the MCMC procedure used in the SAEM algorithm to estimate these conditional distributions. We empirically estimate the conditional mean $E(\phi_i | y_i; \hat{\theta})$ and the conditional standard deviation $sd(\phi_i | y_i; \hat{\theta})$.

See PDF documentation for details of the computation. Briefly, the MCMC algorithm is used to obtain samples from the individual conditional distributions of the parameters. The algorithm is initialised for each subject to the conditional estimate of the individual parameters obtained at the end of the SAEMIX fit. A convergence criterion is used to ensure convergence of the mean and variance of the conditional distributions. When `nsamp > 1`, several chains of the MCMC algorithm are run in parallel to obtain samples from the conditional distributions, and the convergence criterion must be achieved for all chains. When `nsamp > 1`, the estimate of the conditional mean is obtained by averaging over the different samples.

The shrinkage for any given parameter for the conditional estimate is obtained as

$$Sh = 1 - \text{var}(\eta_i) / \omega(\eta)$$

where $\text{var}(\eta_i)$ is the empirical variance of the estimates of the individual random effects, and $\omega(\eta)$ is the estimated variance.

The function adds or modifies the following elements in the results:

cond.mean.phi Conditional mean of the individual distribution of the parameters (obtained as the mean of the samples)

cond.var.phi Conditional variance of the individual distribution of the parameters (obtained as the mean of the estimated variance of the samples)

cond.shrinkage Estimate of the shrinkage for the conditional estimates

cond.mean.eta Conditional mean of the individual distribution of the parameters (obtained as the mean of the samples)

phi.samp An array with 3 dimensions, giving `nsamp` samples from the conditional distributions of the individual parameters

phi.samp.var The estimated individual variances for the sampled parameters `phi.samp`

A warning is output if the maximum number of iterations is reached without convergence (the maximum number of iterations is `saemix.options$nbiter.saemix[2]`).

Author(s)

Emmanuelle Comets <emmanuelle.comets@inserm.fr>, Audrey Lavenu, Marc Lavielle.

References

Comets E, Lavenu A, Lavielle M. Parameter estimation in nonlinear mixed effect models using saemix, an R implementation of the SAEM algorithm. *Journal of Statistical Software* 80, 3 (2017), 1-41.

Kuhn E, Lavielle M. Maximum likelihood estimation in nonlinear mixed effects models. *Computational Statistics and Data Analysis* 49, 4 (2005), 1020-1038.

Comets E, Lavenu A, Lavielle M. SAEMIX, an R version of the SAEM algorithm. 20th meeting of the Population Approach Group in Europe, Athens, Greece (2011), Abstr 2173.

See Also

[SaemixData](#), [SaemixModel](#), [SaemixObject](#), [saemixControl](#), [saemix](#)

Examples

```
data(theo.saemix)

saemix.data<-saemixData(name.data=theo.saemix,header=TRUE,sep=" ",na=NA,
  name.group=c("Id"),name.predictors=c("Dose","Time"),
  name.response=c("Concentration"),name.covariates=c("Weight","Sex"),
  units=list(x="hr",y="mg/L",covariates=c("kg","-")), name.X="Time")

model1cpt<-function(psi,id,xidep) {
  dose<-xidep[,1]
  tim<-xidep[,2]
  ka<-psi[id,1]
  V<-psi[id,2]
  CL<-psi[id,3]
  k<-CL/V
  ypred<-dose*ka/(V*(ka-k))*(exp(-k*tim)-exp(-ka*tim))
  return(ypred)
}

saemix.model<-saemixModel(model=model1cpt,
  description="One-compartment model with first-order absorption",
  psi0=matrix(c(1.,20,0.5,0.1,0,-0.01),ncol=3,byrow=TRUE,dimnames=list(NULL,
  c("ka","V","CL"))),transform.par=c(1,1,1),
  covariate.model=matrix(c(0,1,0,0,0,0),ncol=3,byrow=TRUE),fixed.estim=c(1,1,1),
  covariance.model=matrix(c(1,0,0,0,1,0,0,0,1),ncol=3,byrow=TRUE),
  omega.init=matrix(c(1,0,0,0,1,0,0,0,1),ncol=3,byrow=TRUE), error.model="constant")

saemix.options<-list(seed=632545,save=FALSE,save.graphs=FALSE)

# Not run (strict time constraints for CRAN)
# saemix.fit<-saemix(saemix.model,saemix.data,saemix.options)
```

```
# saemix.fit<-condist.saemix(saemix.fit,nsamp=3)

# First sample from the conditional distribution
# (a N (nb of subject) by nb.etas (nb of parameters) matrix)
# saemix.fit["results"]["phi.samp"][,1]

# Second sample
# saemix.fit["results"]["phi.samp"][,2]
```

 cow.saemix

Evolution of the weight of 560 cows, in SAEM format

Description

cow.saemix contains data from winter wheat experiments.

Usage

```
cow.saemix
```

Format

This data frame contains the following columns:

cow: the id.

time: time (days).

weight: weight of the cow (kg).

birthyear: year of birth (between 1988 and 1998).

twin: existence of a twin (no=1, yes=2).

birthrank: the rank of birth (between 3 and 7).

Details

The data used in this example is the evolution of the weight (in kg) of 560 cows. We have 9 or 10 measurements per subject.

We use an exponential growth model for this data: $y_{ij} = A_i (1 - B_i \exp(-K_i t_{ij})) + \epsilon_{ij}$

Examples

```
data(cow.saemix)
saemix.data<-saemixData(name.data=cow.saemix,header=TRUE,name.group=c("cow"),
  name.predictors=c("time"),name.response=c("weight"),
  name.covariates=c("birthyear","twin","birthrank"),
```



```

units=list(x="days",y="kg",covariates=c("yr","-","-"))

growthcow<-function(psi,id,xidep) {
# input:
# psi : matrix of parameters (3 columns, a, b, k)
# id : vector of indices
# xidep : dependent variables (same nb of rows as length of id)
# returns:
# a vector of predictions of length equal to length of id
x<-xidep[,1]
a<-psi[id,1]
b<-psi[id,2]
k<-psi[id,3]
f<-a*(1-b*exp(-k*x))
return(f)
}
saemix.model<-saemixModel(model=growthcow,
description="Exponential growth model",
psi0=matrix(c(700,0.9,0.02,0,0,0),ncol=3,byrow=TRUE,
dimnames=list(NULL,c("A","B","k"))),transform.par=c(1,1,1),fixed.estim=c(1,1,1),
covariate.model=matrix(c(0,0,0),ncol=3,byrow=TRUE),
covariance.model=matrix(c(1,0,0,0,1,0,0,0,1),ncol=3,byrow=TRUE),
omega.init=matrix(c(1,0,0,0,1,0,0,0,1),ncol=3,byrow=TRUE),error.model="constant")

saemix.options<-list(algorithms=c(1,1,1),nb.chains=1,nbiter.saemix=c(200,100),
seed=4526,save=FALSE,save.graphs=FALSE)

# Plotting the data
plot(saemix.data,xlab="Time (day)",ylab="Weight of the cow (kg)")

# Not run (strict time constraints for CRAN)
# saemix.fit<-saemix(saemix.model,saemix.data,saemix.options)

```

default.saemix.plots *Wrapper functions to produce certain sets of default plots*

Description

These functions produce default sets of plots, corresponding to diagnostic or individual fits.

Usage

```
default.saemix.plots(saemixObject, ...)
```

Arguments

saemixObject an object returned by the [saemix](#) function
... optional arguments passed to the plots

Details

These functions are wrapper functions designed to produce default sets of plots to help the user assess their model fits.

Value

Depending on the type argument, the following plots are produced:

- default.saemix.plots by default, the following plots are produced: a plot of the data, convergence plots, plot of the likelihood by importance sampling (if computed), plots of observations versus predictions, scatterplots and distribution of residuals, boxplot of the random effects, correlations between random effects, distribution of the parameters, VPC
- basic.gof basic goodness-of-fit plots: convergence plots, plot of the likelihood by importance sampling (if computed), plots of observations versus predictions
- advanced.gof advanced goodness-of-fit plots: scatterplots and distribution of residuals, VPC,...
- covariate.fits plots of all estimated parameters versus all covariates in the dataset
- individual.fits plots of individual predictions (line) overlaid on individual observations (dots) for all subjects in the dataset

Author(s)

Emmanuelle Comets <emmanuelle.comets@inserm.fr>, Audrey Lavenu, Marc Lavielle.

References

Comets E, Lavenu A, Lavielle M. Parameter estimation in nonlinear mixed effect models using saemix, an R implementation of the SAEM algorithm. *Journal of Statistical Software* 80, 3 (2017), 1-41.

Kuhn E, Lavielle M. Maximum likelihood estimation in nonlinear mixed effects models. *Computational Statistics and Data Analysis* 49, 4 (2005), 1020-1038.

Comets E, Lavenu A, Lavielle M. SAEMIX, an R version of the SAEM algorithm. 20th meeting of the Population Approach Group in Europe, Athens, Greece (2011), Abstr 2173.

See Also

[saemix](#), [saemix.plot.data](#), [saemix.plot.setoptions](#), [plot.saemix](#)

Examples

```
data(theo.saemix)

saemix.data<-saemixData(name.data=theo.saemix,header=TRUE,sep=" ",na=NA,
  name.group=c("Id"),name.predictors=c("Dose","Time"),
  name.response=c("Concentration"),name.covariates=c("Weight","Sex"),
  units=list(x="hr",y="mg/L",covariates=c("kg","-")), name.X="Time")

model1cpt<-function(psi,id,xidep) {
```

```

    dose<-xidep[,1]
    tim<-xidep[,2]
    ka<-psi[id,1]
    V<-psi[id,2]
    CL<-psi[id,3]
    k<-CL/V
    ypred<-dose*ka/(V*(ka-k))*(exp(-k*tim)-exp(-ka*tim))
    return(ypred)
}

saemix.model<-saemixModel(model=model1cpt,
  description="One-compartment model with first-order absorption",
  psi0=matrix(c(1.,20,0.5,0.1,0,-0.01),ncol=3, byrow=TRUE,
  dimnames=list(NULL, c("ka", "V", "CL"))),transform.par=c(1,1,1),
  covariate.model=matrix(c(0,1,0,0,0,0),ncol=3,byrow=TRUE),fixed.estim=c(1,1,1),
  covariance.model=matrix(c(1,0,0,0,1,0,0,0,1),ncol=3,byrow=TRUE),
  omega.init=matrix(c(1,0,0,0,1,0,0,0,1),ncol=3,byrow=TRUE),error.model="constant")

# Reducing the number of iterations due to time constraints for CRAN
saemix.options<-list(seed=632545,save=FALSE,save.graphs=FALSE,nbiter.saemix=c(100,100))

saemix.fit<-saemix(saemix.model,saemix.data,saemix.options)

default.saemix.plots(saemix.fit)

# Not run (time constraints for CRAN)
# basic.gof(saemix.fit)

# Not run (time constraints for CRAN)
# advanced.gof(saemix.fit)

individual.fits(saemix.fit)

```

fim.saemix

Computes the Fisher Information Matrix by linearisation

Description

Estimate by linearisation the Fisher Information Matrix and the standard error of the estimated parameters.

Usage

```
fim.saemix(saemixObject)
```

Arguments

saemixObject an object returned by the `saemix` function

Details

The inverse of the Fisher Information Matrix provides an estimate of the variance of the estimated parameters θ . This matrix cannot be computed in closed-form for nonlinear mixed-effect models; instead, an approximation is obtained as the Fisher Information Matrix of the Gaussian model deduced from the nonlinear mixed effects model after linearisation of the function f around the conditional expectation of the individual Gaussian parameters. This matrix is a block matrix (no correlations between the estimated fixed effects and the estimated variances).

Value

The function returns an updated version of the object `saemix.fit` in which the following elements have been added:

se.fixed: standard error of fixed effects, obtained as part of the diagonal of the inverse of the Fisher Information Matrix (only when `fim.saemix` has been run, or when the `saemix.options$algorithms[2]` is 1)

se.omega: standard error of the variance of random effects, obtained as part of the diagonal of the inverse of the Fisher Information Matrix (only when `fim.saemix` has been run, or when the `saemix.options$algorithms[2]` is 1)

se.res: standard error of the parameters of the residual error model, obtained as part of the diagonal of the inverse of the Fisher Information Matrix (only when `fim.saemix` has been run, or when the `saemix.options$algorithms[2]` is 1)

fim: Fisher Information Matrix

ll.lin: likelihood calculated by linearisation

Author(s)

Emmanuelle Comets <emmanuelle.comets@inserm.fr>, Audrey Lavenu, Marc Lavielle.

References

Comets E, Lavenu A, Lavielle M. Parameter estimation in nonlinear mixed effect models using `saemix`, an R implementation of the SAEM algorithm. *Journal of Statistical Software* 80, 3 (2017), 1-41.

Kuhn E, Lavielle M. Maximum likelihood estimation in nonlinear mixed effects models. *Computational Statistics and Data Analysis* 49, 4 (2005), 1020-1038.

Comets E, Lavenu A, Lavielle M. SAEMIX, an R version of the SAEM algorithm. 20th meeting of the Population Approach Group in Europe, Athens, Greece (2011), Abstr 2173.

See Also

[SaemixObject](#), [saemix](#)

Examples

```
# Running the main algorithm to estimate the population parameters
data(theo.saemix)

saemix.data<-saemixData(name.data=theo.saemix,header=TRUE,sep=" ",na=NA,
  name.group=c("Id"),name.predictors=c("Dose","Time"),
  name.response=c("Concentration"),name.covariates=c("Weight","Sex"),
  units=list(x="hr",y="mg/L",covariates=c("kg","-")), name.X="Time")

modellcpt<-function(psi,id,xidep) {
  dose<-xidep[,1]
  tim<-xidep[,2]
  ka<-psi[id,1]
  V<-psi[id,2]
  CL<-psi[id,3]
  k<-CL/V
  ypred<-dose*ka/(V*(ka-k))*(exp(-k*tim)-exp(-ka*tim))
  return(ypred)
}

saemix.model<-saemixModel(model=modellcpt,
  description="One-compartment model with first-order absorption",
  psi0=matrix(c(1.,20,0.5,0.1,0,-0.01),ncol=3, byrow=TRUE,
  dimnames=list(NULL, c("ka","V","CL"))),transform.par=c(1,1,1),
  covariate.model=matrix(c(0,1,0,0,0,0),ncol=3,byrow=TRUE),fixed.estim=c(1,1,1),
  covariance.model=matrix(c(1,0,0,0,1,0,0,0,1),ncol=3,byrow=TRUE),
  omega.init=matrix(c(1,0,0,0,1,0,0,0,1),ncol=3,byrow=TRUE), error.model="constant")

saemix.options<-list(algorithm=c(1,0,0),seed=632545,save=FALSE,save.graphs=FALSE)

# Not run (strict time constraints for CRAN)
# saemix.fit<-saemix(saemix.model,saemix.data,saemix.options)

# Estimating the Fisher Information Matrix using the result of saemix
# & returning the result in the same object
# fim.saemix(saemix.fit)
```

 fitted.saemix

Extract Model Predictions

Description

fitted is a generic function which extracts model predictions from objects returned by modelling functions

Usage

```
## S3 method for class 'SaemixRes'
fitted(object, type = c("ipred", "ypred", "ppred",
  "icpred"), ...)

## S3 method for class 'SaemixObject'
fitted(object, type = c("ipred", "ypred", "ppred",
  "icpred"), ...)
```

Arguments

object	an object of type SaemixRes or SaemixObject
type	string determining which predictions are extracted. Possible values are: "ipred" (individual predictions obtained using the mode of the individual distribution for each subject, default), "ypred" (population predictions obtained using the population parameters $f(E(\theta))$), "ppred" (mean of the population predictions ($E(f(\theta))$)) and "icpred" (individual predictions obtained using the conditional mean of the individual distribution). See user guide for details.
...	further arguments to be passed to or from other methods

Value

Model predictions

initialize-methods *Methods for Function initialize*

Description

Constructor functions for Classes in the saemix package

Usage

```
## S4 method for signature 'SaemixData'
initialize(Object, name.data, header, sep, na,
  name.group, name.predictors, name.response, name.covariates, name.X,
  units, name.mdv, name.cens, name.occ, name.ytype, verbose)

## S4 method for signature 'SaemixRepData'
initialize(Object, data = NULL,
  nb.chains = 1)

## S4 method for signature 'SaemixSimData'
initialize(Object, data = NULL,
  datasim = NULL)
```

```
## S4 method for signature 'SaemixModel'
initialize(.Object, model, description, psi0,
  name.response, name.sigma, transform.par, fixed.estim, error.model,
  covariate.model, covariance.model, omega.init, error.init, name.modpar,
  verbose = TRUE)

## S4 method for signature 'SaemixRes'
initialize(.Object, name.fixed, name.random,
  name.sigma, fixed.effects, fixed.psi, betaC, betas, omega, respar,
  cond.mean.phi, cond.var.phi, mean.phi, phi, phi.samp, parpop, allpar,
  MCOV)

## S4 method for signature 'SaemixObject'
initialize(.Object, data, model,
  options = list())
```

Arguments

.Object	a SaemixObject, SaemixRes, SaemixData or SaemixModel object to initialise
name.data	name of the dataset (can be a character string giving the name of a file on disk or of a dataset in the R session, or the name of a dataset)
header	whether the dataset/file contains a header. Defaults to TRUE
sep	the field separator character. Defaults to any number of blank spaces ("")
na	a character vector of the strings which are to be interpreted as NA values. Defaults to c(NA)
name.group	name (or number) of the column containing the subject id
name.predictors	name (or number) of the column(s) containing the predictors (the algorithm requires at least one predictor x)
name.response	name (or number) of the column containing the response variable y modelled by predictor(s) x
name.covariates	name (or number) of the column(s) containing the covariates, if present (otherwise missing)
name.X	name of the column containing the regression variable to be used on the X axis in the plots (defaults to the first predictor)
units	list with up to three elements, x, y and optionally covariates, containing the units for the X and Y variables respectively, as well as the units for the different covariates (defaults to empty)
name.mdv	name of the column containing the indicator for missing variable
name.cens	name of the column containing the indicator for censoring
name.occ	name of the column containing the occasion
name.ytype	name of the column containing the index of the response
verbose	a boolean indicating whether messages should be printed out during the creation of the object

<code>data</code>	an SaemixData object
<code>nb.chains</code>	number of chains used in the algorithm
<code>datasim</code>	dataframe containing the simulated data
<code>model</code>	name of the function used to compute the structural model. The function should return a vector of predicted values given a matrix of individual parameters, a vector of indices specifying which records belong to a given individual, and a matrix of dependent variables (see example below).
<code>description</code>	a character string, giving a brief description of the model or the analysis
<code>psi0</code>	a matrix with a number of columns equal to the number of parameters in the model, and one (when no covariates are available) or two (when covariates enter the model) giving the initial estimates for the fixed effects. The column names of the matrix should be the names of the parameters in the model, and will be used in the plots and the summaries. When only the estimates of the mean parameters are given, <code>psi0</code> may be a named vector.
<code>name.sigma</code>	a vector of character string giving the names of the residual error parameters (defaults to "a" and "b")
<code>transform.par</code>	the distribution for each parameter (0=normal, 1=log-normal, 2=probit, 3=logit). Defaults to a vector of 1s (all parameters have a log-normal distribution)
<code>fixed.estim</code>	whether parameters should be estimated (1) or fixed to their initial estimate (0). Defaults to a vector of 1s
<code>error.model</code>	type of residual error model (valid types are constant, proportional, combined and exponential). Defaults to constant
<code>covariate.model</code>	a matrix giving the covariate model. Defaults to no covariate in the model
<code>covariance.model</code>	a square matrix of size equal to the number of parameters in the model, giving the variance-covariance matrix of the model: 1s correspond to estimated variances (in the diagonal) or covariances (off-diagonal elements). Defaults to the identity matrix
<code>omega.init</code>	a square matrix of size equal to the number of parameters in the model, giving the initial estimate for the variance-covariance matrix of the model. Defaults to the identity matrix
<code>error.init</code>	a vector of size 2 giving the initial value of a and b in the error model. Defaults to 1 for each estimated parameter in the error model
<code>name.modpar</code>	names of the model parameters, if they are not given as the column names (or names) of <code>psi0</code>
<code>name.fixed</code>	a character string giving the name of the fixed parameters
<code>name.random</code>	a character string giving the name of the random parameters
<code>fixed.effects</code>	vector with the estimates of $h(\mu)$ and betas in estimation order
<code>fixed.psi</code>	vector with the estimates of $h(\mu)$
<code>betaC</code>	vector with the estimates of betas (estimated fixed effects for covariates)
<code>betas</code>	vector with the estimates of μ

omega	estimated variance-covariance matrix
respar	vector with the estimates of the parameters of the residual error
cond.mean.phi	matrix of size (number of subjects) x (nb of parameters) containing the conditional mean estimates of the, defined as the mean of the conditional distribution
cond.var.phi	matrix of the variances on cond.mean.phi, defined as the variance of the conditional distribution
mean.phi	matrix of size (number of subjects) x (nb of parameters) giving for each subject the estimates of the population parameters including covariate effects
phi	matrix of size (number of subjects) x (nb of parameters) giving for each subject
phi.samp	samples from the individual conditional distributions of the phi
parpop	population parameters at each iteration
allpar	all parameters (including covariate effects) at each iteration
MCOV	design matrix C
options	a list of options passed to the algorithm

Methods

- list("signature(.Object = \"SaemixData\")")** create a SaemixData object. Please use the [saemixData](#) function.
- list("signature(.Object = \"SaemixModel\")")** create a SaemixModel object Please use the [saemixModel](#) function.
- list("signature(.Object = \"SaemixObject\")")** create a SaemixObject object. This object is obtained after a successful call to [saemix](#)
- list("signature(.Object = \"SaemixRepData\")")** create a SaemixRepData object
- list("signature(.Object = \"SaemixRes\")")** create a SaemixRes object
- list("signature(.Object = \"SaemixSimData\")")** create a SaemixSimData object

llgq.saemix

Log-likelihood using Gaussian Quadrature

Description

Estimate the log-likelihood using Gaussian Quadrature (multidimensional grid)

Usage

```
llgq.saemix(saemixObject)
```

Arguments

saemixObject an object returned by the [saemix](#) function

Details

The likelihood of the observations is estimated using Gaussian Quadrature (see documentation).

Value

the log-likelihood estimated by Gaussian Quadrature

Author(s)

Emmanuelle Comets <emmanuelle.comets@inserm.fr>, Audrey Lavenu, Marc Lavielle.

References

Comets E, Lavenu A, Lavielle M. Parameter estimation in nonlinear mixed effect models using saemix, an R implementation of the SAEM algorithm. *Journal of Statistical Software* 80, 3 (2017), 1-41.

Kuhn E, Lavielle M. Maximum likelihood estimation in nonlinear mixed effects models. *Computational Statistics and Data Analysis* 49, 4 (2005), 1020-1038.

Comets E, Lavenu A, Lavielle M. SAEMIX, an R version of the SAEM algorithm. 20th meeting of the Population Approach Group in Europe, Athens, Greece (2011), Abstr 2173.

See Also

[SaemixObject](#), [saemix](#), [llis.saemix](#)

Examples

```
# Running the main algorithm to estimate the population parameters
data(theo.saemix)
saemix.data<-saemixData(name.data=theo.saemix,header=TRUE,sep=" ",na=NA,
  name.group=c("Id"),name.predictors=c("Dose","Time"),
  name.response=c("Concentration"),name.covariates=c("Weight","Sex"),
  units=list(x="hr",y="mg/L",covariates=c("kg","-")), name.X="Time")

modellcpt<-function(psi,id,xidep) {
  dose<-xidep[,1]
  tim<-xidep[,2]
  ka<-psi[id,1]
  V<-psi[id,2]
  CL<-psi[id,3]
  k<-CL/V
  ypred<-dose*ka/(V*(ka-k))*(exp(-k*tim)-exp(-ka*tim))
  return(ypred)
}
saemix.model<-saemixModel(model=modellcpt,
  description="One-compartment model with first-order absorption",
  psi0=matrix(c(1.,20,0.5,0.1,0,-0.01),ncol=3,byrow=TRUE,
  dimnames=list(NULL, c("ka","V","CL"))),transform.par=c(1,1,1),
  covariate.model=matrix(c(0,1,0,0,0,0),ncol=3,byrow=TRUE),fixed.estim=c(1,1,1),
```

```
covariance.model=matrix(c(1,0,0,0,1,0,0,0,1),ncol=3,byrow=TRUE),
omega.init=matrix(c(1,0,0,0,1,0,0,0,1),ncol=3,byrow=TRUE), error.model="constant")

saemix.options<-list(seed=632545,save=FALSE,save.graphs=FALSE)

# Not run (strict time constraints for CRAN)
# saemix.fit<-saemix(saemix.model,saemix.data,saemix.options)

# Estimating the likelihood by Gaussian Quadrature using the result of saemix
# & returning the result in the same object
# saemix.fit<-llgq.saemix(saemix.fit)
```

llis.saemix

Log-likelihood using Importance Sampling

Description

Estimate the log-likelihood using Importance Sampling

Usage

```
llis.saemix(saemixObject)
```

Arguments

saemixObject an object returned by the [saemix](#) function

Details

The likelihood of the observations is estimated without any approximation using a Monte-Carlo approach (see documentation).

Value

the log-likelihood estimated by Importance Sampling

Author(s)

Emmanuelle Comets <emmanuelle.comets@inserm.fr>, Audrey Lavenu, Marc Lavielle.

References

Comets E, Lavenu A, Lavielle M. Parameter estimation in nonlinear mixed effect models using saemix, an R implementation of the SAEM algorithm. *Journal of Statistical Software* 80, 3 (2017), 1-41.

Kuhn E, Lavielle M. Maximum likelihood estimation in nonlinear mixed effects models. *Computational Statistics and Data Analysis* 49, 4 (2005), 1020-1038.

Comets E, Lavenu A, Lavielle M. SAEMIX, an R version of the SAEM algorithm. 20th meeting of the Population Approach Group in Europe, Athens, Greece (2011), Abstr 2173.

See Also

[SaemixObject](#), [saemix](#), [llgq.saemix](#)

Examples

```
# Running the main algorithm to estimate the population parameters
data(theo.saemix)
saemix.data<-saemixData(name.data=theo.saemix,header=TRUE,sep=" ",na=NA,
  name.group=c("Id"),name.predictors=c("Dose","Time"),
  name.response=c("Concentration"),name.covariates=c("Weight","Sex"),
  units=list(x="hr",y="mg/L",covariates=c("kg","-")), name.X="Time")

modellcpt<-function(psi,id,xidep) {
  dose<-xidep[,1]
  tim<-xidep[,2]
  ka<-psi[id,1]
  V<-psi[id,2]
  CL<-psi[id,3]
  k<-CL/V
  ypred<-dose*ka/(V*(ka-k))*(exp(-k*tim)-exp(-ka*tim))
  return(ypred)
}
saemix.model<-saemixModel(model=modellcpt,
  description="One-compartment model with first-order absorption",
  psi0=matrix(c(1.,20,0.5,0.1,0,-0.01),ncol=3, byrow=TRUE,
  dimnames=list(NULL, c("ka","V","CL"))),transform.par=c(1,1,1),
  covariate.model=matrix(c(0,1,0,0,0,0),ncol=3,byrow=TRUE),fixed.estim=c(1,1,1),
  covariance.model=matrix(c(1,0,0,0,1,0,0,0,1),ncol=3,byrow=TRUE),
  omega.init=matrix(c(1,0,0,0,1,0,0,0,1),ncol=3,byrow=TRUE),error.model="constant")

saemix.options<-list(algorithm=c(1,0,0),seed=632545,save=FALSE,save.graphs=FALSE)

# Not run (strict time constraints for CRAN)
# saemix.fit<-saemix(saemix.model,saemix.data,saemix.options)

# Estimating the likelihood by importance sampling using the result of saemix
# & returning the result in the same object
# saemix.fit<-llis.saemix(saemix.fit)
```

Description

The likelihood in saemix can be computed by one of three methods: linearisation (linearisation of the model), importance sampling (stochastic integration) and gaussian quadrature (numerical integration). The linearised likelihood is obtained as a byproduct of the computation of the Fisher Information Matrix (argument FIM=TRUE in the options given to the saemix function). If no method argument is given, this function will attempt to extract the likelihood computed by importance sampling (method="is"), unless the object contains the likelihood computed by linearisation, in which case the function will extract this component instead. If the requested likelihood is not present in the object, it will be computed and added to the object before returning.

Usage

```
## S3 method for class 'SaemixObject'
logLik(object, method = "is", ...)

## S3 method for class 'SaemixObject'
AIC(object, ..., k = 2)

## S3 method for class 'SaemixObject'
BIC(object, ...)
```

Arguments

object	name of an SaemixObject object
method	character string, one of c("is", "lin", "gq"), to select one of the available approximations to the log-likelihood (is: Importance Sampling; lin: linearisation and gq: Gaussian Quadrature). See documentation for details
...	additional arguments
k	numeric, the penalty per parameter to be used; the default k = 2 is the classical AIC

Value

Returns the selected statistical criterion (log-likelihood, AIC, BIC) extracted from the SaemixObject, computed with the 'method' argument if given (defaults to IS).

Author(s)

Emmanuelle Comets <emmanuelle.comets@inserm.fr>
 Audrey Lavenu
 Marc Lavielle.

References

Comets E, Lavenu A, Lavielle M. Parameter estimation in nonlinear mixed effect models using saemix, an R implementation of the SAEM algorithm. *Journal of Statistical Software* 80, 3 (2017), 1-41.

Kuhn E, Lavielle M. Maximum likelihood estimation in nonlinear mixed effects models. Computational Statistics and Data Analysis 49, 4 (2005), 1020-1038.

Comets E, Lavenu A, Lavielle M. SAEMIX, an R version of the SAEM algorithm. 20th meeting of the Population Approach Group in Europe, Athens, Greece (2011), Abstr 2173.

See Also

[AIC,BIC](#), [saemixControl](#), [saemix](#)

map.saemix

Estimates of the individual parameters (conditional mode)

Description

Compute the estimates of the individual parameters Ψ_i (conditional mode - Maximum A Posteriori)

Usage

```
map.saemix(saemixObject)
```

Arguments

saemixObject an object returned by the [saemix](#) function

Details

The MCMC procedure is used to estimate the conditional mode (or Maximum A Posteriori) $m(\phi_i | y_i ; \hat{\theta}) = \text{Argmax}_{\phi_i} p(\phi_i | y_i ; \hat{\theta})$

Value

saemixObject: returns the object with the estimates of the MAP parameters (see example for usage)

Author(s)

Emmanuelle Comets <emmanuelle.comets@inserm.fr>, Audrey Lavenu, Marc Lavielle.

References

Comets E, Lavenu A, Lavielle M. Parameter estimation in nonlinear mixed effect models using saemix, an R implementation of the SAEM algorithm. Journal of Statistical Software 80, 3 (2017), 1-41.

Kuhn E, Lavielle M. Maximum likelihood estimation in nonlinear mixed effects models. Computational Statistics and Data Analysis 49, 4 (2005), 1020-1038.

Comets E, Lavenu A, Lavielle M. SAEMIX, an R version of the SAEM algorithm. 20th meeting of the Population Approach Group in Europe, Athens, Greece (2011), Abstr 2173.

See Also[SaemixObject,saemix](#)**Examples**

```

data(theo.saemix)

saemix.data<-saemixData(name.data=theo.saemix,header=TRUE,sep=" ",na=NA,
  name.group=c("Id"),name.predictors=c("Dose","Time"),
  name.response=c("Concentration"),name.covariates=c("Weight","Sex"),
  units=list(x="hr",y="mg/L",covariates=c("kg","-")), name.X="Time")

model1cpt<-function(psi,id,xidep) {
  dose<-xidep[,1]
  tim<-xidep[,2]
  ka<-psi[id,1]
  V<-psi[id,2]
  CL<-psi[id,3]
  k<-CL/V
  ypred<-dose*ka/(V*(ka-k))*(exp(-k*tim)-exp(-ka*tim))
  return(ypred)
}

saemix.model<-saemixModel(model=model1cpt,
  description="One-compartment model with first-order absorption",
  psi0=matrix(c(1.,20,0.5,0.1,0,-0.01),ncol=3, byrow=TRUE,
  dimnames=list(NULL, c("ka","V","CL"))),transform.par=c(1,1,1),
  covariate.model=matrix(c(0,1,0,0,0,0),ncol=3,byrow=TRUE),fixed.estim=c(1,1,1),
  covariance.model=matrix(c(1,0,0,0,1,0,0,0,1),ncol=3,byrow=TRUE),
  omega.init=matrix(c(1,0,0,0,1,0,0,0,1),ncol=3,byrow=TRUE),error.model="constant")

saemix.options<-list(algorithm=c(1,0,0),seed=632545,
  save=FALSE,save.graphs=FALSE)

# Not run (strict time constraints for CRAN)
# saemix.fit<-saemix(saemix.model,saemix.data,saemix.options)

# Estimating the individual parameters using the result of saemix
# & returning the result in the same object
# saemix.fit<-map.saemix(saemix.fit)

```

oxboys.saemix

*Heights of Boys in Oxford***Description**

The oxboys.saemix data frame has 234 rows and 4 columns.

Usage

```
oxboys.saemix
```

Format

This data frame contains the following columns:

Subject: an ordered factor giving a unique identifier for each boy in the experiment

age: a numeric vector giving the standardized age (dimensionless)

height: a numeric vector giving the height of the boy (cm)

Occasion: an ordered factor - the result of converting 'age' from a continuous variable to a count so these slightly unbalanced data can be analyzed as balanced.

Details

These data are described in Goldstein (1987) as data on the height of a selection of boys from Oxford, England versus a standardized age. The dataset can be found in the package nlme.

We use an linear model for this data: $y_{ij} = \text{Base}_i + \text{slope}_i x_{ij} + \text{epsilon}_{ij}$

Source

Pinheiro, J. C. and Bates, D. M. (2000), *_Mixed-Effects Models in S and S-PLUS_*, Springer, New York. (Appendix A.19)

Examples

```
data(oxboys.saemix)
saemix.data<-saemixData(name.data=oxboys.saemix,header=TRUE,
  name.group=c("Subject"),name.predictors=c("age"),name.response=c("height"),
  units=list(x="yr",y="cm"))

# plot the data
plot(saemix.data)

growth.linear<-function(psi,id,xidep) {
# input:
# psi : matrix of parameters (2 columns, base and slope)
# id : vector of indices
# xidep : dependent variables (same nb of rows as length of id)
# returns:
# a vector of predictions of length equal to length of id
x<-xidep[,1]
base<-psi[id,1]
slope<-psi[id,2]
f<-base+slope*x
return(f)
}
saemix.model<-saemixModel(model=growth.linear,description="Linear model",
```



```

psi0=matrix(c(140,1),ncol=2,byrow=TRUE,dimnames=list(NULL,c("base","slope"))),
transform.par=c(1,0),covariance.model=matrix(c(1,1,1,1),ncol=2,byrow=TRUE),
error.model="constant")

saemix.options<-list(algorithms=c(1,1,1),nb.chains=1,seed=201004,
save=FALSE,save.graphs=FALSE)

# Not run (strict time constraints for CRAN)
# saemix.fit<-saemix(saemix.model,saemix.data,saemix.options)

```

PD1.saemix	<i>Data simulated according to an Emax response model, in SAEM format</i>
------------	---

Description

PD1.saemix contains data from winter wheat experiments.

Usage

PD1.saemix

PD2.saemix

Format

This data frame contains the following columns:

subject: the site number

dose: simulated dose.

response: simulated response.

gender: gender (0 for male, 1 for female).

Details

These examples were used by P. Girard and F. Mentre for the symposium dedicated to Comparison of Algorithms Using Simulated Data Sets and Blind Analysis, that took place in Lyon, France, September 2004.

The dataset contains 100 individuals, each receiving 3 different doses:(0, 10, 90), (5, 25, 65) or (0, 20, 30). It was assumed that doses were given in a cross-over study with sufficient wash out period to avoid carry over. Responses (y_{ij}) were simulated with the following pharmacodynamic model:

$$y_{ij} = E0_i + D_{ij} Emax_i / (D_{ij} + ED50_i) + \epsilon_{ij}$$

The individual parameters were simulated according to

$$\log(E0_i) = \log(E0) + \eta_{i1} \quad \log(Emax_i) = \log(Emax) + \eta_{i2} \quad \log(ED50_i) = \log(ED50) + \beta w_i + \eta_{i3}$$

PD1.saemix contains the data simulated with a gender effect, $\beta=0.3$.

PD2.saemix contains the data simulated without a gender effect, $\beta=0$.

Source

Girard P., Mentre F. Comparison of Algorithms Using Simulated Data Sets and Blind Analysis workshop, Lyon, France, September 2004.

Examples

```

data(PD1.saemix)
saemix.data<-saemixData(name.data=PD1.saemix,header=TRUE,name.group=c("subject"),
  name.predictors=c("dose"),name.response=c("response"),
  name.covariates=c("gender"), units=list(x="mg",y="-",covariates=c("-")))

modelemax<-function(psi,id,xidep) {
# input:
# psi : matrix of parameters (3 columns, E0, Emax, EC50)
# id : vector of indices
# xidep : dependent variables (same nb of rows as length of id)
# returns:
# a vector of predictions of length equal to length of id
  dose<-xidep[,1]
  e0<-psi[id,1]
  emax<-psi[id,2]
  e50<-psi[id,3]
  f<-e0+emax*dose/(e50+dose)
  return(f)
}

# Plotting the data
plot(saemix.data,main="Simulated data PD1")

# Not run (strict time constraints for CRAN)

# Compare models with and without covariates with LL by Importance Sampling
# SE not computed
model1<-saemixModel(model=modelemax,description="Emax growth model",
  psi=matrix(c(20,300,20,0,0,0),ncol=3,byrow=TRUE,dimnames=list(NULL,
  c("E0","Emax","EC50"))), transform.par=c(1,1,1),
  covariate.model=matrix(c(0,0,0), ncol=3,byrow=TRUE),fixed.estim=c(1,1,1))

model2<-saemixModel(model=modelemax,description="Emax growth model",
  psi=matrix(c(20,300,20,0,0,0),ncol=3,byrow=TRUE,dimnames=list(NULL,
  c("E0","Emax","EC50"))), transform.par=c(1,1,1),
  covariate.model=matrix(c(0,0,1), ncol=3,byrow=TRUE),fixed.estim=c(1,1,1))

saemix.options<-list(algorithms=c(0,1,1),nb.chains=3,seed=765754,
  nbiter.saemix=c(500,300),save=FALSE,save.graphs=FALSE)

# Not run (strict time constraints for CRAN)
# fit1<-saemix(model1,saemix.data,saemix.options)
# fit2<-saemix(model2,saemix.data,saemix.options)
# wstat<-(-2)*(fit1["results"]["ll.is"]-fit2["results"]["ll.is"])

```

```
# cat("LRT test for covariate effect on EC50: p-value=", 1-pchisq(wstat, 1), "\n")
```

```
plot, SaemixObject-method
```

General plot function from SAEM

Description

Several plots (selectable by the type argument) are currently available: convergence plot, individual plots, predictions versus observations, distribution plots, VPC, residual plots.

Usage

```
## S4 method for signature 'SaemixObject'
plot(x, y, ...)
```

Arguments

x	an object returned by the <code>saemix</code> function
y	empty
...	optional arguments passed to the plots

Details

This is the generic plot function for an SaemixObject object, which implements different graphs related to the algorithm (convergence plots, likelihood estimation) as well as diagnostic graphs. A description is provided in the PDF documentation. Arguments such as main, xlab, etc... that can be given to the generic plot function may be used, and will be interpreted according to the type of plot that is to be drawn.

A special argument `plot.type` can be set to determine the type of plot; it can be one of:

data: A spaghetti plot of the data, displaying the observed data y as a function of the regression variable (time for a PK application)

convergence: For each parameter in the model, this plot shows the evolution of the parameter estimate versus the iteration number

likelihood: Graph showing the evolution of the log-likelihood during the estimation by importance sampling

observations.vs.predictions: Plot of the predictions computed with the population parameters versus the observations (left), and plot of the predictions computed with the individual parameters versus the observations (right)

residuals.scatter: Scatterplot of the residuals versus the predictor (top) and versus predictions (bottom), for weighted residuals (population residuals, left), individual weighted residuals (middle) and npde (right).

residuals.distribution: Distribution of the residuals, plotted as histogram (top) and as a QQ-plot (bottom), for weighted residuals (population residuals, left), individual weighted residuals (middle) and npde (right).

individual.fit: Individual fits are obtained using the individual parameters with the individual covariates

population.fit: Population fits are obtained using the population parameters with the individual covariates

both.fit: Individual fits, superposing fits obtained using the population parameters with the individual covariates (red) and using the individual parameters with the individual covariates (green)

marginal.distribution: Distribution of the parameters (conditional on covariates when some are included in the model). A histogram of individual parameter estimates can be overlayed on the plot, but it should be noted that the histogram does not make sense when there are covariates influencing the parameters and a warning will be displayed

random.effects: Boxplot of the random effects

correlations: Correlation between the random effects

parameters.vs.covariates: Plots of the estimates of the individual parameters versus the covariates, using scatterplot for continuous covariates, boxplot for categorical covariates

randeff.vs.covariates: Plots of the estimates of the random effects versus the covariates, using scatterplot for continuous covariates, boxplot for categorical covariates

npde: Plots 4 graphs to evaluate the shape of the distribution of the normalised prediction distribution errors (npde)

vpc: Visual Predictive Check, with options to include the prediction intervals around the boundaries of the selected interval as well as around the median (50th percentile of the simulated data).

In addition, the following values for `plot.type` produce a series of plots:

reduced: produces the following plots: plot of the data, convergence plots, plot of the likelihood by importance sampling (if computed), plots of observations versus predictions. This is the default behaviour of the plot function applied to an `SaemixObject` object

full: produces the following plots: plot of the data, convergence plots, plot of the likelihood by importance sampling (if computed), plots of observations versus predictions, scatterplots and distribution of residuals, VPC, npde, boxplot of the random effects, distribution of the parameters, correlations between random effects, plots of the relationships between individually estimated parameters and covariates, plots of the relationships between individually estimated random effects and covariates

Each plot can be customised by modifying options, either through a list of options set by the `saemix.plot.setoptions` function, or on the fly by passing an option in the call to the plot (see examples).

Value

None

Author(s)

Emmanuelle Comets <emmanuelle.comets@inserm.fr>, Audrey Lavenu, Marc Lavielle.

References

Comets E, Lavenu A, Lavielle M. Parameter estimation in nonlinear mixed effect models using saemix, an R implementation of the SAEM algorithm. *Journal of Statistical Software* 80, 3 (2017), 1-41.

Kuhn E, Lavielle M. Maximum likelihood estimation in nonlinear mixed effects models. *Computational Statistics and Data Analysis* 49, 4 (2005), 1020-1038.

Comets E, Lavenu A, Lavielle M. SAEMIX, an R version of the SAEM algorithm. 20th meeting of the Population Approach Group in Europe, Athens, Greece (2011), Abstr 2173.

See Also

[SaemixObject](#), [saemix](#), [saemix.plot.setoptions](#), [saemix.plot.select](#), [saemix.plot.data](#)

Examples

```
data(theo.saemix)

saemix.data<-saemixData(name.data=theo.saemix,header=TRUE,sep=" ",na=NA,
  name.group=c("Id"),name.predictors=c("Dose","Time"),
  name.response=c("Concentration"),name.covariates=c("Weight","Sex"),
  units=list(x="hr",y="mg/L",covariates=c("kg","-")), name.X="Time")

model1cpt<-function(psi,id,xidep) {
  dose<-xidep[,1]
  tim<-xidep[,2]
  ka<-psi[id,1]
  V<-psi[id,2]
  CL<-psi[id,3]
  k<-CL/V
  ypred<-dose*ka/(V*(ka-k))*(exp(-k*tim)-exp(-ka*tim))
  return(ypred)
}

saemix.model<-saemixModel(model=model1cpt,
  description="One-compartment model with first-order absorption",
  psi0=matrix(c(1.,20,0.5,0.1,0,-0.01),ncol=3, byrow=TRUE,
  dimnames=list(NULL, c("ka","V","CL"))),transform.par=c(1,1,1),
  covariate.model=matrix(c(0,1,0,0,0,0),ncol=3,byrow=TRUE),fixed.estim=c(1,1,1),
  covariance.model=matrix(c(1,0,0,0,1,0,0,0,1),ncol=3,byrow=TRUE),
  omega.init=matrix(c(1,0,0,0,1,0,0,0,1),ncol=3,byrow=TRUE),error.model="constant")

saemix.options<-list(seed=632545,save=FALSE,save.graphs=FALSE)

# Not run (strict time constraints for CRAN)
# saemix.fit<-saemix(saemix.model,saemix.data,saemix.options)

# Set of default plots
# plot(saemix.fit)

# Data
```

```

# plot(saemix.fit,plot.type="data")

# Convergence
# plot(saemix.fit,plot.type="convergence")

# Individual plot for subject 1, smoothed
# plot(saemix.fit,plot.type="individual.fit",ilist=1,smooth=TRUE)

# Individual plot for subject 1 to 12, with ask set to TRUE
# (the system will pause before a new graph is produced)
# plot(saemix.fit,plot.type="individual.fit",ilist=c(1:12),ask=TRUE)

# Diagnostic plot: observations versus population predictions
# par(mfrow=c(1,1))
# plot(saemix.fit,plot.type="observations.vs.predictions",level=0,new=FALSE)

# LL by Importance Sampling
# plot(saemix.fit,plot.type="likelihood")

# Scatter plot of residuals
# Data will be simulated to compute weighted residuals and npde
# the results shall be silently added to the object saemix.fit
# plot(saemix.fit,plot.type="residuals.scatter")

# Boxplot of random effects
# plot(saemix.fit,plot.type="random.effects")

# Relationships between parameters and covariates
# plot(saemix.fit,plot.type="parameters.vs.covariates")

# Relationships between parameters and covariates, on the same page
# par(mfrow=c(3,2))
# plot(saemix.fit,plot.type="parameters.vs.covariates",new=FALSE)

# VPC
# Not run (time constraints for CRAN)
# plot(saemix.fit,plot.type="vpc")

```

plot-methods

Methods for Function plot

Description

Methods for function plot

Methods

list("signature(x = \"ANY\")") default plot function ?

list("signature(x = \"SaemixData\")") Plots the data. Defaults to a spaghetti plot of response versus predictor, with lines joining the data for one individual.

list("signature(x = \"SaemixModel\")") Plots prediction of the model

list("signature(x = \"SaemixObject\")") This method gives access to a number of plots that can be performed on a SaemixObject

list("signature(x = \"SaemixSimData\")") Plots simulated datasets

plot-SaemixData

*Plot of longitudinal data***Description**

This function will plot a longitudinal dataframe contained in an SaemixData object. By default it produces a spaghetti plot, but arguments can be passed on to modify this behaviour.

Arguments

x	an SaemixData object or an SaemixSimData object
y	unused, present for compatibility with base plot function
...	additional arguments to be passed on to plot (titles, legends, ...)
i rep	number of replicate datasets to use in the mirror plot

plot-SaemixModel

*Plot model predictions using an SaemixModel object***Description**

This function will plot predictions obtained from an SaemixModel object over a given range of X. Additional predictors may be passed on to the function using the predictors argument.

Arguments

x	an SaemixData object or an SaemixSimData object
y	unused, present for compatibility with base plot function
range	range of X over which the model is to be plotted
psi	parameters of the model
predictors	additional predictors needed to pass on to the model
...	additional arguments to be passed on to plot (titles, legends, ...)

predict-methods *Methods for Function predict*

Description

Methods for function predict

Usage

```
## S4 method for signature 'SaemixObject'
predict(object, newdata = NULL,
        type = c("ipred", "ypred", "ppred", "icpred"), se.fit = FALSE, ...)
```

Arguments

object	an SaemixObject
newdata	an optional dataframe for which predictions are desired
type	the type of predictions (ipred= individual, ypred= mean of the population predictions, ppred=population predictions obtained with the population estimates, icpred=conditional predictions). With newdata, predictions correspond to the population predictions and type is ignored
se.fit	whether the SE are to be taken into account in the model predictions
...	additional arguments passed on to fitted()

Methods

list("signature(object = \"ANY\")) Default predict functions

list("signature(object = \"SaemixObject\")) Computes predictions using the results of an SAEM fit

print-methods *Methods for Function print*

Description

Prints a summary of an object

Usage

```
## S4 method for signature 'SaemixData'
print(x, nlines = 10, ...)

## S4 method for signature 'SaemixModel'
print(x, ...)

## S4 method for signature 'SaemixRes'
print(x, digits = 2, map = FALSE, ...)

## S4 method for signature 'SaemixObject'
print(x, nlines = 10, ...)
```

Arguments

x	an object of type SaemixData, SaemixModel, SaemixRes or SaemixObject
nlines	maximum number of lines of data to print (defaults to 10)
...	additional arguments passed on the print function
digits	number of digits to use for pretty printing
map	when map is TRUE the individual parameter estimates are shown (defaults to FALSE)

Methods

```
list("signature(x = \"ANY\")") Default print function
list("signature(x = \"SaemixData\")") Prints a summary of a SaemixData object
list("signature(x = \"SaemixModel\")") Prints a summary of a SaemixModel object
list("signature(x = \"SaemixObject\")") Prints a summary of the results from a SAEMIX fit
list("signature(x = \"SaemixRes\")") Not user-level
```

psi-methods

Functions to extract the individual estimates of the parameters and random effects

Description

These three functions are used to access the estimates of individual parameters and random effects.

Usage

```
psi(object, type = c("mode", "mean"))

phi(object, type = c("mode", "mean"))

eta(object, type = c("mode", "mean"))

## S4 method for signature 'SaemixObject'
psi(object, type = c("mode", "mean"))

## S4 method for signature 'SaemixObject'
phi(object, type = c("mode", "mean"))

## S4 method for signature 'SaemixObject'
eta(object, type = c("mode", "mean"))
```

Arguments

object	an SaemixObject object returned by the saemix function
type	a string specifying whether to use the MAP (type="mode") or the mean (type="mean") of the conditional distribution of the individual parameters. Defaults to mode

Details

The ψ_i represent the individual parameter estimates. In the SAEM algorithm, these parameters are assumed to be a transformation of a Gaussian random vector ϕ_i , where the ϕ_i can be written as a function of the individual random effects (η_i), the covariate matrix (C_i) and the vector of fixed effects (μ):

$$\phi_i = C_i \mu + \eta_i$$

More details can be found in the PDF documentation.

Value

a matrix with the individual parameters (ψ/ϕ) or the random effects (η). These functions are used to access and output the estimates of parameters and random effects. When the object passed to the function does not contain these estimates, they are automatically computed. The object is then returned (invisibly) with these estimates added to the results.

Methods

`list("signature(object = \"SaemixObject\")")` please refer to the PDF documentation for the models

Author(s)

Emmanuelle Comets <emmanuelle.comets@inserm.fr>, Audrey Lavenu, Marc Lavielle.

References

Comets E, Lavenu A, Lavielle M. Parameter estimation in nonlinear mixed effect models using saemix, an R implementation of the SAEM algorithm. *Journal of Statistical Software* 80, 3 (2017), 1-41.

Kuhn E, Lavielle M. Maximum likelihood estimation in nonlinear mixed effects models. *Computational Statistics and Data Analysis* 49, 4 (2005), 1020-1038.

Comets E, Lavenu A, Lavielle M. SAEMIX, an R version of the SAEM algorithm. 20th meeting of the Population Approach Group in Europe, Athens, Greece (2011), Abstr 2173.

See Also

[SaemixData](#), [SaemixModel](#), [SaemixObject](#), [saemixControl](#), [plot.saemix](#)

Examples

```
data(theo.saemix)

saemix.data<-saemixData(name.data=theo.saemix,header=TRUE,sep=" ",na=NA,
  name.group=c("Id"),name.predictors=c("Dose","Time"),
  name.response=c("Concentration"),name.covariates=c("Weight","Sex"),
  units=list(x="hr",y="mg/L",covariates=c("kg","-")), name.X="Time")

model1cpt<-function(psi,id,xidep) {
  dose<-xidep[,1]
  tim<-xidep[,2]
  ka<-psi[id,1]
  V<-psi[id,2]
  CL<-psi[id,3]
  k<-CL/V
  ypred<-dose*ka/(V*(ka-k))*(exp(-k*tim)-exp(-ka*tim))
  return(ypred)
}

saemix.model<-saemixModel(model=model1cpt,
  description="One-compartment model with first-order absorption",
  psi0=matrix(c(1.,20,0.5,0.1,0,-0.01),ncol=3, byrow=TRUE,
  dimnames=list(NULL, c("ka","V","CL"))),transform.par=c(1,1,1),
  covariate.model=matrix(c(0,1,0,0,0,0),ncol=3,byrow=TRUE),fixed.estim=c(1,1,1),
  covariance.model=matrix(c(1,0,0,0,1,0,0,0,1),ncol=3,byrow=TRUE),
  omega.init=matrix(c(1,0,0,0,1,0,0,0,1),ncol=3,byrow=TRUE),error.model="constant")

saemix.options<-list(algorithm=c(1,0,0),seed=632545,save=FALSE,save.graphs=FALSE)

# Not run (strict time constraints for CRAN)
# saemix.fit<-saemix(saemix.model,saemix.data,saemix.options)

# psi(saemix.fit)
# phi(saemix.fit)
# eta(saemix.fit,type="mean")
```

resid.saemix	<i>Extract Model Residuals</i>
--------------	--------------------------------

Description

residuals is a generic function which extracts model residuals from objects returned by modelling functions. The abbreviated form resid is an alias for residuals

Usage

```
## S3 method for class 'SaemixRes'
resid(object, type = c("ires", "wres", "npde", "pd",
  "iwres", "icwres"), ...)

## S3 method for class 'SaemixObject'
resid(object, type = c("ires", "wres", "npde",
  "pd", "iwres", "icwres"), ...)
```

Arguments

object	an SaemixRes or an SaemixObject object
type	string determining which residuals are extracted. Possible values are: "ires" (individual residuals, default), "wres" (weighted population residuals), "npde" (normalised prediction distribution errors), "pd" (prediction discrepancies), "iwres" (individual weighted residuals) and "icwres" (conditional individual weighted residuals). See user guide for details.
...	further arguments to be passed to or from other methods

Value

By default, individual residuals are extracted from the model object

saemix	<i>Stochastic Approximation Expectation Maximization (SAEM) algorithm</i>
--------	---

Description

SAEM algorithm perform parameter estimation for nonlinear mixed effects models without any approximation of the model (linearization, quadrature approximation, . . .)

Usage

```
saemix(model, data, control = list())
```

Arguments

model	an object of class <code>SaemixModel</code> , created by a call to the function <code>saemixModel</code>
data	an object of class <code>SaemixData</code> , created by a call to the function <code>saemixData</code>
control	a list of options, see <code>saemixControl</code>

Details

The SAEM algorithm is a stochastic approximation version of the standard EM algorithm proposed by Kuhn and Lavielle (see reference). Details of the algorithm can be found in the pdf file accompanying the package.

Value

An object of class `SaemixObject` containing the results of the fit of the data by the non-linear mixed effect model. A summary of the results is printed out to the terminal, and, provided the appropriate options have not been changed, numerical and graphical outputs are saved in a directory.

Author(s)

Emmanuelle Comets <emmanuelle.comets@inserm.fr>, Audrey Lavenu, Marc Lavielle.

References

- Comets E, Lavenu A, Lavielle M. Parameter estimation in nonlinear mixed effect models using saemix, an R implementation of the SAEM algorithm. *Journal of Statistical Software* 80, 3 (2017), 1-41.
- Kuhn E, Lavielle M. Maximum likelihood estimation in nonlinear mixed effects models. *Computational Statistics and Data Analysis* 49, 4 (2005), 1020-1038.
- Comets E, Lavenu A, Lavielle M. SAEMIX, an R version of the SAEM algorithm. 20th meeting of the Population Approach Group in Europe, Athens, Greece (2011), Abstr 2173.

See Also

[SaemixData](#), [SaemixModel](#), [SaemixObject](#), [saemixControl](#), [plot.saemix](#)

Examples

```
data(theo.saemix)

saemix.data<-saemixData(name.data=theo.saemix,header=TRUE,sep=" ",na=NA,
  name.group=c("Id"),name.predictors=c("Dose","Time"),
  name.response=c("Concentration"),name.covariates=c("Weight","Sex"),
  units=list(x="hr",y="mg/L",covariates=c("kg","-")),name.X="Time")

model1cpt<-function(psi,id,xidep) {
  dose<-xidep[,1]
  tim<-xidep[,2]
  ka<-psi[id,1]
```

```

V<-psi[id,2]
CL<-psi[id,3]
k<-CL/V
ypred<-dose*ka/(V*(ka-k))*(exp(-k*tim)-exp(-ka*tim))
return(ypred)
}

saemix.model<-saemixModel(model=model1cpt,
  description="One-compartment model with first-order absorption",
  psi0=matrix(c(1.,20,0.5,0.1,0,-0.01),ncol=3, byrow=TRUE,
  dimnames=list(NULL, c("ka","V","CL"))),transform.par=c(1,1,1),
  covariate.model=matrix(c(0,1,0,0,0,0),ncol=3,byrow=TRUE),fixed.estim=c(1,1,1),
  covariance.model=matrix(c(1,0,0,0,1,0,0,0,1),ncol=3,byrow=TRUE),
  omega.init=matrix(c(1,0,0,0,1,0,0,0,1),ncol=3,byrow=TRUE),error.model="constant")

# Not run (strict time constraints for CRAN)
# saemix.fit<-saemix(saemix.model,saemix.data,list(seed=632545,directory="newtheo",
# save=FALSE,save.graphs=FALSE))

# Prints a summary of the results
# print(saemix.fit)

# Outputs the estimates of individual parameters
# psi(saemix.fit)

# Shows some diagnostic plots to evaluate the fit
# plot(saemix.fit)

```

saemix.plot.data

Functions implementing each type of plot in SAEM

Description

Several plots (selectable by the type argument) are currently available: convergence plot, individual plots, predictions versus observations, distribution plots, VPC, residual plots.

Usage

```
saemix.plot.data(saemixObject, ...)
```

Arguments

saemixObject an object returned by the [saemix](#) function
... optional arguments passed to the plots

Details

These functions implement plots different graphs related to the algorithm (convergence plots, likelihood estimation) as well as diagnostic graphs. A description is provided in the PDF documentation. `saemix.plot.parcov.aux`, `compute.sres` and `compute.eta.map` are helper functions, not intended to be called by the user directly.

By default, the following plots are produced:

saemix.plot.data: A spaghetti plot of the data, displaying the observed data y as a function of the regression variable (time for a PK application)

saemix.plot.convergence: For each parameter in the model, this plot shows the evolution of the parameter estimate versus the iteration number

saemix.plot.llis: Graph showing the evolution of the log-likelihood during the estimation by importance sampling

saemix.plot.obsvspred: Plot of the predictions computed with the population parameters versus the observations (left), and plot of the predictions computed with the individual parameters versus the observations (right)

saemix.plot.scatterresiduals: Scatterplot of the residuals versus the predictor (top) and versus predictions (bottom), for weighted residuals (population residuals, left), individual weighted residuals (middle) and npde (right).

saemix.plot.distribresiduals: Distribution of the residuals, plotted as histogram (top) and as a QQ-plot (bottom), for weighted residuals (population residuals, left), individual weighted residuals (middle) and npde (right).

saemix.plot.fits: Model fits. Individual fits are obtained using the individual parameters with the individual covariates. Population fits are obtained using the population parameters with the individual covariates (red) and the individual parameters with the individual covariates (green). By default the individual plots are displayed.

saemix.plot.distpsi: Distribution of the parameters (conditional on covariates when some are included in the model). A histogram of individual parameter estimates can be overlayed on the plot, but it should be noted that the histogram does not make sense when there are covariates influencing the parameters and a warning will be displayed

saemix.plot.randeff: Boxplot of the random effects

saemix.plot.correlations: Correlation between the random effects

saemix.plot.parcov: Plots of the estimates of the individual parameters versus the covariates, using scatterplot for continuous covariates, boxplot for categorical covariates

saemix.plot.randeffcov: Plots of the estimates of the random effects versus the covariates, using scatterplot for continuous covariates, boxplot for categorical covariates

saemix.plot.npde: Plots 4 graphs to evaluate the shape of the distribution of the normalised prediction distribution errors (npde)

saemix.plot.vpc: Visual Predictive Check, with options to include the prediction intervals around the boundaries of the selected interval as well as around the median (50th percentile of the simulated data). Several methods are available to define binning on the X-axis (see methods in the PDF guide).

Each plot can be customised by modifying options, either through a list of options set by the `saemix.plot.setoptions` function, or on the fly by passing an option in the call to the plot (see examples).

Value

None

Author(s)

Emmanuelle Comets <emmanuelle.comets@inserm.fr>, Audrey Lavenu, Marc Lavielle.

References

Comets E, Lavenu A, Lavielle M. Parameter estimation in nonlinear mixed effect models using saemix, an R implementation of the SAEM algorithm. *Journal of Statistical Software* 80, 3 (2017), 1-41.

Kuhn E, Lavielle M. Maximum likelihood estimation in nonlinear mixed effects models. *Computational Statistics and Data Analysis* 49, 4 (2005), 1020-1038.

Comets E, Lavenu A, Lavielle M. SAEMIX, an R version of the SAEM algorithm. 20th meeting of the Population Approach Group in Europe, Athens, Greece (2011), Abstr 2173.

See Also

[SaemixObject](#), [saemix](#), [saemix.plot.setoptions](#), [saemix.plot.select](#), [plot.saemix](#)

Examples

```
data(theo.saemix)

saemix.data<-saemixData(name.data=theo.saemix,header=TRUE,sep=" ",na=NA,
  name.group=c("Id"),name.predictors=c("Dose","Time"),
  name.response=c("Concentration"),name.covariates=c("Weight","Sex"),
  units=list(x="hr",y="mg/L",covariates=c("kg","-")), name.X="Time")

modellcpt<-function(psi,id,xidep) {
  dose<-xidep[,1]
  tim<-xidep[,2]
  ka<-psi[id,1]
  V<-psi[id,2]
  CL<-psi[id,3]
  k<-CL/V
  ypred<-dose*ka/(V*(ka-k))*(exp(-k*tim)-exp(-ka*tim))
  return(ypred)
}

saemix.model<-saemixModel(model=modellcpt,
  description="One-compartment model with first-order absorption",
  psi0=matrix(c(1.,20,0.5,0.1,0,-0.01),ncol=3, byrow=TRUE,
  dimnames=list(NULL, c("ka","V","CL"))),transform.par=c(1,1,1),
  covariate.model=matrix(c(0,1,0,0,0,0),ncol=3,byrow=TRUE),fixed.estim=c(1,1,1),
  covariance.model=matrix(c(1,0,0,0,1,0,0,0,1),ncol=3,byrow=TRUE),
  omega.init=matrix(c(1,0,0,0,1,0,0,0,1),ncol=3,byrow=TRUE),error.model="constant")
```



```
saemix.options<-list(seed=632545,save=FALSE,save.graphs=FALSE)

# Not run (strict time constraints for CRAN)
# saemix.fit<-saemix(saemix.model,saemix.data,saemix.options)

# Simulate data and compute weighted residuals and npde
# saemix.fit<-compute.sres(saemix.fit)

# Data
# saemix.plot.data(saemix.fit)

# Convergence
# saemix.plot.convergence(saemix.fit)

# Individual plot for subject 1, smoothed
# saemix.plot.fits(saemix.fit,ilist=1,smooth=TRUE)

# Individual plot for subject 1 to 12, with ask set to TRUE
# (the system will pause before a new graph is produced)
# saemix.plot.fits(saemix.fit,ilist=c(1:12),ask=TRUE)

# Diagnostic plot: observations versus population predictions
# par(mfrow=c(1,1))
# saemix.plot.obsvspred(saemix.fit,level=0,new=FALSE)

# LL by Importance Sampling
# saemix.plot.llis(saemix.fit)

# Scatter plot of residuals
# saemix.plot.scatterresiduals(saemix.fit)

# Boxplot of random effects
# saemix.plot.randeff(saemix.fit)

# Relationships between parameters and covariates
# saemix.plot.parcov(saemix.fit)

# Relationships between parameters and covariates, on the same page
# par(mfrow=c(3,2))
# saemix.plot.parcov(saemix.fit,new=FALSE)

# VPC, default options (10 bins, equal number of observations in each bin)
# Not run (time constraints for CRAN)
# saemix.plot.vpc(saemix.fit)

# VPC, user-defined breaks for binning
# Not run (time constraints for CRAN)
# saemix.plot.vpc(saemix.fit,vpc.method="user", vpc.breaks=c(0.4,0.8,1.5,2.5,4,5.5,8,10,13))
```

Description

Several plots (selectable by the type argument) are currently available: convergence plot, individual plots, predictions versus observations, distribution plots, residual plots, VPC.

Usage

```
saemix.plot.select(saemixObject, data = FALSE, convergence = FALSE,
  likelihood = FALSE, individual.fit = FALSE, population.fit = FALSE,
  both.fit = FALSE, observations.vs.predictions = FALSE,
  residuals.scatter = FALSE, residuals.distribution = FALSE,
  random.effects = FALSE, correlations = FALSE,
  parameters.vs.covariates = FALSE, randeff.vs.covariates = FALSE,
  marginal.distribution = FALSE, vpc = FALSE, npde = FALSE, ...)
```

Arguments

saemixObject	an object returned by the saemix function
data	if TRUE, produce a plot of the data. Defaults to FALSE
convergence	if TRUE, produce a convergence plot. Defaults to FALSE
likelihood	if TRUE, produce a plot of the estimation of the LL by importance sampling. Defaults to FALSE
individual.fit	if TRUE, produce individual fits with individual estimates. Defaults to FALSE
population.fit	if TRUE, produce individual fits with population estimates. Defaults to FALSE
both.fit	if TRUE, produce individual fits with both individual and population estimates. Defaults to FALSE
observations.vs.predictions	if TRUE, produce a plot of observations versus predictions. Defaults to FALSE
residuals.scatter	if TRUE, produce scatterplots of residuals versus predictor and predictions. Defaults to FALSE
residuals.distribution	if TRUE, produce plots of the distribution of residuals. Defaults to FALSE
random.effects	if TRUE, produce boxplots of the random effects. Defaults to FALSE
correlations	if TRUE, produce a matrix plot showing the correlation between random effects. Defaults to FALSE
parameters.vs.covariates	if TRUE, produce plots of the relationships between parameters and covariates, using the Empirical Bayes Estimates of individual parameters. Defaults to FALSE
randeff.vs.covariates	if TRUE, produce plots of the relationships between random effects and covariates, using the Empirical Bayes Estimates of individual random effects. Defaults to FALSE
marginal.distribution	if TRUE, produce plots of the marginal distribution of the random effects. Defaults to FALSE

vpc	if TRUE, produce Visual Predictive Check plots. Defaults to FALSE
npde	if TRUE, produce plots of the npde. Defaults to FALSE
...	optional arguments passed to the plots

Details

This function plots different graphs related to the algorithm (convergence plots, likelihood estimation) as well as diagnostic graphs. A description is provided in the PDF documentation.

data A spaghetti plot of the data, displaying the observed data y as a function of the regression variable (eg time for a PK application)

convergence For each parameter in the model, this plot shows the evolution of the parameter estimate versus the iteration number

likelihood Estimation of the likelihood estimated by importance sampling, as a function of the number of MCMC samples

individual.fit Individual fits, using the individual parameters with the individual covariates

population.fit Individual fits, using the population parameters with the individual covariates

both.fit Individual fits, using the population parameters with the individual covariates and the individual parameters with the individual covariates

observations.vs.predictions Plot of the predictions computed with the population parameters versus the observations (left), and plot of the predictions computed with the individual parameters versus the observations (right)

residuals.scatter Scatterplot of standardised residuals versus the X predictor and versus predictions. These plots are shown for individual and population residuals, as well as for npde when they are available

residuals.distribution Distribution of standardised residuals, using histograms and QQ-plot. These plots are shown for individual and population residuals, as well as for npde when they are available

random.effects Boxplot of the random effects

correlations Correlation between the random effects, with a smoothing spline

parameters.versus.covariates Plots of the estimate of the individual parameters versus the covariates, using scatterplot for continuous covariates, boxplot for categorical covariates

randeff.versus.covariates Plots of the estimate of the individual random effects versus the covariates, using scatterplot for continuous covariates, boxplot for categorical covariates

marginal.distribution Distribution of each parameter in the model (conditional on covariates when some are included in the model)

npde Plot of npde as in package npde

vpc Visual Predictive Check

Value

None

Author(s)

Emmanuelle Comets <emmanuelle.comets@inserm.fr>, Audrey Lavenu, Marc Lavielle.

References

Comets E, Lavenu A, Lavielle M. Parameter estimation in nonlinear mixed effect models using saemix, an R implementation of the SAEM algorithm. *Journal of Statistical Software* 80, 3 (2017), 1-41.

Kuhn E, Lavielle M. Maximum likelihood estimation in nonlinear mixed effects models. *Computational Statistics and Data Analysis* 49, 4 (2005), 1020-1038.

Comets E, Lavenu A, Lavielle M. SAEMIX, an R version of the SAEM algorithm. 20th meeting of the Population Approach Group in Europe, Athens, Greece (2011), Abstr 2173.

See Also

[SaemixObject](#), [saemix](#), [default.saemix.plots](#), [saemix.plot.setoptions](#), [saemix.plot.data](#), [saemix.plot.convergence](#), [saemix.plot.llis](#), [saemix.plot.randeff](#), [saemix.plot.obsvspred](#), [saemix.plot.fits](#), [saemix.plot.parcov](#), [saemix.plot.randeffcov](#), [saemix.plot.distpsi](#), [saemix.plot.scatterresiduals](#), [saemix.plot.distribresiduals](#), [saemix.plot.vpc](#)

Examples

```
data(theo.saemix)

saemix.data<-saemixData(name.data=theo.saemix,header=TRUE,sep=" ",na=NA,
  name.group=c("Id"),name.predictors=c("Dose","Time"),
  name.response=c("Concentration"),name.covariates=c("Weight","Sex"),
  units=list(x="hr",y="mg/L",covariates=c("kg","-")), name.X="Time")

modellcpt<-function(psi,id,xidep) {
  dose<-xidep[,1]
  tim<-xidep[,2]
  ka<-psi[id,1]
  V<-psi[id,2]
  CL<-psi[id,3]
  k<-CL/V
  ypred<-dose*ka/(V*(ka-k))*(exp(-k*tim)-exp(-ka*tim))
  return(ypred)
}

saemix.model<-saemixModel(model=modellcpt,
  description="One-compartment model with first-order absorption",
  psi0=matrix(c(1.,20,0.5,0.1,0,-0.01),ncol=3, byrow=TRUE,
  dimnames=list(NULL, c("ka","V","CL"))),transform.par=c(1,1,1),
  covariate.model=matrix(c(0,1,0,0,0,0),ncol=3,byrow=TRUE),fixed.estim=c(1,1,1),
  covariance.model=matrix(c(1,0,0,0,1,0,0,0,1),ncol=3,byrow=TRUE),
  omega.init=matrix(c(1,0,0,0,1,0,0,0,1),ncol=3,byrow=TRUE),error.model="constant")

saemix.options<-list(seed=632545,save=FALSE,save.graphs=FALSE)
```

```
# Not run (strict time constraints for CRAN)
# saemix.fit<-saemix(saemix.model,saemix.data,saemix.options)

# saemix.plot.select(saemix.fit,data=TRUE,main="Spaghetti plot of data")

# Putting several graphs on the same plot
# par(mfrow=c(2,2))
# saemix.plot.select(saemix.fit,data=TRUE,vpc=TRUE,observations.vs.predictions=TRUE, new=FALSE)
```

saemix.plot.setoptions

Function setting the default options for the plots in SAEM

Description

- `ablinecol` Color of the lines added to the plots (default: "DarkRed")
- `ablinelty` Type of the lines added to the plots. Defaults to 2 (dashed line)
- `ablinelwd` Width of the lines added to the plots (default: 2)
- `ask` A logical value. If TRUE, users will be prompted before each new plot. Defaults to FALSE
- `cex` A numerical value giving the amount by which plotting text and symbols should be magnified relative to the default. Defaults to 1 (no magnification)
- `cex.axis` Magnification to be used for axis annotation relative to the current setting of 'cex'. Defaults to 1 (no magnification)
- `cex.main` Magnification to be used for main titles relative to the current setting of 'cex'. Defaults to 1 (no magnification)
- `cex.lab` Magnification to be used for x and y labels relative to the current setting of 'cex'. Defaults to 1 (no magnification)
- `col.fillmed` For the VPC plots: color filling the prediction interval for the median. Defaults to "pink"
- `col.fillpi` For the VPC plots: color filling the prediction interval for the limits of the prediction interval. Defaults to "slategray1"
- `col.lmed` For the VPC plots: color of the line showing the median of the simulated data. Defaults to "indianred4"
- `col.lobs` For the VPC plots: color of the lines showing the median, 2.5 and 97.5th percentiles (for a 95
- `col.lpi` For the VPC plots: color of the line showing the boundaries of the prediction intervals. Defaults to "slategray4"
- `col.obs` For the VPC plots: color used to plot the observations. Defaults to "steelblue4"
- `cov.name` Name of the covariate to be used in the plots. Defaults to the first covariate in the model

- cov.value Value of the covariate to be used in the plots. Defaults to NA, indicating that the median value of the covariate (for continuous covariates) or the reference category (for categorical covariates) will be used
- ilist List of indices of subjects to be included in the individual plots (defaults to all subjects)
- indiv.par a string, giving the type of the individual estimates ("map"= conditional mode, "eap"=conditional mean). Defaults to conditional mode
- lcol Main line color (default: black)
- line.smooth Type of smoothing when a smoothed line is used in the plot ("m": mean value, "l": linear regression; "s": natural splines). Several options may be combined, for instance "ls" will add both a linear regression line and a line representing the fit of a natural spline. Defaults to "s"
- lty Line type. Defaults to 1, corresponding to a straight line
- lty.lmed For the VPC plots: type of the line showing the median of the simulated data. Defaults to 2 (dashed)
- lty.obs For the VPC plots: type of the line showing the observed data. Defaults to 1
- lty.lpi For the VPC plots: type of the line showing the boundaries of the simulated data. Defaults to 2 (dashed)
- lwd Line width (default: 1)
- lwd.lmed For the VPC plots: thickness of the line showing the median of the simulated data. Defaults to 2
- lwd.obs For the VPC plots: thickness of the line showing the median and boundaries of the observed data. Defaults to 2
- lwd.lpi For the VPC plots: thickness of the line showing the boundaries of the simulated data. Defaults to 1
- par.name Name of the parameter to be used in the plots. Defaults to the first parameter in the model
- pch Symbol type. Defaults to 20, corresponding to small dots
- pcol Main symbol color (default: black)
- range Range (expressed in number of SD) over which to plot the marginal distribution. Defaults to 4, so that the random effects for the marginal distribution is taken over the range [-4 SD; 4 SD]
- res.plot Type of residual plot ("res.vs.x": scatterplot versus X, "res.vs.pred": scatterplot versus predictions, "hist": histogram, "qqplot": QQ-plot) (default: "res.vs.x")
- smooth When TRUE, smoothed lines are added in the plots of predictions versus observations (default: FALSE)
- tit Title of the graph (default: none)
- type Type of the plot (as in the R plot function. Defaults to "b", so that both lines and symbols are shown
- units Name of the predictor used in the plots (X). Defaults to the name of the first predictor in the model (saemix.data\$names\$predictors[1])
- vpc.bin Number of binning intervals when plotting the VPC (the (vpc.bin-1) breakpoints are taken as the empirical quantiles of the X data). Defaults to 10

- `vpc.interval` Size of the prediction intervals. Defaults to 0.95 for the 95% prediction interval
- `vpc.obs` Should the observations be overlaid on the VPC plot. Defaults to TRUE
- `vpc.pi` Should prediction bands be computed around the median and the bounds of the prediction intervals for the VPC. Defaults to TRUE
- `xlab` Label for the X-axis. Defaults to the name of the X predictor followed by the unit in bracket (eg "Time (hr)")
- `xlim` Range for the X-axis. Defaults to NA, indicating that the range is to be set by the plot function
- `xlog` A logical value. If TRUE, a logarithmic scale is in use. Defaults to FALSE
- `xname` Name of the predictor used in the plots (X)
- `ylab` Label for the Y-axis. Defaults to the name of the response followed by the unit in bracket (eg "Concentration (mg/L)" (Default: none)
- `ylim` Range for the Y-axis. Defaults to NA, indicating that the range is to be set by the plot function
- `ylog` A logical value. If TRUE, a logarithmic scale is in use. Defaults to FALSE

Plotting a SaemixData object also allows the following options:

individual if TRUE, plots separate plots for each individual, otherwise plots a spaghetti plot of all the data. Defaults to FALSE

limit for individual plots, plots only a limited number of subjects (nmax). Defaults to TRUE

nmax for individual plots, when limit is TRUE, the maximum number of plots to produce. Defaults to 12

sample for individual plots, if TRUE, randomly samples nmax different subjects to plot. Defaults to FALSE (the first nmax subjects are used in the plots)

Usage

```
saemix.plot.setoptions(saemixObject)
```

Arguments

`saemixObject` an object returned by the `saemix` function

Details

This function can be used to create a list containing the default options and arguments used by the plot functions.

A more detailed description of the options set via these lists is provided in the PDF documentation. The "replace" functions are helper functions used within the plot functions. `saemix.plot.setoptions` has more available options than `saemix.data.setoptions` since it applies to all possible plots while the latter only applies to data.

Value

A list containing the options set at their default value. This list can be stored in an object and its elements modified to provide suitable graphs.

Author(s)

Emmanuelle Comets <emmanuelle.comets@inserm.fr>, Audrey Lavenu, Marc Lavielle.

References

Comets E, Lavenu A, Lavielle M. Parameter estimation in nonlinear mixed effect models using saemix, an R implementation of the SAEM algorithm. *Journal of Statistical Software* 80, 3 (2017), 1-41.

Kuhn E, Lavielle M. Maximum likelihood estimation in nonlinear mixed effects models. *Computational Statistics and Data Analysis* 49, 4 (2005), 1020-1038.

Comets E, Lavenu A, Lavielle M. SAEMIX, an R version of the SAEM algorithm. 20th meeting of the Population Approach Group in Europe, Athens, Greece (2011), Abstr 2173.

See Also

[SaemixObject](#), [saemix](#), [saemix.plot.data](#), [saemix.plot.convergence](#), [saemix.plot.llis](#), [saemix.plot.randeff](#), [saemix.plot.obsvspred](#), [saemix.plot.fits](#), [saemix.plot.parcov](#), [saemix.plot.distpsi](#), [saemix.plot.scatterres](#), [saemix.plot.vpc](#)

Examples

```
# Theophylline example, after a call to fit.saemix (see examples)
# Not run
# sopt<-saemix.plot.setoptions(saemix.fit)
# sopt$ask<-TRUE
```

saemix.predict

Compute model predictions after an saemix fit

Description

In nonlinear mixed effect models, different types of predictions may be obtained, including individual predictions and population predictions

Usage

```
saemix.predict(object)
```

Arguments

object an SaemixObject object

Value

an updated SaemixObject object

saemixControl *List of options for running the algorithm SAEM*

Description

List containing the variables relative to the optimisation algorithm. All these elements are optional and will be set to default values when running the algorithm if they are not specified by the user.

Usage

```
saemixControl(map = TRUE, fim = TRUE, ll.is = TRUE, ll.gq = FALSE,
  nbiter.saemix = c(300, 100), nb.chains = 1, fix.seed = TRUE,
  seed = 23456, nmc.is = 5000, nu.is = 4, print.is = FALSE,
  nbdisplay = 100, displayProgress = TRUE, nbiter.burn = 5,
  nbiter.mcmc = c(2, 2, 2), proba.mcmc = 0.4, stepsize.rw = 0.4,
  rw.init = 0.5, alpha.sa = 0.97, nnodes.gq = 12, nsd.gq = 4,
  maxim.maxiter = 100, nb.sim = 1000, nb.simpred = 100,
  ipar.lmcmc = 50, ipar.rmcmc = 0.05, print = TRUE, save = TRUE,
  save.graphs = TRUE, directory = "newdir", warnings = FALSE)
```

Arguments

map	a boolean specifying whether to estimate the individual parameters (MAP estimates). Defaults to TRUE
fim	a boolean specifying whether to estimate the Fisher Information Matrix and derive the estimation errors for the parameters. Defaults to TRUE. The linearised approximation to the log-likelihood is also computed in the process
ll.is	a boolean specifying whether to estimate the log-likelihood by importance sampling. Defaults to TRUE
ll.gq	a boolean specifying whether to estimate the log-likelihood by Gaussian quadrature. Defaults to FALSE
nbiter.saemix	nb of iterations in each step (a vector containing 2 elements)
nb.chains	nb of chains to be run in parallel in the MCMC algorithm. Defaults to 1.
fix.seed	TRUE (default) to use a fixed seed for the random number generator. When FALSE, the random number generator is initialised using a new seed, created from the current time. Hence, different sessions started at (sufficiently) different times will give different simulation results. The seed is stored in the element seed of the options list.
seed	seed for the random number generator. Defaults to 123456
nmc.is	nb of samples used when computing the likelihood through importance sampling
nu.is	number of degrees of freedom of the Student distribution used for the estimation of the log-likelihood by Importance Sampling. Defaults to 4
print.is	when TRUE, a plot of the likelihood as a function of the number of MCMC samples when computing the likelihood through importance sampling is produced and updated every 500 samples. Defaults to FALSE

nbdisplay	nb of iterations after which to display progress
displayProgress	when TRUE, the convergence plots are plotted after every nbdisplay iteration, and a dot is written in the terminal window to indicate progress. When FALSE, plots are not shown and the algorithm runs silently. Defaults to TRUE
nbiter.burn	nb of iterations for burning
nbiter.mcmc	nb of iterations in each kernel during the MCMC step
proba.mcmc	probability of acceptance
stepsize.rw	stepsize for kernels q2 and q3. Defaults to 0.4
rw.init	initial variance parameters for kernels. Defaults to 0.5
alpha.sa	parameter controlling cooling in the Simulated Annealing algorithm. Defaults to 0.97
nnodes.gq	number of nodes to use for the Gaussian quadrature when computing the likelihood with this method (defaults to 12)
nsd.gq	span (in SD) over which to integrate when computing the likelihood by Gaussian quadrature. Defaults to 4 (eg 4 times the SD)
maxim.maxiter	Maximum number of iterations to use when maximising the fixed effects in the algorithm. Defaults to 100
nb.sim	number of simulations to perform to produce the VPC plots or compute npde. Defaults to 1000
nb.simpred	number of simulations used to compute mean predictions (ypred element), taken as a random sample within the nb.sim simulations used for npde
ipar.lmcmc	number of iterations required to assume convergence for the conditional estimates. Defaults to 50
ipar.rmcmc	confidence interval for the conditional mean and variance. Defaults to 0.95
print	whether the results of the fit should be printed out. Defaults to TRUE
save	whether the results of the fit should be saved to a file. Defaults to TRUE
save.graphs	whether diagnostic graphs and individual graphs should be saved to files. Defaults to TRUE
directory	the directory in which to save the results. Defaults to "newdir" in the current directory
warnings	whether warnings should be output during the fit. Defaults to FALSE

Details

All the variables are optional and will be set to their default value when running [saemix](#).

The function [saemix](#) returns an object with an element options containing the options used for the algorithm, with defaults set for elements which have not been specified by the user.

These elements are used in subsequent functions and are not meant to be used directly.

Author(s)

Emmanuelle Comets <emmanuelle.comets@inserm.fr>, Audrey Lavenu, Marc Lavielle.

References

Comets E, Lavenu A, Lavielle M. Parameter estimation in nonlinear mixed effect models using saemix, an R implementation of the SAEM algorithm. *Journal of Statistical Software* 80, 3 (2017), 1-41.

Kuhn E, Lavielle M. Maximum likelihood estimation in nonlinear mixed effects models. *Computational Statistics and Data Analysis* 49, 4 (2005), 1020-1038.

Comets E, Lavenu A, Lavielle M. SAEMIX, an R version of the SAEM algorithm. 20th meeting of the Population Approach Group in Europe, Athens, Greece (2011), Abstr 2173.

See Also

[SaemixData](#), [SaemixModel](#), [SaemixObject](#), [saemix](#)

Examples

```
# All default options
saemix.options<-saemixControl()

# All default options, changing seed
saemix.options<-saemixControl(seed=632545)
```

saemixData

Function to create a SaemixData object

Description

This function creates a SaemixData object. The only mandatory argument is the name of the dataset. If the dataset has a header (or named columns), the program will attempt to detect which column correspond to ID, predictor(s) and response. Warning messages will be printed during the object creation and should be read for details.

Usage

```
saemixData(name.data, header, sep, na, name.group, name.predictors,
  name.response, name.X, name.covariates = c(),
  name.genetic.covariates = c(), name.mdv = "", name.cens = "",
  name.occ = "", name.ytype = "", units = list(x = "", y = ""),
  covariates = c()), verbose = TRUE)
```

Arguments

<code>name.data</code>	name of the dataset (can be a character string giving the name of a file on disk or of a dataset in the R session, or the name of a dataset)
<code>header</code>	whether the dataset/file contains a header. Defaults to TRUE
<code>sep</code>	the field separator character. Defaults to any number of blank spaces ("")
<code>na</code>	a character vector of the strings which are to be interpreted as NA values. Defaults to <code>c(NA)</code>
<code>name.group</code>	name (or number) of the column containing the subject id
<code>name.predictors</code>	name (or number) of the column(s) containing the predictors (the algorithm requires at least one predictor <code>x</code>)
<code>name.response</code>	name (or number) of the column containing the response variable <code>y</code> modelled by predictor(s) <code>x</code>
<code>name.X</code>	name of the column containing the regression variable to be used on the X axis in the plots (defaults to the first predictor)
<code>name.covariates</code>	name (or number) of the column(s) containing the covariates, if present (otherwise missing)
<code>name.genetic.covariates</code>	name (or number) of the column(s) containing the covariates, if present (otherwise missing)
<code>name.mdv</code>	name of the column containing the indicator for missing variable
<code>name.cens</code>	name of the column containing the indicator for censoring
<code>name.occ</code>	name of the column containing the occasion
<code>name.ytype</code>	name of the column containing the index of the response
<code>units</code>	list with up to three elements, <code>x</code> , <code>y</code> and optionally <code>covariates</code> , containing the units for the X and Y variables respectively, as well as the units for the different covariates (defaults to empty)
<code>verbose</code>	a boolean indicating whether messages should be printed out during the creation of the object

Details

This function is the user-friendly constructor for the `SaemixData` object class. The `read.saemixData` is a helper function, used to read the dataset, and is not intended to be called directly.

This function is the user-friendly constructor for the `SaemixData` object class. The `read` is a helper function, used to read the dataset, and is not intended to be called directly.

Value

A `SaemixData` object (see [saemixData](#)).

Author(s)

Emmanuelle Comets <emmanuelle.comets@inserm.fr>, Audrey Lavenu, Marc Lavielle.

References

Comets E, Lavenu A, Lavielle M. Parameter estimation in nonlinear mixed effect models using saemix, an R implementation of the SAEM algorithm. *Journal of Statistical Software* 80, 3 (2017), 1-41.

Kuhn E, Lavielle M. Maximum likelihood estimation in nonlinear mixed effects models. *Computational Statistics and Data Analysis* 49, 4 (2005), 1020-1038.

Comets E, Lavenu A, Lavielle M. SAEMIX, an R version of the SAEM algorithm. 20th meeting of the Population Approach Group in Europe, Athens, Greece (2011), Abstr 2173.

See Also

[SaemixData](#), [SaemixModel](#), [saemixControl](#), [saemix](#)

Examples

```
data(theo.saemix)

saemix.data<-saemixData(name.data=theo.saemix,header=TRUE,sep=" ",na=NA,
  name.group=c("Id"),name.predictors=c("Dose","Time"),
  name.response=c("Concentration"),name.covariates=c("Weight","Sex"),
  units=list(x="hr",y="mg/L",covariates=c("kg","-")), name.X="Time")

print(saemix.data)

plot(saemix.data)
```

SaemixData-class	<i>Class "SaemixData"</i>
------------------	---------------------------

Description

An object of the SaemixData class, representing a longitudinal data structure, used by the SAEM algorithm.

Slots

`name.data` Object of class "character": name of the dataset
`@slot header` Object of class "logical": whether the dataset/file contains a header. Defaults to TRUE
`@slot sep` Object of class "character": the field separator character
`@slot na` Object of class "character": a character vector of the strings which are to be interpreted as NA values
`@slot messages` Object of class "logical": if TRUE, the program will display information about the creation of the data object
`@slot name.group` Object of class "character": name of the column containing the subject id
`@slot name.predictors` Object of class "character": name of the column(s) containing the predictors
`@slot name.response` Object of class "character": name of the column containing the response variable y modelled by predictor(s) x
`@slot name.covariates` Object of class "character": name of the column(s) containing the covariates, if present

(otherwise empty) @slot name.X Object of class "character": name of the column containing the regression variable to be used on the X axis in the plots @slot name.mdv Object of class "character": name of the column containing the indicator variable denoting missing data @slot name.cens Object of class "character": name of the column containing the indicator variable denoting censored data (the value in the name.response column will be taken as the censoring value) @slot name.occ Object of class "character": name of the column containing the value of the occasion @slot name.ytype Object of class "character": name of the column containing the response number @slot trans.cov Object of class "list": the list of transformation applied to the covariates (currently unused, TODO) @slot units Object of class "list": list with up to three elements, x, y and optionally covariates, containing the units for the X and Y variables respectively, as well as the units for the different covariates @slot data Object of class "data.frame": dataframe containing the data, with columns for id (name.group), predictors (name.predictors), response (name.response), and covariates if present in the dataset (name.covariates). A column "index" contains the subject index (used to map the subject id). The column names, except for the additional column index, correspond to the names in the original dataset. @slot N Object of class "numeric": number of subjects @slot yorig Object of class "numeric": response data, on the original scale. Used when the error model is exponential @slot ocov Object of class "data.frame": original covariate data (before transformation in the algorithm) @slot ind.gen Object of class "logical": indicator for genetic covariates (internal) @slot ntot.obs Object of class "numeric": total number of observations @slot nind.obs Object of class "numeric": vector containing the number of observations for each subject

Objects from the Class

An object of the SaemixData class can be created by using the function `saemixData` and contain the following slots:

Methods

`[<-` signature(x = "SaemixData"): replace elements of object

`[` signature(x = "SaemixData"): access elements of object

initialize signature(.Object = "SaemixData"): internal function to initialise object, not to be used

plot signature(x = "SaemixData"): plot the data

print signature(x = "SaemixData"): prints details about the object (more extensive than show)

read signature(object = "SaemixData"): internal function, not to be used

showall signature(object = "SaemixData"): shows all the elements in the object

show signature(object = "SaemixData"): prints details about the object

summary signature(object = "SaemixData"): summary of the data. Returns a list with a number of elements extracted from the dataset (N: the number of subjects; nobs: the total number of observations; nind.obs: a vector giving the number of observations for each subject; id: subject ID; x: predictors; y: response, and, if present in the data, covariates: the covariates (as many lines as observations) and ind.covariates: the individual covariates (one line per individual).

subset signature(object = "SaemixData"): extract part of the data; this function will operate on the rows of the dataset (it can be used for instance to extract the data corresponding to the first ten subjects)

Author(s)

Emmanuelle Comets <emmanuelle.comets@inserm.fr>

Audrey Lavenu

Marc Lavielle.

References

Comets E, Lavenu A, Lavielle M. Parameter estimation in nonlinear mixed effect models using saemix, an R implementation of the SAEM algorithm. *Journal of Statistical Software* 80, 3 (2017), 1-41.

Kuhn E, Lavielle M. Maximum likelihood estimation in nonlinear mixed effects models. *Computational Statistics and Data Analysis* 49, 4 (2005), 1020-1038.

Comets E, Lavenu A, Lavielle M. SAEMIX, an R version of the SAEM algorithm. 20th meeting of the Population Approach Group in Europe, Athens, Greece (2011), Abstr 2173.

See Also

[saemixData](#) [SaemixModel](#) [saemixControl](#) [saemix](#)

Examples

```
showClass("SaemixData")

# Specifying column names
data(theo.saemix)
saemix.data<-saemixData(name.data=theo.saemix,header=TRUE,sep=" ",na=NA,
  name.group=c("Id"),name.predictors=c("Dose","Time"),
  name.response=c("Concentration"),name.covariates=c("Weight","Sex"),
  units=list(x="hr",y="mg/L",covariates=c("kg","-")), name.X="Time")

# Specifying column numbers
data(theo.saemix)
saemix.data<-saemixData(name.data=theo.saemix,header=TRUE,sep=" ",na=NA,
  name.group=1,name.predictors=c(2,3),name.response=c(4), name.covariates=5:6,
  units=list(x="hr",y="mg/L",covariates=c("kg","-")), name.X="Time")

# No column names specified, using automatic recognition of column names
data(PD1.saemix)
saemix.data<-saemixData(name.data=PD1.saemix,header=TRUE,
  name.covariates=c("gender"),units=list(x="mg",y="-",covariates=c("-")))
```

 saemixModel

Function to create a SaemixModel object

Description

This function creates a SaemixModel object. The two mandatory arguments are the name of a R function computing the model in the SAEMIX format (see details and examples) and a matrix psi0 giving the initial estimates of the fixed parameters in the model, with one row for the population mean parameters and one row for the covariate effects (see documentation).

Usage

```
saemixModel(model, psi0, description = "", name.response = "",
  name.sigma = character(), error.model = character(),
  transform.par = numeric(), fixed.estim = numeric(),
  covariate.model = matrix(nrow = 0, ncol = 0),
  covariance.model = matrix(nrow = 0, ncol = 0),
  omega.init = matrix(nrow = 0, ncol = 0), error.init = numeric(),
  name.modpar = character(), verbose = TRUE)
```

Arguments

model	name of the function used to compute the structural model. The function should return a vector of predicted values given a matrix of individual parameters, a vector of indices specifying which records belong to a given individual, and a matrix of dependent variables (see example below).
psi0	a matrix with a number of columns equal to the number of parameters in the model, and one (when no covariates are available) or two (when covariates enter the model) giving the initial estimates for the fixed effects. The column names of the matrix should be the names of the parameters in the model, and will be used in the plots and the summaries. When only the estimates of the mean parameters are given, psi0 may be a named vector.
description	a character string, giving a brief description of the model or the analysis
name.response	the name of the dependent variable
name.sigma	a vector of character string giving the names of the residual error parameters
error.model	type of residual error model (valid types are constant, proportional, combined and exponential). Defaults to constant
transform.par	the distribution for each parameter (0=normal, 1=log-normal, 2=probit, 3=logit). Defaults to a vector of 1s (all parameters have a log-normal distribution)
fixed.estim	whether parameters should be estimated (1) or fixed to their initial estimate (0). Defaults to a vector of 1s
covariate.model	a matrix giving the covariate model. Defaults to no covariate in the model

covariance.model	a square matrix of size equal to the number of parameters in the model, giving the variance-covariance matrix of the model: 1s correspond to estimated variances (in the diagonal) or covariances (off-diagonal elements). Defaults to the identity matrix
omega.init	a square matrix of size equal to the number of parameters in the model, giving the initial estimate for the variance-covariance matrix of the model. Defaults to the identity matrix
error.init	a vector of size 2 giving the initial value of a and b in the error model. Defaults to 1 for each estimated parameter in the error model
name.modpar	names of the model parameters, if they are not given as the column names (or names) of psi0
verbose	a boolean, controlling whether information about the created should be printed out. Defaults to TRUE

Details

This function is the user-friendly constructor for the SaemixModel object class.

Value

A SaemixModel object (see [saemixModel](#)).

Author(s)

Emmanuelle Comets <emmanuelle.comets@inserm.fr>, Audrey Lavenu, Marc Lavielle.

References

Comets E, Lavenu A, Lavielle M. Parameter estimation in nonlinear mixed effect models using saemix, an R implementation of the SAEM algorithm. *Journal of Statistical Software* 80, 3 (2017), 1-41.

Kuhn E, Lavielle M. Maximum likelihood estimation in nonlinear mixed effects models. *Computational Statistics and Data Analysis* 49, 4 (2005), 1020-1038.

Comets E, Lavenu A, Lavielle M. SAEMIX, an R version of the SAEM algorithm. 20th meeting of the Population Approach Group in Europe, Athens, Greece (2011), Abstr 2173.

See Also

[SaemixData](#), [SaemixModel](#), [saemixControl](#), [saemix](#)

Examples

```
model1cpt<-function(psi,id,xidep) {
  dose<-xidep[,1]
  tim<-xidep[,2]
  ka<-psi[id,1]
  V<-psi[id,2]
```

```

CL<-psi[id,3]
k<-CL/V
ypred<-dose*ka/(V*(ka-k))*(exp(-k*tim)-exp(-ka*tim))
return(ypred)
}

saemix.model<-saemixModel(model=model1cpt,
  description="One-compartment model with first-order absorption",
  psi0=matrix(c(1.,20,0.5,0.1,0,-0.01),ncol=3, byrow=TRUE,
  dimnames=list(NULL, c("ka","V","CL"))),transform.par=c(1,1,1),
  covariate.model=matrix(c(0,1,0,0,0,0),ncol=3,byrow=TRUE),fixed.estim=c(1,1,1),
  covariance.model=matrix(c(1,0,0,0,1,0,0,0,1),ncol=3,byrow=TRUE),
  omega.init=matrix(c(1,0,0,0,1,0,0,0,1),ncol=3,byrow=TRUE),error.model="constant")

```

SaemixModel-class *Class "SaemixModel"*

Description

An object of the SaemixModel class, representing a nonlinear mixed-effect model structure, used by the SAEM algorithm.

Objects from the Class

An object of the SaemixModel class can be created by using the function `saemixModel` and contain the following slots:

- model:** Object of class "function": name of the function used to get predictions from the model (see the User Guide and the online examples for the format and what this function should return).
- description:** Object of class "character": an optional text description of the model
- psi0:** Object of class "matrix": a matrix with named columns containing the initial estimates for the parameters in the model (first line) and for the covariate effects (second and subsequent lines, optional). The number of columns should be equal to the number of parameters in the model.
- transform.par:** Object of class "numeric": vector giving the distribution for each model parameter (0: normal, 1: log-normal, 2: logit, 3: probit). Its length should be equal to the number of parameters in the model.
- fixed.estim:** Object of class "numeric": for each parameter, 0 if the parameter is fixed and 1 if it should be estimated. Defaults to a vector of 1 (all parameters are estimated). Its length should be equal to the number of parameters in the model.
- error.model:** Object of class "character": name of the error model. Valid choices are "constant" (default), "proportional" and "combined" (see equations in User Guide)
- covariate.model:** Object of class "matrix": a matrix of 0's and 1's, with a 1 indicating that a parameter-covariate relationship is included in the model (and an associated fixed effect will be estimated). The number of columns should be equal to the number of parameters in the model and the number of rows to the number of covariates.

`covariance.model`: Object of class "matrix": a matrix of 0's and 1's giving the structure of the variance-covariance matrix. Defaults to the Identity matrix (diagonal IIV, no correlations between parameters)

`omega.init`: Object of class "matrix": a matrix giving the initial estimate for the variance-covariance matrix

`error.init`: Object of class "numeric": a vector giving the initial estimate for the parameters of the residual error

Additional elements are added to the model object after a call to `saemix` and are used in the algorithm.

Methods

`[<- signature(x = "SaemixModel")`: replace elements of object

`[signature(x = "SaemixModel")`: access elements of object

initialize `signature(.Object = "SaemixModel")`: internal function to initialise object, not to be used

plot `signature(x = "SaemixModel")`: plot predictions from the model

print `signature(x = "SaemixModel")`: prints details about the object (more extensive than `show`)

showall `signature(object = "SaemixModel")`: shows all the elements in the object

show `signature(object = "SaemixModel")`: prints details about the object

Author(s)

Emmanuelle Comets <emmanuelle.comets@inserm.fr>

Audrey Lavenu

Marc Lavielle.

References

Comets E, Lavenu A, Lavielle M. Parameter estimation in nonlinear mixed effect models using `saemix`, an R implementation of the SAEM algorithm. *Journal of Statistical Software* 80, 3 (2017), 1-41.

Kuhn E, Lavielle M. Maximum likelihood estimation in nonlinear mixed effects models. *Computational Statistics and Data Analysis* 49, 4 (2005), 1020-1038.

Comets E, Lavenu A, Lavielle M. SAEMIX, an R version of the SAEM algorithm. 20th meeting of the Population Approach Group in Europe, Athens, Greece (2011), Abstr 2173.

See Also

[SaemixData](#) [SaemixObject](#) [saemixControl](#) [saemix plot.saemix](#)

Examples

```
showClass("SaemixModel")
```

SaemixObject-class *Class "SaemixObject"*

Description

An object of the SaemixObject class, storing the input to saemix, and the results obtained by a call to the SAEM algorithm

Details

Details of the algorithm can be found in the pdf file accompanying the package.

Objects from the Class

An object of the SaemixObject class is created after a call to `saemix` and contain the following slots:

`data`: Object of class "SaemixData": saemix dataset, created by a call to `saemixData`

`model`: Object of class "SaemixModel": saemix model, created by a call to `saemixModel`

`results`: Object of class "SaemixData": saemix dataset, created by a call to `saemixData`

`rep.data`: Object of class "SaemixRepData": (internal) replicated saemix dataset, used the execution of the algorithm

`sim.data`: Object of class "SaemixSimData": simulated saemix dataset

`options`: Object of class "list": list of settings for the algorithm

`prefs`: Object of class "list": list of graphical options for the graphs

Methods

`[<- signature(x = "SaemixObject")`: replace elements of object

`[signature(x = "SaemixObject")`: access elements of object

initialize `signature(.Object = "SaemixObject")`: internal function to initialise object, not to be used

plot `signature(x = "SaemixObject")`: plot the data

print `signature(x = "SaemixObject")`: prints details about the object (more extensive than `show`)

showall `signature(object = "SaemixObject")`: shows all the elements in the object

show `signature(object = "SaemixObject")`: prints details about the object

summary `signature(object = "SaemixObject")`: summary of the object. Returns a list with a number of elements extracted from the object.

Author(s)

Emmanuelle Comets <emmanuelle.comets@inserm.fr>

Audrey Lavenu

Marc Lavielle.

References

Kuhn E, Lavielle M. Maximum likelihood estimation in nonlinear mixed effects models. *Computational Statistics and Data Analysis* 49, 4 (2005), 1020-1038.

Comets E, Lavenu A, Lavielle M. SAEMIX, an R version of the SAEM algorithm. 20th meeting of the Population Approach Group in Europe, Athens, Greece (2011), Abstr 2173.

See Also

[SaemixData](#) [SaemixModel](#) [saemixControl](#) [saemix](#) [plot.saemix](#),

Examples

```
showClass("SaemixObject")
```

SaemixRes-class	<i>Class "SaemixRes"</i>
-----------------	--------------------------

Description

An object of the SaemixRes class, representing the results of a fit through the SAEM algorithm.

Slots

`name.fixed` a vector containing the names of the fixed parameters in the model
`name.random` a vector containing the names of the random parameters in the model
`name.sigma` a vector containing the names of the parameters of the residual error model
`npar.est` the number of parameters estimated (fixed, random and residual)
`fixed.effects` a vector giving the estimated $h(\mu)$ and betas
`fixed.psi` a vector giving the estimated $h(\mu)$
`betas` a vector giving the estimated μ
`betaC` a vector with the estimates of the fixed effects for covariates
`omega` the estimated variance-covariance matrix
`respar` the estimated parameters of the residual error model
`fim` the Fisher information matrix
`se.fixed` a vector giving the estimated standard errors of estimation for the fixed effect parameters
`se.omega` a vector giving the estimated standard errors of estimation for Ω
`se.cov` a matrix giving the estimated SE for each term of the covariance matrix (diagonal elements represent the SE on the variances of the random effects and off-diagonal elements represent the SE on the covariance terms)
`se.respar` a vector giving the estimated standard errors of estimation for the parameters of the residual variability

`parpop` a matrix tracking the estimates of the population parameters at each iteration
`allpar` a matrix tracking the estimates of all the parameters (including covariate effects) at each iteration
`indx.fix` the index of the fixed parameters (used in the estimation algorithm)
`indx.cov` the index of the covariance parameters (used in the estimation algorithm)
`indx.omega` the index of the random effect parameters (used in the estimation algorithm)
`indx.res` the index of the residual error model parameters (used in the estimation algorithm)
`MCOV` a matrix of covariates (used in the estimation algorithm)
`cond.mean.phi` a matrix giving the conditional mean estimates of phi (estimated as the mean of the conditional distribution)
`cond.mean.psi` a matrix giving the conditional mean estimates of psi ($h(\text{cond.mean.phi})$)
`cond.var.phi` a matrix giving the variance on the conditional mean estimates of phi (estimated as the variance of the conditional distribution)
`cond.mean.eta` a matrix giving the conditional mean estimates of the random effect eta
`cond.shrinkage` a vector giving the shrinkage on the conditional mean estimates of eta
`mean.phi` a matrix giving the population estimate ($C_i \cdot \mu$) including covariate effects
`map.psi` a matrix giving the MAP estimates of individual parameters
`map.phi` a matrix giving the MAP estimates of individual phi
`map.eta` a matrix giving the individual estimates of the random effects corresponding to the MAP estimates
`map.shrinkage` a vector giving the shrinkage on the MAP estimates of eta
`phi` phi
`psi.samp` a three-dimensional array with samples of psi from the conditional distribution
`phi.samp` a three-dimensional array with samples of phi from the conditional distribution
`phi.samp.var` a three-dimensional array with the variance of phi
`ll.lin` log-likelihood computed by linearisation
`aic.lin` Akaike Information Criterion computed by linearisation
`bic.lin` Bayesian Information Criterion computed by linearisation
`ll.is` log-likelihood computed by Importance Sampling
`aic.is` Akaike Information Criterion computed by Importance Sampling
`bic.is` Bayesian Information Criterion computed by Importance Sampling
`LL` a vector giving the conditional log-likelihood at each iteration of the algorithm
`ll.gq` log-likelihood computed by Gaussian Quadrature
`aic.gq` Akaike Information Criterion computed by Gaussian Quadrature
`bic.gq` Bayesian Information Criterion computed by Gaussian Quadrature
`predictions` a data frame containing all the predictions and residuals in a table format
`ypred` a vector giving the mean population predictions
`ppred` a vector giving the population predictions obtained with the MAP estimates

ipred a vector giving the individual predictions obtained with the MAP estimates
 icpred a vector giving the individual predictions obtained with the conditional estimates
 ired a vector giving the individual residuals obtained with the MAP estimates
 iwres a vector giving the individual weighted residuals obtained with the MAP estimates
 icwres a vector giving the individual weighted residuals obtained with the conditional estimates
 wres a vector giving the population weighted residuals
 npde a vector giving the normalised prediction distribution errors
 pd a vector giving the prediction discrepancies

Objects from the Class

An object of the SaemixData class can be created by using the function `saemixData` and contain the following slots:

Methods

[<- signature(x = "SaemixRes"): replace elements of object
[signature(x = "SaemixRes"): access elements of object
initialize signature(.Object = "SaemixRes"): internal function to initialise object, not to be used
print signature(x = "SaemixRes"): prints details about the object (more extensive than show)
read signature(object = "SaemixRes"): internal function, not to be used
showall signature(object = "SaemixRes"): shows all the elements in the object
show signature(object = "SaemixRes"): prints details about the object
summary signature(object = "SaemixRes"): summary of the results. Returns a list with a number of elements extracted from the results ().

Author(s)

Emmanuelle Comets <emmanuelle.comets@inserm.fr>
 Audrey Lavenu
 Marc Lavielle.

References

Comets E, Lavenu A, Lavielle M. Parameter estimation in nonlinear mixed effect models using saemix, an R implementation of the SAEM algorithm. *Journal of Statistical Software* 80, 3 (2017), 1-41.
 Kuhn E, Lavielle M. Maximum likelihood estimation in nonlinear mixed effects models. *Computational Statistics and Data Analysis* 49, 4 (2005), 1020-1038.
 Comets E, Lavenu A, Lavielle M. SAEMIX, an R version of the SAEM algorithm. 20th meeting of the Population Approach Group in Europe, Athens, Greece (2011), Abstr 2173.

See Also

[saemixData](#) [SaemixModel](#) [saemixControl](#) [saemix](#)

Examples

```
methods(class="SaemixRes")

showClass("SaemixRes")
```

show-methods

Methods for Function show

Description

Prints a short summary of an object

Usage

```
## S4 method for signature 'SaemixData'
show(object)

## S4 method for signature 'SaemixRepData'
show(object)

## S4 method for signature 'SaemixSimData'
show(object)

## S4 method for signature 'SaemixModel'
show(object)

## S4 method for signature 'SaemixRes'
show(object)

## S4 method for signature 'SaemixObject'
show(object)
```

Arguments

object an object of type SaemixData, SaemixModel, SaemixRes or SaemixObject

Methods

```
list("signature(x = \"ANY\")") Default show function
list("signature(x = \"SaemixData\")") Prints a short summary of a SaemixData object
list("signature(x = \"SaemixModel\")") Prints a short summary of a SaemixModel object
```



```
list("signature(x = \"SaemixObject\")") Prints a short summary of the results from a SAEMIX
fit
list("signature(x = \"SaemixRes\")") Not user-level
list("signature(object = \"SaemixRepData\")") Prints a short summary of a SaemixRepData ob-
ject
list("signature(object = \"SaemixSimData\")") Prints a short summary of a SaemixSimData ob-
ject
```

showall-methods

Methods for Function showall

Description

This function is used to visualise the majority of the elements of an object

Usage

```
showall(object)

## S4 method for signature 'SaemixData'
showall(object)

## S4 method for signature 'SaemixModel'
showall(object)

## S4 method for signature 'SaemixRes'
showall(object)

## S4 method for signature 'SaemixObject'
showall(object)
```

Arguments

object	showall methods are available for objects of type SaemixData, SaemixModel and SaemixObject
--------	--

Value

None

Methods

```
list("signature(x = \"SaemixData\")") Prints a extensive summary of a SaemixData object
list("signature(x = \"SaemixModel\")") Prints a extensive summary of a SaemixModel object
list("signature(x = \"SaemixObject\")") Prints a extensive summary of the results from a SAEMIX
fit
list("signature(x = \"SaemixRes\")") Not user-level
```

See Also

[SaemixData](#), [SaemixModel](#), [SaemixObject](#)

Examples

```
# A SaemixData object
data(theo.saemix)
saemix.data<-saemixData(name.data=theo.saemix,header=TRUE,sep=" ",na=NA,
  name.group=c("Id"),name.predictors=c("Dose","Time"),
  name.response=c("Concentration"),name.covariates=c("Weight","Sex"),
  units=list(x="hr",y="mg/L",covariates=c("kg","-")), name.X="Time")
showall(saemix.data)

# A SaemixModel object
model1cpt<-function(psi,id,xidep) {
  dose<-xidep[,1]
  tim<-xidep[,2]
  ka<-psi[id,1]
  V<-psi[id,2]
  CL<-psi[id,3]
  k<-CL/V
  ypred<-dose*ka/(V*(ka-k))*(exp(-k*tim)-exp(-ka*tim))
  return(ypred)
}
saemix.model<-saemixModel(model=model1cpt,
  description="One-compartment model with first-order absorption",
  psi0=matrix(c(1.,20,0.5,0.1,0,-0.01),ncol=3, byrow=TRUE,
  dimnames=list(NULL, c("ka","V","CL"))),transform.par=c(1,1,1),
  covariate.model=matrix(c(0,1,0,0,0,0),ncol=3,byrow=TRUE),fixed.estim=c(1,1,1),
  covariance.model=matrix(c(1,0,0,0,1,0,0,0,1),ncol=3,byrow=TRUE),
  omega.init=matrix(c(1,0,0,0,1,0,0,0,1),ncol=3,byrow=TRUE),error.model="constant")
showall(saemix.model)
```

simul.saemix

Perform simulations under the model

Description

This function is used to simulate from the model. It can be called with the estimated parameters (the default), the initial parameters, or with a set of parameters. The original design can be used in the simulations, or a different dataset may be used with the same structure (covariates) as the original design. This function is not yet implemented.

Usage

```
simul.saemix(saemixObject, nsim = saemixObject["options"]$nb.sim,
  predictions = TRUE, res.var = TRUE, uncertainty = FALSE)
```

Arguments

saemixObject	an object returned by the saemix function
nsim	Number of simulations to perform. Defaults to the nb.simpred element in options
predictions	Whether the simulated parameters should be used to compute predictions. Defaults to TRUE
res.var	Whether residual variability should be added to the predictions. Defaults to TRUE
uncertainty	Uses uncertainty (currently not implemented). Defaults to FALSE

Details

This function is used to produce Visual Predictive Check graphs, as well as to compute the normalised prediction distribution errors (npde).

Author(s)

Emmanuelle Comets <emmanuelle.comets@inserm.fr>, Audrey Lavenu, Marc Lavielle.

References

Brendel, K, Comets, E, Laffont, C, Laveille, C, Mentre, F. Metrics for external model evaluation with an application to the population pharmacokinetics of gliclazide, *Pharmaceutical Research* 23 (2006), 2036-2049.

Holford, N. The Visual Predictive Check: superiority to standard diagnostic (Rorschach) plots (Abstract 738), in: 14th Meeting of the Population Approach Group in Europe, Pamplona, Spain, 2005.

See Also

[SaemixObject](#), [saemix](#), [saemix.plot.data](#), [saemix.plot.convergence](#), [saemix.plot.llis](#), [saemix.plot.randeff](#), [saemix.plot.obsvspred](#), [saemix.plot.fits](#), [saemix.plot.parcov](#), [saemix.plot.distpsi](#), [saemix.plot.scatterres](#), [saemix.plot.vpc](#)

subset.SaemixData *Data subsetting*

Description

Return an SaemixData object containing the subset of data which meets conditions.

Usage

```
## S3 method for class 'SaemixData'  
subset(x, subset, ...)
```

Arguments

x	saemixData object
subset	logical expression indicating elements or rows to keep: missing values are taken as false
...	additional parameters (ignored)

Value

an object of class "[SaemixData](#)"

Examples

```
# TODO
```

summary-methods	<i>Methods for Function summary</i>
-----------------	-------------------------------------

Description

Methods for function summary
summary method for class SaemixData

Usage

```
## S4 method for signature 'SaemixData'
summary(object, print = TRUE, ...)

## S4 method for signature 'SaemixModel'
summary(object, print = TRUE, ...)

## S4 method for signature 'SaemixObject'
summary(object, print = TRUE, ...)
```

Arguments

object	an object of class SaemixData
print	a boolean controlling whether to print the output or return it silently
...	additional arguments (ignored)

Value

a list with a number of elements extracted from the dataset

N number of subjects

nobs the total number of observations

nind.obs a vector giving the number of observations for each subject

id subject ID; **x**: predictors; **y**: response, and, if present in the data, **covariates**: the covariates (as many lines as observations) and **ind.covariates**: the individual covariates (one

Methods

list("signature(x = \"ANY\")") default summary function ?
list("signature(x = \"SaemixData\")") summary of the data
list("signature(x = \"SaemixModel\")") summary of the model
list("signature(x = \"SaemixObject\")") summary of an SaemixObject

testnpde

*Tests for normalised prediction distribution errors***Description**

Performs tests for the normalised prediction distribution errors returned by npde

Usage

```
testnpde(npde)
```

Arguments

npde the vector of prediction distribution errors

Details

Given a vector of normalised prediction distribution errors (npde), this function compares the npde to the standardised normal distribution $N(0,1)$ using a Wilcoxon test of the mean, a Fisher test of the variance, and a Shapiro-Wilks test for normality. A global test is also reported.

The helper functions `kurtosis` and `skewness` are called to compute the kurtosis and skewness of the distribution of the npde.

Value

a list containing 4 components:

`Wilcoxon test of mean=0` compares the mean of the npde to 0 using a Wilcoxon test
`variance test` compares the variance of the npde to 1 using a Fisher test
`SW test of normality` compares the npde to the normal distribution using a Shapiro-Wilks test
`global test` an adjusted p-value corresponding to the minimum of the 3 previous p-values multiplied by the number of tests (3), or 1 if this p-value is larger than 1.

Author(s)

Emmanuelle Comets <emmanuelle.comets@inserm.fr>

References

K. Brendel, E. Comets, C. Laffont, C. Laveille, and F. Mentré. Metrics for external model evaluation with an application to the population pharmacokinetics of gliclazide. *Pharmaceutical Research*, 23:2036–49, 2006.

See Also

[saemix](#), [saemix.plot.npde](#)

theo.saemix

Pharmacokinetics of theophylline, in SAEM format

Description

The theo.saemix data frame has 132 rows and 6 columns of data from an experiment on the pharmacokinetics of theophylline. A column with gender was added to the original data for demo purposes, and contains simulated data.

Usage

```
theo.saemix
```

Format

This data frame contains the following columns:

Id: an ordered factor with levels 1, ..., 12 identifying the subject on whom the observation was made. The ordering is by Time at which the observation was made.

Dose: dose of theophylline administered orally to the subject (mg/kg).

Time: time since drug administration when the sample was drawn (hr).

Concentration: theophylline concentration in the sample (mg/L).

Weight: weight of the subject (kg).

Sex: gender of the subject (0=men, 1=women).

Details

Boeckmann, Sheiner and Beal (1994) report data from a study by Dr. Robert Upton of the kinetics of the anti-asthmatic drug theophylline. Twelve subjects were given oral doses of theophylline then serum concentrations were measured at 11 time points over the next 25 hours. In the present package *npde*, we removed the data at time 0.

These data are analyzed in Davidian and Giltinan (1995) and Pinheiro and Bates (2000) using a two-compartment open pharmacokinetic model.

These data are also available in the library datasets under the name Theoph in a slightly modified format and including the data at time 0.

Source

Boeckmann, A. J., Sheiner, L. B. and Beal, S. L. (1994), *NONMEM Users Guide: Part V*, NONMEM Project Group, University of California, San Francisco.

Davidian, M. and Giltinan, D. M. (1995) *Nonlinear Models for Repeated Measurement Data*, Chapman & Hall (section 5.5, p. 145 and section 6.6, p. 176)

Pinheiro, J. C. and Bates, D. M. (2000) *Mixed-effects Models in S and S-PLUS*, Springer (Appendix A.29)

Examples

```
data(theo.saemix)
saemix.data<-saemixData(name.data=theo.saemix,header=TRUE,sep=" ",na=NA,
  name.group=c("Id"),name.predictors=c("Dose","Time"),
  name.response=c("Concentration"),name.covariates=c("Weight","Sex"),
  units=list(x="hr",y="mg/L",covariates=c("kg","-")), name.X="Time")

model1cpt<-function(psi,id,xidep) {
  dose<-xidep[,1]
  tim<-xidep[,2]
  ka<-psi[id,1]
  V<-psi[id,2]
  CL<-psi[id,3]
  k<-CL/V
  ypred<-dose*ka/(V*(ka-k))*(exp(-k*tim)-exp(-ka*tim))
  return(ypred)
}
# Default model, no covariate
saemix.model<-saemixModel(model=model1cpt,
  description="One-compartment model with first-order absorption",
  psi0=matrix(c(1.,20,0.5,0.1,0,-0.01),ncol=3,byrow=TRUE,
  dimnames=list(NULL, c("ka","V","CL"))),transform.par=c(1,1,1))

# Note: remove the options save=FALSE and save.graphs=FALSE
# to save the results and graphs
saemix.options<-list(seed=632545,save=FALSE,save.graphs=FALSE)

# Not run (strict time constraints for CRAN)
# saemix.fit<-saemix(saemix.model,saemix.data,saemix.options)

# Model with covariates
saemix.model<-saemixModel(model=model1cpt,
  description="One-compartment model with first-order absorption",
  psi0=matrix(c(1.,20,0.5,0.1,0,-0.01),ncol=3,byrow=TRUE,
  dimnames=list(NULL, c("ka","V","CL"))),transform.par=c(1,1,1),
  covariate.model=matrix(c(0,0,1,0,0,0),ncol=3,byrow=TRUE),fixed.estim=c(1,1,1),
  covariance.model=matrix(c(1,0,0,0,1,1,0,1,1),ncol=3,byrow=TRUE),
  omega.init=matrix(c(1,0,0,0,1,0,0,0,1),ncol=3,byrow=TRUE),error.model="combined")

# saemix.options<-list(seed=39546,save=FALSE,save.graphs=FALSE)
```

```
# Not run (strict time constraints for CRAN)
# saemix.fit<-saemix(saemix.model,saemix.data,saemix.options)
```

transformCatCov	<i>Transform covariates</i>
-----------------	-----------------------------

Description

Regroup categorical covariates

Usage

```
transformCatCov(object, covariate, group, reference, verbose = FALSE)
```

Arguments

object	saemixData object
covariate	name of the covariate
group	a vector giving the categories to which the initial values of the covariates should be mapped. If the resulting covariate is binary, it will be stored as 0/1. If it has more than 2 categories, dummy covariates will be created for the analysis.
reference	the reference group
verbose	a boolean, prints messages during the execution of the function if TRUE. Defaults to FALSE.

Value

an object of class "[SaemixData](#)"

Examples

```
# TODO
```

transformContCov	<i>Transform covariates</i>
------------------	-----------------------------

Description

Transform and/or center continuous covariates

Usage

```
transformContCov(object, covariate, transformation = function(x) x,
  centering = "median", verbose = FALSE)
```


Arguments

object	saemixData object
covariate	name of the covariate
transformation	transformation function. Defaults to no transformation
centering	string, giving the value used to center the covariate; can be "mean" or "median", in which case this value will be computed from the data, 'none' or 0 for no centering, or a value given by the user. Defaults to the median value over the dataset.
verbose	a boolean, prints messages during the execution of the function if TRUE. Defaults to FALSE.

Value

an object of class "[SaemixData](#)"

Examples

```
# TODO
```

validate.names	<i>Name validation (##)Helper function not intended to be called by the user)</i>
----------------	--

Description

Helper function, checks if the names given by the user match to the names in the dataset. If not, automatic recognition is attempted.

Arguments

usernames	vector of strings
datanames	vector of strings
recognisednames	vector of strings, values for automatic recognition
verbose	logical, whether to print warning messages

Value

a vector with valid names

Examples

```
# TODO
```

vcov	<i>Extracts the Variance-Covariance Matrix for a Fitted Model Object</i>
------	--

Description

Returns the variance-covariance matrix of the main parameters of a fitted model object

Usage

```
## S3 method for class 'SaemixRes'
vcov(object, ...)

## S3 method for class 'SaemixObject'
vcov(object, ...)
```

Arguments

object	a fitted object from a call to saemix
...	further arguments to be passed to or from other methods

Value

A matrix of the estimated covariances between the parameter estimates in model. In saemix, this matrix is obtained as the inverse of the Fisher Information Matrix computed by linearisation

yield.saemix	<i>Wheat yield in crops treated with fertiliser, in SAEM format</i>
--------------	---

Description

yield.saemix contains data from winter wheat experiments.

Usage

```
yield.saemix
```

Format

This data frame contains the following columns:

site: the site number

dose: dose of nitrogen fertiliser (kg/ha).

yield: grain yield (kg/ha).

soil.nitrogen: end-of-winter mineral soil nitrogen (NO₃⁻ plus NH₄⁺) in the 0 to 90 cm layer was measured on each site/year (kg/ha).

Details

The data in the `yield.saemix` comes from 37 winter wheat experiments carried out between 1990 and 1996 on commercial farms near Paris, France. Each experiment was from a different site. Two soil types were represented, a loam soil and a chalky soil. Common winter wheat varieties were used. Each experiment consisted of five to eight different nitrogen fertiliser rates, for a total of 224 nitrogen treatments. Nitrogen fertilizer was applied in two applications during the growing season. For each nitrogen treatment, grain yield (adjusted to 150 g.kg⁻¹ grain moisture content) was measured. In addition, end-of-winter mineral soil nitrogen (NO₃⁻ plus NH₄⁺) in the 0 to 90 cm layer was measured on each site-year during February when the crops were tillering. Yield and end-of-winter mineral soil nitrogen measurements were in the ranges 3.44-11.54 t.ha⁻¹, and 40-180 kg.ha⁻¹ respectively.

Source

Makowski, D., Wallach, D., and Meynard, J.-M (1999). Models of yield, grain protein, and residual mineral nitrogen responses to applied nitrogen for winter wheat. *Agronomy Journal* 91: 377-385.

Examples

```
data(yield.saemix)
saemix.data<-saemixData(name.data=yield.saemix,header=TRUE,name.group=c("site"),
  name.predictors=c("dose"),name.response=c("yield"),
  name.covariates=c("soil.nitrogen"),units=list(x="kg/ha",y="t/ha",
  covariates=c("kg/ha")))

# Model: linear + plateau
yield.LP<-function(psi,id,xidep) {
# input:
# psi : matrix of parameters (3 columns, ymax, xmax, slope)
# id : vector of indices
# xidep : dependent variables (same nb of rows as length of id)
# returns:
# a vector of predictions of length equal to length of id
  x<-xidep[,1]
  ymax<-psi[id,1]
  xmax<-psi[id,2]
  slope<-psi[id,3]
  f<-ymax+slope*(x-xmax)
# cat(length(f)," ",length(ymax),"\n")
  f[x>xmax]<-ymax[x>xmax]
  return(f)
}
saemix.model<-saemixModel(model=yield.LP,description="Linear plus plateau model",
  psi0=matrix(c(8,100,0.2,0,0,0),ncol=3,byrow=TRUE,dimnames=list(NULL,
  c("Ymax","Xmax","slope"))),covariate.model=matrix(c(0,0,0),ncol=3,byrow=TRUE),
  transform.par=c(0,0,0),covariance.model=matrix(c(1,0,0,0,1,0,0,0,1),ncol=3,
  byrow=TRUE),error.model="constant")

saemix.options<-list(algorithms=c(1,1,1),nb.chains=1,seed=666,
  save=FALSE,save.graphs=FALSE)
```

```

# Plotting the data
plot(saemix.data,xlab="Fertiliser dose (kg/ha)", ylab="Wheat yield (t/ha)")

# Not run (strict time constraints for CRAN)
# saemix.fit<-saemix(saemix.model,saemix.data,saemix.options)

# Comparing the likelihoods obtained by linearisation and importance sampling
# to the likelihood obtained by Gaussian Quadrature
# Not run
# saemix.fit<-llgq.saemix(saemix.fit)
{
# cat("LL by Importance sampling, LL_IS=",saemix.fit["results"]["ll.is"],"\n")
# cat("LL by linearisation, LL_lin=",saemix.fit["results"]["ll.lin"],"\n")
# cat("LL by Gaussian Quadrature, LL_GQ=",saemix.fit["results"]["ll.gq"],"\n")
}

# Testing for an effect of covariate soil.nitrogen on Xmax
saemix.model2<-saemixModel(model=yield.LP,description="Linear plus plateau model",
  psi0=matrix(c(8,100,0.2,0,0,0),ncol=3,byrow=TRUE,dimnames=list(NULL,
  c("Ymax","Xmax","slope"))),covariate.model=matrix(c(0,1,0),ncol=3,byrow=TRUE),
  transform.par=c(0,0,0),covariance.model=matrix(c(1,0,0,0,1,0,0,0,1),ncol=3,
  byrow=TRUE),error.model="constant")

# saemix.fit2<-saemix(saemix.model2,saemix.data,saemix.options)
# BIC for the two models
{
# cat("Model without covariate, BIC=",saemix.fit["results"]["bic.is"],"\n")
# cat("Model with covariate, BIC=",saemix.fit2["results"]["bic.is"],"\n")
# pval<-1-pchisq(-2*saemix.fit["results"]["ll.is"]+2*saemix.fit2["results"]["ll.is"],1)
# cat("      LRT: p=",pval,"\n")
}

```

[*Get/set methods for SaemixData object*]

Description

Access slots of a SaemixData object using the object["slot"] format

Usage

```

## S4 method for signature 'SaemixData'
x[i, j, drop]

## S4 method for signature 'SaemixRepData'
x[i, j, drop]

## S4 replacement method for signature 'SaemixRepData'
x[i, j] <- value

```

```
## S4 method for signature 'SaemixSimData'
x[i, j, drop]

## S4 replacement method for signature 'SaemixSimData'
x[i, j] <- value

## S4 replacement method for signature 'SaemixRes'
x[i, j] <- value
```

Arguments

x	object
i	element to be replaced
j	element to replace with
drop	whether to drop unused dimensions
value	value to replace with

[,SaemixModel-method *Get/set methods for SaemixModel object*

Description

Access slots of a SaemixModel object using the object["slot"] format

Usage

```
## S4 method for signature 'SaemixModel'
x[i, j, drop]
```

Arguments

x	object
i	element to be replaced
j	element to replace with
drop	whether to drop unused dimensions

[,SaemixObject-method *Get/set methods for SaemixObject object*

Description

Access slots of a SaemixObject object using the object["slot"] format

Usage

```
## S4 method for signature 'SaemixObject'
x[i, j, drop]
```

Arguments

x	object
i	element to be replaced
j	element to replace with
drop	whether to drop unused dimensions

[,SaemixRes-method *Get/set methods for SaemixRes object*

Description

Access slots of a SaemixRes object using the object["slot"] format

Usage

```
## S4 method for signature 'SaemixRes'
x[i, j, drop]
```

Arguments

x	object
i	element to be replaced
j	element to replace with
drop	whether to drop unused dimensions

[-methods

*Methods for "get" Function [***Description**

Methods for function [, to allow access to the value of an element within an S4 object

Methods

signature(x = "SaemixData") access elements of an object SaemixData
signature(x = "SaemixModel") access elements of an object SaemixModel
signature(x = "SaemixObject") access elements of an object SaemixObject
signature(x = "SaemixRepData") access elements of an object SaemixRepData
signature(x = "SaemixRes") access elements of an object SaemixRes
signature(x = "SaemixSimData") access elements of an object SaemixSimData

[<-methods

*Methods for "set" Function [<-***Description**

Methods for function [<-, to allow replacements of the value of an element within an S4 object

Methods

signature(x = "SaemixData") replace elements of an object SaemixData
signature(x = "SaemixModel") replace elements of an object SaemixModel
signature(x = "SaemixObject") replace elements of an object SaemixObject
signature(x = "SaemixRepData") replace elements of an object SaemixRepData
signature(x = "SaemixRes") replace elements of an object SaemixRes
signature(x = "SaemixSimData") replace elements of an object SaemixSimData

Index

- *Topic **classes**
 - SaemixData-class, 53
 - SaemixModel-class, 58
 - SaemixObject-class, 60
 - SaemixRes-class, 61
- *Topic **datasets**
 - cow.saemix, 8
 - oxboys.saemix, 23
 - PD1.saemix, 25
 - theo.saemix, 70
 - yield.saemix, 74
- *Topic **data**
 - transformCatCov, 72
 - transformContCov, 72
- *Topic **methods**
 - [, 76
 - [,SaemixModel-method, 77
 - [,SaemixObject-method, 78
 - [,SaemixRes-method, 78
 - [-methods, 79
 - [<--methods, 79
 - fitted.saemix, 13
 - initialize-methods, 14
 - logLik, 20
 - plot-methods, 30
 - plot-SaemixModel, 31
 - predict-methods, 32
 - print-methods, 32
 - psi-methods, 33
 - resid.saemix, 36
 - saemix.predict, 48
 - show-methods, 64
 - showall-methods, 65
 - subset.SaemixData, 67
 - summary-methods, 68
 - validate.names, 73
- *Topic **models**
 - fim.saemix, 11
 - llgq.saemix, 17
 - llis.saemix, 19
 - map.saemix, 22
 - saemix, 36
 - saemixControl, 49
 - saemixModel, 56
 - testnpde, 69
- *Topic **model**
 - conddist.saemix, 5
 - saemix-package, 3
 - simul.saemix, 66
- *Topic **plots**
 - default.saemix.plots, 9
- *Topic **plot**
 - plot,SaemixObject-method, 27
 - plot-SaemixData, 31
 - saemix.plot.data, 38
 - saemix.plot.select, 42
 - saemix.plot.setoptions, 45
- *Topic **saemix**
 - saemix-package, 3
 - [, 76
 - [,SaemixData-method ([), 76
 - [,SaemixModel-method, 77
 - [,SaemixObject-method, 78
 - [,SaemixRepData-method ([), 76
 - [,SaemixRes-method, 78
 - [,SaemixSimData-method ([), 76
 - [-methods, 79
 - [<--methods, 79
 - [<- , SaemixData-method ([), 76
 - [<- , SaemixModel-method (SaemixModel-class), 58
 - [<- , SaemixObject-method (SaemixObject-class), 60
 - [<- , SaemixRepData-method ([), 76
 - [<- , SaemixRes-method ([), 76
 - [<- , SaemixSimData-method ([), 76
 - ##vcov,SaemixRes (vcov), 74
 - advanced.gof (default.saemix.plots), 9

- AIC, 22
- AIC.SaemixObject (logLik), 20
- basic.gof (default.saemix.plots), 9
- BIC, 22
- BIC.SaemixObject (logLik), 20
- coef (coef.saemix), 5
- coef.saemix, 5
- compute.eta.map (saemix.plot.data), 38
- compute.sres (saemix.plot.data), 38
- compute.Uy (saemix-package), 3
- condist.saemix, 5
- conditional.distribution
 - (saemix-package), 3
- covariate.fits (default.saemix.plots), 9
- cow.saemix, 8
- cutoff (saemix-package), 3
- default.saemix.plots, 9, 44
- derivphi (saemix-package), 3
- dtransphi (saemix-package), 3
- error (saemix-package), 3
- estep (saemix), 36
- eta (psi-methods), 33
- eta, SaemixObject-method (psi-methods), 33
- eta-methods (psi-methods), 33
- fim.saemix, 11
- fitted (fitted.saemix), 13
- fitted.saemix, 13
- gammarnd.mlx (saemix-package), 3
- ggq.mlx (llgq.saemix), 17
- ggq.mlx (saemix-package), 3
- individual.fits (default.saemix.plots), 9
- initialiseMainAlgo (saemix), 36
- initialize, SaemixData-method
 - (initialize-methods), 14
- initialize, SaemixModel-method
 - (initialize-methods), 14
- initialize, SaemixObject-method
 - (initialize-methods), 14
- initialize, SaemixRepData-method
 - (initialize-methods), 14
- initialize, SaemixRes-method
 - (initialize-methods), 14
- initialize, SaemixSimData-method
 - (initialize-methods), 14
- initialize-methods, 14
- kurtosis (testnpde), 69
- llgq.saemix, 17, 20
- llis.saemix, 18, 19
- llqg.saemix (llgq.saemix), 17
- logLik, 20
- map.saemix, 22
- mstep (saemix), 36
- mydiag (saemix-package), 3
- normcdf (saemix-package), 3
- norminv (saemix-package), 3
- oxboys.saemix, 23
- PD1.saemix, 25
- PD2.saemix (PD1.saemix), 25
- phi (psi-methods), 33
- phi, SaemixObject-method (psi-methods), 33
- phi-methods (psi-methods), 33
- plot (plot, SaemixObject-method), 27
- plot, ANY-method (plot-methods), 30
- plot, SaemixData-method (plot-methods), 30
- plot, SaemixData-methods
 - (plot-SaemixData), 31
- plot, SaemixModel-method (plot-methods), 30
- plot, SaemixModel-methods
 - (plot-SaemixModel), 31
- plot, SaemixObject
 - (plot, SaemixObject-method), 27
- plot, SaemixObject-method, 27
- plot, SaemixSimData (plot-SaemixData), 31
- plot, SaemixSimData-method
 - (plot-SaemixData), 31
- plot-methods, 30
- plot-SaemixData, 31
- plot-SaemixModel, 31
- plot.saemix, 10, 35, 37, 40, 59, 61
- plot.saemix (plot, SaemixObject-method), 27

- predict, ANY-method (predict-methods), 32
- predict, SaemixObject
 - (SaemixObject-class), 60
- predict, SaemixObject-method
 - (predict-methods), 32
- predict-methods, 32
- print, ANY-method (print-methods), 32
- print, SaemixData-method
 - (print-methods), 32
- print, SaemixModel-method
 - (print-methods), 32
- print, SaemixObject
 - (SaemixObject-class), 60
- print, SaemixObject-method
 - (print-methods), 32
- print, SaemixRes-method (print-methods), 32
- print-methods, 32
- print.saemix (print-methods), 32
- psi (psi-methods), 33
- psi, SaemixObject-method (psi-methods), 33
- psi-methods, 33
- replace.data.options
 - (saemix.plot.setoptions), 45
- replace.plot.options
 - (saemix.plot.setoptions), 45
- resid.saemix, 36
- resid.SaemixObject (resid.saemix), 36
- resid.SaemixRes (resid.saemix), 36
- residuals.SaemixRes (resid.saemix), 36
- saemix, 4, 6, 7, 9–12, 17–20, 22, 23, 27, 29, 34, 36, 38, 40, 42, 44, 47, 48, 50, 51, 53, 55, 57, 59–61, 64, 67, 70
- saemix-package, 3
- saemix.data.setoptions
 - (saemix.plot.setoptions), 45
- saemix.plot.convergence, 44, 48, 67
- saemix.plot.convergence
 - (saemix.plot.data), 38
- saemix.plot.correlations
 - (saemix.plot.data), 38
- saemix.plot.data, 10, 29, 38, 44, 48, 67
- saemix.plot.distpsi, 44, 48, 67
- saemix.plot.distpsi (saemix.plot.data), 38
- saemix.plot.distribresiduals, 44
- saemix.plot.distribresiduals
 - (saemix.plot.data), 38
- saemix.plot.fits, 44, 48, 67
- saemix.plot.fits (saemix.plot.data), 38
- saemix.plot.llis, 44, 48, 67
- saemix.plot.llis (saemix.plot.data), 38
- saemix.plot.npde, 70
- saemix.plot.npde (saemix.plot.data), 38
- saemix.plot.obsvspred, 44, 48, 67
- saemix.plot.obsvspred
 - (saemix.plot.data), 38
- saemix.plot.parcov, 44, 48, 67
- saemix.plot.parcov (saemix.plot.data), 38
- saemix.plot.randeff, 44, 48, 67
- saemix.plot.randeff (saemix.plot.data), 38
- saemix.plot.randeffcov, 44
- saemix.plot.randeffcov
 - (saemix.plot.data), 38
- saemix.plot.scatterresiduals, 44, 48, 67
- saemix.plot.scatterresiduals
 - (saemix.plot.data), 38
- saemix.plot.select, 29, 40, 41
- saemix.plot.setoptions, 10, 28, 29, 39, 40, 44, 45
- saemix.plot.vpc, 44, 48, 67
- saemix.plot.vpc (saemix.plot.data), 38
- saemix.predict, 48
- saemixControl, 7, 22, 35, 37, 49, 53, 55, 57, 59, 61, 64
- SaemixData, 4, 7, 35, 37, 51, 53, 57, 59, 61, 66, 68, 72, 73
- SaemixData (SaemixData-class), 53
- saemixData, 17, 37, 51, 52, 54, 55, 63, 64
- SaemixData-class, 53
- SaemixModel, 4, 7, 35, 37, 51, 53, 55, 57, 61, 64, 66
- SaemixModel (SaemixModel-class), 58
- saemixModel, 17, 37, 56, 57, 58
- SaemixModel-class, 58
- SaemixObject, 4, 7, 12, 18, 20, 23, 29, 35, 37, 40, 44, 48, 51, 59, 66, 67
- SaemixObject (SaemixObject-class), 60
- SaemixObject-class, 60
- SaemixRepData-class (SaemixData-class), 53
- SaemixRes (SaemixRes-class), 61

- SaemixRes-class, [61](#)
- SaemixSimData-class (SaemixData-class), [53](#)
- show, SaemixData-method (show-methods), [64](#)
- show, SaemixModel-method (show-methods), [64](#)
- show, SaemixObject (SaemixObject-class), [60](#)
- show, SaemixObject-method (show-methods), [64](#)
- show, SaemixRepData-method (show-methods), [64](#)
- show, SaemixRes-method (show-methods), [64](#)
- show, SaemixSimData-method (show-methods), [64](#)
- show-methods, [64](#)
- showall (showall-methods), [65](#)
- showall, SaemixData-method (showall-methods), [65](#)
- showall, SaemixModel-method (showall-methods), [65](#)
- showall, SaemixObject (SaemixObject-class), [60](#)
- showall, SaemixObject-method (showall-methods), [65](#)
- showall, SaemixRes-method (showall-methods), [65](#)
- showall-methods, [65](#)
- simul.saemix, [66](#)
- skewness (testnpde), [69](#)
- subset (subset.SaemixData), [67](#)
- subset-methods (subset.SaemixData), [67](#)
- subset.SaemixData, [67](#)
- summary (summary-methods), [68](#)
- summary, ANY-method (summary-methods), [68](#)
- summary, SaemixData (summary-methods), [68](#)
- summary, SaemixData-method (summary-methods), [68](#)
- summary, SaemixModel-method (summary-methods), [68](#)
- summary, SaemixObject (SaemixObject-class), [60](#)
- summary, SaemixObject-method (summary-methods), [68](#)
- summary-methods, [68](#)

- testnpde, [69](#)
- theo.saemix, [70](#)

- tpdf.mlx (saemix-package), [3](#)
- transform.SaemixData (transformContCov), [72](#)
- transformCatCov, [72](#)
- transformContCov, [72](#)
- transphi (saemix-package), [3](#)
- transpsi (saemix-package), [3](#)
- trnd.mlx (saemix-package), [3](#)

- validate.names, [73](#)
- vcov, [74](#)
- vcov, SaemixObject (vcov), [74](#)
- vcov.SaemixObject (vcov), [74](#)
- vcov.SaemixRes (vcov), [74](#)

- yield.saemix, [74](#)