

Package ‘shinyWidgets’

March 15, 2021

Title Custom Inputs Widgets for Shiny

Version 0.6.0

Description

Collection of custom input controls and user interface components for 'Shiny' applications.
Give your applications a unique and colorful style !

URL <https://github.com/dreamRs/shinyWidgets>

BugReports <https://github.com/dreamRs/shinyWidgets/issues>

License GPL-3

Encoding UTF-8

LazyData true

RoxygenNote 7.1.1

Depends R (>= 3.1.0)

Imports bslib, sass, shiny (>= 0.14), htmltools, jsonlite, grDevices

Suggests shinydashboard, testthat, covr, shinydashboardPlus (>= 2.0.0), bs4Dash, argonR, argonDash, tablerDash, ggplot2, DT, scales

NeedsCompilation no

Author Victor Perrier [aut, cre, cph],
Fanny Meyer [aut],
David Granjon [aut],
Ian Fellows [ctb] (Methods for mutating vertical tabs &
updateMultiInput),
Wil Davis [ctb] (numericRangeInput function),
Spencer Matthews [ctb] (autoNumeric methods),
JavaScript and CSS libraries authors [ctb, cph] (All authors are listed
in LICENSE.md)

Maintainer Victor Perrier <victor.perrier@dreamrs.fr>

Repository CRAN

Date/Publication 2021-03-15 20:50:02 UTC

R topics documented:

actionBtn	4
actionGroupButtons	5
addSpinner	7
airDatepicker	8
animateOptions	12
animations	13
appendVerticalTab	13
autonumericInput	14
awesomeCheckbox	20
awesomeCheckboxGroup	21
awesomeRadio	22
bootstrap-utils	24
checkboxGroupButtons	27
chooseSliderSkin	29
circleButton	31
closeSweetAlert	32
colorPickr	33
colorSelectorInput	37
currencyInput	39
demoAirDatepicker	41
demoNoUiSlider	42
demoNumericRange	43
downloadBtn	43
drop-menu-interaction	44
dropdown	46
dropdownButton	48
dropMenu	51
dropMenuOptions	53
execute_safely	54
html-dependencies	55
inputSweetAlert	56
knobInput	58
materialSwitch	61
multiInput	62
noUiSliderInput	64
numericInputIcon	67
numericRangeInput	69
pickerGroup-module	70
pickerInput	73
pickerOptions	78
prettyCheckbox	82
prettyCheckboxGroup	86
prettyRadioButtons	89
prettySwitch	92
prettyToggle	94
progress-bar	97

progressSweetAlert	100
radioGroupButtons	102
searchInput	104
selectizeGroup-module	105
setBackground-color	109
setBackgroundImage	112
setShadow	112
setSliderColor	114
shinyWidgets	115
shinyWidgetsGallery	116
show_toast	116
sliderTextInput	119
spectrumInput	121
stati-card	122
sweetalert	125
sweetalert-confirmation	129
switchInput	132
textInputAddon	134
textInputIcon	135
toggleDropdownButton	137
tooltipOptions	138
updateAirDateInput	139
updateAutonumericInput	140
updateAwesomeCheckbox	142
updateAwesomeCheckboxGroup	143
updateAwesomeRadio	145
updateCheckboxGroupButtons	146
updateCurrencyInput	149
updateKnobInput	151
updateMaterialSwitch	153
updateMultiInput	153
updateNoUiSliderInput	155
updateNumericInputIcon	156
updateNumericRangeInput	157
updatePickerInput	158
updatePrettyCheckbox	160
updatePrettyCheckboxGroup	161
updatePrettyRadioButtons	164
updatePrettySwitch	166
updatePrettyToggle	167
updateRadioGroupButtons	168
updateSearchInput	170
updateSliderTextInput	172
updateSpectrumInput	173
updateSwitchInput	175
updateTextInputIcon	179
updateVerticalTabsetPanel	181
useArgonDash	182

useBs4Dash	185
useShinydashboard	188
useShinydashboardPlus	190
useSweetAlert	193
useTablerDash	195
vertical-tab	199
wNumbFormat	200

Index 203

actionBtn	<i>Awesome action button</i>
-----------	------------------------------

Description

Like actionButton but awesome, via <https://bbtn.surge.sh/>

Usage

```
actionBtn(
  inputId,
  label = NULL,
  icon = NULL,
  style = "unite",
  color = "default",
  size = "md",
  block = FALSE,
  no_outline = TRUE
)
```

Arguments

inputId	The input slot that will be used to access the value.
label	The contents of the button, usually a text label.
icon	An optional icon to appear on the button.
style	Style of the button, to choose between simple, bordered, minimal, stretch, jelly, gradient, fill, material-circle, material-flat, pill, float, unite.
color	Color of the button : default, primary, warning, danger, success, royal.
size	Size of the button : xs,sm, md, lg.
block	Logical, full width button.
no_outline	Logical, don't show outline when navigating with keyboard/interact using mouse or touch.

See Also

[downloadBtn](#)

Examples

```
if (interactive()) {  
  
  library(shiny)  
  library(shinyWidgets)  
  
  ui <- fluidPage(  
    tags$h2("Awesome action button"),  
    tags$br(),  
    actionBttn(  
      inputId = "btttn1",  
      label = "Go!",  
      color = "primary",  
      style = "bordered"  
    ),  
    tags$br(),  
    verbatimTextOutput(outputId = "res_btttn1"),  
    tags$br(),  
    actionBttn(  
      inputId = "btttn2",  
      label = "Go!",  
      color = "success",  
      style = "material-flat",  
      icon = icon("sliders"),  
      block = TRUE  
    ),  
    tags$br(),  
    verbatimTextOutput(outputId = "res_btttn2")  
  )  
  
  server <- function(input, output, session) {  
    output$res_btttn1 <- renderPrint(input$btttn1)  
    output$res_btttn2 <- renderPrint(input$btttn2)  
  }  
  
  shinyApp(ui = ui, server = server)  
  
}
```

actionGroupButtons *Actions Buttons Group Inputs*

Description

Create a group of actions buttons.

Usage

```
actionGroupButtons(  
  
```

```

    inputIds,
    labels,
    status = "default",
    size = "normal",
    direction = "horizontal",
    fullwidth = FALSE
  )

```

Arguments

<code>inputIds</code>	The inputs slot that will be used to access the value, one for each button.
<code>labels</code>	Labels for each buttons, must have same length as <code>inputIds</code> .
<code>status</code>	Add a class to the buttons, you can use Bootstrap status like 'info', 'primary', 'danger', 'warning' or 'success'. Or use an arbitrary strings to add a custom class, e.g. : with <code>status = 'myClass'</code> , buttons will have class <code>btn-myClass</code> .
<code>size</code>	Size of the buttons ('xs', 'sm', 'normal', 'lg').
<code>direction</code>	Horizontal or vertical.
<code>fullwidth</code>	If TRUE, fill the width of the parent div.

Value

An actions buttons group control that can be added to a UI definition.

Examples

```

if (interactive()) {
  library("shiny")
  library("shinyWidgets")

  ui <- fluidPage(
    br(),
    actionGroupButtons(
      inputIds = c("btn1", "btn2", "btn3"),
      labels = list("Action 1", "Action 2", tags$span(icon("gear"), "Action 3")),
      status = "primary"
    ),
    verbatimTextOutput(outputId = "res1"),
    verbatimTextOutput(outputId = "res2"),
    verbatimTextOutput(outputId = "res3")
  )

  server <- function(input, output, session) {

    output$res1 <- renderPrint(input$btn1)

    output$res2 <- renderPrint(input$btn2)

    output$res3 <- renderPrint(input$btn3)

  }
}

```

```
  shinyApp(ui = ui, server = server)
}
```

addSpinner*Display a spinner above an output when this one recalculate*

Description

Display a spinner above an output when this one recalculate

Usage

```
addSpinner(output, spin = "double-bounce", color = "#112446")
```

Arguments

output	An output element, typically the result of renderPlot.
spin	Style of the spinner, choice between : circle, bounce, folding-cube, rotating-plane, cube-grid, fading-circle, double-bounce, dots, cube.
color	Color for the spinner.

Value

a list of tags

Note

The spinner don't disappear from the page, it's only masked by the plot, so the plot must have a non-transparent background. For a more robust way to insert loaders, see package "shinycssloaders".

Examples

```
# wrap an output:
addSpinner(shiny::plotOutput("plot"))

# Complete demo:

if (interactive()) {

  library(shiny)
  library(shinyWidgets)

  ui <- fluidPage(
    tags$h2("Exemple spinners"),
    actionButton(inputId = "refresh", label = "Refresh", width = "100%"),
    fluidRow(
      column(
        width = 5, offset = 1,
```

```

    addSpinner(plotOutput("plot1"), spin = "circle", color = "#E41A1C"),
    addSpinner(plotOutput("plot3"), spin = "bounce", color = "#377EB8"),
    addSpinner(plotOutput("plot5"), spin = "folding-cube", color = "#4DAF4A"),
    addSpinner(plotOutput("plot7"), spin = "rotating-plane", color = "#984EA3"),
    addSpinner(plotOutput("plot9"), spin = "cube-grid", color = "#FF7F00")
  ),
  column(
    width = 5,
    addSpinner(plotOutput("plot2"), spin = "fading-circle", color = "#FFFF33"),
    addSpinner(plotOutput("plot4"), spin = "double-bounce", color = "#A65628"),
    addSpinner(plotOutput("plot6"), spin = "dots", color = "#F781BF"),
    addSpinner(plotOutput("plot8"), spin = "cube", color = "#999999")
  )
),
actionButton(inputId = "refresh2", label = "Refresh", width = "100%")
)

server <- function(input, output, session) {

  dat <- reactive({
    input$refresh
    input$refresh2
    Sys.sleep(3)
    Sys.time()
  })

  lapply(
    X = seq_len(9),
    FUN = function(i) {
      output[[paste0("plot", i)]] <- renderPlot({
        dat()
        plot(sin, -pi, i*pi)
      })
    }
  )
}

shinyApp(ui, server)
}

```

Description

An alternative to dateInput to select single, multiple or date range. And two alias to select months or years.

Usage

```
airDatepickerInput(  
  inputId,  
  label = NULL,  
  value = NULL,  
  multiple = FALSE,  
  range = FALSE,  
  timepicker = FALSE,  
  separator = " - ",  
  placeholder = NULL,  
  dateFormat = "yyyy-mm-dd",  
  firstDay = NULL,  
  minDate = NULL,  
  maxDate = NULL,  
  disabledDates = NULL,  
  highlightedDates = NULL,  
  view = c("days", "months", "years"),  
  startView = NULL,  
  minView = c("days", "months", "years"),  
  monthsField = c("monthsShort", "months"),  
  clearButton = FALSE,  
  todayButton = FALSE,  
  autoClose = FALSE,  
  timepickerOpts = timepickerOptions(),  
  position = NULL,  
  update_on = c("change", "close"),  
  addon = c("right", "left", "none"),  
  language = "en",  
  inline = FALSE,  
  onlyTimepicker = FALSE,  
  width = NULL,  
  toggleSelected = TRUE  
)  
  
timepickerOptions(  
  dateTimeSeparator = NULL,  
  timeFormat = NULL,  
  minHours = NULL,  
  maxHours = NULL,  
  minMinutes = NULL,  
  maxMinutes = NULL,  
  hoursStep = NULL,  
  minutesStep = NULL  
)  
  
airMonthpickerInput(inputId, label = NULL, value = NULL, ...)  
  
airYearpickerInput(inputId, label = NULL, value = NULL, ...)
```

Arguments

inputId	The input slot that will be used to access the value.
label	Display label for the control, or NULL for no label.
value	Initial value(s), dates as character string are accepted in yyyy-mm-dd format, or Date/POSIXct object. Can be a single value or several values.
multiple	Select multiple dates. If TRUE, then one can select unlimited dates. If numeric is passed, then amount of selected dates will be limited by it.
range	Select a date range.
timepicker	Add a timepicker below calendar to select time.
separator	Separator between dates when several are selected, default to " -".
placeholder	A character string giving the user a hint as to what can be entered into the control.
dateFormat	Format to use to display date(s), default to "yyyy-mm-dd".
firstDay	Day index from which week will be started. Possible values are from 0 to 6, where 0 - Sunday and 6 - Saturday. By default value is taken from current localization, but if it passed here then it will have higher priority.
minDate	The minimum allowed date. Either a Date object, or a string in yyyy-mm-dd format.
maxDate	The maximum allowed date. Either a Date object, or a string in yyyy-mm-dd format.
disabledDates	A vector of dates to disable, e.g. won't be able to select one of dates passed.
highlightedDates	A vector of dates to highlight.
view	Starting view, one of 'days' (default), 'months' or 'years'.
startView	Date shown in calendar when date picker is opened.
minView	Minimal view, one of 'days' (default), 'months' or 'years'.
monthsField	Names for the months when view is 'months', use 'monthsShort' for abbreviations or 'months' for full names.
clearButton	If TRUE, then button "Clear" will be visible.
todayButton	If TRUE, then button "Today" will be visible to set view to current date, if a Date is used, it will set view to the given date and select it..
autoClose	If TRUE, then after date selection, datepicker will be closed.
timepickerOpts	Options for timepicker, see timepickerOptions .
position	Where calendar should appear, a two word string like 'bottom left' (default), or 'top right', 'left top'.
update_on	When to send selected value to server: on 'change' or when calendar is 'close'd.
addon	Display a calendar icon to 'right' or the 'left' of the widget, or 'none'. This icon act likes an actionButton, you can retrieve value server-side with input\$<inputId>_button.
language	Language to use, can be one of 'cs', 'da', 'de', 'en', 'es', 'fi', 'fr', 'hu', 'it', 'nl', 'pl', 'pt-BR', 'pt', 'ro', 'ru', 'sk', 'zh', 'ja'.

<code>inline</code>	If TRUE, datepicker will always be visible.
<code>onlyTimepicker</code>	Display only the time picker.
<code>width</code>	The width of the input, e.g. '400px', or '100%'.
<code>toggleSelected</code>	When TRUE, in range mode, it's not possible to select the same date as start and end.
<code>dateTimeSeparator</code>	Separator between date and time, default to " ".
<code>timeFormat</code>	Desirable time format. You can use h (hours), hh (hours with leading zero), i (minutes), ii (minutes with leading zero), aa (day period - 'am' or 'pm'), AA (day period capitalized)
<code>minHours</code>	Minimal hours value, must be between 0 and 23. You will not be able to choose value lower than this.
<code>maxHours</code>	Maximum hours value, must be between 0 and 23. You will not be able to choose value higher than this.
<code>minMinutes</code>	Minimal minutes value, must be between 0 and 59. You will not be able to choose value lower than this.
<code>maxMinutes</code>	Maximum minutes value, must be between 0 and 59. You will not be able to choose value higher than this.
<code>hoursStep</code>	Hours step in slider.
<code>minutesStep</code>	Minutes step in slider.
<code>...</code>	Arguments passed to <code>airDatepickerInput</code> .

Value

a Date object or a POSIXct in UTC timezone.

Note

Since shinyWidgets 0.5.2 there's no more conflicts with `dateInput`.

See Also

See [updateAirDateInput](#) for updating slider value server-side. And [demoAirDatepicker](#) for examples.

Examples

```
if (interactive()) {

# examples of different options to select dates:
demoAirDatepicker("datepicker")

# select month(s)
demoAirDatepicker("months")

# select year(s)
demoAirDatepicker("years")
```

```
# select date and time
demoAirDatepicker("timepicker")

# You can select multiple dates :
library(shiny)
library(shinyWidgets)

ui <- fluidPage(
  airDatepickerInput(
    inputId = "multiple",
    label = "Select multiple dates:",
    placeholder = "You can pick 5 dates",
    multiple = 5, clearButton = TRUE
  ),
  verbatimTextOutput("res")
)

server <- function(input, output, session) {
  output$res <- renderPrint(input$multiple)
}

shinyApp(ui, server)

}
```

animateOptions

Animate options

Description

Animate options

Usage

```
animateOptions(enter = "fadeInDown", exit = "fadeOutUp", duration = 1)
```

Arguments

enter	Animation name on appearance
exit	Animation name on disappearance
duration	Duration of the animation

Value

a list

See Also

[animations](#)

Examples

```
## Only run examples in interactive R sessions
if (interactive()) {

  dropdown(
    "Your contents goes here ! You can pass several elements",
    circle = TRUE, status = "danger", icon = icon("gear"), width = "300px",
    animate = animateOptions(enter = "fadeInDown", exit = "fadeOutUp", duration = 3)
  )

}
```

animations	<i>Animation names</i>
------------	------------------------

Description

List of all animations by categories

Usage

```
animations
```

Format

A list of lists

Source

<https://github.com/animate-css/animate.css>

appendVerticalTab	<i>Mutate Vertical Tabset Panel</i>
-------------------	-------------------------------------

Description

Mutate Vertical Tabset Panel

Usage

```
appendVerticalTab(inputId, tab, session = shiny::getDefaultReactiveDomain())

removeVerticalTab(inputId, index, session = shiny::getDefaultReactiveDomain())

reorderVerticalTabs(
  inputId,
  newOrder,
  session = shiny::getDefaultReactiveDomain()
)
```

Arguments

inputId	The id of the verticalTabsetPanel object.
tab	The verticalTab to append.
session	The session object passed to function given to shinyServer .
index	The index of the the tab to remove.
newOrder	The new index order.

Examples

```
if (interactive()) {  
  
  library(shiny)  
  library(shinyWidgets)  
  
  ui <- fluidPage(  
  
    verticalTabsetPanel(  
      verticalTabPanel("blaa","foo"),  
      verticalTabPanel("yarp","bar"),  
      id="hippi"  
    )  
  )  
  
  server <- function(input, output, session) {  
    appendVerticalTab("hippi", verticalTabPanel("bipi","long"))  
    removeVerticalTab("hippi", 1)  
    appendVerticalTab("hippi", verticalTabPanel("howdy","fair"))  
    reorderVerticalTabs("hippi", c(3,2,1))  
  }  
  
  # Run the application  
  shinyApp(ui = ui, server = server)  
  
}
```

autonumericInput

Autonumeric Input Widget

Description

An R wrapper over the javascript AutoNumeric library, for formatting numeric inputs in shiny applications.

Usage

```

autonumericInput(
  inputId,
  label,
  value,
  width = NULL,
  align = "center",
  currencySymbol = NULL,
  currencySymbolPlacement = NULL,
  decimalCharacter = NULL,
  digitGroupSeparator = NULL,
  allowDecimalPadding = NULL,
  decimalPlaces = NULL,
  divisorWhenUnfocused = NULL,
  rawValueDivisor = NULL,
  formatOnPageLoad = NULL,
  maximumValue = NULL,
  minimumValue = NULL,
  modifyValueOnWheel = NULL,
  ...
)

```

Arguments

<code>inputId</code>	The input slot that will be used to access the value.
<code>label</code>	Display label for the control, or <code>NULL</code> for no label.
<code>value</code>	Initial value (unformatted).
<code>width</code>	The width of the input box, eg. <code>"200px"</code> or <code>"100%"</code> .
<code>align</code>	The alignment of the text inside the input box, one of <code>"center"</code> (default), <code>"left"</code> , <code>"right"</code> .
<code>currencySymbol</code>	Defines the currency symbol string. It can be a string of more than one character (allowing for instance to use a space on either side of it, example: <code>'\$ '</code> or <code>' \$'</code>). Defaults to <code>""</code> .
<code>currencySymbolPlacement</code>	Defines where the currency symbol should be placed, <code>"p"</code> for prefix or <code>"s"</code> for suffix (default).
<code>decimalCharacter</code>	Defines what decimal separator character is used. Defaults to <code>","</code> .
<code>digitGroupSeparator</code>	Defines what decimal separator character is used. Defaults to <code>","</code> .
<code>allowDecimalPadding</code>	Defines if decimal places should be padded with zeros. Defaults to <code>TRUE</code> .
<code>decimalPlaces</code>	Defines the default number of decimal places to show on the formatted value, and keep for the precision. Must be 0 or a positive integer. Defaults to 2.

<code>divisorWhenUnfocused</code>	The number that divides the element value on blur. On focus, the number is multiplied back in. Defaults to NULL.
<code>rawValueDivisor</code>	Divides the formatted value shown in the AutoNumeric element and store the divided result in <code>rawValue</code> . Defaults to 1.
<code>formatOnPageLoad</code>	Determine if the default value will be formatted on initialization. Defaults to TRUE.
<code>maximumValue</code>	Defines the maximum possible value a user can enter.
<code>minimumValue</code>	Defines the minimum possible value a user can enter.
<code>modifyValueOnWheel</code>	Allows the user to increment or decrement the element value with the mouse wheel. The wheel behavior can be modified by the <code>wheelStep</code> option. Defaults to TRUE.
<code>...</code>	Additional parameters that can be passed to AutoNumeric. See details for more information.

Details

This function wraps the AutoNumeric.js library. The parameter documentation provided here should be sufficient for most users, but for those wishing to use advanced configurations it is advised to look at the documentation on the [AutoNumeric GitHub repository](#). Alexandre Bonneau has done a wonderful job of documenting all parameters and full explanations of all parameters and their associated values can be found there.

The `...` parameter can take any of the arguments listed on the [AutoNumeric GitHub repository](#). A quick reference follows:

- `decimalPlacesRawValue` - Defines How many decimal places should be kept for the raw value. If set to NULL (default) then `decimalPlaces` is used.
- `decimalPlacesShownOnBlur` - Defines how many decimal places should be visible when the element is unfocused. If NULL (default) then `decimalPlaces` is used.
- `decimalPlacesShownOnFocus` - Defines how many decimal places should be visible when the element has the focus. If NULL (default) then `decimalPlaces` is used.
- `digitalGroupSpacing` - Defines how many numbers should be grouped together for the thousands separator groupings. Must be one of c("2", "2s", "3", "4"). Defaults to 3.
- `alwaysAllowDecimalCharacter` - Defines if the decimal character or decimal character alternative should be accepted when there is already a decimal character shown in the element. If set to TRUE, any decimal character input will be accepted and will subsequently modify the decimal character position, as well as the `rawValue`. If set to FALSE, the decimal character and its alternative key will be dropped. This is the default setting.
- `createLocalList` - Defines if a local list of AutoNumeric objects should be kept when initializing this object. Defaults to TRUE.
- `decimalCharacterAlternative` - Allow to declare an alternative decimal separator which is automatically replaced by `decimalCharacter` when typed. This is useful for countries that use a

comma ',' as the decimal character and have keyboards with numeric pads providing a period '.' as the decimal character (in France or Spain for instance). Must be NULL (default), ",", or ".".

- `emptyInputBehavior` - Defines what should be displayed in the element if the raw value is missing. One of c(NULL, "focus", "press", "always", "min", "max", "zero") or a custom value. Defaults to NULL. See [AutoNumeric GitHub repository](#) for full details.
- `selectNumberOnly` - Determine if the select all keyboard command will select the complete input text, or only the input numeric value. Defaults to TRUE.
- `selectOnFocus` - Defines if the element value should be selected on focus. Note: The selection is done using the `selectNumberOnly` option. Defaults to TRUE.
- `eventBubbles` - Defines if the custom and native events triggered by AutoNumeric should bubble up or not. Defaults to TRUE.
- `eventIsCancelable` - Defines if the custom and native events triggered by AutoNumeric should be cancelable. Defaults to TRUE.
- `formulaMode` - Defines if the formula mode can be activated by the user. If set to true, then the user can enter the formula mode by entering the '=' character. The user will then be allowed to enter any simple math formula using numeric characters as well as the following operators: +, -, *, /, (and). The formula mode is exited when the user either validate their math expression using the Enter key, or when the element is blurred. Defaults to FALSE.
- `historySize` - Set the undo/redo history table size. Defaults to 20.
- `isCancelable` - Allow the user to cancel and undo the changes he made to the given autonumeric-managed element, by pressing the Escape key. Defaults to TRUE.
- `leadingZero` - This options describes if entering 0 on the far left of the numbers is allowed, and if the superfluous zeroes should be kept when the input is blurred. One of c("allow", "deny", and "keep"). Defaults to "deny". See [AutoNumeric GitHub repository](#) for full details.
- `wheelOn` - Defines when the wheel event will increment or decrement the element value. One of c("focus", "hover"). Defaults to "focus".
- `wheelStep` - Defines by how much the element value should be incremented/decremented on the wheel event. Can be a set value or the string "progressive" which determines the step from the size of the input. Defaults to "progressive".
- `negativeBracketsTypeOnBlur` - Adds brackets-like characters on negative values when unfocused. Those brackets are visible only when the field does not have the focus. The left and right symbols should be enclosed in quotes and separated by a comma. Defaults to NULL.
- `negativePositiveSignPlacement` - Placement of the negative/positive sign relative to the `currencySymbol` option. One of c("p", "s", "l", "r", NULL), defaults to NULL. See [AutoNumeric GitHub repository](#) for further documentation.
- `negativeSignCharacter` - Defines the negative sign symbol to use. Must be a single character and be non-numeric. Defaults to "-".
- `positiveSignCharacter` - Defines the positive sign symbol to use. Must be a single character and be non-numeric. Defaults to "+".
- `showPositiveSign` - Allow the positive sign symbol `positiveSignCharacter` to be displayed for positive numbers. Defaults to FALSE.
- `onInvalidPaste` - Manage how autoNumeric react when the user tries to paste an invalid number. One of c("error", "ignore", "clamp", "truncate", "replace"). Defaults to "error".

- `overrideMinMaxLimits` - Override the minimum and maximum limits. Must be one of c("ceiling", "floor", "ignore", NULL). Defaults to "ceiling".
- `readOnly` - Defines if the element (<input> or another allowed html tag) should be set as read only on initialization. Defaults to FALSE.
- `roundingMethod` - Defines the rounding method to use. One of c("S", "A", "s", "a", "B", "U", "D", "C", "F", "N05", "CHF", "U05", "D05"). Defaults to "S". See [AutoNumeric GitHub repository](#) for further documentation.
- `saveValueToSessionStorage` - Set to TRUE to allow the `decimalPlacesShownOnFocus` value to be saved with `sessionStorage`. Defaults to FALSE.
- `serializeSpaces` - Defines how the serialize functions should treat the spaces. Either "+" (default) or "%20" (the older behavior).
- `showOnlyNumbersOnFocus` - Defines if the element value should be converted to the raw value on focus or mouseenter, (and back to the formatted on blur or mouseleave). Defaults to FALSE.
- `showWarnings` - Defines if warnings should be shown in the console. Defaults to TRUE.
- `styleRules` - Defines the rules that calculate the CSS class(es) to apply on the element, based on the raw unformatted value. Defaults to NULL.
- `suffixText` - Add a text on the right hand side of the element value. This suffix text can have any characters in its string, except numeric characters and the negative or positive sign. Defaults to NULL.
- `symbolWhenUnfocused` - Defines the symbol placed as a suffix when not in focus or hovered. Defaults to NULL.
- `unformatOnHover` - Defines if the element value should be unformatted when the user hover his mouse over it while holding the Alt key. Defaults to TRUE.
- `valuesToStrings` - Provides a way for automatically replacing the formatted value with a pre-defined string, when the raw value is equal to a specific value. Defaults to NULL.
- `watchExternalChanges` - Defines if the AutoNumeric element should watch external changes made without using `.set()`. Defaults to FALSE.

Value

An `autonumericInput` object to be used in the UI function of a Shiny App.

References

Bonneau, Alexandre. 2018. "AutoNumeric.js javascript Package". <http://autonumeric.org>

See Also

Other autonumeric: [currencyInput\(\)](#), [updateAutonumericInput\(\)](#), [updateCurrencyInput\(\)](#)

Examples

```
if (interactive()) {
  library(shiny)
  library(shinyWidgets)

  ui <- fluidPage(
    h1("Autonumeric Inputs"),
    br(),
    autonumericInput(
      inputId = "id1",
      label = "Default Input",
      value = 1234.56
    ),
    verbatimTextOutput("res1"),

    autonumericInput(
      inputId = "id2",
      label = "Custom Thousands of Dollars Input",
      value = 1234.56,
      align = "right",
      currencySymbol = "$",
      currencySymbolPlacement = "p",
      decimalCharacter = ".",
      digitGroupSeparator = ",",
      divisorWhenUnfocused = 1000,
      symbolWhenUnfocused = "K"
    ),
    verbatimTextOutput("res2"),

    autonumericInput(
      inputId = "id3",
      label = "Custom Millions of Euros Input with Positive Sign",
      value = 12345678910,
      align = "right",
      currencySymbol = "\u20ac",
      currencySymbolPlacement = "s",
      decimalCharacter = ",",
      digitGroupSeparator = ".",
      divisorWhenUnfocused = 1000000,
      symbolWhenUnfocused = " (millions)",
      showPositiveSign = TRUE
    ),
    verbatimTextOutput("res3")
  )

  server <- function(input, output, session) {
    output$res1 <- renderPrint(input$id1)
    output$res2 <- renderPrint(input$id2)
    output$res3 <- renderPrint(input$id3)
  }

  shinyApp(ui, server)
```

```
}
```

awesomeCheckbox	<i>Awesome Checkbox Input Control</i>
-----------------	---------------------------------------

Description

Create a Font Awesome Bootstrap checkbox that can be used to specify logical values.

Usage

```
awesomeCheckbox(  
  inputId,  
  label,  
  value = FALSE,  
  status = "primary",  
  width = NULL  
)
```

Arguments

inputId	The input slot that will be used to access the value.
label	Input label.
value	Initial value (TRUE or FALSE).
status	Color of the buttons, a valid Bootstrap status : default, primary, info, success, warning, danger.
width	The width of the input

Value

A checkbox control that can be added to a UI definition.

See Also

[updateAwesomeCheckbox](#)

Examples

```
## Only run examples in interactive R sessions  
if (interactive()) {  
  
  ui <- fluidPage(  
    awesomeCheckbox(inputId = "somevalue",  
                    label = "A single checkbox",  
                    value = TRUE,  
                    status = "danger"),  
    verbatimTextOutput("value")  
  )  
}
```

```
)
server <- function(input, output) {
  output$value <- renderText({ input$somevalue })
}
shinyApp(ui, server)
}
```

awesomeCheckboxGroup *Awesome Checkbox Group Input Control*

Description

Create a Font Awesome Bootstrap checkbox that can be used to specify logical values.

Usage

```
awesomeCheckboxGroup(
  inputId,
  label,
  choices,
  selected = NULL,
  inline = FALSE,
  status = "primary",
  width = NULL
)
```

Arguments

inputId	The input slot that will be used to access the value.
label	Input label.
choices	List of values to show checkboxes for.
selected	The values that should be initially selected, if any.
inline	If TRUE, render the choices inline (i.e. horizontally)
status	Color of the buttons
width	The width of the input

Value

A checkbox control that can be added to a UI definition.

See Also

[updateAwesomeCheckboxGroup](#)

Examples

```
if (interactive()) {  
  
  ui <- fluidPage(  
    br(),  
    awesomeCheckboxGroup(  
      inputId = "id1", label = "Make a choice:",  
      choices = c("graphics", "ggplot2")  
    ),  
    verbatimTextOutput(outputId = "res1"),  
    br(),  
    awesomeCheckboxGroup(  
      inputId = "id2", label = "Make a choice:",  
      choices = c("base", "dplyr", "data.table"),  
      inline = TRUE, status = "danger"  
    ),  
    verbatimTextOutput(outputId = "res2")  
  )  
  
  server <- function(input, output, session) {  
  
    output$res1 <- renderPrint({  
      input$id1  
    })  
  
    output$res2 <- renderPrint({  
      input$id2  
    })  
  
  }  
  
  shinyApp(ui = ui, server = server)  
  
}
```

awesomeRadio

Awesome Radio Buttons Input Control

Description

Create a set of prettier radio buttons used to select an item from a list.

Usage

```
awesomeRadio(  
  inputId,  
  label,
```

```

    choices,
    selected = NULL,
    inline = FALSE,
    status = "primary",
    checkbox = FALSE,
    width = NULL
  )

```

Arguments

inputId	The input slot that will be used to access the value.
label	Display label for the control, or NULL for no label.
choices	List of values to select from (if elements of the list are named then that name rather than the value is displayed to the user)
selected	The initially selected value (if not specified then defaults to the first value).
inline	If TRUE, render the choices inline (i.e. horizontally).
status	Color of the buttons, a valid Bootstrap status : default, primary, info, success, warning, danger.
checkbox	Logical, render radio like checkboxes (with a square shape).
width	The width of the input, e.g. 400px, or 100%.

Value

A set of radio buttons that can be added to a UI definition.

See Also

[updateAwesomeRadio](#)

Examples

```

## Only run examples in interactive R sessions
if (interactive()) {

ui <- fluidPage(
  br(),
  awesomeRadio(
    inputId = "id1", label = "Make a choice:",
    choices = c("graphics", "ggplot2")
  ),
  verbatimTextOutput(outputId = "res1"),
  br(),
  awesomeRadio(
    inputId = "id2", label = "Make a choice:",
    choices = c("base", "dplyr", "data.table"),
    inline = TRUE, status = "danger"
  ),
  verbatimTextOutput(outputId = "res2")
)

```

```
server <- function(input, output, session) {  
  
  output$res1 <- renderPrint({  
    input$id1  
  })  
  
  output$res2 <- renderPrint({  
    input$id2  
  })  
  
}  
  
shinyApp(ui = ui, server = server)  
  
}
```

bootstrap-utils

Bootstrap panel / alert

Description

Create a panel (box) with basic border and padding, you can use Bootstrap status to style the panel, see <https://getbootstrap.com/docs/3.4/components/#panels>.

Usage

```
panel(  
  ...,  
  heading = NULL,  
  footer = NULL,  
  extra = NULL,  
  status = c("default", "primary", "success", "info", "warning", "danger")  
)  
  
alert(  
  ...,  
  status = c("info", "success", "danger", "warning"),  
  dismissible = FALSE  
)  
  
list_group(...)
```

Arguments

...	UI elements to include inside the panel or alert.
heading	Title for the panel in a plain header.
footer	Footer for the panel.

extra	Additional elements to include like a table or a <code>list_group</code> , see examples.
status	Bootstrap status for contextual alternative.
dismissible	Adds the possibility to close the alert.

Value

A UI definition.

Examples

```
# Panels -----  
  
library(shiny)  
library(shinyWidgets)  
  
ui <- fluidPage(  
  
  tags$h2("Bootstrap panel"),  
  
  # Default  
  panel(  
    "Content goes here",  
  ),  
  
  # With header and footer  
  panel(  
    "Content goes here",  
    heading = "My title",  
    footer = "Something"  
  ),  
  
  # With status  
  panel(  
    "Content goes here",  
    heading = "My title",  
    status = "primary"  
  ),  
  
  # With table  
  panel(  
    heading = "A famous table",  
    extra = tableOutput(outputId = "table")  
  ),  
  
  # With list group  
  panel(  
    heading = "A list of things",  
    extra = list_group(  
      "First item",  
      "Second item",  
      "And third item"
```

```

    )
  )
)

server <- function(input, output, session) {

  output$table <- renderTable({
    head(mtcars)
  }, width = "100%")

}

if (interactive())
  shinyApp(ui = ui, server = server)

# Alerts -----

library(shiny)
library(shinyWidgets)

ui <- fluidPage(
  tags$h2("Alerts"),
  fluidRow(
    column(
      width = 6,
      alert(
        status = "success",
        tags$b("Well done!"), "You successfully read this important alert message."
      ),
      alert(
        status = "info",
        tags$b("Heads up!"), "This alert needs your attention, but it's not super important."
      ),
      alert(
        status = "info",
        dismissible = TRUE,
        tags$b("Dismissable"), "You can close this one."
      )
    ),
    column(
      width = 6,
      alert(
        status = "warning",
        tags$b("Warning!"), "Better check yourself, you're not looking too good."
      ),
      alert(
        status = "danger",
        tags$b("Oh snap!"), "Change a few things up and try submitting again."
      )
    )
  )
)

```

```
    )
  )
)

server <- function(input, output, session) {

}

if (interactive())
  shinyApp(ui, server)

# List group -----

library(shiny)
library(shinyWidgets)

ui <- fluidPage(
  tags$h2("List group"),

  tags$b("List of item:"),
  list_group(
    "First item",
    "Second item",
    "And third item"
  ),

  tags$b("Set active item:"),
  list_group(
    list(class = "active", "First item"),
    "Second item",
    "And third item"
  )
)

server <- function(input, output, session) {

}

if (interactive())
  shinyApp(ui, server)
```

checkboxGroupButtons *Buttons Group checkbox Input Control*

Description

Create buttons grouped that act like checkboxes.

Usage

```
checkboxGroupButtons(
  inputId,
  label = NULL,
  choices = NULL,
  selected = NULL,
  status = "default",
  size = "normal",
  direction = "horizontal",
  justified = FALSE,
  individual = FALSE,
  checkIcon = list(),
  width = NULL,
  choiceNames = NULL,
  choiceValues = NULL,
  disabled = FALSE
)
```

Arguments

inputId	The input slot that will be used to access the value.
label	Input label.
choices	List of values to select from (if elements of the list are named then that name rather than the value is displayed to the user)
selected	The initially selected value.
status	Add a class to the buttons, you can use Bootstrap status like 'info', 'primary', 'danger', 'warning' or 'success'. Or use an arbitrary strings to add a custom class, e.g. : with status = 'myClass', buttons will have class btn-myClass.
size	Size of the buttons ('xs', 'sm', 'normal', 'lg')
direction	Horizontal or vertical.
justified	If TRUE, fill the width of the parent div.
individual	If TRUE, buttons are separated.
checkIcon	A list, if no empty must contain at least one element named 'yes' corresponding to an icon to display if the button is checked.
width	The width of the input, e.g. '400px', or '100%'.
choiceNames, choiceValues	Same as in checkboxGroupInput . List of names and values, respectively, that are displayed to the user in the app and correspond to the each choice (for this reason, choiceNames and choiceValues must have the same length).
disabled	Initialize buttons in a disabled state (users won't be able to select a value).

Value

A buttons group control that can be added to a UI definition.

See Also[updateCheckboxGroupButtons](#)**Examples**

```
if (interactive()) {  
  
  ui <- fluidPage(  
    tags$h1("checkboxGroupButtons examples"),  
  
    checkboxGroupButtons(  
      inputId = "somevalue1",  
      label = "Make a choice: ",  
      choices = c("A", "B", "C")  
    ),  
    verbatimTextOutput("value1"),  
  
    checkboxGroupButtons(  
      inputId = "somevalue2",  
      label = "With custom status:",  
      choices = names(iris),  
      status = "primary"  
    ),  
    verbatimTextOutput("value2"),  
  
    checkboxGroupButtons(  
      inputId = "somevalue3",  
      label = "With icons:",  
      choices = names(mtcars),  
      checkIcon = list(  
        yes = icon("check-square"),  
        no = icon("square-o")  
      )  
    ),  
    verbatimTextOutput("value3")  
  )  
  server <- function(input, output) {  
  
    output$value1 <- renderPrint({ input$somevalue1 })  
    output$value2 <- renderPrint({ input$somevalue2 })  
    output$value3 <- renderPrint({ input$somevalue3 })  
  
  }  
  shinyApp(ui, server)  
}
```

Description

Customize the appearance of the original shiny's sliderInput

Usage

```
chooseSliderSkin(
  skin = c("Shiny", "Flat", "Big", "Modern", "Sharp", "Round", "Square", "Nice",
    "Simple", "HTML5"),
  color = NULL
)
```

Arguments

skin	The skin to apply. Choose among 5 different flavors, namely 'Shiny', 'Flat', 'Modern', 'Nice', 'Simple', 'HTML5', 'Round' and 'Square'.
color	A color to apply to all sliders. Works with following skins: 'Shiny', 'Flat', 'Modern', 'HTML5'. For 'Flat' a CSS filter is applied, desired color maybe a little offset.

Note

It is not currently possible to apply multiple themes at the same time.

See Also

See [setSliderColor](#) to update the color of your sliderInput.

Examples

```
if (interactive()) {

  library(shiny)
  library(shinyWidgets)

  # With Modern design

  ui <- fluidPage(
    chooseSliderSkin("Modern"),
    sliderInput("obs", "Customized single slider:",
      min = 0, max = 100, value = 50
    ),
    sliderInput("obs2", "Customized range slider:",
      min = 0, max = 100, value = c(40, 80)
    ),
    plotOutput("distPlot")
  )

  server <- function(input, output) {

    output$distPlot <- renderPlot({
      hist(rnorm(input$obs))
    })
  }
}
```

```

    })
  }

  shinyApp(ui, server)

# Use Flat design & a custom color

ui <- fluidPage(
  chooseSliderSkin("Flat", color = "#112446"),
  sliderInput("obs", "Customized single slider:",
    min = 0, max = 100, value = 50
  ),
  sliderInput("obs2", "Customized range slider:",
    min = 0, max = 100, value = c(40, 80)
  ),
  sliderInput("obs3", "An other slider:",
    min = 0, max = 100, value = 50
  ),
  plotOutput("distPlot")
)

server <- function(input, output) {

  output$distPlot <- renderPlot({
    hist(rnorm(input$obs))
  })
}

shinyApp(ui, server)
}

```

circleButton

Circle Action button

Description

Create a rounded action button.

Usage

```
circleButton(inputId, icon = NULL, status = "default", size = "default", ...)
```

Arguments

inputId	The input slot that will be used to access the value.
icon	An icon to appear on the button.

status	Color of the button.
size	Size of the button : default, lg, sm, xs.
...	Named attributes to be applied to the button.

Examples

```

if (interactive()) {
  library(shiny)
  library(shinyWidgets)

  ui <- fluidPage(
    tags$h3("Rounded actionBution"),
    circleButton(inputId = "btn1", icon = icon("gear")),
    circleButton(
      inputId = "btn2",
      icon = icon("sliders"),
      status = "primary"
    ),
    verbatimTextOutput("res1"),
    verbatimTextOutput("res2")
  )

  server <- function(input, output, session) {

    output$res1 <- renderPrint({
      paste("value button 1:", input$btn1)
    })
    output$res2 <- renderPrint({
      paste("value button 2:", input$btn2)
    })

  }

  shinyApp(ui, server)
}

```

closeSweetAlert

Close Sweet Alert

Description

Close Sweet Alert

Usage

```
closeSweetAlert(session = shiny::getDefaultReactiveDomain())
```

Arguments

session	The session object passed to function given to shinyServer.
---------	---

 colorPickr

*Color Pickr***Description**

A widget to pick color with different themes and options.

Usage

```

colorPickr(
  inputId,
  label,
  selected = "#112446",
  swatches = NULL,
  preview = TRUE,
  hue = TRUE,
  opacity = FALSE,
  interaction = NULL,
  theme = c("classic", "monolith", "nano"),
  update = c("save", "changestop", "change", "swatchselect"),
  position = "bottom-middle",
  hideOnSave = TRUE,
  useAsButton = FALSE,
  inline = FALSE,
  i18n = NULL,
  pickr_width = NULL,
  width = NULL
)

updateColorPickr(session, inputId, value = NULL, action = NULL)

```

Arguments

inputId	The id of the input object.
label	Display label for the color pickr, or NULL for no label.
selected	Default selected value.
swatches	Optional color swatches. When NULL, swatches are disabled.
preview	Display comparison between previous state and new color.
hue	Display hue slider.
opacity	Display opacity slider.
interaction	List of parameters to show or hide components on the bottom interaction bar. See link below for documentation.
theme	Which theme you want to use. Can be 'classic', 'monolith' or 'nano'.
update	When to update value server-side.

position	Defines the position of the color-picker.
hideOnSave	Hide color-picker after selecting a color.
useAsButton	Show color-picker in a button instead of an input with value displayed.
inline	Always show color-picker in page as a full element.
i18n	List of translations for labels, see online documentation.
pickr_width	Color-picker width (correspond to popup window).
width	Color-picker width (correspond to input).
session	The session object passed to function given to shinyServer.
value	The value to set for the input object.
action	Action to perform on color-picker: enable, disable, show or hide.

Value

a color picker input widget that can be added to the UI of a shiny app.

No return value.

Note

Widget based on JS library pickr by [Simonwep](https://github.com/Simonwep/pickr). See online documentation for more information: <https://github.com/Simonwep/pickr>.

Examples

```
library(shiny)
library(shinyWidgets)

ui <- fluidPage(
  tags$h2("Color pickr"),
  fluidRow(
    column(
      width = 4,
      tags$h4("Appearance"),
      colorPickr(
        inputId = "id1",
        label = "Pick a color (classic theme):",
        width = "100%"
      ),
      verbatimTextOutput("res1"),
      colorPickr(
        inputId = "id2",
        label = "Pick a color (monolith theme):",
        theme = "monolith",
        width = "100%"
      ),
      verbatimTextOutput("res2"),
      colorPickr(
        inputId = "id3",
```

```

    label = "Pick a color (nano theme):",
    theme = "nano",
    width = "100%"
  ),
  verbatimTextOutput("res3"),
  colorPickr(
    inputId = "id4",
    label = "Pick a color (swatches + opacity):",
    swatches = scales::viridis_pal()(10),
    opacity = TRUE
  ),
  verbatimTextOutput("res4"),
  colorPickr(
    inputId = "id5",
    label = "Pick a color (only swatches):",
    selected = "#440154",
    swatches = c(
      scales::viridis_pal()(9),
      scales::brewer_pal(palette = "Blues")(9),
      scales::brewer_pal(palette = "Reds")(9)
    ),
    update = "change",
    opacity = FALSE,
    preview = FALSE,
    hue = FALSE,
    interaction = list(
      hex = FALSE,
      rgba = FALSE,
      input = FALSE,
      save = FALSE,
      clear = FALSE
    ),
    pickr_width = "245px"
  ),
  verbatimTextOutput("res5"),
  colorPickr(
    inputId = "id6",
    label = "Pick a color (button):",
    swatches = scales::viridis_pal()(10),
    theme = "monolith",
    useAsButton = TRUE
  ),
  verbatimTextOutput("res6"),
  colorPickr(
    inputId = "id7",
    label = "Pick a color (inline):",
    swatches = scales::viridis_pal()(10),
    theme = "monolith",
    inline = TRUE,
    width = "100%"
  ),
  verbatimTextOutput("res7")
),

```

```

column(
  width = 4,
  tags$h4("Trigger server update"),
  colorPickr(
    inputId = "id11",
    label = "Pick a color (update on save):",
    position = "right-start"
  ),
  verbatimTextOutput("res11"),
  colorPickr(
    inputId = "id12",
    label = "Pick a color (update on change):",
    update = "change",
    interaction = list(
      clear = FALSE,
      save = FALSE
    ),
    position = "right-start"
  ),
  verbatimTextOutput("res12"),
  colorPickr(
    inputId = "id13",
    label = "Pick a color (update on change stop):",
    update = "changestop",
    interaction = list(
      clear = FALSE,
      save = FALSE
    ),
    position = "right-start"
  ),
  verbatimTextOutput("res13")
),
column(
  width = 4,
  tags$h4("Update server-side"),
  colorPickr(
    inputId = "id21",
    label = "Pick a color (update value):",
    width = "100%"
  ),
  verbatimTextOutput("res21"),
  actionButton("red", "Update red"),
  actionButton("green", "Update green"),
  actionButton("blue", "Update blue"),
  colorPickr(
    inputId = "id22",
    label = "Pick a color (enable/disable):",
    width = "100%"
  ),
  verbatimTextOutput("res22"),
  actionButton("enable", "Enable"),
  actionButton("disable", "Disable")
)

```

```
)
)

server <- function(input, output, session) {

  output$res1 <- renderPrint(input$id1)
  output$res2 <- renderPrint(input$id2)
  output$res3 <- renderPrint(input$id3)
  output$res4 <- renderPrint(input$id4)
  output$res5 <- renderPrint(input$id5)
  output$res6 <- renderPrint(input$id6)
  output$res7 <- renderPrint(input$id7)

  output$res11 <- renderPrint(input$id11)
  output$res12 <- renderPrint(input$id12)
  output$res13 <- renderPrint(input$id13)

  output$res21 <- renderPrint(input$id21)
  observeEvent(input$red, {
    updateColorPickr(session, "id21", "firebrick")
  })
  observeEvent(input$green, {
    updateColorPickr(session, "id21", "forestgreen")
  })
  observeEvent(input$blue, {
    updateColorPickr(session, "id21", "steelblue")
  })

  output$res22 <- renderPrint(input$id22)
  observeEvent(input$enable, {
    updateColorPickr(session, "id22", action = "enable")
  })
  observeEvent(input$disable, {
    updateColorPickr(session, "id22", action = "disable")
  })

}

if (interactive())
  shinyApp(ui, server)
```

colorSelectorInput *Color Selector Input*

Description

Choose between a restrictive set of colors.

Usage

```
colorSelectorInput(
  inputId,
  label,
  choices,
  selected = NULL,
  mode = c("radio", "checkbox"),
  display_label = FALSE,
  ncol = 10
)
```

```
colorSelectorExample()
```

```
colorSelectorDrop(
  inputId,
  label,
  choices,
  selected = NULL,
  display_label = FALSE,
  ncol = 10,
  circle = TRUE,
  size = "sm",
  up = FALSE,
  width = NULL
)
```

Arguments

inputId	The input slot that will be used to access the value.
label	Display label for the control, or NULL for no label.
choices	A list of colors, can be a list of named list, see example.
selected	Default selected color, if NULL the first color for mode = 'radio' and none for mode = 'checkbox'
mode	'radio' for only one choice, 'checkbox' for selecting multiple values.
display_label	Display list's names after palette of color.
ncol	If choices is not a list but a vector, go to line after n elements.
circle	Logical, use a circle or a square button
size	Size of the button : default, lg, sm, xs.
up	Logical. Display the dropdown menu above.
width	Width of the dropdown menu content.

Functions

- colorSelectorExample: Examples of use for colorSelectorInput
- colorSelectorDrop: Display a colorSelector in a dropdown button

Examples

```

if (interactive()) {

# Full example
colorSelectorExample()

# Simple example
ui <- fluidPage(
  colorSelectorInput(
    inputId = "mycolor1", label = "Pick a color :",
    choices = c("steelblue", "cornflowerblue",
               "firebrick", "palegoldenrod",
               "forestgreen")
  ),
  verbatimTextOutput("result1")
)

server <- function(input, output, session) {
  output$result1 <- renderPrint({
    input$mycolor1
  })
}

shinyApp(ui = ui, server = server)

}

```

currencyInput

Format Numeric Inputs

Description

Shiny widgets for as-you-type formatting of currency and numeric values. For a more modifiable version see [autonumericInput](#). These two functions do the exact same thing but are named differently for more intuitive use (currency for money, formatNumeric for percentage or other).

Usage

```

currencyInput(
  inputId,
  label,
  value,
  format = "euro",
  width = NULL,
  align = "center"
)

formatNumericInput(
  inputId,

```

```

    label,
    value,
    format = "commaDecimalCharDotSeparator",
    width = NULL,
    align = "center"
  )

```

Arguments

inputId	The input slot that will be used to access the value.
label	Display label for the control, or NULL for no label.
value	Initial value (unformatted).
format	A character string specifying the currency format of the input. See "Details" for possible values.
width	The width of the input box, eg. "200px" or "100%".
align	The alignment of the text inside the input box, one of "center", "left", "right". Defaults to "center".

Details

In regards to format, there are currently 41 sets of predefined options that can be used, most of which are variations of one another. The most common are:

- "French"
- "Spanish"
- "NorthAmerican"
- "British"
- "Swiss"
- "Japanese"
- "Chinese"
- "Brazilian"
- "Turkish"
- "euro" (same as "French")
- "dollar" (same as "NorthAmerican")
- "percentageEU2dec"
- "percentageUS2dec"
- "dotDecimalCharCommaSeparator"
- "commaDecimalCharDotSeparator"

To see the full list please visit [this section](#) of the AutoNumeric Github Page.

Value

a currency input widget that can be added to the UI of a shiny app.

References

Bonneau, Alexandre. 2018. "AutoNumeric.js javascript Package". <http://autonumeric.org>

See Also

Other autonumeric: [autonumericInput\(\)](#), [updateAutonumericInput\(\)](#), [updateCurrencyInput\(\)](#)

Examples

```
if (interactive()) {
  library(shiny)
  library(shinyWidgets)

  ui <- fluidPage(
    tags$h2("Currency Input"),

    currencyInput("id1", "Euro:", value = 1234, format = "euro", width = 200, align = "right"),
    verbatimTextOutput("res1"),

    currencyInput("id2", "Dollar:", value = 1234, format = "dollar", width = 200, align = "right"),
    verbatimTextOutput("res2"),

    currencyInput("id3", "Yen:", value = 1234, format = "Japanese", width = 200, align = "right"),
    verbatimTextOutput("res3"),

    br(),
    tags$h2("Formatted Numeric Input"),

    formatNumericInput("id4", "Numeric:", value = 1234, width = 200),
    verbatimTextOutput("res4"),

    formatNumericInput("id5", "Percent:", value = 1234, width = 200, format = "percentageEU2dec"),
    verbatimTextOutput("res5")
  )

  server <- function(input, output, session) {
    output$res1 <- renderPrint(input$id1)
    output$res2 <- renderPrint(input$id2)
    output$res3 <- renderPrint(input$id3)
    output$res4 <- renderPrint(input$id4)
    output$res5 <- renderPrint(input$id5)
  }

  shinyApp(ui, server)
}
```

Description

Some examples on how to use airDatepickerInput

Usage

```
demoAirDatepicker(example = "datepicker")
```

Arguments

example	Name of the example : "datepicker", "timepicker", "months", "years", "update".
---------	--

Examples

```
if (interactive()) {  
  demoAirDatepicker("datepicker")  
}
```

demoNoUiSlider

Some examples on how to use noUiSliderInput

Description

Some examples on how to use noUiSliderInput

Usage

```
demoNoUiSlider(example = "color")
```

Arguments

example	Name of the example : "color", "update", "behaviour", "more", "format".
---------	---

Examples

```
if (interactive()) {  
  demoNoUiSlider("color")  
}
```

demoNumericRange	<i>An example showing how numericRangeInput works</i>
------------------	---

Description

An example showing how numericRangeInput works

Usage

```
demoNumericRange()
```

Examples

```
if (interactive()) {  
    demoNumericRange()  
}
```

downloadBttn	<i>Create a download actionBttn</i>
--------------	---

Description

Create a download button with [actionBttn](#).

Usage

```
downloadBttn(  
    outputId,  
    label = "Download",  
    style = "unite",  
    color = "primary",  
    size = "md",  
    block = FALSE,  
    no_outline = TRUE  
)
```

Arguments

outputId	The name of the output slot that the downloadHandler is assigned to.
label	The label that should appear on the button.
style	Style of the button, to choose between simple, bordered, minimal, stretch, jelly, gradient, fill, material-circle, material-flat, pill, float, unite.
color	Color of the button : default, primary, warning, danger, success, royal.

size	Size of the button : xs,sm, md, lg.
block	Logical, full width button.
no_outline	Logical, don't show outline when navigating with keyboard/interact using mouse or touch.

Examples

```

if (interactive()) {

  library(shiny)
  library(shinyWidgets)

  ui <- fluidPage(
    tags$h2("Download btn"),
    downloadBttn(
      outputId = "downloadData",
      style = "bordered",
      color = "primary"
    )
  )

  server <- function(input, output, session) {

    output$downloadData <- downloadHandler(
      filename = function() {
        paste('data-', Sys.Date(), '.csv', sep='')
      },
      content = function(con) {
        write.csv(mtcars, con)
      }
    )

  }

  shinyApp(ui, server)
}

```

drop-menu-interaction *Interact with Drop Menu*

Description

Interact with Drop Menu

Usage

```
enableDropMenu(id, session = shiny::getDefaultReactiveDomain())
```

```

disableDropMenu(id, session = shiny::getDefaultReactiveDomain())

showDropMenu(id, session = shiny::getDefaultReactiveDomain())

hideDropMenu(id, session = shiny::getDefaultReactiveDomain())

```

Arguments

<code>id</code>	Drop menu ID, the tag's ID followed by "_dropmenu".
<code>session</code>	Shiny session.

Examples

```

if (interactive()) {
  library(shiny)
  library(shinyWidgets)

  ui <- fluidPage(
    tags$h2("Drop Menu interactions"),
    dropMenu(
      actionButton("myid", "See what's inside"),
      "Drop menu content",
      actionButton("hide", "Close menu"),
      position = "right middle"
    ),
    tags$br(),
    tags$p("Is drop menu opened?"),
    verbatimTextOutput("isOpen"),
    actionButton("show", "show menu"),
    tags$br(),
    tags$br(),
    dropMenu(
      actionButton("dontclose", "Only closeable from server"),
      "Drop menu content",
      actionButton("close", "Close menu"),
      position = "right middle",
      hideOnClick = FALSE
    )
  )
}

server <- function(input, output, session) {

  output$isOpen <- renderPrint({
    input$myid_dropmenu
  })

  observeEvent(input$show, {
    showDropMenu("myid_dropmenu")
  })

  observeEvent(input$hide, {
    hideDropMenu("myid_dropmenu")
  })
}

```

```

    })

    observeEvent(input$close, {
      hideDropMenu("dontclose_dropdown")
    })
  }

  shinyApp(ui, server)
}

```

 dropdown

Dropdown

Description

Create a dropdown menu

Usage

```

dropdown(
  ...,
  style = "default",
  status = "default",
  size = "md",
  icon = NULL,
  label = NULL,
  tooltip = FALSE,
  right = FALSE,
  up = FALSE,
  width = NULL,
  animate = FALSE,
  inputId = NULL
)

```

Arguments

...	List of tag to be displayed into the dropdown menu.
style	Character. if default use Bootstrap button (like an <code>actionButton</code>), else use an actionBtn , see argument <code>style</code> (in actionBtn documentation) for possible values.
status	Add a class to the buttons, you can use Bootstrap status like 'info', 'primary', 'danger', 'warning' or 'success'. Or use an arbitrary strings to add a custom class, e.g. : with <code>status = 'myClass'</code> , buttons will have class <code>btn-myClass</code> .
size	Size of the button : default, lg, sm, xs.
icon	An icon to appear on the button.

label	Label to appear on the button. If circle = TRUE and tooltip = TRUE, label is used in tooltip.
tooltip	Put a tooltip on the button, you can customize tooltip with tooltipOptions.
right	Logical. The dropdown menu starts on the right.
up	Logical. Display the dropdown menu above.
width	Width of the dropdown menu content.
animate	Add animation on the dropdown, can be logical or result of animateOptions.
inputId	Optional, id for the button, the button act like an actionButton, and you can use the id to toggle the dropdown menu server-side.

Details

This function is similar to `dropdownButton` but don't use Bootstrap, so you can put `pickerInput` in it. Moreover you can add animations on the appearance / disappearance of the dropdown with `animate.css`.

See Also

[animateOptions](#) for animation, [tooltipOptions](#) for tooltip and [actionBttn](#) for the button.

Examples

```
## Only run examples in interactive R sessions
if (interactive()) {

  library("shiny")
  library("shinyWidgets")

  ui <- fluidPage(
    tags$h2("pickerInput in dropdown"),
    br(),
    dropdown(

      tags$h3("List of Input"),

      pickerInput(inputId = 'xcol2',
                  label = 'X Variable',
                  choices = names(iris),
                  options = list(`style` = "btn-info")),

      pickerInput(inputId = 'ycol2',
                  label = 'Y Variable',
                  choices = names(iris),
                  selected = names(iris)[[2]],
                  options = list(`style` = "btn-warning")),

      sliderInput(inputId = 'clusters2',
                  label = 'Cluster count',
                  value = 3,
                  min = 1, max = 9),
```

```

    style = "unite", icon = icon("gear"),
    status = "danger", width = "300px",
    animate = animateOptions(
      enter = animations$fading_entrances$fadeInLeftBig,
      exit = animations$fading_exits$fadeOutRightBig
    )
  ),
)

plotOutput(outputId = 'plot2')
)

server <- function(input, output, session) {

  selectedData2 <- reactive({
    iris[, c(input$xcoll2, input$ycol2)]
  })

  clusters2 <- reactive({
    kmeans(selectedData2(), input$clusters2)
  })

  output$plot2 <- renderPlot({
    palette(c("#E41A1C", "#377EB8", "#4DAF4A",
              "#984EA3", "#FF7F00", "#FFFF33",
              "#A65628", "#F781BF", "#999999"))

    par(mar = c(5.1, 4.1, 0, 1))
    plot(selectedData2(),
          col = clusters2()$cluster,
          pch = 20, cex = 3)
    points(clusters2()$centers, pch = 4, cex = 4, lwd = 4)
  })

}

shinyApp(ui = ui, server = server)

}

```

dropdownButton

Dropdown Button

Description

Create a dropdown menu with Bootstrap where you can put input elements.

Usage

```
dropdownButton(
```

```

    ...,
    circle = TRUE,
    status = "default",
    size = "default",
    icon = NULL,
    label = NULL,
    tooltip = FALSE,
    right = FALSE,
    up = FALSE,
    width = NULL,
    margin = "10px",
    inline = FALSE,
    inputId = NULL
)

```

Arguments

...	List of tag to be displayed into the dropdown menu.
circle	Logical. Use a circle button
status	Add a class to the buttons, you can use Bootstrap status like 'info', 'primary', 'danger', 'warning' or 'success'. Or use an arbitrary strings to add a custom class, e.g. : with status = 'myClass', buttons will have class btn-myClass.
size	Size of the button : default, lg, sm, xs.
icon	An icon to appear on the button.
label	Label to appear on the button. If circle = TRUE and tooltip = TRUE, label is used in tooltip.
tooltip	Put a tooltip on the button, you can customize tooltip with tooltipOptions.
right	Logical. The dropdown menu starts on the right.
up	Logical. Display the dropdown menu above.
width	Width of the dropdown menu content.
margin	Value of the dropdown margin-right and margin-left menu content.
inline	use an inline (span()) or block container (div()) for the output.
inputId	Optional, id for the button, the button act like an <code>actionButton</code> , and you can use the id to toggle the dropdown menu server-side with toggleDropdownButton .

Details

It is possible to know if a dropdown is open or closed server-side with `input$<inputId>_state`.

Note

`pickerInput` doesn't work inside `dropdownButton` because that's also a dropdown and you can't nest them. Instead use [dropdown](#), it has similar features but is built differently so it works.

Examples

```
## Only run examples in interactive R sessions
if (interactive()) {

  library(shiny)
  library(shinyWidgets)

  ui <- fluidPage(
    dropdownButton(
      inputId = "mydropdown",
      label = "Controls",
      icon = icon("sliders"),
      status = "primary",
      circle = FALSE,
      sliderInput(
        inputId = "n",
        label = "Number of observations",
        min = 10, max = 100, value = 30
      ),
      prettyToggle(
        inputId = "na",
        label_on = "NAs kept",
        label_off = "NAs removed",
        icon_on = icon("check"),
        icon_off = icon("remove")
      )
    ),
    tags$div(style = "height: 140px;"), # spacing
    verbatimTextOutput(outputId = "out"),
    verbatimTextOutput(outputId = "state")
  )

  server <- function(input, output, session) {

    output$out <- renderPrint({
      cat(
        " # n\n", input$n, "\n",
        "# na\n", input$na
      )
    })

    output$state <- renderPrint({
      cat("Open:", input$mydropdown_state)
    })

  }

  shinyApp(ui, server)
}
```

 dropMenu

Drop Menu

Description

A pop-up menu to hide inputs and other elements into.

Usage

```
dropMenu(
  tag,
  ...,
  padding = "5px",
  placement = c("bottom", "bottom-start", "bottom-end", "top", "top-start", "top-end",
    "right", "right-start", "right-end", "left", "left-start", "left-end"),
  trigger = "click",
  arrow = TRUE,
  theme = c("light", "light-border", "material", "translucent"),
  hideOnClick = TRUE,
  maxWidth = "none",
  options = NULL
)
```

Arguments

tag	An HTML tag to which attach the menu.
...	UI elements to be displayed in the menu.
padding	Amount of padding to apply. Can be numeric (in pixels) or character (e.g. "3em").
placement	Positions of the menu relative to its reference element (tag).
trigger	The event(s) which cause the menu to show.
arrow	Determines if the menu has an arrow.
theme	CSS theme to use.
hideOnClick	Determines if the menu should hide if a mousedown event was fired outside of it (i.e. clicking on the reference element or the body of the page).
maxWidth	Determines the maximum width of the menu.
options	Additional options, see dropMenuOptions .

Value

A UI definition.

See Also

[dropMenu interaction](#) for functions and examples to interact with dropMenu from server.

Examples

```

if (interactive()) {
  library(shiny)
  library(shinyWidgets)

  ui <- fluidPage(
    tags$h3("drop example"),

    dropMenu(
      actionButton("go0", "See what"),
      tags$div(
        tags$h3("This is a dropdown"),
        tags$ul(
          tags$li("You can use HTML inside"),
          tags$li("Maybe Shiny inputs"),
          tags$li("And maybe outputs"),
          tags$li("and should work in markdown")
        )
      ),
      theme = "light-border",
      placement = "right",
      arrow = FALSE
    ),

    tags$br(),

    dropMenu(
      actionButton("go", "See what"),
      tags$h3("Some inputs"),
      sliderInput(
        "obs", "Number of observations:",
        min = 0, max = 1000, value = 500
      ),
      selectInput(
        "variable", "Variable:",
        c("Cylinders" = "cyl",
          "Transmission" = "am",
          "Gears" = "gear")
      ),
      pickerInput(
        inputId = "pckr",
        label = "Select all option",
        choices = rownames(mtcars),
        multiple = TRUE,
        options = list(`actions-box` = TRUE)
      ),
      radioButtons(
        "dist", "Distribution type:",
        c("Normal" = "norm",
          "Uniform" = "unif",
          "Log-normal" = "lnorm",

```

```

      "Exponential" = "exp")
    )
  ),
  verbatimTextOutput("slider"),
  verbatimTextOutput("select"),
  verbatimTextOutput("picker"),
  verbatimTextOutput("radio")
)

server <- function(input, output, session) {

  output$slider <- renderPrint(input$obs)
  output$select <- renderPrint(input$variable)
  output$picker <- renderPrint(input$pckr)
  output$radio <- renderPrint(input$dist)

}

shinyApp(ui, server)
}

```

 dropMenuOptions

Drop menu options

Description

Those options will be passed to the underlying JavaScript library powering dropMenu : tippy.js. See all available options here <https://atomiks.github.io/tippyjs/all-props/>.

Usage

```
dropMenuOptions(duration = c(275, 250), animation = "fade", flip = FALSE, ...)
```

Arguments

duration	Duration of the CSS transition animation in ms.
animation	The type of transition animation.
flip	Determines if the tippy flips so that it is placed within the viewport as best it can be if there is not enough space.
...	Additional arguments.

Value

a list of options to be used in [dropMenu](#).

execute_safely	<i>Execute an expression safely in server</i>
----------------	---

Description

Execute an expression without generating an error, instead display the error to the user in an alert.

Usage

```
execute_safely(  
  expr,  
  title = "Error",  
  message = "An error occurred, detail below:",  
  include_error = TRUE,  
  error_return = NULL,  
  session = shiny::getDefaultReactiveDomain()  
)
```

Arguments

expr	Expression to evaluate
title	Title to display in the alert in case of error.
message	Message to display below title.
include_error	Include the error message generated by R.
error_return	Value to return in case of error.
session	Shiny session.

Value

Result of expr if no error, otherwise the value of error_return (NULL by default to use [req](#) in other reactive context).

Examples

```
library(shiny)  
library(shinyWidgets)  
  
ui <- fluidPage(  
  tags$h2("Execute code safely in server"),  
  fileInput(  
    inputId = "file",  
    label = "Try to import something else than a text file (Excel for example)"  
  ),  
  verbatimTextOutput(outputId = "file_value")  
)  
  
server <- function(input, output, session) {
```

```
options(warn = 2) # turns warnings into errors
onStop(function() {
  options(warn = 0)
})

r <- reactive({
  req(input$file)
  execute_safely(
    read.csv(input$file$datapath)
  )
})

output$file_value <- renderPrint({
  head(r())
})

}

if (interactive())
  shinyApp(ui, server)
```

html-dependencies

HTML dependencies

Description

These functions are used internally to load dependencies for widgets. Not all of them are exported. Below are the ones needed for package **fresh**.

Usage

```
html_dependency_awesome()
```

```
html_dependency_btn()
```

```
html_dependency_pretty()
```

```
html_dependency_bsswitch()
```

```
html_dependency_sweetalert2(
  theme = c("sweetalert2", "minimal", "dark", "bootstrap-4", "material-ui", "bulma",
    "borderless")
)
```

Arguments

theme SweetAlert theme to use.

Value

an `htmlDependency`.

Examples

```
# Use in UI or tags function

library(shiny)
fluidPage(
  html_dependency_awesome()
)
```

inputSweetAlert	<i>Launch an input text dialog</i>
-----------------	------------------------------------

Description

Launch a popup with a text input

Usage

```
inputSweetAlert(
  session,
  inputId,
  title = NULL,
  text = NULL,
  type = NULL,
  input = c("text", "password", "textarea", "radio", "checkbox", "select"),
  inputOptions = NULL,
  inputPlaceholder = NULL,
  btn_labels = "Ok",
  btn_colors = NULL,
  reset_input = TRUE,
  ...
)
```

Arguments

<code>session</code>	The session object passed to function given to <code>shinyServer</code> .
<code>inputId</code>	The input slot that will be used to access the value. If in a Shiny module, it use same logic than inputs : use namespace in UI, not in server.
<code>title</code>	Title of the pop-up.
<code>text</code>	Text of the pop-up.
<code>type</code>	Type of the pop-up : "info", "success", "warning", "error" or "question".

input	Type of input, possible values are : "text", "password", "textarea", "radio", "checkbox" or "select".
inputOptions	Options for the input. For "radio" and "select" it will be choices.
inputPlaceholder	Placeholder for the input, use it for "text" or "checkbox".
btn_labels	Label(s) for button(s).
btn_colors	Color(s) for button(s).
reset_input	Set the input value to NULL when alert is displayed.
...	Other arguments passed to JavaScript method.

Note

This function use the JavaScript sweetalert2 library, see the official documentation for more <https://sweetalert2.github.io/>.

See Also

[sendSweetAlert](#), [confirmSweetAlert](#), [closeSweetAlert](#).

Examples

```
if (interactive()) {
  library("shiny")
  library("shinyWidgets")

  ui <- fluidPage(
    tags$h1("Input sweet alert"),
    actionButton(inputId = "text", label = "Text Input"),
    verbatimTextOutput(outputId = "text"),
    actionButton(inputId = "password", label = "Password Input"),
    verbatimTextOutput(outputId = "password"),
    actionButton(inputId = "radio", label = "Radio Input"),
    verbatimTextOutput(outputId = "radio"),
    actionButton(inputId = "checkbox", label = "Checkbox Input"),
    verbatimTextOutput(outputId = "checkbox"),
    actionButton(inputId = "select", label = "Select Input"),
    verbatimTextOutput(outputId = "select")
  )
  server <- function(input, output, session) {

    observeEvent(input$text, {
      inputSweetAlert(
        session = session, inputId = "mytext", input = "text",
        title = "What's your name ?"
      )
    })
    output$text <- renderPrint(input$mytext)

    observeEvent(input$password, {
```

```

    inputSweetAlert(
      session = session, inputId = "mypassword", input = "password",
      title = "What's your password ?"
    )
  })
  output$password <- renderPrint(input$mypassword)

  observeEvent(input$radio, {
    inputSweetAlert(
      session = session, inputId = "myradio", input = "radio",
      inputOptions = c("Banana" , "Orange", "Apple"),
      title = "What's your favorite fruit ?"
    )
  })
  output$radio <- renderPrint(input$myradio)

  observeEvent(input$checkbox, {
    inputSweetAlert(
      session = session, inputId = "mycheckbox", input = "checkbox",
      inputPlaceholder = "Yes I agree",
      title = "Do you agree ?"
    )
  })
  output$checkbox <- renderPrint(input$mycheckbox)

  observeEvent(input$select, {
    inputSweetAlert(
      session = session, inputId = "myselect", input = "select",
      inputOptions = c("Banana" , "Orange", "Apple"),
      title = "What's your favorite fruit ?"
    )
  })
  output$select <- renderPrint(input$myselect)
}

shinyApp(ui = ui, server = server)
}

```

knobInput

Knob Input

Description

Knob Input

Usage

```
knobInput(
  inputId,
```

```

    label,
    value,
    min = 0,
    max = 100,
    step = 1,
    angleOffset = 0,
    angleArc = 360,
    cursor = FALSE,
    thickness = NULL,
    lineCap = c("default", "round"),
    displayInput = TRUE,
    displayPrevious = FALSE,
    rotation = c("clockwise", "anticlockwise"),
    fgColor = NULL,
    inputColor = NULL,
    bgColor = NULL,
    pre = NULL,
    post = NULL,
    fontSize = NULL,
    readOnly = FALSE,
    skin = NULL,
    width = NULL,
    height = NULL,
    immediate = TRUE
)

```

Arguments

inputId	The input slot that will be used to access the value.
label	Display label for the control, or NULL for no label.
value	Initial value.
min	Minimum allowed value, default to 0.
max	Maximum allowed value, default to 100.
step	Specifies the interval between each selectable value, default to 1.
angleOffset	Starting angle in degrees, default to 0.
angleArc	Arc size in degrees, default to 360.
cursor	Display mode "cursor", don't work properly if width is not set in pixel, (TRUE or FALSE).
thickness	Gauge thickness, numeric value.
lineCap	Gauge stroke endings, 'default' or 'round'.
displayInput	Hide input in the middle of the knob (TRUE or FALSE).
displayPrevious	Display the previous value with transparency (TRUE or FALSE).
rotation	Direction of progression, 'clockwise' or 'anticlockwise'.
fgColor	Foreground color.

<code>inputColor</code>	Input value (number) color.
<code>bgColor</code>	Background color.
<code>pre</code>	A prefix string to put in front of the value.
<code>post</code>	A suffix string to put after the value.
<code>fontSize</code>	Font size, must be a valid CSS unit.
<code>readOnly</code>	Disable knob (TRUE or FALSE).
<code>skin</code>	Change Knob skin, only one option available : 'tron'.
<code>width, height</code>	The width and height of the input, e.g. 400px, or 100%. A value a pixel is recommended, otherwise the knob won't be able to initialize itself in some case (if hidden at start for example).
<code>immediate</code>	If TRUE (default), server-side value is updated each time value change, if FALSE value is updated when user release the widget.

Value

Numeric value server-side.

See Also

[updateKnobInput](#) for updating the value server-side.

Examples

```
if (interactive()) {

  library("shiny")
  library("shinyWidgets")

  ui <- fluidPage(
    knobInput(
      inputId = "myKnob",
      label = "Display previous:",
      value = 50,
      min = -100,
      displayPrevious = TRUE,
      fgColor = "#428BCA",
      inputColor = "#428BCA"
    ),
    verbatimTextOutput(outputId = "res")
  )

  server <- function(input, output, session) {

    output$res <- renderPrint(input$myKnob)

  }

  shinyApp(ui = ui, server = server)
}
```

materialSwitch	<i>Material Design Switch Input Control</i>
----------------	---

Description

A toggle switch to turn a selection on or off.

Usage

```
materialSwitch(  
  inputId,  
  label = NULL,  
  value = FALSE,  
  status = "default",  
  right = FALSE,  
  inline = FALSE,  
  width = NULL  
)
```

Arguments

inputId	The input slot that will be used to access the value.
label	Input label.
value	TRUE or FALSE.
status	Color, must be a valid Bootstrap status : default, primary, info, success, warning, danger.
right	Should the the label be on the right? default to FALSE.
inline	Display the input inline, if you want to place buttons next to each other.
width	The width of the input, e.g. '400px', or '100%'.

Value

A switch control that can be added to a UI definition.

See Also

[updateMaterialSwitch](#), [switchInput](#)

Examples

```
if (interactive()) {  
  library(shiny)  
  library(shinyWidgets)  
  
  ui <- fluidPage(  
    tags$h3("Material switch examples"),
```

```

    materialSwitch(inputId = "switch1", label = "Night mode"),
    verbatimTextOutput("value1"),

    materialSwitch(inputId = "switch2", label = "Night mode", status = "danger"),
    verbatimTextOutput("value2")
  )
  server <- function(input, output) {

    output$value1 <- renderText({ input$switch1 })

    output$value2 <- renderText({ input$switch2 })

  }
  shinyApp(ui, server)
}

```

multiInput

Create a multiselect input control

Description

A user-friendly replacement for select boxes with the multiple attribute

Usage

```

multiInput(
  inputId,
  label,
  choices = NULL,
  selected = NULL,
  options = NULL,
  width = NULL,
  choiceNames = NULL,
  choiceValues = NULL
)

```

Arguments

inputId	The input slot that will be used to access the value.
label	Display label for the control, or NULL for no label.
choices	List of values to select from.
selected	The initially selected value.
options	List of options passed to multi (enable_search = FALSE for disabling the search bar for example).
width	The width of the input, e.g. 400px, or 100%.
choiceNames	List of names to display to the user.
choiceValues	List of values corresponding to choiceNames.

Value

A multiselect control

See Also

[updateMultiInput](#) to update value server-side.

Examples

```
## Only run examples in interactive R sessions
if (interactive()) {

  library("shiny")
  library("shinyWidgets")

  # simple use

  ui <- fluidPage(
    multiInput(
      inputId = "id", label = "Fruits :",
      choices = c("Banana", "Blueberry", "Cherry",
                  "Coconut", "Grapefruit", "Kiwi",
                  "Lemon", "Lime", "Mango", "Orange",
                  "Papaya"),
      selected = "Banana", width = "350px"
    ),
    verbatimTextOutput(outputId = "res")
  )

  server <- function(input, output, session) {
    output$res <- renderPrint({
      input$id
    })
  }

  shinyApp(ui = ui, server = server)

  # with options

  ui <- fluidPage(
    multiInput(
      inputId = "id", label = "Fruits :",
      choices = c("Banana", "Blueberry", "Cherry",
                  "Coconut", "Grapefruit", "Kiwi",
                  "Lemon", "Lime", "Mango", "Orange",
                  "Papaya"),
      selected = "Banana", width = "400px",
      options = list(
        enable_search = FALSE,
        non_selected_header = "Choose between:",

```

```

        selected_header = "You have selected:"
      )
    ),
    verbatimTextOutput(outputId = "res")
  )

server <- function(input, output, session) {
  output$res <- renderPrint({
    input$id
  })
}

shinyApp(ui = ui, server = server)
}

```

noUiSliderInput

Numeric range slider

Description

A minimal numeric range slider with a lot of features.

Usage

```

noUiSliderInput(
  inputId,
  label = NULL,
  min,
  max,
  value,
  step = NULL,
  tooltips = TRUE,
  connect = TRUE,
  padding = 0,
  margin = NULL,
  limit = NULL,
  orientation = c("horizontal", "vertical"),
  direction = c("ltr", "rtl"),
  behaviour = "tap",
  range = NULL,
  pips = NULL,
  format = wNumbFormat(),
  update_on = c("end", "change"),
  color = NULL,
  inline = FALSE,
  width = NULL,
  height = NULL
)

```

Arguments

inputId	The input slot that will be used to access the value.
label	Display label for the control, or NULL for no label.
min	Minimal value that can be selected.
max	Maximal value that can be selected.
value	The initial value of the slider. as many cursors will be created as values provided.
step	numeric, by default, the slider slides fluently. In order to make the handles jump between intervals, you can use the step option.
tooltips	logical, display slider's value in a tooltip above slider.
connect	logical, vector of length value + 1, color slider between handle(s).
padding	numeric, padding limits how close to the slider edges handles can be.
margin	numeric, when using two handles, the minimum distance between the handles can be set using the margin option.
limit	numeric, the limit option is the opposite of the margin option, limiting the maximum distance between two handles.
orientation	The orientation setting can be used to set the slider to "vertical" or "horizontal".
direction	"ltr" or "rtl", By default the sliders are top-to-bottom and left-to-right, but you can change this using the direction option, which decides where the upper side of the slider is.
behaviour	Option to handle user interaction, a value or several between "drag", "tap", "fixed", "snap" or "none". See https://refreshless.com/nouislider/behaviour-option/ for more examples.
range	list, can be used to define non-linear sliders.
pips	list, used to generate points along the slider.
format	numbers format, see wNumbFormat .
update_on	When to send value to server: "end" (when slider is released) or "update" (each time value changes).
color	color in Hex format for the slider.
inline	If TRUE, it's possible to position sliders side-by-side.
width	The width of the input, e.g. 400px, or 100%.
height	The height of the input, e.g. 400px, or 100%.

Value

a ui definition

Note

See [updateNoUiSliderInput](#) for updating slider value server-side. And [demoNoUiSlider](#) for examples.

Examples

```
if (interactive()) {

  ### examples ----

  # see ?demoNoUiSlider
  demoNoUiSlider("more")

  ### basic usage ----

  library( shiny )
  library( shinyWidgets )

  ui <- fluidPage(

    tags$br(),

    noUiSliderInput(
      inputId = "noui1",
      min = 0, max = 100,
      value = 20
    ),
    verbatimTextOutput(outputId = "res1"),

    tags$br(),

    noUiSliderInput(
      inputId = "noui2", label = "Slider vertical:",
      min = 0, max = 1000, step = 50,
      value = c(100, 400), margin = 100,
      orientation = "vertical",
      width = "100px", height = "300px"
    ),
    verbatimTextOutput(outputId = "res2")

  )

  server <- function(input, output, session) {

    output$res1 <- renderPrint(input$noui1)
    output$res2 <- renderPrint(input$noui2)

  }

  shinyApp(ui, server)

}
```

numericInputIcon *Create a numeric input control with icon(s)*

Description

Extend form controls by adding text or icons before, after, or on both sides of a classic numericInput.

Usage

```
numericInputIcon(
  inputId,
  label,
  value,
  min = NULL,
  max = NULL,
  step = NULL,
  icon = NULL,
  size = NULL,
  help_text = NULL,
  width = NULL
)
```

Arguments

inputId	The input slot that will be used to access the value.
label	Display label for the control, or NULL for no label.
value	Initial value.
min	Minimum allowed value
max	Maximum allowed value
step	Interval to use when stepping between min and max
icon	An icon or a list, containing icons or text, to be displayed on the right or left of the numeric input.
size	Size of the input, default to NULL, can be "sm" (small) or "lg" (large).
help_text	Help text placed below the widget and only displayed if value entered by user is outside of min and max.
width	The width of the input, e.g. '400px', or '100%'; see validateCssUnit() .

Value

A numeric input control that can be added to a UI definition.

Examples

```

if (interactive()) {
  library(shiny)
  library(shinyWidgets)

  ui <- fluidPage(
    tags$h2("numericInputIcon examples"),
    fluidRow(
      column(
        width = 6,
        numericInputIcon(
          inputId = "ex1",
          label = "With an icon",
          value = 10,
          icon = icon("percent")
        ),
        verbatimTextOutput("res1"),
        numericInputIcon(
          inputId = "ex2",
          label = "With an icon (right)",
          value = 90,
          step = 10,
          icon = list(NULL, icon("percent"))
        ),
        verbatimTextOutput("res2"),
        numericInputIcon(
          inputId = "ex3",
          label = "With text",
          value = 50,
          icon = list("km/h")
        ),
        verbatimTextOutput("res3"),
        numericInputIcon(
          inputId = "ex4",
          label = "Both side",
          value = 10000,
          icon = list(icon("dollar"), ".00")
        ),
        verbatimTextOutput("res4"),
        numericInputIcon(
          inputId = "ex5",
          label = "Sizing",
          value = 10000,
          icon = list(icon("dollar"), ".00"),
          size = "lg"
        ),
        verbatimTextOutput("res5")
      )
    )
  )

  server <- function(input, output, session) {

```

```

    output$res1 <- renderPrint(input$ex1)
    output$res2 <- renderPrint(input$ex2)
    output$res3 <- renderPrint(input$ex3)
    output$res4 <- renderPrint(input$ex4)
    output$res5 <- renderPrint(input$ex5)

  }

  shinyApp(ui, server)
}

```

numericRangeInput *Numeric Range Input*

Description

Create an input group of numeric inputs that function as a range input.

Usage

```
numericRangeInput(inputId, label, value, width = NULL, separator = " to ")
```

Arguments

inputId	The input slot that will be used to access the value.
label	Display label for the control, or NULL for no label.
value	The initial value(s) for the range. A numeric vector of length one will be duplicated to represent the minimum and maximum of the range; a numeric vector of two or more will have its minimum and maximum set the minimum and maximum of the range.
width	The width of the input, e.g. '400px', or '100%'; see validateCssUnit() .
separator	String to display between the start and end input boxes.

Examples

```

if (interactive()) {

### examples ----

# see ?demoNumericRange
demoNumericRange()

### basic usage ----

library( shiny )
library( shinyWidgets )

```

```
ui <- fluidPage(  
  tags$br(),  
  numericRangeInput(  
    inputId = "noui1", label = "Numeric Range Input:",  
    value = c(100, 400)  
  ),  
  verbatimTextOutput(outputId = "res1")  
)  
  
server <- function(input, output, session) {  
  output$res1 <- renderPrint(input$noui1)  
}  
  
shinyApp(ui, server)  
  
}
```

pickerGroup-module *Picker Group*

Description

Group of mutually dependent [pickerInput](#) for filtering data.frame's columns.

Usage

```
pickerGroupUI(  
  id,  
  params,  
  label = NULL,  
  btn_label = "Reset filters",  
  options = list(),  
  inline = TRUE  
)  
  
pickerGroupServer(input, output, session, data, vars)
```

Arguments

id Module's id.

params	A named list of parameters passed to each <code>pickerInput</code> , you can use : 'inputId' (obligatory, must be variable name), 'label', 'placeholder'.
label	Character, global label on top of all labels.
btn_label	Character, reset button label.
options	See <code>pickerInput</code> options argument.
inline	If TRUE (the default), pickerInputs are horizontally positioned, otherwise vertically.
input	standard shiny input.
output	standard shiny output.
session	standard shiny session.
data	a <code>data.frame</code> , or an object that can be coerced to <code>data.frame</code> .
vars	character, columns to use to create filters, must correspond to variables listed in <code>params</code> .

Value

a reactive function containing data filtered.

Examples

```

if (interactive()) {

  library(shiny)
  library(shinyWidgets)

  data("mpg", package = "ggplot2")

  ui <- fluidPage(
    fluidRow(
      column(
        width = 10, offset = 1,
        tags$h3("Filter data with picker group"),
        panel(
          pickerGroupUI(
            id = "my-filters",
            params = list(
              manufacturer = list(inputId = "manufacturer", label = "Manufacturer:"),
              model = list(inputId = "model", label = "Model:"),
              trans = list(inputId = "trans", label = "Trans:"),
              class = list(inputId = "class", label = "Class:")
            )
          ), status = "primary"
        ),
      ),
      DT::dataTableOutput(outputId = "table")
    )
  )
}

```

```

server <- function(input, output, session) {
  res_mod <- callModule(
    module = pickerGroupServer,
    id = "my-filters",
    data = mpg,
    vars = c("manufacturer", "model", "trans", "class")
  )
  output$table <- DT::renderDataTable(res_mod())
}

shinyApp(ui, server)

}

### Not inline example

if (interactive()) {

  library(shiny)
  library(shinyWidgets)

  data("mpg", package = "ggplot2")

  ui <- fluidPage(
    fluidRow(
      column(
        width = 4,
        tags$h3("Filter data with picker group"),
        pickerGroupUI(
          id = "my-filters",
          inline = FALSE,
          params = list(
            manufacturer = list(inputId = "manufacturer", label = "Manufacturer:"),
            model = list(inputId = "model", label = "Model:"),
            trans = list(inputId = "trans", label = "Trans:"),
            class = list(inputId = "class", label = "Class:")
          )
        )
      ),
      column(
        width = 8,
        DT::dataTableOutput(outputId = "table")
      )
    )
  )

  server <- function(input, output, session) {
    res_mod <- callModule(
      module = pickerGroupServer,

```

```

      id = "my-filters",
      data = mpg,
      vars = c("manufacturer", "model", "trans", "class")
    )
    output$table <- DT::renderDataTable(res_mod())
  }

  shinyApp(ui, server)
}

```

 pickerInput

Select Picker Input Control

Description

An alternative to selectInput with plenty of options to customize it.

Usage

```

pickerInput(
  inputId,
  label = NULL,
  choices,
  selected = NULL,
  multiple = FALSE,
  options = list(),
  choicesOpt = NULL,
  width = NULL,
  inline = FALSE
)

```

Arguments

inputId	The input slot that will be used to access the value.
label	Display label for the control, or NULL for no label.
choices	List of values to select from. If elements of the list are named then that name rather than the value is displayed to the user.
selected	The initially selected value (or multiple values if multiple = TRUE). If not specified then defaults to the first value for single-select lists and no values for multiple select lists.
multiple	Is selection of multiple items allowed?
options	List of options, see pickerOptions for all available options. To limit the number of selection possible, see example below.
choicesOpt	Options for choices in the dropdown menu.
width	The width of the input : 'auto', 'fit', '100px', '75%'.
inline	Display picker inline, to have label and menu on same line use width = "fit".

Value

A select control that can be added to a UI definition.

References

SnapAppointments and contributors. "The jQuery plugin that brings select elements into the 21st century with intuitive multiselection, searching, and much more. Now with Bootstrap 4 support". <https://github.com/snapappointments/bootstrap-select/>

See Also

[updatePickerInput](#) to update value server-side.

Examples

```
## Only run examples in interactive R sessions
if (interactive()) {

# You can run the gallery to see other examples
shinyWidgetsGallery()

# Basic usage
library("shiny")
library(shinyWidgets)

ui <- fluidPage(
  pickerInput(
    inputId = "somevalue",
    label = "A label",
    choices = c("a", "b")
  ),
  verbatimTextOutput("value")
)

server <- function(input, output) {
  output$value <- renderPrint(input$somevalue)
}

shinyApp(ui, server)

}

### Add actions box for selecting ----
### deselecting all options

if (interactive()) {

  library(shiny)
  library(shinyWidgets)

  ui <- fluidPage(
```

```

tags$h2("Select / Deselect all"),
pickerInput(
  inputId = "p1",
  label = "Select all option",
  choices = rownames(mtcars),
  multiple = TRUE,
  options = list(`actions-box` = TRUE)
),
verbatimTextOutput("r1"),
br(),
pickerInput(
  inputId = "p2",
  label = "Select all option / custom text",
  choices = rownames(mtcars),
  multiple = TRUE,
  options = list(
    `actions-box` = TRUE,
    `deselect-all-text` = "None...",
    `select-all-text` = "Yeah, all !",
    `none-selected-text` = "zero"
  )
),
verbatimTextOutput("r2")
)

server <- function(input, output, session) {

  output$r1 <- renderPrint(input$p1)
  output$r2 <- renderPrint(input$p2)

}

shinyApp(ui = ui, server = server)

}

### Customize the values displayed in the box ----

if (interactive()) {

  library(shiny)
  library(shinyWidgets)

  ui <- fluidPage(
    br(),
    pickerInput(
      inputId = "p1",
      label = "Default",
      multiple = TRUE,
      choices = rownames(mtcars),
      selected = rownames(mtcars)[1:5]
    ),
    br(),

```

```

pickerInput(
  inputId = "p1b",
  label = "Default with | separator",
  multiple = TRUE,
  choices = rownames(mtcars),
  selected = rownames(mtcars)[1:5],
  options = list(`multiple-separator` = " | ")
),
br(),
pickerInput(
  inputId = "p2",
  label = "Static",
  multiple = TRUE,
  choices = rownames(mtcars),
  selected = rownames(mtcars)[1:5],
  options = list(`selected-text-format` = "static",
                 title = "Won't change")
),
br(),
pickerInput(
  inputId = "p3",
  label = "Count",
  multiple = TRUE,
  choices = rownames(mtcars),
  selected = rownames(mtcars)[1:5],
  options = list(`selected-text-format` = "count")
),
br(),
pickerInput(
  inputId = "p3",
  label = "Customize count",
  multiple = TRUE,
  choices = rownames(mtcars),
  selected = rownames(mtcars)[1:5],
  options = list(
    `selected-text-format` = "count",
    `count-selected-text` = "{0} models choosed (on a total of {1})"
  )
)
)
)

server <- function(input, output, session) {

}

shinyApp(ui = ui, server = server)

}

### Limit the number of selections ----

if (interactive()) {

```

```
library(shiny)
library(shinyWidgets)

ui <- fluidPage(
  pickerInput(
    inputId = "groups",
    label = "Select one from each group below:",
    choices = list(
      Group1 = c("1", "2", "3", "4"),
      Group2 = c("A", "B", "C", "D")
    ),
    multiple = TRUE,
    options = list("max-options-group" = 1)
  ),
  verbatimTextOutput(outputId = "res_grp"),
  pickerInput(
    inputId = "groups_2",
    label = "Select two from each group below:",
    choices = list(
      Group1 = c("1", "2", "3", "4"),
      Group2 = c("A", "B", "C", "D")
    ),
    multiple = TRUE,
    options = list("max-options-group" = 2)
  ),
  verbatimTextOutput(outputId = "res_grp_2"),
  pickerInput(
    inputId = "classic",
    label = "Select max two option below:",
    choices = c("A", "B", "C", "D"),
    multiple = TRUE,
    options = list(
      "max-options" = 2,
      "max-options-text" = "No more!"
    )
  ),
  verbatimTextOutput(outputId = "res_classic")
)

server <- function(input, output) {

  output$res_grp <- renderPrint(input$groups)
  output$res_grp_2 <- renderPrint(input$groups_2)
  output$res_classic <- renderPrint(input$classic)

}

shinyApp(ui, server)
}
```

`pickerOptions`*Options for 'pickerInput'*

Description

Wrapper of options available here: <https://developer.snapappointments.com/bootstrap-select/options/>

Usage

```
pickerOptions(  
  actionsBox = NULL,  
  container = NULL,  
  countSelectedText = NULL,  
  deselectAllText = NULL,  
  dropdownAlignRight = NULL,  
  dropupAuto = NULL,  
  header = NULL,  
  hideDisabled = NULL,  
  iconBase = NULL,  
  liveSearch = NULL,  
  liveSearchNormalize = NULL,  
  liveSearchPlaceholder = NULL,  
  liveSearchStyle = NULL,  
  maxOptions = NULL,  
  maxOptionsText = NULL,  
  mobile = NULL,  
  multipleSeparator = NULL,  
  noneSelectedText = NULL,  
  noneResultsText = NULL,  
  selectAllText = NULL,  
  selectedTextFormat = NULL,  
  selectOnTab = NULL,  
  showContent = NULL,  
  showIcon = NULL,  
  showSubtext = NULL,  
  showTick = NULL,  
  size = NULL,  
  style = NULL,  
  tickIcon = NULL,  
  title = NULL,  
  virtualScroll = NULL,  
  width = NULL,  
  windowPadding = NULL,  
  ...  
)
```

Arguments

actionsBox	When set to true, adds two buttons to the top of the dropdown menu (Select All & Deselect All). Type: boolean; Default: false.
container	When set to a string, appends the select to a specific element or selector, e.g., container: 'body' '.main-body' Type: string false; Default: false.
countSelectedText	Sets the format for the text displayed when selectedTextFormat is count or count > #. 0 is the selected amount. 1 is total available for selection. When set to a function, the first parameter is the number of selected options, and the second is the total number of options. The function must return a string. Type: string function; Default: function.
deselectAllText	The text on the button that deselects all options when actionsBox is enabled. Type: string; Default: 'Deselect All'.
dropdownAlignRight	Align the menu to the right instead of the left. If set to 'auto', the menu will automatically align right if there isn't room for the menu's full width when aligned to the left. Type: boolean 'auto'; Default: false.
dropupAuto	checks to see which has more room, above or below. If the dropup has enough room to fully open normally, but there is more room above, the dropup still opens normally. Otherwise, it becomes a dropup. If dropupAuto is set to false, dropups must be called manually. Type: boolean; Default: true.
header	adds a header to the top of the menu; includes a close button by default Type: string; Default: false.
hideDisabled	removes disabled options and optgroups from the menu data-hide-disabled: true Type: boolean; Default: false.
iconBase	Set the base to use a different icon font instead of Glyphicons. If changing iconBase, you might also want to change tickIcon, in case the new icon font uses a different naming scheme. Type: string; Default: 'glyphicon'.
liveSearch	When set to true, adds a search box to the top of the selectpicker dropdown. Type: boolean; Default: false.
liveSearchNormalize	Setting liveSearchNormalize to true allows for accent-insensitive searching. Type: boolean; Default: false.
liveSearchPlaceholder	When set to a string, a placeholder attribute equal to the string will be added to the liveSearch input. Type: string; Default: null.
liveSearchStyle	When set to 'contains', searching will reveal options that contain the searched text. For example, searching for pl will return both Apple, Plum, and Plantain. When set to 'startsWith', searching for pl will return only Plum and Plantain. Type: string; Default: 'contains'.
maxOptions	When set to an integer and in a multi-select, the number of selected options cannot exceed the given value. This option can also exist as a data-attribute for an <optgroup>, in which case it only applies to that <optgroup>. Type: integer false; Default: false.

<code>maxOptionsText</code>	The text that is displayed when <code>maxOptions</code> is enabled and the maximum number of options for the given scenario have been selected. If a function is used, it must return an array. <code>array[0]</code> is the text used when <code>maxOptions</code> is applied to the entire select element. <code>array[1]</code> is the text used when <code>maxOptions</code> is used on an <code>optgroup</code> . If a string is used, the same text is used for both the element and the <code>optgroup</code> . Type: <code>string array function</code> ; Default: <code>function</code> .
<code>mobile</code>	When set to true, enables the device's native menu for select menus. Type: <code>boolean</code> ; Default: <code>false</code> .
<code>multipleSeparator</code>	Set the character displayed in the button that separates selected options. Type: <code>string</code> ; Default: <code>' , '</code> .
<code>noneSelectedText</code>	The text that is displayed when a multiple select has no selected options. Type: <code>string</code> ; Default: <code>'Nothing selected'</code> .
<code>noneResultsText</code>	The text displayed when a search doesn't return any results. Type: <code>string</code> ; Default: <code>'No results matched 0'</code> .
<code>selectAllText</code>	The text on the button that selects all options when <code>actionsBox</code> is enabled. Type: <code>string</code> ; Default: <code>'Select All'</code> .
<code>selectedTextFormat</code>	Specifies how the selection is displayed with a multiple select. <code>'values'</code> displays a list of the selected options (separated by <code>multipleSeparator</code>). <code>'static'</code> simply displays the select element's title. <code>'count'</code> displays the total number of selected options. <code>'count > x'</code> behaves like <code>'values'</code> until the number of selected options is greater than <code>x</code> ; after that, it behaves like <code>'count'</code> . Type: <code>'values' 'static' 'count' 'count > x'</code> (where <code>x</code> is an integer); Default: <code>'values'</code> .
<code>selectOnTab</code>	When set to true, treats the tab character like the enter or space characters within the selectpicker dropdown. Type: <code>boolean</code> ; Default: <code>false</code> .
<code>showContent</code>	When set to true, display custom HTML associated with selected option(s) in the button. When set to false, the option value will be displayed instead. Type: <code>boolean</code> ; Default: <code>true</code> .
<code>showIcon</code>	When set to true, display icon(s) associated with selected option(s) in the button. Type: <code>boolean</code> ; Default: <code>true</code> .
<code>showSubtext</code>	When set to true, display subtext associated with a selected option in the button. Type: <code>boolean</code> ; Default: <code>false</code> .
<code>showTick</code>	Show checkmark on selected option (for items without multiple attribute). Type: <code>boolean</code> ; Default: <code>false</code> .
<code>size</code>	When set to <code>'auto'</code> , the menu always opens up to show as many items as the window will allow without being cut off. When set to an integer, the menu will show the given number of items, even if the dropdown is cut off. When set to false, the menu will always show all items. Type: <code>'auto' integer false</code> ; Default: <code>'auto'</code> .
<code>style</code>	When set to a string, add the value to the button's style. Type: <code>string null</code> ; Default: <code>null</code> .

tickIcon	Set which icon to use to display as the "tick" next to selected options. Type: string; Default: 'glyphicon-ok'.
title	The default title for the selectpicker. Type: string null; Default: null.
virtualScroll	If enabled, the items in the dropdown will be rendered using virtualization (i.e. only the items that are within the viewport will be rendered). This drastically improves performance for selects with a large number of options. Set to an integer to only use virtualization if the select has at least that number of options. Type: boolean integer; Default: 600.
width	When set to auto, the width of the selectpicker is automatically adjusted to accommodate the widest option. When set to a css-width, the width of the selectpicker is forced inline to the given value. When set to false, all width information is removed. Type: 'auto' 'fit' css-width false (where css-width is a CSS width with units, e.g. 100px); Default: false.
windowPadding	This is useful in cases where the window has areas that the dropdown menu should not cover - for instance a fixed header. When set to an integer, the same padding will be added to all sides. Alternatively, an array of integers can be used in the format [top, right, bottom, left]. Type: integer array; Default: 0.
...	Other options not listed here.

Note

Documentation is from Bootstrap-select page (<https://developer.snapappointments.com/bootstrap-select/options/>).

Examples

```

if (interactive()) {
  library(shiny)
  library(shinyWidgets)

  ui <- fluidPage(
    pickerInput(
      inputId = "month",
      label = "Select a month",
      choices = month.name,
      multiple = TRUE,
      options = pickerOptions(
        actionsBox = TRUE,
        title = "Please select a month",
        header = "This is a title"
      )
    )
  )
}

server <- function(input, output, session) {
}

```

```

    shinyApp(ui, server)
  }

```

prettyCheckbox

Pretty Checkbox Input

Description

Create a pretty checkbox that can be used to specify logical values.

Usage

```

prettyCheckbox(
  inputId,
  label,
  value = FALSE,
  status = "default",
  shape = c("square", "curve", "round"),
  outline = FALSE,
  fill = FALSE,
  thick = FALSE,
  animation = NULL,
  icon = NULL,
  plain = FALSE,
  bigger = FALSE,
  inline = FALSE,
  width = NULL
)

```

Arguments

inputId	The input slot that will be used to access the value.
label	Display label for the control.
value	Initial value (TRUE or FALSE).
status	Add a class to the checkbox, you can use Bootstrap status like 'info', 'primary', 'danger', 'warning' or 'success'.
shape	Shape of the checkbox between square, curve and round.
outline	Color also the border of the checkbox (TRUE or FALSE).
fill	Fill the checkbox with color (TRUE or FALSE).
thick	Make the content inside checkbox smaller (TRUE or FALSE).
animation	Add an animation when checkbox is checked, a value between smooth, jelly, tada, rotate, pulse.
icon	Optional, display an icon on the checkbox, must be an icon created with icon.

plain	Remove the border when checkbox is checked (TRUE or FALSE).
bigger	Scale the checkboxes a bit bigger (TRUE or FALSE).
inline	Display the input inline, if you want to place checkboxes next to each other.
width	The width of the input, e.g. 400px, or 100%.

Value

TRUE or FALSE server-side.

Note

Due to the nature of different checkbox design, certain animations are not applicable in some arguments combinations. You can find examples on the pretty-checkbox official page : <https://lokesh-coder.github.io/pretty-checkbox/>.

See Also

See [updatePrettyCheckbox](#) to update the value server-side. See [prettySwitch](#) and [prettyToggle](#) for similar widgets.

Examples

```
library(shiny)
library(shinyWidgets)

ui <- fluidPage(
  tags$h1("Pretty checkbox"),
  br(),

  fluidRow(
    column(
      width = 4,
      prettyCheckbox(
        inputId = "checkbox1",
        label = "Click me!"
      ),
      verbatimTextOutput(outputId = "res1"),
      br(),
      prettyCheckbox(
        inputId = "checkbox4",
        label = "Click me!",
        outline = TRUE,
        plain = TRUE,
        icon = icon("thumbs-up")
      ),
      verbatimTextOutput(outputId = "res4")
    ),
    column(
      width = 4,
      prettyCheckbox(
        inputId = "checkbox2",
```

```

      label = "Click me!",
      thick = TRUE,
      animation = "pulse",
      status = "info"
    ),
    verbatimTextOutput(outputId = "res2"),
    br(),
    prettyCheckbox(
      inputId = "checkbox5",
      label = "Click me!",
      icon = icon("check"),
      animation = "tada",
      status = "default"
    ),
    verbatimTextOutput(outputId = "res5")
  ),
  column(
    width = 4,
    prettyCheckbox(
      inputId = "checkbox3",
      label = "Click me!",
      shape = "round",
      status = "danger",
      fill = TRUE,
      value = TRUE
    ),
    verbatimTextOutput(outputId = "res3")
  )
)
)

server <- function(input, output, session) {

  output$res1 <- renderPrint(input$checkbox1)
  output$res2 <- renderPrint(input$checkbox2)
  output$res3 <- renderPrint(input$checkbox3)
  output$res4 <- renderPrint(input$checkbox4)
  output$res5 <- renderPrint(input$checkbox5)

}

if (interactive())
  shinyApp(ui, server)

# Inline example ----

ui <- fluidPage(
  tags$h1("Pretty checkbox: inline example"),
  br(),

```

```
prettyCheckbox(  
  inputId = "checkbox1",  
  label = "Click me!",  
  status = "success",  
  outline = TRUE,  
  inline = TRUE  
)  
prettyCheckbox(  
  inputId = "checkbox2",  
  label = "Click me!",  
  thick = TRUE,  
  shape = "curve",  
  animation = "pulse",  
  status = "info",  
  inline = TRUE  
)  
prettyCheckbox(  
  inputId = "checkbox3",  
  label = "Click me!",  
  shape = "round",  
  status = "danger",  
  value = TRUE,  
  inline = TRUE  
)  
prettyCheckbox(  
  inputId = "checkbox4",  
  label = "Click me!",  
  outline = TRUE,  
  plain = TRUE,  
  animation = "rotate",  
  icon = icon("thumbs-up"),  
  inline = TRUE  
)  
prettyCheckbox(  
  inputId = "checkbox5",  
  label = "Click me!",  
  icon = icon("check"),  
  animation = "tada",  
  status = "primary",  
  inline = TRUE  
)  
verbatimTextOutput(outputId = "res")  
)  
  
server <- function(input, output, session) {  
  
  output$res <- renderPrint(  
    c(input$checkbox1,  
      input$checkbox2,  
      input$checkbox3,  
      input$checkbox4,  
      input$checkbox5)  
  )  
}
```

```

}

if (interactive())
  shinyApp(ui, server)

```

```
prettyCheckboxGroup Pretty Checkbox Group Input Control
```

Description

Create a group of pretty checkboxes that can be used to toggle multiple choices independently. The server will receive the input as a character vector of the selected values.

Usage

```

prettyCheckboxGroup(
  inputId,
  label,
  choices = NULL,
  selected = NULL,
  status = "default",
  shape = c("square", "curve", "round"),
  outline = FALSE,
  fill = FALSE,
  thick = FALSE,
  animation = NULL,
  icon = NULL,
  plain = FALSE,
  bigger = FALSE,
  inline = FALSE,
  width = NULL,
  choiceNames = NULL,
  choiceValues = NULL
)

```

Arguments

inputId	The input slot that will be used to access the value.
label	Display label for the control.
choices	List of values to show checkboxes for. If elements of the list are named then that name rather than the value is displayed to the user. If this argument is provided, then choiceNames and choiceValues must not be provided, and vice-versa. The values should be strings; other types (such as logicals and numbers) will be coerced to strings.
selected	The values that should be initially selected, if any.

status	Add a class to the checkbox, you can use Bootstrap status like 'info', 'primary', 'danger', 'warning' or 'success'.
shape	Shape of the checkbox between square, curve and round.
outline	Color also the border of the checkbox (TRUE or FALSE).
fill	Fill the checkbox with color (TRUE or FALSE).
thick	Make the content inside checkbox smaller (TRUE or FALSE).
animation	Add an animation when checkbox is checked, a value between smooth, jelly, tada, rotate, pulse.
icon	Optional, display an icon on the checkbox, must be an icon created with icon.
plain	Remove the border when checkbox is checked (TRUE or FALSE).
bigger	Scale the checkboxes a bit bigger (TRUE or FALSE).
inline	If TRUE, render the choices inline (i.e. horizontally).
width	The width of the input, e.g. 400px, or 100%.
choiceNames	List of names to display to the user.
choiceValues	List of values corresponding to choiceNames

Value

A character vector or NULL server-side.

See Also

[updatePrettyCheckboxGroup](#) for updating values server-side.

Examples

```
library(shiny)
library(shinyWidgets)

ui <- fluidPage(
  tags$h1("Pretty checkbox group"),
  br(),

  fluidRow(
    column(
      width = 4,
      prettyCheckboxGroup(
        inputId = "checkgroup1",
        label = "Click me!",
        choices = c("Click me !", "Me !", "Or me !")
      ),
      verbatimTextOutput(outputId = "res1"),
      br(),
      prettyCheckboxGroup(
        inputId = "checkgroup4",
        label = "Click me!",
        choices = c("Click me !", "Me !", "Or me !"),
```

```

        outline = TRUE,
        plain = TRUE,
        icon = icon("thumbs-up")
      ),
      verbatimTextOutput(outputId = "res4")
    ),
    column(
      width = 4,
      prettyCheckboxGroup(
        inputId = "checkgroup2",
        label = "Click me!",
        thick = TRUE,
        choices = c("Click me !", "Me !", "Or me !"),
        animation = "pulse",
        status = "info"
      ),
      verbatimTextOutput(outputId = "res2"),
      br(),
      prettyCheckboxGroup(
        inputId = "checkgroup5",
        label = "Click me!",
        icon = icon("check"),
        choices = c("Click me !", "Me !", "Or me !"),
        animation = "tada",
        status = "default"
      ),
      verbatimTextOutput(outputId = "res5")
    ),
    column(
      width = 4,
      prettyCheckboxGroup(
        inputId = "checkgroup3",
        label = "Click me!",
        choices = c("Click me !", "Me !", "Or me !"),
        shape = "round",
        status = "danger",
        fill = TRUE,
        inline = TRUE
      ),
      verbatimTextOutput(outputId = "res3")
    )
  )
)

server <- function(input, output, session) {

  output$res1 <- renderPrint(input$checkgroup1)
  output$res2 <- renderPrint(input$checkgroup2)
  output$res3 <- renderPrint(input$checkgroup3)
  output$res4 <- renderPrint(input$checkgroup4)
  output$res5 <- renderPrint(input$checkgroup5)
}

```

```
}  
  
if (interactive())  
  shinyApp(ui, server)
```

prettyRadioButtons *Pretty radio Buttons Input Control*

Description

Create a set of radio buttons used to select an item from a list.

Usage

```
prettyRadioButtons(  
  inputId,  
  label,  
  choices = NULL,  
  selected = NULL,  
  status = "primary",  
  shape = c("round", "square", "curve"),  
  outline = FALSE,  
  fill = FALSE,  
  thick = FALSE,  
  animation = NULL,  
  icon = NULL,  
  plain = FALSE,  
  bigger = FALSE,  
  inline = FALSE,  
  width = NULL,  
  choiceNames = NULL,  
  choiceValues = NULL  
)
```

Arguments

inputId	The input slot that will be used to access the value.
label	Display label for the control.
choices	List of values to show radio buttons for. If elements of the list are named then that name rather than the value is displayed to the user. If this argument is provided, then choiceNames and choiceValues must not be provided, and vice-versa. The values should be strings; other types (such as logicals and numbers) will be coerced to strings.
selected	The values that should be initially selected, (if not specified then defaults to the first value).

<code>status</code>	Add a class to the radio, you can use Bootstrap status like 'info', 'primary', 'danger', 'warning' or 'success'.
<code>shape</code>	Shape of the radio between square, curve and round.
<code>outline</code>	Color also the border of the radio (TRUE or FALSE).
<code>fill</code>	Fill the radio with color (TRUE or FALSE).
<code>thick</code>	Make the content inside radio smaller (TRUE or FALSE).
<code>animation</code>	Add an animation when radio is checked, a value between smooth, jelly, tada, rotate, pulse.
<code>icon</code>	Optional, display an icon on the radio, must be an icon created with icon.
<code>plain</code>	Remove the border when radio is checked (TRUE or FALSE).
<code>bigger</code>	Scale the radio a bit bigger (TRUE or FALSE).
<code>inline</code>	If TRUE, render the choices inline (i.e. horizontally).
<code>width</code>	The width of the input, e.g. 400px, or 100%.
<code>choiceNames</code>	List of names to display to the user.
<code>choiceValues</code>	List of values corresponding to choiceNames

Value

A character vector or NULL server-side.

Examples

```
library(shiny)
library(shinyWidgets)

ui <- fluidPage(
  tags$h1("Pretty radio buttons"),
  br(),

  fluidRow(
    column(
      width = 4,
      prettyRadioButtons(
        inputId = "radio1",
        label = "Click me!",
        choices = c("Click me !", "Me !", "Or me !")
      ),
      verbatimTextOutput(outputId = "res1"),
      br(),
      prettyRadioButtons(
        inputId = "radio4",
        label = "Click me!",
        choices = c("Click me !", "Me !", "Or me !"),
        outline = TRUE,
        plain = TRUE,
        icon = icon("thumbs-up")
      ),
    ),
```

```

      verbatimTextOutput(outputId = "res4")
    ),
    column(
      width = 4,
      prettyRadioButtons(
        inputId = "radio2",
        label = "Click me!",
        thick = TRUE,
        choices = c("Click me !", "Me !", "Or me !"),
        animation = "pulse",
        status = "info"
      ),
      verbatimTextOutput(outputId = "res2"),
      br(),
      prettyRadioButtons(
        inputId = "radio5",
        label = "Click me!",
        icon = icon("check"),
        choices = c("Click me !", "Me !", "Or me !"),
        animation = "tada",
        status = "default"
      ),
      verbatimTextOutput(outputId = "res5")
    ),
    column(
      width = 4,
      prettyRadioButtons(
        inputId = "radio3",
        label = "Click me!",
        choices = c("Click me !", "Me !", "Or me !"),
        shape = "round",
        status = "danger",
        fill = TRUE,
        inline = TRUE
      ),
      verbatimTextOutput(outputId = "res3")
    )
  )
)

server <- function(input, output, session) {

  output$res1 <- renderPrint(input$radio1)
  output$res2 <- renderPrint(input$radio2)
  output$res3 <- renderPrint(input$radio3)
  output$res4 <- renderPrint(input$radio4)
  output$res5 <- renderPrint(input$radio5)

}

if (interactive())
  shinyApp(ui, server)

```

prettySwitch

Pretty Switch Input

Description

A toggle switch to replace checkbox

Usage

```
prettySwitch(  
  inputId,  
  label,  
  value = FALSE,  
  status = "default",  
  slim = FALSE,  
  fill = FALSE,  
  bigger = FALSE,  
  inline = FALSE,  
  width = NULL  
)
```

Arguments

inputId	The input slot that will be used to access the value.
label	Display label for the control, or NULL for no label.
value	Initial value (TRUE or FALSE).
status	Add a class to the switch, you can use Bootstrap status like 'info', 'primary', 'danger', 'warning' or 'success'.
slim	Change the style of the switch (TRUE or FALSE), see examples.
fill	Change the style of the switch (TRUE or FALSE), see examples.
bigger	Scale the switch a bit bigger (TRUE or FALSE).
inline	Display the input inline, if you want to place switch next to each other.
width	The width of the input, e.g. 400px, or 100%.

Value

TRUE or FALSE server-side.

Note

Appearance is better in a browser such as Chrome than in RStudio Viewer

See Also

See [updatePrettySwitch](#) to update the value server-side.

Examples

```

library(shiny)
library(shinyWidgets)

ui <- fluidPage(
  tags$h1("Pretty switches"),
  br(),

  fluidRow(
    column(
      width = 4,
      prettySwitch(inputId = "switch1", label = "Default:"),
      verbatimTextOutput(outputId = "res1"),
      br(),
      prettySwitch(
        inputId = "switch4",
        label = "Fill switch with status:",
        fill = TRUE, status = "primary"
      ),
      verbatimTextOutput(outputId = "res4")
    ),
    column(
      width = 4,
      prettySwitch(
        inputId = "switch2",
        label = "Danger status:",
        status = "danger"
      ),
      verbatimTextOutput(outputId = "res2")
    ),
    column(
      width = 4,
      prettySwitch(
        inputId = "switch3",
        label = "Slim switch:",
        slim = TRUE
      ),
      verbatimTextOutput(outputId = "res3")
    )
  )
)

server <- function(input, output, session) {

  output$res1 <- renderPrint(input$switch1)
  output$res2 <- renderPrint(input$switch2)
  output$res3 <- renderPrint(input$switch3)
  output$res4 <- renderPrint(input$switch4)

}

```

```
if (interactive())
  shinyApp(ui, server)
```

```
prettyToggle
```

```
Pretty Toggle Input
```

Description

A single checkbox that changes appearance if checked or not.

Usage

```
prettyToggle(
  inputId,
  label_on,
  label_off,
  icon_on = NULL,
  icon_off = NULL,
  value = FALSE,
  status_on = "success",
  status_off = "danger",
  shape = c("square", "curve", "round"),
  outline = FALSE,
  fill = FALSE,
  thick = FALSE,
  plain = FALSE,
  bigger = FALSE,
  animation = NULL,
  inline = FALSE,
  width = NULL
)
```

Arguments

<code>inputId</code>	The input slot that will be used to access the value.
<code>label_on</code>	Display label for the control when value is TRUE.
<code>label_off</code>	Display label for the control when value is FALSE
<code>icon_on</code>	Optional, display an icon on the checkbox when value is TRUE, must be an icon created with <code>icon</code> .
<code>icon_off</code>	Optional, display an icon on the checkbox when value is FALSE, must be an icon created with <code>icon</code> .
<code>value</code>	Initial value (TRUE or FALSE).
<code>status_on</code>	Add a class to the checkbox when value is TRUE, you can use Bootstrap status like 'info', 'primary', 'danger', 'warning' or 'success'.

status_off	Add a class to the checkbox when value is FALSE, you can use Bootstrap status like 'info', 'primary', 'danger', 'warning' or 'success'.
shape	Shape of the checkbox between square, curve and round.
outline	Color also the border of the checkbox (TRUE or FALSE).
fill	Fill the checkbox with color (TRUE or FALSE).
thick	Make the content inside checkbox smaller (TRUE or FALSE).
plain	Remove the border when checkbox is checked (TRUE or FALSE).
bigger	Scale the checkboxes a bit bigger (TRUE or FALSE).
animation	Add an animation when checkbox is checked, a value between smooth, jelly, tada, rotate, pulse.
inline	Display the input inline, if you want to place checkboxes next to each other.
width	The width of the input, e.g. 400px, or 100%.

Value

TRUE or FALSE server-side.

See Also

See [updatePrettyToggle](#) to update the value server-side.

Examples

```
library(shiny)
library(shinyWidgets)

ui <- fluidPage(
  tags$h1("Pretty toggles"),
  br(),

  fluidRow(
    column(
      width = 4,
      prettyToggle(
        inputId = "toggle1",
        label_on = "Checked!",
        label_off = "Unchecked..."
      ),
      verbatimTextOutput(outputId = "res1"),
      br(),
      prettyToggle(
        inputId = "toggle4", label_on = "Yes!",
        label_off = "No..", outline = TRUE,
        plain = TRUE,
        icon_on = icon("thumbs-up"),
        icon_off = icon("thumbs-down")
      ),
      verbatimTextOutput(outputId = "res4")
    ),
  ),
```

```

column(
  width = 4,
  prettyToggle(
    inputId = "toggle2",
    label_on = "Yes!", icon_on = icon("check"),
    status_on = "info", status_off = "warning",
    label_off = "No..", icon_off = icon("remove")
  ),
  verbatimTextOutput(outputId = "res2")
),
column(
  width = 4,
  prettyToggle(
    inputId = "toggle3", label_on = "Yes!",
    label_off = "No..", shape = "round",
    fill = TRUE, value = TRUE
  ),
  verbatimTextOutput(outputId = "res3")
)
)
)

server <- function(input, output, session) {

  output$res1 <- renderPrint(input$toggle1)
  output$res2 <- renderPrint(input$toggle2)
  output$res3 <- renderPrint(input$toggle3)
  output$res4 <- renderPrint(input$toggle4)

}

if (interactive())
  shinyApp(ui, server)

# Inline example ----

ui <- fluidPage(
  tags$h1("Pretty toggles: inline example"),
  br(),

  prettyToggle(
    inputId = "toggle1",
    label_on = "Checked!",
    label_off = "Unchecked...",
    inline = TRUE
  ),
  prettyToggle(
    inputId = "toggle2",
    label_on = "Yep",

```

```

      status_on = "default",
      icon_on = icon("ok-circle", lib = "glyphicon"),
      label_off = "Nope",
      status_off = "default",
      icon_off = icon("remove-circle", lib = "glyphicon"),
      plain = TRUE,
      inline = TRUE
    ),
    prettyToggle(
      inputId = "toggle3",
      label_on = "",
      label_off = "",
      icon_on = icon("volume-up", lib = "glyphicon"),
      icon_off = icon("volume-off", lib = "glyphicon"),
      status_on = "primary",
      status_off = "default",
      plain = TRUE,
      outline = TRUE,
      bigger = TRUE,
      inline = TRUE
    ),
    prettyToggle(
      inputId = "toggle4",
      label_on = "Yes!",
      label_off = "No..",
      outline = TRUE,
      plain = TRUE,
      icon_on = icon("thumbs-up"),
      icon_off = icon("thumbs-down"),
      inline = TRUE
    ),

    verbatimTextOutput(outputId = "res")

  )

server <- function(input, output, session) {

  output$res <- renderPrint(
    c(input$toggle1,
      input$toggle2,
      input$toggle3,
      input$toggle4)
  )

}

if (interactive())
  shinyApp(ui, server)

```

Description

Create a progress bar to provide feedback on calculation.

Usage

```
progressBar(
  id,
  value,
  total = NULL,
  display_pct = FALSE,
  size = NULL,
  status = NULL,
  striped = FALSE,
  title = NULL,
  range_value = NULL,
  unit_mark = "%"
)
```

```
updateProgressBar(
  session,
  id,
  value,
  total = NULL,
  title = NULL,
  status = NULL,
  range_value = NULL,
  unit_mark = "%"
)
```

Arguments

<code>id</code>	An id used to update the progress bar. If in a Shiny module, it use same logic than inputs : use namespace in UI, not in server.
<code>value</code>	Value of the progress bar between 0 and 100, if >100 you must provide total.
<code>total</code>	Used to calculate percentage if value > 100, force an indicator to appear on top right of the progress bar.
<code>display_pct</code>	logical, display percentage on the progress bar.
<code>size</code>	Size, 'NULL' by default or a value in 'xxs', 'xs', 'sm', only work with package 'shinydashboard'.
<code>status</code>	Color, must be a valid Bootstrap status : primary, info, success, warning, danger.
<code>striped</code>	logical, add a striped effect.
<code>title</code>	character, optional title.
<code>range_value</code>	Default is to display percentage ([0, 100]), but you can specify a custom range, e.g. -50, 50.
<code>unit_mark</code>	Unit for value displayed on the progress bar, default to "%".
<code>session</code>	The 'session' object passed to function given to shinyServer.

Value

A progress bar that can be added to a UI definition.

See Also

[progressSweetAlert](#) for progress bar in a sweet alert

Examples

```
if (interactive()) {

  library("shiny")
  library("shinyWidgets")

  ui <- fluidPage(
    column(
      width = 7,
      tags$b("Default"), br(),
      progressBar(id = "pb1", value = 50),
      sliderInput(
        inputId = "up1",
        label = "Update",
        min = 0,
        max = 100,
        value = 50
      ),
      br(),
      tags$b("Other options"), br(),
      progressBar(
        id = "pb2",
        value = 0,
        total = 100,
        title = "",
        display_pct = TRUE
      ),
      actionButton(
        inputId = "go",
        label = "Launch calculation"
      )
    )
  )

  server <- function(input, output, session) {
    observeEvent(input$up1, {
      updateProgressBar(
        session = session,
        id = "pb1",
        value = input$up1
      )
    })
    observeEvent(input$go, {
      for (i in 1:100) {
```

```

    updateProgressBar(
      session = session,
      id = "pb2",
      value = i, total = 100,
      title = paste("Process", trunc(i/10))
    )
    Sys.sleep(0.1)
  }
})
}

shinyApp(ui = ui, server = server)

}

```

progressSweetAlert *Progress bar in a sweet alert*

Description

Progress bar in a sweet alert

Usage

```

progressSweetAlert(
  session,
  id,
  value,
  total = NULL,
  display_pct = FALSE,
  size = NULL,
  status = NULL,
  striped = FALSE,
  title = NULL
)

```

Arguments

session	The session object passed to function given to shinyServer.
id	An id used to update the progress bar.
value	Value of the progress bar between 0 and 100, if >100 you must provide total.
total	Used to calculate percentage if value > 100, force an indicator to appear on top right of the progress bar.
display_pct	logical, display percentage on the progress bar.
size	Size, 'NULL' by default or a value in 'xxs', 'xs', 'sm', only work with package 'shinydashboard'.

status Color, must be a valid Bootstrap status : primary, info, success, warning, danger.
 striped logical, add a striped effect.
 title character, optional title.

Examples

```

if (interactive()) {

  library("shiny")
  library("shinyWidgets")

  ui <- fluidPage(
    tags$h1("Progress bar in Sweet Alert"),
    useSweetAlert(), # /\ needed with 'progressSweetAlert'
    actionButton(
      inputId = "go",
      label = "Launch long calculation !"
    )
  )

  server <- function(input, output, session) {

    observeEvent(input$go, {
      progressSweetAlert(
        session = session, id = "myprogress",
        title = "Work in progress",
        display_pct = TRUE, value = 0
      )
      for (i in seq_len(50)) {
        Sys.sleep(0.1)
        updateProgressBar(
          session = session,
          id = "myprogress",
          value = i*2
        )
      }
      closeSweetAlert(session = session)
      sendSweetAlert(
        session = session,
        title = " Calculation completed !",
        type = "success"
      )
    })

  }

  shinyApp(ui = ui, server = server)

}

```

radioGroupButtons *Buttons Group Radio Input Control*

Description

Create buttons grouped that act like radio buttons.

Usage

```
radioGroupButtons(
  inputId,
  label = NULL,
  choices = NULL,
  selected = NULL,
  status = "default",
  size = "normal",
  direction = "horizontal",
  justified = FALSE,
  individual = FALSE,
  checkIcon = list(),
  width = NULL,
  choiceNames = NULL,
  choiceValues = NULL,
  disabled = FALSE
)
```

Arguments

inputId	The input slot that will be used to access the value.
label	Input label.
choices	List of values to select from (if elements of the list are named then that name rather than the value is displayed to the user).
selected	The initially selected value.
status	Add a class to the buttons, you can use Bootstrap status like 'info', 'primary', 'danger', 'warning' or 'success'. Or use an arbitrary strings to add a custom class, e.g. : with status = 'myClass', buttons will have class btn=myClass.
size	Size of the buttons ('xs', 'sm', 'normal', 'lg')
direction	Horizontal or vertical
justified	If TRUE, fill the width of the parent div
individual	If TRUE, buttons are separated.
checkIcon	A list, if no empty must contain at least one element named 'yes' corresponding to an icon to display if the button is checked.
width	The width of the input, e.g. '400px', or '100%'.

choiceNames, choiceValues
 Same as in [radioButtons](#). List of names and values, respectively, that are displayed to the user in the app and correspond to the each choice (for this reason, choiceNames and choiceValues must have the same length).

disabled
 Initialize buttons in a disabled state (users won't be able to select a value).

Value

A buttons group control that can be added to a UI definition.

See Also

[updateRadioGroupButtons](#)

Examples

```
if (interactive()) {

  ui <- fluidPage(
    tags$h1("radioGroupButtons examples"),

    radioGroupButtons(
      inputId = "somevalue1",
      label = "Make a choice: ",
      choices = c("A", "B", "C")
    ),
    verbatimTextOutput("value1"),

    radioGroupButtons(
      inputId = "somevalue2",
      label = "With custom status:",
      choices = names(iris),
      status = "primary"
    ),
    verbatimTextOutput("value2"),

    radioGroupButtons(
      inputId = "somevalue3",
      label = "With icons:",
      choices = names(mtcars),
      checkIcon = list(
        yes = icon("check-square"),
        no = icon("square-o")
      )
    ),
    verbatimTextOutput("value3")
  )
  server <- function(input, output) {

    output$value1 <- renderPrint({ input$somevalue1 })
    output$value2 <- renderPrint({ input$somevalue2 })
    output$value3 <- renderPrint({ input$somevalue3 })
  }
}
```

```

    }
    shinyApp(ui, server)
  }

```

 searchInput

Search Input

Description

A text input only triggered when Enter key is pressed or search button clicked

Usage

```

searchInput(
  inputId,
  label = NULL,
  value = "",
  placeholder = NULL,
  btnSearch = NULL,
  btnReset = NULL,
  resetValue = "",
  width = NULL
)

```

Arguments

inputId	The input slot that will be used to access the value.
label	Display label for the control, or NULL for no label.
value	Initial value.
placeholder	A character string giving the user a hint as to what can be entered into the control.
btnSearch	An icon for the button which validate the search.
btnReset	An icon for the button which reset the search.
resetValue	Value used when reset button is clicked, default to "", if NULL value is not reset.
width	The width of the input, e.g. '400px', or '100%'.

Note

The two buttons ('search' and 'reset') act like `actionButton`, you can retrieve their value server-side with `input$<INPUTID>_search` and `input$<INPUTID>_reset`.

See Also

[updateSearchInput](#) to update value server-side.

Examples

```
if (interactive()) {
  ui <- fluidPage(
    tags$h1("Search Input"),
    br(),
    searchInput(
      inputId = "search", label = "Enter your text",
      placeholder = "A placeholder",
      btnSearch = icon("search"),
      btnReset = icon("remove"),
      width = "450px"
    ),
    br(),
    verbatimTextOutput(outputId = "res")
  )

  server <- function(input, output, session) {
    output$res <- renderPrint({
      input$search
    })
  }

  shinyApp(ui = ui, server = server)
}
```

selectizeGroup-module *Selectize Group*

Description

Group of mutually dependent ‘selectizeInput‘ for filtering data.frame’s columns (like in Excel).

Usage

```
selectizeGroupUI(
  id,
  params,
  label = NULL,
  btn_label = "Reset filters",
  inline = TRUE
)

selectizeGroupServer(input, output, session, data, vars)
```

Arguments

id Module’s id.

params	A named list of parameters passed to each 'selectizeInput', you can use : 'inputId' (obligatory, must be variable name), 'label', 'placeholder'.
label	Character, global label on top of all labels.
btn_label	Character, reset button label.
inline	If TRUE (the default), 'selectizeInput's are horizontally positioned, otherwise vertically.
input, output, session	standards shiny server arguments.
data	Either a data.frame or a reactive function returning a data.frame (do not use parentheses).
vars	character, columns to use to create filters, must correspond to variables listed in params. Can be a reactive function, but values must be included in the initial ones (in params).

Value

a reactive function containing data filtered.

Examples

```
# Default -----
if (interactive()) {
  library(shiny)
  library(shinyWidgets)

  data("mpg", package = "ggplot2")

  ui <- fluidPage(
    fluidRow(
      column(
        width = 10, offset = 1,
        tags$h3("Filter data with selectize group"),
        panel(
          selectizeGroupUI(
            id = "my-filters",
            params = list(
              manufacturer = list(inputId = "manufacturer", title = "Manufacturer:"),
              model = list(inputId = "model", title = "Model:"),
              trans = list(inputId = "trans", title = "Trans:"),
              class = list(inputId = "class", title = "Class:")
            )
          ), status = "primary"
        ),
      DT::dataTableOutput(outputId = "table")
    )
  )
}
```

```

server <- function(input, output, session) {
  res_mod <- callModule(
    module = selectizeGroupServer,
    id = "my-filters",
    data = mpg,
    vars = c("manufacturer", "model", "trans", "class")
  )
  output$table <- DT::renderDataTable(res_mod())
}

shinyApp(ui, server)

}

# Select variables -----

if (interactive()) {

  library(shiny)
  library(shinyWidgets)

  data("mpg", package = "ggplot2")

  ui <- fluidPage(
    fluidRow(
      column(
        width = 10, offset = 1,
        tags$h3("Filter data with selectize group"),
        panel(
          checkboxGroupInput(
            inputId = "vars",
            label = "Variables to use:",
            choices = c("manufacturer", "model", "trans", "class"),
            selected = c("manufacturer", "model", "trans", "class"),
            inline = TRUE
          ),
          selectizeGroupUI(
            id = "my-filters",
            params = list(
              manufacturer = list(inputId = "manufacturer", title = "Manufacturer:"),
              model = list(inputId = "model", title = "Model:"),
              trans = list(inputId = "trans", title = "Trans:"),
              class = list(inputId = "class", title = "Class:")
            )
          ),
          status = "primary"
        ),
      DT::dataTableOutput(outputId = "table")
    )
  )
}

server <- function(input, output, session) {

```

```

vars_r <- reactive({
  input$vars
})

res_mod <- callModule(
  module = selectizeGroupServer,
  id = "my-filters",
  data = mpg,
  vars = vars_r
)

output$table <- DT::renderDataTable({
  req(res_mod())
  res_mod()
})
}

shinyApp(ui, server)
}

# Subset data -----
if (interactive()) {

  library(shiny)
  library(shinyWidgets)

  data("mpg", package = "ggplot2")

  ui <- fluidPage(
    fluidRow(
      column(
        width = 10, offset = 1,
        tags$h3("Filter data with selectize group"),
        panel(
          pickerInput(
            inputId = "car_select",
            choices = unique(mpg$manufacturer),
            options = list(
              `live-search` = TRUE,
              title = "None selected"
            )
          ),
          selectizeGroupUI(
            id = "my-filters",
            params = list(
              manufacturer = list(inputId = "manufacturer", title = "Manufacturer:"),
              model = list(inputId = "model", title = "Model:"),
              trans = list(inputId = "trans", title = "Trans:"),
              class = list(inputId = "class", title = "Class:")
            )
          ),
        )
      )
    )
  }

```

```
        status = "primary"
      ),
      DT::dataTableOutput(outputId = "table")
    )
  )
}

server <- function(input, output, session) {

  mpg_filter <- reactive({
    subset(mpg, manufacturer %in% input$car_select)
  })

  res_mod <- callModule(
    module = selectizeGroupServer,
    id = "my-filters",
    data = mpg_filter,
    vars = c("manufacturer", "model", "trans", "class")
  )

  output$table <- DT::renderDataTable({
    req(res_mod())
    res_mod()
  })
}

shinyApp(ui, server)
}
```

setBackgroundColor *Custom background color for your shinyapp*

Description

Allow to change the background color of your shiny application.

Usage

```
setBackgroundColor(
  color = "ghostwhite",
  gradient = c("linear", "radial"),
  direction = c("bottom", "top", "right", "left"),
  shinydashboard = FALSE
)
```

Arguments

color Background color. Use either the fullname or the Hex code (https://www.w3schools.com/colors/colors_hex.asp). If more than one color is used, a gradient background is set.

`gradient` Type of gradient: linear or radial.

`direction` Direction for gradient, by default to bottom. Possibles choices are bottom, top, right or left, two values can be used, e.g. `c("bottom", "right")`.

`shinydashboard` Set to TRUE if in a shinydasboard application.

Examples

```

if (interactive()) {

### Uniform color background :

library(shiny)
library(shinyWidgets)

ui <- fluidPage(
  tags$h2("Change shiny app background"),
  setBackgroundColor("ghostwhite")
)

server <- function(input, output, session) {

}

shinyApp(ui, server)

### linear gradient background :

library(shiny)
library(shinyWidgets)

ui <- fluidPage(

# use a gradient in background
setBackgroundColor(
  color = c("#F7FBFF", "#2171B5"),
  gradient = "linear",
  direction = "bottom"
),

titlePanel("Hello Shiny!"),
sidebarLayout(
  sidebarPanel(
    sliderInput("obs",
      "Number of observations:",
      min = 0,
      max = 1000,
      value = 500)
  ),
  mainPanel(
    plotOutput("distPlot")
  )
)

```

```
)
)

server <- function(input, output, session) {
  output$distPlot <- renderPlot({
    hist(rnorm(input$obs))
  })
}

shinyApp(ui, server)

### radial gradient background :

library(shiny)
library(shinyWidgets)

ui <- fluidPage(

  # use a gradient in background
  setBackgroundColor(
    color = c("#F7FBFF", "#2171B5"),
    gradient = "radial",
    direction = c("top", "left")
  ),

  titlePanel("Hello Shiny!"),
  sidebarLayout(
    sidebarPanel(
      sliderInput("obs",
                  "Number of observations:",
                  min = 0,
                  max = 1000,
                  value = 500)
    ),
    mainPanel(
      plotOutput("distPlot")
    )
  )
)

server <- function(input, output, session) {
  output$distPlot <- renderPlot({
    hist(rnorm(input$obs))
  })
}

shinyApp(ui, server)

}
```

setBackgroundImage *Custom background image for your shinyapp*

Description

Allow to change the background image of your shinyapp.

Usage

```
setBackgroundImage(src = NULL, shinydashboard = FALSE)
```

Arguments

src Url or path to the image, if using local image, the file must be in www/ directory and the path not contain www/.

shinydashboard Set to TRUE if in a shinydasboard application.

Examples

```
if (interactive()) {  
  
  library(shiny)  
  library(shinyWidgets)  
  
  ui <- fluidPage(  
    tags$h2("Add a shiny app background image"),  
    setBackgroundImage(  
      src = "https://www.fillmurray.com/1920/1080"  
    )  
  )  
  
  server <- function(input, output, session) {  
  
  }  
  
  shinyApp(ui, server)  
  
}
```

setShadow *Custom shadows*

Description

Allow to apply a shadow on a given element.

Usage

```
setShadow(id = NULL, class = NULL)
```

Arguments

<code>id</code>	Use this argument if you want to target an individual element.
<code>class</code>	The element to which the shadow should be applied. For example, class is set to <code>box</code> .

Examples

```
if (interactive()) {  
  
  library(shiny)  
  library(shinydashboard)  
  library(shinydashboardPlus)  
  library(shinyWidgets)  
  
  boxTag <- box(  
    title = "Closable box, with label",  
    closable = TRUE,  
    label = boxLabel(  
      text = 1,  
      status = "danger"  
    ),  
    status = "warning",  
    solidHeader = FALSE,  
    collapsible = TRUE,  
    p("Box Content")  
  )  
  
  shinyApp(  
    ui = dashboardPage(  
      header = dashboardHeader(),  
      sidebar = dashboardSidebar(),  
      body = dashboardBody(  
  
        setShadow(class = "box"),  
        setShadow(id = "my-progress"),  
  
        tags$h2("Add shadow to the box class"),  
        fluidRow(boxTag, boxTag),  
        tags$h2("Add shadow only to the first element using id"),  
        tagAppendAttributes(  
          shinydashboardPlus::progressBar(  
            value = 10,  
            striped = TRUE,  
            animated = TRUE  
          ),  
          id = "my-progress"  
        ),  
      )  
    )  
  )  
}
```

```

shinydashboardPlus::progressBar(
  value = 50,
  status = "warning"
),
shinydashboardPlus::progressBar(
  value = 20,
  status = "danger"
)
),
controlbar = dashboardControlbar(),
title = "DashboardPage"
),
server = function(input, output) { }
}

```

setSliderColor *Color editor for sliderInput*

Description

Edit the color of the original shiny's sliderInputs

Usage

```
setSliderColor(color, sliderId)
```

Arguments

color	The color to apply. This can also be a vector of colors if you want to customize more than 1 slider. Either pass the name of the color such as 'Chartreuse' and 'Chocolate' or the HEX notation such as '#7FFF00' and '#D2691E'.
sliderId	The id of the customized slider(s). This can be a vector like c(1, 2), if you want to modify the 2 first sliders. However, if you only want to modify the second slider, just use the value 2.

Note

See also https://www.w3schools.com/colors/colors_names.asp to have an overview of all colors.

See Also

See [chooseSliderSkin](#) to update the global skin of your sliders.

Examples

```

if (interactive()) {

  library(shiny)
  library(shinyWidgets)

  ui <- fluidPage(

    # only customize the 2 first sliders and the last one
    # the color of the third one is empty
    setSliderColor(c("DeepPink ", "#FF4500", "", "Teal"), c(1, 2, 4)),
    sliderInput("obs", "My pink slider:",
                min = 0, max = 100, value = 50
    ),
    sliderInput("obs2", "My orange slider:",
                min = 0, max = 100, value = 50
    ),
    sliderInput("obs3", "My basic slider:",
                min = 0, max = 100, value = 50
    ),
    sliderInput("obs3", "My teal slider:",
                min = 0, max = 100, value = 50
    ),
    plotOutput("distPlot")
  )

  server <- function(input, output) {

    output$distPlot <- renderPlot({
      hist(rnorm(input$obs))
    })
  }

  shinyApp(ui, server)

}

```

shinyWidgets

*shinyWidgets: Custom inputs widgets for Shiny.***Description**

The shinyWidgets package provides several custom widgets to extend those available in package shiny

Examples

```

if (interactive()) {
  shinyWidgets::shinyWidgetsGallery()
}

```

shinyWidgetsGallery *Launch the shinyWidget Gallery*

Description

A gallery of widgets available in the package.

Usage

```
shinyWidgetsGallery()
```

Examples

```
if (interactive()) {  
  shinyWidgetsGallery()  
}
```

show_toast *Show a toast notification*

Description

Show a toast notification

Usage

```
show_toast(  
  title,  
  text = NULL,  
  type = c("default", "success", "error", "info", "warning", "question"),  
  timer = 3000,  
  timerProgressBar = TRUE,  
  position = c("bottom-end", "top", "top-start", "top-end", "center", "center-start",  
    "center-end", "bottom", "bottom-start"),  
  width = NULL,  
  session = shiny::getDefaultReactiveDomain()  
)
```

Arguments

title	Title for the toast.
text	Text for the toast.
type	Type of the toast: "default", "success", "error", "info", "warning" or "question".
timer	Auto close timer of the modal. Set in ms (milliseconds).
timerProgressBar	If set to true, the timer will have a progress bar at the bottom of a popup.
position	Modal window position, can be "top", "top-start", "top-end", "center", "center-start", "center-end", "bottom", "bottom-start", or "bottom-end".
width	Modal window width, including paddings.
session	The session object passed to function given to shinyServer.

Value

No value.

See Also

[show_alert](#), [ask_confirmation](#), [closeSweetAlert](#).

Examples

```
library(shiny)
library(shinyWidgets)

ui <- fluidPage(
  tags$h2("Sweet Alert Toast"),
  actionButton(
    inputId = "toast",
    label = "Show default toast"
  ),
  actionButton(
    inputId = "success",
    label = "Show success toast",
    icon = icon("check")
  ),
  actionButton(
    inputId = "error",
    label = "Show error toast",
    icon = icon("remove")
  ),
  actionButton(
    inputId = "warning",
    label = "Show warning toast",
    icon = icon("exclamation-triangle")
  ),
  actionButton(
```

```
    inputId = "info",
    label = "Show info toast",
    icon = icon("info")
  )
)

server <- function(input, output, session) {

  observeEvent(input$toast, {
    show_toast(
      title = "Notification",
      text = "An imortant message"
    )
  })

  observeEvent(input$success, {
    show_toast(
      title = "Bravo",
      text = "Well done!",
      type = "success"
    )
  })

  observeEvent(input$error, {
    show_toast(
      title = "Ooops",
      text = "It's broken",
      type = "error",
      width = "800px",
      position = "bottom"
    )
  })

  observeEvent(input$warning, {
    show_toast(
      title = "Careful!",
      text = "Almost broken",
      type = "warning",
      position = "top-end"
    )
  })

  observeEvent(input$info, {
    show_toast(
      title = "Heads up",
      text = "Just a message",
      type = "info",
      position = "top-end"
    )
  })
}

if (interactive())
```

```
shinyApp(ui, server)
```

sliderTextInput	<i>Slider Text Input Widget</i>
-----------------	---------------------------------

Description

Constructs a slider widget with characters instead of numeric values.

Usage

```
sliderTextInput(  
  inputId,  
  label,  
  choices,  
  selected = NULL,  
  animate = FALSE,  
  grid = FALSE,  
  hide_min_max = FALSE,  
  from_fixed = FALSE,  
  to_fixed = FALSE,  
  from_min = NULL,  
  from_max = NULL,  
  to_min = NULL,  
  to_max = NULL,  
  force_edges = FALSE,  
  width = NULL,  
  pre = NULL,  
  post = NULL,  
  dragRange = TRUE  
)
```

Arguments

inputId	The input slot that will be used to access the value.
label	Display label for the control, or NULL for no label.
choices	Character vector to select a value from.
selected	The initially selected value, if length > 1, create a range slider.
animate	TRUE to show simple animation controls with default settings, for more details see sliderInput .
grid	Logical, show or hide ticks marks.
hide_min_max	Hides min and max labels.
from_fixed	Fix position of left (or single) handle.
to_fixed	Fix position of right handle.

<code>from_min</code>	Set minimum limit for left handle.
<code>from_max</code>	Set the maximum limit for left handle.
<code>to_min</code>	Set minimum limit for right handle.
<code>to_max</code>	Set the maximum limit for right handle.
<code>force_edges</code>	Slider will be always inside it's container.
<code>width</code>	The width of the input, e.g. 400px, or 100%.
<code>pre</code>	A prefix string to put in front of the value.
<code>post</code>	A suffix string to put after the value.
<code>dragRange</code>	See the same argument in sliderInput .

Value

The value retrieved server-side is a character vector.

See Also

[updateSliderTextInput](#) to update value server-side.

Examples

```
if (interactive()) {  
  
  library("shiny")  
  library("shinyWidgets")  
  
  ui <- fluidPage(  
    br(),  
    sliderTextInput(  
      inputId = "mySliderText",  
      label = "Month range slider:",  
      choices = month.name,  
      selected = month.name[c(4, 7)]  
    ),  
    verbatimTextOutput(outputId = "result")  
  )  
  
  server <- function(input, output, session) {  
    output$result <- renderPrint(str(input$mySliderText))  
  }  
  
  shinyApp(ui = ui, server = server)  
}
```

spectrumInput *Palette Color Picker with Spectrum Library*

Description

A widget to select a color within palettes, and with more options if needed.

Usage

```
spectrumInput(  
  inputId,  
  label,  
  choices = NULL,  
  selected = NULL,  
  flat = FALSE,  
  options = list(),  
  update_on = c("move", "dragstop", "change"),  
  width = NULL  
)
```

Arguments

inputId	The input slot that will be used to access the value.
label	Display label for the control, or NULL for no label.
choices	List of colors to display in the menu.
selected	The initially selected value.
flat	Display the menu inline.
options	Additional options to pass to spectrum, possible values are described here : https://bgrins.github.io/spectrum/#options .
update_on	When to update value server-side: "move" (default, each time a new color is selected), "dragstop" (when use user stop dragging cursor), "change" (when the input is closed).
width	The width of the input, e.g. 400px, or 100%.

Value

The selected color in Hex format server-side

Examples

```
if (interactive()) {  
  
  library("shiny")  
  library("shinyWidgets")  
  library("scales")  
}
```

```

ui <- fluidPage(
  tags$h1("Spectrum color picker"),

  br(),

  spectrumInput(
    inputId = "myColor",
    label = "Pick a color:",
    choices = list(
      list('black', 'white', 'blanchedalmond', 'steelblue', 'forestgreen'),
      as.list(brewer_pal(palette = "Blues")(9)),
      as.list(brewer_pal(palette = "Greens")(9)),
      as.list(brewer_pal(palette = "Spectral")(11)),
      as.list(brewer_pal(palette = "Dark2")(8))
    ),
    options = list(`toggle-palette-more-text` = "Show more")
  ),
  verbatimTextOutput(outputId = "res")
)

server <- function(input, output, session) {

  output$res <- renderPrint(input$myColor)

}

shinyApp(ui, server)

}

```

stati-card

Minimal statistic cards

Description

Minimal statistic cards

Usage

```

statiCard(
  value,
  subtitle,
  icon = NULL,
  left = FALSE,
  color = "steelblue",
  background = "white",
  animate = FALSE,
  duration = 2000,
  id = NULL
)

```

```
)  
  
updateStatiCard(  
  id,  
  value,  
  duration = 2000,  
  session = getDefaultReactiveDomain()  
)
```

Arguments

value	Value to display.
subtitle	A subtitle to describe the value.
icon	An optional icon created with <code>icon()</code> .
left	Display value and subtitle to the right.
color	Text color.
background	Background color.
animate	Add an animation when value is displayed.
duration	Duration of animation.
id	An id that can be used to update the card server-side.
session	Shiny session.

Value

A UI definition.

Note

Based on work by Dastanbek and ArielDavid on codepen.io

Examples

```
library(shiny)  
library(shinyWidgets)  
  
ui <- fluidPage(  
  tags$h2("Stati Card"),  
  
  fluidRow(  
    column(  
      width = 3,  
      statiCard(12, "Subtitle", icon("home")),  
      statiCard(  
        93, "Animated card", icon("users"),  
        background = "deepskyblue",  
        color = "white",
```

```

        animate = TRUE,
        id = "card1"
    ),
    actionButton("update1", "Update card above server-side"),
    statiCard(
        93, "No animation", icon("users"),
        background = "deepskyblue",
        color = "white",
        id = "card2"
    ),
    actionButton("update2", "Update card above server-side")
),
column(
    width = 3,
    statiCard("$123,456", "Total spend", icon("rocket"), left = TRUE, animate = TRUE),
    tags$br(),
    actionButton("show", "Show card (rendered server-side)"),
    uiOutput(outputId = "card")
),
column(
    width = 3,
    statiCard(12, "No animation", icon("home"), color = "firebrick")
),
column(
    width = 3,
    statiCard(
        "123456 something very very long",
        "Long value text",
        icon = NULL,
        left = TRUE,
        background = "steelblue",
        color = "white"
    ),
    statiCard(
        "123456 something very very long",
        "Long value text with icon",
        icon = icon("tachometer"),
        left = TRUE
    ),
    statiCard(
        "123456 something very very long",
        "Long value text with icon right",
        icon = icon("tasks")
    )
)
)
)

server <- function(input, output, session) {

    observeEvent(input$update1, {

```

```
      updateStatiCard(  
        id = "card1",  
        value = sample.int(200, 1)  
      )  
    })  
  
    observeEvent(input$update2, {  
      updateStatiCard(  
        id = "card2",  
        value = sample.int(200, 1)  
      )  
    })  
  
    output$card <- renderUI({  
      req(input$show)  
      statiCard(  
        format(sample.int(1e6, 1), big.mark = " "),  
        "Total spend",  
        icon("shopping-cart"),  
        left = TRUE,  
        animate = TRUE  
      )  
    })  
  }  
  
  if (interactive())  
    shinyApp(ui, server)
```

sweetalert

Display a Sweet Alert to the user

Description

Show an alert message to the user to provide some feedback.

Usage

```
sendSweetAlert(  
  session,  
  title = "Title",  
  text = NULL,  
  type = NULL,  
  btn_labels = "Ok",  
  btn_colors = "#3085d6",  
  html = FALSE,  
  closeOnClickOutside = TRUE,  
  showCloseButton = FALSE,  
  width = NULL,
```

```

    ...
  )

show_alert(
  title = "Title",
  text = NULL,
  type = NULL,
  btn_labels = "Ok",
  btn_colors = "#3085d6",
  html = FALSE,
  closeOnClickOutside = TRUE,
  showCloseButton = FALSE,
  width = NULL,
  ...,
  session = shiny::getDefaultReactiveDomain()
)

```

Arguments

session	The session object passed to function given to shinyServer.
title	Title of the alert.
text	Text of the alert.
type	Type of the alert : info, success, warning or error.
btn_labels	Label(s) for button(s), can be of length 2, in which case the alert will have two buttons. Use NA for no buttons.s
btn_colors	Color(s) for the buttons.
html	Does text contains HTML tags ?
closeOnClickOutside	Decide whether the user should be able to dismiss the modal by clicking outside of it, or not.
showCloseButton	Show close button in top right corner of the modal.
width	Width of the modal (in pixel).
...	Other arguments passed to JavaScript method.

Note

This function use the JavaScript/sweetalert2 library, see the official documentation for more <https://sweetalert2.github.io/>.

See Also

[confirmSweetAlert](#), [inputSweetAlert](#), [closeSweetAlert](#).

Examples

```
library(shiny)
library(shinyWidgets)

ui <- fluidPage(
  tags$h2("Sweet Alert examples"),
  actionButton(
    inputId = "success",
    label = "Launch a success sweet alert",
    icon = icon("check")
  ),
  actionButton(
    inputId = "error",
    label = "Launch an error sweet alert",
    icon = icon("remove")
  ),
  actionButton(
    inputId = "sw_html",
    label = "Sweet alert with HTML",
    icon = icon("thumbs-up")
  )
)

server <- function(input, output, session) {

  observeEvent(input$success, {
    show_alert(
      title = "Success !!",
      text = "All in order",
      type = "success"
    )
  })

  observeEvent(input$error, {
    show_alert(
      title = "Error !!",
      text = "It's broken...",
      type = "error"
    )
  })

  observeEvent(input$sw_html, {
    show_alert(
      title = NULL,
      text = tags$span(
        tags$h3("With HTML tags",
          style = "color: steelblue;"),
        "In", tags$b("bold"), "and", tags$em("italic"),
        tags$br(),
        "and",
        tags$br(),
        "line",

```

```

        tags$br(),
        "breaks",
        tags$br(),
        "and an icon", icon("thumbs-up")
      ),
      html = TRUE
    )
  })
}

if (interactive())
  shinyApp(ui, server)

# Ouptut in alert ----

library(shiny)
library(shinyWidgets)

ui <- fluidPage(
  tags$h1("Click the button to open the alert"),
  actionButton(
    inputId = "sw_html",
    label = "Sweet alert with plot"
  )
)

server <- function(input, output, session) {

  observeEvent(input$sw_html, {
    show_alert(
      title = "Yay a plot!",
      text = tags$div(
        plotOutput(outputId = "plot"),
        sliderInput(
          inputId = "clusters",
          label = "Number of clusters",
          min = 2, max = 6, value = 3, width = "100%"
        )
      ),
      html = TRUE,
      width = "80%"
    )
  })

  output$plot <- renderPlot({
    plot(Sepal.Width ~ Sepal.Length,
         data = iris, col = Species,
         pch = 20, cex = 2)
    points(kmeans(iris[, 1:2], input$clusters)$centers,
           pch = 4, cex = 4, lwd = 4)
  })
}

```

```
if (interactive())  
  shinyApp(ui, server)
```

sweetalert-confirmation

Launch a confirmation dialog

Description

Launch a popup to ask the user for confirmation.

Usage

```
confirmSweetAlert(  
  session,  
  inputId,  
  title = NULL,  
  text = NULL,  
  type = "question",  
  btn_labels = c("Cancel", "Confirm"),  
  btn_colors = NULL,  
  closeOnClickOutside = FALSE,  
  showCloseButton = FALSE,  
  html = FALSE,  
  ...  
)  
  
ask_confirmation(  
  inputId,  
  title = NULL,  
  text = NULL,  
  type = "question",  
  btn_labels = c("Cancel", "Confirm"),  
  btn_colors = NULL,  
  closeOnClickOutside = FALSE,  
  showCloseButton = FALSE,  
  html = FALSE,  
  ...,  
  session = shiny::getDefaultReactiveDomain()  
)
```

Arguments

`session` The session object passed to function given to `shinyServer`.

<code>inputId</code>	The input slot that will be used to access the value. If in a Shiny module, it use same logic than inputs : use namespace in UI, not in server.
<code>title</code>	Title of the alert.
<code>text</code>	Text of the alert, can contains HTML tags.
<code>type</code>	Type of the alert : info, success, warning or error.
<code>btn_labels</code>	Labels for buttons, cancel button (FALSE) first then confirm button (TRUE).
<code>btn_colors</code>	Colors for buttons.
<code>closeOnClickOutside</code>	Decide whether the user should be able to dismiss the modal by clicking outside of it, or not.
<code>showCloseButton</code>	Show close button in top right corner of the modal.
<code>html</code>	Does text contains HTML tags ?
<code>...</code>	Additional arguments (not used)

See Also

[sendSweetAlert](#), [inputSweetAlert](#), [closeSweetAlert](#).

Examples

```
library(shiny)
library(shinyWidgets)

ui <- fluidPage(
  tags$h1("Ask the user for confirmation"),
  actionButton(
    inputId = "launch",
    label = "Ask for confirmation"
  ),
  verbatimTextOutput(outputId = "res"),
  uiOutput(outputId = "count")
)

server <- function(input, output, session) {

  # Launch sweet alert confirmation
  observeEvent(input$launch, {
    ask_confirmation(
      inputId = "myconfirmation",
      title = "Want to confirm ?"
    )
  })

  # raw output
  output$res <- renderPrint(input$myconfirmation)

  # count click
```

```

true <- reactiveVal(0)
false <- reactiveVal(0)
observeEvent(input$myconfirmation, {
  if (isTRUE(input$myconfirmation)) {
    x <- true() + 1
    true(x)
  } else {
    x <- false() + 1
    false(x)
  }
}, ignoreNULL = TRUE)

output$count <- renderUI({
  tags$span(
    "Confirm:", tags$b(true()),
    tags$br(),
    "Cancel:", tags$b(false())
  )
})
}

if (interactive())
  shinyApp(ui, server)

# -----
library(shiny)
library(shinyWidgets)

ui <- fluidPage(
  tags$h1("Ask for confirmation"),
  actionButton(
    inputId = "launch1",
    label = "Launch confirmation dialog"
  ),
  verbatimTextOutput(outputId = "res1"),
  tags$br(),
  actionButton(
    inputId = "launch2",
    label = "Launch confirmation dialog (with normal mode)"
  ),
  verbatimTextOutput(outputId = "res2"),
  tags$br(),
  actionButton(
    inputId = "launch3",
    label = "Launch confirmation dialog (with HTML)"
  ),
  verbatimTextOutput(outputId = "res3")
)

server <- function(input, output, session) {

  observeEvent(input$launch1, {
    ask_confirmation(

```

```

      inputId = "myconfirmation1",
      type = "warning",
      title = "Want to confirm ?"
    )
  })
  output$res1 <- renderPrint(input$myconfirmation1)

  observeEvent(input$launch2, {
    ask_confirmation(
      inputId = "myconfirmation2",
      type = "warning",
      title = "Are you sure ??",
      btn_labels = c("Nope", "Yep"),
      btn_colors = c("#FE642E", "#04B404")
    )
  })
  output$res2 <- renderPrint(input$myconfirmation2)

  observeEvent(input$launch3, {
    ask_confirmation(
      inputId = "myconfirmation3",
      title = NULL,
      text = tags$b(
        icon("file"),
        "Do you really want to delete this file ?",
        style = "color: #FA5858;"
      ),
      btn_labels = c("Cancel", "Delete file"),
      btn_colors = c("#00BFFF", "#FE2E2E"),
      html = TRUE
    )
  })
  output$res3 <- renderPrint(input$myconfirmation3)
}

if (interactive())
  shinyApp(ui, server)

```

switchInput

Bootstrap Switch Input Control

Description

Create a toggle switch.

Usage

```

switchInput(
  inputId,

```

```
    label = NULL,  
    value = FALSE,  
    onLabel = "ON",  
    offLabel = "OFF",  
    onStatus = NULL,  
    offStatus = NULL,  
    size = "default",  
    labelWidth = "auto",  
    handleWidth = "auto",  
    disabled = FALSE,  
    inline = FALSE,  
    width = NULL  
  )
```

Arguments

inputId	The input slot that will be used to access the value.
label	Display a text in the center of the switch.
value	Initial value (TRUE or FALSE).
onLabel	Text on the left side of the switch (TRUE).
offLabel	Text on the right side of the switch (FALSE).
onStatus	Color (bootstrap status) of the left side of the switch (TRUE).
offStatus	Color (bootstrap status) of the right side of the switch (FALSE).
size	Size of the buttons ('default', 'mini', 'small', 'normal', 'large').
labelWidth	Width of the center handle in pixels.
handleWidth	Width of the left and right sides in pixels.
disabled	Logical, display the toggle switch in disabled state?.
inline	Logical, display the toggle switch inline?
width	The width of the input : 'auto', 'fit', '100px', '75%'.

Value

A switch control that can be added to a UI definition.

Note

For more information, see the project on Github <https://github.com/Bttstrp/bootstrap-switch>.

See Also

[updateSwitchInput](#), [materialSwitch](#)

Examples

```
## Only run examples in interactive R sessions
if (interactive()) {

# Examples in the gallery :
shinyWidgets::shinyWidgetsGallery()

# Basic usage :
ui <- fluidPage(
  switchInput(inputId = "somevalue"),
  verbatimTextOutput("value")
)
server <- function(input, output) {
  output$value <- renderPrint({ input$somevalue })
}
shinyApp(ui, server)
}
```

textInputAddon	<i>Text with Add-on Input Control</i>
----------------	---------------------------------------

Description

Create text field with add-on.

Usage

```
textInputAddon(
  inputId,
  label,
  value = "",
  placeholder = NULL,
  addon,
  width = NULL
)
```

Arguments

inputId	The input slot that will be used to access the value.
label	Display label for the control, or NULL for no label.
value	Initial value..
placeholder	A character string giving the user a hint as to what can be entered into the control.
addon	An icon tag, created by icon .
width	The width of the input : 'auto', 'fit', '100px', '75%'

Value

A switch control that can be added to a UI definition.

Examples

```
## Only run examples in interactive R sessions
if (interactive()) {
shinyApp(
  ui = fluidPage(
    textInputAddon(inputId = "id", label = "Label", placeholder = "Username", addon = icon("at")),
    verbatimTextOutput(outputId = "out")
  ),
  server = function(input, output) {
    output$out <- renderPrint({
      input$id
    })
  }
)
}
```

textInputIcon

Create a text input control with icon(s)

Description

Extend form controls by adding text or icons before, after, or on both sides of a classic textInput.

Usage

```
textInputIcon(
  inputId,
  label,
  value = "",
  placeholder = NULL,
  icon = NULL,
  size = NULL,
  width = NULL
)
```

Arguments

inputId	The input slot that will be used to access the value.
label	Display label for the control, or NULL for no label.
value	Initial value.
placeholder	A character string giving the user a hint as to what can be entered into the control. Internet Explorer 8 and 9 do not support this option.

icon	An icon or a list, containing icons or text, to be displayed on the right or left of the text input.
size	Size of the input, default to NULL, can be "sm" (small) or "lg" (large).
width	The width of the input, e.g. '400px', or '100%'; see validateCssUnit() .

Value

A text input control that can be added to a UI definition.

Examples

```
if (interactive()) {
  library(shiny)
  library(shinyWidgets)

  ui <- fluidPage(
    tags$h2("textInputIcon examples"),
    fluidRow(
      column(
        width = 6,
        textInputIcon(
          inputId = "ex1",
          label = "With an icon",
          icon = icon("user-circle-o")
        ),
        verbatimTextOutput("res1"),
        textInputIcon(
          inputId = "ex2",
          label = "With an icon (right)",
          icon = list(NULL, icon("user-circle-o"))
        ),
        verbatimTextOutput("res2"),
        textInputIcon(
          inputId = "ex3",
          label = "With text",
          icon = list("https://")
        ),
        verbatimTextOutput("res3"),
        textInputIcon(
          inputId = "ex4",
          label = "Both side",
          icon = list(icon("envelope"), "@mail.com")
        ),
        verbatimTextOutput("res4"),
        textInputIcon(
          inputId = "ex5",
          label = "Sizing",
          icon = list(icon("envelope"), "@mail.com"),
          size = "lg"
        ),
        verbatimTextOutput("res5")
      )
    )
  )
}
```

```
    )
  )

  server <- function(input, output, session) {

    output$res1 <- renderPrint(input$ex1)
    output$res2 <- renderPrint(input$ex2)
    output$res3 <- renderPrint(input$ex3)
    output$res4 <- renderPrint(input$ex4)
    output$res5 <- renderPrint(input$ex5)

  }

  shinyApp(ui, server)
}
```

toggleDropDownButton *Toggle a dropdown menu*

Description

Open or close a dropdown menu server-side.

Usage

```
toggleDropDownButton(inputId, session = getDefaultReactiveDomain())
```

Arguments

inputId	Id for the dropdown to toggle.
session	Standard shiny session.

Examples

```
if (interactive()) {

  library("shiny")
  library("shinyWidgets")

  ui <- fluidPage(
    tags$h2("Toggle Dropdown Button"),
    br(),
    fluidRow(
      column(
        width = 6,
        dropdownButton(
          tags$h3("List of Inputs"),
          selectInput(inputId = 'xcol',
                      label = 'X Variable',
                      choices = names(iris)),
        )
      )
    )
  )
}
```

```

        sliderInput(inputId = 'clusters',
                    label = 'Cluster count',
                    value = 3,
                    min = 1,
                    max = 9),
        actionButton(inputId = "toggle2",
                     label = "Close dropdown"),
        circle = TRUE, status = "danger",
        inputId = "mydropdown",
        icon = icon("gear"), width = "300px"
    )
  ),
  column(
    width = 6,
    actionButton(inputId = "toggle1",
                 label = "Open dropdown")
  )
)
)
)

server <- function(input, output, session) {

  observeEvent(list(input$toggle1, input$toggle2), {
    toggleDropdownButton(inputId = "mydropdown")
  }, ignoreInit = TRUE)

}

shinyApp(ui = ui, server = server)

}

```

 tooltipOptions

Tooltip options

Description

List of options for tooltip for a dropdown menu button.

Usage

```
tooltipOptions(placement = "right", title = "Params", html = FALSE)
```

Arguments

placement	Placement of tooltip : right, top, bottom, left.
title	Text of the tooltip
html	Logical, allow HTML tags inside tooltip

updateAirDateInput *Change the value of `airDatepickerInput` on the client*

Description

Change the value of `airDatepickerInput` on the client

Usage

```
updateAirDateInput(  
  session,  
  inputId,  
  label = NULL,  
  value = NULL,  
  clear = FALSE,  
  options = NULL,  
  show = FALSE,  
  hide = FALSE  
)
```

Arguments

<code>session</code>	The session object passed to function given to shinyServer.
<code>inputId</code>	The id of the input object.
<code>label</code>	The label to set for the input object.
<code>value</code>	The value to set for the input object.
<code>clear</code>	Logical, clear all previous selected dates.
<code>options</code>	Options to update, see available ones here: http://t1m0n.name/air-datepicker/docs/ .
<code>show, hide</code>	Show / hide datepicker.

Examples

```
if (interactive()) {  
  demoAirDatepicker("update")  
}
```

`updateAutonumericInput`*Update an Autonumeric Input Object*

Description

Update an Autonumeric Input Object

Usage

```
updateAutonumericInput(  
  session,  
  inputId,  
  label = NULL,  
  value = NULL,  
  options = NULL  
)
```

Arguments

<code>session</code>	Standard shiny session.
<code>inputId</code>	The id of the input object.
<code>label</code>	The label to set for the input object.
<code>value</code>	The value to set for the input object.
<code>options</code>	List of additional parameters to update, use <code>autonumericInput</code> 's arguments.

See Also

Other autonumeric: [autonumericInput\(\)](#), [currencyInput\(\)](#), [updateCurrencyInput\(\)](#)

Examples

```
if (interactive()) {  
  library(shiny)  
  library(shinyWidgets)  
  
  ui <- fluidPage(  
    h1("AutonumericInput Update Example"),  
    br(),  
    autonumericInput(  
      inputId = "id1",  
      label = "Autonumeric Input",  
      value = 1234.56,  
      align = "center",  
      currencySymbol = "$ ",  
      currencySymbolPlacement = "p",  
      decimalCharacter = ".",  
    )  
  )  
}
```

```

    digitGroupSeparator = ","
  ),
  verbatimTextOutput("res1"),
  actionButton("bbtn1", "Change Input to Euros"),
  actionButton("bbtn2", "Change Input to Dollars"),
  br(),
  br(),
  sliderInput("decimals", "Select Number of Decimal Places",
    value = 2, step = 1, min = 0, max = 6),
  actionButton("bbtn3", "Update Number of Decimal Places")
)

server <- function(input, output, session) {
  output$res1 <- renderPrint(input$id1)

  observeEvent(input$bbtn1, {
    updateAutonumericInput(
      session = session,
      inputId = "id1",
      label = "Euros:",
      value = 6543.21,
      options = list(
        currencySymbol = "\u20ac",
        currencySymbolPlacement = "s",
        decimalCharacter = ",",
        digitGroupSeparator = "."
      )
    )
  })
  observeEvent(input$bbtn2, {
    updateAutonumericInput(
      session = session,
      inputId = "id1",
      label = "Dollars:",
      value = 6543.21,
      options = list(
        currencySymbol = "$",
        currencySymbolPlacement = "p",
        decimalCharacter = ".",
        digitGroupSeparator = ","
      )
    )
  })
  observeEvent(input$bbtn3, {
    updateAutonumericInput(
      session = session,
      inputId = "id1",
      options = list(
        decimalPlaces = input$decimals
      )
    )
  })
}

```

```
  shinyApp(ui, server)
}
```

updateAwesomeCheckbox *Change the value of an awesome checkbox input on the client*

Description

Change the value of an awesome checkbox input on the client

Usage

```
updateAwesomeCheckbox(session, inputId, label = NULL, value = NULL)
```

Arguments

session	standard shiny session
inputId	The id of the input object.
label	The label to set for the input object.
value	The value to set for the input object.

See Also

[awesomeCheckbox](#)

Examples

```
if (interactive()) {

  library("shiny")
  library("shinyWidgets")

  ui <- fluidPage(
    awesomeCheckbox(
      inputId = "somevalue",
      label = "My label",
      value = FALSE
    ),

    verbatimTextOutput(outputId = "res"),

    actionButton(inputId = "updatevalue", label = "Toggle value"),
    textInput(inputId = "updatelabel", label = "Update label")
  )

  server <- function(input, output, session) {
```

```
output$res <- renderPrint({
  input$somevalue
})

observeEvent(input$updatevalue, {
  updateAwesomeCheckbox(
    session = session, inputId = "somevalue",
    value = as.logical(input$updatevalue %%2)
  )
})

observeEvent(input$updatelabel, {
  updateAwesomeCheckbox(
    session = session, inputId = "somevalue",
    label = input$updatelabel
  )
}, ignoreInit = TRUE)

}

shinyApp(ui = ui, server = server)

}
```

updateAwesomeCheckboxGroup

Change the value of a [awesomeCheckboxGroup](#) input on the client

Description

Change the value of a [awesomeCheckboxGroup](#) input on the client

Usage

```
updateAwesomeCheckboxGroup(
  session,
  inputId,
  label = NULL,
  choices = NULL,
  selected = NULL,
  inline = FALSE,
  status = "primary"
)
```

Arguments

session	The session object passed to function given to shinyServer.
inputId	The id of the input object.

label	Input label.
choices	List of values to show checkboxes for.
selected	The values that should be initially selected, if any.
inline	If TRUE, render the choices inline (i.e. horizontally)
status	Color of the buttons.

See Also

[awesomeCheckboxGroup](#)

Examples

```

if (interactive()) {

  library("shiny")
  library("shinyWidgets")

  ui <- fluidPage(
    awesomeCheckboxGroup(
      inputId = "somevalue",
      choices = c("A", "B", "C"),
      label = "My label"
    ),

    verbatimTextOutput(outputId = "res"),

    actionButton(inputId = "updatechoices", label = "Random choices"),
    textInput(inputId = "updatelabel", label = "Update label")
  )

  server <- function(input, output, session) {

    output$res <- renderPrint({
      input$somevalue
    })

    observeEvent(input$updatechoices, {
      updateAwesomeCheckboxGroup(
        session = session, inputId = "somevalue",
        choices = sample(letters, sample(2:6))
      )
    })

    observeEvent(input$updatelabel, {
      updateAwesomeCheckboxGroup(
        session = session, inputId = "somevalue",
        label = input$updatelabel
      )
    })
  }, ignoreInit = TRUE)

```

```
}  
shinyApp(ui = ui, server = server)  
}
```

updateAwesomeRadio *Change the value of a radio input on the client*

Description

Change the value of a radio input on the client

Usage

```
updateAwesomeRadio(  
  session,  
  inputId,  
  label = NULL,  
  choices = NULL,  
  selected = NULL,  
  inline = FALSE,  
  status = "primary",  
  checkbox = FALSE  
)
```

Arguments

session	The session object passed to function given to shinyServer.
inputId	The id of the input object.
label	Input label.
choices	List of values to select from (if elements of the list are named then that name rather than the value is displayed to the user)
selected	The initially selected value
inline	If TRUE, render the choices inline (i.e. horizontally)
status	Color of the buttons
checkbox	Checkbox style

See Also

[awesomeRadio](#)

Examples

```
if (interactive()) {  
  
  library("shiny")  
  library("shinyWidgets")  
  
  ui <- fluidPage(  
    awesomeRadio(  
      inputId = "somevalue",  
      choices = c("A", "B", "C"),  
      label = "My label"  
    ),  
  
    verbatimTextOutput(outputId = "res"),  
  
    actionButton(inputId = "updatechoices", label = "Random choices"),  
    textInput(inputId = "updatelabel", label = "Update label")  
  )  
  
  server <- function(input, output, session) {  
  
    output$res <- renderPrint({  
      input$somevalue  
    })  
  
    observeEvent(input$updatechoices, {  
      updateAwesomeRadio(  
        session = session, inputId = "somevalue",  
        choices = sample(letters, sample(2:6))  
      )  
    })  
  
    observeEvent(input$updatelabel, {  
      updateAwesomeRadio(  
        session = session, inputId = "somevalue",  
        label = input$updatelabel  
      )  
    }, ignoreInit = TRUE)  
  
  }  
  
  shinyApp(ui = ui, server = server)  
  
}
```

updateCheckboxGroupButtons

Change the value of a checkboxes group buttons input on the client

Description

Change the value of a radio group buttons input on the client

Usage

```
updateCheckboxGroupButtons(  
  session,  
  inputId,  
  label = NULL,  
  choices = NULL,  
  selected = NULL,  
  status = "default",  
  size = "normal",  
  checkIcon = list(),  
  choiceNames = NULL,  
  choiceValues = NULL,  
  disabled = FALSE,  
  disabledChoices = NULL  
)
```

Arguments

session	The session object passed to function given to shinyServer.
inputId	The id of the input object.
label	The label to set.
choices	The new choices for the input.
selected	The values selected.
status	Status, only used if choices is not NULL.
size	Size, only used if choices is not NULL.
checkIcon	Icon, only used if choices is not NULL.
choiceNames, choiceValues	List of names and values, an alternative to choices.
disabled	Logical, disable or enable buttons, if TRUE users won't be able to select a value.
disabledChoices	Vector of specific choices to disable.

See Also

[checkboxGroupButtons](#)

Examples

```
if (interactive()) {  
  
  library(shiny)  
  library(shinyWidgets)
```

```

# Example 1 ----

ui <- fluidPage(

  radioButton(inputId = "up", label = "Update button :", choices = c("All", "None")),

  checkboxGroupButtons(
    inputId = "btn", label = "Power :",
    choices = c("Nuclear", "Hydro", "Solar", "Wind"),
    selected = "Hydro"
  ),

  verbatimTextOutput(outputId = "res")

)

server <- function(input,output, session){

  observeEvent(input$up, {
    if (input$up == "All"){
      updateCheckboxGroupButtons(session, "btn", selected = c("Nuclear", "Hydro", "Solar", "Wind"))
    } else {
      updateCheckboxGroupButtons(session, "btn", selected = character(0))
    }
  }, ignoreInit = TRUE)

  output$res <- renderPrint({
    input$btn
  })
}

shinyApp(ui = ui, server = server)

# Example 2 ----

library("shiny")
library("shinyWidgets")

ui <- fluidPage(
  checkboxGroupButtons(
    inputId = "somevalue",
    choices = c("A", "B", "C"),
    label = "My label"
  ),

  verbatimTextOutput(outputId = "res"),

  actionButton(inputId = "updatechoices", label = "Random choices"),
  pickerInput(
    inputId = "updateselected", label = "Update selected:",
    choices = c("A", "B", "C"), multiple = TRUE
  )
)

```

```

    ),
    textInput(inputId = "updatelabel", label = "Update label")
  )

  server <- function(input, output, session) {

    output$res <- renderPrint({
      input$somevalue
    })

    observeEvent(input$updatechoices, {
      newchoices <- sample(letters, sample(2:6))
      updateCheckboxGroupButtons(
        session = session, inputId = "somevalue",
        choices = newchoices
      )
      updatePickerInput(
        session = session, inputId = "updateselected",
        choices = newchoices
      )
    })

    observeEvent(input$updateselected, {
      updateCheckboxGroupButtons(
        session = session, inputId = "somevalue",
        selected = input$updateselected
      )
    }, ignoreNULL = TRUE, ignoreInit = TRUE)

    observeEvent(input$updatelabel, {
      updateCheckboxGroupButtons(
        session = session, inputId = "somevalue",
        label = input$updatelabel
      )
    }, ignoreInit = TRUE)

  }

  shinyApp(ui = ui, server = server)
}

```

updateCurrencyInput *Update a Formatted Numeric Input Widget*

Description

Update a Formatted Numeric Input Widget

Usage

```
updateCurrencyInput(
  session,
  inputId,
  label = NULL,
  value = NULL,
  format = NULL
)

updateFormatNumericInput(
  session,
  inputId,
  label = NULL,
  value = NULL,
  format = NULL
)
```

Arguments

session	Standard shiny session.
inputId	The id of the input object.
label	The label to set for the input object.
value	The value to set for the input object.
format	The format to change the input object to.

See Also

Other autonumeric: [autonumericInput\(\)](#), [currencyInput\(\)](#), [updateAutonumericInput\(\)](#)

Examples

```
if (interactive()) {
  library(shiny)
  library(shinyWidgets)

  ui <- fluidPage(
    tags$h2("Currency Input"),

    currencyInput("id1", "Euro:", value = 1234, format = "euro", width = 200, align = "right"),
    verbatimTextOutput("res1"),
    actionButton("bbtn0", "Change Input to Euros"),
    actionButton("bbtn1", "Change Input to Dollars"),
    actionButton("bbtn2", "Change Input to Yen")
  )

  server <- function(input, output, session) {
    output$res1 <- renderPrint(input$id1)
  }
}
```

```

    observeEvent(input$btn0, {
      updateCurrencyInput(
        session = session,
        inputId = "id1",
        label = "Euro:",
        format = "euro"
      )
    })
    observeEvent(input$btn1, {
      updateCurrencyInput(
        session = session,
        inputId = "id1",
        label = "Dollar:",
        format = "dollar"
      )
    })
    observeEvent(input$btn2, {
      updateCurrencyInput(
        session = session,
        inputId = "id1",
        label = "Yen:",
        format = "Japanese"
      )
    })
  }

  shinyApp(ui, server)
}

```

updateKnobInput

Change the value of a knob input on the client

Description

Change the value of a knob input on the client

Usage

```
updateKnobInput(session, inputId, label = NULL, value = NULL, options = NULL)
```

Arguments

session	Standard shiny session.
inputId	The id of the input object.
label	The label to set for the input object.
value	The value to set for the input object.
options	List of additional parameters to update, use knobInput's arguments.

Examples

```

if (interactive()) {

  library("shiny")
  library("shinyWidgets")

  ui <- fluidPage(
    tags$h1("knob update examples"),
    br(),

    fluidRow(

      column(
        width = 6,
        knobInput(
          inputId = "knob1", label = "Update value:",
          value = 75, angleOffset = 90, lineCap = "round"
        ),
        verbatimTextOutput(outputId = "res1"),
        sliderInput(
          inputId = "upknob1", label = "Update knob:",
          min = 0, max = 100, value = 75
        )
      ),

      column(
        width = 6,
        knobInput(
          inputId = "knob2", label = "Update label:",
          value = 50, angleOffset = -125, angleArc = 250
        ),
        verbatimTextOutput(outputId = "res2"),
        textInput(inputId = "upknob2", label = "Update label:")
      )
    )
  )

  server <- function(input, output, session) {

    output$res1 <- renderPrint(input$knob1)

    observeEvent(input$upknob1, {
      updateKnobInput(
        session = session,
        inputId = "knob1",
        value = input$upknob1
      )
    }, ignoreInit = TRUE)

    output$res2 <- renderPrint(input$knob2)
  }
}

```

```
observeEvent(input$upknob2, {
  updateKnobInput(
    session = session,
    inputId = "knob2",
    label = input$upknob2
  )
}, ignoreInit = TRUE)
}

shinyApp(ui = ui, server = server)
}
```

updateMaterialSwitch *Change the value of a materialSwitch input on the client*

Description

Change the value of a materialSwitch input on the client

Usage

```
updateMaterialSwitch(session, inputId, value = NULL)
```

Arguments

session	The session object passed to function given to shinyServer.
inputId	The id of the input object.
value	The value to set for the input object.

See Also

[materialSwitch](#)

updateMultiInput *Change the value of a multi input on the client*

Description

Change the value of a multi input on the client

Usage

```
updateMultiInput(  
  session,  
  inputId,  
  label = NULL,  
  selected = NULL,  
  choices = NULL  
)
```

Arguments

session	The session object passed to function given to shinyServer.
inputId	The id of the input object.
label	The label to set.
selected	The values selected. To select none, use character(0).
choices	The new choices for the input.

Note

Thanks to [Ian Fellows](#) for this one !

See Also

[multiInput](#)

Examples

```
if (interactive()) {  
  
  library(shiny)  
  library(shinyWidgets)  
  
  fruits <- c("Banana", "Blueberry", "Cherry",  
             "Coconut", "Grapefruit", "Kiwi",  
             "Lemon", "Lime", "Mango", "Orange",  
             "Papaya")  
  
  ui <- fluidPage(  
    tags$h2("Multi update"),  
    multiInput(  
      inputId = "my_multi",  
      label = "Fruits :",  
      choices = fruits,  
      selected = "Banana",  
      width = "350px"  
    ),  
    verbatimTextOutput(outputId = "res"),  
    selectInput(  
      inputId = "selected",
```

```
      label = "Update selected:",
      choices = fruits,
      multiple = TRUE
    ),
    textInput(inputId = "label", label = "Update label:")
  )

server <- function(input, output, session) {

  output$res <- renderPrint(input$my_multi)

  observeEvent(input$selected, {
    updateMultiInput(
      session = session,
      inputId = "my_multi",
      selected = input$selected
    )
  })

  observeEvent(input$label, {
    updateMultiInput(
      session = session,
      inputId = "my_multi",
      label = input$label
    )
  }, ignoreInit = TRUE)
}

shinyApp(ui, server)

}
```

updateNoUiSliderInput *Change the value of a no ui slider input on the client*

Description

Change the value of a no ui slider input on the client

Usage

```
updateNoUiSliderInput(
  session,
  inputId,
  value = NULL,
  range = NULL,
  disable = FALSE
)
```

Arguments

session	The session object passed to function given to shinyServer.
inputId	The id of the input object.
value	The new value.
range	The new range, must be of length 2 with c(min,max).
disable	logical, disable or not the slider, if disabled the user can no longer modify the slider value

Examples

```
if (interactive()) {
  demoNoUiSlider("update")
}
```

```
updateNumericInputIcon
```

Change the value of a numeric input icon on the client

Description

Change the value of a numeric input icon on the client

Usage

```
updateNumericInputIcon(
  session,
  inputId,
  label = NULL,
  value = NULL,
  min = NULL,
  max = NULL,
  step = NULL,
  icon = NULL
)
```

Arguments

session	The session object passed to function given to shinyServer. Default is getDefaultReactiveDomain()
inputId	The id of the input object.
label	The label to set for the input object.
value	Initial value.
min	Minimum allowed value
max	Maximum allowed value
step	Interval to use when stepping between min and max
icon	Icon to update, note that you can update icon only if initialized in numericInputIcon .

Value

No value.

Examples

```
library(shiny)
library(shinyWidgets)

ui <- fluidPage(
  numericInputIcon(
    inputId = "id",
    label = "With an icon",
    value = 10,
    icon = icon("percent")
  ),
  actionButton("updateValue", "Update value"),
  actionButton("updateIcon", "Update icon"),
  verbatimTextOutput("value")
)

server <- function(input, output, session) {

  output$value <- renderPrint(input$id)

  observeEvent(input$updateValue, {
    updateNumericInputIcon(
      session = session,
      inputId = "id",
      value = sample.int(100, 1)
    )
  })

  observeEvent(input$updateIcon, {
    i <- sample(c("home", "gears", "dollar", "globe", "sliders"), 1)
    updateNumericInputIcon(
      session = session,
      inputId = "id",
      icon = icon(i)
    )
  })
}

if (interactive())
  shinyApp(ui, server)
```

updateNumericRangeInput

Change the value of a numeric range input

Description

Change the value of a numeric range input

Usage

```
updateNumericRangeInput(session, inputId, label = NULL, value = NULL)
```

Arguments

session	The session object passed to function given to shinyServer.
inputId	The input slot that will be used to access the value.
label	Display label for the control, or NULL for no label.
value	The initial value(s) for the range. A numeric vector of length one will be duplicated to represent the minimum and maximum of the range; a numeric vector of two or more will have its minimum and maximum set the minimum and maximum of the range.

updatePickerInput	<i>Change the value of a select picker input on the client</i>
-------------------	--

Description

Change the value of a picker input on the client

Usage

```
updatePickerInput(
  session,
  inputId,
  label = NULL,
  selected = NULL,
  choices = NULL,
  choicesOpt = NULL,
  options = NULL,
  clearOptions = FALSE
)
```

Arguments

session	The session object passed to function given to shinyServer.
inputId	The id of the input object.
label	Display a text in the center of the switch.
selected	The new selected value (or multiple values if multiple = TRUE). To reset selected value, in case of multiple picker, use character(0).

choices	List of values to select from. If elements of the list are named then that name rather than the value is displayed to the user.
choicesOpt	Options for choices in the dropdown menu.
options	Options for the picker via pickerOptions .
clearOptions	Clear previous options, otherwise the ones set previously are still active.

See Also

[pickerInput](#).

Examples

```
if (interactive()) {  
  
  library("shiny")  
  library("shinyWidgets")  
  
  ui <- fluidPage(  
    tags$h2("Update pickerInput"),  
  
    fluidRow(  
      column(  
        width = 5, offset = 1,  
        pickerInput(  
          inputId = "p1",  
          label = "classic update",  
          choices = rownames(mtcars)  
        )  
      ),  
      column(  
        width = 5,  
        pickerInput(  
          inputId = "p2",  
          label = "disabled update",  
          choices = rownames(mtcars)  
        )  
      )  
    ),  
  
    fluidRow(  
      column(  
        width = 10, offset = 1,  
        sliderInput(  
          inputId = "up",  
          label = "Select between models with mpg greater than :",  
          width = "50%",  
          min = min(mtcars$mpg),  
          max = max(mtcars$mpg),  
          value = min(mtcars$mpg),  
          step = 0.1  
        )  
      )  
    )  
  )  
}
```

```

    )
  )
)

server <- function(input, output, session) {

  observeEvent(input$up, {
    mtcars2 <- mtcars[mtcars$mpg >= input$up, ]

    # Method 1
    updatePickerInput(session = session, inputId = "p1",
                      choices = rownames(mtcars2))

    # Method 2
    disabled_choices <- !rownames(mtcars) %in% rownames(mtcars2)
    updatePickerInput(
      session = session, inputId = "p2",
      choices = rownames(mtcars),
      choicesOpt = list(
        disabled = disabled_choices,
        style = ifelse(disabled_choices,
                      yes = "color: rgba(119, 119, 119, 0.5);",
                      no = "")
      )
    )
  }, ignoreInit = TRUE)
}

shinyApp(ui = ui, server = server)
}

```

updatePrettyCheckbox *Change the value of a pretty checkbox on the client*

Description

Change the value of a pretty checkbox on the client

Usage

```
updatePrettyCheckbox(session, inputId, label = NULL, value = NULL)
```

Arguments

session	The session object passed to function given to shinyServer.
inputId	The id of the input object.
label	The label to set for the input object.
value	The value to set for the input object.

Examples

```
library(shiny)
library(shinyWidgets)

ui <- fluidPage(
  tags$h1("Pretty checkbox update value"),
  br(),

  prettyCheckbox(
    inputId = "checkbox1",
    label = "Update me!",
    shape = "curve",
    thick = TRUE,
    outline = TRUE
  ),
  verbatimTextOutput(outputId = "res1"),
  radioButtons(
    inputId = "update",
    label = "Value to set:",
    choices = c("FALSE", "TRUE")
  )
)

server <- function(input, output, session) {

  output$res1 <- renderPrint(input$checkbox1)

  observeEvent(input$update, {
    updatePrettyCheckbox(
      session = session,
      inputId = "checkbox1",
      value = as.logical(input$update)
    )
  })
}

if (interactive())
  shinyApp(ui, server)
```

updatePrettyCheckboxGroup

Change the value of a pretty checkbox on the client

Description

Change the value of a pretty checkbox on the client

Usage

```
updatePrettyCheckboxGroup(
  session,
  inputId,
  label = NULL,
  choices = NULL,
  selected = NULL,
  inline = FALSE,
  choiceNames = NULL,
  choiceValues = NULL,
  prettyOptions = list()
)
```

Arguments

session	The session object passed to function given to shinyServer.
inputId	The id of the input object.
label	The label to set for the input object.
choices	The choices to set for the input object, updating choices will reset parameters like status, shape, ... on the checkboxes, you can re-specify (or change them) in argument prettyOptions.
selected	The value to set for the input object.
inline	If TRUE, render the choices inline (i.e. horizontally).
choiceNames	The choices names to set for the input object.
choiceValues	The choices values to set for the input object.
prettyOptions	Arguments passed to prettyCheckboxGroup for styling checkboxes. This can be needed if you update choices.

Examples

```
library(shiny)
library(shinyWidgets)

ui <- fluidPage(
  tags$h1("Update pretty checkbox group"),
  br(),

  fluidRow(
    column(
      width = 6,
      prettyCheckboxGroup(
        inputId = "checkgroup1",
        label = "Update my value!",
        choices = month.name[1:4],
        status = "danger",
        icon = icon("remove")
      )
    ),
  ),
```

```

    verbatimTextOutput(outputId = "res1"),
    br(),
    checkboxGroupInput(
      inputId = "update1", label = "Update value :",
      choices = month.name[1:4], inline = TRUE
    )
  ),
  column(
    width = 6,
    prettyCheckboxGroup(
      inputId = "checkgroup2",
      label = "Update my choices!",
      thick = TRUE,
      choices = month.name[1:4],
      animation = "pulse",
      status = "info"
    ),
    verbatimTextOutput(outputId = "res2"),
    br(),
    actionButton(inputId = "update2", label = "Update choices !")
  )
)
)

server <- function(input, output, session) {

  output$res1 <- renderPrint(input$checkgroup1)

  observeEvent(input$update1, {
    if (is.null(input$update1)) {
      selected_ <- character(0) # no choice selected
    } else {
      selected_ <- input$update1
    }
    updatePrettyCheckboxGroup(
      session = session,
      inputId = "checkgroup1",
      selected = selected_
    )
  }, ignoreNULL = FALSE)

  output$res2 <- renderPrint(input$checkgroup2)
  observeEvent(input$update2, {
    updatePrettyCheckboxGroup(
      session = session,
      inputId = "checkgroup2",
      choices = sample(month.name, 4),
      prettyOptions = list(animation = "pulse", status = "info")
    )
  }, ignoreInit = TRUE)
}

```

```
if (interactive())
  shinyApp(ui, server)
```

updatePrettyRadioButtons

Change the value pretty radio buttons on the client

Description

Change the value pretty radio buttons on the client

Usage

```
updatePrettyRadioButtons(
  session,
  inputId,
  label = NULL,
  choices = NULL,
  selected = NULL,
  inline = FALSE,
  choiceNames = NULL,
  choiceValues = NULL,
  prettyOptions = list()
)
```

Arguments

session	The session object passed to function given to shinyServer.
inputId	The id of the input object.
label	The label to set for the input object.
choices	The choices to set for the input object, updating choices will reset parameters like status, shape, ... on the radio buttons, you can re-specify (or change them) in argument prettyOptions.
selected	The value to set for the input object.
inline	If TRUE, render the choices inline (i.e. horizontally).
choiceNames	The choices names to set for the input object.
choiceValues	The choices values to set for the input object.
prettyOptions	Arguments passed to prettyRadioButtons for styling radio buttons. This can be needed if you update choices.

Examples

```

library(shiny)
library(shinyWidgets)

ui <- fluidPage(
  tags$h1("Update pretty radio buttons"),
  br(),

  fluidRow(
    column(
      width = 6,
      prettyRadioButtons(
        inputId = "radio1",
        label = "Update my value!",
        choices = month.name[1:4],
        status = "danger",
        icon = icon("remove")
      ),
      verbatimTextOutput(outputId = "res1"),
      br(),
      radioButtons(
        inputId = "update1", label = "Update value :",
        choices = month.name[1:4], inline = TRUE
      )
    ),
    column(
      width = 6,
      prettyRadioButtons(
        inputId = "radio2",
        label = "Update my choices!",
        thick = TRUE,
        choices = month.name[1:4],
        animation = "pulse",
        status = "info"
      ),
      verbatimTextOutput(outputId = "res2"),
      br(),
      actionButton(inputId = "update2", label = "Update choices !")
    )
  )
)

server <- function(input, output, session) {

  output$res1 <- renderPrint(input$radio1)

  observeEvent(input$update1, {
    updatePrettyRadioButtons(
      session = session,
      inputId = "radio1",
      selected = input$update1
    )
  })
}

```

```

    )
  }, ignoreNULL = FALSE)

  output$res2 <- renderPrint(input$radio2)
  observeEvent(input$update2, {
    updatePrettyRadioButtons(
      session = session,
      inputId = "radio2",
      choices = sample(month.name, 4),
      prettyOptions = list(animation = "pulse",
                           status = "info",
                           shape = "round")
    )
  }, ignoreInit = TRUE)
}

if (interactive())
  shinyApp(ui, server)

```

updatePrettySwitch *Change the value of a pretty switch on the client*

Description

Change the value of a pretty switch on the client

Usage

```
updatePrettySwitch(session, inputId, label = NULL, value = NULL)
```

Arguments

session	The session object passed to function given to shinyServer.
inputId	The id of the input object.
label	The label to set for the input object.
value	The value to set for the input object.

Examples

```

library(shiny)
library(shinyWidgets)

ui <- fluidPage(
  tags$h1("Pretty switch update value"),
  br(),

  prettySwitch(inputId = "switch1", label = "Update me !"),
  verbatimTextOutput(outputId = "res1"),

```

```

radioButtons(
  inputId = "update",
  label = "Value to set:",
  choices = c("FALSE", "TRUE")
)
)

server <- function(input, output, session) {

  output$res1 <- renderPrint(input$switch1)

  observeEvent(input$update, {
    updatePrettySwitch(
      session = session,
      inputId = "switch1",
      value = as.logical(input$update)
    )
  })
}

if (interactive())
  shinyApp(ui, server)

```

updatePrettyToggle *Change the value of a pretty toggle on the client*

Description

Change the value of a pretty toggle on the client

Usage

```
updatePrettyToggle(session, inputId, label = NULL, value = NULL)
```

Arguments

session	The session object passed to function given to shinyServer.
inputId	The id of the input object.
label	The label to set for the input object.
value	The value to set for the input object.

Examples

```

library(shiny)
library(shinyWidgets)

ui <- fluidPage(

```

```

tags$h1("Pretty toggle update value"),
br(),

prettyToggle(
  inputId = "toggle1",
  label_on = "Checked!",
  label_off = "Unchecked..."
),
verbatimTextOutput(outputId = "res1"),
radioButtons(
  inputId = "update",
  label = "Value to set:",
  choices = c("FALSE", "TRUE")
)
)

server <- function(input, output, session) {

  output$res1 <- renderPrint(input$toggle1)

  observeEvent(input$update, {
    updatePrettyToggle(
      session = session,
      inputId = "toggle1",
      value = as.logical(input$update)
    )
  })
}

if (interactive())
  shinyApp(ui, server)

```

updateRadioGroupButtons

Change the value of a radio group buttons input on the client

Description

Change the value of a radio group buttons input on the client

Usage

```

updateRadioGroupButtons(
  session,
  inputId,
  label = NULL,
  choices = NULL,
  selected = NULL,

```

```

    status = "default",
    size = "normal",
    checkIcon = list(),
    choiceNames = NULL,
    choiceValues = NULL,
    disabled = FALSE,
    disabledChoices = NULL
  )

```

Arguments

session	The session object passed to function given to shinyServer.
inputId	The id of the input object.
label	The label to set.
choices	The new choices for the input.
selected	The value selected.
status	Status, only used if choices is not NULL.
size	Size, only used if choices is not NULL.
checkIcon	Icon, only used if choices is not NULL.
choiceNames, choiceValues	List of names and values, an alternative to choices.
disabled	Logical, disable or enable buttons, if TRUE users won't be able to select a value.
disabledChoices	Vector of specific choices to disable.

Examples

```

if (interactive()) {

  library("shiny")
  library("shinyWidgets")

  ui <- fluidPage(
    radioGroupButtons(
      inputId = "somevalue",
      choices = c("A", "B", "C"),
      label = "My label"
    ),

    verbatimTextOutput(outputId = "res"),

    actionButton(inputId = "updatechoices", label = "Random choices"),
    pickerInput(
      inputId = "updateselected", label = "Update selected:",
      choices = c("A", "B", "C"), multiple = FALSE
    ),
    textInput(inputId = "updatelabel", label = "Update label")
  )
}

```

```
server <- function(input, output, session) {  
  
  output$res <- renderPrint({  
    input$somevalue  
  })  
  
  observeEvent(input$updatechoices, {  
    newchoices <- sample(letters, sample(2:6))  
    updateRadioGroupButtons(  
      session = session, inputId = "somevalue",  
      choices = newchoices  
    )  
    updatePickerInput(  
      session = session, inputId = "updateselected",  
      choices = newchoices  
    )  
  })  
  
  observeEvent(input$updateselected, {  
    updateRadioGroupButtons(  
      session = session, inputId = "somevalue",  
      selected = input$updateselected  
    )  
  }, ignoreNULL = TRUE, ignoreInit = TRUE)  
  
  observeEvent(input$updatelabel, {  
    updateRadioGroupButtons(  
      session = session, inputId = "somevalue",  
      label = input$updatelabel  
    )  
  }, ignoreInit = TRUE)  
  
}  
  
shinyApp(ui = ui, server = server)  
  
}
```

updateSearchInput *Change the value of a search input on the client*

Description

Change the value of a search input on the client

Usage

```
updateSearchInput(  
  session,
```

```

    inputId,
    label = NULL,
    value = NULL,
    placeholder = NULL,
    trigger = FALSE
  )

```

Arguments

session	The session object passed to function given to shinyServer.
inputId	The id of the input object.
label	The label to set for the input object.
value	The value to set for the input object.
placeholder	The placeholder to set for the input object.
trigger	Logical, update value server-side as well.

Note

By default, only UI value is updated, use `trigger = TRUE` to update both UI and Server value.

Examples

```

if (interactive()) {

  library(shiny)
  library(shinyWidgets)

  ui <- fluidPage(
    tags$h2("Update searchinput"),
    searchInput(
      inputId = "search", label = "Enter your text",
      placeholder = "A placeholder",
      btnSearch = icon("search"),
      btnReset = icon("remove"),
      width = "450px"
    ),
    br(),
    verbatimTextOutput(outputId = "res"),
    br(),
    textInput(
      inputId = "update_search",
      label = "Update search"
    ),
    checkboxInput(
      inputId = "trigger_search",
      label = "Trigger update search",
      value = TRUE
    )
  )
}

```

```

server <- function(input, output, session) {

  output$res <- renderPrint({
    input$search
  })

  observeEvent(input$update_search, {
    updateSearchInput(
      session = session,
      inputId = "search",
      value = input$update_search,
      trigger = input$trigger_search
    )
  }, ignoreInit = TRUE)
}

shinyApp(ui, server)

}

```

updateSliderTextInput *Change the value of a slider text input on the client*

Description

Change the value of a slider text input on the client

Usage

```

updateSliderTextInput(
  session,
  inputId,
  label = NULL,
  selected = NULL,
  choices = NULL,
  from_fixed = NULL,
  to_fixed = NULL
)

```

Arguments

session	The session object passed to function given to shinyServer.
inputId	The id of the input object.
label	The label to set.
selected	The values selected.
choices	The new choices for the input.
from_fixed	Fix the left handle (or single handle).
to_fixed	Fix the right handle.

See Also[sliderTextInput](#)**Examples**

```

if (interactive()) {
  library("shiny")
  library("shinyWidgets")

  ui <- fluidPage(
    br(),
    sliderTextInput(
      inputId = "mySlider",
      label = "Pick a month :",
      choices = month.abb,
      selected = "Jan"
    ),
    verbatimTextOutput(outputId = "res"),
    radioButtons(
      inputId = "up",
      label = "Update choices:",
      choices = c("Abbreviations", "Full names")
    )
  )

  server <- function(input, output, session) {
    output$res <- renderPrint(str(input$mySlider))

    observeEvent(input$up, {
      choices <- switch(
        input$up,
        "Abbreviations" = month.abb,
        "Full names" = month.name
      )
      updateSliderTextInput(
        session = session,
        inputId = "mySlider",
        choices = choices
      )
    }, ignoreInit = TRUE)
  }

  shinyApp(ui = ui, server = server)
}

```

updateSpectrumInput *Change the value of a spectrum input on the client*

Description

Change the value of a spectrum input on the client

Usage

```
updateSpectrumInput(session, inputId, selected)
```

Arguments

<code>session</code>	The session object passed to function given to shinyServer.
<code>inputId</code>	The id of the input object.
<code>selected</code>	The value to select.

Examples

```
if (interactive()) {

  library("shiny")
  library("shinyWidgets")

  ui <- fluidPage(
    tags$h1("Spectrum color picker"),

    br(),

    spectrumInput(
      inputId = "myColor",
      label = "Pick a color:",
      choices = list(
        list('black', 'white', 'blanchedalmond', 'steelblue', 'forestgreen')
      )
    ),
    verbatimTextOutput(outputId = "res"),
    radioButtons(
      inputId = "update", label = "Update:",
      choices = c(
        'black', 'white', 'blanchedalmond', 'steelblue', 'forestgreen'
      )
    )
  )

  server <- function(input, output, session) {

    output$res <- renderPrint(input$myColor)

    observeEvent(input$update, {
      updateSpectrumInput(session = session, inputId = "myColor", selected = input$update)
    }, ignoreInit = TRUE)

  }

  shinyApp(ui, server)
```

```
}
```

updateSwitchInput	<i>Change the value of a switch input on the client</i>
-------------------	---

Description

Change the value of a switch input on the client

Usage

```
updateSwitchInput(  
  session,  
  inputId,  
  value = NULL,  
  label = NULL,  
  onLabel = NULL,  
  offLabel = NULL,  
  onStatus = NULL,  
  offStatus = NULL,  
  disabled = NULL  
)
```

Arguments

session	The session object passed to function given to shinyServer.
inputId	The id of the input object.
value	The value to set for the input object.
label	The label to set for the input object.
onLabel	The onLabel to set for the input object.
offLabel	The offLabel to set for the input object.
onStatus	The onStatus to set for the input object.
offStatus	The offStatus to set for the input object.
disabled	Logical, disable state.

See Also

[switchInput](#)

Examples

```

if (interactive()) {
  library("shiny")
  library("shinyWidgets")

  ui <- fluidPage(
    tags$h1("Update", tags$code("switchInput")),
    br(),
    fluidRow(
      column(
        width = 4,
        panel(
          switchInput(inputId = "switch1"),
          verbatimTextOutput(outputId = "resup1"),
          tags$div(
            class = "btn-group",
            actionButton(
              inputId = "updatevaluetrue",
              label = "Set to TRUE"
            ),
            actionButton(
              inputId = "updatevaluefalse",
              label = "Set to FALSE"
            )
          )
        ),
        heading = "Update value"
      )
    ),

    column(
      width = 4,
      panel(
        switchInput(inputId = "switch2",
                    label = "My label"),
        verbatimTextOutput(outputId = "resup2"),
        textInput(inputId = "updatelabeltext",
                  label = "Update label:"),
        heading = "Update label"
      )
    ),

    column(
      width = 4,
      panel(
        switchInput(
          inputId = "switch3",
          onLabel = "Yeaah",
          offLabel = "Noooo"
        ),
        verbatimTextOutput(outputId = "resup3"),
        fluidRow(column(

```

```

        width = 6,
        textInput(inputId = "updateonLabel",
                  label = "Update onLabel:")
    ),
    column(
        width = 6,
        textInput(inputId = "updateoffLabel",
                  label = "Update offLabel:")
    )),
    heading = "Update onLabel & offLabel"
)
)
),
fluidRow(column(
    width = 4,
    panel(
        switchInput(inputId = "switch4"),
        verbatimTextOutput(outputId = "resup4"),
        fluidRow(
            column(
                width = 6,
                pickerInput(
                    inputId = "updateonStatus",
                    label = "Update onStatus:",
                    choices = c("default", "primary", "success",
                               "info", "warning", "danger")
                )
            ),
            column(
                width = 6,
                pickerInput(
                    inputId = "updateoffStatus",
                    label = "Update offStatus:",
                    choices = c("default", "primary", "success",
                               "info", "warning", "danger")
                )
            )
        ),
        heading = "Update onStatus & offStatusr"
    )
),
column(
    width = 4,
    panel(
        switchInput(inputId = "switch5"),
        verbatimTextOutput(outputId = "resup5"),
        checkboxInput(
            inputId = "disabled",
            label = "Disabled",
            value = FALSE
        ),
    ),

```

```

        heading = "Disabled"
      )
    ))
  )

server <- function(input, output, session) {
  # Update value
  observeEvent(input$updatevaluetrue, {
    updateSwitchInput(session = session,
                      inputId = "switch1",
                      value = TRUE)
  })
  observeEvent(input$updatevaluefalse, {
    updateSwitchInput(session = session,
                      inputId = "switch1",
                      value = FALSE)
  })
  output$resup1 <- renderPrint({
    input$switch1
  })

  # Update label
  observeEvent(input$updatelabeltext, {
    updateSwitchInput(
      session = session,
      inputId = "switch2",
      label = input$updatelabeltext
    )
  }, ignoreInit = TRUE)
  output$resup2 <- renderPrint({
    input$switch2
  })

  # Update onLabel & offLabel
  observeEvent(input$updateonLabel, {
    updateSwitchInput(
      session = session,
      inputId = "switch3",
      onLabel = input$updateonLabel
    )
  }, ignoreInit = TRUE)
  observeEvent(input$updateoffLabel, {
    updateSwitchInput(
      session = session,
      inputId = "switch3",
      offLabel = input$updateoffLabel
    )
  }, ignoreInit = TRUE)
  output$resup3 <- renderPrint({
    input$switch3
  })
}

```

```
  })

  # Update onStatus & offStatus
  observeEvent(input$updateonStatus, {
    updateSwitchInput(
      session = session,
      inputId = "switch4",
      onStatus = input$updateonStatus
    )
  }, ignoreInit = TRUE)
  observeEvent(input$updateoffStatus, {
    updateSwitchInput(
      session = session,
      inputId = "switch4",
      offStatus = input$updateoffStatus
    )
  }, ignoreInit = TRUE)
  output$resup4 <- renderPrint({
    input$switch4
  })

  # Disabled
  observeEvent(input$disabled, {
    updateSwitchInput(
      session = session,
      inputId = "switch5",
      disabled = input$disabled
    )
  }, ignoreInit = TRUE)
  output$resup5 <- renderPrint({
    input$switch5
  })
}

shinyApp(ui = ui, server = server)
}
```

updateTextInputIcon *Change the value of a text input icon on the client*

Description

Change the value of a text input icon on the client

Usage

```
updateTextInputIcon(
  session,
  inputId,
  label = NULL,
  value = NULL,
  placeholder = NULL,
  icon = NULL
)
```

Arguments

session	The session object passed to function given to shinyServer. Default is getDefaultReactiveDomain()
inputId	The id of the input object.
label	The label to set for the input object.
value	Initial value.
placeholder	A character string giving the user a hint as to what can be entered into the control. Internet Explorer 8 and 9 do not support this option.
icon	Icon to update, note that you can update icon only if initialized in textInputIcon .

Value

No value.

Examples

```
library(shiny)
library(shinyWidgets)

ui <- fluidPage(
  textInputIcon(
    inputId = "id",
    label = "With an icon",
    icon = icon("user-circle-o")
  ),
  actionButton("updateValue", "Update value"),
  actionButton("updateIcon", "Update icon"),
  verbatimTextOutput("value")
)

server <- function(input, output, session) {

  output$value <- renderPrint(input$id)

  observeEvent(input$updateValue, {
    updateTextInputIcon(
      session = session,
      inputId = "id",
      value = paste(sample(letters, 8), collapse = "")
    )
  })
}
```

```
    )
  })

  observeEvent(input$updateIcon, {
    i <- sample(c("home", "gears", "dollar", "globe", "sliders"), 1)
    updateTextInputIcon(
      session = session,
      inputId = "id",
      icon = icon(i)
    )
  })
}

if (interactive())
  shinyApp(ui, server)
```

updateVerticalTabsetPanel

Update selected vertical tab

Description

Update selected vertical tab

Usage

```
updateVerticalTabsetPanel(session, inputId, selected = NULL)
```

Arguments

session	The session object passed to function given to shinyServer.
inputId	The id of the verticalTabsetPanel object.
selected	The name of the tab to make active.

See Also

[verticalTabsetPanel](#)

Examples

```
if (interactive()) {

  library(shiny)
  library(shinyWidgets)

  ui <- fluidPage(
    fluidRow(
```

```

column(
  width = 10, offset = 1,
  tags$h2("Update vertical tab panel example:"),
  verbatimTextOutput("res"),
  radioButtons(
    inputId = "update", label = "Update selected:",
    choices = c("Title 1", "Title 2", "Title 3"),
    inline = TRUE
  ),
  verticalTabsetPanel(
    id = "TABS",
    verticalTabPanel(
      title = "Title 1", icon = icon("home", "fa-2x"),
      "Content panel 1"
    ),
    verticalTabPanel(
      title = "Title 2", icon = icon("map", "fa-2x"),
      "Content panel 2"
    ),
    verticalTabPanel(
      title = "Title 3", icon = icon("rocket", "fa-2x"),
      "Content panel 3"
    )
  )
)
)
)

server <- function(input, output, session) {
  output$res <- renderPrint(input$TABS)
  observeEvent(input$update, {
    shinyWidgets::updateVerticalTabsetPanel(
      session = session,
      inputId = "TABS",
      selected = input$update
    )
  }, ignoreInit = TRUE)
}

shinyApp(ui, server)
}

```

 useArgonDash

Use 'argonDash' in 'shiny'

Description

Allow to use functions from 'argonDash' into a classic 'shiny' app, specifically argonCard, argonTabSet and argonInfoCard.

Usage

```
useArgonDash()
```

Examples

```
if (interactive()) {

  library(shiny)
  library(argonR)
  library(argonDash)
  library(shinyWidgets)

  ui <- fluidPage(
    h1("Import argonDash elements inside shiny!", align = "center"),
    h5("Don't need any sidebar, navbar, ...", align = "center"),
    h5("Only focus on basic elements for a pure interface", align = "center"),

    # use this in non dashboard app
    setBackgroundColor(color = "ghostwhite"),
    useArgonDash(),

    fluidRow(
      column(
        width = 6,
        argonCard(
          status = "primary",
          width = 12,
          title = "Card 1",
          hover_lift = TRUE,
          shadow = TRUE,
          icon = "check-bold",
          src = "#",
          "Argon is a great free UI package based on Bootstrap 4
            that includes the most important components and features."
        )
      ),
      column(
        width = 6,
        argonTabSet(
          id = "tab-1",
          card_wrapper = TRUE,
          horizontal = TRUE,
          circle = FALSE,
          size = "sm",
          width = 6,
          iconList = list("cloud-upload-96", "bell-55", "calendar-grid-58"),
          argonTab(
            tabName = "Tab 1",
            active = TRUE,
            sliderInput(
              "number",
              "Number of observations:"
            )
          )
        )
      )
    )
  )
}
```

```

        min = 0,
        max = 100,
        value = 50
    ),
    uiOutput("progress")
),
argonTab(
  tabName = "Tab 2",
  active = FALSE,
  prettyRadioButtons(
    inputId = "dist",
    inline = TRUE,
    animation = "pulse",
    label = "Distribution type:",
    c("Normal" = "norm",
      "Uniform" = "unif",
      "Log-normal" = "lnorm",
      "Exponential" = "exp")
  ),
  plotOutput("distPlot")
),
argonTab(
  tabName = "Tab 3",
  active = FALSE,
  numericInput("valueBox", "Second value box:", 10, min = 1, max = 100)
)
)
)
),
br(),
fluidRow(
  argonInfoCard(
    value = "350,897",
    title = "TRAFFIC",
    stat = 3.48,
    stat_icon = "arrow-up",
    description = "Since last month",
    icon = "chart-bar",
    icon_background = "danger",
    hover_lift = TRUE
  ),
  argonInfoCard(
    value = textOutput("value"),
    title = "NEW USERS",
    stat = -3.48,
    stat_icon = "arrow-down",
    description = "Since last week",
    icon = "chart-pie",
    icon_background = "warning",
    shadow = TRUE
  ),
  argonInfoCard(
    value = "924",

```

```

    title = "SALES",
    stat = -1.10,
    stat_icon = "arrow-down",
    description = "Since yesterday",
    icon = "users",
    icon_background = "yellow",
    background_color = "default"
  ),
  argonInfoCard(
    value = "49,65%",
    title = "PERFORMANCE",
    stat = 12,
    stat_icon = "arrow-up",
    description = "Since last month",
    icon = "percent",
    icon_background = "info",
    gradient = TRUE,
    background_color = "orange",
    hover_lift = TRUE
  )
)
)
)

server <- function(input, output, session) {

  output$progress <- renderUI({
    argonProgress(value = input$number, status = "danger", text = "Custom Text")
  })

  output$distPlot <- renderPlot({
    dist <- switch(input$dist,
      norm = rnorm,
      unif = runif,
      lnorm = rlnorm,
      exp = rexp,
      rnorm)

    hist(dist(500))
  })

  output$value <- renderText(input$valueBox)

}

shinyApp(ui, server)

}

```

Description

Allow to use functions from 'bs4Dash' into a classic 'shiny' app, specifically bs4ValueBox, bs4InfoBox and bs4Card.

Usage

```
useBs4Dash(old_school = FALSE)
```

Arguments

old_school FALSE by default. Experimental.

Examples

```
if (interactive()) {  
  
  library(shiny)  
  library(bs4Dash)  
  library(shinyWidgets)  
  
  ui <- fluidPage(  
    h1("Import bs4Dash elements inside shiny!", align = "center"),  
    h5("Don't need any sidebar, navbar, ...", align = "center"),  
    h5("Only focus on basic elements for a pure interface", align = "center"),  
  
    # use this in non dashboard app  
    setBackgroundColor(color = "ghostwhite"),  
    useBs4Dash(old_school = FALSE),  
  
    # infoBoxes  
    fluidRow(  
      bs4InfoBox(  
        title = "Messages",  
        value = 1410,  
        icon = "envelope"  
      ),  
      bs4InfoBox(  
        title = "Bookmarks",  
        status = "info",  
        value = 240,  
        icon = "bookmark"  
      ),  
      bs4InfoBox(  
        title = "Comments",  
        gradientColor = "danger",  
        value = 41410,  
        icon = "comments"  
      )  
    ),  
  
    # valueBoxes  
    fluidRow(  

```

```

    bs4ValueBox(
      value = uiOutput("orderNum"),
      subtitle = "New Orders",
      icon = "credit-card",
      href = "http://google.com"
    ),
    bs4ValueBox(
      value = "60%",
      subtitle = "Approval Rating",
      icon = "line-chart",
      status = "success"
    ),
    bs4ValueBox(
      value = htmlOutput("progress"),
      subtitle = "Progress",
      icon = "users",
      status = "danger"
    )
  ),
  # Boxes
  fluidRow(
    bs4Card(
      status = "primary",
      sliderInput("orders", "Orders", min = 1, max = 2000, value = 650),
      selectInput(
        "progress",
        "Progress",
        choices = c(
          "0%" = 0, "20%" = 20, "40%" = 40,
          "60%" = 60, "80%" = 80, "100%" = 100
        )
      )
    ),
    bs4Card(
      title = "Histogram box title",
      status = "warning",
      solidHeader = TRUE,
      collapsible = TRUE,
      plotOutput("plot", height = 250)
    )
  )
)

server <- function(input, output, session) {

  output$orderNum <- renderText({
    prettyNum(input$orders, big.mark=",")
  })

  output$orderNum2 <- renderText({
    prettyNum(input$orders, big.mark=",")
  })
}

```

```

output$progress <- renderUI({
  tagList(input$progress, tags$sup(style="font-size: 20px", "%"))
})

output$progress2 <- renderUI({
  paste0(input$progress)
})

output$plot <- renderPlot({
  hist(rnorm(input$orders))
})

}

shinyApp(ui, server)

}

```

useShinydashboard *Use 'shinydashboard' in 'shiny'*

Description

Allow to use functions from 'shinydashboard' into a classic 'shiny' app, specifically valueBox, infoBox and box.

Usage

```
useShinydashboard()
```

Examples

```

if (interactive()) {

  library(shiny)
  library(shinydashboard)
  library(shinyWidgets)

  # example taken from ?box

  ui <- fluidPage(
    tags$h2("Classic shiny"),

    # use this in non shinydashboard app
    setBackgroundColor(color = "ghostwhite"),
    useShinydashboard(),
    # -----

```

```

# infoBoxes
fluidRow(
  infoBox(
    "Orders", uiOutput("orderNum2"), "Subtitle", icon = icon("credit-card")
  ),
  infoBox(
    "Approval Rating", "60%", icon = icon("line-chart"), color = "green",
    fill = TRUE
  ),
  infoBox(
    "Progress", uiOutput("progress2"), icon = icon("users"), color = "purple"
  )
),

# valueBoxes
fluidRow(
  valueBox(
    uiOutput("orderNum"), "New Orders", icon = icon("credit-card"),
    href = "http://google.com"
  ),
  valueBox(
    tagList("60", tags$sup(style="font-size: 20px", "%")),
    "Approval Rating", icon = icon("line-chart"), color = "green"
  ),
  valueBox(
    htmlOutput("progress"), "Progress", icon = icon("users"), color = "purple"
  )
),

# Boxes
fluidRow(
  box(status = "primary",
    sliderInput("orders", "Orders", min = 1, max = 2000, value = 650),
    selectInput("progress", "Progress",
      choices = c("0%" = 0, "20%" = 20, "40%" = 40, "60%" = 60, "80%" = 80,
        "100%" = 100)
    )
  ),
  box(title = "Histogram box title",
    status = "warning", solidHeader = TRUE, collapsible = TRUE,
    plotOutput("plot", height = 250)
  )
)

server <- function(input, output, session) {

  output$orderNum <- renderText({
    prettyNum(input$orders, big.mark=",")
  })

  output$orderNum2 <- renderText({
    prettyNum(input$orders, big.mark=",")
  })
}

```

```

    })

    output$progress <- renderUI({
      tagList(input$progress, tags$sup(style="font-size: 20px", "%"))
    })

    output$progress2 <- renderUI({
      paste0(input$progress, "%")
    })

    output$plot <- renderPlot({
      hist(rnorm(input$orders))
    })
  }

  shinyApp(ui, server)
}

```

useShinydashboardPlus *Use 'shinydashboardPlus' in 'shiny'*

Description

Allow to use functions from 'shinydashboardPlus' into a classic 'shiny' app.

Usage

```
useShinydashboardPlus()
```

Examples

```

if (interactive()) {

  library(shiny)
  library(shinydashboard)
  library(shinydashboardPlus)
  library(shinyWidgets)

  # example taken from ?box

  ui <- fluidPage(
    tags$h2("Classic shiny"),

    # use this in non shinydashboardPlus app
    useShinydashboardPlus(),
    setBackgroundColor(color = "ghostwhite"),

```

```
# boxPlus
box(
  title = "Improved box",
  closable = TRUE,
  width = 12,
  status = "warning",
  solidHeader = FALSE,
  collapsible = TRUE,
  label = boxLabel(
    text = 1,
    status = "danger",
    style = "circle"
  ),
),
dropdownMenu = boxDropdown(
  boxDropdownItem("Link to google", href = "http://www.google.com"),
  boxDropdownItem("item 2", href = "#"),
  dropdownDivider(),
  boxDropdownItem("item 3", href = "#", icon = icon("th"))
),
sidebar = boxSidebar(
  startOpen = TRUE,
  id = "mycardsidebar",
  sliderInput(
    "obs",
    "Number of observations:",
    min = 0,
    max = 1000,
    value = 500
  )
),
plotOutput("distPlot")
),

br(),

# extra elements
fluidRow(
  column(
    width = 6,
    timelineBlock(
      reversed = FALSE,
      timelineEnd(color = "red"),
      timelineLabel(2018, color = "teal"),
      timelineItem(
        title = "Item 1",
        icon = icon("gears"),
        color = "olive",
        time = "now",
        footer = "Here is the footer",
        "This is the body"
      ),
    ),
    timelineItem(
```

```

      title = "Item 2",
      border = FALSE
    ),
    timelineLabel(2015, color = "orange"),
    timelineItem(
      title = "Item 3",
      icon = icon("paint-brush"),
      color = "maroon",
      timelineItemMedia(image = "https://placeholder.it/150x100"),
      timelineItemMedia(image = "https://placeholder.it/150x100")
    ),
    timelineStart(color = "purple")
  )
),
column(
  width = 6,
  box(
    title = "Box with boxPad containing inputs",
    status = "warning",
    width = 12,
    fluidRow(
      column(
        width = 6,
        boxPad(
          color = "gray",
          sliderInput(
            "obs2",
            "Number of observations:",
            min = 0, max = 1000, value = 500
          ),
          checkboxGroupInput(
            "variable",
            "Variables to show:",
            c(
              "Cylinders" = "cyl",
              "Transmission" = "am",
              "Gears" = "gear"
            )
          )
        ),
      ),
      knobInput(
        inputId = "myKnob",
        skin = "tron",
        readOnly = TRUE,
        label = "Display previous:",
        value = 50,
        min = -100,
        displayPrevious = TRUE,
        fgColor = "#428BCA",
        inputColor = "#428BCA"
      )
    )
  )
),

```

```

        column(
          width = 6,
          plotOutput("distPlot2", height = "200px"),
          tableOutput("data")
        )
      )
    )
  )
}

server <- function(input, output, session) {

  output$distPlot <- renderPlot({
    hist(rnorm(input$obs))
  })

  output$distPlot2 <- renderPlot({
    hist(rnorm(input$obs2))
  })

  output$data <- renderTable({
    head(mtcars[, c("mpg", input$variable), drop = FALSE])
  }, rownames = TRUE)

}

shinyApp(ui, server)

}

```

useSweetAlert

Load Sweet Alert dependencies

Description

This function isn't necessary for `sendSweetAlert`, `confirmSweetAlert`, `inputSweetAlert` (except if you want to use a theme other than the default one), but is still needed for `progressSweetAlert`.

Usage

```

useSweetAlert(
  theme = c("sweetalert2", "minimal", "dark", "bootstrap-4", "material-ui", "bulma",
    "borderless"),
  ie = FALSE
)

```

Arguments

<code>theme</code>	Theme to modify alerts appearance.
<code>ie</code>	Add a polyfill to work in Internet Explorer.

See Also

[sendSweetAlert](#), [confirmSweetAlert](#), [inputSweetAlert](#), [closeSweetAlert](#).

Examples

```
if (interactive()) {  
  
  library(shiny)  
  library(shinyWidgets)  
  
  ui <- fluidPage(  
  
    useSweetAlert("borderless", ie = TRUE),  
  
    tags$h2("Sweet Alert examples (with custom theme)"),  
    actionButton(  
      inputId = "success",  
      label = "Launch a success sweet alert",  
      icon = icon("check")  
    ),  
    actionButton(  
      inputId = "error",  
      label = "Launch an error sweet alert",  
      icon = icon("remove")  
    ),  
    actionButton(  
      inputId = "sw_html",  
      label = "Sweet alert with HTML",  
      icon = icon("thumbs-up")  
    )  
  )  
}  
  
server <- function(input, output, session) {  
  
  observeEvent(input$success, {  
    show_alert(  
      title = "Success !!",  
      text = "All in order",  
      type = "success"  
    )  
  })  
  
  observeEvent(input$error, {  
    show_alert(  
      title = "Error !!",  
      text = "It's broken...",  
      type = "error"  
    )  
  })  
  
  observeEvent(input$sw_html, {  
    show_alert(  

```

```

    title = NULL,
    text = tags$span(
      tags$h3("With HTML tags",
        style = "color: steelblue;"),
      "In", tags$b("bold"), "and", tags$em("italic"),
      tags$br(),
      "and",
      tags$br(),
      "line",
      tags$br(),
      "breaks",
      tags$br(),
      "and an icon", icon("thumbs-up")
    ),
    html = TRUE
  )
})

}

shinyApp(ui, server)
}

```

useTablerDash

Use 'tablerDash' in 'shiny'

Description

Allow to use functions from 'tablerDash' (<https://github.com/RinteRface/tablerDash>) into a classic 'shiny' app.

Usage

```
useTablerDash()
```

Examples

```

if (interactive()) {
  library(shiny)
  library(tablerDash)
  library(shinyWidgets)

  profileCard <- tablerProfileCard(
    width = 12,
    title = "Peter Richards",
    subtitle = "Big belly rude boy, million
      dollar hustler. Unemployed.",
    background = "https://preview.tabler.io/demo/photos/ilnur-kalimullin-218996-500.jpg",
    src = "https://preview.tabler.io/demo/faces/male/16.jpg",

```

```

tablerSocialLinks(
  tablerSocialLink(
    name = "facebook",
    href = "https://www.facebook.com",
    icon = "facebook"
  ),
  tablerSocialLink(
    name = "twitter",
    href = "https://www.twitter.com",
    icon = "twitter"
  )
)
)
)

```

```

plotCard <- tablerCard(
  title = "Plots",
  zoomable = TRUE,
  closable = TRUE,
  options = tagList(
    switchInput(
      inputId = "enable_distPlot",
      label = "Plot?",
      value = TRUE,
      onStatus = "success",
      offStatus = "danger"
    )
  ),
  plotOutput("distPlot"),
  status = "info",
  statusSide = "left",
  width = 12,
  footer = tagList(
    column(
      width = 12,
      align = "center",
      sliderInput(
        "obs",
        "Number of observations:",
        min = 0,
        max = 1000,
        value = 500
      )
    )
  )
)
)
)
)

```

```

# app
shiny::shinyApp(
  ui = fluidPage(
    useTablerDash(),
    chooseSliderSkin("Nice"),

```

```
h1("Import tablerDash elements inside shiny!", align = "center"),
h5("Don't need any sidebar, navbar, ...", align = "center"),
h5("Only focus on basic elements for a pure interface", align = "center"),

fluidRow(
  column(
    width = 3,
    profileCard,
    tablerStatCard(
      value = 43,
      title = "Followers",
      trend = -10,
      width = 12
    ),
    tablerAvatarList(
      stacked = TRUE,
      tablerAvatar(
        name = "DG",
        size = "xxl"
      ),
      tablerAvatar(
        name = "DG",
        color = "orange"
      ),
      tablerAvatar(
        name = "DG",
        status = "warning"
      ),
      tablerAvatar(url = "https://image.flaticon.com/icons/svg/145/145852.svg")
    )
  ),
  column(
    width = 6,
    plotCard
  ),
  column(
    width = 3,
    tablerCard(
      width = 12,
      tablerTimeline(
        tablerTimelineItem(
          title = "Item 1",
          status = "green",
          date = "now"
        ),
        tablerTimelineItem(
          title = "Item 2",
          status = NULL,
          date = "yesterday",
          "Lorem ipsum dolor sit amet,
            consectetur adipisicing elit."
        )
      )
    )
  )
)
```

```

    )
  ),
  tabletInfoCard(
    value = "132 sales",
    status = "danger",
    icon = "dollar-sign",
    description = "12 waiting payments",
    width = 12
  ),
  numericInput(
    inputId = "totalStorage",
    label = "Enter storage capacity",
    value = 1000,
  uiOutput("info"),
  knobInput(
    inputId = "knob",
    width = "50%",
    label = "Progress value:",
    value = 10,
    min = 0,
    max = 100,
    skin = "tron",
    displayPrevious = TRUE,
    fgColor = "#428BCA",
    inputColor = "#428BCA"
  ),
  uiOutput("progress")
)
)
),
server = function(input, output) {

  output$distPlot <- renderPlot({
    if (input$enable_distPlot) hist(rnorm(input$obs))
  })

  output$info <- renderUI({
    tabletInfoCard(
      width = 12,
      value = paste0(input$totalStorage, "GB"),
      status = "success",
      icon = "database",
      description = "Total Storage Capacity"
    )
  })

  output$progress <- renderUI({
    tagList(
      tabletProgress(value = input$knob, size = "xs", status = "yellow"),
      tabletProgress(value = input$knob, status = "red", size = "sm")
    )
  })
}

```

```

    }
  )
}

```

vertical-tab

Vertical tab panel

Description

Vertical tab panel

Usage

```

verticalTabsetPanel(
  ...,
  selected = NULL,
  id = NULL,
  color = "#112446",
  contentWidth = 9,
  menuSide = "left"
)

verticalTabPanel(title, ..., value = title, icon = NULL, box_height = "160px")

```

Arguments

...	For <code>verticalTabsetPanel</code> , <code>verticalTabPanel</code> to include, and for the later, UI elements.
selected	The value (or, if none was supplied, the <code>title</code>) of the tab that should be selected by default. If <code>NULL</code> , the first tab will be selected.
id	If provided, you can use <code>input\$id</code> in your server logic to determine which of the current tabs is active. The value will correspond to the <code>value</code> argument that is passed to <code>verticalTabPanel</code> .
color	Color for the tab panels.
contentWidth	Width of the content panel (must be between 1 and 12), menu width will be <code>12 - contentWidth</code> .
menuSide	Side for the menu: right or left.
title	Display title for tab.
value	Not used yet.
icon	Optional icon to appear on the tab.
box_height	Height for the title box.

See Also

[updateVerticalTabsetPanel](#) for updating selected tabs.

Examples

```
if (interactive()) {  
  
  library(shiny)  
  library(shinyWidgets)  
  
  ui <- fluidPage(  
    fluidRow(  
      column(  
        width = 10, offset = 1,  
        tags$h2("Vertical tab panel example"),  
        verticalTabsetPanel(  
          verticalTabPanel(  
            title = "Title 1", icon = icon("home", "fa-2x"),  
            "Content panel 1"  
          ),  
          verticalTabPanel(  
            title = "Title 2", icon = icon("map", "fa-2x"),  
            "Content panel 2"  
          ),  
          verticalTabPanel(  
            title = "Title 3", icon = icon("rocket", "fa-2x"),  
            "Content panel 3"  
          )  
        )  
      )  
    )  
  )  
  )  
  )  
  
  server <- function(input, output, session) {  
  
  }  
  
  shinyApp(ui, server)  
  
}
```

wNumbFormat

Format numbers in noUiSliderInput

Description

Format numbers in noUiSliderInput

Usage

```
wNumbFormat(  
  decimals = NULL,
```

```

    mark = NULL,
    thousand = NULL,
    prefix = NULL,
    suffix = NULL,
    negative = NULL
  )

```

Arguments

decimals	The number of decimals to include in the result. Limited to 7.
mark	The decimal separator. Defaults to '.' if thousand isn't already set to '.'.
thousand	Separator for large numbers. For example: ' ' would result in a formatted number of 1 000 000.
prefix	A string to prepend to the number. Use cases include prefixing with money symbols such as '\$' or the euro sign.
suffix	A number to append to a number. For example: ', -'.
negative	The prefix for negative values. Defaults to '- '.

Value

a named list.

Note

Performed via wNumb JavaScript library : <https://refreshless.com/wnumb/>.

Examples

```

if (interactive()) {

  library( shiny )
  library( shinyWidgets )

  ui <- fluidPage(
    tags$h3("Format numbers"),
    tags$br(),

    noUiSliderInput(
      inputId = "form1",
      min = 0, max = 10000,
      value = 800,
      format = wNumbFormat(decimals = 3,
                           thousand = ".",
                           suffix = " (US $)")
    ),
    verbatimTextOutput(outputId = "res1"),

    tags$br(),

    noUiSliderInput(

```

```
    inputId = "form2",
    min = 1988, max = 2018,
    value = 1988,
    format = wNumbFormat(decimals = 0,
                          thousand = "",
                          prefix = "Year: ")
  ),
  verbatimTextOutput(outputId = "res2"),

  tags$br()
)

server <- function(input, output, session) {

  output$res1 <- renderPrint(input$form1)
  output$res2 <- renderPrint(input$form2)

}

shinyApp(ui, server)

}
```

Index

- * **autonumeric**
 - autonumericInput, 14
 - currencyInput, 39
 - updateAutonumericInput, 140
 - updateCurrencyInput, 149
- * **datasets**
 - animations, 13
- actionBtnn, 4, 43, 46, 47
- actionGroupButtons, 5
- addSpinner, 7
- airDatepicker, 8
- airDatepickerInput, 139
- airDatepickerInput (airDatepicker), 8
- airMonthpickerInput (airDatepicker), 8
- airYearpickerInput (airDatepicker), 8
- alert (bootstrap-utils), 24
- animateOptions, 12, 47
- animations, 12, 13
- appendVerticalTab, 13
- ask_confirmation, 117
- ask_confirmation
 - (sweetalert-confirmation), 129
- autonumericInput, 14, 39, 41, 140, 150
- awesomeCheckbox, 20, 142
- awesomeCheckboxGroup, 21, 143, 144
- awesomeRadio, 22, 145
- bootstrap-utils, 24
- checkboxGroupButtons, 27, 147
- checkboxGroupInput, 28
- chooseSliderSkin, 29, 114
- circleButton, 31
- closeSweetAlert, 32, 57, 117, 126, 130, 194
- colorPickr, 33
- colorSelectorDrop (colorSelectorInput), 37
- colorSelectorExample
 - (colorSelectorInput), 37
- colorSelectorInput, 37
- confirmSweetAlert, 57, 126, 194
- confirmSweetAlert
 - (sweetalert-confirmation), 129
- currencyInput, 18, 39, 140, 150
- demoAirDatepicker, 11, 41
- demoNoUiSlider, 42, 65
- demoNumericRange, 43
- disableDropMenu
 - (drop-menu-interaction), 44
- downloadBtnn, 4, 43
- drop-menu-interaction, 44
- dropdown, 46, 49
- dropdownButton, 48
- dropMenu, 51, 53
- dropMenu interaction, 51
- dropMenuOptions, 51, 53
- enableDropMenu (drop-menu-interaction), 44
- execute_safely, 54
- formatNumericInput (currencyInput), 39
- hideDropMenu (drop-menu-interaction), 44
- html-dependencies, 55
- html_dependency_awesome
 - (html-dependencies), 55
- html_dependency_bsswitch
 - (html-dependencies), 55
- html_dependency_btnn
 - (html-dependencies), 55
- html_dependency_pretty
 - (html-dependencies), 55
- html_dependency_sweetalert2
 - (html-dependencies), 55
- htmlDependency, 56
- icon, 134
- inputSweetAlert, 56, 126, 130, 194

- knobInput, 58
- list_group (bootstrap-utils), 24
- materialSwitch, 61, 133, 153
- multiInput, 62, 154
- noUiSliderInput, 64
- numericInputIcon, 67, 156
- numericRangeInput, 69
- panel (bootstrap-utils), 24
- pickerGroup-module, 70
- pickerGroupServer (pickerGroup-module), 70
- pickerGroupUI (pickerGroup-module), 70
- pickerInput, 70, 71, 73, 159
- pickerOptions, 73, 78, 159
- prettyCheckbox, 82
- prettyCheckboxGroup, 86, 162
- prettyRadioButtons, 89, 164
- prettySwitch, 83, 92
- prettyToggle, 83, 94
- progress-bar, 97
- progressBar (progress-bar), 98
- progressSweetAlert, 99, 100
- radioButtons, 103
- radioGroupButtons, 102
- removeVerticalTab (appendVerticalTab), 13
- reorderVerticalTabs (appendVerticalTab), 13
- req, 54
- searchInput, 104
- selectizeGroup-module, 105
- selectizeGroupServer (selectizeGroup-module), 105
- selectizeGroupUI (selectizeGroup-module), 105
- sendSweetAlert, 57, 130, 194
- sendSweetAlert (sweetalert), 125
- setBackgroundColor, 109
- setBackgroundImage, 112
- setShadow, 112
- setSliderColor, 30, 114
- shinyWidgets, 115
- shinyWidgetsGallery, 116
- show_alert, 117
- show_alert (sweetalert), 125
- show_toast, 116
- showDropMenu (drop-menu-interaction), 44
- sliderInput, 119, 120
- sliderTextInput, 119, 173
- spectrumInput, 121
- stati-card, 122
- statiCard (stati-card), 122
- sweetalert, 125
- sweetalert-confirmation, 129
- switchInput, 61, 132, 175
- textInputAddon, 134
- textInputIcon, 135, 180
- timepickerOptions, 10
- timepickerOptions (airDatepicker), 8
- toggleDropDownButton, 49, 137
- tooltipOptions, 47, 138
- updateAirDateInput, 11, 139
- updateAutonumericInput, 18, 41, 140, 150
- updateAwesomeCheckbox, 20, 142
- updateAwesomeCheckboxGroup, 21, 143
- updateAwesomeRadio, 23, 145
- updateCheckboxGroupButtons, 29, 146
- updateColorPickr (colorPickr), 33
- updateCurrencyInput, 18, 41, 140, 149
- updateFormatNumericInput (updateCurrencyInput), 149
- updateKnobInput, 60, 151
- updateMaterialSwitch, 61, 153
- updateMultiInput, 63, 153
- updateNoUiSliderInput, 65, 155
- updateNumericInputIcon, 156
- updateNumericRangeInput, 157
- updatePickerInput, 74, 158
- updatePrettyCheckbox, 83, 160
- updatePrettyCheckboxGroup, 87, 161
- updatePrettyRadioButtons, 164
- updatePrettySwitch, 92, 166
- updatePrettyToggle, 95, 167
- updateProgressBar (progress-bar), 98
- updateRadioGroupButtons, 103, 168
- updateSearchInput, 104, 170
- updateSliderTextInput, 120, 172
- updateSpectrumInput, 173
- updateStatiCard (stati-card), 122
- updateSwitchInput, 133, 175
- updateTextInputIcon, 179

updateVerticalTabsetPanel, [181](#), [199](#)
useArgonDash, [182](#)
useBs4Dash, [185](#)
useShinydashboard, [188](#)
useShinydashboardPlus, [190](#)
useSweetAlert, [193](#)
useTablerDash, [195](#)

validateCssUnit(), [67](#), [69](#), [136](#)
vertical-tab, [199](#)
verticalTabPanel (vertical-tab), [199](#)
verticalTabsetPanel, [181](#)
verticalTabsetPanel (vertical-tab), [199](#)

wNumbFormat, [65](#), [200](#)