

Package ‘siera’

May 9, 2026

Type Package

Title Generate Analysis Results Programmes Using ARS Metadata

Version 0.5.5

Maintainer Malan Bosman <malanbos@gmail.com>

Description Analysis Results Standard (ARS), a foundational standard by CDISC (Clinical Data Interchange Standards Consortium), provides a logical data model for metadata describing all components to calculate Analysis Results. <<https://www.cdisc.org/standards/foundational/analysis-results-standard>> Using 'siera' package, ARS metadata is ingested (JSON or Excel format), producing programmes to generate Analysis Results Datasets (ARDs).

License MIT + file LICENSE

Encoding UTF-8

RoxygenNote 7.3.2

Depends R (>= 4.1)

Imports magrittr, dplyr, tibble, tidyr, jsonlite, stringr, readxl, cli

Suggests knitr, rmarkdown, testthat (>= 3.0.0), withr, readr, cards, cardx, covr, parameters, broom, broom.helpers

VignetteBuilder knitr

URL <https://clymbclinical.github.io/siera/>,
<https://github.com/clymbclinical/siera>

BugReports <https://github.com/clymbclinical/siera/issues>

Config/testthat/edition 3

NeedsCompilation no

Author Malan Bosman [aut, cre],
Clymb Clinical [cph, fnd]

Repository CRAN

Date/Publication 2025-12-01 16:10:02 UTC

Contents

ARD_script_example	2
ARS_example	2
readARS	3

Index	5
--------------	----------

ARD_script_example	<i>Get path to example ARD scripts, auto-generated by siera</i>
--------------------	---

Description

siera comes bundled with some example ARD-producing scripts in its ‘inst/script’ directory. This function make them easy to access.

Usage

```
ARD_script_example(path = NULL)
```

Arguments

path Name of R file. If ‘NULL’, the example files will be listed.

Value

A list of example R files (if path is NULL), or a file itself if path is used.

Examples

```
ARD_script_example()
ARD_script_example("ARD_Out14-1-1.R")
```

ARS_example	<i>Get path to ARS example files</i>
-------------	--------------------------------------

Description

siera comes bundled with some example files in its ‘inst/extdata’ directory. This function make them easy to access.

Usage

```
ARS_example(path = NULL)
```

Arguments

path Name of file. If ‘NULL’, the example files will be listed.

Value

A list of example files (if path is NULL), or a file itself if path is used.

Examples

```
ARS_example()  
ARS_example("Common_Safety_Displays_cards.xlsx")
```

readARS	<i>Ingest ARS (Analysis Results Standard) metadata, produce ARD (Analysis Results Dataset) code for each output</i>
---------	---

Description

Ingest ARS (Analysis Results Standard) metadata, and meta-programme R scripts that could be run as-is to produce Analysis Results Datasets when ingesting ADaM datasets

Usage

```
readARS(  
  ARS_path,  
  output_path = tempdir(),  
  adam_path = tempdir(),  
  spec_output = ""  
)
```

Arguments

ARS_path	A file containing ARS metadata for a reporting event
output_path	Path to store .R ARD scripts
adam_path	Path to folder containing ADaM datasets, to be run in ARD program
spec_output	The output ID for a specific output to be run from the metadata

Value

R programmes generating ARDs - one for each output (or analysis from an output) specified in the ARS metadata

Examples

```
# path to file containing ARS metadata  
  
ARS_path <- ARS_example("Common_Safety_Displays_cards.xlsx")  
  
# output path for R programs  
output_dir <- tempdir()
```

```
# folder containing ADaM datasets
adam_folder <- tempdir()

# run function, write to temp directory
readARS(ARS_path, output_dir, adam_folder)
```

Index

ARD_script_example, [2](#)

ARS_example, [2](#)

readARS, [3](#)