

Package ‘squat’

July 9, 2023

Title Statistics for Quaternion Temporal Data

Version 0.2.1

Description An implementation of statistical tools for the analysis of rotation-valued time series and functional data. It relies on pre-existing quaternion data structure provided by the ‘Eigen’ ‘C++’ library.

License GPL (>= 3)

Encoding UTF-8

LazyData true

RoxygenNote 7.2.3

LinkingTo Rcpp, RcppArmadillo, RcppEigen, fdacluster

Imports cli, dbscan, dtw, fdacluster, funData, furrr, ggplot2, ggrepel, MFPCA, progressr, purrr, Rcpp, rlang, roahd, scales, tibble, tidy

Depends R (>= 4.1.0)

Suggests covr, future, gganimate, gghighlight, testthat (>= 3.0.0), vdiff, withr

Config/testthat/edition 3

URL <https://github.com/LMJL-Alea/squat>,
<https://lmjl-alea.github.io/squat/>

BugReports <https://github.com/LMJL-Alea/squat/issues>

NeedsCompilation yes

Author Lise Bellanger [aut],
Pierre Drouin [aut],
Aymeric Stamm [aut, cre] (<<https://orcid.org/0000-0002-8725-3654>>),
Benjamin Martineau [ctb]

Maintainer Aymeric Stamm <aymeric.stamm@cnrs.fr>

Repository CRAN

Date/Publication 2023-07-09 09:10:05 UTC

R topics documented:

append	3
autoplot.prcomp_qts	4
autoplot.qts	5
autoplot.qtsclust	5
autoplot.qts_sample	6
centring	7
dbscan	8
differentiate	10
dist	10
DTW	12
exp	13
hclust	14
hemispherize	15
kmeans	16
log	18
mean.qts_sample	19
median.qts_sample	20
moving_average	20
normalize	21
plot.prcomp_qts	22
plot.qts	23
plot.qtsclust	23
plot.qts_sample	24
prcomp.qts_sample	25
qts	25
qts2ats	26
qts2avts	27
qts2dts	28
qts2nts	28
qts_sample	29
reorient	30
resample	31
rnorm_qts	32
scale	32
smooth	34
straighten	35
vespa	35
vespa64	36

append	<i>QTS Sample Concatenation</i>
--------	---------------------------------

Description

QTS Sample Concatenation

Usage

```
append(x, ...)  
  
## Default S3 method:  
append(x, values, after = length(x), ...)  
  
## S3 method for class 'qts_sample'  
append(x, y, ...)
```

Arguments

x	Either a numeric vector or an object of class <code>qts_sample</code> .
...	Extra arguments to be passed on to next methods.
values	to be included in the modified vector.
after	a subscript, after which the values are to be appended.
y	Either a numeric vector or an object of class <code>qts_sample</code> or an object of class <code>qts</code> .

Value

If x is a numeric vector, the output is a numeric vector containing the values in x with the elements of values appended after the specified element of x. If x is of class `qts_sample`, the output is another object of class `qts_sample` containing the elements in x and the ones in y appended after the last element of x.

Examples

```
append(vespa64$igp, vespa64$igp[1])  
append(vespa64$igp, vespa64$igp[[1]])
```

autoplot.prcomp_qts *Plot for prcomp_qts objects*

Description

This function creates a visualization of the results of the PCA applied on a sample of QTS and returns the corresponding `ggplot2::ggplot` object which enable further customization of the plot.

Usage

```
## S3 method for class 'prcomp_qts'  
autoplot(object, what = "PC1", ...)
```

Arguments

<code>object</code>	An object of class <code>prcomp_qts</code> as produced by the <code>prcomp.qts_sample()</code> method.
<code>what</code>	A string specifying what kind of visualization the user wants to perform. Choices are words starting with PC and ending with a PC number (in which case the mean QTS is displayed along with its perturbations due to the required PC) or scores (in which case individuals are projected on the required plane). Defaults to PC1.
<code>...</code>	If <code>what = "PC?"</code> , the user can specify whether to plot the QTS in the tangent space or in the original space by providing a boolean argument <code>original_space</code> which defaults to TRUE. If <code>what = "scores"</code> , the user can specify the plane onto which the individuals will be projected by providing a length-2 integer vector <code>plane</code> which defaults to 1:2.

Value

A `ggplot2::ggplot` object.

Examples

```
df <- as_qts_sample(vespa64$igp[1:16])  
res_pca <- prcomp(df)  
  
# Plot the data points in a PC plane  
# And color points according to a categorical variable  
p <- ggplot2::autoplot(res_pca, what = "scores")  
p + ggplot2::geom_point(ggplot2::aes(color = vespa64$V[1:16]))
```

autoplot.qts	<i>Plot for qts objects</i>
--------------	-----------------------------

Description

This function creates a visualization of a QTS and returns the corresponding `ggplot2::ggplot` object which enable further customization of the plot.

Usage

```
## S3 method for class 'qts'  
autoplot(object, highlighted_points = NULL, ...)
```

Arguments

<code>object</code>	An object of class <code>qts</code> .
<code>highlighted_points</code>	An integer vector specifying point indices to be highlighted. Defaults to <code>NULL</code> , in which case no point will be highlighted with respect to the others.
<code>...</code>	Further arguments to be passed on to next methods.

Value

A `ggplot2::ggplot` object.

Examples

```
ggplot2::autoplot(vespa64$igp[[1]])
```

autoplot.qtsclust	<i>Plot for qtsclust objects</i>
-------------------	----------------------------------

Description

This function creates a visualization of the clustering results obtained on a sample of QTS and returns the corresponding `ggplot2::ggplot` object which enable further customization of the plot.

Usage

```
## S3 method for class 'qtsclust'  
autoplot(object, ...)
```

Arguments

object An object of class `qtsclust` as produced by `kmeans.qts_sample()` or `hclust.qts_sample()`.
 ... Further arguments to be passed to other methods.

Value

A `ggplot2::ggplot` object.

Examples

```
out <- kmeans(vespa64$igp[1:10], n_clusters = 2)
ggplot2::autoplot(out)
```

`autoplot.qts_sample` *Plot for `qts_sample` objects*

Description

This function creates a visualization of a sample of QTS and returns the corresponding `ggplot2::ggplot` object which enable further customization of the plot.

Usage

```
## S3 method for class 'qts_sample'
autoplot(
  object,
  memberships = NULL,
  highlighted = NULL,
  with_animation = FALSE,
  ...
)
```

Arguments

object An object of class `qts_sample`.
 memberships A vector coercible as factor specifying a group membership for each QTS in the sample. Defaults to `NULL`, in which case no grouping structure is displayed.
 highlighted A boolean vector specifying whether each QTS in the sample should be highlighted. Defaults to `NULL`, in which case no QTS is highlighted w.r.t. the others.
 with_animation A boolean value specifying whether to create a an animated plot or a static `ggplot2::ggplot` object. Defaults to `FALSE` which will create a static plot.
 ... Further arguments to be passed to methods.

Value

A `ggplot2::ggplot` object.

Examples

```
ggplot2::autoplot(vespa64$igp)
```

centring

QTS Centering and Standardization

Description

This function operates a centering of the QTS around the geometric mean of its quaternions. This is effectively achieved by left-multiplying each quaternion by the inverse of their geometric mean.

Usage

```
centring(x, standardize = FALSE, keep_summary_stats = FALSE)
```

Arguments

- | | |
|--------------------|---|
| x | An object of class <code>qts</code> . |
| standardize | A boolean specifying whether to standardize the QTS in addition to centering it. Defaults to FALSE. |
| keep_summary_stats | A boolean specifying whether the mean and standard deviation used for standardizing the data should be stored in the output object. Defaults to FALSE in which case only the centered <code>qts</code> is returned. |

Value

If `keep_summary_stats = FALSE`, an object of class `qts` in which quaternions have been centered (and possibly standardized) around their geometric mean. If `keep_summary_stats = TRUE`, a list with three components:

- `qts`: an object of class `qts` in which quaternions have been centered (and possibly standardized) around their geometric mean;
- `mean`: a numeric vector with the quaternion Fréchet mean;
- `sd`: a numeric value with the quaternion Fréchet standard deviation.

Examples

```
centring(vespa64$igp[[1]])
```

 dbscan

QTS Nearest-Neighbor Clustering

Description

This function massages the input quaternion time series to apply DBSCAN clustering on them, with the possibility of separating amplitude and phase variability and of choosing the source of variability through which clusters should be searched.

Usage

```
dbscan(x, ...)

## Default S3 method:
dbscan(x, eps, minPts = 5, weights = NULL, borderPoints = TRUE, ...)

## S3 method for class 'qts_sample'
dbscan(
  x,
  warping_class = c("affine", "dilation", "none", "shift", "srsf"),
  centroid_type = "mean",
  metric = c("l2", "pearson"),
  cluster_on_phase = FALSE,
  use_fence = FALSE,
  ...
)
```

Arguments

<code>x</code>	Either a numeric matrix of data, or an object that can be coerced to such a matrix (such as a numeric vector or a data frame with all numeric columns) or an object of class <code>qts_sample</code> .
<code>...</code>	additional arguments are passed on to the fixed-radius nearest neighbor search algorithm. See <code>frNN()</code> for details on how to control the search strategy.
<code>eps</code>	size (radius) of the epsilon neighborhood. Can be omitted if <code>x</code> is a <code>frNN</code> object.
<code>minPts</code>	number of minimum points required in the <code>eps</code> neighborhood for core points (including the point itself).
<code>weights</code>	numeric; weights for the data points. Only needed to perform weighted clustering.
<code>borderPoints</code>	logical; should border points be assigned to clusters. The default is <code>TRUE</code> for regular DBSCAN. If <code>FALSE</code> then border points are considered noise (see DBSCAN* in Campello et al, 2013).
<code>warping_class</code>	A string specifying the warping class Choices are "affine", "dilation", "none", "shift" or "srsf". Defaults to "affine". The SRSF class is the only class which is boundary-preserving.

centroid_type	A string specifying the type of centroid to compute. Choices are "mean", "median", "medoid", "lowess" or "poly". Defaults to "mean". If LOWESS approximation is chosen, the user can append an integer between 0 and 100 as in "lowess20". This number will be used as the smoother span. This gives the proportion of points in the plot which influence the smooth at each value. Larger values give more smoothness. The default value is 10%. If polynomial approximation is chosen, the user can append a positive integer as in "poly3". This number will be used as the degree of the polynomial model. The default value is 4L.
metric	A character string specifying the distance measure to be used. This must be one of "euclidean", "maximum", "manhattan", "canberra", "binary" or "minkowski" if x is not a QTS sample. Otherwise, it must be one of "l2", "pearson" or "dtw".
cluster_on_phase	A boolean specifying whether clustering should be based on phase variation or amplitude variation. Defaults to FALSE which implies amplitude variation.
use_fence	A boolean specifying whether the fence algorithm should be used to robustify the algorithm against outliers. Defaults to FALSE. This is used only when warping_class != "srsf".

Value

An object of class `stats::kmeans` or `stats::hclust` or `dbscan_fast` if the input x is NOT of class `qts_sample`. Otherwise, an object of class `qtsclust` which is effectively a list with four components:

- `qts_aligned`: An object of class `qts_sample` storing the sample of aligned QTS;
- `qts_centers`: A list of objects of class `qts` representing the centers of the clusters;
- `best_clustering`: An object of class `fdacluster::caps` storing the results of the best k-mean alignment result among all initialization that were tried.
- `call_name`: A string storing the name of the function that was used to produce the clustering structure;
- `call_args`: A list containing the exact arguments that were passed to the function `call_name` that produced this output.

Examples

```
out <- dbscan(vespa64$igp[1:10])
plot(out)
```

differentiate	<i>QTS Differentiation</i>
---------------	----------------------------

Description

This function computes the first derivative of quaternion time series with respect to time.

Usage

```
differentiate(x)

## S3 method for class 'qts'
differentiate(x)

## S3 method for class 'qts_sample'
differentiate(x)
```

Arguments

x An object of class `qts` or `qts_sample`.

Value

An object of the same class as the input argument x in which quaternions measure the rotation to be applied to transform attitude at previous time point to attitude at current time point.

Examples

```
differentiate(vespa64$igp[[1]])
differentiate(vespa64$igp)
```

dist	<i>QTS Distance Matrix Computation</i>
------	--

Description

This function massages an input sample of quaternion time series to turn it into a pairwise distance matrix.

Usage

```

dist(x, metric, ...)

## Default S3 method:
dist(
  x,
  metric = c("euclidean", "maximum", "manhattan", "canberra", "binary", "minkowski"),
  diag = FALSE,
  upper = FALSE,
  p = 2,
  ...
)

## S3 method for class 'qts_sample'
dist(
  x,
  metric = c("l2", "pearson", "dtw"),
  warping_class = c("affine", "dilation", "none", "shift", "srsf"),
  cluster_on_phase = FALSE,
  labels = NULL,
  ...
)

```

Arguments

x	A numeric matrix, data frame, <code>stats::dist</code> object or object of class <code>qts_sample</code> specifying the sample on which to compute the pairwise distance matrix.
metric	A character string specifying the distance measure to be used. This must be one of "euclidean", "maximum", "manhattan", "canberra", "binary" or "minkowski" if x is not a QTS sample. Otherwise, it must be one of "l2", "pearson" or "dtw".
...	not used.
diag	logical value indicating whether the diagonal of the distance matrix should be printed by <code>print.dist</code> .
upper	logical value indicating whether the upper triangle of the distance matrix should be printed by <code>print.dist</code> .
p	The power of the Minkowski distance.
warping_class	A string specifying the warping class Choices are "affine", "dilation", "none", "shift" or "srsf". Defaults to "affine". The SRSF class is the only class which is boundary-preserving.
cluster_on_phase	A boolean specifying whether clustering should be based on phase variation or amplitude variation. Defaults to FALSE which implies amplitude variation.
labels	A character vector specifying curve labels. Defaults to NULL which uses sequential numbers as labels.

Value

An object of class `stats::dist`.

Examples

```
D <- dist(vespa64$igp[1:5])
```

DTW

Dynamic Time Warping for Quaternion Time Series

Description

This function evaluates the Dynamic Time Warping (DTW) distance between two quaternion time series (QTS).

Usage

```
DTW(
  qts1,
  qts2,
  resample = TRUE,
  disable_normalization = FALSE,
  distance_only = FALSE,
  step_pattern = dtw::symmetric2
)
```

Arguments

<code>qts1</code>	An object of class <code>qts</code> .
<code>qts2</code>	An object of class <code>qts</code> .
<code>resample</code>	A boolean specifying whether the QTS should be uniformly resampled on their domain before computing distances. Defaults to TRUE.
<code>disable_normalization</code>	A boolean specifying whether quaternion normalization should be disabled. Defaults to FALSE which ensures that we always deal with unit quaternions.
<code>distance_only</code>	A boolean specifying whether to only compute distance (no backtrack, faster). Defaults to FALSE.
<code>step_pattern</code>	A <code>dtw::stepPattern</code> specifying the local constraints on the warping path. Defaults to <code>dtw::symmetric2</code> which uses symmetric and normalizable warping paths with no local slope constraints. See <code>dtw::stepPattern</code> for more information.

Details

If no evaluation grid is provided, the function assumes that the two input QTS are evaluated on the same grid.

Value

An object of class `dtw::dtw` storing the dynamic time warping results.

Examples

```
DTW(vespa64$igp[[1]], vespa64$igp[[2]])
```

 exp

QTS Exponential

Description

This function computes the exponential of quaternion time series as the time series of the quaternion exponentials.

Usage

```
## S3 method for class 'qts'
exp(x, ...)

## S3 method for class 'qts_sample'
exp(x, ...)
```

Arguments

`x` An object of class `qts` or `qts_sample`.

`...` Extra arguments to be passed on to next methods.

Value

An object of the same class as the input argument `x` in which quaternions have been replaced by their exponential.

Examples

```
x <- log(vespa64$igp[[1]])
exp(x)
y <- log(vespa64$igp)
exp(y)
```

hclust

*QTS Hierarchical Agglomerative Clustering***Description**

This function massages the input quaternion time series to apply hierarchical agglomerative clustering on them, with the possibility of separating amplitude and phase variability and of choosing the source of variability through which clusters should be searched.

Usage

```
hclust(x, metric, linkage_criterion, ...)

## Default S3 method:
hclust(
  x,
  metric = c("euclidean", "maximum", "manhattan", "canberra", "binary", "minkowski"),
  linkage_criterion = c("complete", "average", "single", "ward.D2"),
  ...
)

## S3 method for class 'qts_sample'
hclust(
  x,
  metric = c("l2", "pearson"),
  linkage_criterion = c("complete", "average", "single", "ward.D2"),
  n_clusters = 1L,
  warping_class = c("affine", "dilation", "none", "shift", "srsf"),
  centroid_type = "mean",
  cluster_on_phase = FALSE,
  ...
)
```

Arguments

x Either a numeric matrix of data, or an object that can be coerced to such a matrix (such as a numeric vector or a data frame with all numeric columns) or an object of class `qts_sample`.

metric A character string specifying the distance measure to be used. This must be one of "euclidean", "maximum", "manhattan", "canberra", "binary" or "minkowski" if `x` is not a QTS sample. Otherwise, it must be one of "l2", "pearson" or "dtw".

linkage_criterion A string specifying which linkage criterion should be used to compute distances between sets of curves. Choices are "complete" for complete linkage, "average" for average linkage and "single" for single linkage. See `stats::hclust()` for more details. Defaults to "complete".

...	Further graphical arguments. E.g., <code>cex</code> controls the size of the labels (if plotted) in the same way as <code>text</code> .
<code>n_clusters</code>	An integer value specifying the number of clusters. Defaults to 1L.
<code>warping_class</code>	A string specifying the warping class. Choices are "affine", "dilation", "none", "shift" or "srsf". Defaults to "affine". The SRSF class is the only class which is boundary-preserving.
<code>centroid_type</code>	A string specifying the type of centroid to compute. Choices are "mean", "median", "medoid", "lowess" or "poly". Defaults to "mean". If LOWESS approximation is chosen, the user can append an integer between 0 and 100 as in "lowess20". This number will be used as the smoother span. This gives the proportion of points in the plot which influence the smooth at each value. Larger values give more smoothness. The default value is 10%. If polynomial approximation is chosen, the user can append a positive integer as in "poly3". This number will be used as the degree of the polynomial model. The default value is 4L.
<code>cluster_on_phase</code>	A boolean specifying whether clustering should be based on phase variation or amplitude variation. Defaults to FALSE which implies amplitude variation.

Value

An object of class `stats::kmeans` or `stats::hclust` or `dbscan_fast` if the input `x` is NOT of class `qts_sample`. Otherwise, an object of class `qtsclust` which is effectively a list with four components:

- `qts_aligned`: An object of class `qts_sample` storing the sample of aligned QTS;
- `qts_centers`: A list of objects of class `qts` representing the centers of the clusters;
- `best_clustering`: An object of class `fdacluster::caps` storing the results of the best k-mean alignment result among all initialization that were tried.
- `call_name`: A string storing the name of the function that was used to produce the clustering structure;
- `call_args`: A list containing the exact arguments that were passed to the function `call_name` that produced this output.

Examples

```
out <- hclust(vespa64$igp[1:10], n_clusters = 2)
plot(out)
```

hemispherize

QTS Hemispherization

Description

This function ensures that there are no discontinuities in QTS due to quaternion flips since two unit quaternions `q` and `-q` encode the same rotation.

Usage

```
hemispherize(x)

## S3 method for class 'qts'
hemispherize(x)

## S3 method for class 'qts_sample'
hemispherize(x)
```

Arguments

x An object of class `qts` or `qts_sample`.

Value

An object of the same class as the input argument `x` with no quaternion flip discontinuities.

Examples

```
hemispherize(vespa64$igp[[1]])
hemispherize(vespa64$igp)
```

kmeans

QTS K-Means Alignment Algorithm

Description

This function massages the input quaternion time series to feed them into the k-means alignment algorithm for jointly clustering and aligning the input QTS.

Usage

```
kmeans(x, n_clusters, ...)

## Default S3 method:
kmeans(
  x,
  n_clusters = 1,
  iter_max = 10,
  nstart = 1,
  algorithm = c("Hartigan-Wong", "Lloyd", "Forgy", "MacQueen"),
  trace = FALSE,
  ...
)

## S3 method for class 'qts_sample'
kmeans(
```



```

x,
n_clusters = 1L,
seeds = NULL,
seeding_strategy = c("kmeans++", "exhaustive-kmeans++", "exhaustive", "hclust"),
warping_class = c("affine", "dilation", "none", "shift", "srsf"),
centroid_type = "mean",
metric = c("l2", "pearson"),
cluster_on_phase = FALSE,
use_fence = FALSE,
...
)

```

Arguments

x	Either a numeric matrix of data, or an object that can be coerced to such a matrix (such as a numeric vector or a data frame with all numeric columns) or an object of class <code>qts_sample</code> .
n_clusters	An integer value specifying the number of clusters to be look for.
...	not used.
iter_max	An integer value specifying the maximum number of iterations for terminating the k-mean algorithm. Defaults to 10L.
nstart	if centers is a number, how many random sets should be chosen?
algorithm	character: may be abbreviated. Note that "Lloyd" and "Forgy" are alternative names for one algorithm.
trace	logical or integer number, currently only used in the default method ("Hartigan-Wong"): if positive (or true), tracing information on the progress of the algorithm is produced. Higher values may produce more tracing information.
seeds	An integer value or vector specifying the indices of the initial centroids. If an integer vector, it is interpreted as the indices of the initial centroids and should therefore be of length n_clusters. If an integer value, it is interpreted as the index of the first initial centroid and subsequent centroids are chosen according to the k-means++ strategy. It can be NULL in which case the argument seeding_strategy is used to automatically provide suitable indices. Defaults to NULL.
seeding_strategy	A character string specifying the strategy for choosing the initial centroids in case the argument seeds is set to NULL. Choices are "kmeans++", "exhaustive-kmeans++" which performs an exhaustive search over the choice of the first centroid, "exhaustive" which tries on all combinations of initial centroids or "hclust" which first performs hierarchical clustering using Ward's linkage criterion to identify initial centroids. Defaults to "kmeans++", which is the fastest strategy.
warping_class	A string specifying the warping class Choices are "affine", "dilation", "none", "shift" or "srsf". Defaults to "affine". The SRSF class is the only class which is boundary-preserving.
centroid_type	A string specifying the type of centroid to compute. Choices are "mean", "median", "medoid", "lowess" or "poly". Defaults to "mean". If LOWESS approximation is chosen, the user can append an integer between 0 and 100 as in

	"lowess20". This number will be used as the smoother span. This gives the proportion of points in the plot which influence the smooth at each value. Larger values give more smoothness. The default value is 10%. If polynomial approximation is chosen, the user can append an positive integer as in "poly3". This number will be used as the degree of the polynomial model. The default value is 4L.
metric	A string specifying the metric used to compare curves. Choices are "l2" or "pearson". Defaults to "l2". Used only when <code>warping_class != "srsf"</code> . For the boundary-preserving warping class, the L2 distance between the SRSFs of the original curves is used.
cluster_on_phase	A boolean specifying whether clustering should be based on phase variation or amplitude variation. Defaults to FALSE which implies amplitude variation.
use_fence	A boolean specifying whether the fence algorithm should be used to robustify the algorithm against outliers. Defaults to FALSE. This is used only when <code>warping_class != "srsf"</code> .

Value

An object of class `stats::kmeans` or `stats::hclust` or `dbscan_fast` if the input `x` is NOT of class `qts_sample`. Otherwise, an object of class `qtsclust` which is effectively a list with four components:

- `qts_aligned`: An object of class `qts_sample` storing the sample of aligned QTS;
- `qts_centers`: A list of objects of class `qts` representing the centers of the clusters;
- `best_clustering`: An object of class `fdacluster::caps` storing the results of the best k-mean alignment result among all initialization that were tried.
- `call_name`: A string storing the name of the function that was used to produce the clustering structure;
- `call_args`: A list containing the exact arguments that were passed to the function `call_name` that produced this output.

Examples

```
out <- kmeans(vespa64$igp[1:10], n_clusters = 2)
```

log

QTS Logarithm

Description

This function computes the logarithm of quaternion time series as the time series of the quaternion logarithms.

Usage

```
## S3 method for class 'qts'
log(x, ...)

## S3 method for class 'qts_sample'
log(x, ...)
```

Arguments

x An object of class `qts` or `qts_sample`.
 ... Extra arguments to be passed on to next methods.

Value

An object of the same class as the input argument x in which quaternions have been replaced by their logarithm.

Examples

```
log(vespa64$igp[[1]])
log(vespa64$igp)
```

mean.qts_sample	<i>QTS Geometric Mean</i>
-----------------	---------------------------

Description

This function computes the pointwise geometric mean of a QTS sample.

Usage

```
## S3 method for class 'qts_sample'
mean(x, ...)
```

Arguments

x An object of class `qts_sample`.
 ... Further arguments passed to or from other methods.

Value

An object of class `qts` in which quaternions are the pointwise geometric mean of the input QTS sample.

Examples

```
mean(vespa64$igp)
```

median.qts_sample	<i>QTS Geometric Median</i>
-------------------	-----------------------------

Description

This function computes the pointwise geometric median of a QTS sample.

Usage

```
## S3 method for class 'qts_sample'
median(x, na.rm = FALSE, ...)
```

Arguments

x	An object of class <code>qts_sample</code> .
na.rm	A logical value indicating whether NA values should be stripped before the computation proceeds.
...	Further arguments passed to or from other methods.

Value

An object of class `qts` in which quaternions are the pointwise geometric median of the input QTS sample.

Examples

```
median(vespa64$igp)
```

moving_average	<i>QTS Moving Average</i>
----------------	---------------------------

Description

This function performs QTS smoothing via moving average.

Usage

```
moving_average(x, window_size = 0)

## S3 method for class 'qts'
moving_average(x, window_size = 0)

## S3 method for class 'qts_sample'
moving_average(x, window_size = 0)
```

Arguments

- `x` An object of class `qts` or `qts_sample`.
- `window_size` An integer value specifying the size of the sliding window used to compute the median value. Defaults to `0L`.

Value

An object of the same class as the input argument `x` storing the smoothed QTS.

Examples

```
moving_average(vespa64$igp[[1]], window_size = 5)
moving_average(vespa64$igp, window_size = 5)
```

normalize

QTS Normalization

Description

This function ensures that all quaternions in the time series are unit quaternions.

Usage

```
normalize(x)

## S3 method for class 'qts'
normalize(x)

## S3 method for class 'qts_sample'
normalize(x)
```

Arguments

- `x` An object of class `qts` or `qts_sample`.

Value

An object of the same class as the input argument `x` in which quaternions are unit quaternions.

Examples

```
normalize(vespa64$igp[[1]])
normalize(vespa64$igp)
```

plot.prcomp_qts *Plot for prcomp_qts objects*

Description

This function creates a visualization of the results of the PCA applied on a sample of QTS **without** returning the plot data as an object.

Usage

```
## S3 method for class 'prcomp_qts'  
plot(x, what = "PC1", ...)  
  
## S3 method for class 'prcomp_qts'  
screepplot(x, ...)
```

Arguments

x	An object of class prcomp_qts as produced by the <code>prcomp.qts_sample()</code> method.
what	A string specifying what kind of visualization the user wants to perform. Choices are words starting with PC and ending with a PC number (in which case the mean QTS is displayed along with its perturbations due to the required PC) or scores (in which case individuals are projected on the required plane). Defaults to PC1.
...	If what = "PC?", the user can specify whether to plot the QTS in the tangent space or in the original space by providing a boolean argument <code>original_space</code> which defaults to TRUE. If what = "scores", the user can specify the plane onto which the individuals will be projected by providing a length-2 integer vector argument <code>plane</code> which defaults to 1:2.

Value

No return value, called for side effects.

Examples

```
df <- as_qts_sample(vespa64$igp[1:16])  
res_pca <- prcomp(df)  
  
# You can plot the effect of a PC on the mean  
plot(res_pca, what = "PC1")  
  
# You can plot the data points in a PC plane  
plot(res_pca, what = "scores")
```

plot.qts	<i>Plot for qts objects</i>
----------	-----------------------------

Description

This function creates a visualization of a QTS **without** returning the plot data as an object.

Usage

```
## S3 method for class 'qts'  
plot(x, highlighted_points = NULL, ...)
```

Arguments

x	An object of class <code>qts</code> .
highlighted_points	An integer vector specifying point indices to be highlighted. Defaults to NULL, in which case no point will be highlighted with respect to the others.
...	Further arguments to be passed on to next methods.

Value

No return value, called for side effects.

Examples

```
plot(vespa64$igp[[1]])
```

plot.qtsclust	<i>Plot for qtsclust objects</i>
---------------	----------------------------------

Description

This function creates a visualization of the clustering results obtained on a sample of QTS **without** returning the plot data as an object.

Usage

```
## S3 method for class 'qtsclust'  
plot(x, ...)
```

Arguments

x	An object of class <code>qtsclust</code> as produced by <code>kmeans.qts_sample()</code> or <code>hclust.qts_sample()</code> .
...	Further arguments to be passed to other methods.

Value

No return value, called for side effects.

Examples

```
out <- kmeans(vespa64$igp[1:10], n_clusters = 2)
plot(out)
```

plot.qts_sample *Plot for qts_sample objects*

Description

This function creates a visualization of a sample of QTS **without** returning the corresponding `ggplot2::ggplot` object

Usage

```
## S3 method for class 'qts_sample'
plot(x, memberships = NULL, highlighted = NULL, with_animation = FALSE, ...)
```

Arguments

x	An object of class <code>qts_sample</code> .
memberships	A vector coercible as factor specifying a group membership for each QTS in the sample. Defaults to NULL, in which case no grouping structure is displayed.
highlighted	A boolean vector specifying whether each QTS in the sample should be highlighted. Defaults to NULL, in which case no QTS is highlighted w.r.t. the others.
with_animation	A boolean value specifying whether to create a an animated plot or a static <code>ggplot2::ggplot</code> object. Defaults to FALSE which will create a static plot.
...	Further arguments to be passed to methods.

Value

No return value, called for side effects.

Examples

```
plot(vespa64$igp)
```

prcomp.qts_sample	<i>PCA for QTS Sample</i>
-------------------	---------------------------

Description

PCA for QTS Sample

Usage

```
## S3 method for class 'qts_sample'
prcomp(x, M = 5, fit = FALSE, ...)
```

Arguments

x	An object of class qts_sample .
M	An integer value specifying the number of principal component to compute. Defaults to 5L.
fit	A boolean specifying whether the resulting prcomp_qts object should store a reconstruction of the sample from the retained PCs. Defaults to FALSE.
...	Arguments passed to or from other methods.

Value

An object of class prcomp_qts which is a list with the following components:

- `tpca`: An object of class MFPCAfit as produced by the function `MFPCA::MFPCA()`,
- `var_props`: A numeric vector storing the percentage of variance explained by each PC,
- `mean_qts`: An object of class [qts](#) containing the mean QTS,
- `principal_qts`: A list of [qts](#)s containing the required principal components.

Examples

```
res_pca <- prcomp(vespa64$igp[1:16])
```

qts	<i>QTS Class</i>
-----	------------------

Description

A collection of functions that implements the QTS class. It currently provides the `as_qts()` function for QTS coercion of `tibble::tibble`s and the `is_qts()` function for checking if an object is a QTS.

Usage

```
as_qts(x)

is_qts(x)

## S3 method for class 'qts'
format(x, digits = 5, ...)
```

Arguments

x	A <code>tibble::tibble</code> with columns time, w, x, y and z.
digits	An integer value specifying the number of digits to keep for printing. Defaults to 5L.
...	Further arguments passed to or from other methods.

Details

A quaternion time series (QTS) is stored as a `tibble::tibble` with 5 columns:

- time: A first column specifying the time points at which quaternions were collected;
- w: A second column specifying the first coordinate of the collected quaternions;
- x: A third column specifying the second coordinate of the collected quaternions;
- y: A fourth column specifying the third coordinate of the collected quaternions;
- z: A fifth column specifying the fourth coordinate of the collected quaternions.

Value

An object of class `qts`.

Examples

```
qts1 <- vespa64$igp[[1]]
qts2 <- as_qts(qts1)
is_qts(qts1)
is_qts(qts2)
```

qts2ats

QTS Transformation To Angle Time Series

Description

This function computes a univariate time series representing the angle between the first and other attitudes.

Usage

```
qts2ats(x, disable_normalization = FALSE)
```

Arguments

- `x` An object of class `qts`.
- `disable_normalization` A boolean specifying whether quaternion normalization should be disabled. Defaults to FALSE.

Value

A time series stored as a `tibble::tibble` with columns `time` and `angle` in which `angle` measures the angle between the current rotation and the first one.

Examples

```
qts2ats(vespa64$igp[[1]])
```

qts2avts

QTS Transformation to Angular Velocity Time Series

Description

This function projects a quaternion time series into the space of angular velocities.

Usage

```
qts2avts(x, body_frame = FALSE)
```

Arguments

- `x` An object of class `qts`.
- `body_frame` A boolean specifying whether the fixed frame with respect to which coordinates of the angular velocity should be computed is the body frame or the global frame. Defaults to FALSE.

Value

A time series stored as a `tibble::tibble` with columns `time`, `x`, `y` and `z` containing the angular velocity at each time point.

Examples

```
qts2avts(vespa64$igp[[1]])
```

qts2dts *QTS Transformation To Distance Time Series*

Description

This function computes a real-valued time series reporting the pointwise geodesic distance between the two input QTS at each time point.

Usage

```
qts2dts(x, y)
```

Arguments

x An object of class [qts](#).
y An object of class [qts](#).

Details

The function currently expects that the two input QTS are evaluated on the same time grid.

Value

A time series stored as a [tibble::tibble](#) with columns `time` and `distance` in which distance measures the angular distance between the quaternions of both input QTS at a given time point.

Examples

```
qts2dts(vespa64$igp[[1]], vespa64$igp[[2]])
```

qts2nts *QTS Transformation To Norm Time Series*

Description

This function computes a univariate time series representing the norm of the quaternions.

Usage

```
qts2nts(x, disable_normalization = FALSE)
```

Arguments

x An object of class [qts](#).
disable_normalization A boolean specifying whether quaternion normalization should be disabled. Defaults to FALSE.

Value

A time series stored as a `tibble::tibble` with columns `time` and `norm` in which `norm` measures the angular distance between the current quaternion and the identity.

Examples

```
qts2nts(vespa64$igp[[1]])
```

qts_sample	<i>QTS Sample Class</i>
------------	-------------------------

Description

A collection of functions that implements the QTS sample class. It currently provides the `as_qts_sample()` function for QTS sample coercion of lists of `qts` objects, the `is_qts_sample()` function for checking if an object is a QTS sample and the subset operator.

Usage

```
as_qts_sample(x)

is_qts_sample(x)

## S3 method for class 'qts_sample'
x[i, simplify = FALSE]
```

Arguments

<code>x</code>	A list of <code>tibble::tibbles</code> , each of which with columns <code>time</code> , <code>w</code> , <code>x</code> , <code>y</code> and <code>z</code> .
<code>i</code>	A valid expression to subset observations from a QTS sample.
<code>simplify</code>	A boolean value specifying whether the resulting subset should be turned into a single QTS in case the subset is of size 1. Defaults to <code>FALSE</code> .

Details

A QTS sample is a collection of quaternion time series (QTS), each of which is stored as a `tibble::tibble` with 5 columns:

- `time`: A first column specifying the time points at which quaternions were collected;
- `w`: A second column specifying the first coordinate of the collected quaternions;
- `x`: A third column specifying the second coordinate of the collected quaternions;
- `y`: A fourth column specifying the third coordinate of the collected quaternions;
- `z`: A fifth column specifying the fourth coordinate of the collected quaternions.

Value

An object of class `qts_sample`.

Examples

```
x <- vespa64$igp
y <- as_qts_sample(x)
is_qts_sample(x)
is_qts_sample(y)
x[1]
x[1, simplify = TRUE]
```

reorient

QTS Reorientation

Description

This function reorients the quaternions in a QTS for representing attitude with respect to the orientation of the sensor at the first time point.

Usage

```
reorient(x, disable_normalization = FALSE)

## S3 method for class 'qts'
reorient(x, disable_normalization = FALSE)

## S3 method for class 'qts_sample'
reorient(x, disable_normalization = FALSE)
```

Arguments

x An object of class `qts` or `qts_sample`.

disable_normalization A boolean specifying whether quaternion normalization should be disabled. Defaults to FALSE.

Value

An object of the same class as the input argument `x` in which quaternions measure attitude with respect to the orientation of the sensor at the first time point.

Examples

```
reorient(vespa64$igp[[1]])
reorient(vespa64$igp)
```

resample	<i>QTS Resampling</i>
----------	-----------------------

Description

This function performs uniform resampling using SLERP.

Usage

```
resample(x, tmin = NA, tmax = NA, nout = 0L, disable_normalization = FALSE)

## S3 method for class 'qts'
resample(x, tmin = NA, tmax = NA, nout = 0L, disable_normalization = FALSE)

## S3 method for class 'qts_sample'
resample(x, tmin = NA, tmax = NA, nout = 0L, disable_normalization = FALSE)
```

Arguments

x	An object of class <code>qts</code> or <code>qts_sample</code> .
tmin	A numeric value specifying the lower bound of the time interval over which uniform resampling should take place. It must satisfy $tmin \geq \min(qts\$time)$. Defaults to NA in which case it is set to $\min(qts\$time)$.
tmax	A numeric value specifying the upper bound of the time interval over which uniform resampling should take place. It must satisfy $tmax \leq \max(qts\$time)$. Defaults to NA in which case it is set to $\max(qts\$time)$.
nout	An integer specifying the size of the uniform grid for time resampling. Defaults to 0L in which case it uses the same grid size as the input QTS.
disable_normalization	A boolean specifying whether quaternion normalization should be disabled. Defaults to FALSE in which case the function makes sure that quaternions are normalized prior to performing SLERP interpolation.

Value

An object of the same class as the input argument x in which quaternions are uniformly sampled in the range [tmin, tmax].

Examples

```
resample(vespa64$igp[[1]])
resample(vespa64$igp)
```

rnorm_qts	<i>QTS Random Sampling</i>
-----------	----------------------------

Description

This function adds uncorrelated Gaussian noise to the logarithm QTS using an exponential covariance function.

Usage

```
rnorm_qts(n, mean_qts, alpha = 0.01, beta = 0.001)
```

Arguments

n	An integer specifying how many QTS should be generated.
mean_qts	An object of class <code>qts</code> specifying the mean QTS.
alpha	A positive scalar specifying the variance of each component of the log-QTS. Defaults to 0.01.
beta	A positive scalar specifying the exponential weight. Defaults to 0.001.

Details

See [exp_cov_function](#) for details about the roles of alpha and beta in the definition of the covariance operator.

Value

A list of n objects of class `qts` with added noise as specified by parameters alpha and beta.

Examples

```
rnorm_qts(1, vespa64$igp[[1]])
```

scale	<i>QTS Sample Centering and Standardization</i>
-------	---

Description

QTS Sample Centering and Standardization

Usage

```

scale(x, center = TRUE, scale = TRUE, ...)

## Default S3 method:
scale(x, center = TRUE, scale = TRUE, ...)

## S3 method for class 'qts_sample'
scale(
  x,
  center = TRUE,
  scale = TRUE,
  by_row = FALSE,
  keep_summary_stats = FALSE,
  ...
)

```

Arguments

<code>x</code>	An object coercible into a numeric matrix or an object of class <code>qts_sample</code> representing a sample of observed QTS.
<code>center</code>	A boolean specifying whether to center the sample. If set to <code>FALSE</code> , the original sample is returned, meaning that no standardization is performed regardless of whether argument <code>scale</code> was set to <code>TRUE</code> or not. Defaults to <code>TRUE</code> .
<code>scale</code>	A boolean specifying whether to standardize the sample once it has been centered. Defaults to <code>TRUE</code> .
<code>...</code>	Extra arguments passed on to next methods.
<code>by_row</code>	A boolean specifying whether the QTS scaling should happen for each data point (<code>by_row = TRUE</code>) or for each time point (<code>by_row = FALSE</code>). Defaults to <code>FALSE</code> .
<code>keep_summary_stats</code>	A boolean specifying whether the mean and standard deviation used for standardizing the data should be stored in the output object. Defaults to <code>FALSE</code> in which case only the list of properly rescaled QTS is returned.

Value

A list of properly rescaled QTS stored as an object of class `qts_sample` when `keep_summary_stats = FALSE`. Otherwise a list with three components:

- `rescaled_sample`: a list of properly rescaled QTS stored as an object of class `qts_sample`;
- `mean`: a list of numeric vectors storing the corresponding quaternion Fréchet means;
- `sd`: a numeric vector storing the corresponding quaternion Fréchet standard deviations.

Examples

```

x <- scale(vespa64$igp)
x[[1]]

```

smooth

*QTS Smoothing via SLERP Interpolation***Description**

This function performs a smoothing of a QTS by SLERP interpolation.

Usage

```
smooth(x, ...)

## Default S3 method:
smooth(
  x,
  kind = c("3RS3R", "3RSS", "3RSR", "3R", "3", "S"),
  twiceit = FALSE,
  endrule = c("Tukey", "copy"),
  do.ends = FALSE,
  ...
)

## S3 method for class 'qts'
smooth(x, alpha = 0.5, ...)

## S3 method for class 'qts_sample'
smooth(x, alpha = 0.5, ...)
```

Arguments

x	An object of class <code>qts</code> or <code>qts_sample</code> .
...	Extra arguments passed on to next methods.
kind	a character string indicating the kind of smoother required; defaults to "3RS3R".
twiceit	logical, indicating if the result should be 'twiced'. Twicing a smoother $S(y)$ means $S(y) + S(y - S(y))$, i.e., adding smoothed residuals to the smoothed values. This decreases bias (increasing variance).
endrule	a character string indicating the rule for smoothing at the boundary. Either "Tukey" (default) or "copy".
do.ends	logical, indicating if the 3-splitting of ties should also happen at the boundaries (ends). This is only used for <code>kind = "S"</code> .
alpha	A numeric value in $[0, 1]$ specifying the amount of smoothing. The closer to one, the smoother the resulting QTS. Defaults to 0.5.

Value

An object of the same class as the input argument `x` which is a smooth version of the input QTS.

Examples

```
smooth(vespa64$igp[[1]])
smooth(vespa64$igp)
```

straighten	<i>QTS Straightening</i>
------------	--------------------------

Description

This function straightens QTS so that the last point equals the first point.

Usage

```
straighten(x)

## S3 method for class 'qts'
straighten(x)

## S3 method for class 'qts_sample'
straighten(x)
```

Arguments

x An object of class [qts](#) or [qts_sample](#).

Value

An object of the same class as the input argument x storing the straightened QTS.

Examples

```
straighten(vespa64$igp[[1]])
straighten(vespa64$igp)
```

vespa	<i>The VESPA dataset</i>
-------	--------------------------

Description

A set of QTS representing individual gait patterns (IGPs) of individuals collected under a number of varying factors.

Usage

```
vespa
```

Format

A [tibble](#) with 320 rows and 7 columns:

- V: a categorical variable with two levels specifying the ID of the Volunteer;
- E: a categorical variable with two levels specifying the ID of the Experimenter;
- S: a categorical variable with four levels specifying the type of Sensor;
- P: a categorical variable with four levels specifying the Position of the sensor;
- A: a categorical variable with two levels specifying the ID of the Acquisition pathway;
- R: a categorical variable with 5 levels specifying the ID of the Repetition;
- igp: A 101x5 [tibble](#) storing a QTS which represents the IGP of the individual under a specific set of VESPA conditions.

Details

The IGP measures the hip rotation during a typical gait cycle. Each rotation is expressed with respect to the mean position of the sensor during the gait cycle. Each IGP is then straightened so that it is periodic with a last point matching the first one.

vespa64

The VESPA64 dataset

Description

A set of QTS representing individual gait patterns (IGPs) of individuals collected under a number of varying factors.

Usage

vespa64

Format

A [tibble](#) with 320 rows and 7 columns:

- V: a categorical variable with two levels specifying the ID of the Volunteer;
- E: a categorical variable with two levels specifying the ID of the Experimenter;
- S: a categorical variable with four levels specifying the type of Sensor;
- P: a categorical variable with four levels specifying the Position of the sensor;
- A: a categorical variable with two levels specifying the ID of the Acquisition pathway;
- igp: A 101x5 [tibble](#) storing a QTS which represents the IGP of the individual under a specific set of VESPA conditions.

Details

The IGP measures the hip rotation during a typical gait cycle. Each rotation is expressed with respect to the mean position of the sensor during the gait cycle. Each IGP is then straightened so that it is periodic with a last point matching the first one.

It is essentially a reduced version of the VESPA data set where IGPs have been averaged over the repetition for each set of conditions.

Index

- * **datasets**
 - vespa, 35
 - vespa64, 36
- [.qts_sample (qts_sample), 29
- append, 3
- as_qts (qts), 25
- as_qts(), 25
- as_qts_sample (qts_sample), 29
- as_qts_sample(), 29
- autoplot.prcomp_qts, 4
- autoplot.qts, 5
- autoplot.qts_sample, 6
- autoplot.qtsclust, 5
- centring, 7
- dbscan, 8
- differentiate, 10
- dist, 10
- DTW, 12
- dtw::dtw, 13
- dtw::stepPattern, 12
- dtw::symmetric2, 12
- exp, 13
- exp_cov_function, 32
- fdacluster::caps, 9, 15, 18
- format.qts (qts), 25
- frNN(), 8
- ggplot2::ggplot, 4–7, 24
- hclust, 14
- hclust.qts_sample(), 6, 23
- hemispherize, 15
- is_qts (qts), 25
- is_qts(), 25
- is_qts_sample (qts_sample), 29
- is_qts_sample(), 29
- kmeans, 16
- kmeans.qts_sample(), 6, 23
- log, 18
- mean.qts_sample, 19
- median.qts_sample, 20
- MFPCA::MFPCA(), 25
- moving_average, 20
- normalize, 21
- plot.prcomp_qts, 22
- plot.qts, 23
- plot.qts_sample, 24
- plot.qtsclust, 23
- prcomp.qts_sample, 25
- prcomp.qts_sample(), 4, 22
- qts, 3, 5, 7, 9, 10, 12, 13, 15, 16, 18–21, 23, 25, 25, 26–32, 34, 35
- qts2ats, 26
- qts2avts, 27
- qts2dts, 28
- qts2nts, 28
- qts_sample, 3, 6, 8–11, 13–21, 24, 25, 29, 29, 30, 31, 33–35
- reorient, 30
- resample, 31
- rnorm_qts, 32
- scale, 32
- screplot.prcomp_qts (plot.prcomp_qts), 22
- smooth, 34
- stats::dist, 11, 12
- stats::hclust, 9, 15, 18
- stats::hclust(), 14

stats::kmeans, [9](#), [15](#), [18](#)
straighten, [35](#)

text, [15](#)
tibble, [36](#)
tibble::tibble, [25–29](#)

vespa, [35](#)
vespa64, [36](#)