

Package ‘sweep’

August 19, 2018

Type Package

Title Tidy Tools for Forecasting

Version 0.2.1.1

Date 2018-03-03

Maintainer ORPHANED

Description Tidies up the forecasting modeling and prediction work flow, extends the 'broom' package with 'sw_tidy', 'sw_glance', 'sw_augment', and 'sw_tidy_decomp' functions for various forecasting models, and enables converting 'forecast' objects to ``tidy'' data frames with 'sw_sweep'.

URL <https://github.com/business-science/sweep>

BugReports <https://github.com/business-science/sweep/issues>

License GPL (>= 3)

Encoding UTF-8

LazyData true

Depends R (>= 3.3.0)

Imports broom (>= 0.4.2), devtools (>= 1.12.0), dplyr (>= 0.7.0), forecast (>= 8.0), lazyeval (>= 0.2.0), lubridate (>= 1.6.0), tibble (>= 1.2), tidyr (>= 0.6.1), timetk (>= 0.1.0)

Suggests forcats, knitr, rmarkdown, testthat, purrr, readr, robots, stringr, scales, tidyquant, tidyverse, fracdiff

RoxygenNote 6.0.1

VignetteBuilder knitr

NeedsCompilation no

Author Matt Dancho [aut, cre],
Davis Vaughan [aut]

Repository CRAN

Date/Publication 2018-08-19 08:51:40 UTC

X-CRAN-Original-Maintainer Matt Dancho <mdancho@business-science.io>

X-CRAN-Comment Orphaned and corrected on 2018-08-19 as check problems were not corrected despite reminders.

R topics documented:

add_index	2
arima_string	3
bats_string	3
bike_sales	4
sweep_package	5
sw_augment	5
sw_augment.default	6
sw_augment_columns	6
sw_glance	7
sw_glance.default	7
sw_sweep	8
sw_tidy	9
sw_tidy.default	10
sw_tidy_decomp	10
tbats_string	11
tidiers_arima	12
tidiers_bats	13
tidiers_decomposed_ts	16
tidiers_ets	17
tidiers_HoltWinters	19
tidiers_nnetar	21
tidiers_robets	22
tidiers_stl	25
tidiers_StructTS	26
validate_index	28
Index	29

add_index	<i>Adds a sequential index column to a data frame</i>
-----------	---

Description

Adds a sequential index column to a data frame

Usage

```
add_index(ret, rename_index)
```

Arguments

ret	An object of class tibble
rename_index	A variable indicating the index name to be used in the tibble returned

arima_string	<i>Print the ARIMA model parameters</i>
--------------	---

Description

Refer to forecast:::arima.string. [forecast arima.R](#)

Usage

```
arima_string(object, padding = FALSE)
```

Arguments

object	An object of class Arima
padding	Add padding to the name returned

bats_string	<i>Print the BATS model parameters</i>
-------------	--

Description

Refer to forecast:::makeText. [forecast bats.R](#)

Usage

```
bats_string(object)
```

Arguments

object	An object of class bats
--------	-------------------------

`bike_sales`*Fictional sales data for bike shops purchasing Cannondale bikes*

Description

A dataset containing the fictional bicycle orders spanning 2011 through 2015. Hypothetically, the `bike_sales` data are similar to sales data maintained in a business' sales data base. The unit price and model names come from data provided by model for the bicycle manufacturer, Cannondale (2016). The customers (bicycle shops) including name, location, etc and the orders including quantity purchased and order dates are fictional. The data is intended for implementing business analytics techniques (e.g. forecast, clustering, etc) to identify underlying trends.

Usage

`bike_sales`

Format

A data frame with 15644 rows and 17 variables:

order.date Date the order was placed
order.id A unique order identification number
order.line The sequential identification number for products on and order
quantity Number of units purchased
price The unit price of the bicycle
price.ext The extended price = price x quantity
customer.id A unique customer identification number
bikeshop.name The customer name
bikeshop.city The city that the bike shop is located
bikeshop.state The state that the bike shop is located
latitude The geographic latitude of the customer location
longitude The geographic longitude of the customer location
product.id A unique product identification number
model The model name of the bicycle
category.primary The main bicycle category, either "Mountain" or "Road"
category.secondary One of nine more specific bicycle categories
frame The bicycle frame material, either "Carbon" or "Aluminum"

Source

The 2016 bicycle model names and prices originated from <http://www.cannondale.com/en/USA>

sweep_package	<i>sweep: Extending broom to time series forecasting</i>
---------------	--

Description

sweep: Extending broom to time series forecasting

Details

The sweep package "tidies" up the modeling workflow of the forecast package. The model and forecast objects are not covered by the broom package. It includes the `sw_tidy()`, `sw_glance()`, and `sw_augment()` functions that work in a similar capacity as broom functions. In addition, it provides `sw_tidy_decomp()` to tidy decompositions, and `sw_sweep()` to coerce forecast objects to "tibbles" for easy visualization with `ggplot2` and manipulation with `dplyr`.

To learn more about sweep, start with the vignettes: `browseVignettes(package = "sweep")`

sw_augment	<i>Augment data according to a tidied model</i>
------------	---

Description

Given an R statistical model or other non-tidy object, add columns to the original dataset such as predictions, residuals and cluster assignments.

Usage

```
sw_augment(x, ...)
```

Arguments

x	model or other R object to convert to data frame
...	other arguments passed to methods

Details

`sw_augment()` is a wrapper for `broom::augment()`. The benefit of `sw_augment` is that it has methods for various time-series model classes such as `HoltWinters`, `ets`, `Arima`, etc.

For non-time series, `sw_augment()` defaults to `broom::augment()`. The only difference is that the return is a tibble.

Note that by convention the first argument is almost always data, which specifies the original data object. This is not part of the S3 signature, partly because it prevents `rowwise_df_tidiers` from taking a column name as the first argument.

See Also

[broom::augment\(\)](#)

sw_augment.default	<i>Default augment method</i>
--------------------	-------------------------------

Description

By default, `sw_augment()` uses `broom::augment()` to convert its output.

Usage

```
## Default S3 method:
sw_augment(x, ...)
```

Arguments

x	an object to be tidied
...	extra arguments passed to <code>broom::augment()</code>

Value

A tibble generated by `broom::augment()`

sw_augment_columns	<i>Augments data</i>
--------------------	----------------------

Description

Augments data

Usage

```
sw_augment_columns(ret, data, rename_index, timetk_idx = FALSE)
```

Arguments

ret	An object of class tibble
data	Any time series data that is to be augmented
rename_index	A variable indicating the index name to be used in the tibble returned
timetk_idx	Uses the timetk index (irregular time index) if present.

sw_glance	<i>Construct a single row summary "glance" of a model, fit, or other object</i>
-----------	---

Description

Construct a single row summary "glance" of a model, fit, or other object

Usage

```
sw_glance(x, ...)
```

Arguments

x	model or other R object to convert to single-row data frame
...	other arguments passed to methods

Details

sw_glance() is a wrapper for broom::glance(). The benefit of sw_glance is that it has methods for various time-series model classes such as HoltWinters, ets, Arima, etc. sw_glance methods always return either a one-row tibble or NULL. The single row includes summary statistics relevant to the model accuracy, which can be used to assess model fit and quality.

For non-time series, sw_glance() defaults to broom::glance(). The only difference is that the return is a tibble.

Value

single-row tibble with model summary information.

See Also

[broom::glance\(\)](#)

sw_glance.default	<i>Default glance method</i>
-------------------	------------------------------

Description

By default, sw_glance() uses [broom::glance\(\)](#) to convert its output.

Usage

```
## Default S3 method:  
sw_glance(x, ...)
```

Arguments

x an object to be tidied
 ... extra arguments passed to broom::glance()

Value

A tibble generated by broom::glance()

sw_sweep	<i>Tidy forecast objects</i>
----------	------------------------------

Description

Tidy forecast objects

Usage

```
sw_sweep(x, fitted = FALSE, timetk_idx = FALSE, rename_index = "index",
  ...)
```

Arguments

x A time-series forecast of class forecast.
 fitted Whether or not to return the fitted values (model values) in the results. FALSE by default.
 timetk_idx If timetk index (non-regularized index) is present, uses it to develop forecast. Otherwise uses default index.
 rename_index Enables the index column to be renamed.
 ... Additional arguments passed to tk_make_future_timeseries()

Details

sw_sweep is designed to coerce forecast objects from the forecast package into tibble objects in a "tidy" format (long). The returned object contains both the actual values and the forecasted values including the point forecast and upper and lower confidence intervals.

The timetk_idx argument is used to modify the return format of the index.

- If timetk_idx = FALSE, a regularized time index is always constructed. This may be in the format of numeric values (e.g. 2010.000) or the higher order yearmon and yearqtr classes from the zoo package. A higher order class is attempted to be returned.
- If timetk_idx = TRUE and a timetk index is present, an irregular time index will be returned that combines the original time series (i.e. date or datetime) along with a computed future time series created using tk_make_future_timeseries() from the timetk package. The ... can be used to pass additional arguments to tk_make_future_timeseries() such as inspect_weekdays, skip_values, etc that can be useful in tuning the future time series sequence.

The index column name can be changed using the rename_index argument.

Value

Returns a tibble object.

See Also

[tk_make_future_timeseries\(\)](#)

Examples

```
library(forecast)
library(sweep)

# ETS forecasts
USAccDeaths %>%
  ets() %>%
  forecast(level = c(80, 95, 99)) %>%
  sw_sweep()
```

sw_tidy

Tidy the result of a time-series model into a summary tibble

Description

Tidy the result of a time-series model into a summary tibble

Usage

```
sw_tidy(x, ...)
```

Arguments

x	An object to be converted into a tibble ("tidy" data.frame)
...	extra arguments

Details

sw_tidy() is a wrapper for broom::tidy(). The main benefit of sw_tidy() is that it has methods for various time-series model classes such as HoltWinters, ets, Arima, etc. sw_tidy() methods always returns a "tidy" tibble with model coefficient / parameters.

For non-time series, sw_tidy() defaults to broom::tidy(). The only difference is that the return is a tibble. The output of sw_tidy() is always a tibble with disposable row names. It is therefore suited for further manipulation by packages like dplyr and ggplot2.

Value

a tibble

See Also

[broom::tidy\(\)](#)

Examples

```
library(forecast)
WWWusage %>%
  auto.arima() %>%
  sw_tidy(conf.int = TRUE)
```

sw_tidy.default	<i>Default tidying method</i>
-----------------	-------------------------------

Description

By default, `sw_tidy()` uses [broom::tidy\(\)](#) to convert its output.

Usage

```
## Default S3 method:
sw_tidy(x, ...)
```

Arguments

`x` an object to be tidied
`...` extra arguments passed to [broom::tidy\(\)](#)

Value

A tibble generated by [broom::tidy\(\)](#)

sw_tidy_decomp	<i>Coerces decomposed time-series objects to tibble format.</i>
----------------	---

Description

Coerces decomposed time-series objects to tibble format.

Usage

```
sw_tidy_decomp(x, timetk_idx = FALSE, rename_index = "index", ...)
```

Arguments

x	A time-series object of class <code>stl</code> , <code>ets</code> , <code>decomposed.ts</code> , <code>HoltWinters</code> , <code>bats</code> or <code>tbats</code> .
timetk_idx	When TRUE, uses a timetk index (irregular, typically date or datetime) if present.
rename_index	Enables the index column to be renamed.
...	Not used.

Details

`sw_tidy_decomp` is designed to coerce time-series objects with decompositions to tibble objects.

A regularized time index is always constructed. If no time index is detected, a sequential index is returned as a default. The index column name can be changed using the `rename_index` argument.

Value

Returns a tibble object.

Examples

```
library(forecast)
library(sweep)

# Decompose ETS model
USAccDeaths %>%
  ets() %>%
  sw_tidy_decomp()

# Decompose STL object
USAccDeaths %>%
  stl(s.window = 'periodic') %>%
  sw_tidy_decomp()
```

tbats_string

Print the TBATS model parameters

Description

Refer to `forecast:::makeTextTBATS`. [forecast bats.R](#)

Usage

```
tbats_string(object)
```

Arguments

object	An object of class <code>bats</code> or <code>tbats</code>
--------	--

Description

These methods tidy the coefficients of ARIMA models of univariate time series.

Usage

```
## S3 method for class 'Arima'
sw_tidy(x, ...)
```

```
## S3 method for class 'Arima'
sw_glance(x, ...)
```

```
## S3 method for class 'Arima'
sw_augment(x, data = NULL, rename_index = "index",
           timetk_idx = FALSE, ...)
```

Arguments

x	An object of class "Arima"
...	Additional parameters (not used)
data	Used with <code>sw_augment</code> only. NULL by default which simply returns augmented columns only. User can supply the original data, which returns the data + augmented columns.
rename_index	Used with <code>sw_augment</code> only. A string representing the name of the index generated.
timetk_idx	Used with <code>sw_augment</code> only. Uses a irregular timetk index if present.

Value

`sw_tidy()` returns one row for each coefficient in the model, with five columns:

- `term`: The term in the nonlinear model being estimated and tested
- `estimate`: The estimated coefficient

`sw_glance()` returns one row with the columns

- `model.desc`: A description of the model including the three integer components (p, d, q) are the AR order, the degree of differencing, and the MA order.
- `sigma`: The square root of the estimated residual variance
- `logLik`: The data's log-likelihood under the model
- `AIC`: The Akaike Information Criterion
- `BIC`: The Bayesian Information Criterion

- ME: Mean error
- RMSE: Root mean squared error
- MAE: Mean absolute error
- MPE: Mean percentage error
- MAPE: Mean absolute percentage error
- MASE: Mean absolute scaled error
- ACF1: Autocorrelation of errors at lag 1

sw_augment() returns a tibble with the following time series attributes:

- index: An index is either attempted to be extracted from the model or a sequential index is created for plotting purposes
- .actual: The original time series
- .fitted: The fitted values from the model
- .resid: The residual values from the model

See Also

[arima\(\)](#), [Arima\(\)](#)

Examples

```
library(forecast)
library(sweep)

fit_arima <- WWWusage %>%
  auto.arima()

sw_tidy(fit_arima)
sw_glance(fit_arima)
sw_augment(fit_arima)
```

Description

Tidying methods for BATS and TBATS modeling of time series

Usage

```
## S3 method for class 'bats'
sw_tidy(x, ...)

## S3 method for class 'bats'
sw_glance(x, ...)

## S3 method for class 'bats'
sw_augment(x, data = NULL, rename_index = "index",
  timetk_idx = FALSE, ...)

## S3 method for class 'bats'
sw_tidy_decomp(x, timetk_idx = FALSE, rename_index = "index",
  ...)
```

Arguments

x	An object of class "bats" or "tbats"
...	Additional parameters (not used)
data	Used with <code>sw_augment</code> only. NULL by default which simply returns augmented columns only. User can supply the original data, which returns the data + augmented columns.
rename_index	Used with <code>sw_augment</code> only. A string representing the name of the index generated.
timetk_idx	Used with <code>sw_augment</code> and <code>sw_tidy_decomp</code> . When TRUE, uses a timetk index (irregular, typically date or datetime) if present.

Value

`sw_tidy()` returns one row for each model parameter, with two columns:

- term: The various parameters (lambda, alpha, gamma, etc)
- estimate: The estimated parameter value

`sw_glance()` returns one row with the columns

- model.desc: A description of the model including the three integer components (p, d, q) are the AR order, the degree of differencing, and the MA order.
- sigma: The square root of the estimated residual variance
- logLik: The data's log-likelihood under the model
- AIC: The Akaike Information Criterion
- BIC: The Bayesian Information Criterion (NA for bats / tbats)
- ME: Mean error
- RMSE: Root mean squared error
- MAE: Mean absolute error

- MPE: Mean percentage error
- MAPE: Mean absolute percentage error
- MASE: Mean absolute scaled error
- ACF1: Autocorrelation of errors at lag 1

`sw_augment()` returns a tibble with the following time series attributes:

- `index`: An index is either attempted to be extracted from the model or a sequential index is created for plotting purposes
- `.actual`: The original time series
- `.fitted`: The fitted values from the model
- `.resid`: The residual values from the model

`sw_tidy_decomp()` returns a tibble with the following time series attributes:

- `index`: An index is either attempted to be extracted from the model or a sequential index is created for plotting purposes
- `observed`: The original time series
- `level`: The level component
- `slope`: The slope component (Not always present)
- `season`: The seasonal component (Not always present)

See Also

[bats\(\)](#), [tbats\(\)](#)

Examples

```
library(forecast)
library(sweep)

fit_bats <- WWWusage %>%
  bats()

sw_tidy(fit_bats)
sw_glance(fit_bats)
sw_augment(fit_bats)
```

tidiers_decomposed_ts *Tidying methods for decomposed time series*

Description

Tidying methods for decomposed time series

Usage

```
## S3 method for class 'decomposed.ts'  
sw_tidy_decomp(x, timetk_idx = FALSE,  
  rename_index = "index", ...)
```

Arguments

x	An object of class "decomposed.ts"
timetk_idx	Used with <code>sw_augment</code> and <code>sw_tidy_decomp</code> . When TRUE, uses a timetk index (irregular, typically date or datetime) if present.
rename_index	Used with <code>sw_augment</code> and <code>sw_tidy_decomp</code> . A string representing the name of the index generated.
...	Not used.

Value

`sw_tidy_decomp()` returns a tibble with the following time series attributes:

- `index`: An index is either attempted to be extracted from the model or a sequential index is created for plotting purposes
- `season`: The seasonal component
- `trend`: The trend component
- `random`: The error component
- `seasadj`: observed - season

See Also

[decompose\(\)](#)

Examples

```
library(forecast)  
library(sweep)  
  
fit_decomposed <- USAccDeaths %>%  
  decompose()  
  
sw_tidy_decomp(fit_decomposed)
```

tidiers_ets	<i>Tidying methods for ETS (Error, Trend, Seasonal) exponential smoothing modeling of time series</i>
-------------	---

Description

Tidying methods for ETS (Error, Trend, Seasonal) exponential smoothing modeling of time series

Usage

```
## S3 method for class 'ets'
sw_tidy(x, ...)

## S3 method for class 'ets'
sw_glance(x, ...)

## S3 method for class 'ets'
sw_augment(x, data = NULL, timetk_idx = FALSE,
           rename_index = "index", ...)

## S3 method for class 'ets'
sw_tidy_decomp(x, timetk_idx = FALSE, rename_index = "index",
              ...)
```

Arguments

x	An object of class "ets"
...	Not used.
data	Used with <code>sw_augment</code> only. NULL by default which simply returns augmented columns only. User can supply the original data, which returns the data + augmented columns.
timetk_idx	Used with <code>sw_augment</code> and <code>sw_tidy_decomp</code> . When TRUE, uses a timetk index (irregular, typically date or datetime) if present.
rename_index	Used with <code>sw_augment</code> and <code>sw_tidy_decomp</code> . A string representing the name of the index generated.

Value

`sw_tidy()` returns one row for each model parameter, with two columns:

- `term`: The smoothing parameters (alpha, gamma) and the initial states (l, s0 through s10)
- `estimate`: The estimated parameter value

`sw_glance()` returns one row with the columns

- `model.desc`: A description of the model including the three integer components (p, d, q) are the AR order, the degree of differencing, and the MA order.

- `sigma`: The square root of the estimated residual variance
- `logLik`: The data's log-likelihood under the model
- `AIC`: The Akaike Information Criterion
- `BIC`: The Bayesian Information Criterion
- `ME`: Mean error
- `RMSE`: Root mean squared error
- `MAE`: Mean absolute error
- `MPE`: Mean percentage error
- `MAPE`: Mean absolute percentage error
- `MASE`: Mean absolute scaled error
- `ACF1`: Autocorrelation of errors at lag 1

`sw_augment()` returns a tibble with the following time series attributes:

- `index`: An index is either attempted to be extracted from the model or a sequential index is created for plotting purposes
- `.actual`: The original time series
- `.fitted`: The fitted values from the model
- `.resid`: The residual values from the model

`sw_tidy_decomp()` returns a tibble with the following time series attributes:

- `index`: An index is either attempted to be extracted from the model or a sequential index is created for plotting purposes
- `observed`: The original time series
- `level`: The level component
- `slope`: The slope component (Not always present)
- `season`: The seasonal component (Not always present)

See Also

[ets\(\)](#)

Examples

```
library(forecast)
library(sweep)

fit_ets <- WWWusage %>%
  ets()

sw_tidy(fit_ets)
sw_glance(fit_ets)
sw_augment(fit_ets)
sw_tidy_decomp(fit_ets)
```

tidiers_HoltWinters *Tidying methods for HoltWinters modeling of time series*

Description

These methods tidy HoltWinters models of univariate time series.

Usage

```
## S3 method for class 'HoltWinters'
sw_tidy(x, ...)

## S3 method for class 'HoltWinters'
sw_glance(x, ...)

## S3 method for class 'HoltWinters'
sw_augment(x, data = NULL, rename_index = "index",
           timetk_idx = FALSE, ...)

## S3 method for class 'HoltWinters'
sw_tidy_decomp(x, timetk_idx = FALSE,
              rename_index = "index", ...)
```

Arguments

x	An object of class "HoltWinters"
...	Additional parameters (not used)
data	Used with sw_augment only. NULL by default which simply returns augmented columns only. User can supply the original data, which returns the data + augmented columns.
rename_index	Used with sw_augment only. A string representing the name of the index generated.
timetk_idx	Used with sw_augment and sw_tidy_decomp. When TRUE, uses a timetk index (irregular, typically date or datetime) if present.

Value

sw_tidy() returns one row for each model parameter, with two columns:

- term: The various parameters (alpha, beta, gamma, and coefficients)
- estimate: The estimated parameter value

sw_glance() returns one row with the following columns:

- model.desc: A description of the model
- sigma: The square root of the estimated residual variance

- logLik: The data's log-likelihood under the model
- AIC: The Akaike Information Criterion
- BIC: The Bayesian Information Criterion (NA for bats / tbats)
- ME: Mean error
- RMSE: Root mean squared error
- MAE: Mean absolute error
- MPE: Mean percentage error
- MAPE: Mean absolute percentage error
- MASE: Mean absolute scaled error
- ACF1: Autocorrelation of errors at lag 1

sw_augment() returns a tibble with the following time series attributes:

- index: An index is either attempted to be extracted from the model or a sequential index is created for plotting purposes
- .actual: The original time series
- .fitted: The fitted values from the model
- .resid: The residual values from the model

sw_tidy_decomp() returns a tibble with the following time series attributes:

- index: An index is either attempted to be extracted from the model or a sequential index is created for plotting purposes
- observed: The original time series
- season: The seasonal component
- trend: The trend component
- remainder: observed - (season + trend)
- seasadj: observed - season (or trend + remainder)

See Also

[HoltWinters\(\)](#)

Examples

```
library(forecast)
library(sweep)

fit_hw <- USAccDeaths %>%
  stats::HoltWinters()

sw_tidy(fit_hw)
sw_glance(fit_hw)
sw_augment(fit_hw)
sw_tidy_decomp(fit_hw)
```

tidiers_nnetar *Tidying methods for Neural Network Time Series models*

Description

These methods tidy the coefficients of NNETAR models of univariate time series.

Usage

```
## S3 method for class 'nnetar'
sw_tidy(x, ...)

## S3 method for class 'nnetar'
sw_glance(x, ...)

## S3 method for class 'nnetar'
sw_augment(x, data = NULL, timetk_idx = FALSE,
           rename_index = "index", ...)
```

Arguments

x	An object of class "nnetar"
...	Additional parameters (not used)
data	Used with <code>sw_augment</code> only. NULL by default which simply returns augmented columns only. User can supply the original data, which returns the data + augmented columns.
timetk_idx	Used with <code>sw_augment</code> only. Uses a irregular timetk index if present.
rename_index	Used with <code>sw_augment</code> only. A string representing the name of the index generated.

Value

`sw_tidy()` returns one row for each model parameter, with two columns:

- `term`: The smoothing parameters (alpha, gamma) and the initial states (l, s0 through s10)
- `estimate`: The estimated parameter value

`sw_glance()` returns one row with the columns

- `model.desc`: A description of the model including the three integer components (p, d, q) are the AR order, the degree of differencing, and the MA order.
- `sigma`: The square root of the estimated residual variance
- `logLik`: The data's log-likelihood under the model (NA)
- `AIC`: The Akaike Information Criterion (NA)
- `BIC`: The Bayesian Information Criterion (NA)

- ME: Mean error
- RMSE: Root mean squared error
- MAE: Mean absolute error
- MPE: Mean percentage error
- MAPE: Mean absolute percentage error
- MASE: Mean absolute scaled error
- ACF1: Autocorrelation of errors at lag 1

`sw_augment()` returns a tibble with the following time series attributes:

- `index`: An index is either attempted to be extracted from the model or a sequential index is created for plotting purposes
- `.actual`: The original time series
- `.fitted`: The fitted values from the model
- `.resid`: The residual values from the model

See Also

[nnetar\(\)](#)

Examples

```
library(forecast)
library(sweep)

fit_nnetar <- lynx %>%
  nnetar()

sw_tidy(fit_nnetar)
sw_glance(fit_nnetar)
sw_augment(fit_nnetar)
```

tidiers_robets

Tidying methods for robets (Robust Error, Trend, Seasonal) exponential smoothing modeling of time series

Description

Tidying methods for robets (Robust Error, Trend, Seasonal) exponential smoothing modeling of time series

Usage

```
## S3 method for class 'robets'
sw_tidy(x, ...)

## S3 method for class 'robets'
sw_glance(x, ...)

## S3 method for class 'robets'
sw_augment(x, data = NULL, timetk_idx = FALSE,
  rename_index = "index", ...)

## S3 method for class 'robets'
sw_tidy_decomp(x, timetk_idx = FALSE,
  rename_index = "index", ...)
```

Arguments

x	An object of class "robets"
...	Not used.
data	Used with <code>sw_augment</code> only. NULL by default which simply returns augmented columns only. User can supply the original data, which returns the data + augmented columns.
timetk_idx	Used with <code>sw_augment</code> and <code>sw_tidy_decomp</code> . When TRUE, uses a timetk index (irregular, typically date or datetime) if present.
rename_index	Used with <code>sw_augment</code> and <code>sw_tidy_decomp</code> . A string representing the name of the index generated.

Value

`sw_tidy()` returns one row for each model parameter, with two columns:

- term: The smoothing parameters (alpha, gamma) and the initial states (l, s0 through s10)
- estimate: The estimated parameter value

`sw_glance()` returns one row with the columns

- model.desc: A description of the model including the three integer components (p, d, q) are the AR order, the degree of differencing, and the MA order.
- sigma: The square root of the estimated residual variance
- logLik: The data's log-likelihood under the model
- AIC: The Akaike Information Criterion
- BIC: The Bayesian Information Criterion
- ME: Mean error
- RMSE: Root mean squared error
- MAE: Mean absolute error

- MPE: Mean percentage error
- MAPE: Mean absolute percentage error
- MASE: Mean absolute scaled error
- ACF1: Autocorrelation of errors at lag 1

`sw_augment()` returns a tibble with the following time series attributes:

- `index`: An index is either attempted to be extracted from the model or a sequential index is created for plotting purposes
- `.actual`: The original time series
- `.fitted`: The fitted values from the model
- `.resid`: The residual values from the model

`sw_tidy_decomp()` returns a tibble with the following time series attributes:

- `index`: An index is either attempted to be extracted from the model or a sequential index is created for plotting purposes
- `observed`: The original time series
- `level`: The level component
- `slope`: The slope component (Not always present)
- `season`: The seasonal component (Not always present)

See Also

[robets::robets\(\)](#)

Examples

```
library(robets)
library(sweep)

fit_robets <- WWWusage %>%
  robets()

sw_tidy(fit_robets)
sw_glance(fit_robets)
sw_augment(fit_robets)
sw_tidy_decomp(fit_robets)
```

tidiers_stl	<i>Tidying methods for STL (Seasonal, Trend, Level) decomposition of time series</i>
-------------	--

Description

Tidying methods for STL (Seasonal, Trend, Level) decomposition of time series

Usage

```
## S3 method for class 'stl'  
sw_tidy(x, ...)  
  
## S3 method for class 'stl'  
sw_tidy_decomp(x, timetk_idx = FALSE, rename_index = "index",  
  ...)  
  
## S3 method for class 'stlm'  
sw_tidy_decomp(x, timetk_idx = FALSE, rename_index = "index",  
  ...)
```

Arguments

x	An object of class "stl" or "stlm"
...	Not used.
timetk_idx	Used with sw_tidy_decomp. When TRUE, uses a timetk index (irregular, typically date or datetime) if present.
rename_index	Used with sw_tidy_decomp. A string representing the name of the index generated.

Value

sw_tidy() wraps sw_tidy_decomp()

sw_tidy_decomp() returns a tibble with the following time series attributes:

- index: An index is either attempted to be extracted from the model or a sequential index is created for plotting purposes
- season: The seasonal component
- trend: The trend component
- remainder: observed - (season + trend)
- seasadj: observed - season (or trend + remainder)

See Also

[stl\(\)](#)

Examples

```
library(forecast)
library(sweep)

fit_stl <- USAccDeaths %>%
  stl(s.window = "periodic")

sw_tidy_decomp(fit_stl)
```

tidiers_StructTS	<i>Tidying methods for StructTS (Error, Trend, Seasonal) / exponential smoothing modeling of time series</i>
------------------	--

Description

These methods tidy the coefficients of StructTS models of univariate time series.

Usage

```
## S3 method for class 'StructTS'
sw_tidy(x, ...)

## S3 method for class 'StructTS'
sw_glance(x, ...)

## S3 method for class 'StructTS'
sw_augment(x, data = NULL, timetk_idx = FALSE,
  rename_index = "index", ...)
```

Arguments

x	An object of class "StructTS"
...	Additional parameters (not used)
data	Used with <code>sw_augment</code> only. NULL by default which simply returns augmented columns only. User can supply the original data, which returns the data + augmented columns.
timetk_idx	Used with <code>sw_augment</code> only. Uses an irregular timetk index if present.
rename_index	Used with <code>sw_augment</code> only. A string representing the name of the index generated.

Value

`sw_tidy()` returns one row for each model parameter, with two columns:

- term: The model parameters

- `estimate`: The estimated parameter value

`sw_glance()` returns one row with the columns

- `model.desc`: A description of the model including the three integer components (p, d, q) are the AR order, the degree of differencing, and the MA order.
- `sigma`: The square root of the estimated residual variance
- `logLik`: The data's log-likelihood under the model
- `AIC`: The Akaike Information Criterion
- `BIC`: The Bayesian Information Criterion
- `ME`: Mean error
- `RMSE`: Root mean squared error
- `MAE`: Mean absolute error
- `MPE`: Mean percentage error
- `MAPE`: Mean absolute percentage error
- `MASE`: Mean absolute scaled error
- `ACF1`: Autocorrelation of errors at lag 1

`sw_augment()` returns a tibble with the following time series attributes:

- `index`: An index is either attempted to be extracted from the model or a sequential index is created for plotting purposes
- `.actual`: The original time series
- `.fitted`: The fitted values from the model
- `.resid`: The residual values from the model

See Also

[StructTS\(\)](#)

Examples

```
library(forecast)
library(sweep)

fit_StructTS <- WWWusage %>%
  StructTS()

sw_tidy(fit_StructTS)
sw_glance(fit_StructTS)
sw_augment(fit_StructTS)
```

validate_index	<i>Validates data frame has column named the same name as variable rename_index</i>
----------------	---

Description

Validates data frame has column named the same name as variable rename_index

Usage

```
validate_index(ret, rename_index)
```

Arguments

ret	An object of class tibble
rename_index	A variable indicating the index name to be used in the tibble returned

Index

*Topic **datasets**

- bike_sales, 4
- add_index, 2
- Arima(), 13
- arima(), 13
- arima_string, 3
- bats(), 15
- bats_string, 3
- bike_sales, 4
- broom::augment(), 5, 6
- broom::glance(), 7, 8
- broom::tidy(), 10
- decompose(), 16
- ets(), 18
- HoltWinters(), 20
- nnetar(), 22
- robets::robets(), 24
- rowwise_df_tidiers, 5
- stl(), 25
- StructTS(), 27
- sw_augment, 5
- sw_augment(), 5
- sw_augment.Arima(tidiers_arima), 12
- sw_augment.bats(tidiers_bats), 13
- sw_augment.default, 6
- sw_augment.ets(tidiers_ets), 17
- sw_augment.HoltWinters
(tidiers_HoltWinters), 19
- sw_augment.nnetar(tidiers_nnetar), 21
- sw_augment.robets(tidiers_robets), 22
- sw_augment.StructTS(tidiers_StructTS),
26
- sw_augment_columns, 6
- sw_glance, 7
- sw_glance(), 5
- sw_glance.Arima(tidiers_arima), 12
- sw_glance.bats(tidiers_bats), 13
- sw_glance.default, 7
- sw_glance.ets(tidiers_ets), 17
- sw_glance.HoltWinters
(tidiers_HoltWinters), 19
- sw_glance.nnetar(tidiers_nnetar), 21
- sw_glance.robets(tidiers_robets), 22
- sw_glance.StructTS(tidiers_StructTS),
26
- sw_sweep, 8
- sw_sweep(), 5
- sw_tidy, 9
- sw_tidy(), 5
- sw_tidy.Arima(tidiers_arima), 12
- sw_tidy.bats(tidiers_bats), 13
- sw_tidy.default, 10
- sw_tidy.ets(tidiers_ets), 17
- sw_tidy.HoltWinters
(tidiers_HoltWinters), 19
- sw_tidy.nnetar(tidiers_nnetar), 21
- sw_tidy.robets(tidiers_robets), 22
- sw_tidy.stl(tidiers_stl), 25
- sw_tidy.StructTS(tidiers_StructTS), 26
- sw_tidy_decomp, 10
- sw_tidy_decomp(), 5
- sw_tidy_decomp.bats(tidiers_bats), 13
- sw_tidy_decomp.decomposed.ts
(tidiers_decomposed_ts), 16
- sw_tidy_decomp.ets(tidiers_ets), 17
- sw_tidy_decomp.HoltWinters
(tidiers_HoltWinters), 19
- sw_tidy_decomp.robets(tidiers_robets),
22
- sw_tidy_decomp.stl(tidiers_stl), 25
- sw_tidy_decomp.stlm(tidiers_stl), 25
- sweep_package, 5

sweep_package-package (sweep_package), 5

tbats(), 15

tbats_string, 11

tidiers_arima, 12

tidiers_bats, 13

tidiers_decomposed_ts, 16

tidiers_ets, 17

tidiers_HoltWinters, 19

tidiers_nnetar, 21

tidiers_robets, 22

tidiers_stl, 25

tidiers_StructTS, 26

tk_make_future_timeseries(), 9

validate_index, 28