

Package ‘text2map’

April 12, 2022

Type Package

Title R Tools for Text Matrices, Embeddings, and Networks

Version 0.1.4

Description This is a collection of functions optimized for working with various kinds of text matrices. Focusing on the text matrix as the primary object - represented either as a base R dense matrix or a 'Matrix' package sparse matrix - allows for a consistent and intuitive interface that stays close to the underlying mathematical foundation of computational text analysis. In particular, the package includes functions for working with word embeddings, text networks, and document-term matrices. Methods developed in Stoltz and Taylor (2019) <[doi:10.1007/s42001-019-00048-6](https://doi.org/10.1007/s42001-019-00048-6)>, Taylor and Stoltz (2020) <[doi:10.1007/s42001-020-00075-8](https://doi.org/10.1007/s42001-020-00075-8)>, Taylor and Stoltz (2020) <[doi:10.15195/v7.a23](https://doi.org/10.15195/v7.a23)>, and Stoltz and Taylor (2021) <[doi:10.1016/j.poetic.2021.101567](https://doi.org/10.1016/j.poetic.2021.101567)>.

URL <https://gitlab.com/culturalcartography/text2map>

License MIT + file LICENSE

Encoding UTF-8

LazyData true

BugReports <https://gitlab.com/culturalcartography/text2map/-/issues>

RoxygenNote 7.1.2

Depends R (>= 3.5.0)

Imports tibble, Matrix, text2vec, parallel, doParallel, foreach, stringr, stringi, dplyr, kit, fastmatch, mlpack, methods, qgraph (>= 1.6.9), igraph (>= 1.2.6), magrittr, rlang

Suggests testthat (>= 3.0.0), tidytext, tm, quanteda, knitr, rmarkdown

Config/testthat/edition 3

VignetteBuilder knitr, rmarkdown

NeedsCompilation no

Author Dustin Stoltz [aut, cre] (<<https://orcid.org/0000-0002-4774-0765>>),
 Marshall Taylor [aut] (<<https://orcid.org/0000-0002-7440-0723>>)

Maintainer Dustin Stoltz <maintainers@textmapping.com>

Repository CRAN

Date/Publication 2022-04-12 07:10:02 UTC

R topics documented:

anchor_lists	2
CMDist	3
CoCA	6
dtm_builder	8
dtm_melter	10
dtm_resampler	11
dtm_stats	12
dtm_stopper	13
find_projection	15
find_rejection	16
find_transformation	17
ft_wv_sample	18
get_anchors	18
get_centroid	20
get_direction	21
get_regions	22
get_stoplist	24
jfk_speech	26
plot.CoCA	26
print.CoCA	27
stoplists	28
tiny_gender_tagger	29
vocab_builder	29
Index	30

anchor_lists	<i>A dataset of anchor lists</i>
--------------	----------------------------------

Description

A dataset containing juxtaposing pairs of English words for 26 semantic relations. These anchors are used with the `get_anchors()` function, which can then be used with the `get_direction()` function. These have been collected from previously published articles and should be used as a starting point for defining a given relation in a word embedding model.

Usage

anchor_lists

Format

A data frame with 303 rows and 4 variables.

Variables

Variables:

- add. words to be added (or the positive direction)
- subtract. words to be subtract (or the negative direction)
- relation. the relation to be extracted, 26 relations available
- domain. 6 broader categories within which each relation falls

See Also

[CoCA](#), [get_direction](#), [get_centroid](#), [get_anchors](#)

CMDist

Calculate Concept Mover's Distance

Description

Concept Mover's Distance classifies documents of any length along a continuous measure of engagement with a given concept of interest using word embeddings.

Usage

```
CMDist(  
  dtm,  
  cw = NULL,  
  cv = NULL,  
  wv,  
  missing = "stop",  
  scale = TRUE,  
  sens_interval = FALSE,  
  alpha = 1,  
  n_iters = 20L,  
  parallel = FALSE,  
  threads = 2L,  
  setup_timeout = 120L  
)
```

Arguments

<code>dtm</code>	Document-term matrix with words as columns. Works with DTMs produced by any popular text analysis package, or using the <code>dtm_builder()</code> function.
<code>cw</code>	Vector with concept word(s) (e.g., <code>c("love", "money")</code> , <code>c("critical thinking")</code>)
<code>cv</code>	Concept vector(s) as output from <code>get_direction()</code> , <code>get_centroid()</code> , or <code>get_regions()</code>
<code>wv</code>	Matrix of word embedding vectors (a.k.a embedding model) with rows as words.
<code>missing</code>	Indicates what action to take if words are not in embeddings. If <code>action = "stop"</code> (default), the function is stopped and an error messages states which words are missing. If <code>action = "remove"</code> , output is the same as terms but missing words or rows with missing words are removed. Missing words will be printed as a message.
<code>scale</code>	Logical (default = <code>FALSE</code>) uses <code>scale()</code> on output. This will set zero to the mean of the estimates, and scale by the standard deviation of the estimates. Document estimates will, therefore, be relative to other documents within that specific run, but not necessarily across discrete runs.
<code>sens_interval</code>	logical (default = <code>FALSE</code>), if <code>TRUE</code> several CMDs will be estimate on <code>N</code> resampled DTMs, sensitivity intervals are produced by returning the 2.5 and 97.5 percentiles of estimated CMDs for a given concept word or concept vector.
<code>alpha</code>	If <code>sens_interval = TRUE</code> , a number indicating the proportion of the document length to be resampled for sensitivity intervals. Default is 1 or 100 percent of each documents' length.
<code>n_iters</code>	If <code>sens_interval = TRUE</code> , integer (default = 20L) indicates the number of resampled DTMs to produced for sensitivity intervals
<code>parallel</code>	Logical (default = <code>FALSE</code>), whether to parallelize estimate
<code>threads</code>	If <code>parallel = TRUE</code> , an integer indicating attempts to connect to master before failing.
<code>setup_timeout</code>	If <code>parallel = TRUE</code> , maximum number of seconds a worker attempts to connect to master before failing.

Details

`CMDist()` requires three things: a (1) document-term matrix (DTM), a (2) matrix of word embedding vectors, and (3) concept words or concept vectors. The function uses *word counts* from the DTM and *word similarities* from the cosine similarity of their respective word vectors in a word embedding model. The "cost" of transporting all the words in a document to a single vector or a few vectors (denoting a concept of interest) is the measure of engagement, with higher costs indicating less engagement. For intuitiveness the output of `CMDist()` is inverted such that higher numbers will indicate *more engagement* with a concept of interest.

The vector, or vectors, of the concept are specified in several ways. The simplest involves selecting a single word from the word embeddings, the analyst can also specify the concept by indicating a few words. The algorithm then splits the overall flow between each concept word (roughly) depending on which word in the document is nearest. The words need not be in the DTM, but they must be in the word embeddings (the function will either stop or remove words not in the embeddings).

Instead of selecting a word already in the embedding space, the function can also take a vector extracted from the embedding space in the form of a centroid (which averages the vectors of several words), a direction (which uses the offset of several juxtaposing words), or a region (which is built by clustering words into k regions). The `get_centroid()`, `get_direction()`, and `get_regions()` functions will extract these.

Value

Returns a data frame with the first column as document ids and each subsequent column as the CMD engagement corresponding to each concept word or concept vector. The upper and lower bound estimates will follow each unique CMD if `sens_interval = TRUE`.

Author(s)

Dustin Stoltz and Marshall Taylor

References

- Stoltz, Dustin S., and Marshall A. Taylor. (2019) 'Concept Mover's Distance' *Journal of Computational Social Science* 2(2):293-313. doi: [10.1007/s42001019000486](https://doi.org/10.1007/s42001019000486).
- Taylor, Marshall A., and Dustin S. Stoltz. (2020) 'Integrating semantic directions with concept mover's distance to measure binary concept engagement.' *Journal of Computational Social Science* 1-12. doi: [10.1007/s42001020000758](https://doi.org/10.1007/s42001020000758).
- Taylor, Marshall A., and Dustin S. Stoltz. (2020) 'Concept Class Analysis: A Method for Identifying Cultural Schemas in Texts.' *Sociological Science* 7:544-569. doi: [10.15195/v7.a23](https://doi.org/10.15195/v7.a23).

See Also

[CoCA](#), [get_direction](#), [get_centroid](#)

Examples

```
# load example word embeddings
data(ft_wv_sample)

# load example text
data(jfk_speech)

# minimal preprocessing
jfk_speech$sentence <- tolower(jfk_speech$sentence)
jfk_speech$sentence <- gsub("[[:punct:]]+", " ", jfk_speech$sentence)

# create DTM
dtm <- dtm_builder(jfk_speech, sentence, sentence_id)

# example 1
cm.dists <- CMDist(dtm,
  cw = "space",
  wv = ft_wv_sample)
```

```

)

# example 2
space <- c("spacecraft", "rocket", "moon")
cen <- get_centroid(anchors = space, wv = ft_wv_sample)

cm.dists <- CMDist(dtm,
  cv = cen,
  wv = ft_wv_sample
)

```

CoCA

Performs Concept Class Analysis (CoCA)

Description

CoCA outputs schematic classes derived from documents' engagement with multiple bi-polar concepts (in a Likert-style fashion). The function requires a (1) DTM of a corpus which can be obtained using any popular text analysis package, or from the `dtm_builder()` function, and (2) semantic directions as output from the `get_direction()`. `CMDist()` works under the hood. Code modified from the `corclass` package.

Usage

```

CoCA(
  dtm,
  wv = NULL,
  directions = NULL,
  filter_sig = TRUE,
  filter_value = 0.05,
  zero_action = c("drop", "ownclass")
)

```

Arguments

<code>dtm</code>	Document-term matrix with words as columns. Works with DTMs produced by any popular text analysis package, or you can use the <code>dtm_builder()</code> function.
<code>wv</code>	Matrix of word embedding vectors (a.k.a embedding model) with rows as words.
<code>directions</code>	direction vectors output from <code>get_direction()</code>
<code>filter_sig</code>	logical (default = TRUE), sets 'insignificant' ties to 0 to decrease noise and increase stability
<code>filter_value</code>	Minimum significance cutoff. Absolute row correlations below this value will be set to 0
<code>zero_action</code>	If 'drop', CCA drops rows with 0 variance from the analyses (default). If 'own-class', the correlations between 0-variance rows and all other rows is set 0, and the correlations between all pairs of 0-var rows are set to 1

Value

Returns a named list object of class CoCA. List elements include:

- membership: document memberships
- modules: schematic classes
- cormat: correlation matrix

Author(s)

Dustin Stoltz and Marshall Taylor

References

Taylor, Marshall A., and Dustin S. Stoltz. (2020) 'Concept Class Analysis: A Method for Identifying Cultural Schemas in Texts.' *Sociological Science* 7:544-569. doi: [10.15195/v7.a23](https://doi.org/10.15195/v7.a23).
Boutyline, Andrei. 'Improving the measurement of shared cultural schemas with correlational class analysis: Theory and method.' *Sociological Science* 4.15 (2017): 353-393. doi: [10.15195/v4.a15](https://doi.org/10.15195/v4.a15)

See Also

[CMDist](#), [get_direction](#)

Examples

```
## load example word embeddings
data(ft_wv_sample)

## load example text
data(jfk_speech)

## minimal preprocessing
jfk_speech$sentence <- tolower(jfk_speech$sentence)
jfk_speech$sentence <- gsub("[[:punct:]]+", " ", jfk_speech$sentence)

## create DTM
dtm <- dtm_builder(jfk_speech, sentence, sentence_id)

## create semantic directions
gen <- data.frame(
  add = c("woman"),
  subtract = c("man")
)

die <- data.frame(
  add = c("alive"),
  subtract = c("die")
)

gen.dir <- get_direction(anchors = gen, wv = ft_wv_sample)
```

```

die.dir <- get_direction(anchors = die, wv = ft_wv_sample)

sem_dirs <- rbind(gen.dir, die.dir)

classes <- CoCA(
  dtm = dtm,
  wv = ft_wv_sample,
  directions = sem_dirs,
  filter_sig = TRUE,
  filter_value = 0.05,
  zero_action = "drop"
)

print(classes)

```

dtm_builder

A fast unigram DTM builder

Description

A streamlined function to take raw texts from a column of a data.frame and produce a sparse Document-Term Matrix (of generic class "dgCMatrix").

Usage

```

dtm_builder(
  data,
  text,
  doc_id = NULL,
  vocab = NULL,
  chunk = NULL,
  dense = FALSE
)

```

Arguments

data	Data.frame with column of texts and column of document ids
text	Name of the column with documents' text
doc_id	Name of the column with documents' unique ids.
vocab	Default is NULL, if a list of terms is provided, the function will return a DTM with terms restricted to this vocabulary. Columns will also be in the same order as the list of terms.
chunk	Default is NULL, if an integer is provided, the function will "re-chunk" the corpus into new documents of a particular length. For example, 100L will divide the corpus into new documents with 100 terms (with the final document likely including slightly less than 100).
dense	The default (FALSE) is to return a matrix of class "dgCMatrix" because document-term matrix typically have mostly zero cells. This is much more memory efficient. Setting dense to TRUE will return a normal baseR' matrix.

Details

The function is fast because it has few bells and whistles:

- No weighting schemes other than raw counts
- Tokenizes by the fixed, single whitespace
- Only tokenizes unigrams. No bigrams, trigrams, etc...
- Columns are in the order unique terms are discovered
- No preprocessing during building
- Outputs a basic sparse Matrix or dense matrix

Weighting or stopping terms can be done efficiently after the fact with simple matrix operations, rather than achieved implicitly within the function itself. For example, using the `dtm_stopper()` function. Prior to creating the DTM, texts should have whitespace trimmed, if desired, punctuation removed and terms lowercased.

Like `tidytext`'s DTM functions, `dtm_builder()` is optimized for use in a pipeline, but unlike `tidytext`, it does not build an intermediary tripletlist, so `dtm_builder()` is faster and far more memory efficient.

The function can also chunk the corpus into documents of a given length (default is `NULL`). If the integer provided is `200L`, this will divide the corpus into new documents with 200 terms (with the final document likely including slightly less than 200). If the total terms in the corpus were less than or equal to chunk integer, this would produce a DTM with one document (most will probably not want this).

If the vocabulary is already known, or standardizing vocabulary across several DTMs is desired, a list of terms can be provided to the `vocab` argument. Columns of the DTM will be in the order of the list of terms.

Value

returns a document-term matrix of class "dgCMatrix" or class "matrix"

Author(s)

Dustin Stoltz

Examples

```
library(dplyr)

my.corpus <- data.frame(
  text = c(
    "I hear babies crying I watch them grow",
    "They'll learn much more than I'll ever know",
    "And I think to myself",
    "What a wonderful world",
    "Yes I think to myself",
    "What a wonderful world"
  ),
```

```

  line_id = paste0("line", seq_len(6))
)
## some text preprocessing
my.corpus$clean_text <- tolower(gsub("'", "", my.corpus$text))

# example 1 with R 4.1 pipe

dtm <- my.corpus |>
  dtm_builder(clean_text, line_id)

# example 2 without pipe
dtm <- dtm_builder(
  data = my.corpus,
  text = clean_text,
  doc_id = line_id
)

# example 3 with dplyr pipe and mutate
dtm <- my.corpus %>%
  mutate(
    clean_text = gsub("'", "", text),
    clean_text = tolower(clean_text)
  ) %>%
  dtm_builder(clean_text, line_id)

# example 4 with dplyr and chunk of 3 terms
dtm <- my.corpus %>%
  dtm_builder(clean_text,
    line_id,
    chunk = 3L
  )

# example 5 with user defined vocabulary
my.vocab <- c("wonderful", "world", "haiku", "think")

dtm <- dtm_builder(
  data = my.corpus,
  text = clean_text,
  doc_id = line_id,
  vocab = my.vocab
)

```

dtm_melter

Melt a DTM into a triplet data frame

Description

Converts a DTM into a data frame with three columns: documents, terms, frequency. Each row is a unique document by term frequency. This is akin to reshape2 packages melt function, but works on a sparse matrix. The resulting data frame is also equivalent to the tidytext triplet tibble.

Usage

```
dtm_melter(dtm)
```

Arguments

dtm Document-term matrix with terms as columns. Works with DTMs produced by any popular text analysis package, or using the `dtm_builder()` function.

Value

returns data frame with three columns: `doc_id`, `term`, `freq`

Author(s)

Dustin Stoltz

dtm_resampler	<i>Resamples an input DTM to generate new DTMs</i>
---------------	--

Description

Takes any DTM and randomly resamples from each row, creating a new DTM

Usage

```
dtm_resampler(dtm, alpha = NULL, n = NULL)
```

Arguments

dtm Document-term matrix with terms as columns. Works with DTMs produced by any popular text analysis package, or you can use the `dtm_builder()` function.

alpha Number indicating proportion of document lengths, e.g., `alpha = 1` returns resampled rows that are the same lengths as the original DTM.

n Integer indicating the length of documents to be returned, e.g., `n = 100L` will bring documents shorter than 100 tokens up to 100, while bringing documents longer than 100 tokens down to 100.

Details

Using the row counts as probabilities, each document's tokens are resampled with replacement up to a certain proportion of the row count (set by `alpha`). This function can be used with iteration to "bootstrap" a DTM without returning to the raw text. It does not iterate, however, so operations can be performed on one DTM at a time without storing multiple DTMs in memory.

If `alpha` is less than 1, then a proportion of each documents' lengths is returned. For example, `alpha = 0.50` will return a resampled DTM where each row has half the tokens of the original DTM. If `alpha = 2`, then each row in the resampled DTM twice the number of tokens of the original DTM. If an integer is provided to `n` then all documents will be resampled to that length. For example, `n =`

2000L will resample each document until they are 2000 tokens long – meaning those shorter than 2000 will be increased in length, while those longer than 2000 will be decreased in length. alpha and n should not be specified at the same time.

Value

returns a document-term matrix of class "dgCMatrix"

dtm_stats	<i>Gets DTM summary statistics</i>
-----------	------------------------------------

Description

dtm_stats() provides a summary, corpus-level statistics using any document-term matrix

Usage

```
dtm_stats(
  dtm,
  richness = TRUE,
  distribution = TRUE,
  central = TRUE,
  character = TRUE,
  simplify = FALSE
)
```

Arguments

dtm	Document-term matrix with terms as columns. Works with DTMs produced by any popular text analysis package, or you can use the dtm_builder() function.
richness	Logical (default = TRUE), whether to include statistics about lexical richness, i.e. terms that occur once, twice, and three times (hapax, dis, tris), and the total type-token ratio.
distribution	Logical (default = TRUE), whether to include statistics about the distribution, i.e. min, max st. dev, skewness, kurtosis.
central	Logical (default = TRUE), whether to include statistics about the central tendencies i.e. mean and median for types and tokens.
character	Logical (default = TRUE), whether to include statistics about the character lengths of terms, i.e. min, max, mean
simplify	Logical (default = FALSE), whether to return statistics as a data frame where each statistic is a column. Default returns a list of small data frames.

Value

A list of one to five data frames with summary statistics (if simplify=FALSE), otherwise a single data frame where each statistics is a column.

Author(s)

Dustin Stoltz

dtm_stopper

*Removes terms from a DTM based on rules***Description**

dtm_stopper will "stop" terms from the analysis by removing columns in a DTM based on stop rules. Rules include matching terms in a precompiled or custom list, terms meeting an upper or lower document frequency threshold, or terms meeting an upper or lower term frequency threshold.

Usage

```
dtm_stopper(
  dtm,
  stop_list = NULL,
  stop_termfreq = NULL,
  stop_termrank = NULL,
  stop_termprop = NULL,
  stop_docfreq = NULL,
  stop_docprop = NULL,
  stop_hapax = FALSE,
  stop_null = FALSE,
  ignore_case = TRUE
)
```

Arguments

dtm	Document-term matrix with terms as columns. Works with DTMs produced by any popular text analysis package, or you can use the dtm_builder function.
stop_list	Vector of terms, from a precompiled stoplist or custom list such as c("never", "gonna", "give").
stop_termfreq	Vector of two numbers indicating the lower and upper threshold for exclusion (see details). Use Inf for max or min, respectively.
stop_termrank	Single integer indicating upper term rank threshold for exclusion (see details).
stop_termprop	Vector of two numbers indicating the lower and upper threshold for exclusion (see details). Use Inf for max or min, respectively.
stop_docfreq	Vector of two numbers indicating the lower and upper threshold for exclusion (see details). Use Inf for max or min, respectively.
stop_docprop	Vector of two numbers indicating the lower and upper threshold for exclusion (see details). Use Inf for max or min, respectively.
stop_hapax	Logical (default = FALSE) indicating whether to remove terms occurring one time (or zero times), a.k.a. hapax legomena
stop_null	Logical (default = FALSE) indicating whether to remove terms that occur zero times in the DTM.
ignore_case	Logical (default = TRUE) indicating whether to ignore capitalization.

Details

Stopping terms by removing their respective columns in the DTM is significantly more efficient than searching raw text with string matching and deletion rules. Behind the scenes, the function relies on the `fastmatch` package to quickly match/not-match terms.

The `stop_list` argument takes a list of terms which are matched and removed from the DTM. If `ignore_case = TRUE` (the default) then word case will be ignored.

The `stop_termfreq` argument provides rules based on a term's occurrences in the DTM as a whole – regardless of its within document frequency. If real numbers between 0 and 1 are provided then terms will be removed by corpus proportion. For example `c(0.01, 0.99)`, terms that are either below 1% of the total tokens or above 99% of the total tokens will be removed. If integers are provided then terms will be removed by total count. For example `c(100, 9000)`, occurring less than 100 or more than 9000 times in the corpus will be removed. This also means that if `c(0, 1)` is provided, then the will only *keep* terms occurring once.

The `stop_termrank` argument provides the upper threshold for a terms' rank in the corpus. For example, `5L` will remove the five most frequent terms.

The `stop_docfreq` argument provides rules based on a term's document frequency – i.e. the number of documents within which it occurs, regardless of how many times it occurs. If real numbers between 0 and 1 are provided then terms will be removed by corpus proportion. For example `c(0.01, 0.99)`, terms in more than 99% of all documents or terms that are in less than 1% of all documents. For example `c(100, 9000)`, then words occurring in less than 100 documents or more than 9000 documents will be removed. This means that if `c(0, 1)` is provided, then the function will only *keep* terms occurring in exactly one document, and remove terms in more than one.

The `stop_hapax` argument is a shortcut for removing terms occurring just one time in the corpus – called hapax legomena. Typically, a size-able portion of the corpus tends to be hapax terms, and removing them is a quick solution to reducing the dimensions of a DTM. The DTM must be frequency counts (not relative frequencies).

The `stop_null` argument removes terms that do not occur at all. In other words, there is a column for the term, but the entire column is zero. This can occur for a variety of reasons, such as starting with a predefined vocabulary (e.g., using `dtm_builder`'s `vocab` argument) or through some cleaning processes.

Value

returns a document-term matrix of class "dgCMatrix"

Author(s)

Dustin Stoltz

Examples

```
# create corpus and DTM
my.corpus <- data.frame(
  text = c(
    "I hear babies crying I watch them grow",
    "They'll learn much more than I'll ever know",
```

```
      "And I think to myself",
      "What a wonderful world",
      "Yes I think to myself",
      "What a wonderful world"
    ),
    line_id = paste0("line", seq_len(6))
  )
## some text preprocessing
my.corpus$clean_text <- tolower(gsub("'", "", my.corpus$text))

dtm <- dtm_builder(
  data = my.corpus,
  text = clean_text,
  doc_id = line_id
)

## example 1 with R 4.1 pipe

dtm_st <- dtm |>
  dtm_stopper(stop_list = c("world", "babies"))

## example 2 without pipe
dtm_st <- dtm_stopper(
  dtm,
  stop_list = c("world", "babies")
)

## example 3 precompiled stoplist
dtm_st <- dtm_stopper(
  dtm,
  stop_list = get_stoplist("snowball2014")
)

## example 4, stop top 2
dtm_st <- dtm_stopper(
  dtm,
  stop_termrank = 2L
)

## example 5, stop docfreq
dtm_st <- dtm_stopper(
  dtm,
  stop_docfreq = c(2, 5)
)
```

Description

"Project" each word in a word embedding matrix of D dimension along a vector of D dimensions, extracted from the same embedding space. The vector can be a single word, or a concept vector obtained from `get_centroid()`, `get_direction()`, or `get_regions()`.

Usage

```
find_projection(wv, vec)
```

Arguments

wv Matrix of word embedding vectors (a.k.a embedding model) with rows as words.
vec Vector extracted from the embeddings

Details

All the vectors in the matrix A are projected onto the a vector, v , to find the projection matrix, P , defined as:

$$P = \frac{A \cdot v}{v \cdot v} * v$$

Value

A new word embedding matrix, each row of which is parallel to vector.

find_rejection	<i>Find the 'rejection matrix' from a semantic vector</i>
----------------	---

Description

"Reject" each word in a word embedding matrix of D dimension from a vector of D dimensions, extracted from the same embedding space. The vector can be a single word, or a concept vector obtained from `get_centroid()`, `get_direction()`, or `get_regions()`.

Usage

```
find_rejection(wv, vec)
```

Arguments

wv Matrix of word embedding vectors (a.k.a embedding model) with rows as words.
vec Vector extracted from the embeddings

Value

A new word embedding matrix, each row of which is rejected from vector.

find_transformation *Find a specified matrix transformation*

Description

Given a matrix, B , of word embedding vectors (source) with terms as rows, this function finds a transformed matrix following a specified operation. These include: centering (i.e. translation) and normalization (i.e. scaling). In the first, B is centered by subtracting column means. In the second, B is normalized by the L2 norm. Both have been found to improve word embedding representations. The function also finds a transformed matrix that approximately aligns B , with another matrix, A , of word embedding vectors (reference), using Procrustes transformation (see details).

Usage

```
find_transformation(wv, ref = NULL, method = c("align", "norm", "center"))
```

Arguments

wv	Matrix of word embedding vectors (a.k.a embedding model) with rows as terms (the source matrix to be transformed).
ref	If method = "align", this is the reference matrix toward which the source matrix is to be aligned.
method	Character vector indicating the method to use for the transformation. Current methods include: "align", "norm", and "center" – see details.

Details

Aligning a source matrix of word embedding vectors, B , to a reference matrix, A , has primarily been used as a post-processing step for embeddings trained on longitudinal corpora for diachronic analysis or for cross-lingual embeddings. Aligning preserves internal (cosine) distances, while orient the source embeddings to minimize the sum of squared distances (and is therefore a Least Squares problem). Alignment is accomplished with the following steps:

- translation: centering by column means
- scaling: scale (normalizes) by the L2 Norm
- rotation/reflection: rotates and a reflects to minimize sum of squared differences, using singular value decomposition

Alignment is asymmetrical, and only outputs the transformed source matrix, B . Therefore, it is typically recommended to align B to A , and then A to B . However, simply centering and norming A after may be sufficient.

Value

A new word embedding matrix, transformed using the specified method.

References

- Mikel Artetxe, Gorka Labaka, and Eneko Agirre. (2018). 'A robust self-learning method for fully unsupervised cross-lingual mappings of word embeddings.' *In Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics*. 789-798
- Mikel Artetxe, Gorka Labaka, and Eneko Agirre. 2019. 'An effective approach to unsupervised machine translation.' *In Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*. 194-203
- Hamilton, William L., Jure Leskovec, and Dan Jurafsky. (2018). 'Diachronic Word Embeddings Reveal Statistical Laws of Semantic Change.' <https://arxiv.org/abs/1605.09096v6>.
- Lin, Zefeng, Xiaojun Wan, and Zongming Guo. (2019). 'Learning Diachronic Word Embeddings with Iterative Stable Information Alignment.' *Natural Language Processing and Chinese Computing*. 749-60. doi: [10.1007/9783030322335_58](https://doi.org/10.1007/9783030322335_58).
- Schlechtweg et al. (2019). 'A Wind of Change: Detecting and Evaluating Lexical Semantic Change across Times and Domains.' <https://arxiv.org/abs/1906.02979v1>. Shoemark et a. (2019). 'Room to Glo: A Systematic Comparison of Semantic Change Detection Approaches with Word Embeddings.' *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing*. 66-76. doi: [10.18653/v1/D191007](https://doi.org/10.18653/v1/D191007)
- Borg and Groenen. (1997). *Modern Multidimensional Scaling*. New York: Springer. 340-342

ft_wv_sample	<i>Sample of fastText embeddings</i>
--------------	--------------------------------------

Description

These are a sample of the English fastText embeddings including 770 words matching those used in the jfk_speech. These are intended to be used for example code.

Usage

```
ft_wv_sample
```

Format

A matrix of 770 rows and 300 columns

get_anchors	<i>Gets anchor terms from precompiled anchor lists</i>
-------------	--

Description

Produces a data.frame of juxtaposed word pairs used to extract a semantic direction in word embeddings. Can be used as input to [get_direction\(\)](#).

Usage

```
get_anchors(relation)
```

Arguments

`relation` String indicating a semantic relation, 26 relations are available in the dataset (see details) but should be used as a starting point.

Details

Sets of juxtaposed "anchor" pairs are adapted from published work and associated with a particular semantic relation. These should be used as a starting point, not as "ground truth."

Available relations include:

- activity
- affluence
- age
- attractiveness
- borders
- concreteness
- cultivation
- dominance
- education
- gender
- government
- purity
- safety
- sexuality
- skills
- status
- valence
- whiteness

Value

returns a tibble with two columns

Author(s)

Dustin Stoltz

Examples

```
gen <- get_anchors(relation = "gender")
```

get_centroid	<i>Word embedding semantic centroid extractor</i>
--------------	---

Description

The function outputs an averaged vector from a set of anchor terms' word vectors. This average is roughly equivalent to the intersection of the contexts in which each word is used. This semantic centroid can be used for a variety of ends, and specifically as input to `CMDist()`. `get_centroid()` requires a list of terms, string of terms, `data.frame` or matrix. In the latter two cases, the first column will be used. The vectors are aggregated using the simple average. Terms can be repeated, and are therefore "weighted" by their counts.

Usage

```
get_centroid(anchors, wv, missing = "stop")
```

Arguments

anchors	List of terms to be averaged
wv	Matrix of word embedding vectors (a.k.a embedding model) with rows as words.
missing	what action to take if terms are not in embeddings. If action = "stop" (default), the function is stopped and an error messages states which terms are missing. If action = "remove", missing terms or rows with missing terms are removed. Missing terms will be printed as a message.

Value

returns a one row matrix

Author(s)

Dustin Stoltz

Examples

```
# load example word embeddings
data(ft_wv_sample)

space1 <- c("spacecraft", "rocket", "moon")

cen1 <- get_centroid(anchors = space1, wv = ft_wv_sample)

space2 <- c("spacecraft rocket moon")
cen2 <- get_centroid(anchors = space2, wv = ft_wv_sample)

identical(cen1, cen2)
```

get_direction	<i>Word embedding semantic direction extractor</i>
---------------	--

Description

get_direction() outputs a vector corresponding to one pole of a "semantic direction" built from sets of antonyms or juxtaposed terms. The output can be used as an input to [CMDist\(\)](#) and [CoCA\(\)](#).

Usage

```
get_direction(anchors, wv, method = "paired", missing = "stop", n_dirs = 1L)
```

Arguments

anchors	Two column data frame of juxtaposed 'anchor' terms
wv	Matrix of word embedding vectors (a.k.a embedding model) with rows as terms.
method	Indicates the method used to generate vector offset. Default is 'paired'. See details.
missing	what action to take if terms are not in embeddings. If action = "stop" (default), the function is stopped and an error messages states which terms are missing. If action = "remove", missing terms or rows with missing terms are removed. Missing terms will be printed as a message.
n_dirs	If method = "PCA", an integer indicating how many directions to return. Default = 1L, indicating a single, bipolar, direction.

Details

Semantic directions can be estimated in using a few methods:

- 'paired' (default): each individual term is subtracted from exactly one other paired term. there must be the same number of terms for each side of the direction (although one word may be used more than once).
- 'pooled': terms corresponding to one side of a direction are first averaged, and then these averaged vectors are subtracted. A different number of terms can be used for each side of the direction.
- 'L2': the vector is calculated the same as with 'pooled' but is then divided by the L2 'Euclidean' norm
- 'PCA': vector offsets are calculated for each pair of terms, as with 'paired', and if n_dirs = 1L (the default) then the direction is the first principal component. Users can return more than one direction by increasing the n_dirs parameter.

Value

returns a one row matrix

Author(s)

Dustin Stoltz

References

- Bolukbasi, T., Chang, K. W., Zou, J., Saligrama, V., and Kalai, A. (2016). Quantifying and reducing stereotypes in word embeddings. arXiv preprint <https://arxiv.org/abs/1606.06121v1>.
- Bolukbasi, Tolga, Kai-Wei Chang, James Zou, Venkatesh Saligrama, Adam Kalai (2016). 'Man Is to Computer Programmer as Woman Is to Homemaker? Debiasing Word Embeddings.' Proceedings of the 30th International Conference on Neural Information Processing Systems. 4356-4364. <https://dl.acm.org/doi/10.5555/3157382.3157584>.
- Taylor, Marshall A., and Dustin S. Stoltz. (2020) 'Concept Class Analysis: A Method for Identifying Cultural Schemas in Texts.' *Sociological Science* 7:544-569. doi: [10.15195/v7.a23](https://doi.org/10.15195/v7.a23).
- Taylor, Marshall A., and Dustin S. Stoltz. (2020) 'Integrating semantic directions with concept mover's distance to measure binary concept engagement.' *Journal of Computational Social Science* 1-12. doi: [10.1007/s42001020000758](https://doi.org/10.1007/s42001020000758).
- Kozlowski, Austin C., Matt Taddy, and James A. Evans. (2019). 'The geometry of culture: Analyzing the meanings of class through word embeddings.' *American Sociological Review* 84(5):905-949. doi: [10.1177/0003122419877135](https://doi.org/10.1177/0003122419877135).
- Arseniev-Koehler, Alina, and Jacob G. Foster. (2020). 'Machine learning as a model for cultural learning: Teaching an algorithm what it means to be fat.' arXiv preprint <https://arxiv.org/abs/2003.12133v2>.

Examples

```
# load example word embeddings
data(ft_wv_sample)

# create anchor list
gen <- data.frame(
  add = c("woman"),
  subtract = c("man")
)

dir <- get_direction(anchors = gen, wv = ft_wv_sample)

dir <- get_direction(
  anchors = gen, wv = ft_wv_sample,
  method = "PCA", n = 1L
)
```

Description

Given a set of word embeddings of d dimensions and v vocabulary, `get_regions()` finds k semantic regions in d dimensions. This, in effect, learns latent topics from an embedding space (a.k.a. topic modeling), which are directly comparable to both terms (with cosine similarity) and documents (with Concept Mover's distance using `CMDist()`).

Usage

```
get_regions(
    wv,
    k_regions = 5L,
    max_iter = 20L,
    algorithm = "hamerly",
    seed = 0
)
```

Arguments

<code>wv</code>	Matrix of word embedding vectors (a.k.a embedding model) with rows as words.
<code>k_regions</code>	Integer indicating the k number of regions to return
<code>max_iter</code>	Integer indicating the maximum number of iterations before k-means terminates.
<code>algorithm</code>	Character indicating the algorithm to use for the Lloyd iteration ('naive', 'pelleg-moore', 'elkan', 'hamerly' (default), 'dualtree', or 'dualtree-covertree').
<code>seed</code>	Integer indicating a random seed. Default is 0, which calls 'std::time(NULL)'.

Details

To group words into more encompassing "semantic regions" we use k -means clustering. We choose k -means primarily for its ubiquity and the wide range of available diagnostic tools for k -means cluster.

A word embedding matrix of d dimensions and v vocabulary is "clustered" into k semantic regions which have d dimensions. Each region is represented by a single point defined by the d dimensional vector. The process discretely assigns all word vectors are assigned to a given region so as to minimize some error function, however as the resulting regions are in the same dimensions as the word embeddings, we can measure each terms similarity to each region. This, in effect, is a mixed membership topic model similar to topic modeling by Latent Dirichlet Allocation.

We use the `kmeans` function from the `mlpack` package, which offers several algorithms for each "Lloyd iteration," we use the "naive" as the default. Options include:

- "naive": O(kN) Lloyd's approach
- "pelleg-moore": Pelleg-Moore tree-based algorithm
- "elkan": Elkan's triangle-inequality based algorithm
- "hamerly" (default): Hamerly's modification to Elkan's algorithm
- "dualtree": dual-tree k-means
- "dualtree-covertree": dual-tree k-means sing the cover tree

Value

returns a matrix of class "dgCMatrix" with k rows and d dimensions

Author(s)

Dustin Stoltz

References

Butnaru, Andrei M., and Radu Tudor Ionescu. (2017) 'From image to text classification: A novel approach based on clustering word embeddings.' *Procedia computer science*. 112:1783-1792. doi: [10.1016/j.procs.2017.08.211](https://doi.org/10.1016/j.procs.2017.08.211).

Zhang, Yi, Jie Lu, Feng Liu, Qian Liu, Alan Porter, Hongshu Chen, and Guangquan Zhang. (2018). 'Does Deep Learning Help Topic Extraction? A Kernel K-Means Clustering Method with Word Embedding.' *Journal of Informetrics*. 12(4):1099-1117. doi: [10.1016/j.joi.2018.09.004](https://doi.org/10.1016/j.joi.2018.09.004).

Arseniev-Koehler, Alina and Cochran, Susan D and Mays, Vickie M and Chang, Kai-Wei and Foster, Jacob Gates (2021) 'Integrating topic modeling and word embedding to characterize violent deaths' doi: [10.31235/osf.io/nkyaq](https://doi.org/10.31235/osf.io/nkyaq)

Examples

```
# load example word embeddings
data(ft_wv_sample)

my.regions <- get_regions(
  wv = ft_wv_sample,
  k_regions = 10L,
  max_iter = 10L,
  algorithm = "hamerly",
  seed = 01984
)
```

get_stoplist

Gets stoplist from precompiled lists

Description

Provides access to 8 precompiled stoplists, including the most commonly used stoplist from the Snowball stemming package ("snowball2014"), text2map's tiny stoplist ("tiny2020"), a few historically important stop lists. This aims to be a transparent and well-document collection of stoplists. Only includes English language stoplists at the moment.

Usage

```
get_stoplist(source = "tiny2020", language = "en", tidy = FALSE)
```


Arguments

source	Character indicating source, default = "tiny2020"
language	Character (default = "en") indicating language of stopwords by ISO 639-1 code, currently only English is supported.
tidy	logical (default = FALSE), returns a tibble

Details

There is no such thing as a *stopword*! But, there are **tons** of precompiled lists of words that someone thinks we should remove from our texts. (See for example: <https://github.com/igorbrigadir/stopwords>) One of the first stoplists is from C.J. van Rijsbergen's "Information retrieval: theory and practice" (1979) and includes 250 words. text2map's very own stoplist tiny2020 is a lean 34 words.

Below are stoplists available with [get_stoplist](#):

- "tiny2020": Tiny (2020) list of 33 words (Default)
- "snowball2001": Snowball stemming package's (2001) list of 127 words
- "snowball2014": Updated Snowball (2014) list of 175 words
- "van1979": C. J. van Rijsbergen's (1979) list of 250 words
- "fox1990": Christopher Fox's (1990) list of 421 words
- "smart1993": Original SMART (1993) list of 570 words
- "onix2000": ONIX (2000) list of 196 words
- "nltk2001": Python's NLTK (2009) list of 179 words

The Snowball (2014) stoplist is likely the most commonly, it is the default in the stopwords package, which is used by quanteda, tidytext and tokenizers packages, followed closely by the Smart (1993) stoplist, the default in the tm package. The word counts for SMART (1993) and ONIX (2000) are slightly different than in other places because of duplicate words.

Value

Character vector of words to be stopped, if tidy = TRUE, a tibble is returned

Author(s)

Dustin Stoltz

jfk_speech

Full Text of JFK's Rice Speech

Description

This is a data frame for the text of JFK's Rice Speech "We choose to go to the moon." Each row is a 10 word string of the speech – roughly a sentence. This is intended to be used for example code.

Usage

```
jfk_speech
```

Format

A data frame with 2 columns

Variables

Variables:

- sentence_id. Order and unique ID for the sentence
- sentence. The text of a sentence

plot.CoCA

Plot CoCA

Description

Plot CoCA

Usage

```
## S3 method for class 'CoCA'
plot(
  x,
  module = NULL,
  cutoff = 0.05,
  repulse = 1.86,
  min = 0.15,
  max = 1,
  main = NULL,
  ...
)
```

Arguments

x	CoCA object returned by <code>CoCA()</code>
module	index for which module to plot (default = NULL)
cutoff	minimum absolute value of correlations to plot
repulse	repulse radius in the spring layout
min	edges with absolute weights under this value are not shown (default = 0.15)
max	highest weight to scale the edge widths too (default = 1)
main	title for plot (default = NULL)
...	Arguments to be passed to methods

Value

returns qgraph object

print.CoCA	<i>Prints CoCA class information</i>
------------	--------------------------------------

Description

Prints CoCA class information

Usage

```
## S3 method for class 'CoCA'
print(x, ...)
```

Arguments

x	CoCA object returned by <code>CoCA()</code>
...	Arguments to be passed to methods

Value

prints a message indicating the classes and sizes

stoplists

A dataset of stoplists

Description

A dataset containing eight English stoplist. Is used with the `get_stoplist()` function.

Usage

```
stoplists
```

Format

A data frame with 1775 rows and 2 variables.

Details

The stoplists include:

- "tiny2020": Tiny (2020) list of 33 words (Default)
- "snowball2001": Snowball (2001) list of 127 words
- "snowball2014": Updated Snowball (2014) list of 175 words
- "van1979": van Rijsbergen's (1979) list of 250 words
- "fox1990": Christopher Fox's (1990) list of 421 words
- "smart1993": Original SMART (1993) list of 570 words
- "onix2000": ONIX (2000) list of 196 words
- "nltk2001": Python's NLTK (2009) list of 179 words

Tiny 2020, is a very small stop list of the most frequent English conjunctions, articles, prepositions, and demonstratives (N=17). Also includes the 8 forms of the copular verb "to be" and the 8 most frequent personal (singular and plural) pronouns (minus gendered and possessive pronouns).

No contractions are included.

Variables

Variables:

- words. words to be stopped
- source. source of the list

tiny_gender_tagger	<i>A very tiny "gender" tagger</i>
--------------------	------------------------------------

Description

Provides a small dictionary which matches common English pronouns and nouns to conventional gender categories ("masculine" or "feminine"). There are 20 words in each category.

Usage

```
tiny_gender_tagger()
```

Value

returns a tibble with two columns

Author(s)

Dustin Stoltz

vocab_builder	<i>A fast unigram vocabulary builder</i>
---------------	--

Description

A streamlined function to take raw texts from a column of a data.frame and produce a list of all the unique tokens. Tokenizes by the fixed, single whitespace, and then extracts the unique tokens. This can be used as input to dtm_builder() to standardize the vocabulary (i.e. the columns) across multiple DTMs. Prior to building the vocabulary, texts should have whitespace trimmed, if desired, punctuation removed and terms lowercased.

Usage

```
vocab_builder(data, text)
```

Arguments

data	Data.frame with one column of texts
text	Name of the column with documents' text

Value

returns a list of unique terms in a corpus

Author(s)

Dustin Stoltz

Index

* datasets

- anchor_lists, 2
- ft_wv_sample, 18
- jfk_speech, 26
- stoplists, 28

anchor_lists, 2

CMDist, 3, 7

CMDist(), 6, 20, 21, 23

CoCA, 3, 5, 6

CoCA(), 21, 27

dtm_builder, 8, 14

dtm_builder(), 6

dtm_melter, 10

dtm_resampler, 11

dtm_stats, 12

dtm_stopper, 13

find_projection, 15

find_rejection, 16

find_transformation, 17

ft_wv_sample, 18

get_anchors, 3, 18

get_anchors(), 2

get_centroid, 3, 5, 20

get_centroid(), 4, 5, 16

get_direction, 3, 5, 7, 21

get_direction(), 2, 4–6, 16, 18

get_regions, 22

get_regions(), 4, 5, 16, 23

get_stoplist, 24, 25

get_stoplist(), 28

jfk_speech, 26

plot.CoCA, 26

print.CoCA, 27

stoplists, 28

tiny_gender_tagger, 29

vocab_builder, 29