

Package ‘textshape’

June 7, 2018

Title Tools for Reshaping Text

Version 1.6.0

Maintainer Tyler Rinker <tyler.rinker@gmail.com>

Description Tools that can be used to reshape and restructure text data.

Depends R (>= 3.4.0)

Imports data.table, slam, stats, stringi, utils

Suggests testthat

License GPL-2

LazyData TRUE

RoxygenNote 6.0.1

URL <http://github.com/trinker/textshape>

BugReports <http://github.com/trinker/textshape/issues>

Collate 'bind_list.R' 'bind_table.R' 'bind_vector.R' 'change_index.R'
'cluster_matrix.R' 'column_to_rownames.R' 'combine.R'
'duration.R' 'flatten.R' 'from_to.R' 'mtabulate.R'
'split_index.R' 'split_match.R'
'split_match_regex_to_transcript.R' 'split_portion.R'
'split_run.R' 'split_sentence.R' 'split_sentence_token.R'
'split_speaker.R' 'split_token.R' 'split_transcript.R'
'split_word.R' 'textshape-package.R' 'tidy_colo_dtm.R'
'utils.R' 'tidy_dtm.R' 'tidy_list.R' 'tidy_matrix.R'
'tidy_table.R' 'tidy_vector.R' 'unique_pairs.R' 'unnest_text.R'

NeedsCompilation no

Author Tyler Rinker [aut, cre],
Joran Elias [ctb],
Matthew Flickinger [ctb],
Paul Foster [ctb]

Repository CRAN

Date/Publication 2018-06-07 16:15:43 UTC

R topics documented:

bind_list	2
bind_table	4
bind_vector	4
change_index	5
cluster_matrix	6
column_to_rownames	7
combine	8
DATA	9
duration	10
flatten	11
from_to	13
golden_rules	14
hamlet	15
mtabulate	16
simple_dtm	17
split_index	18
split_match	19
split_match_regex_to_transcript	20
split_portion	21
split_run	22
split_sentence	23
split_sentence_token	25
split_speaker	26
split_token	27
split_transcript	28
split_word	29
textshape	30
tidy_colo_tdm	30
tidy_dtm	31
tidy_list	33
tidy_matrix	34
tidy_table	35
tidy_vector	36
unique_pairs	36
unnest_text	37
Index	39

 bind_list

Row Bind a List of Named Dataframes or Vectors

Description

Deprecated, use [tidy_list](#) instead.

Usage

```
bind_list(x, id.name = "id", content.name = "content", ...)
```

Arguments

x	A named <code>list</code> of <code>data.frames</code> or <code>vector</code> .
id.name	The name to use for the column created from the <code>list</code> .
content.name	The name to use for the column created from the <code>list</code> of <code>vectors</code> (only used if x is <code>vector</code>).
...	ignored.

Value

Returns a `data.table` with the `names` from the `list` as an id column.

Examples

```
## Not run:
bind_list(list(p=1:500, r=letters))
bind_list(list(p=mtcars, r=mtcars, z=mtcars, d=mtcars))

## 2015 Vice-Presidential Debates Example
if (!require("pacman")) install.packages("pacman")
pacman::p_load(rvest, magrittr, xml2)

debates <- c(
  wisconsin = "110908",
  boulder = "110906",
  california = "110756",
  ohio = "110489"
)

lapply(debates, function(x){
  xml2::read_html(paste0("http://www.presidency.ucsb.edu/ws/index.php?pid=", x)) %>%
  rvest::html_nodes("p") %>%
  rvest::html_text() %>%
  textshape::split_index(grep("^[A-Z]+:", .)) %>%
  textshape::combine() %>%
  textshape::split_transcript() %>%
  textshape::split_sentence()
}) %>%
  textshape::bind_list("location")

## End(Not run)
```

bind_table	<i>Column Bind a Table's Values with Its Names</i>
------------	--

Description

Deprecated, use [tidy_table](#) instead.

Usage

```
bind_table(x, id.name = "id", content.name = "content", ...)
```

Arguments

x	A table .
id.name	The name to use for the column created from the table names .
content.name	The name to use for the column created from the table values .
...	ignored.

Value

Returns a [data.table](#) with the [names](#) from the [table](#) as an id column.

Examples

```
## Not run:
x <- table(sample(LETTERS[1:6], 1000, TRUE))
bind_table(x)

## End(Not run)
```

bind_vector	<i>Column Bind an Atomic Vector's Values with Its Names</i>
-------------	---

Description

Deprecated, use [tidy_vector](#) instead.

Usage

```
bind_vector(x, id.name = "id", content.name = "content", ...)
```

Arguments

x	A named atomic vector .
id.name	The name to use for the column created from the vector names .
content.name	The name to use for the column created from the vector values .
...	ignored.

Value

Returns a `data.table` with the `names` from the `vector` as an id column.

Examples

```
## Not run:
x <- setNames(sample(LETTERS[1:6], 1000, TRUE), sample(state.name[1:5], 1000, TRUE))
bind_vector(x)

## End(Not run)
```

`change_index`*Indexing of Changes in Runs*

Description

Find the indices of changes in runs in a vector. This function pairs well with `split_index` and is the default for the indices in all `split_index` functions that act on atomic vectors.

Usage

```
change_index(x, ...)
```

Arguments

<code>x</code>	A vector.
<code>...</code>	ignored.

Value

Returns a vector of integer indices of where a vector initially changes.

See Also

[split_index](#)

Examples

```
set.seed(10)
(x <- sample(0:1, 20, TRUE))
change_index(x)
split_index(x, change_index(x))

(p_chng <- change_index(CO2[["Plant"]]))
split_index(CO2[["Plant"]], p_chng)
```

cluster_matrix	<i>Reorder a Matrix Based on Hierarchical Clustering</i>
----------------	--

Description

Reorder matrix rows, columns, or both via hierarchical clustering.

Usage

```
cluster_matrix(x, dim = "both", method = "ward.D2", ...)
```

Arguments

x	A matrix.
dim	The dimension to reorder (cluster); must be set to "row", "col", or "both".
method	The agglomeration method to be used (see hclust).
...	ignored.

Value

Returns a reordered matrix.

See Also

[hclust](#)

Examples

```
cluster_matrix(mtcars)
cluster_matrix(mtcars, dim = 'row')
cluster_matrix(mtcars, dim = 'col')

## Not run:
if (!require("pacman")) install.packages("pacman")
pacman::p_load(tidyverse, viridis, gridExtra)

## plot heatmap w/o clustering
wo <- mtcars %>%
  cor() %>%
  tidy_matrix('car', 'var') %>%
  ggplot(aes(var, car, fill = value)) +
  geom_tile() +
  scale_fill_viridis(name = expression(r[xy])) +
  theme(
    axis.text.y = element_text(size = 8) ,
    axis.text.x = element_text(
      size = 8,
      hjust = 1,
```

```

        vjust = 1,
        angle = 45
      ),
      legend.position = 'bottom',
      legend.key.height = grid::unit(.1, 'cm'),
      legend.key.width = grid::unit(.5, 'cm')
    ) +
    labs(subtitle = "With Out Clustering")

## plot heatmap w clustering
w <- mtcars %>%
  cor() %>%
  cluster_matrix() %>%
  tidy_matrix('car', 'var') %>%
  mutate(
    var = factor(var, levels = unique(var)),
    car = factor(car, levels = unique(car))
  ) %>%
  group_by(var) %>%
  ggplot(aes(var, car, fill = value)) +
  geom_tile() +
  scale_fill_viridis(name = expression(r[xy])) +
  theme(
    axis.text.y = element_text(size = 8) ,
    axis.text.x = element_text(
      size = 8,
      hjust = 1,
      vjust = 1,
      angle = 45
    ),
    legend.position = 'bottom',
    legend.key.height = grid::unit(.1, 'cm'),
    legend.key.width = grid::unit(.5, 'cm')
  ) +
  labs(subtitle = "With Clustering")

gridExtra::grid.arrange(wo, w, ncol = 2)

## End(Not run)

```

column_to_rownames *Add a Column as Rownames*

Description

Takes an existing column and uses it as rownames instead. This is useful when turning a [data.frame](#) into a [matrix](#). Inspired by the [tibble](#) package's `column_to_row` which is now deprecated if done on a [tibble](#) object. By coercing to a [data.frame](#) this problem is avoided.

Usage

```
column_to_rownames(x, loc = 1)
```

Arguments

`x` An object that can be coerced to a `data.frame`.

`loc` The column location as either an integer or string index location. Must be unique row names.

Value

Returns a `data.frame` with the specified column moved to rownames.

Examples

```
state_dat <- data.frame(state.name, state.area, state.center, state.division)
column_to_rownames(state_dat)
column_to_rownames(state_dat, 'state.name')
```

combine

Combine Elements

Description

Combine (`paste`) elements (`vectors`, `lists`, or `data.frames`) together with `collapse = TRUE`.

Usage

```
combine(x, ...)

## Default S3 method:
combine(x, fix.punctuation = TRUE, ...)

## S3 method for class 'data.frame'
combine(x, text.var = TRUE, ...)
```

Arguments

`x` A `data.frame` or character vector with runs.

`fix.punctuation` logical If TRUE spaces before/after punctuation that should not be are a removed (regex used: "`(\s+(?=[, .?!; :%-]))|((?<=[-])\s+)`").

`text.var` The name of the text variable.

`...` Ignored.

Value

Returns a vector (if given a list/vector) or an expanded `data.table` with elements pasted together.

Examples

```
(x <- split_token(DATA[["state"]][1], FALSE))
combine(x)

(x2 <- split_token(DATA[["state"]], FALSE))
combine(x2)

(x3 <- split_sentence(DATA))

## without dropping the non-group variable column
combine(x3)

## Dropping the non-group variable column
combine(x3[, 1:5, with=FALSE])
```

DATA

Fictitious Classroom Dialogue

Description

A fictitious dataset useful for small demonstrations.

Usage

```
data(DATA)
```

Format

A data frame with 11 rows and 5 variables

Details

- person. Speaker
- sex. Gender
- adult. Dummy coded adult (0-no; 1-yes)
- state. Statement (dialogue)
- code. Dialogue coding scheme

duration *Duration of Turns of Talk*

Description

duration - Calculate duration (start and end times) for duration of turns of talk measured in words.

startss - Calculate start times from a numeric vector.

ends - Calculate end times from a numeric vector.

Usage

```
duration(x, ...)

## Default S3 method:
duration(x, grouping.var = NULL, ...)

## S3 method for class 'data.frame'
duration(x, text.var = TRUE, ...)

## S3 method for class 'numeric'
duration(x, ...)

starts(x, ...)

ends(x, ...)
```

Arguments

x	A data.frame or character vector with a text variable or a numeric vector.
grouping.var	The grouping variables. Default NULL generates one word list for all text. Also takes a single grouping variable or a list of 1 or more grouping variables.
text.var	The name of the text variable. If TRUE duration tries to detect the text column.
...	Ignored.

Value

Returns a vector or data frame of starts and/or ends.

Examples

```
(x <- c(
  "Mr. Brown comes! He says hello. i give him coffee.",
  "I'll go at 5 p. m. eastern time. Or somewhere in between!",
  "go there"
))
duration(x)
```

```
group <- c("A", "B", "A")
duration(x, group)

groups <- list(group1 = c("A", "B", "A"), group2 = c("red", "red", "green"))
duration(x, groups)

data(DATA)
duration(DATA)

## Larger data set
duration(hamlet)

## Integer values
x <- sample(1:10, 10)
duration(x)
starts(x)
ends(x)
```

flatten

Flatten a Nested List of Vectors Into a Single Tier List of Vectors

Description

Flatten a named, nested list of atomic vectors to a single level using the concatenated list/atomic vector names as the names of the single tiered list.

Usage

```
flatten(x, sep = "_", ...)
```

Arguments

x	A nested, named list of vectors.
sep	A separator to use for the concatenation of the names from the nested list.
...	ignored.

Value

Returns a flattened list.

Note

The order of the list is sorted alphabetically. Pull requests for the option to return the original order would be appreciated.

Author(s)

StackOverflow user @Michael and Paul Foster and Tyler Rinker <tyler.rinker@gmail.com>.

References

<https://stackoverflow.com/a/41882883/1000343>

<https://stackoverflow.com/a/48357114/1000343>

Examples

```
x <- list(
  urban = list(
    cars = c('volvo', 'ford'),
    food.dining = list(
      local.business = c('carls'),
      chain.business = c('dennys', 'panera')
    )
  ),
  rural = list(
    land.use = list(
      farming =list(
        dairy = c('cows'),
        vegie.plan = c('carrots')
      )
    ),
    social.rec = list(
      community.center = c('town.square')
    ),
    people.type = c('good', 'bad', 'in.between')
  ),
  other.locales = c('suburban'),
  missing = list(
    unknown = c(),
    known = c()
  ),
  end = c('wow')
)

x

flatten(x)
flatten(x, ' -> ')

## Not run:
## dictionary from quanteda
require(quanteda); library(textreadr); library(dplyr)
mydict <- https://provalisresearch.com/Download/LaverGarry.zip" %>%
  textreadr::download(") %>%
  unzip(exdir = tempdir()) %>%
  `[`(1) %>%
  quanteda::dictionary(file = .)

mydict
flatten(as.list(mydict))

## End(Not run)
```

 from_to

Prepare Discourse Data for Network Plotting

Description

from_to - Add the next speaker as the from variable in a to/from network data structure. Assumes that the flow of discourse is coming from person A to person B, or at the very least the talk is taken up by person B. Works by taking the vector of speakers and shifting everything down one and then adding a closing element.

from_to_summarize - A wrapper for from_to.data.frame that adds a word.count column and then combines duplicate rows.

Usage

```

from_to(x, ...)

## Default S3 method:
from_to(x, final = "End", ...)

## S3 method for class 'character'
from_to(x, final = "End", ...)

## S3 method for class 'numeric'
from_to(x, final = "End", ...)

## S3 method for class 'data.frame'
from_to(x, from.var, final = "End", ...)

from_to_summarize(x, from.var, id.vars = NULL, text.var = TRUE, ...)
```

Arguments

x	A data form vector or data.frame.
final	The name of the closing element or node.
from.var	A character string naming the column to be considered the origin of the talk.
id.vars	The variables that correspond to the speaker or are attributes of the speaker (from variable).
text.var	The name of the text variable. If TRUE duration tries to detect the text column.
...	Ignored.

Value

Returns a vector (if given a vector) or an augmented [data.table](#).

Examples

```

from_to(DATA, 'person')
from_to_summarize(DATA, 'person')
from_to_summarize(DATA, 'person', c('sex', 'adult'))
## Not run:
if (!require("pacman")) install.packages("pacman"); library(pacman)
p_load(dplyr, geomnet, qdap, stringi, scales)
p_load_current_gh('trinker/textsahpe')

dat <- from_to_summarize(DATA, 'person', c('sex', 'adult')) %>%
  mutate(words = rescale(word.count, c(.5, 1.5)))

dat %>%
  ggplot(aes(from_id = from, to_id = to)) +
    geom_net(
      aes(linewidth = words),
      layout.alg = "fruchtermanreingold",
      directed = TRUE,
      labelon = TRUE,
      size = 1,
      labelcolour = 'black',
      ecolour = "grey70",
      arrowsize = 1,
      curvature = .1
    ) +
    theme_net() +
    xlim(c(-0.05, 1.05))

## End(Not run)

```

golden_rules

Sentence Boundary Disambiguation Edge Cases

Description

A slightly filtered dataset containing Dias's sentence boundary disambiguation edge cases. This is a nested data set with the outcome column as a nested list of desired splits. The non-ASCII cases and spaced ellipsis examples have been removed.

Usage

```
data(golden_rules)
```

Format

A data frame with 45 rows and 3 variables

Details

- Rule. The name of the rule to test
- Text. The testing text
- Outcome. The desired outcome of the sentence disambiguation

References

Dias, Kevin S. 2015. Golden Rules (English). Retrieved: https://s3.amazonaws.com/tm-town-nlp-resources/golden_rules.txt

hamlet

Hamlet (Complete & Split by Sentence)

Description

A dataset containing the complete dialogue of Hamlet with turns of talk split into sentences.

Usage

```
data(hamlet)
```

Format

A data frame with 2007 rows and 7 variables

Details

- act. The act (akin to repeated measures)
- tot. The turn of talk
- scene. The scene (nested within an act)
- location. Location of the scene
- person. Character in the play
- died. Logical coded death variable if yes the character dies in the play
- dialogue. The spoken dialogue

References

<http://www.gutenberg.org>

`mtabulate`*Tabulate Frequency Counts for Multiple Vectors*

Description

`mtabulate` - Similar to `tabulate` that works on multiple vectors.

`as_list` - Convert a count matrix to a named list of elements. The semantic inverse of `mtabulate`.

Usage

```
mtabulate(vects)
```

```
as_list(mat, nm = rownames(mat))
```

Arguments

`vects` A `vector`, `list`, or `data.frame` of named/unnamed vectors.

`mat` A matrix of counts.

`nm` A character vector of names to assign to the list.

Value

`mtabulate` - Returns a `data.frame` with columns equal to number of unique elements and the number of rows equal to the the original length of the `vector`, `list`, or `data.frame` (length equals number of columns in `data.frame`). If list of vectors is named these will be the rownames of the dataframe.

`as_list` - Returns a list of elements.

Author(s)

Joran Elias and Tyler Rinker <tyler.rinker@gmail.com>.

References

<http://stackoverflow.com/a/9961324/1000343>

See Also

`tabulate`

Examples

```
mtabulate(list(w=letters[1:10], x=letters[1:5], z=letters))
mtabulate(list(mtcars$cyl[1:10]))

## Dummy coding
mtabulate(mtcars$cyl[1:10])
mtabulate(CO2[, "Plant"])

dat <- data.frame(matrix(sample(c("A", "B"), 30, TRUE), ncol=3))
mtabulate(dat)
as_list(mtabulate(dat))
t(mtabulate(dat))
as_list(t(mtabulate(dat)))
```

simple_dtm

Simple DocumentTermMatrix

Description

A dataset containing a simple [DocumentTermMatrix](#).

Usage

```
data(simple_dtm)
```

Format

A list with 6 elements

Details

- i** The document locations
- j** The term locations
- v** The count of terms for that particular element position
- nrow** The number of rows
- ncol** The number of columns
- dimnames** document and terms

split_index

*Split Data Forms at Specified Indices***Description**

Split data forms at specified integer indices.

Usage

```
split_index(x, indices = if (is.atomic(x)) { NULL } else {
  change_index(x) }, names = NULL, ...)
```

```
## S3 method for class 'list'
split_index(x, indices, names = NULL, ...)
```

```
## S3 method for class 'data.frame'
split_index(x, indices, names = NULL, ...)
```

```
## S3 method for class 'matrix'
split_index(x, indices, names = NULL, ...)
```

```
## S3 method for class 'numeric'
split_index(x, indices = change_index(x), names = NULL,
  ...)
```

```
## S3 method for class 'factor'
split_index(x, indices = change_index(x), names = NULL,
  ...)
```

```
## S3 method for class 'character'
split_index(x, indices = change_index(x), names = NULL,
  ...)
```

```
## Default S3 method:
split_index(x, indices = change_index(x), names = NULL,
  ...)
```

Arguments

x	A data form (list, vector, data.frame, matrix).
indices	A vector of integer indices to split at. If indices contains the index 1, it will be silently dropped. The default value when x evaluates to TRUE for <code>is.atomic</code> is to use <code>change_index(x)</code> .
names	Optional vector of names to give to the list elements.
...	Ignored.

Value

Returns of list of data forms broken at the indices.

Note

Two dimensional object will retain dimension (i.e., drop = FALSE is used).

See Also

[change_index](#)

Examples

```
## character
split_index(LETTERS, c(4, 10, 16))
split_index(LETTERS, c(4, 10, 16), c("dog", "cat", "chicken", "rabbit"))

## numeric
split_index(1:100, c(33, 66))

## factor
(p_chng <- change_index(CO2[["Plant"]]))
split_index(CO2[["Plant"]], p_chng)
#`change_index` was unnecessary as it is the default of atomic vectors
split_index(CO2[["Plant"]])

## list
split_index(as.list(LETTERS), c(4, 10, 16))

## data.frame
(vs_change <- change_index(mtcars[["vs"]]))
split_index(mtcars, vs_change)

## matrix
(mat <- matrix(1:50, nrow=10))
split_index(mat, c(3, 6, 10))
```

split_match

Split a Vector By Split Points

Description

split_match - Splits a vector into a list of vectors based on split points.

split_match_regex - split_match with regex = TRUE.

Usage

```
split_match(x, split = "", include = FALSE, regex = FALSE, ...)
```

```
split_match_regex(x, split = "", include = FALSE, ...)
```

Arguments

x	A vector with split points.
split	A vector of places (elements) to split on or a regular expression if regex argument is TRUE.
include	An integer of 1 (split character(s) are not included in the output), 2 (split character(s) are included at the beginning of the output), or 3 (split character(s) are included at the end of the output).
regex	logical. If TRUE regular expressions will be enabled for split argument.
...	other arguments passed to <code>grep</code> and <code>grepl</code> .

Value

Returns a list of vectors.

Author(s)

Matthew Flickinger and Tyler Rinker <tyler.rinker@gmail.com>.

References

<http://stackoverflow.com/a/24319217/1000343>

Examples

```
set.seed(15)
x <- sample(c("", LETTERS[1:10]), 25, TRUE, prob=c(.2, rep(.08, 10)))

split_match(x)
split_match(x, "C")
split_match(x, c("", "C"))

split_match(x, include = 0)
split_match(x, include = 1)
split_match(x, include = 2)

set.seed(15)
x <- sample(1:11, 25, TRUE, prob=c(.2, rep(.08, 10)))
split_match(x, 1)
```

split_match_regex_to_transcript

Split Text by Regex Into a Transcript

Description

A wrapper for `split_match_regex` and `textreadr`'s `as_transcript` to detect person variable, split the text into turns of talk, and convert to a data.frame with person and dialogue variables. There is a bit of cleansing that is closer to `as_transcript` than `split_transcript`.

Usage

```
split_match_regex_to_transcript(x, person.regex = "[A-Z]{3,}",
  col.names = c("Person", "Dialogue"), dash = "", ellipsis = "...",
  quote2bracket = FALSE, rm.empty.rows = TRUE, skip = 0, ...)
```

Arguments

x	A vector with split points.
person.regex	A vector of places (elements) to split on or a regular expression if regex argument is TRUE.
col.names	A character vector specifying the column names of the transcript columns.
dash	A character string to replace the en and em dashes special characters (default is to remove).
ellipsis	A character string to replace the ellipsis special characters.
quote2bracket	logical. If TRUE replaces curly quotes with curly braces (default is FALSE). If FALSE curly quotes are removed.
rm.empty.rows	logical. If TRUE read_transcript attempts to remove empty rows.
skip	Integer; the number of lines of the data file to skip before beginning to read data.
...	ignored.

Value

Returns a data.frame of dialogue and people.

Examples

```
## Not run:
system.file(
  "docs/Simpsons_Roasting_on_an_Open_Fire_Script.pdf",
  package = "textshape"
) %>%
  textreadr::read_document() %>%
  split_match_regex_to_transcript("[A-Z]{3,}", skip = 2)

## End(Not run)
```

split_portion

Break Text Into Ordered Word Chunks

Description

Some visualizations and algorithms require text to be broken into chunks of ordered words. `split_portion` breaks text, optionally by grouping variables, into equal chunks. The chunk size can be specified by giving number of words to be in each chunk or the number of chunks.

Usage

```
split_portion(text.var, grouping.var = NULL, n.words, n.chunks,
  as.string = TRUE, rm.unequal = FALSE, as.table = TRUE, ...)
```

Arguments

text.var	The text variable
grouping.var	The grouping variables. Default NULL generates one word list for all text. Also takes a single grouping variable or a list of 1 or more grouping variables.
n.words	An integer specifying the number of words in each chunk (must specify n.chunks or n.words).
n.chunks	An integer specifying the number of chunks (must specify n.chunks or n.words).
as.string	logical. If TRUE the chunks are returned as a single string. If FALSE the chunks are returned as a vector of single words.
rm.unequal	logical. If TRUE final chunks that are unequal in length to the other chunks are removed.
as.table	logical. If TRUE the list output is coerced to data.table or tibble .
...	Ignored.

Value

Returns a list or [data.table](#) of text chunks.

Examples

```
with(DATA, split_portion(state, n.chunks = 10))
with(DATA, split_portion(state, n.words = 10))
with(DATA, split_portion(state, n.chunks = 10, as.string=FALSE))
with(DATA, split_portion(state, n.chunks = 10, rm.unequal=TRUE))
with(DATA, split_portion(state, person, n.chunks = 10))
with(DATA, split_portion(state, list(sex, adult), n.words = 10))
with(DATA, split_portion(state, person, n.words = 10, rm.unequal=TRUE))

## Bigger data
with(hamlet, split_portion(dialogue, person, n.chunks = 10))
with(hamlet, split_portion(dialogue, list(act, scene, person), n.chunks = 10))
with(hamlet, split_portion(dialogue, person, n.words = 300))
with(hamlet, split_portion(dialogue, list(act, scene, person), n.words = 300))
```

split_run

Split Runs

Description

Split runs of consecutive characters.

Usage

```
split_run(x, ...)

## Default S3 method:
split_run(x, ...)

## S3 method for class 'data.frame'
split_run(x, text.var = TRUE, ...)
```

Arguments

x	A data.frame or character vector with runs.
text.var	The name of the text variable with runs. If TRUE <code>split_word</code> tries to detect the text column with runs.
...	Ignored.

Value

Returns a list of vectors of runs or an expanded [data.table](#) with runs split apart.

Examples

```
x1 <- c(
  "12233344445555566666",
  NA,
  "abbccdddeeeeffffff",
  "sddfg",
  "11112222333"
)

x <- c(rep(x1, 2), ">>???,,,,.....:;;;[[")

split_run(x)

DATA[["run.col"]] <- x
split_run(DATA, "run.col")
```

split_sentence

Split Sentences

Description

Split sentences.

Usage

```
split_sentence(x, ...)

## Default S3 method:
split_sentence(x, ...)

## S3 method for class 'data.frame'
split_sentence(x, text.var = TRUE, ...)
```

Arguments

<code>x</code>	A <code>data.frame</code> or character vector with sentences.
<code>text.var</code>	The name of the text variable. If TRUE <code>split_sentence</code> tries to detect the column with sentences.
<code>...</code>	Ignored.

Value

Returns a list of vectors of sentences or an expanded `data.frame` with sentences split apart.

Examples

```
(x <- c(paste0(
  "Mr. Brown comes! He says hello. i give him coffee. i will ",
  "go at 5 p. m. eastern time. Or somewhere in between!go there"
),
paste0(
  "Marvin K. Mooney Will You Please Go Now!", "The time has come.",
  "The time has come. The time is now. Just go. Go. GO!",
  "I don't care how."
)))
split_sentence(x)

data(DATA)
split_sentence(DATA)

## Not run:
## Kevin S. Dias' sentence boundary disambiguation test set
data(golden_rules)
library(magrittr)

golden_rules %>%
  split_sentence(Text)

## End(Not run)
```

`split_sentence_token` *Split Sentences & Tokens*

Description

Split sentences and tokens.

Usage

```
split_sentence_token(x, ...)  
  
## Default S3 method:  
split_sentence_token(x, lower = TRUE, ...)  
  
## S3 method for class 'data.frame'  
split_sentence_token(x, text.var = TRUE, lower = TRUE,  
  ...)
```

Arguments

<code>x</code>	A <code>data.frame</code> or character vector with sentences.
<code>lower</code>	logical. If TRUE the words are converted to lower case.
<code>text.var</code>	The name of the text variable. If TRUE <code>split_sentence_token</code> tries to detect the column with sentences.
<code>...</code>	Ignored.

Value

Returns a list of vectors of sentences or an expanded `data.frame` with sentences split apart.

Examples

```
(x <- c(paste0(  
  "Mr. Brown comes! He says hello. i give him coffee. i will ",  
  "go at 5 p. m. eastern time. Or somewhere in between!go there"  
),  
paste0(  
  "Marvin K. Mooney Will You Please Go Now!", "The time has come.",  
  "The time has come. The time is now. Just go. Go. GO!",  
  "I don't care how."  
)))  
split_sentence_token(x)  
  
data(DATA)  
split_sentence_token(DATA)  
  
## Not run:  
## Kevin S. Dias' sentence boundary disambiguation test set
```

```

data(golden_rules)
library(magrittr)

golden_rules %$%
  split_sentence_token(Text)

## End(Not run)

```

split_speaker

Break and Stretch if Multiple Persons per Cell

Description

Look for cells with multiple people and create separate rows for each person.

Usage

```
split_speaker(dataframe, speaker.var = 1, sep = c("and", "&", ","), ...)
```

Arguments

dataframe	A dataframe that contains the person variable.
speaker.var	The person variable to be stretched.
sep	The separator(s) to search for and break on. Default is: c("and", "&", ",")
...	Ignored.

Value

Returns an expanded dataframe with person variable stretched and accompanying rows repeated.

Examples

```

## Not run:
DATA$person <- as.character(DATA$person)
DATA$person[c(1, 4, 6)] <- c("greg, sally, & sam",
  "greg, sally", "sam and sally")

split_speaker(DATA)

DATA$person[c(1, 4, 6)] <- c("greg_sally_sam",
  "greg.sally", "sam; sally")

split_speaker(DATA, sep = c(".", "_", ";"))

DATA <- textshape::DATA #reset DATA

## End(Not run)

```

`split_token`*Split Tokens*

Description

Split tokens.

Usage

```
split_token(x, ...)  
  
## Default S3 method:  
split_token(x, lower = TRUE, ...)  
  
## S3 method for class 'data.frame'  
split_token(x, text.var = TRUE, lower = TRUE, ...)
```

Arguments

<code>x</code>	A data.frame or character vector with tokens.
<code>lower</code>	logical. If TRUE the words are converted to lower case.
<code>text.var</code>	The name of the text variable. If TRUE <code>split_token</code> tries to detect the text column with tokens.
<code>...</code>	Ignored.

Value

Returns a list of vectors of tokens or an expanded [data.table](#) with tokens split apart.

Examples

```
(x <- c(  
  "Mr. Brown comes! He says hello. i give him coffee.",  
  "I'll go at 5 p. m. eastern time. Or somewhere in between!",  
  "go there"  
)  
)  
split_token(x)  
split_token(x, lower=FALSE)  
  
data(DATA)  
split_token(DATA)  
split_token(DATA, lower=FALSE)  
  
## Larger data set  
split_token(hamlet)
```

split_transcript *Split a Transcript Style Vector on Delimiter & Coerce to Dataframe*

Description

Split a transcript style vector (e.g., `c("greg: Who me", "sarah: yes you!")`) into a name and dialogue vector that is coerced to a `data.table`. Leading/trailing white space in the columns is stripped out.

Usage

```
split_transcript(x, delim = ":", colnames = c("person", "dialogue"),
  max.delim = 15, ...)
```

Arguments

<code>x</code>	A transcript style vector (e.g., <code>c("greg: Who me", "sarah: yes you!")</code>).
<code>delim</code>	The delimiter to split on.
<code>colnames</code>	The column names to use for the <code>data.table</code> output.
<code>max.delim</code>	An integer stating how many characters may come before a delimiter is found. This is useful for the case when a colon is the delimiter but time stamps are also found in the text.
<code>...</code>	Ignored.

Value

Returns a 2 column `data.table`.

Examples

```
split_transcript(c("greg: Who me", "sarah: yes you!"))

## Not run:
## 2015 Vice-Presidential Debates Example
if (!require("pacman")) install.packages("pacman")
pacman::p_load(rvest, magrittr, xml2)

debates <- c(
  wisconsin = "110908",
  boulder = "110906",
  california = "110756",
  ohio = "110489"
)

lapply(debates, function(x){
  xml2::read_html(paste0("http://www.presidency.ucsb.edu/ws/index.php?pid=", x)) %>%
    rvest::html_nodes("p") %>%
    rvest::html_text() %>%
```

```

    textshape::split_index(grep("^[A-Z]+:", .)) %>%
    textshape::combine() %>%
    textshape::split_transcript() %>%
    textshape::split_sentence()
  })

  ## End(Not run)

```

split_word

Split Words

Description

Split words.

Usage

```

split_word(x, ...)

## Default S3 method:
split_word(x, lower = TRUE, ...)

## S3 method for class 'data.frame'
split_word(x, text.var = TRUE, lower = TRUE, ...)

```

Arguments

x	A data.frame or character vector with words.
lower	logical. If TRUE the words are converted to lower case.
text.var	The name of the text variable. If TRUE <code>split_word</code> tries to detect the text column with words.
...	Ignored.

Value

Returns a list of vectors of words or an expanded [data.table](#) with words split apart.

Examples

```

(x <- c(
  "Mr. Brown comes! He says hello. i give him coffee.",
  "I'll go at 5 p. m. eastern time. Or somewhere in between!",
  "go there"
))
split_word(x)
split_word(x, lower=FALSE)

data(DATA)

```

```
split_word(DATA)
split_word(DATA, lower=FALSE)

## Larger data set
split_word(hamlet)
```

textshape	<i>Tools for Reshaping Text</i>
-----------	---------------------------------

Description

Tools that can be used to reshape and restructure text data.

tidy_colo_tdm	<i>Convert a DocumentTermMatrix/TermDocumentMatrix into Collocating Words in Tidy Form</i>
---------------	--

Description

Converts non-zero elements of a [DocumentTermMatrix/TermDocumentMatrix](#) into a tidy data set made of collocating words.

Usage

```
tidy_colo_tdm(x, ...)
tidy_colo_dtm(x, ...)
```

Arguments

x	A DocumentTermMatrix/TermDocumentMatrix .
...	Ignored.

Value

Returns a tidied data.frame.

See Also

[unique_pairs](#)

Examples

```

data(simple_dtm)

tidied <- tidy_colo_dtm(simple_dtm)
tidied
unique_pairs(tidied)

## Not run:
if (!require("pacman")) install.packages("pacman")
pacman::p_load_current_gh('trinker/gofastr', 'trinker/lexicon')
pacman::p_load(tidyverse, magrittr, ggstance)

my_dtm <- with(
  presidential_debates_2012,
  q_dtm(dialogue, paste(time, tot, sep = "_"))
)

tidy_colo_dtm(my_dtm) %>%
  tbl_df() %>%
  filter(!term_1 %in% c('i', lexicon::sw_onix) &
         !term_2 %in% lexicon::sw_onix
  ) %>%
  filter(term_1 != term_2) %>%
  unique_pairs() %>%
  filter(n > 15) %>%
  complete(term_1, term_2, fill = list(n = 0)) %>%
  ggplot(aes(x = term_1, y = term_2, fill = n)) +
  geom_tile() +
  scale_fill_gradient(low= 'white', high = 'red') +
  theme(axis.text.x = element_text(angle = 45, hjust = 1))

## End(Not run)

```

tidy_dtm	<i>Convert a DocumentTermMatrix/TermDocumentMatrix into Tidy Form</i>
----------	---

Description

Converts non-zero elements of a [DocumentTermMatrix](#)/[TermDocumentMatrix](#) into a tidy data set.

Usage

```
tidy_dtm(x, ...)
```

```
tidy_tdm(x, ...)
```

Arguments

x A `DocumentTermMatrix`/`TermDocumentMatrix`.
 ... ignored.

Value

Returns a tidied data.frame.

Examples

```
data(simple_dtm)

tidy_dtm(simple_dtm)

## Not run:
if (!require("pacman")) install.packages("pacman")
pacman::p_load_current_gh('trinker/gofastr')
pacman::p_load(tidyverse, magrittr, ggstance)

my_dtm <- with(
  presidential_debates_2012,
  q_dtm(dialogue, paste(time, tot, sep = "_"))
)

tidy_dtm(my_dtm) %>%
  tidyr::extract(
    col = doc,
    into = c("time", "turn", "sentence"),
    regex = "(\\d)_?(\\d+)\\.?(\\d+)"
  ) %>%
  mutate(
    time = as.numeric(time),
    turn = as.numeric(turn),
    sentence = as.numeric(sentence)
  ) %>%
  tbl_df() %T>%
  print() %>%
  group_by(time, term) %>%
  summarize(n = sum(n)) %>%
  group_by(time) %>%
  arrange(desc(n)) %>%
  slice(1:10) %>%
  ungroup() %>%
  mutate(
    term = factor(paste(term, time, sep = "__"),
      levels = rev(paste(term, time, sep = "__")))
  ) %>%
  ggplot(aes(x = n, y = term)) +
  geom_barh(stat='identity') +
  facet_wrap(~time, ncol=2, scales = 'free_y') +
  scale_y_discrete(labels = function(x) gsub("__+$$", "", x))
```



```
## End(Not run)
```

tidy_list

Tidy a List of Named Dataframes or Named Vectors or Vectors

Description

`rbind` a named `list` of `data.frames` or `vectors` to output a single `data.frame` with the `names` from the `list` as an id column.

Usage

```
tidy_list(x, id.name = "id", content.name = "content",
  content.attribute.name = "attribute", ...)
```

Arguments

<code>x</code>	A named <code>list</code> of <code>data.frames</code> or <code>vector</code> .
<code>id.name</code>	The name to use for the column created from the <code>list</code> .
<code>content.name</code>	The name to use for the column created from the <code>list</code> of <code>vectors</code> (only used if <code>x</code> is <code>vector</code>).
<code>content.attribute.name</code>	The name to use for the column created from the <code>list</code> of names given to the <code>vectors</code> (only used if <code>x</code> is named <code>vector</code>).
<code>...</code>	Ignored.

Value

Returns a `data.table` with the `names` from the `list` as an id column.

Examples

```
tidy_list(list(p=1:500, r=letters))
tidy_list(list(p=mtcars, r=mtcars, z=mtcars, d=mtcars))

x <- list(
  a = setNames(c(1:4), LETTERS[1:4]),
  b = setNames(c(7:9), LETTERS[7:9]),
  c = setNames(c(10:15), LETTERS[10:15]),
  d = c(x=4, y=6, 4),
  e = setNames(1:10, sample(state.abb, 10, TRUE)),
  f = setNames(1:10, sample(month.abb, 10, TRUE))
)

tidy_list(x)

## Not run:
## 2015 Vice-Presidential Debates Example
```

```

if (!require("pacman")) install.packages("pacman")
pacman::p_load(rvest, magrittr, xml2)

debates <- c(
  wisconsin = "110908",
  boulder = "110906",
  california = "110756",
  ohio = "110489"
)

lapply(debates, function(x){
  paste0("http://www.presidency.ucsb.edu/ws/index.php?pid=", x) %>%
    xml2::read_html() %>%
    rvest::html_nodes("p") %>%
    rvest::html_text() %>%
    textshape::split_index(grep("^[A-Z]+:", .)) %>%
    textshape::combine() %>%
    textshape::split_transcript() %>%
    textshape::split_sentence()
}) %>%
  textshape::tidy_list("location")

## End(Not run)

```

tidy_matrix

Convert a Matrix into Tidy Form

Description

`tidy_matrix` - Converts matrices into a tidy data set. Essentially, a stacking of the matrix columns and repeating row/column names as necessary.

`tidy_adjacency_matrix` - A wrapper for `tidy_matrix` with the `row.name`, `col.name`, & `value.name` all set to "from", "to", & "n", assuming preparation for network analysis.

Usage

```
tidy_matrix(x, row.name = "row", col.name = "col", value.name = "value",
  ...)
```

```
tidy_adjacency_matrix(x, ...)
```

Arguments

<code>x</code>	A matrix.
<code>row.name</code>	A string to use for the row names that are now a column.
<code>col.name</code>	A string to use for the column names that are now a column.
<code>value.name</code>	A string to use for the values that are now a column.
<code>...</code>	ignored.

Value

Returns a tidied data.frame.

Examples

```
mat <- matrix(1:16, nrow = 4,
  dimnames = list(LETTERS[1:4], LETTERS[23:26])
)

mat
tidy_matrix(mat)

data(simple_dtm)
tidy_matrix(as.matrix(simple_dtm), 'doc', 'term', 'n')

X <- as.matrix(simple_dtm[1:10, 1:10])
tidy_adjacency_matrix(crossprod(X))
tidy_adjacency_matrix(crossprod(t(X)))
```

tidy_table

Tidy a Table: Bind Its Values with Its Names

Description

`cbind` a [table](#)'s values with its [names](#) to form id (from the names) and content columns.

Usage

```
tidy_table(x, id.name = "id", content.name = "content", ...)
```

Arguments

<code>x</code>	A table .
<code>id.name</code>	The name to use for the column created from the table names .
<code>content.name</code>	The name to use for the column created from the table values.
<code>...</code>	ignored.

Value

Returns a [data.table](#) with the [names](#) from the [table](#) as an id column.

Examples

```
x <- table(sample(LETTERS[1:6], 1000, TRUE))
tidy_table(x)
```

tidy_vector	<i>Tidy a Named Atomic Vector: Bind Its Values with Its Names</i>
-------------	---

Description

`cbind` a named atomic `vector`'s values with its `names` to form `id` (from the names) and `content` columns.

Usage

```
tidy_vector(x, id.name = "id", content.name = "content", ...)
```

Arguments

<code>x</code>	A named atomic <code>vector</code> .
<code>id.name</code>	The name to use for the column created from the <code>vector names</code> .
<code>content.name</code>	The name to use for the column created from the <code>vector</code> values.
<code>...</code>	ignored.

Value

Returns a `data.table` with the `names` from the `vector` as an `id` column.

Examples

```
x <- setNames(sample(LETTERS[1:6], 1000, TRUE), sample(state.name[1:5], 1000, TRUE))
tidy_vector(x)
```

unique_pairs	<i>Extract Only Unique Pairs of Collocating Words in tidy_colo_dtm</i>
--------------	--

Description

`tidy_colo_dtm` utilizes the entire matrix to generate the tidied data.frame. This means that the upper and lower triangles are used redundantly. This function eliminates this redundancy by dropping one set of the pairs from a tidied data.frame.

Usage

```
unique_pairs(x, col1 = "term_1", col2 = "term_2", ...)
```

```
## Default S3 method:
```

```
unique_pairs(x, col1 = "term_1", col2 = "term_2", ...)
```

```
## S3 method for class 'data.table'
```

```
unique_pairs(x, col1 = "term_1", col2 = "term_2", ...)
```

Arguments

x	A <code>data.frame</code> with two columns that contain redundant pairs.
col1	A string naming column 1.
col2	A string naming column 2.
...	ignored.

Value

Returns a filtered `data.frame`.

See Also

[tidy_colo_dtm](#)

Examples

```
dat <- data.frame(
  term_1 = LETTERS[1:10],
  term_2 = LETTERS[10:1],
  stringsAsFactors = FALSE
)

unique_pairs(dat)
```

unnest_text

Un-nest Nested Text Columns

Description

Un-nest nested text columns in a `data.frame`. Attempts to locate the nested text column without specifying.

Usage

```
unnest_text(dataframe, column, integer.rownames = TRUE, ...)
```

Arguments

dataframe	A dataframe object.
column	Column name to search for markers/terms.
integer.rownames	logical. If TRUE then the rownames are numbered 1 through number of rows, otherwise the original row number is retained followed by a period and the element number from the list.
...	ignored.

Value

Returns an un-nested data.frame.

Examples

```
dat <- DATA

## Add a nested/list text column
dat$split <- lapply(dat$state, function(x) {
  unlist(strsplit(x, '(?<=[?!.]\\s+', perl = TRUE))
})

unnest_text(dat)
unnest_text(dat, integer.rownames = FALSE)

## Add a second nested integer column
dat$d <- lapply(dat$split, nchar)
## Not run:
unnest_text(dat) # causes error, must supply column explicitly

## End(Not run)
unnest_text(dat, 'split')

## As a data.table
library(data.table)
dt_dat <- data.table::as.data.table(data.table::copy(dat))
unnest_text(dt_dat, 'split')
## Not run:
unnest_text(dt_dat, 'd')

## End(Not run)

## Not run:
## As a tibble
library(tibble)
t_dat <- tibble::as_tibble(dat)
unnest_text(t_dat, 'split')

## End(Not run)
```

Index

- *Topic **chunks**
 - split_portion, 21
- *Topic **datasets**
 - DATA, 9
 - golden_rules, 14
 - hamlet, 15
 - simple_dtm, 17
- *Topic **frequency**
 - mtabulate, 16
- *Topic **group**
 - split_portion, 21
- *Topic **tabulate**
 - mtabulate, 16
- *Topic **text**
 - split_portion, 21
- as_list (mtabulate), 16
- bind_list, 2
- bind_table, 4
- bind_vector, 4
- cbind, 35, 36
- change_index, 5, 18, 19
- cluster_matrix, 6
- column_to_rownames, 7
- combine, 8
- DATA, 9
- data.frame, 3, 7, 8, 10, 16, 23–25, 27, 29, 33, 37
- data.table, 3–5, 9, 13, 22, 23, 27–29, 33, 35, 36
- DocumentTermMatrix, 17, 30–32
- duration, 10
- ends (duration), 10
- flatten, 11
- from_to, 13
- from_to_summarize (from_to), 13
- golden_rules, 14
- grep, 20
- grepl, 20
- hamlet, 15
- hclust, 6
- is.atomic, 18
- list, 3, 8, 16, 33
- matrix, 7
- mtabulate, 16
- names, 3–5, 33, 35, 36
- package-textshape (textshape), 30
- paste, 8
- rbind, 33
- read_transcript, 21
- simple_dtm, 17
- split_index, 5, 18
- split_match, 19
- split_match_regex, 20
- split_match_regex (split_match), 19
- split_match_regex_to_transcript, 20
- split_portion, 21
- split_run, 22
- split_sentence, 23
- split_sentence_token, 25
- split_speaker, 26
- split_token, 27
- split_transcript, 20, 28
- split_word, 29
- starts (duration), 10
- table, 4, 35
- tabulate, 16
- TermDocumentMatrix, 30–32

textshape, 30
textshape-package (textshape), 30
tidy_adjacency_matrix (tidy_matrix), 34
tidy_colo_dtm, 36, 37
tidy_colo_dtm (tidy_colo_tdm), 30
tidy_colo_tdm, 30
tidy_dtm, 31
tidy_list, 2, 33
tidy_matrix, 34
tidy_table, 4, 35
tidy_tdm (tidy_dtm), 31
tidy_vector, 4, 36

unique_pairs, 30, 36
unnest_text, 37

vector, 3–5, 8, 16, 33, 36