

Package ‘tracee’

March 23, 2023

Type Package

Title Easily Save Output and Trace it Back to Code

Version 0.0.3

Maintainer Philip Delff <philip@delff.dk>

Description Write output (plots and tables) ensuring traceability back to code. Includes a graphics saver with simple automation of stamping with source, destination and creation time. A list of plots can be saved at once. A user-friendly selection of output dimensions for presentations, on-screen inspections, and more available.

License MIT + file LICENSE

RoxygenNote 7.2.3

Depends R (>= 4.0.0)

Imports NMdata (>= 0.0.14), data.table, ggplot2, grid, gridExtra, flextable

Suggests knitr

Encoding UTF-8

NeedsCompilation no

Author Philip Delff [aut, cre]

Repository CRAN

Date/Publication 2023-03-23 05:30:02 UTC

R topics documented:

canvasSize	2
ftstamp	3
ftwrite	3
ggstamp	4
ggwater	5
ggwrite	6
stampFlexTab	7

Index	8
--------------	----------

canvasSize	<i>Get predefined canvas sizes</i>
------------	------------------------------------

Description

Get predefined canvas sizes

Usage

```
canvasSize(canvas, scale = 1, simplify = TRUE)
```

Arguments

canvas	<p>Can either be a character with one of the values</p> <ul style="list-style-type: none"> • "standard" A powerpoint standard size, and two can be shown side by side - 7.2 by 5.4 in (WxH). • "wide" For a single wide plot on a powerpoint slide - 9.6 by 5.4 in • "A4" A full A4 page - 5.4 by 7.2 in • "square" As reads - 5.4 by 5.4 in • "wide-screen" For full screen display - 18.6 by 9 in <p>or it can be a list with elements width and height with single values (unit is inches). Example: canvas=list(height=5,width=9).</p>
scale	A scale to apply to both directions of the canvas size. This can be useful in combination with the pre-defined canvas sizes.
simplify	If only one canvas returned and simplify=TRUE, the result will not be wrapped in a list. For programming, you most likely want simplify=FALSE to be sure to always get the same format back.

Value

A list with numerical elements width and height as used by ggwrite.

See Also

Other Plotting: [ggstamp\(\)](#), [ggwater\(\)](#), [ggwrite\(\)](#)

ftstamp	<i>Stamp and write flextab objects to one or multiple formats</i>
---------	---

Description

Stamp and write flextab objects to one or multiple formats

Usage

```
ftstamp(ft, file, script, bg = "#ffffff", time)
```

Arguments

ft	a flextable object
file	The file that the flextable will be written to (no file is written by this function)
script	path to script - will be pasted as caption.
bg	Default background colour is #ffffff.
time	The default is to insert a time stamp taken from result of Sys.time(). Using the time argument you can overrule this by setting a fixed string instead. Use "" to omit.

ftwrite	<i>Stamp and write flextab objects to one or multiple formats</i>
---------	---

Description

Stamp and write flextab objects to one or multiple formats

Usage

```
ftwrite(ft, file, script, formats, save, quiet = FALSE, ...)
```

```
writeFlexTab(ft, file, script, formats, save, quiet = FALSE, ...)
```

Arguments

ft	A flextab object.
file	to save to. See formats to generate multiple files.
script	path to script - will be pasted as caption. If provided, a stamp will be included on the plot when writing file(s).
formats	One or more of png, docx, pptx, html. As a character vector.
save	Save the table to the given file or just show? Defaults to TRUE. Hint, if you use an "exportFlag", use save=exportFlag.
quiet	Default is false but use TRUE to suppress messages about what was saved.
...	Arguments passed to stampFlexTab.

Functions

- `writeFlextab()`: Deprecated function name. Use `ftwrite`.

 ggstamp

Always stamp your plots with script name

Description

This function is used to stamp ggplot type plots with datetime and script name. User must provide the script name.

Usage

```
ggstamp(plot, script = "", file, time = Sys.time())
```

Arguments

<code>plot</code>	The plot to be stamped.
<code>script</code>	the script name. Date and time will be added automatically.
<code>file</code>	An optional output filename to be included in the stamp.
<code>time</code>	The timestamp to be included.

Details

The stamp is adding using the caption label. If a caption is already in the plot, the stamp will be added in a new line.

The caption is derived as `caption=paste(c(plot$label$caption,stamp,paste(date.txt,file)),collapse="\n")`
 ggplot 2.2.1 (which is years old) or newer is required.

Value

the plot with a stamp
 A plot object with the stamp added as caption

See Also

Other Plotting: [canvasSize\(\)](#), [ggwater\(\)](#), [ggwrite\(\)](#)

Examples

```
library(ggplot2)
data(ChickWeight)
p1 <- ggplot(ChickWeight, aes(Time, weight, group=Chick, colour=factor(Diet)))+geom_line()
script <- "note"
ggstamp(p1, script)
## Or use ggwrite which will call ggstamp when the `script` argument is provided.
ggwrite(p1, script=script, canvas="wide")
```

`ggwater`*Add watermarks to ggplots*

Description

Add watermarks to ggplots

Usage

```
ggwater(text = "Not validated", scale = 1, rot = 30, col = "grey", alpha = 0.5)
```

Arguments

<code>text</code>	What should be written on the plot
<code>scale</code>	the size
<code>rot</code>	rotation of the mark. Don't remember the unit.
<code>col</code>	the colour (a value, not an expression) of the watermark. Default is grey.
<code>alpha</code>	alpha value for the watermark. Default is 0.5.

Details

This used to be based on <https://www.r-bloggers.com/adding-watermarks-to-plots/> That solution stopped working, and this new solution is simpler and based on ggplot2 alone.

Value

a layer with a watermark that can be added to a plot

See Also

Other Plotting: [canvasSize\(\)](#), [ggstamp\(\)](#), [ggwrite\(\)](#)

Examples

```
library(ggplot2)
ff <- qplot(1:10, 11:20) + ggwater()
```

ggwrite	<i>Export plots created with ggplot (and more) or tables to files (png or pdf) - or show them on screen.</i>
---------	--

Description

Export plots created with ggplot (and more) or tables to files (png or pdf) - or show them on screen.

Usage

```
ggwrite(
  plot,
  file,
  script,
  time,
  canvas = "standard",
  formats,
  onefile = FALSE,
  res = 200,
  paper = "special",
  save = TRUE,
  show = !save,
  useNames = FALSE,
  quiet = FALSE
)
```

Arguments

plot	A plot object or a list of plots. Normally generated with ggplot or qplot. But it can also be from grid.arrange or arrangeGrob with class gtable. That is experimental though. Not sure exactly what classes are supported.
file	A file to export to. Must end in .png or .pdf. If plot is a list, see onefile. If missing, plot is shown on screen.
script	This should normally be the path to your script. Requires ggplot >=2.2.1.
time	Passed to ggwrite.
canvas	Either a list of height and width or a shortname of predefined canvas size. See ?canvasSize.
formats	File formats to write to as a character vector. Must be a subset of c("png", "pdf"). Default is to only write to the format matching the file name extension of file.
onefile	Only applicable if plot is a list. If plot is a list and onefile=TRUE, all plots will be put in a pdf (file must end in pdf) with one plot per page. If plot is a list and onefile=FALSE, numbered files will be created - one per list element.
res	Resolution. Passed to png.
paper	Only used with pdf device. See ?pdf.

save	Save the plot to the given file or just show? Defaults to TRUE. Hint, if you use an "exportFlag", use save=exportFlag.
show	Print the plot to the screen? Defaults to the opposite of save. Hint, combining save and show in knitr can give you both a high quality plot in your pdf and a png optimized for powerpoint.
useNames	If length(plot)>1 use names(plot) in the file names? Default is to use 1:length(plot). Only used if save is TRUE, and length(plot)>1.
quiet	Default is false but use TRUE to suppress messages about what was saved.

Value

Nothing. Files written and/or plots shown, depending on argument values.

See Also

Other Plotting: [canvasSize\(\)](#), [ggstamp\(\)](#), [ggwater\(\)](#)

Examples

```
library(ggplot2)
writeOutput <- FALSE
data(ChickWeight)
p1 <- ggplot(ChickWeight, aes(Time, weight, group=Chick, colour=factor(Diet)))+geom_line()
ggwrite(p1) ## view plot on screen
script <- "note"
ggwrite(p1, script=script, canvas="wide", file="myplot1.png", save=writeOutput)
```

stampFlextab

Stamp and write flextab objects to one or multiple formats

Description

Stamp and write flextab objects to one or multiple formats

Usage

```
stampFlextab(ft, file, script, bg = "#ffffff", time)
```

Arguments

ft	a flextable object
file	The file that the flextable will be written to (no file is written by this function)
script	path to script - will be pasted as caption.
bg	Default background colour is #ffffff.
time	The default is to insert a time stamp taken from result of Sys.time(). Using the time argument you can overrule this by setting a fixed string instead. Use "" to omit.

Index

* Plotting

canvasSize, 2

ggstamp, 4

ggwater, 5

ggwrite, 6

canvasSize, 2, 4, 5, 7

ftstamp, 3

ftwrite, 3

ggstamp, 2, 4, 5, 7

ggwater, 2, 4, 5, 7

ggwrite, 2, 4, 5, 6

stampFlextab, 7

writeFlextab (ftwrite), 3