

Package ‘tsbox’

April 3, 2019

Type Package

Title Class-Agnostic Time Series

Version 0.1.0

Date 2019-04-03

Description Time series toolkit with identical behavior for all time series classes: 'ts','xts', 'data.frame', 'data.table', 'tibble', 'zoo', 'timeSeries', 'tsibble'. Also converts reliably between these classes.

Imports data.table (>= 1.10.0), anytime

Suggests testthat, dplyr, tibble, forecast, seasonal, dygraphs, xts, ggplot2, scales, knitr, rmarkdown, tsibble, tibbletime, zoo, timeSeries, nycflights13

License GPL-3

Encoding UTF-8

URL <https://www.tsbox.help>

BugReports <https://github.com/christoph sax/tsbox/issues>

RoxygenNote 6.1.1

VignetteBuilder knitr

NeedsCompilation no

Author Christoph Sax [aut, cre]

Maintainer Christoph Sax <christoph.sax@gmail.com>

Repository CRAN

Date/Publication 2019-04-03 09:40:03 UTC

R topics documented:

tsbox-package	2
copy_class	3
relevant_class	3
tsbox-deprecated	4

ts_	4
ts_arithmetic	5
ts_bind	6
ts_boxable	7
ts_c	8
ts_default	9
ts_dts	9
ts_examples	10
ts_frequency	11
ts_ggplot	12
ts_index	13
ts_lag	14
ts_long	15
ts_na_omit	16
ts_pc	17
ts_pick	17
ts_plot	18
ts_regular	20
ts_save	20
ts_scale	21
ts_span	21
ts_summary	23
ts_trend	24
ts_ts	24
Index	27

 tsbox-package

tsbox: Class-Agnostic Time Series

Description

The R ecosystem knows a vast number of time series classes: `ts`, `xts`, `zoo`, `tsibble`, `tibbletime` or `timeSeries`. The plethora of standards causes confusion. As different packages rely on different classes, it is hard to use them in the same analysis. `tsbox` provides a set of tools that make it easy to switch between these classes. It also allows the user to treat time series as plain data frames, facilitating the use with tools that assume rectangular data.

Details

The package is built around a set of functions that convert time series of different classes to each other. They are frequency-agnostic, and allow the user to combine multiple non-standard and irregular frequencies. Because coercion works reliably, it is easy to write functions that work identically for all classes. So whether we want to smooth, scale, differentiate, chain-link, forecast, regularize or seasonally adjust a time series, we can use the same `tsbox`-command for any time series class.

The best way to start is to check out the package [website](#).

Author(s)

Christoph Sax <christoph.sax@gmail.com>

 copy_class

Re-Class ts-Boxable Object

Description

Copies class attributes from an existing ts-boxable series. Mainly used internally.

Usage

```
copy_class(x, template, preserve.mode = TRUE, preserve.names = FALSE,
           preserve.time = FALSE)
```

Arguments

x	ts-boxable time series, an object of class ts, xts, zoo, data.frame, data.table, tbl, tbl_ts, tbl_time, or timeSeries.
template	ts-boxable time series, an object of class ts, xts, data.frame, data.table, or tibble. Template.
preserve.mode	should the mode the time column be preserved (data frame only)
preserve.names	should the name of the time column be preserved (data frame only)
preserve.time	should the values time column be preserved (data frame only)

Details

Inspired by xts::reclass, which does something similar.

 relevant_class

Extract Relevant Class

Description

Mainly used internally.

Usage

```
relevant_class(x)
```

Arguments

x	ts-boxable time series, an object of class ts, xts, zoo, data.frame, data.table, tbl, tbl_ts, tbl_time, or timeSeries.
---	--

Examples

```
relevant_class(AirPassengers)
relevant_class(ts_df(AirPassengers))
```

tsbox-deprecated	<i>Start and end of time series</i>
------------------	-------------------------------------

Description

Start and end of time series

Usage

```
ts_start(x)
```

```
ts_end(x)
```

Arguments

x	ts-boxable time series, an object of class <code>ts</code> , <code>xts</code> , <code>zoo</code> , <code>data.frame</code> , <code>data.table</code> , <code>tbl</code> , <code>tbl_ts</code> , <code>tbl_time</code> , or <code>timeSeries</code> .
---	--

ts_	<i>Constructing ts-Functions</i>
-----	----------------------------------

Description

ts_ turns an existing function into a function that can deal with ts-boxable time series objects.

Usage

```
load_suggested(pkg)
```

```
ts_(fun, class = "ts", vectorize = FALSE, reclass = TRUE)
```

```
ts_apply(x, fun, ...)
```

Arguments

pkg	external package, to be suggested (automatically added by ts_) predict(). (See examples)
fun	function, to be made available to all time series classes
class	class that the function uses as its first argument
vectorize	should the function be vectorized? (not yet implemented)

reclass	logical, should the new function return the same same ts-boxable output as imputed?
x	ts-boxable time series, an object of class ts, xts, zoo, data.frame, data.table, tbl, tbl_ts, tbl_time, or timeSeries.
...	arguments passed to subfunction

Details

The `ts_` function is a constructor function for `tsbox` time series functions. It can be used to wrap any function that works with time series. The default is set to R base "ts" class. `ts_` deals with the conversion stuff, 'vectorizes' the function so that it can be used with multiple time series.

Value

A function that accepts ts-boxable time series as an input.

See Also

[ts_examples](#), for a few useful examples of functions generated by `ts_`.

[Vignette](#) on how to make arbitrary functions ts-boxable.

Examples

```
ts_(rowSums)(ts_c(mdeaths, fdeaths))
ts_plot(mean = ts_(rowMeans)(ts_c(mdeaths, fdeaths)), mdeaths, fdeaths)
ts_(function(x) predict(prcomp(x)))(ts_c(mdeaths, fdeaths))
ts_(function(x) predict(prcomp(x, scale = TRUE)))(ts_c(mdeaths, fdeaths))
ts_(dygraphs::dygraph, class = "xts")

# attach series to serach path
ts_attach <- ts_(attach, class = "tslist", reclass = FALSE)
ts_attach(EuStockMarkets)
ts_plot(DAX, SMI)
detach()
```

ts_arithmetic

Arithmetic Operators for ts-boxable objects

Description

Arithmetic Operators for ts-boxable objects

Usage

```
e1 %ts+% e2
```

```
e1 %ts-% e2
```

```
e1 %ts*% e2
```

```
e1 %ts/% e2
```

Arguments

e1 ts-boxable time series, an object of class `ts`, `xts`, `data.frame`, `data.table`, or `tibble`.

e2 ts-boxable time series, an object of class `ts`, `xts`, `data.frame`, `data.table`, or `tibble`.

Value

a ts-boxable time series, with the same class as the left input.

Examples

```
head(fdeaths - mdeaths)
head(fdeaths %ts-% mdeaths)
head(ts_df(fdeaths) %ts-% mdeaths)
```

ts_bind

Bind Time Series

Description

Combine time series to a new, single time series. `ts_bind` combines time series as they are, `ts_chain` chains them together, using percentage change rates.

Usage

```
ts_bind(...)
```

```
ts_chain(...)
```

Arguments

... ts-boxable time series, objects of class `ts`, `xts`, `data.frame`, `data.table`, or `tibble`. Or a numeric vector (see examples).

Value

A ts-boxable object of the same class as the input. If series of different classes are combined, the class of the first series is used (if possible).

See Also

[ts_c](#) to collect multiple time series

Examples

```
ts_bind(ts_span(mdeaths, end = "1975-12-01"), fdeaths)
ts_bind(mdeaths, c(2, 2))
ts_bind(mdeaths, 3, ts_bind(fdeaths, c(99, 2)))
ts_bind(ts_dt(mdeaths), AirPassengers)

# numeric vectors
ts_bind(12, AirPassengers, c(2, 3))

ts_chain(ts_span(mdeaths, end = "1975-12-01"), fdeaths)

ts_plot(ts_pc(ts_c(
  comb = ts_chain(ts_span(mdeaths, end = "1975-12-01"), fdeaths),
  fdeaths
)))
```

ts_boxable

Test if an Object is ts-Boxable

Description

Mainly used internally.

Usage

```
ts_boxable(x)
```

Arguments

x ts-boxable time series, an object of class ts, xts, zoo, data.frame, data.table, tbl, tbl_ts, tbl_time, or timeSeries.

Value

logical, either TRUE or FALSE

Examples

```
ts_boxable(AirPassengers)
ts_boxable(lm)
```

`ts_c`*Collect Time Series*

Description

Collect time series as multiple time series.

Usage

```
ts_c(...)
```

Arguments

... ts-boxable time series, objects of class `ts`, `xts`, `data.frame`, `data.table`, or `tibble`.

Details

In data frame objects, multiple time series are stored in a long data frame. In `ts` and `xts` objects, time series are combined horizontally.

Value

a ts-boxable object of the same class as the input. If series of different classes are combined, the class of the first series is used (if possible).

See Also

[ts_bind](#), to bind multiple time series to a single series.

Examples

```
head(ts_c(ts_df(EuStockMarkets), AirPassengers))

# labeling
x <- ts_c(
  `International Airline Passengers` = ts_xts(AirPassengers),
  `Deaths from Lung Diseases` = ldeaths
)
head(x)
```

ts_default	<i>Default Column Names</i>
------------	-----------------------------

Description

In data frame objects (`data.frame`, `tibble`, `data.table`), `tsbox` automatically detects the time and the value column. This function changes the column names to the defaults (`time`, `value`), so that auto-detection can be avoided in future operations.

Usage

```
ts_default(x)
```

Arguments

`x` ts-boxable time series, an object of class `ts`, `xts`, `zoo`, `data.frame`, `data.table`, `tbl`, `tbl_ts`, `tbl_time`, or `timeSeries`.

Value

a ts-boxable time series, with the same class as the input.

Examples

```
df <- ts_df(ts_c(mdeaths, fdeaths))
# non-default colnames
colnames(df) <- c("id", "date", "count")
# switch back to default colnames
head(ts_default(df))
```

ts_dts	<i>Internal Time Series Class</i>
--------	-----------------------------------

Description

Internal Time Series Class

Usage

```
ts_dts(x)
```

Arguments

`x` ts-boxable time series, an object of class `ts`, `xts`, `zoo`, `data.frame`, `data.table`, `tbl`, `tbl_ts`, `tbl_time`, or `timeSeries`.

Description

Example Functions, Generated by `ts_`. `ts_prcomp` calculates the principal components of multiple time series, `ts_dygraphs` generates an interactive graphical visualization, `ts_forecast` return an univariate forecast, `ts_seas` the seasonally adjusted series.

Usage

```
ts_prcomp(x, ...)
```

```
ts_dygraphs(x, ...)
```

```
ts_forecast(x, ...)
```

```
ts_seas(x, ...)
```

Arguments

<code>x</code>	ts-boxable time series, an object of class <code>ts</code> , <code>xts</code> , <code>zoo</code> , <code>data.frame</code> , <code>data.table</code> , <code>tbl</code> , <code>tbl_ts</code> , <code>tbl_time</code> , or <code>timeSeries</code> .
<code>...</code>	further arguments, passed to the underlying function. For help, consider these functions, e.g., stats::prcomp .

Details

With the exception of `ts_prcomp`, these functions depend on external packages.

Value

Usually, a ts-boxable time series, with the same class as the input. `ts_dygraphs` draws a plot.

See Also

[Vignette](#) on how to make arbitrary functions ts-boxable.

Examples

```
ts_plot(
  ts_scale(ts_c(
    Male = mdeaths,
    Female = fdeaths,
    `First principal compenent` = -ts_prcomp(ts_c(mdeaths, fdeaths))[, 1]
  )),
  title = "Deaths from lung diseases",
```

```

    subtitle = "Normalized values"
  )

  ts_plot(ts_c(
    male = mdeaths, female = fdeaths,
    ts_forecast(ts_c(`male (fct)` = mdeaths, `female (fct)` = fdeaths))),
    title = "Deaths from lung diseases",
    subtitle = "Exponential smoothing forecast"
  )

  ts_plot(
    `Raw series` = AirPassengers,
    `Adjusted series` = ts_seas(AirPassengers),
    title = "Airline passengers",
    subtitle = "X-13 seasonal adjustment"
  )

  ts_dygraphs(ts_c(mdeaths, EuStockMarkets))

```

ts_frequency

Change Frequency

Description

Changes the frequency of a time series. By default, incomplete periods of regular series are omitted.

Usage

```
ts_frequency(x, to = "year", aggregate = "mean", na.rm = FALSE)
```

Arguments

x	ts-boxable time series, an object of class <code>ts</code> , <code>xts</code> , <code>zoo</code> , <code>data.frame</code> , <code>data.table</code> , <code>tbl</code> , <code>tbl_ts</code> , <code>tbl_time</code> , or <code>timeSeries</code> .
to	desired frequency, either a character string ("year", "quarter", "month") or an integer (1, 4, 12).
aggregate	character string, or function. Either "mean", "sum", "first", or "last", or any aggregate function, such as <code>base::mean()</code> .
na.rm	logical, if TRUE, incomplete periods are aggregated as well. For irregular series, incomplete periods are always aggregated.

Value

a ts-boxable time series, with the same class as the input.

Examples

```
ts_frequency(cbind(mdeaths, fdeaths), "year", "sum")
ts_frequency(cbind(mdeaths, fdeaths), "quarter", "last")

ts_frequency(AirPassengers, 4, "sum")

# Note that incomplete years are omitted by default
ts_frequency(EuStockMarkets, "year")
ts_frequency(EuStockMarkets, "year", na.rm = TRUE)
```

 ts_ggplot

Plot Time Series, Using ggplot2

Description

ts_ggplot() has the same syntax and produces a similar plot as `ts_plot()`, but uses the `ggplot2` graphic system, and can be customized. With `theme_tsbox()` and `scale_color_tsbox()`, the output of `ts_ggplot` has a similar look and feel.

Usage

```
ts_ggplot(..., title, subtitle, ylab = "")

theme_tsbox(base_family = getOption("ts_font", ""), base_size = 12)

colors_tsbox()

scale_color_tsbox(...)

scale_fill_tsbox(...)
```

Arguments

...	ts-boxable time series, objects of class <code>ts</code> , <code>xts</code> , <code>data.frame</code> , <code>data.table</code> , or <code>tibble</code> . For <code>scale_</code> functions, arguments passed to subfunctions.
title	title (optional)
subtitle	subtitle (optional)
ylab	ylab (optional)
base_family	base font family (can also be set via options)
base_size	base font size

Details

Both `ts_plot()` and `ts_ggplot()` combine multiple ID dimensions into a single dimension. To plot multiple dimensions in different shapes, facets, etc., use standard `ggplot` (see examples).

See Also

[ts_plot\(\)](#), for a simpler and faster plotting function. [ts_dygraphs\(\)](#), for interactive time series plots.

Examples

```
# using the ggplot2 graphic system
p <- ts_ggplot(total = ldeaths, female = fdeaths, male = mdeaths)
p

# with themes for the look and feel of ts_plot()
p + theme_tsbox() + scale_color_tsbox()

# also use themes with standard ggplot
suppressMessages(library(ggplot2))
df <- ts_df(ts_c(total = ldeaths, female = fdeaths, male = mdeaths))
ggplot(df, aes(x = time, y = value)) +
  facet_wrap("id") +
  geom_line() +
  theme_tsbox() +
  scale_color_tsbox()

## Not run:
library(dataseries)
dta <- ds(c("GDP.PBRTT.A.R", "CCI.CCIIR"), "xts")
ts_ggplot(ts_scale(ts_span(
  ts_c(
    `GDP Growth` = ts_pc(dta[, 'GDP.PBRTT.A.R']),
    `Consumer Sentiment Index` = dta[, 'CCI.CCIIR']
  ),
  start = "1995-01-01"
))) +
  ggplot2::ggtitle("GDP and Consumer Sentiment", subtitle = "normalized values") +
  theme_tsbox() +
  scale_color_tsbox()

## End(Not run)
```

 ts_index

Indices from Levels or Percentage Rates

Description

`ts_index` returns an index series, with value of 1 at base date. `ts_compound` builds an index from percentage change rates, starting with 1 and compounding the rates.

Usage

```
ts_compound(x, denominator = 100)
```

```
ts_index(x, base = NULL)
```

Arguments

x	ts-boxable time series, an object of class <code>ts</code> , <code>xts</code> , <code>zoo</code> , <code>data.frame</code> , <code>data.table</code> , <code>tbl</code> , <code>tbl_ts</code> , <code>tbl_time</code> , or <code>timeSeries</code> .
denominator	numeric, set equal to one if percentage change rate is given a decimal fraction
base	base date, character string, <code>Date</code> or <code>POSIXct</code> , at which the

Value

a ts-boxable time series, with the same class as the input.

Examples

```
head(ts_compound(ts_pc(ts_c(fdeaths, mdeaths))))
head(ts_index(ts_df(ts_c(fdeaths, mdeaths)), "1974-02-01"))
```

```
ts_plot(
  `My Expert Knowledge` = ts_chain(
    mdeaths,
    ts_compound(ts_bind(ts_pc(mdeaths), 15, 23, 33))),
  `So Far` = mdeaths,
  title = "A Very Manual Forecast"
)
```

 ts_lag

Lag or Lead of Time Series

Description

Shift time stamps in ts-boxable time series, either by a number of periods or by a fixed amount of time.

Usage

```
ts_lag(x, by = 1)
```

Arguments

x	ts-boxable time series, an object of class <code>ts</code> , <code>xts</code> , <code>zoo</code> , <code>data.frame</code> , <code>data.table</code> , <code>tbl</code> , <code>tbl_ts</code> , <code>tbl_time</code> , or <code>timeSeries</code> .
by	integer or character, either the number of shifting periods (<code>integer</code>), or an absolute amount of time (<code>character</code>). See details.

Details

The lag order, by, is defined the opposite way as in R base. Thus, -1 is a lead and +1 a lag.

If by is integer, the time stamp is shifted by the number of periods. This requires the series to be regular.

If by is character, the time stamp is shifted by a specific amount of time. This can be one of "sec", "min", "hour", "day", "week", "month", "quarter" or "year", optionally preceded by a (positive or negative) integer and a space, or followed by plural "s". This is passed to `base::seq.Date()`. This does not require the series to be regular.

Value

a ts-boxable time series, with the same class as the input. If time stamp shifting causes the object to be irregular, a data frame is returned.

Examples

```
ts_plot(AirPassengers, ts_lag(AirPassengers), title = "Illustrating the need for glasses")

head(ts_lag(AirPassengers, "1 month"))
head(ts_lag(AirPassengers, "1 year"))
head(ts_lag(ts_df(AirPassengers), "2 day"))
# head(ts_lag(ts_df(AirPassengers), "2 min")) not yet working
```

 ts_long

Reshaping Multiple Time Series

Description

Functions to reshape multiple time series from 'wide' to 'long' and vice versa. Note that long format data frames are ts-boxable objects, where wide format data frames are not. `ts_long` automatically identifies a **time** column, and uses columns on the left as id columns.

Usage

```
ts_long(x)
```

```
ts_wide(x)
```

Arguments

x a ts-boxable time series, or a wide data.frame, data.table, or tibble.

Value

object with the same class as input

Examples

```
df.wide <- ts_wide(ts_df(ts_c(mdeaths, fdeaths)))
head(df.wide)
head(ts_long(df.wide))
```

ts_na_omit

Omit NA values

Description

Remove NA values in ts-boxable objects, turning explicit into implicit missing values.

Usage

```
ts_na_omit(x)
```

Arguments

x ts-boxable time series, an object of class ts, xts, zoo, data.frame, data.table, tbl, tbl_ts, tbl_time, or timeSeries.

Details

Note that internal NAs in ts time series will not be removed, as this conflicts with the regular structure.

Value

a ts-boxable time series, with the same class as the input.

See Also

[ts_regular](#), for the opposite, turning implicit into explicit missing values.

Examples

```
x <- AirPassengers
x[c(2, 4)] <- NA

# A ts object does only know explicit NAs
head(ts_na_omit(x))

# by default, NAs are implicit in data frames
head(ts_df(x))

# make NAs explicit
head(ts_regular(ts_df(x)))

# and implicit again
head(ts_na_omit(ts_regular(ts_df(x))))
```

 ts_pc

First Differences and Percentage Change Rates

Description

ts_pcy and ts_diffy calculate the percentage change rate and the difference compared to the previous period, ts_pcy and ts_diffy calculate compared to the same period of the previous year. ts_pca calculates annualized percentage change rates compared to the previous period.

Usage

```
ts_pc(x)
ts_diff(x)
ts_pca(x)
ts_pcy(x)
ts_diffy(x)
```

Arguments

x ts-boxable time series, an object of class ts, xts, zoo, data.frame, data.table, tbl, tbl_ts, tbl_time, or timeSeries.

Value

a ts-boxable time series, with the same class as the input.

Examples

```
tail(ts_diff(ts_c(fdeaths, mdeaths)))
tail(ts_pc(ts_c(fdeaths, mdeaths)))
tail(ts_pca(ts_c(fdeaths, mdeaths)))
tail(ts_pcy(ts_c(fdeaths, mdeaths)))
tail(ts_diffy(ts_c(fdeaths, mdeaths)))
```

 ts_pick

Pick Series (Experimental)

Description

Pick (and optionally rename) series from multiple time series.

Usage

```
ts_pick(x, ...)
```

Arguments

`x` ts-boxable time series, an object of class `ts`, `xts`, `zoo`, `data.frame`, `data.table`, `tbl`, `tbl_ts`, `tbl_time`, or `timeSeries`.

`...` character string(s), names of the series to be picked, or integer, with positions. If arguments are named, the series will be renamed.

Value

a ts-boxable time series, with the same class as the input.

Examples

```
# Interactive use

ts_plot(ts_pick(
  EuStockMarkets,
  `My Dax` = "DAX",
  `My Smi` = "SMI"
))
head(ts_pick(EuStockMarkets, c(1, 2)))
head(ts_pick(EuStockMarkets, `My Dax` = 'DAX', `My Smi` = 'SMI'))

# Programming use
to.be.picked.and.renamed <- c(`My Dax` = "DAX", `My Smi` = "SMI")
head(ts_pick(EuStockMarkets, to.be.picked.and.renamed))
```

ts_plot

Plot Time Series

Description

`ts_plot()` is a fast and simple plotting function for ts-boxable time series, with limited customizability. For more theme options, use [ts_ggplot\(\)](#).

Usage

```
ts_plot(..., title, subtitle, ylab = "", family = getOption("ts_font",
  "sans"))
```

Arguments

...	ts-boxable time series, objects of class <code>ts</code> , <code>xts</code> , <code>data.frame</code> , <code>data.table</code> , or <code>tibble</code> .
<code>title</code>	title (optional)
<code>subtitle</code>	subtitle (optional)
<code>ylab</code>	ylab (optional)
<code>family</code>	font family (optional, can also be set via options)

Details

Both `ts_plot()` and `ts_ggplot()` combine multiple ID dimensions into a single dimension. To plot multiple dimensions in different shapes, facets, etc., use standard `ggplot`.

Limited customizability of `ts_plot` is available via options. See examples.

See Also

`ts_ggplot()`, for a plotting function based on `ggplot2`. `ts_dygraphs()`, for interactive time series plots. `ts_save()` to save a plot to the file system.

Examples

```
ts_plot(  
  AirPassengers,  
  title = "Airline passengers",  
  subtitle = "The classic Box & Jenkins airline data"  
)  
  
# naming arguments  
ts_plot(total = ldeaths, female = fdeaths, male = mdeaths)  
  
# using different ts-boxable objects  
ts_plot(ts_scale(ts_c(  
  ts_xts(airmiles),  
  ts_tbl(co2),  
  JohnsonJohnson,  
  ts_df(discoveries)  
)))  
  
# customize ts_plot  
op <- options(  
  tsbox.lwd = 3,  
  tsbox.col = c("gray51", "gray11"),  
  tsbox.lty = "dashed"  
)  
ts_plot(  
  "Female" = fdeaths,  
  "Male" = mdeaths  
)
```

```
options(op) # restore defaults
```

ts_regular	<i>Enforce Regularity</i>
------------	---------------------------

Description

Enforces regularity in data frame and xts objects, by turning implicit NAs into explicit NAs. In ts objects, regularity is automatically enforced.

Usage

```
ts_regular(x, fill = NA)
```

Arguments

x	ts-boxable time series, an object of class ts, xts, zoo, data.frame, data.table, tbl, tbl_ts, tbl_time, or timeSeries.
fill	instead of NA, an alternative value can be specified

Examples

```
x0 <- AirPassengers
x0[c(10, 15)] <- NA
x <- ts_na_omit(ts_dts(x0))
ts_regular(x)
ts_regular(x, fill = 0)

m <- mdeaths
m[c(10, 69)] <- NA
f <- fdeaths
f[c(1, 3, 15)] <- NA

ts_regular(ts_na_omit(ts_dts(ts_c(f, m))))
```

ts_save	<i>Save Previous Plot</i>
---------	---------------------------

Description

Save Previous Plot

Usage

```
ts_save(filename = tempfile(fileext = ".pdf"), width = 10,
        height = 5, device = NULL, open = TRUE)
```

Arguments

filename	filename
width	width
height	height
device	device
open	logical, should the saved plot be opened?

ts_scale	<i>Normalized Time Series</i>
----------	-------------------------------

Description

Subtract mean and divide by standard deviation. Based on `base::scale()`.

Usage

```
ts_scale(x, center = TRUE, scale = TRUE)
```

Arguments

x	ts_boxable time series
center	logical
scale	logical

Examples

```
ts_plot(ts_scale((ts_c(airmiles, co2, JohnsonJohnson, discoveries))))
ts_plot(ts_scale(ts_c(AirPassengers, DAX = EuStockMarkets[, 'DAX'])))
```

ts_span	<i>Limit Time Span</i>
---------	------------------------

Description

Filter time series for a time span.

Usage

```
ts_span(x, start = NULL, end = NULL, template = NULL,
        extend = FALSE)
```

Arguments

x	ts-boxable time series, an object of class <code>ts</code> , <code>xts</code> , <code>zoo</code> , <code>data.frame</code> , <code>data.table</code> , <code>tbl</code> , <code>tbl_ts</code> , <code>tbl_time</code> , or <code>timeSeries</code> .
start	start date, character string, <code>Date</code> or <code>POSIXct</code> .
end	end date, character string, <code>Date</code> or <code>POSIXct</code> .
template	ts-boxable time series, an object of class <code>ts</code> , <code>xts</code> , <code>data.frame</code> , <code>data.table</code> , or <code>tibble</code> . If provided, <code>from</code> and <code>to</code> will be extracted from the object.
extend	logical. If true, the start and end values are allowed to extend the series (by adding NA values).

Details

All date and times, when entered as character strings, are processed by `anytime::anydate()` or `anytime::anytime()`. Thus a wide range of inputs are possible. See examples.

`start` and `end` can be specified relative to each other, using one of "sec", "min", "hour", "day", "week", "month", "quarter" or "year", or an abbreviation. If the series are of the same frequency, the shift can be specified in periods. See examples.

Value

a ts-boxable time series, with the same class as the input.

Examples

```
# use 'anytime' shortcuts
ts_span(mdeaths, start = "1979")      # shortcut for 1979-01-01
ts_span(mdeaths, start = "1979-4")   # shortcut for 1979-04-01
ts_span(mdeaths, start = "197904")   # shortcut for 1979-04-01

# it's fine to use an to date outside of series span
ts_span(mdeaths, end = "2001-01-01")

# use strings to set start or end relative to each other

ts_span(mdeaths, start = "-7 month") # last 7 months
ts_span(mdeaths, start = -7)         # last 7 periods
ts_span(mdeaths, start = -1)         # last single value
ts_span(mdeaths, end = "1e4 hours")  # first 10000 hours

ts_plot(
  ts_span(mdeaths, start = "-3 years"),
  title = "Three years ago",
  subtitle = "The last three years of available data"
)

ts_ggplot(
  ts_span(mdeaths, end = "28 weeks"),
```

```

    title = "28 weeks later",
    subtitle = "The first 28 weeks of available data"
) + theme_tsbox() + scale_color_tsbox()

# Limit span of 'discoveries' to the same span as 'AirPassengers'
ts_span(discoveries, template = AirPassengers)
ts_span(mdeaths, end = "19801201", extend = TRUE)

```

ts_summary

Time Series Properties

Description

Extract time series properties, such as the number of observations (`obs`), the time differences between observations (`obs`), the number of observations per year (`freq`), and the start time stamp (`start`) and the end time stamp (`end`) of the series.

Usage

```
ts_summary(x, spark = FALSE)
```

Arguments

<code>x</code>	ts-boxable time series, an object of class <code>ts</code> , <code>xts</code> , <code>zoo</code> , <code>data.frame</code> , <code>data.table</code> , <code>tbl</code> , <code>tbl_ts</code> , <code>tbl_time</code> , or <code>timeSeries</code> .
<code>spark</code>	logical should an additional column with a spark-line added to the data frame (experimental, ASCII only on Windows.)

Value

`ts_summary` returns a `data.frame`. Individual column can be accessed through the `$` notation (see examples).

Examples

```

ts_summary(ts_c(mdeaths, austres))
ts_summary(ts_c(mdeaths, austres), spark = TRUE)
# Extracting specific properties
ts_summary(AirPassengers)$start
ts_summary(AirPassengers)$freq
ts_summary(AirPassengers)$obs

```

ts_trend	<i>Loess Trend Estimation</i>
----------	-------------------------------

Description

Trend estimation that uses `stats::loess()`.

Usage

```
ts_trend(x, ...)
```

Arguments

x	ts-boxable time series, an object of class <code>ts</code> , <code>xts</code> , <code>zoo</code> , <code>data.frame</code> , <code>data.table</code> , <code>tbl</code> , <code>tbl_ts</code> , <code>tbl_time</code> , or <code>timeSeries</code> .
...	arguments, passed to <code>stats::loess()</code> : <ul style="list-style-type: none"> • degree degree of Loess smoothing • span smoothing parameter, if <code>NULL</code>, an automated search performed (see Details)

Examples

```
ts_plot(
  `Raw series` = fdeaths,
  `Loess trend` = ts_trend(fdeaths),
  title = "Deaths from Lung Diseases",
  subtitle = "per month"
)
```

ts_ts	<i>Convert Everything to Everything</i>
-------	---

Description

`tsbox` is built around a set of converters, which convert time series stored as `ts`, `xts`, `data.frame`, `data.table` or `tibble` to each other.

Usage`ts_data.frame(x)``ts_df(x)``ts_data.table(x)``ts_dt(x)``ts_tbl(x)``ts_tibbletime(x)``ts_timeSeries(x)``ts_ts(x)``ts_tsibble(x)``ts_tslist(x)``ts_xts(x)``ts_zoo(x)`**Arguments**

`x` ts-boxable time series, an object of class `ts`, `xts`, `zoo`, `data.frame`, `data.table`, `tbl`, `tbl_ts`, `tbl_time`, or `timeSeries`.

Details

In data frames, multiple time series will be stored in a 'long' format. `tsbox` detects a *value*, a *time* and zero to several *id* columns. Column detection is done in the following order:

1. Starting **on the right**, the first numeric or integer column is used as **value column**.
2. Using the remaining columns, and starting on the right again, the first Date, POSIXct, numeric or character column is used as **time column**. character strings are parsed by `anytime::anytime()`. The time stamp, `time`, indicates the beginning of a period.
3. **All remaining** columns are **id columns**. Each unique combination of id columns points to a time series.

Alternatively, the **time** column and the **value** column to be explicitly named as `time` and `value`. If explicit names are used, the column order will be ignored.

Whenever possible, `tsbox` relies on **heuristic time conversion**. When a monthly "ts" time series, e.g., `AirPassengers`, is converted to a data frame, each time stamp (of class "Date") is the first day of the month. In most circumstances, this reflects the actual meaning of the data stored in a "ts" object. Technically, of course, this is not correct: "ts" objects divide time in period of equal length,

while in reality, February is shorter than January. Heuristic conversion is done for frequencies of 0.1 (decades), 1 (years), 4 (quarters) and 12 (month).

For other frequencies, e.g. 260, of `EuStockMarkets`, `tsbox` uses **exact time conversion**. The year is divided into 260 equally long units, and time stamp of a period will be a point in time (of class `"POSIXct"`).

Value

ts-boxable time series of the desired class, an object of class `ts`, `xts`, `data.frame`, `data.table`, or `tibble`.

Examples

```
x.ts <- ts_c(mdeaths, fdeaths)
head(x.ts)
head(ts_df(x.ts))

suppressMessages(library(dplyr))
head(ts_tbl(x.ts))

suppressMessages(library(data.table))
head(ts_dt(x.ts))

suppressMessages(library(xts))
head(ts_xts(x.ts))

# heuristic time conversion
# 1 month: approx. 1/12 year
head(ts_df(AirPassengers))

# exact time conversion
# 1 trading day: exactly 1/260 year
head(ts_df(EuStockMarkets))

# multiple id
multi.id.df <- rbind(
  within(ts_df(ts_c(fdeaths, mdeaths)), type <- "level"),
  within(ts_pc(ts_df(ts_c(fdeaths, mdeaths))), type <- "pc")
)
head(ts_ts(multi.id.df))
ts_plot(multi.id.df)
```

Index

*Topic **package**
 tsbox-package, 2
%ts*(ts_arithmetic), 5
%ts+(ts_arithmetic), 5
%ts-(ts_arithmetic), 5
%ts/(ts_arithmetic), 5

anytime::anytime(), 25

base::mean(), 11
base::scale(), 21
base::seq.Date(), 15

colors_tsbox (ts_ggplot), 12
copy_class, 3

load_suggested (ts_), 4

relevant_class, 3

scale_color_tsbox (ts_ggplot), 12
scale_color_tsbox(), 12
scale_fill_tsbox (ts_ggplot), 12
stats::loess(), 24
stats::prcomp, 10

theme_tsbox (ts_ggplot), 12
theme_tsbox(), 12
ts_, 4, 10
ts_apply (ts_), 4
ts_arithmetic, 5
ts_bind, 6, 8
ts_boxable, 7
ts_c, 7, 8
ts_chain (ts_bind), 6
ts_compound (ts_index), 13
ts_data.frame (ts_ts), 24
ts_data.table (ts_ts), 24
ts_default, 9
ts_df (ts_ts), 24
ts_diff (ts_pc), 17
ts_diffy (ts_pc), 17
ts_dt (ts_ts), 24
ts_dts, 9
ts_dygraphs (ts_examples), 10
ts_dygraphs(), 13, 19
ts_end (tsbox-deprecated), 4
ts_examples, 5, 10
ts_forecast (ts_examples), 10
ts_frequency, 11
ts_ggplot, 12
ts_ggplot(), 18, 19
ts_index, 13
ts_lag, 14
ts_long, 15
ts_na_omit, 16
ts_pc, 17
ts_pca (ts_pc), 17
ts_pcy (ts_pc), 17
ts_pick, 17
ts_plot, 18
ts_plot(), 12, 13
ts_prcomp (ts_examples), 10
ts_regular, 16, 20
ts_save, 20
ts_save(), 19
ts_scale, 21
ts_seas (ts_examples), 10
ts_span, 21
ts_start (tsbox-deprecated), 4
ts_summary, 23
ts_tbl (ts_ts), 24
ts_tibbletime (ts_ts), 24
ts_timeSeries (ts_ts), 24
ts_trend, 24
ts_ts, 24
ts_tsibble (ts_ts), 24
ts_tslist (ts_ts), 24
ts_wide (ts_long), 15
ts_xts (ts_ts), 24

`ts_zoo` (`ts_ts`), [24](#)
`tsbox` (`tsbox-package`), [2](#)
`tsbox-deprecated`, [4](#)
`tsbox-package`, [2](#)