

# Package ‘utile.visuals’

January 27, 2021

**Title** Create Visuals for Publication

**Version** 0.3.0

**Description** A small set of functions to aid in the production of visuals in ggplot2. Includes minimalist themes with transparent backgrounds and a suite of tools for building survival curves with risk tables.

**License** LGPL (>= 2)

**URL** <https://github.com/efinite/utile.visuals>

**BugReports** <https://github.com/efinite/utile.visuals/issues>

**Encoding** UTF-8

**LazyData** TRUE

**Depends** R (>= 3.4.0)

**Imports** dplyr, ggplot2, gridExtra, purrr

**Suggests** survival, broom, grid

**RoxygenNote** 7.1.1

**NeedsCompilation** no

**Author** Eric Finnesgard [aut, cre]

**Maintainer** Eric Finnesgard <efinite@outlook.com>

**Repository** CRAN

**Date/Publication** 2021-01-26 23:10:02 UTC

## R topics documented:

append_table . . . . .	2
geom_stepconfint . . . . .	3
ggrisktable . . . . .	5
theme_black . . . . .	6
theme_risk_black . . . . .	6
theme_risk_white . . . . .	7
theme_white . . . . .	8

<b>Index</b>	<b>9</b>
--------------	----------

---

append_table	<i>Append a ggplot2 table to the bottom of a ggplot2 plot</i>
--------------	---

---

### Description

Aligns axes and combines a ggplot2 plot and table into a single plot. Can handle legends.

### Usage

```
append_table(
  plot = NULL,
  table = NULL,
  plot.height = 1,
  table.height = 0.1,
  plot.width = 1,
  extract.legend = TRUE,
  legend.width = 0.2,
  legend.offset = -15
)
```

### Arguments

plot	Required. ggplot2::ggplot() object. If a legend is present, it will be extracted.
table	Required. ggplot2::ggplot object. If a legend is present, it will be removed and ignored.
plot.height	Optional. Numeric. Height of plot relative to table. Defaults to 1.
table.height	Optional. Numeric. Height of table relative to plot. Defaults to 0.1.
plot.width	Optional. Numeric. Width of plot relative to legend. Ignored if no legend present in plot. Defaults to 1.
extract.legend	Optional. Logical. Indicates whether to extract the legend from the plot and reinsert it adjacent to the final combined plot. May be undesired if legend already embedded within the plot area. Defaults to TRUE.
legend.width	Optional. Numeric. Width of legend relative to plot. Ignored if no legend present in plot or 'extract.legend'=FALSE. Defaults 0.2.
legend.offset	Optional. Numeric. Vertical offset of legend. Used to raise or lower. Ignored if no legend present in plot or 'extract.legend'=FALSE. Defaults to -15.

### Value

A ggplot2 tableGrob object. Use grid::grid.draw() to open in RStudio viewer. Works with ggplot2::ggsave() out of the box.

### Note

To ensure proper alignment, double check that both plots use the same scale and breaks!

**Examples**

```

library(survival)
library(ggplot2)
library(broom) # tidy() model data
library(grid) # grid.draw() finished plot

# Data with group names specified
data_diabetic <- diabetic
data_diabetic$trt <- as.factor(data_diabetic$trt)
levels(data_diabetic$trt) <- c('None', 'Laser')

# Survival Model
fit <- survfit(Surv(time, status) ~ trt, data = data_diabetic)

# Kaplan Meier (KM) Plot
plot_km <- ggplot(
  data = tidy(fit),
  mapping = aes(x = time, y = estimate)
) +
  geom_step(aes(color = strata)) +
  geom_stepconfint(aes(ymin = conf.low, ymax = conf.high, fill = strata), alpha = 0.3) +
  coord_cartesian(c(0, 50)) + # Note scale set here!
  scale_x_continuous(expand = c(0.02,0)) +
  labs(x = 'Time', y = 'Freedom From Event') +
  scale_color_manual(
    values = c('#d83641', '#1A45A7'),
    name = 'Treatment',
    labels = c('Laser', 'None'),
    aesthetics = c('colour', 'fill')) +
  theme_black()

# Risk Table
tbl_risk <- ggrisktable(fit, c(0, 10, 20, 30, 40, 50)) +
  coord_cartesian(c(0, 50)) +
  scale_x_continuous(expand = c(0.02,0)) +
  theme_risk_black()

# Combine KM plot and risk table
plot_cmbd <- append_table(
  plot = plot_km,
  table = tbl_risk
)

# Draw in RStudio viewer
grid.newpage()
grid.draw(plot_cmbd)

```

**Description**

Produces a step function confidence interval for survival curves. Essentially the `geom_step()` for confidence intervals which `ggplot2` does not provide.

**Usage**

```
geom_stepconfint(
  mapping = NULL,
  data = NULL,
  stat = "identity",
  position = "identity",
  na.rm = FALSE,
  ...
)
```

**Arguments**

<code>mapping</code>	Aesthetic mappings with <code>aes()</code> function. Like <code>geom_ribbon()</code> , you must provide columns for <code>x</code> , <code>ymin</code> (lower limit), <code>ymax</code> (upper limit).
<code>data</code>	The data to be displayed in this layer. Can inherit from <code>ggplot</code> parent.
<code>stat</code>	The statistical transformation to use on the data for this layer, as a string. Defaults to 'identity'.
<code>position</code>	Position adjustment, either as a string, or the result of a call to a position adjustment function.
<code>na.rm</code>	If <code>FALSE</code> , the default, missing values are removed with a warning. If <code>TRUE</code> , missing values are silently removed.
<code>...</code>	Optional. Any other <code>ggplot geom_ribbon()</code> arguments.

**Note**

Adapted from the `survminer` package <<https://github.com/kassambara/survminer>>.

**Examples**

```
library(survival)
library(broom)
library(ggplot2)

fit <- survfit(Surv(time, status) ~ trt, data = diabetic)
fit <- survfit0(fit) # connect origin

ggplot(
  data = tidy(fit),
  mapping = aes(x = time, y = estimate)
) +
  geom_step(aes(color = strata)) +
  geom_stepconfint(aes(ymin = conf.low, ymax = conf.high, fill = strata), alpha = 0.3) +
  coord_cartesian(c(0, 50)) +
  scale_x_continuous(expand = c(0.02, 0)) +
```

```
labs(x = 'Time', y = 'Freedom From Event') +
scale_color_manual(
  values = c('#d83641', '#1A45A7'),
  name = 'Treatment',
  labels = c('None', 'Laser'),
  aesthetics = c('colour', 'fill')) +
theme_black()
```

---

**ggrisktable***Create a ggplot2 table showing the number at risk*

---

## Description

A simple wrapper function which calculates the numbers at risk for a survival model and a given set of time points then creates a ggplot2 table with them.

## Usage

```
ggrisktable(
  fit = NULL,
  times = NULL,
  text.color = "black",
  strata.order = NULL
)
```

## Arguments

<code>fit</code>	Required. <code>survival::survfit()</code> object.
<code>times</code>	Required. Numeric. One or more time points to calculate the number at risk for.
<code>text.color</code>	Optional. Character. Color of text within table. Defaults to 'black'.
<code>strata.order</code>	Optional. Character. Ordered names of strata factor levels.

## Value

An unformatted ggplot2 table showing the number at risk.

## Examples

```
library(survival)

fit <- survfit(Surv(time, status) ~ trt, data = diabetic)

ggrisktable(
  fit = fit,
  times = c(0, 10, 20, 30, 40, 50),
  strata.order = c('0', '1')
) + theme_risk_black()
```

---

`theme_black`*Minimalist black theme for ggplot2*

---

**Description**

A ggplot2 theme which removes most background elements and makes all text/lines black.

**Usage**

```
theme_black(  
  base_size = 11,  
  base_family = "",  
  base_line_size = base_size/22,  
  base_rect_size = base_size/22  
)
```

**Arguments**

`base_size` Optional. Numeric. Base font size. Defaults to 11.  
`base_family` Optional. Numeric. Base font family. Defaults to ?.  
`base_line_size` Optional. Numeric. Base line element size. Defaults to `base_size/22`.  
`base_rect_size` Optional. Numeric. Base rectangle element size. Defaults to `base_size/22`.

**Note**

Recommend exporting as PNG or TIFF to preserve background transparency.

---

`theme_risk_black`*Minimalist black risk table theme for ggplot2*

---

**Description**

Ggplot2 theme which removes most background elements and makes all text/lines black.

**Usage**

```
theme_risk_black(  
  base_size = 10,  
  base_family = "",  
  base_line_size = base_size/22,  
  base_rect_size = base_size/22  
)
```

**Arguments**

base\_size      Optional. Numeric. Base font size. Defaults to 10.  
base\_family    Optional. Numeric. Base font family. Defaults to ?.  
base\_line\_size Optional. Numeric. Base line element size. Defaults to base\_size/22.  
base\_rect\_size Optional. Numeric. Base rectangle element size. Defaults to base\_size/22.

**Note**

Recommend exporting as PNG or TIFF to preserve background transparency.

---

theme_risk_white	<i>Minimalist white risk table theme for ggplot2</i>
------------------	--

---

**Description**

Ggplot2 theme which removes most background elements and makes all text/lines white.

**Usage**

```
theme_risk_white(  
  base_size = 10,  
  base_family = "",  
  base_line_size = base_size/22,  
  base_rect_size = base_size/22  
)
```

**Arguments**

base\_size      Optional. Numeric. Base font size. Defaults to 10.  
base\_family    Optional. Numeric. Base font family. Defaults to ?.  
base\_line\_size Optional. Numeric. Base line element size. Defaults to base\_size/22.  
base\_rect\_size Optional. Numeric. Base rectangle element size. Defaults to base\_size/22.

**Note**

Recommend exporting as PNG or TIFF to preserve background transparency.

---

`theme_white`*Minimalist white theme for ggplot2*

---

**Description**

A ggplot2 theme which removes most background elements and makes all text/lines white.

**Usage**

```
theme_white(  
  base_size = 11,  
  base_family = "",  
  base_line_size = base_size/22,  
  base_rect_size = base_size/22  
)
```

**Arguments**

`base_size` Optional. Numeric. Base font size. Defaults to 11.  
`base_family` Optional. Numeric. Base font family. Defaults to ?.  
`base_line_size` Optional. Numeric. Base line element size. Defaults to `base_size/22`.  
`base_rect_size` Optional. Numeric. Base rectangle element size. Defaults to `base_size/22`.

**Note**

Recommend exporting as PNG or TIFF to preserve background transparency.



# Index

`append_table`, 2

`geom_stepconfint`, 3

`ggrisktable`, 5

`theme_black`, 6

`theme_risk_black`, 6

`theme_risk_white`, 7

`theme_white`, 8