

Package ‘whitebox’

May 15, 2022

Type Package

Title 'WhiteboxTools' R Frontend

Version 2.1.4

Description An R frontend for the 'WhiteboxTools' library, which is an advanced geospatial data analysis platform developed by Prof. John Lindsay at the University of Guelph's Geomorphometry and Hydrogeomatics Research Group. 'WhiteboxTools' can be used to perform common geographical information systems (GIS) analysis operations, such as cost-distance analysis, distance buffering, and raster reclassification. Remote sensing and image processing tasks include image enhancement (e.g. panchromatic sharpening, contrast adjustments), image mosaicing, numerous filtering operations, simple classification (k-means), and common image transformations. 'WhiteboxTools' also contains advanced tooling for spatial hydrological analysis (e.g. flow-accumulation, watershed delineation, stream network analysis, sink removal), terrain analysis (e.g. common terrain indices such as slope, curvatures, wetness index, hillshading; hypsometric analysis; multi-scale topographic position analysis), and LiDAR data processing. Suggested citation: Lindsay (2016) <[doi:10.1016/j.cageo.2016.07.003](https://doi.org/10.1016/j.cageo.2016.07.003)>.

Maintainer Andrew Brown <brown.andrewg@gmail.com>

License MIT + file LICENSE

SystemRequirements WhiteboxTools
(<https://github.com/jblindsay/whitebox-tools/releases/latest>)

Encoding UTF-8

RoxygenNote 7.1.2

URL <https://github.com/giswqs/whiteboxR>

BugReports <https://github.com/giswqs/whiteboxR/issues>

Suggests knitr, rmarkdown, testthat, terra

VignetteBuilder knitr

Depends R (>= 3.0.0)

LazyData true

NeedsCompilation no

Author Qiusheng Wu [aut],
Andrew Brown [ctb, cre]

Repository CRAN

Date/Publication 2022-05-15 17:20:02 UTC

R topics documented:

check_whitebox_binary	13
sample_dem_data	13
wbttoolparameters	14
wbttools	15
wbt_absolute_value	16
wbt_accumulation_curvature	16
wbt_adaptive_filter	17
wbt_add	18
wbt_add_point_coordinates_to_table	19
wbt_aggregate_raster	20
wbt_and	21
wbt_anova	22
wbt_arcosh	23
wbt_arc_cos	23
wbt_arc_sin	24
wbt_arc_tan	25
wbt_arsinh	26
wbt_artanh	27
wbt_ascii_to_las	27
wbt_aspect	28
wbt_assess_route	29
wbt_atan2	30
wbt_attribute_correlation	31
wbt_attribute_correlation_neighbourhood_analysis	31
wbt_attribute_histogram	32
wbt_attribute_scattergram	33
wbt_average_flowpath_slope	34
wbt_average_normal_vector_angular_deviation	35
wbt_average_overlay	36
wbt_average_upslope_flowpath_length	37
wbt_balance_contrast_enhancement	37
wbt_basins	38
wbt_bilateral_filter	39
wbt_block_maximum_gridding	40
wbt_block_minimum_gridding	41
wbt_boundary_shape_complexity	42
wbt_breach_depressions	43
wbt_breach_depressions_least_cost	44
wbt_breach_single_cell_pits	45
wbt_buffer_raster	45
wbt_burn_streams_at_roads	46
wbt_canny_edge_detection	47
wbt_ceil	48
wbt_centroid	49
wbt_centroid_vector	50
wbt_change_vector_analysis	51

wbt_circular_variance_of_aspect	52
wbt_classify_buildings_in_lidar	53
wbt_classify_overlap_points	54
wbt_clean_vector	55
wbt_clip	55
wbt_clip_lidar_to_polygon	56
wbt_clip_raster_to_polygon	57
wbt_closing	58
wbt_clump	59
wbt_compactness_ratio	60
wbt_conditional_evaluation	60
wbt_conservative_smoothing_filter	61
wbt_construct_vector_tin	62
wbt_contours_from_points	63
wbt_contours_from_raster	64
wbt_convert_nodata_to_zero	65
wbt_convert_raster_format	66
wbt_corner_detection	67
wbt_correct_vignetting	68
wbt_cos	69
wbt_cosh	69
wbt_cost_allocation	70
wbt_cost_distance	71
wbt_cost_pathway	72
wbt_count_if	73
wbt_create_colour_composite	74
wbt_create_hexagonal_vector_grid	75
wbt_create_plane	76
wbt_create_rectangular_vector_grid	77
wbt_crispness_index	78
wbt_cross_tabulation	78
wbt_csv_points_to_vector	79
wbt_cumulative_distribution	80
wbt_curvedness	81
wbt_d8_flow_accumulation	82
wbt_d8_mass_flux	83
wbt_d8_pointer	84
wbt_dbscan	85
wbt_decrement	86
wbt_depth_in_sink	86
wbt_dev_from_mean_elev	87
wbt_difference	88
wbt_difference_curvature	89
wbt_diff_from_mean_elev	90
wbt_diff_of_gaussian_filter	91
wbt_directional_relief	92
wbt_direct_decorrelation_stretch	93
wbt_dissolve	94

wbt_distance_to_outlet	95
wbt_diversity_filter	96
wbt_divide	97
wbt_downslope_distance_to_stream	98
wbt_downslope_flowpath_length	99
wbt_downslope_index	100
wbt_d_inf_flow_accumulation	101
wbt_d_inf_mass_flux	102
wbt_d_inf_pointer	103
wbt_edge_contamination	103
wbt_edge_density	104
wbt_edge_preserving_mean_filter	105
wbt_edge_proportion	106
wbt_elevation_above_stream	107
wbt_elevation_above_stream_euclidean	108
wbt_elev_above_pit	109
wbt_elev_percentile	109
wbt_elev_relative_to_min_max	110
wbt_elev_relative_to_watershed_min_max	111
wbt_eliminate_coincident_points	112
wbt_elongation_ratio	113
wbt_embankment_mapping	114
wbt_emboss_filter	115
wbt_equal_to	116
wbt_erase	117
wbt_erase_polygon_from_lidar	118
wbt_erase_polygon_from_raster	119
wbt_euclidean_allocation	120
wbt_euclidean_distance	120
wbt_evaluate_training_sites	121
wbt_exp	122
wbt_exp2	123
wbt_export_table_to_csv	124
wbt_exposure_towards_wind_flux	125
wbt_extend_vector_lines	126
wbt_extract_nodes	127
wbt_extract_raster_values_at_points	127
wbt_extract_streams	128
wbt_extract_valleys	129
wbt_farthest_channel_head	130
wbt_fast_almost_gaussian_filter	131
wbt_fd8_flow_accumulation	132
wbt_fd8_pointer	133
wbt_feature_preserving_smoothing	134
wbt_fetch_analysis	135
wbt_fill_burn	136
wbt_fill_depressions	137
wbt_fill_depressions_planchon_and_darboux	138

wbt_fill_depressions_wang_and_liu	139
wbt_fill_missing_data	140
wbt_fill_single_cell_pits	141
wbt_filter_lidar_classes	141
wbt_filter_lidar_scan_angles	142
wbt_filter_raster_features_by_area	143
wbt_find_flightline_edge_points	144
wbt_find_lowest_or_highest_points	145
wbt_find_main_stem	146
wbt_find_no_flow_cells	147
wbt_find_parallel_flow	147
wbt_find_patch_or_class_edge_cells	148
wbt_find_ridges	149
wbt_fix_dangling_arcs	150
wbt_flatten_lakes	151
wbt_flightline_overlap	152
wbt_flip_image	153
wbt_flood_order	154
wbt_floor	154
wbt_flow_accumulation_full_workflow	155
wbt_flow_length_diff	156
wbt_gamma_correction	157
wbt_gaussian_contrast_stretch	158
wbt_gaussian_curvature	159
wbt_gaussian_filter	160
wbt_gaussian_scale_space	161
wbt_generalize_classified_raster	162
wbt_generalize_with_similarity	163
wbt_generating_function	164
wbt_geomorphons	165
wbt_greater_than	166
wbt_hack_stream_order	167
wbt_height_above_ground	168
wbt_help	168
wbt_highest_position	169
wbt_high_pass_filter	170
wbt_high_pass_median_filter	171
wbt_hillshade	172
wbt_hillslopes	173
wbt_histogram_equalization	174
wbt_histogram_matching	175
wbt_histogram_matching_two_images	176
wbt_hole_proportion	177
wbt_horizontal_excess_curvature	177
wbt_horizon_angle	178
wbt_horton_stream_order	179
wbt_hydrologic_connectivity	180
wbt_hypsometrically_tinted_hillshade	181

wbt_hypsometric_analysis	182
wbt_idw_interpolation	183
wbt_ihs_to_rgb	184
wbt_image_autocorrelation	185
wbt_image_correlation	186
wbt_image_correlation_neighbourhood_analysis	187
wbt_image_regression	188
wbt_image_segmentation	189
wbt_image_slider	190
wbt_image_stack_profile	191
wbt_impoundment_size_index	192
wbt_increment	193
wbt_init	193
wbt_insert_dams	197
wbt_install	198
wbt_integer_division	198
wbt_integral_image	199
wbt_intersect	200
wbt_inverse_principal_component_analysis	201
wbt_in_place_add	202
wbt_in_place_divide	202
wbt_in_place_multiply	203
wbt_in_place_subtract	204
wbt_isobasins	205
wbt_is_no_data	206
wbt_jenson_snap_pour_points	206
wbt_join_tables	207
wbt_kappa_index	208
wbt_knn_classification	209
wbt_knn_regression	210
wbt_ks_test_for_normality	211
wbt_k_means_clustering	212
wbt_k_nearest_mean_filter	213
wbt_laplacian_filter	214
wbt_laplacian_of_gaussian_filter	215
wbt_las_to_ascii	216
wbt_las_to_laz	217
wbt_las_to_multipoint_shapefile	217
wbt_las_to_shapefile	218
wbt_las_to_zlidar	219
wbt_layer_footprint	220
wbt_laz_to_las	221
wbt_lee_sigma_filter	221
wbt_length_of_upstream_channels	222
wbt_less_than	223
wbt_license	224
wbt_lidar_block_maximum	225
wbt_lidar_block_minimum	226

wbt_lidar_classify_subset	227
wbt_lidar_colourize	228
wbt_lidar_contour	229
wbt_lidar_digital_surface_model	230
wbt_lidar_elevation_slice	231
wbt_lidar_ground_point_filter	232
wbt_lidar_hex_binning	233
wbt_lidar_hillshade	234
wbt_lidar_histogram	235
wbt_lidar_idw_interpolation	236
wbt_lidar_info	237
wbt_lidar_join	238
wbt_lidar_kappa_index	239
wbt_lidar_nearest_neighbour_gridding	240
wbt_lidar_point_density	241
wbt_lidar_point_return_analysis	242
wbt_lidar_point_stats	243
wbt_lidar_ransac_planes	244
wbt_lidar_rbf_interpolation	245
wbt_lidar_remove_duplicates	246
wbt_lidar_remove_outliers	247
wbt_lidar_rooftop_analysis	248
wbt_lidar_segmentation	250
wbt_lidar_segmentation_based_filter	251
wbt_lidar_shift	252
wbt_lidar_sibson_interpolation	253
wbt_lidar_sort_by_time	254
wbt_lidar_thin	255
wbt_lidar_thin_high_density	256
wbt_lidar_tile	257
wbt_lidar_tile_footprint	258
wbt_lidar_tin_gridding	259
wbt_lidar_tophat_transform	260
wbt_linearity_index	261
wbt_lines_to_polygons	261
wbt_line_detection_filter	262
wbt_line_intersections	263
wbt_line_thinning	264
wbt_list_tools	265
wbt_list_unique_values	265
wbt_ln	266
wbt_local_hypsometric_analysis	267
wbt_local_quadratic_regression	268
wbt_log10	269
wbt_log2	269
wbt_logistic_regression	270
wbt_longest_flowpath	271
wbt_long_profile	272

wbt_long_profile_from_points	273
wbt_lowest_position	274
wbt_low_points_on_headwater_divides	275
wbt_majority_filter	276
wbt_map_off_terrain_objects	277
wbt_max	278
wbt_maximal_curvature	279
wbt_maximum_filter	280
wbt_max_absolute_overlay	281
wbt_max_anisotropy_dev	281
wbt_max_anisotropy_dev_signature	282
wbt_max_branch_length	283
wbt_max_difference_from_mean	284
wbt_max_downslope_elev_change	285
wbt_max_elevation_deviation	286
wbt_max_elev_dev_signature	287
wbt_max_overlay	288
wbt_max_upslope_elev_change	289
wbt_max_upslope_flowpath_length	289
wbt_md_inf_flow_accumulation	290
wbt_mean_curvature	291
wbt_mean_filter	292
wbt_median_filter	293
wbt_medoid	294
wbt_merge_line_segments	295
wbt_merge_table_with_csv	296
wbt_merge_vectors	297
wbt_min	297
wbt_minimal_curvature	298
wbt_minimum_bounding_box	299
wbt_minimum_bounding_circle	300
wbt_minimum_bounding_envelope	301
wbt_minimum_convex_hull	302
wbt_minimum_filter	303
wbt_min_absolute_overlay	304
wbt_min_dist_classification	304
wbt_min_downslope_elev_change	305
wbt_min_max_contrast_stretch	306
wbt_min_overlay	307
wbt_modified_k_means_clustering	308
wbt_modify_no_data_value	309
wbt_modulo	310
wbt_mosaic	311
wbt_mosaic_with_feathering	312
wbt_multidirectional_hillshade	313
wbt_multiply	314
wbt_multiscale_elevation_percentile	315
wbt_multiscale_roughness	316

wbt_multiscale_roughness_signature	317
wbt_multiscale_std_dev_normals	318
wbt_multiscale_std_dev_normals_signature	319
wbt_multiscale_topographic_position_image	320
wbt_multi_part_to_single_part	321
wbt_narrowness_index	322
wbt_natural_neighbour_interpolation	322
wbt_nearest_neighbour_gridding	323
wbt_negate	324
wbt_new_raster_from_base	325
wbt_normalized_difference_index	326
wbt_normal_vectors	327
wbt_not	328
wbt_not_equal_to	329
wbt_num_downslope_neighbours	330
wbt_num_inflowing_neighbours	330
wbt_num_upslope_neighbours	331
wbt_olympic_filter	332
wbt_opening	333
wbt_openness	334
wbt_or	335
wbt_paired_sample_t_test	336
wbt_panchromatic_sharpening	337
wbt_parallelepiped_classification	338
wbt_patch_orientation	339
wbt_pennock_landform_class	339
wbt_percentage_contrast_stretch	340
wbt_percentile_filter	341
wbt_percent_elev_range	342
wbt_percent_equal_to	343
wbt_percent_greater_than	344
wbt_percent_less_than	345
wbt_perimeter_area_ratio	346
wbt_phi_coefficient	347
wbt_pick_from_list	348
wbt_plan_curvature	349
wbt_polygonize	350
wbt_polygons_to_lines	350
wbt_polygon_area	351
wbt_polygon_long_axis	352
wbt_polygon_perimeter	353
wbt_polygon_short_axis	353
wbt_power	354
wbt_prewitt_filter	355
wbt_principal_component_analysis	356
wbt_print_geo_tiff_tags	357
wbt_profile	357
wbt_profile_curvature	358

wbt_qin_flow_accumulation	359
wbt_quantiles	360
wbt_quinn_flow_accumulation	361
wbt_radial_basis_function_interpolation	362
wbt_radius_of_gyration	363
wbt_raise_walls	364
wbt_random_field	365
wbt_random_forest_classification	366
wbt_random_forest_regression	367
wbt_random_sample	368
wbt_range_filter	369
wbt_rasterize_streams	370
wbt_raster_area	371
wbt_raster_calculator	372
wbt_raster_cell_assignment	373
wbt_raster_histogram	374
wbt_raster_perimeter	375
wbt_raster_streams_to_vector	376
wbt_raster_summary_stats	377
wbt_raster_to_vector_lines	377
wbt_raster_to_vector_points	378
wbt_raster_to_vector_polygons	379
wbt_reciprocal	380
wbt_reclass	381
wbt_reclass_equal_interval	382
wbt_reclass_from_file	383
wbt_reconcile_multiple_headers	384
wbt_recreate_pass_lines	385
wbt_reinitialize_attribute_table	386
wbt_related_circumscribing_circle	387
wbt_relative_aspect	387
wbt_relative_topographic_position	388
wbt_remove_field_edge_points	389
wbt_remove_off_terrain_objects	390
wbt_remove_polygon_holes	391
wbt_remove_short_streams	392
wbt_remove_spurs	393
wbt_repair_stream_vector_topology	394
wbt_resample	395
wbt_rescale_value_range	396
wbt_rgb_to_ihs	397
wbt_rho8_flow_accumulation	398
wbt_rho8_pointer	399
wbt_ring_curvature	400
wbt_roberts_cross_filter	401
wbt_root_mean_square_error	402
wbt_rotor	402
wbt_round	403

wbt_ruggedness_index	404
wbt_run_tool	405
wbt_scharr_filter	406
wbt_sediment_transport_index	407
wbt_select_tiles_by_polygon	408
wbt_set_nodata_value	409
wbt_shadow_animation	410
wbt_shadow_image	411
wbt_shape_complexity_index	412
wbt_shape_complexity_index_raster	413
wbt_shape_index	413
wbt_shreve_stream_magnitude	414
wbt_sigmoidal_contrast_stretch	415
wbt_sin	416
wbt_single_part_to_multi_part	417
wbt_sinh	418
wbt_sink	418
wbt_slope	419
wbt_slope_vs_aspect_plot	420
wbt_slope_vs_elevation_plot	421
wbt_smooth_vectors	422
wbt_smooth_vegetation_residual	423
wbt_snap_pour_points	424
wbt_sobel_filter	425
wbt_spherical_std_dev_of_normals	426
wbt_split_colour_composite	427
wbt_split_vector_lines	428
wbt_split_with_lines	429
wbt_square	430
wbt_square_root	430
wbt_standard_deviation_contrast_stretch	431
wbt_standard_deviation_filter	432
wbt_standard_deviation_of_slope	433
wbt_stochastic_depression_analysis	434
wbt_strahler_order_basins	435
wbt_strahler_stream_order	436
wbt_stream_link_class	437
wbt_stream_link_identifier	438
wbt_stream_link_length	439
wbt_stream_link_slope	440
wbt_stream_power_index	441
wbt_stream_slope_continuous	442
wbt_subbasins	443
wbt_subtract	444
wbt_sum_overlay	445
wbt_surface_area_ratio	445
wbt_svm_classification	446
wbt_svm_regression	447

wbt_symmetrical_difference	449
wbt_tan	450
wbt_tangential_curvature	450
wbt_tanh	451
wbt_thicken_raster_line	452
wbt_time_in_daylight	453
wbt_tin_gridding	454
wbt_toolbox	455
wbt_tool_help	456
wbt_tool_parameters	456
wbt_tophat_transform	457
wbt_topographic_position_animation	458
wbt_topological_stream_order	459
wbt_total_curvature	460
wbt_total_filter	461
wbt_to_degrees	462
wbt_to_radians	462
wbt_trace_downslope_flowpaths	463
wbt_trend_surface	464
wbt_trend_surface_vector_points	465
wbt_tributary_identifier	466
wbt_truncate	467
wbt_turning_bands_simulation	468
wbt_two_sample_ks_test	469
wbt_union	470
wbt_unnest_basins	471
wbt_unsharp_masking	472
wbt_unsphericity	473
wbt_update_nodata_cells	474
wbt_upslope_depression_storage	475
wbt_user_defined_weights_filter	475
wbt_vector_hex_binning	476
wbt_vector_lines_to_raster	477
wbt_vector_points_to_raster	478
wbt_vector_polygons_to_raster	479
wbt_vector_stream_network_analysis	480
wbt_version	481
wbt_vertical_excess_curvature	482
wbt_viewshed	483
wbt_view_code	484
wbt_visibility_index	484
wbt_voronoi_diagram	485
wbt_watershed	486
wbt_weighted_overlay	487
wbt_weighted_sum	488
wbt_wetness_index	489
wbt_wilcoxon_signed_rank_test	490
wbt_write_function_memory_insertion	491

wbt_xor	492
wbt_yield_filter	493
wbt_yield_map	494
wbt_yield_normalization	495
wbt_zlidar_to_las	496
wbt_zonal_statistics	496
wbt_z_scores	497

Index **499**

check_whitebox_binary *Check for WhiteboxTools executable path*

Description

Check for WhiteboxTools executable path

Usage

```
check_whitebox_binary(silent = TRUE)
```

Arguments

silent logical. Print help on installation/setting path. Default TRUE.

Value

logical if WhiteboxTools executable file exists.

See Also

[wbt_exe_path\(\)](#)

sample_dem_data *Convenience method for path to sample DEM*

Description

Get a file path to DEM.tif stored in extdata subfolder of whitebox package installation directory. If needed, download the TIFF file from GitHub.

Usage

```
sample_dem_data(
  destfile = file.path(system.file("extdata", package = "whitebox"), "DEM.tif"),
  ...
)
```

Arguments

destfile Path to target location of sample data. Will be downloaded if does not exist. Defaults to file path of extdata subfolder of whitebox package installation directory.

... additional arguments to download.file()

Value

character.

Examples

```
if (check_whitebox_binary()) {
  wbt_slope(sample_dem_data(), output = "slope.tif")
}
unlink(c('slope.tif', 'settings.json'))
```

wbttoolparameters

WhiteboxTools Tool Parameters

Description

This data set is a data.frame containing tool parameters and associated metadata

Usage

```
wbttoolparameters
```

Format

A data.frame with 2082 observations of 13 variables

- "function_name" - R function name
- "tool_name" - WhiteboxTools tool name
- "name" - parameter name
- "flags" - flags used to specify parameter on command line; comma separated
- "description" - parameter description
- "parameter_class" - parameter type
- "parameter_detail" - parameter details; character: data type followed by colon and more specifics, For OptionList possible values, comma-separated (if defined)
- "default_value" - parameter default value, if any
- "optional" - parameter "optional" flag; note that some combination of optional parameters may be required for certain conditions

- "label" - labels for selected subset of "flags" **used as R function argument names** for wbt_ functions
- "is_input" - logical. Classification of 'input' parameters
- "is_output" - logical. Classification of 'output' parameters

Source

[WhiteboxTools](#)

See Also

[wbtttools wbt_tool_parameters\(\)](#)

wbtttools

WhiteboxTools Tool List

Description

This data set is a data.frame containing tools by name and associated R function name

Usage

wbtttools

Format

A data.frame with 518 observations of 7 variables

- "tool_name" - WhiteboxTools tool name
- "function_name" - R function name
- "toolbox_name" - WhiteboxTools toolbox name
- "label" - WhiteboxTools tool label
- "description" - Brief description
- "github" - Link to related code on GitHub
- "book" - Link to WhiteboxTools Manual

Source

[WhiteboxTools](#)

See Also

[wbtttoolparameters wbt_list_tools\(\)](#)

wbt_absolute_value *Absolute value*

Description

Calculates the absolute value of every cell in a raster.

Usage

```
wbt_absolute_value(  
    input,  
    output,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

input	Input raster file.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_accumulation_curvature
Accumulation curvature

Description

This tool calculates accumulation curvature from an input DEM.

Usage

```
wbt_accumulation_curvature(
    dem,
    output,
    log = FALSE,
    zfactor = 1,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

dem	Name of the input raster DEM file.
output	Name of the output raster image file.
log	Display output values using a log-scale.
zfactor	Z conversion factor.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_adaptive_filter *Adaptive filter*

Description

Performs an adaptive filter on an image.

Usage

```
wbt_adaptive_filter(
    input,
    output,
    filterx = 11,
    filtery = 11,
    threshold = 2,
```

```

    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)

```

Arguments

input	Input raster file.
output	Output raster file.
filterx	Size of the filter kernel in the x-direction.
filtery	Size of the filter kernel in the y-direction.
threshold	Difference from mean threshold, in standard deviations.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by <code>system()</code> rather than running tool.

Value

Returns the tool text outputs.

wbt_add

Add

Description

Performs an addition operation on two rasters or a raster and a constant value.

Usage

```

wbt_add(
  input1,
  input2,
  output,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)

```

Arguments

input1	Input raster file or constant value.
input2	Input raster file or constant value.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_add_point_coordinates_to_table
Add point coordinates to table

Description

Modifies the attribute table of a point vector by adding fields containing each point's X and Y coordinates.

Usage

```
wbt_add_point_coordinates_to_table(  
  input,  
  wd = NULL,  
  verbose_mode = FALSE,  
  compress_rasters = FALSE,  
  command_only = FALSE  
)
```

Arguments

input	Input vector Points file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_aggregate_raster *Aggregate raster*

Description

Aggregates a raster to a lower resolution.

Usage

```
wbt_aggregate_raster(
    input,
    output,
    agg_factor = 2,
    type = "mean",
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input	Input raster file.
output	Output raster file.
agg_factor	Aggregation factor, in pixels.
type	Statistic used to fill output pixels.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_and	<i>And</i>
---------	------------

Description

Performs a logical AND operator on two Boolean raster images.

Usage

```
wbt_and(  
    input1,  
    input2,  
    output,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

input1	Input raster file.
input2	Input raster file.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_anova	<i>Anova</i>
-----------	--------------

Description

Performs an analysis of variance (ANOVA) test on a raster dataset.

Usage

```
wbt_anova(  
    input,  
    features,  
    output,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

input	Input raster file.
features	Feature definition (or class) raster.
output	Output HTML file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by <code>system()</code> rather than running tool.

Value

Returns the tool text outputs.

wbt_arcosh	<i>Arcosh</i>
------------	---------------

Description

Returns the inverse hyperbolic cosine (arcosh) of each values in a raster.

Usage

```
wbt_arcosh(
    input,
    output,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input	Input raster file.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_arc_cos	<i>Arc cos</i>
-------------	----------------

Description

Returns the inverse cosine (arccos) of each values in a raster.

Usage

```
wbt_arc_cos(
    input,
    output,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input	Input raster file.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_arc_sin	<i>Arc sin</i>
-------------	----------------

Description

Returns the inverse sine (arcsin) of each values in a raster.

Usage

```
wbt_arc_sin(
    input,
    output,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```


Arguments

input	Input raster file.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_arc_tan	<i>Arc tan</i>
-------------	----------------

Description

Returns the inverse tangent (arctan) of each values in a raster.

Usage

```
wbt_arc_tan(
  input,
  output,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

input	Input raster file.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_arsinh	<i>Arsinh</i>
------------	---------------

Description

Returns the inverse hyperbolic sine (arsinh) of each values in a raster.

Usage

```
wbt_arsinh(
  input,
  output,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

input	Input raster file.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_artanh	<i>Artanh</i>
------------	---------------

Description

Returns the inverse hyperbolic tangent (arctanh) of each values in a raster.

Usage

```
wbt_artanh(
  input,
  output,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

input	Input raster file.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_ascii_to_las	<i>Ascii to las</i>
------------------	---------------------

Description

Converts one or more ASCII files containing LiDAR points into LAS files.

Usage

```
wbt_ascii_to_las(
    inputs,
    pattern,
    proj = NULL,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

inputs	Input LiDAR ASCII files (.csv).
pattern	Input field pattern.
proj	Well-known-text string or EPSG code describing projection.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_aspect	<i>Aspect</i>
------------	---------------

Description

Calculates an aspect raster from an input DEM.

Usage

```
wbt_aspect(
    dem,
    output,
    zfactor = NULL,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

dem	Input raster DEM file.
output	Output raster file.
zfactor	Optional multiplier for when the vertical and horizontal units are not the same.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_assess_route	<i>Assess route</i>
------------------	---------------------

Description

This tool assesses a route for slope, elevation, and visibility variation.

Usage

```
wbt_assess_route(
  routes,
  dem,
  output,
  length = "",
  dist = 20,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

routes	Name of the input routes vector file.
dem	Name of the input DEM raster file.
output	Name of the output lines shapefile.
length	Maximum segment length (m).
dist	Search distance, in grid cells, used in visibility analysis.

wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_atan2	<i>Atan2</i>
-----------	--------------

Description

Returns the 2-argument inverse tangent (atan2).

Usage

```
wbt_atan2(
  input_y,
  input_x,
  output,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

input_y	Input y raster file or constant value (rise).
input_x	Input x raster file or constant value (run).
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_attribute_correlation
Attribute correlation

Description

Performs a correlation analysis on attribute fields from a vector database.

Usage

```
wbt_attribute_correlation(  
    input,  
    output = NULL,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

input	Input vector file.
output	Output HTML file (default name will be based on input file if unspecified).
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_attribute_correlation_neighbourhood_analysis
Attribute correlation neighbourhood analysis

Description

Performs a correlation on two input vector attributes within a neighbourhood search windows.

Usage

```
wbt_attribute_correlation_neighbourhood_analysis(
    input,
    field1,
    field2,
    radius = NULL,
    min_points = NULL,
    stat = "pearson",
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input	Input vector file.
field1	First input field name (dependent variable) in attribute table.
field2	Second input field name (independent variable) in attribute table.
radius	Search Radius (in map units).
min_points	Minimum number of points.
stat	Correlation type; one of 'pearson' (default) and 'spearman'.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_attribute_histogram

Attribute histogram

Description

Creates a histogram for the field values of a vector's attribute table.

Usage

```
wbt_attribute_histogram(
    input,
    field,
    output,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input	Input raster file.
field	Input field name in attribute table.
output	Output HTML file (default name will be based on input file if unspecified).
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_attribute_scattergram
Attribute scattergram

Description

Creates a scattergram for two field values of a vector's attribute table.

Usage

```
wbt_attribute_scattergram(
    input,
    fieldx,
    fieldy,
    output,
    trendline = FALSE,
    wd = NULL,
```

```

    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)

```

Arguments

input	Input raster file.
fieldx	Input field name in attribute table for the x-axis.
fieldy	Input field name in attribute table for the y-axis.
output	Output HTML file (default name will be based on input file if unspecified).
trendline	Draw the trendline.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

```

wbt_average_flowpath_slope
    Average flowpath slope

```

Description

Measures the average slope gradient from each grid cell to all upslope divide cells.

Usage

```

wbt_average_flowpath_slope(
  dem,
  output,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)

```

Arguments

dem	Input raster DEM file.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_average_normal_vector_angular_deviation
Average normal vector angular deviation

Description

Calculates the circular variance of aspect at a scale for a DEM.

Usage

```
wbt_average_normal_vector_angular_deviation(
  dem,
  output,
  filter = 11,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

dem	Input raster DEM file.
output	Output raster file.
filter	Size of the filter kernel.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_average_overlay	<i>Average overlay</i>
---------------------	------------------------

Description

Calculates the average for each grid cell from a group of raster images.

Usage

```
wbt_average_overlay(  
    inputs,  
    output,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

inputs	Input raster files.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_average_upslope_flowpath_length
Average upslope flowpath length

Description

Measures the average length of all upslope flowpaths draining each grid cell.

Usage

```
wbt_average_upslope_flowpath_length(
    dem,
    output,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

dem	Input raster DEM file.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_balance_contrast_enhancement
Balance contrast enhancement

Description

Performs a balance contrast enhancement on a colour-composite image of multispectral data.

Usage

```
wbt_balance_contrast_enhancement(
    input,
    output,
    band_mean = 100,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input	Input colour composite image file.
output	Output raster file.
band_mean	Band mean value.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_basins	<i>Basins</i>
------------	---------------

Description

Identifies drainage basins that drain to the DEM edge.

Usage

```
wbt_basins(
    d8_pntr,
    output,
    esri_pntr = FALSE,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

d8_pntr	Input raster D8 pointer file.
output	Output raster file.
esri_pntr	D8 pointer uses the ESRI style scheme.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_bilateral_filter *Bilateral filter*

Description

A bilateral filter is an edge-preserving smoothing filter introduced by Tomasi and Manduchi (1998).

Usage

```
wbt_bilateral_filter(  
  input,  
  output,  
  sigma_dist = 0.75,  
  sigma_int = 1,  
  wd = NULL,  
  verbose_mode = FALSE,  
  compress_rasters = FALSE,  
  command_only = FALSE  
)
```

Arguments

input	Input raster file.
output	Output raster file.
sigma_dist	Standard deviation in distance in pixels.
sigma_int	Standard deviation in intensity in pixels.
wd	Changes the working directory.

<code>verbose_mode</code>	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
<code>compress_rasters</code>	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
<code>command_only</code>	Return command that would be executed by <code>system()</code> rather than running tool.

Value

Returns the tool text outputs.

`wbt_block_maximum_gridding`
Block maximum gridding

Description

Creates a raster grid based on a set of vector points and assigns grid values using a block maximum scheme.

Usage

```
wbt_block_maximum_gridding(  
  input,  
  field,  
  output,  
  use_z = FALSE,  
  cell_size = NULL,  
  base = NULL,  
  wd = NULL,  
  verbose_mode = FALSE,  
  compress_rasters = FALSE,  
  command_only = FALSE  
)
```

Arguments

<code>input</code>	Input vector Points file.
<code>field</code>	Input field name in attribute table.
<code>output</code>	Output raster file.
<code>use_z</code>	Use z-coordinate instead of field?.
<code>cell_size</code>	Optionally specified cell size of output raster. Not used when base raster is specified.
<code>base</code>	Optionally specified input base raster file. Not used when a cell size is specified.
<code>wd</code>	Changes the working directory.

verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_block_minimum_gridding
Block minimum gridding

Description

Creates a raster grid based on a set of vector points and assigns grid values using a block minimum scheme.

Usage

```
wbt_block_minimum_gridding(
  input,
  field,
  output,
  use_z = FALSE,
  cell_size = NULL,
  base = NULL,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

input	Input vector Points file.
field	Input field name in attribute table.
output	Output raster file.
use_z	Use z-coordinate instead of field?.
cell_size	Optionally specified cell size of output raster. Not used when base raster is specified.
base	Optionally specified input base raster file. Not used when a cell size is specified.
wd	Changes the working directory.

<code>verbose_mode</code>	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
<code>compress_rasters</code>	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
<code>command_only</code>	Return command that would be executed by <code>system()</code> rather than running tool.

Value

Returns the tool text outputs.

`wbt_boundary_shape_complexity`
Boundary shape complexity

Description

Calculates the complexity of the boundaries of raster polygons.

Usage

```
wbt_boundary_shape_complexity(
  input,
  output,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

<code>input</code>	Input raster file.
<code>output</code>	Output raster file.
<code>wd</code>	Changes the working directory.
<code>verbose_mode</code>	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
<code>compress_rasters</code>	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
<code>command_only</code>	Return command that would be executed by <code>system()</code> rather than running tool.

Value

Returns the tool text outputs.

wbt_breach_depressions
Breach depressions

Description

Breaches all of the depressions in a DEM using Lindsay's (2016) algorithm. This should be preferred over depression filling in most cases.

Usage

```
wbt_breach_depressions(  
  dem,  
  output,  
  max_depth = NULL,  
  max_length = NULL,  
  flat_increment = NULL,  
  fill_pits = FALSE,  
  wd = NULL,  
  verbose_mode = FALSE,  
  compress_rasters = FALSE,  
  command_only = FALSE  
)
```

Arguments

dem	Input raster DEM file.
output	Output raster file.
max_depth	Optional maximum breach depth (default is Inf).
max_length	Optional maximum breach channel length (in grid cells; default is Inf).
flat_increment	Optional elevation increment applied to flat areas.
fill_pits	Optional flag indicating whether to fill single-cell pits.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_breach_depressions_least_cost
Breach depressions least cost

Description

Breaches the depressions in a DEM using a least-cost pathway method.

Usage

```
wbt_breach_depressions_least_cost(
    dem,
    output,
    dist,
    max_cost = NULL,
    min_dist = TRUE,
    flat_increment = NULL,
    fill = TRUE,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

dem	Input raster DEM file.
output	Output raster file.
dist	Maximum search distance for breach paths in cells.
max_cost	Optional maximum breach cost (default is Inf).
min_dist	Optional flag indicating whether to minimize breach distances.
flat_increment	Optional elevation increment applied to flat areas.
fill	Optional flag indicating whether to fill any remaining unbreached depressions.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_breach_single_cell_pits
Breach single cell pits

Description

Removes single-cell pits from an input DEM by breaching.

Usage

```
wbt_breach_single_cell_pits(  
    dem,  
    output,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

dem	Input raster DEM file.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_buffer_raster *Buffer raster*

Description

Maps a distance-based buffer around each non-background (non-zero/non-nodata) grid cell in an input image.

Usage

```
wbt_buffer_raster(
    input,
    output,
    size,
    gridcells = FALSE,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input	Input raster file.
output	Output raster file.
size	Buffer size.
gridcells	Optional flag to indicate that the 'size' threshold should be measured in grid cells instead of the default map units.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_burn_streams_at_roads

Burn streams at roads

Description

Burns-in streams at the sites of road embankments.

Usage

```
wbt_burn_streams_at_roads(
    dem,
    streams,
    roads,
    output,
    width = NULL,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

dem	Input raster digital elevation model (DEM) file.
streams	Input vector streams file.
roads	Input vector roads file.
output	Output raster file.
width	Maximum road embankment width, in map units.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_canny_edge_detection

Canny edge detection

Description

This tool performs a Canny edge-detection filter on an input image.

Usage

```
wbt_canny_edge_detection(
    input,
    output,
    sigma = 0.5,
    low = 0.05,
    high = 0.15,
    add_back = FALSE,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input	Name of the input raster image file.
output	Name of the output raster image file.
sigma	Sigma value used in Gaussian filtering, default = 0.5.
low	Low threshold, default = 0.05.
high	High threshold, default = 0.15.
add_back	Add the edge cells back to the input image.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_ceil

Ceil

Description

Returns the smallest (closest to negative infinity) value that is greater than or equal to the values in a raster.

Usage

```
wbt_ceil(
    input,
    output,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input	Input raster file.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_centroid	<i>Centroid</i>
--------------	-----------------

Description

Calculates the centroid, or average location, of raster polygon objects.

Usage

```
wbt_centroid(
    input,
    output,
    text_output = FALSE,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input	Input raster file.
output	Output raster file.
text_output	Optional text output.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_centroid_vector *Centroid vector*

Description

Identifies the centroid point of a vector polyline or polygon feature or a group of vector points.

Usage

```
wbt_centroid_vector(
  input,
  output,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

input	Input vector file.
output	Output vector file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_change_vector_analysis
Change vector analysis

Description

Performs a change vector analysis on a two-date multi-spectral dataset.

Usage

```
wbt_change_vector_analysis(  
    date1,  
    date2,  
    magnitude,  
    direction,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

date1	Input raster files for the earlier date.
date2	Input raster files for the later date.
magnitude	Output vector magnitude raster file.
direction	Output vector Direction raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_circular_variance_of_aspect
Circular variance of aspect

Description

Calculates the circular variance of aspect at a scale for a DEM.

Usage

```
wbt_circular_variance_of_aspect(  
    dem,  
    output,  
    filter = 11,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

dem	Input raster DEM file.
output	Output raster file.
filter	Size of the filter kernel.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_classify_buildings_in_lidar
Classify buildings in lidar

Description

Reclassifies a LiDAR points that lie within vector building footprints.

Usage

```
wbt_classify_buildings_in_lidar(  
    input,  
    buildings,  
    output,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

input	Input LiDAR file.
buildings	Input vector polygons file.
output	Output LiDAR file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_classify_overlap_points
Classify overlap points

Description

Classifies or filters LAS points in regions of overlapping flight lines.

Usage

```
wbt_classify_overlap_points(  
    input,  
    output,  
    resolution = 2,  
    filter = FALSE,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

input	Input LiDAR file.
output	Output LiDAR file.
resolution	The size of the square area used to evaluate nearby points in the LiDAR data.
filter	Filter out points from overlapping flightlines? If false, overlaps will simply be classified.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_clean_vector	<i>Clean vector</i>
------------------	---------------------

Description

Removes null features and lines/polygons with fewer than the required number of vertices.

Usage

```
wbt_clean_vector(  
    input,  
    output,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

input	Input vector file.
output	Output vector file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_clip	<i>Clip</i>
----------	-------------

Description

Extract all the features, or parts of features, that overlap with the features of the clip vector.

Usage

```
wbt_clip(
    input,
    clip,
    output,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input	Input vector file.
clip	Input clip polygon vector file.
output	Output vector file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

```
wbt_clip_lidar_to_polygon
    Clip lidar to polygon
```

Description

Clips a LiDAR point cloud to a vector polygon or polygons.

Usage

```
wbt_clip_lidar_to_polygon(
    input,
    polygons,
    output,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```


Arguments

input	Input LiDAR file.
polygons	Input vector polygons file.
output	Output LiDAR file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_clip_raster_to_polygon
Clip raster to polygon

Description

Clips a raster to a vector polygon.

Usage

```
wbt_clip_raster_to_polygon(
  input,
  polygons,
  output,
  maintain_dimensions = FALSE,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

input	Input raster file.
polygons	Input vector polygons file.
output	Output raster file.
maintain_dimensions	Maintain input raster dimensions?.

wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_closing	<i>Closing</i>
-------------	----------------

Description

A closing is a mathematical morphology operation involving an erosion (min filter) of a dilation (max filter) set.

Usage

```
wbt_closing(
  input,
  output,
  filterx = 11,
  filtery = 11,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

input	Input raster file.
output	Output raster file.
filterx	Size of the filter kernel in the x-direction.
filtery	Size of the filter kernel in the y-direction.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_clump

Clump

Description

Groups cells that form discrete areas, assigning them unique identifiers.

Usage

```
wbt_clump(
    input,
    output,
    diag = TRUE,
    zero_back = FALSE,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input	Input raster file.
output	Output raster file.
diag	Flag indicating whether diagonal connections should be considered.
zero_back	Flag indicating whether zero values should be treated as a background.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_compactness_ratio *Compactness ratio*

Description

Calculates the compactness ratio (A/P), a measure of shape complexity, for vector polygons.

Usage

```
wbt_compactness_ratio(  
    input,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

input	Input vector polygon file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by <code>system()</code> rather than running tool.

Value

Returns the tool text outputs.

wbt_conditional_evaluation
Conditional evaluation

Description

This tool performs a conditional evaluation (if-then-else) operation on a raster.

Usage

```
wbt_conditional_evaluation(
    input,
    output,
    statement = "",
    true = NULL,
    false = NULL,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input	Name of the input raster file.
output	Name of the output raster file.
statement	Conditional statement e.g. value > 35.0. This statement must be a valid Rust statement.
true	Value where condition evaluates TRUE (input raster or constant value).
false	Value where condition evaluates FALSE (input raster or constant value).
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_conservative_smoothing_filter
Conservative smoothing filter

Description

Performs a conservative-smoothing filter on an image.

Usage

```
wbt_conservative_smoothing_filter(
    input,
    output,
    filterx = 3,
    filtery = 3,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input	Input raster file.
output	Output raster file.
filterx	Size of the filter kernel in the x-direction.
filtery	Size of the filter kernel in the y-direction.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_construct_vector_tin

Construct vector tin

Description

Creates a vector triangular irregular network (TIN) for a set of vector points.

Usage

```
wbt_construct_vector_tin(
    input,
    output,
    field = NULL,
    use_z = FALSE,
```

```

    max_triangle_edge_length = NULL,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)

```

Arguments

input	Input vector points file.
output	Output vector polygon file.
field	Input field name in attribute table.
use_z	Use the 'z' dimension of the Shapefile's geometry instead of an attribute field?.
max_triangle_edge_length	Optional maximum triangle edge length; triangles larger than this size will not be gridded.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

```

wbt_contours_from_points
    Contours from points

```

Description

Creates a contour coverage from a set of input points.

Usage

```

wbt_contours_from_points(
  input,
  output,
  field = NULL,
  use_z = FALSE,
  max_triangle_edge_length = NULL,
  interval = 10,

```

```

base = 0,
smooth = 5,
wd = NULL,
verbose_mode = FALSE,
compress_rasters = FALSE,
command_only = FALSE
)

```

Arguments

input	Input vector points file.
output	Output vector lines file.
field	Input field name in attribute table.
use_z	Use the 'z' dimension of the Shapefile's geometry instead of an attribute field?.
max_triangle_edge_length	Optional maximum triangle edge length; triangles larger than this size will not be gridded.
interval	Contour interval.
base	Base contour height.
smooth	Smoothing filter size (in num. points), e.g. 3, 5, 7, 9, 11.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_contours_from_raster
Contours from raster

Description

Derives a vector contour coverage from a raster surface.

Usage

```
wbt_contours_from_raster(
    input,
    output,
    interval = 10,
    base = 0,
    smooth = 9,
    tolerance = 10,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input	Input surface raster file.
output	Output vector contour file.
interval	Contour interval.
base	Base contour height.
smooth	Smoothing filter size (in num. points), e.g. 3, 5, 7, 9, 11.
tolerance	Tolerance factor, in degrees (0-45); determines generalization level.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_convert_nodata_to_zero

Convert nodata to zero

Description

Converts nodata values in a raster to zero.

Usage

```
wbt_convert_nodata_to_zero(
    input,
    output,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input	Input raster file.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

```
wbt_convert_raster_format
    Convert raster format
```

Description

Converts raster data from one format to another.

Usage

```
wbt_convert_raster_format(
    input,
    output,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input	Input raster file.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_corner_detection *Corner detection*

Description

Identifies corner patterns in boolean images using hit-and-miss pattern matching.

Usage

```
wbt_corner_detection(
  input,
  output,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

input	Input boolean image.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

```
wbt_correct_vignetting
    Correct vignetting
```

Description

Corrects the darkening of images towards corners.

Usage

```
wbt_correct_vignetting(
    input,
    pp,
    output,
    focal_length = 304.8,
    image_width = 228.6,
    n = 4,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input	Input raster file.
pp	Input principal point file.
output	Output raster file.
focal_length	Camera focal length, in millimeters.
image_width	Distance between photograph edges, in millimeters.
n	The 'n' parameter.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_cos	<i>Cos</i>
---------	------------

Description

Returns the cosine (cos) of each values in a raster.

Usage

```
wbt_cos(
    input,
    output,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input	Input raster file.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_cosh	<i>Cosh</i>
----------	-------------

Description

Returns the hyperbolic cosine (cosh) of each values in a raster.

Usage

```
wbt_cosh(
  input,
  output,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

input	Input raster file.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by <code>system()</code> rather than running tool.

Value

Returns the tool text outputs.

wbt_cost_allocation *Cost allocation*

Description

Identifies the source cell to which each grid cell is connected by a least-cost pathway in a cost-distance analysis.

Usage

```
wbt_cost_allocation(
  source,
  backlink,
  output,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

source	Input source raster file.
backlink	Input backlink raster file generated by the cost-distance tool.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_cost_distance	<i>Cost distance</i>
-------------------	----------------------

Description

Performs cost-distance accumulation on a cost surface and a group of source cells.

Usage

```
wbt_cost_distance(
  source,
  cost,
  out_accum,
  out_backlink,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

source	Input source raster file.
cost	Input cost (friction) raster file.
out_accum	Output cost accumulation raster file.
out_backlink	Output backlink raster file.
wd	Changes the working directory.

verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_cost_pathway	<i>Cost pathway</i>
------------------	---------------------

Description

Performs cost-distance pathway analysis using a series of destination grid cells.

Usage

```
wbt_cost_pathway(
  destination,
  backlink,
  output,
  zero_background = FALSE,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

destination	Input destination raster file.
backlink	Input backlink raster file generated by the cost-distance tool.
output	Output cost pathway raster file.
zero_background	Flag indicating whether zero values should be treated as a background.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_count_if	<i>Count if</i>
--------------	-----------------

Description

Counts the number of occurrences of a specified value in a cell-stack of rasters.

Usage

```
wbt_count_if(
  inputs,
  output,
  value,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

inputs	Input raster files.
output	Output raster file.
value	Search value (e.g. countif value = 5.0).
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_create_colour_composite
Create colour composite

Description

Creates a colour-composite image from three bands of multispectral imagery.

Usage

```
wbt_create_colour_composite(
    red,
    green,
    blue,
    output,
    opacity = NULL,
    enhance = TRUE,
    zeros = FALSE,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

red	Input red band image file.
green	Input green band image file.
blue	Input blue band image file.
output	Output colour composite file.
opacity	Input opacity band image file (optional).
enhance	Optional flag indicating whether a balance contrast enhancement is performed.
zeros	Optional flag to indicate if zeros are nodata values.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

`wbt_create_hexagonal_vector_grid`*Create hexagonal vector grid*

Description

Creates a hexagonal vector grid.

Usage

```
wbt_create_hexagonal_vector_grid(  
    input,  
    output,  
    width,  
    orientation = "horizontal",  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

<code>input</code>	Input base file.
<code>output</code>	Output vector polygon file.
<code>width</code>	The grid cell width.
<code>orientation</code>	Grid Orientation, 'horizontal' or 'vertical'.
<code>wd</code>	Changes the working directory.
<code>verbose_mode</code>	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
<code>compress_rasters</code>	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
<code>command_only</code>	Return command that would be executed by <code>system()</code> rather than running tool.

Value

Returns the tool text outputs.

wbt_create_plane *Create plane*

Description

Creates a raster image based on the equation for a simple plane.

Usage

```
wbt_create_plane(  
    base,  
    output,  
    gradient = 15,  
    aspect = 90,  
    constant = 0,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

base	Input base raster file.
output	Output raster file.
gradient	Slope gradient in degrees (-85.0 to 85.0).
aspect	Aspect (direction) in degrees clockwise from north (0.0-360.0).
constant	Constant value.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_create_rectangular_vector_grid
Create rectangular vector grid

Description

Creates a rectangular vector grid.

Usage

```
wbt_create_rectangular_vector_grid(  
    input,  
    output,  
    width,  
    height,  
    xorig = 0,  
    yorig = 0,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

input	Input base file.
output	Output vector polygon file.
width	The grid cell width.
height	The grid cell height.
xorig	The grid origin x-coordinate.
yorig	The grid origin y-coordinate.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_crispness_index *Crispness index*

Description

Calculates the Crispness Index, which is used to quantify how crisp (or conversely how fuzzy) a probability image is.

Usage

```
wbt_crispness_index(
    input,
    output = NULL,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input	Input raster file.
output	Optional output html file (default name will be based on input file if unspecified).
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_cross_tabulation *Cross tabulation*

Description

Performs a cross-tabulation on two categorical images.

Usage

```
wbt_cross_tabulation(
    input1,
    input2,
    output,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input1	Input raster file 1.
input2	Input raster file 1.
output	Output HTML file (default name will be based on input file if unspecified).
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_csv_points_to_vector

Csv points to vector

Description

Converts a CSV text file to vector points.

Usage

```
wbt_csv_points_to_vector(
    input,
    output,
    xfield = 0,
    yfield = 1,
    epsg = NULL,
    wd = NULL,
```

```

    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)

```

Arguments

input	Input CSV file (i.e. source of data to be imported).
output	Output vector file.
xfield	X field number (e.g. 0 for first field).
yfield	Y field number (e.g. 1 for second field).
epsg	EPSG projection (e.g. 2958).
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

```

wbt_cumulative_distribution
    Cumulative distribution

```

Description

Converts a raster image to its cumulative distribution function.

Usage

```

wbt_cumulative_distribution(
  input,
  output,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)

```


Arguments

input	Input raster file.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_curvedness	<i>Curvedness</i>
----------------	-------------------

Description

This tool calculates curvedness from an input DEM.

Usage

```
wbt_curvedness(
  dem,
  output,
  log = FALSE,
  zfactor = 1,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

dem	Name of the input raster DEM file.
output	Name of the output raster image file.
log	Display output values using a log-scale.
zfactor	Z conversion factor.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.

compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_d8_flow_accumulation
D8 flow accumulation

Description

Calculates a D8 flow accumulation raster from an input DEM or flow pointer.

Usage

```
wbt_d8_flow_accumulation(
  input,
  output,
  out_type = "cells",
  log = FALSE,
  clip = FALSE,
  pntr = FALSE,
  esri_pntr = FALSE,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

input	Input raster DEM or D8 pointer file.
output	Output raster file.
out_type	Output type; one of 'cells' (default), 'catchment area', and 'specific contributing area'.
log	Optional flag to request the output be log-transformed.
clip	Optional flag to request clipping the display max by 1 percent.
pntr	Is the input raster a D8 flow pointer rather than a DEM?.
esri_pntr	Input D8 pointer uses the ESRI style scheme.
wd	Changes the working directory.

verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_d8_mass_flux	<i>D8 mass flux</i>
------------------	---------------------

Description

Performs a D8 mass flux calculation.

Usage

```
wbt_d8_mass_flux(
  dem,
  loading,
  efficiency,
  absorption,
  output,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

dem	Input raster DEM file.
loading	Input loading raster file.
efficiency	Input efficiency raster file.
absorption	Input absorption raster file.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_d8_pointer	<i>D8 pointer</i>
----------------	-------------------

Description

Calculates a D8 flow pointer raster from an input DEM.

Usage

```
wbt_d8_pointer(
    dem,
    output,
    esri_pntr = FALSE,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

dem	Input raster DEM file.
output	Output raster file.
esri_pntr	D8 pointer uses the ESRI style scheme.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_dbscan
Dbscan

Description

Performs a DBSCAN-based unsupervised clustering operation.

Usage

```
wbt_dbscan(
    inputs,
    output,
    scaling = "Normalize",
    search_dist = 0.01,
    min_points = 5,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

inputs	Names of the input rasters.
output	Name of the output raster file.
scaling	Scaling method for predictors. Options include 'None', 'Normalize', and 'Standardize'.
search_dist	Search-distance parameter.
min_points	Minimum point density needed to define 'core' point in cluster.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_decrement	<i>Decrement</i>
---------------	------------------

Description

Decreases the values of each grid cell in an input raster by 1.0 (see also InPlaceSubtract).

Usage

```
wbt_decrement(
    input,
    output,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input	Input raster file.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_depth_in_sink	<i>Depth in sink</i>
-------------------	----------------------

Description

Measures the depth of sinks (depressions) in a DEM.

Usage

```
wbt_depth_in_sink(
    dem,
    output,
    zero_background = FALSE,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

dem	Input raster DEM file.
output	Output raster file.
zero_background	Flag indicating whether the background value of zero should be used.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_dev_from_mean_elev

Dev from mean elev

Description

Calculates deviation from mean elevation.

Usage

```
wbt_dev_from_mean_elev(
    dem,
    output,
    filterx = 11,
    filtery = 11,
    wd = NULL,
```

```

    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)

```

Arguments

dem	Input raster DEM file.
output	Output raster file.
filterx	Size of the filter kernel in the x-direction.
filtery	Size of the filter kernel in the y-direction.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_difference	<i>Difference</i>
----------------	-------------------

Description

Outputs the features that occur in one of the two vector inputs but not both, i.e. no overlapping features.

Usage

```

wbt_difference(
  input,
  overlay,
  output,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)

```


Arguments

input	Input vector file.
overlay	Input overlay vector file.
output	Output vector file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_difference_curvature
Difference curvature

Description

This tool calculates difference curvature from an input DEM.

Usage

```
wbt_difference_curvature(  
  dem,  
  output,  
  log = FALSE,  
  zfactor = 1,  
  wd = NULL,  
  verbose_mode = FALSE,  
  compress_rasters = FALSE,  
  command_only = FALSE  
)
```

Arguments

dem	Name of the input raster DEM file.
output	Name of the output raster image file.
log	Display output values using a log-scale.
zfactor	Z conversion factor.
wd	Changes the working directory.

verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

```
wbt_diff_from_mean_elev
    Diff from mean elev
```

Description

Calculates difference from mean elevation (equivalent to a high-pass filter).

Usage

```
wbt_diff_from_mean_elev(
    dem,
    output,
    filterx = 11,
    filtery = 11,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

dem	Input raster DEM file.
output	Output raster file.
filterx	Size of the filter kernel in the x-direction.
filtery	Size of the filter kernel in the y-direction.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

```
wbt_diff_of_gaussian_filter
    Diff of gaussian filter
```

Description

Performs a Difference of Gaussian (DoG) filter on an image.

Usage

```
wbt_diff_of_gaussian_filter(
    input,
    output,
    sigma1 = 2,
    sigma2 = 4,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input	Input raster file.
output	Output raster file.
sigma1	Standard deviation distance in pixels.
sigma2	Standard deviation distance in pixels.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

`wbt_directional_relief`*Directional relief*

Description

Calculates relief for cells in an input DEM for a specified direction.

Usage

```
wbt_directional_relief(  
    dem,  
    output,  
    azimuth = 0,  
    max_dist = NULL,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

<code>dem</code>	Input raster DEM file.
<code>output</code>	Output raster file.
<code>azimuth</code>	Wind azimuth in degrees.
<code>max_dist</code>	Optional maximum search distance (unspecified if none; in xy units).
<code>wd</code>	Changes the working directory.
<code>verbose_mode</code>	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
<code>compress_rasters</code>	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
<code>command_only</code>	Return command that would be executed by <code>system()</code> rather than running tool.

Value

Returns the tool text outputs.

wbt_direct_decorrelation_stretch
Direct decorrelation stretch

Description

Performs a direct decorrelation stretch enhancement on a colour-composite image of multispectral data.

Usage

```
wbt_direct_decorrelation_stretch(  
    input,  
    output,  
    k = 0.5,  
    clip = 1,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

input	Input colour composite image file.
output	Output raster file.
k	Achromatic factor (k) ranges between 0 (no effect) and 1 (full saturation stretch), although typical values range from 0.3 to 0.7.
clip	Optional percent to clip the upper tail by during the stretch.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_dissolve	<i>Dissolve</i>
--------------	-----------------

Description

Removes the interior, or shared, boundaries within a vector polygon coverage.

Usage

```
wbt_dissolve(  
    input,  
    output,  
    field = NULL,  
    snap = 0,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

input	Input vector file.
output	Output vector file.
field	Dissolve field attribute (optional).
snap	Snap tolerance.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_distance_to_outlet
Distance to outlet

Description

Calculates the distance of stream grid cells to the channel network outlet cell.

Usage

```
wbt_distance_to_outlet(  
    d8_pntr,  
    streams,  
    output,  
    esri_pntr = FALSE,  
    zero_background = FALSE,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

d8_pntr	Input raster D8 pointer file.
streams	Input raster streams file.
output	Output raster file.
esri_pntr	D8 pointer uses the ESRI style scheme.
zero_background	Flag indicating whether a background value of zero should be used.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_diversity_filter *Diversity filter*

Description

Assigns each cell in the output grid the number of different values in a moving window centred on each grid cell in the input raster.

Usage

```
wbt_diversity_filter(  
    input,  
    output,  
    filterx = 11,  
    filtery = 11,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

input	Input raster file.
output	Output raster file.
filterx	Size of the filter kernel in the x-direction.
filtery	Size of the filter kernel in the y-direction.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_divide	<i>Divide</i>
------------	---------------

Description

Performs a division operation on two rasters or a raster and a constant value.

Usage

```
wbt_divide(  
    input1,  
    input2,  
    output,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

input1	Input raster file or constant value.
input2	Input raster file or constant value.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by <code>system()</code> rather than running tool.

Value

Returns the tool text outputs.

wbt_downslope_distance_to_stream
Downslope distance to stream

Description

Measures distance to the nearest downslope stream cell.

Usage

```
wbt_downslope_distance_to_stream(  
    dem,  
    streams,  
    output,  
    dinf = FALSE,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

dem	Input raster DEM file.
streams	Input raster streams file.
output	Output raster file.
dinf	Use the D-infinity flow algorithm instead of D8?.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_downslope_flowpath_length
Downslope flowpath length

Description

Calculates the downslope flowpath length from each cell to basin outlet.

Usage

```
wbt_downslope_flowpath_length(  
    d8_pntr,  
    output,  
    watersheds = NULL,  
    weights = NULL,  
    esri_pntr = FALSE,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

d8_pntr	Input D8 pointer raster file.
output	Output raster file.
watersheds	Optional input watershed raster file.
weights	Optional input weights raster file.
esri_pntr	D8 pointer uses the ESRI style scheme.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_downslope_index *Downslope index*

Description

Calculates the Hjerdt et al. (2004) downslope index.

Usage

```
wbt_downslope_index(  
    dem,  
    output,  
    drop = 2,  
    out_type = "tangent",  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

dem	Input raster DEM file.
output	Output raster file.
drop	Vertical drop value (default is 2.0).
out_type	Output type, options include 'tangent', 'degrees', 'radians', 'distance' (default is 'tangent').
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

```
wbt_d_inf_flow_accumulation
    D inf flow accumulation
```

Description

Calculates a D-infinity flow accumulation raster from an input DEM.

Usage

```
wbt_d_inf_flow_accumulation(
    input,
    output,
    out_type = "Specific Contributing Area",
    threshold = NULL,
    log = FALSE,
    clip = FALSE,
    pntr = FALSE,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input	Input raster DEM or D-infinity pointer file.
output	Output raster file.
out_type	Output type; one of 'cells', 'sca' (default), and 'ca'.
threshold	Optional convergence threshold parameter, in grid cells; default is infinity.
log	Optional flag to request the output be log-transformed.
clip	Optional flag to request clipping the display max by 1 percent.
pntr	Is the input raster a D-infinity flow pointer rather than a DEM?.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_d_inf_mass_flux *D inf mass flux*

Description

Performs a D-infinity mass flux calculation.

Usage

```
wbt_d_inf_mass_flux(  
    dem,  
    loading,  
    efficiency,  
    absorption,  
    output,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

dem	Input raster DEM file.
loading	Input loading raster file.
efficiency	Input efficiency raster file.
absorption	Input absorption raster file.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_d_inf_pointer *D inf pointer*

Description

Calculates a D-infinity flow pointer (flow direction) raster from an input DEM.

Usage

```
wbt_d_inf_pointer(
    dem,
    output,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

dem	Input raster DEM file.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_edge_contamination *Edge contamination*

Description

This tool identifies grid cells within an input DEM that may be impacted by edge contamination for hydrological applications.

Usage

```
wbt_edge_contamination(
    dem,
    output,
    flow_type = "mfd",
    zfactor = "",
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

dem	Name of the input DEM raster file; must be depressionless.
output	Name of the output raster file.
flow_type	Flow algorithm type, one of 'd8', 'mfd', or 'dinf'.
zfactor	Optional multiplier for when the vertical and horizontal units are not the same.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_edge_density	<i>Edge density</i>
------------------	---------------------

Description

Calculates the density of edges, or breaks-in-slope within DEMs.

Usage

```
wbt_edge_density(
    dem,
    output,
    filter = 11,
    norm_diff = 5,
    zfactor = NULL,
```



```

    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)

```

Arguments

dem	Input raster DEM file.
output	Output raster file.
filter	Size of the filter kernel.
norm_diff	Maximum difference in normal vectors, in degrees.
zfactor	Optional multiplier for when the vertical and horizontal units are not the same.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

```

wbt_edge_preserving_mean_filter
    Edge preserving mean filter

```

Description

Performs a simple edge-preserving mean filter on an input image.

Usage

```

wbt_edge_preserving_mean_filter(
  input,
  output,
  threshold,
  filter = 11,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)

```

Arguments

input	Input raster file.
output	Output raster file.
threshold	Maximum difference in values.
filter	Size of the filter kernel.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_edge_proportion *Edge proportion*

Description

Calculate the proportion of cells in a raster polygon that are edge cells.

Usage

```
wbt_edge_proportion(
  input,
  output,
  output_text = FALSE,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

input	Input raster file.
output	Output raster file.
output_text	flag indicating whether a text report should also be output.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.

compress_rasters Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.

command_only Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_elevation_above_stream
Elevation above stream

Description

Calculates the elevation of cells above the nearest downslope stream cell.

Usage

```
wbt_elevation_above_stream(  
  dem,  
  streams,  
  output,  
  wd = NULL,  
  verbose_mode = FALSE,  
  compress_rasters = FALSE,  
  command_only = FALSE  
)
```

Arguments

dem Input raster DEM file.

streams Input raster streams file.

output Output raster file.

wd Changes the working directory.

verbose_mode Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.

compress_rasters Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.

command_only Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_elevation_above_stream_euclidean
Elevation above stream euclidean

Description

Calculates the elevation of cells above the nearest (Euclidean distance) stream cell.

Usage

```
wbt_elevation_above_stream_euclidean(  
    dem,  
    streams,  
    output,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

dem	Input raster DEM file.
streams	Input raster streams file.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_elev_above_pit *Elev above pit*

Description

Calculate the elevation of each grid cell above the nearest downstream pit cell or grid edge cell.

Usage

```
wbt_elev_above_pit(
    dem,
    output,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

dem	Input raster DEM file.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_elev_percentile *Elev percentile*

Description

Calculates the elevation percentile raster from a DEM.

Usage

```
wbt_elev_percentile(
    dem,
    output,
    filterx = 11,
    filtery = 11,
    sig_digits = 2,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

dem	Input raster DEM file.
output	Output raster file.
filterx	Size of the filter kernel in the x-direction.
filtery	Size of the filter kernel in the y-direction.
sig_digits	Number of significant digits.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by <code>system()</code> rather than running tool.

Value

Returns the tool text outputs.

wbt_elev_relative_to_min_max

Elev relative to min max

Description

Calculates the elevation of a location relative to the minimum and maximum elevations in a DEM.

Usage

```
wbt_elev_relative_to_min_max(
    dem,
    output,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

dem	Input raster DEM file.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

```
wbt_elev_relative_to_watershed_min_max
    Elev relative to watershed min max
```

Description

Calculates the elevation of a location relative to the minimum and maximum elevations in a watershed.

Usage

```
wbt_elev_relative_to_watershed_min_max(
    dem,
    watersheds,
    output,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

dem	Input raster DEM file.
watersheds	Input raster watersheds file.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_eliminate_coincident_points
Eliminate coincident points

Description

Removes any coincident, or nearly coincident, points from a vector points file.

Usage

```
wbt_eliminate_coincident_points(  
  input,  
  output,  
  tolerance,  
  wd = NULL,  
  verbose_mode = FALSE,  
  compress_rasters = FALSE,  
  command_only = FALSE  
)
```

Arguments

input	Input vector file.
output	Output vector polygon file.
tolerance	The distance tolerance for points.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.

compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_elongation_ratio *Elongation ratio*

Description

Calculates the elongation ratio for vector polygons.

Usage

```
wbt_elongation_ratio(
  input,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

input	Input vector polygon file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_embankment_mapping

Embankment mapping

Description

Maps and/or removes road embankments from an input fine-resolution DEM.

Usage

```
wbt_embankment_mapping(
  dem,
  road_vec,
  output,
  search_dist = 2.5,
  min_road_width = 6,
  typical_width = 30,
  max_height = 2,
  max_width = 60,
  max_increment = 0.05,
  spillout_slope = 4,
  remove_embankments = FALSE,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

dem	Input raster DEM file.
road_vec	Input vector polygons file.
output	Output raster file.
search_dist	Search distance used to reposition transportation vectors onto road embankments (in map units).
min_road_width	Minimum road width; this is the width of the paved road surface (in map units).
typical_width	Typical embankment width; this is the maximum width of an embankment with roadside ditches (in map units).
max_height	Typical embankment maximum height; this is the height a typical embankment with roadside ditches (in map units).
max_width	Maximum embankment width, typically where embankments traverse steep-sided valleys (in map units).
max_increment	Maximum upwards increment between neighbouring cells on an embankment (in elevation units).

spillout_slope	Spillout slope (in degrees).
remove_embankments	Optional flag indicating whether to output a DEM with embankments removed (true) or an embankment raster map (false).
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_emboss_filter	<i>Emboss filter</i>
-------------------	----------------------

Description

Performs an emboss filter on an image, similar to a hillshade operation.

Usage

```
wbt_emboss_filter(
    input,
    output,
    direction = "n",
    clip = 0,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input	Input raster file.
output	Output raster file.
direction	Direction of reflection; options include 'n', 's', 'e', 'w', 'ne', 'se', 'nw', 'sw'.
clip	Optional amount to clip the distribution tails by, in percent.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.

`compress_rasters` Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.

`command_only` Return command that would be executed by `system()` rather than running tool.

Value

Returns the tool text outputs.

`wbt_equal_to` *Equal to*

Description

Performs a equal-to comparison operation on two rasters or a raster and a constant value.

Usage

```
wbt_equal_to(
  input1,
  input2,
  output,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

`input1` Input raster file or constant value.

`input2` Input raster file or constant value.

`output` Output raster file.

`wd` Changes the working directory.

`verbose_mode` Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.

`compress_rasters` Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.

`command_only` Return command that would be executed by `system()` rather than running tool.

Value

Returns the tool text outputs.

wbt_erase	<i>Erase</i>
-----------	--------------

Description

Removes all the features, or parts of features, that overlap with the features of the erase vector polygon.

Usage

```
wbt_erase(  
    input,  
    erase,  
    output,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

input	Input vector file.
erase	Input erase polygon vector file.
output	Output vector file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

```
wbt_erase_polygon_from_lidar
```

Erase polygon from lidar

Description

Erases (cuts out) a vector polygon or polygons from a LiDAR point cloud.

Usage

```
wbt_erase_polygon_from_lidar(  
    input,  
    polygons,  
    output,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

input	Input LiDAR file.
polygons	Input vector polygons file.
output	Output LiDAR file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by <code>system()</code> rather than running tool.

Value

Returns the tool text outputs.

```
wbt_erase_polygon_from_raster
    Erase polygon from raster
```

Description

Erases (cuts out) a vector polygon from a raster.

Usage

```
wbt_erase_polygon_from_raster(  
    input,  
    polygons,  
    output,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

input	Input raster file.
polygons	Input vector polygons file.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by <code>system()</code> rather than running tool.

Value

Returns the tool text outputs.

wbt_euclidean_allocation

Euclidean allocation

Description

Assigns grid cells in the output raster the value of the nearest target cell in the input image, measured by the Shih and Wu (2004) Euclidean distance transform.

Usage

```
wbt_euclidean_allocation(  
  input,  
  output,  
  wd = NULL,  
  verbose_mode = FALSE,  
  compress_rasters = FALSE,  
  command_only = FALSE  
)
```

Arguments

input	Input raster file.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_euclidean_distance

Euclidean distance

Description

Calculates the Shih and Wu (2004) Euclidean distance transform.

Usage

```
wbt_euclidean_distance(
    input,
    output,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input	Input raster file.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

```
wbt_evaluate_training_sites
    Evaluate training sites
```

Description

This tool can be used to inspect the overlap in spectral signatures of training sites for various classes.

Usage

```
wbt_evaluate_training_sites(
    inputs,
    polys,
    field,
    output,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

inputs	Name of the input band images.
polys	Name of the input training site polygons shapefile.
field	Name of the attribute containing class name data.
output	Name of the output report file (*.html).
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_exp	<i>Exp</i>
---------	------------

Description

Returns the exponential (base e) of values in a raster.

Usage

```
wbt_exp(
  input,
  output,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

input	Input raster file.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_exp2	<i>Exp2</i>
----------	-------------

Description

Returns the exponential (base 2) of values in a raster.

Usage

```
wbt_exp2(
  input,
  output,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

input	Input raster file.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by <code>system()</code> rather than running tool.

Value

Returns the tool text outputs.

wbt_export_table_to_csv
Export table to csv

Description

Exports an attribute table to a CSV text file.

Usage

```
wbt_export_table_to_csv(  
    input,  
    output,  
    headers = TRUE,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

input	Input vector file.
output	Output csv file.
headers	Export field names as file header?.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_exposure_towards_wind_flux
Exposure towards wind flux

Description

This tool evaluates hydrologic connectivity within a DEM.

Usage

```
wbt_exposure_towards_wind_flux(  
    dem,  
    output,  
    azimuth = "",  
    max_dist = "",  
    zfactor = "",  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

dem	Name of the input DEM raster file.
output	Name of the output raster file.
azimuth	Wind azimuth, in degrees.
max_dist	Optional maximum search distance. Minimum value is 5 x cell size.
zfactor	Optional multiplier for when the vertical and horizontal units are not the same.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

`wbt_extend_vector_lines`*Extend vector lines*

Description

Extends vector lines by a specified distance.

Usage

```
wbt_extend_vector_lines(  
    input,  
    output,  
    dist,  
    extend = "both ends",  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

<code>input</code>	Input vector polyline file.
<code>output</code>	Output vector polyline file.
<code>dist</code>	The distance to extend.
<code>extend</code>	Extend direction, 'both ends' (default), 'line start', 'line end'.
<code>wd</code>	Changes the working directory.
<code>verbose_mode</code>	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
<code>compress_rasters</code>	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
<code>command_only</code>	Return command that would be executed by <code>system()</code> rather than running tool.

Value

Returns the tool text outputs.

wbt_extract_nodes *Extract nodes*

Description

Converts vector lines or polygons into vertex points.

Usage

```
wbt_extract_nodes(  
    input,  
    output,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

input	Input vector lines or polygon file.
output	Output vector points file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_extract_raster_values_at_points
Extract raster values at points

Description

Extracts the values of raster(s) at vector point locations.

Usage

```
wbt_extract_raster_values_at_points(
    inputs,
    points,
    out_text = FALSE,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

inputs	Input raster files.
points	Input vector points file.
out_text	Output point values as text? Otherwise, the only output is to the points file's attribute table.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_extract_streams *Extract streams*

Description

Extracts stream grid cells from a flow accumulation raster.

Usage

```
wbt_extract_streams(
    flow_accum,
    output,
    threshold,
    zero_background = FALSE,
    wd = NULL,
    verbose_mode = FALSE,
```



```

    compress_rasters = FALSE,
    command_only = FALSE
)

```

Arguments

flow_accum	Input raster D8 flow accumulation file.
output	Output raster file.
threshold	Threshold in flow accumulation values for channelization.
zero_background	Flag indicating whether a background value of zero should be used.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_extract_valleys *Extract valleys*

Description

Identifies potential valley bottom grid cells based on local topography alone.

Usage

```

wbt_extract_valleys(
  dem,
  output,
  variant = "LQ",
  line_thin = TRUE,
  filter = 5,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)

```

Arguments

dem	Input raster DEM file.
output	Output raster file.
variant	Options include 'LQ' (lower quartile), 'JandR' (Johnston and Rosenfeld), and 'PandD' (Peucker and Douglas); default is 'LQ'.
line_thin	Optional flag indicating whether post-processing line-thinning should be performed.
filter	Optional argument (only used when variant='lq') providing the filter size, in grid cells, used for lq-filtering (default is 5).
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_farthest_channel_head
Farthest channel head

Description

Calculates the distance to the furthest upstream channel head for each stream cell.

Usage

```
wbt_farthest_channel_head(
  d8_pntr,
  streams,
  output,
  esri_pntr = FALSE,
  zero_background = FALSE,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

d8_pntr	Input raster D8 pointer file.
streams	Input raster streams file.
output	Output raster file.
esri_pntr	D8 pointer uses the ESRI style scheme.
zero_background	Flag indicating whether a background value of zero should be used.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_fast_almost_gaussian_filter
Fast almost gaussian filter

Description

Performs a fast approximate Gaussian filter on an image.

Usage

```
wbt_fast_almost_gaussian_filter(  
    input,  
    output,  
    sigma = 1.8,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

input	Input raster file.
output	Output raster file.
sigma	Standard deviation distance in pixels.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_fd8_flow_accumulation
Fd8 flow accumulation

Description

Calculates an FD8 flow accumulation raster from an input DEM.

Usage

```
wbt_fd8_flow_accumulation(
  dem,
  output,
  out_type = "specific contributing area",
  exponent = 1.1,
  threshold = NULL,
  log = FALSE,
  clip = FALSE,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

dem	Input raster DEM file.
output	Output raster file.
out_type	Output type; one of 'cells', 'specific contributing area' (default), and 'catchment area'.
exponent	Optional exponent parameter; default is 1.1.
threshold	Optional convergence threshold parameter, in grid cells; default is infinity.
log	Optional flag to request the output be log-transformed.
clip	Optional flag to request clipping the display max by 1 percent.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_fd8_pointer	<i>Fd8 pointer</i>
-----------------	--------------------

Description

Calculates an FD8 flow pointer raster from an input DEM.

Usage

```
wbt_fd8_pointer(
  dem,
  output,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

dem	Input raster DEM file.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_feature_preserving_smoothing
Feature preserving smoothing

Description

Reduces short-scale variation in an input DEM using a modified Sun et al. (2007) algorithm.

Usage

```
wbt_feature_preserving_smoothing(  
  dem,  
  output,  
  filter = 11,  
  norm_diff = 15,  
  num_iter = 3,  
  max_diff = 0.5,  
  zfactor = NULL,  
  wd = NULL,  
  verbose_mode = FALSE,  
  compress_rasters = FALSE,  
  command_only = FALSE  
)
```

Arguments

dem	Input raster DEM file.
output	Output raster file.
filter	Size of the filter kernel.

norm_diff	Maximum difference in normal vectors, in degrees.
num_iter	Number of iterations.
max_diff	Maximum allowable absolute elevation change (optional).
zfactor	Optional multiplier for when the vertical and horizontal units are not the same.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_fetch_analysis *Fetch analysis*

Description

Performs an analysis of fetch or upwind distance to an obstacle.

Usage

```
wbt_fetch_analysis(
  dem,
  output,
  azimuth = 0,
  hgt_inc = 0.05,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

dem	Input raster DEM file.
output	Output raster file.
azimuth	Wind azimuth in degrees in degrees.
hgt_inc	Height increment value.
wd	Changes the working directory.

verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_fill_burn	<i>Fill burn</i>
---------------	------------------

Description

Burns streams into a DEM using the FillBurn (Saunders, 1999) method.

Usage

```
wbt_fill_burn(
  dem,
  streams,
  output,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

dem	Input raster DEM file.
streams	Input vector streams file.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_fill_depressions *Fill depressions*

Description

Fills all of the depressions in a DEM. Depression breaching should be preferred in most cases.

Usage

```
wbt_fill_depressions(  
    dem,  
    output,  
    fix_flats = TRUE,  
    flat_increment = NULL,  
    max_depth = NULL,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

dem	Input raster DEM file.
output	Output raster file.
fix_flats	Optional flag indicating whether flat areas should have a small gradient applied.
flat_increment	Optional elevation increment applied to flat areas.
max_depth	Optional maximum depression depth to fill.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

`wbt_fill_depressions_planchon_and_darboux`*Fill depressions planchon and darboux*

Description

Fills all of the depressions in a DEM using the Planchon and Darboux (2002) method.

Usage

```
wbt_fill_depressions_planchon_and_darboux(  
    dem,  
    output,  
    fix_flats = TRUE,  
    flat_increment = NULL,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

<code>dem</code>	Input raster DEM file.
<code>output</code>	Output raster file.
<code>fix_flats</code>	Optional flag indicating whether flat areas should have a small gradient applied.
<code>flat_increment</code>	Optional elevation increment applied to flat areas.
<code>wd</code>	Changes the working directory.
<code>verbose_mode</code>	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
<code>compress_rasters</code>	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
<code>command_only</code>	Return command that would be executed by <code>system()</code> rather than running tool.

Value

Returns the tool text outputs.

`wbt_fill_depressions_wang_and_liu`*Fill depressions wang and liu*

Description

Fills all of the depressions in a DEM using the Wang and Liu (2006) method. Depression breaching should be preferred in most cases.

Usage

```
wbt_fill_depressions_wang_and_liu(  
    dem,  
    output,  
    fix_flats = TRUE,  
    flat_increment = NULL,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

<code>dem</code>	Input raster DEM file.
<code>output</code>	Output raster file.
<code>fix_flats</code>	Optional flag indicating whether flat areas should have a small gradient applied.
<code>flat_increment</code>	Optional elevation increment applied to flat areas.
<code>wd</code>	Changes the working directory.
<code>verbose_mode</code>	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
<code>compress_rasters</code>	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
<code>command_only</code>	Return command that would be executed by <code>system()</code> rather than running tool.

Value

Returns the tool text outputs.

wbt_fill_missing_data *Fill missing data*

Description

Fills NoData holes in a DEM.

Usage

```
wbt_fill_missing_data(  
    input,  
    output,  
    filter = 11,  
    weight = 2,  
    no_edges = TRUE,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

input	Input raster file.
output	Output raster file.
filter	Filter size (cells).
weight	IDW weight value.
no_edges	Optional flag indicating whether to exclude NoData cells in edge regions.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

```
wbt_fill_single_cell_pits
    Fill single cell pits
```

Description

Raises pit cells to the elevation of their lowest neighbour.

Usage

```
wbt_fill_single_cell_pits(
    dem,
    output,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

dem	Input raster DEM file.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

```
wbt_filter_lidar_classes
    Filter lidar classes
```

Description

Removes points in a LAS file with certain specified class values.

Usage

```
wbt_filter_lidar_classes(
    input,
    output,
    exclude_cls = NULL,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

<code>input</code>	Input LiDAR file.
<code>output</code>	Output LiDAR file.
<code>exclude_cls</code>	Optional exclude classes from interpolation; Valid class values range from 0 to 18, based on LAS specifications. Example, <code>-exclude_cls='3,4,5,6,7,18'</code> .
<code>wd</code>	Changes the working directory.
<code>verbose_mode</code>	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
<code>compress_rasters</code>	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
<code>command_only</code>	Return command that would be executed by <code>system()</code> rather than running tool.

Value

Returns the tool text outputs.

`wbt_filter_lidar_scan_angles`
Filter lidar scan angles

Description

Removes points in a LAS file with scan angles greater than a threshold.

Usage

```
wbt_filter_lidar_scan_angles(
    input,
    output,
    threshold,
    wd = NULL,
    verbose_mode = FALSE,
```

```

    compress_rasters = FALSE,
    command_only = FALSE
)

```

Arguments

input	Input LiDAR file.
output	Output LiDAR file.
threshold	Scan angle threshold.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

```

wbt_filter_raster_features_by_area
    Filter raster features by area

```

Description

Removes small-area features from a raster.

Usage

```

wbt_filter_raster_features_by_area(
  input,
  output,
  threshold,
  background = "zero",
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)

```

Arguments

input	Input raster file.
output	Output raster file.
threshold	Remove features with fewer grid cells than this threshold value.
background	Background value.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by <code>system()</code> rather than running tool.

Value

Returns the tool text outputs.

`wbt_find_flightline_edge_points`
Find flightline edge points

Description

Identifies points along a flightline's edge in a LAS file.

Usage

```
wbt_find_flightline_edge_points(  
  input,  
  output,  
  wd = NULL,  
  verbose_mode = FALSE,  
  compress_rasters = FALSE,  
  command_only = FALSE  
)
```

Arguments

input	Input LiDAR file.
output	Output file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.

compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_find_lowest_or_highest_points
Find lowest or highest points

Description

Locates the lowest and/or highest valued cells in a raster.

Usage

```
wbt_find_lowest_or_highest_points(
    input,
    output,
    out_type = "lowest",
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input	Input raster file.
output	Output vector points file.
out_type	Output type; one of 'area' (default) and 'volume'.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_find_main_stem *Find main stem*

Description

Finds the main stem, based on stream lengths, of each stream network.

Usage

```
wbt_find_main_stem(  
    d8_pntr,  
    streams,  
    output,  
    esri_pntr = FALSE,  
    zero_background = FALSE,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

d8_pntr	Input raster D8 pointer file.
streams	Input raster streams file.
output	Output raster file.
esri_pntr	D8 pointer uses the ESRI style scheme.
zero_background	Flag indicating whether a background value of zero should be used.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

```
wbt_find_no_flow_cells
    Find no flow cells
```

Description

Finds grid cells with no downslope neighbours.

Usage

```
wbt_find_no_flow_cells(
    dem,
    output,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

dem	Input raster DEM file.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

```
wbt_find_parallel_flow
    Find parallel flow
```

Description

Finds areas of parallel flow in D8 flow direction rasters.

Usage

```
wbt_find_parallel_flow(
    d8_pntr,
    streams,
    output,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

<code>d8_pntr</code>	Input D8 pointer raster file.
<code>streams</code>	Input raster streams file.
<code>output</code>	Output raster file.
<code>wd</code>	Changes the working directory.
<code>verbose_mode</code>	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
<code>compress_rasters</code>	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
<code>command_only</code>	Return command that would be executed by <code>system()</code> rather than running tool.

Value

Returns the tool text outputs.

`wbt_find_patch_or_class_edge_cells`
Find patch or class edge cells

Description

Finds all cells located on the edge of patch or class features.

Usage

```
wbt_find_patch_or_class_edge_cells(
    input,
    output,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input	Input raster file.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_find_ridges	<i>Find ridges</i>
-----------------	--------------------

Description

Identifies potential ridge and peak grid cells.

Usage

```
wbt_find_ridges(
  dem,
  output,
  line_thin = TRUE,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

dem	Input raster DEM file.
output	Output raster file.
line_thin	Optional flag indicating whether post-processing line-thinning should be performed.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_fix_dangling_arcs *Fix dangling arcs*

Description

This tool fixes undershot and overshoot arcs, two common topological errors, in an input vector lines file.

Usage

```
wbt_fix_dangling_arcs(
    input,
    output,
    dist = "",
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input	Name of the input lines vector file.
output	Name of the output lines vector file.
dist	Snap distance, in xy units (metres).
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_flatten_lakes	<i>Flatten lakes</i>
-------------------	----------------------

Description

Flattens lake polygons in a raster DEM.

Usage

```
wbt_flatten_lakes(  
    dem,  
    lakes,  
    output,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

dem	Input raster DEM file.
lakes	Input lakes vector polygons file.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by <code>system()</code> rather than running tool.

Value

Returns the tool text outputs.

`wbt_flightline_overlap`*Flightline overlap*

Description

Reads a LiDAR (LAS) point file and outputs a raster containing the number of overlapping flight lines in each grid cell.

Usage

```
wbt_flightline_overlap(  
    input,  
    output = NULL,  
    resolution = 1,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

<code>input</code>	Input LiDAR file.
<code>output</code>	Output file.
<code>resolution</code>	Output raster's grid resolution.
<code>wd</code>	Changes the working directory.
<code>verbose_mode</code>	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
<code>compress_rasters</code>	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
<code>command_only</code>	Return command that would be executed by <code>system()</code> rather than running tool.

Value

Returns the tool text outputs.

wbt_flip_image	<i>Flip image</i>
----------------	-------------------

Description

Reflects an image in the vertical or horizontal axis.

Usage

```
wbt_flip_image(  
    input,  
    output,  
    direction = "vertical",  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

input	Input raster file.
output	Output raster file.
direction	Direction of reflection; options include 'v' (vertical), 'h' (horizontal), and 'b' (both).
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_flood_order	<i>Flood order</i>
-----------------	--------------------

Description

Assigns each DEM grid cell its order in the sequence of inundations that are encountered during a search starting from the edges, moving inward at increasing elevations.

Usage

```
wbt_flood_order(  
    dem,  
    output,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

dem	Input raster DEM file.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_floor	<i>Floor</i>
-----------	--------------

Description

Returns the largest (closest to positive infinity) value that is less than or equal to the values in a raster.

Usage

```
wbt_floor(
    input,
    output,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input	Input raster file.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_flow_accumulation_full_workflow
Flow accumulation full workflow

Description

Resolves all of the depressions in a DEM, outputting a breached DEM, an aspect-aligned non-divergent flow pointer, and a flow accumulation raster.

Usage

```
wbt_flow_accumulation_full_workflow(
    dem,
    out_dem,
    out_pntr,
    out_accum,
    out_type = "Specific Contributing Area",
    log = FALSE,
    clip = FALSE,
```

```

    esri_pntr = FALSE,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)

```

Arguments

dem	Input raster DEM file.
out_dem	Output raster DEM file.
out_pntr	Output raster flow pointer file.
out_accum	Output raster flow accumulation file.
out_type	Output type; one of 'cells', 'sca' (default), and 'ca'.
log	Optional flag to request the output be log-transformed.
clip	Optional flag to request clipping the display max by 1 percent.
esri_pntr	D8 pointer uses the ESRI style scheme.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_flow_length_diff *Flow length diff*

Description

Calculates the local maximum absolute difference in downslope flowpath length, useful in mapping drainage divides and ridges.

Usage

```

wbt_flow_length_diff(
  d8_pntr,
  output,
  esri_pntr = FALSE,
  wd = NULL,

```

```

    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)

```

Arguments

d8_pntr	Input D8 pointer raster file.
output	Output raster file.
esri_pntr	D8 pointer uses the ESRI style scheme.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_gamma_correction *Gamma correction*

Description

Performs a gamma correction on an input images.

Usage

```

wbt_gamma_correction(
  input,
  output,
  gamma = 0.5,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)

```

Arguments

input	Input raster file.
output	Output raster file.
gamma	Gamma value.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_gaussian_contrast_stretch
Gaussian contrast stretch

Description

Performs a Gaussian contrast stretch on input images.

Usage

```
wbt_gaussian_contrast_stretch(
  input,
  output,
  num_tones = 256,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

input	Input raster file.
output	Output raster file.
num_tones	Number of tones in the output image.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.

compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by <code>system()</code> rather than running tool.

Value

Returns the tool text outputs.

wbt_gaussian_curvature
Gaussian curvature

Description

Calculates a mean curvature raster from an input DEM.

Usage

```
wbt_gaussian_curvature(
  dem,
  output,
  log = FALSE,
  zfactor = NULL,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

dem	Input raster DEM file.
output	Output raster file.
log	Display output values using a log-scale.
zfactor	Optional multiplier for when the vertical and horizontal units are not the same.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by <code>system()</code> rather than running tool.

Value

Returns the tool text outputs.

wbt_gaussian_filter *Gaussian filter*

Description

Performs a Gaussian filter on an image.

Usage

```
wbt_gaussian_filter(  
    input,  
    output,  
    sigma = 0.75,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

input	Input raster file.
output	Output raster file.
sigma	Standard deviation distance in pixels.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_gaussian_scale_space
Gaussian scale space

Description

This tool uses the fast Gaussian approximation algorithm to produce scaled land-surface parameter measurements from an input DEM.

Usage

```
wbt_gaussian_scale_space(
  dem,
  output,
  output_zscore,
  output_scale,
  points = NULL,
  sigma = 0.5,
  step = 0.5,
  num_steps = 10,
  lsp = "Slope",
  z_factor = NULL,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

dem	Name of the input DEM raster file.
output	Name of the output land-surface parameter raster file.
output_zscore	Name of the output z-score raster file.
output_scale	Name of the output scale raster file.
points	Name of the input vector points shapefile.
sigma	Initial sigma value (cells).
step	Step size as any positive non-zero integer.
num_steps	Number of steps.
lsp	Output land-surface parameter; one of 'AnisotropyLTP', 'Aspect', 'DiffMeanElev', 'Eastness', 'Elevation', 'Hillshade', 'MeanCurvature', 'Northness', 'PlanCurvature', 'ProfileCurvature', 'Ruggedness', 'Slope', 'TanCurvature', 'TotalCurvature'.
z_factor	Optional multiplier for when the vertical and horizontal units are not the same.
wd	Changes the working directory.

<code>verbose_mode</code>	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
<code>compress_rasters</code>	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
<code>command_only</code>	Return command that would be executed by <code>system()</code> rather than running tool.

Value

Returns the tool text outputs.

`wbt_generalize_classified_raster`
Generalize classified raster

Description

Generalizes a raster containing class or object features by removing small features.

Usage

```
wbt_generalize_classified_raster(
  input,
  output,
  min_size = 4,
  method = "longest",
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

<code>input</code>	Name of the input raster image file.
<code>output</code>	Name of the output raster file.
<code>min_size</code>	Minimum feature size, in grid cells.
<code>method</code>	Grouping method; one of 'longest' (default), 'largest', and 'nearest'.
<code>wd</code>	Changes the working directory.
<code>verbose_mode</code>	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
<code>compress_rasters</code>	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
<code>command_only</code>	Return command that would be executed by <code>system()</code> rather than running tool.

Value

Returns the tool text outputs.

wbt_generalize_with_similarity
Generalize with similarity

Description

Generalizes a raster containing class or object features by removing small features using similarity criteria of neighbouring features.

Usage

```
wbt_generalize_with_similarity(  
    input,  
    similarity,  
    output,  
    min_size = 4,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

input	Name of the input raster image file.
similarity	Names of the input similarity images.
output	Name of the output raster file.
min_size	Minimum feature size, in grid cells.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

`wbt_generating_function`*Generating function*

Description

This tool calculates generating function from an input DEM.

Usage

```
wbt_generating_function(  
    dem,  
    output,  
    log = FALSE,  
    zfactor = 1,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

<code>dem</code>	Name of the input raster DEM file.
<code>output</code>	Name of the output raster image file.
<code>log</code>	Display output values using a log-scale.
<code>zfactor</code>	Z conversion factor.
<code>wd</code>	Changes the working directory.
<code>verbose_mode</code>	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
<code>compress_rasters</code>	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
<code>command_only</code>	Return command that would be executed by <code>system()</code> rather than running tool.

Value

Returns the tool text outputs.

wbt_geomorphons	<i>Geomorphons</i>
-----------------	--------------------

Description

Computes geomorphon patterns.

Usage

```
wbt_geomorphons(
  dem,
  output,
  search = 50,
  threshold = 0,
  tdist = 0,
  forms = TRUE,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

dem	Input raster DEM file.
output	Output raster file.
search	Look up distance.
threshold	Flatness threshold for the classification function (in degrees).
tdist	Distance (in cells) to begin reducing the flatness threshold to avoid problems with pseudo-flat lines-of-sight.
forms	Classify geomorphons into 10 common land morphologies, else, output ternary code.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by <code>system()</code> rather than running tool.

Value

Returns the tool text outputs.

wbt_greater_than	<i>Greater than</i>
------------------	---------------------

Description

Performs a greater-than comparison operation on two rasters or a raster and a constant value.

Usage

```
wbt_greater_than(  
    input1,  
    input2,  
    output,  
    incl_equals = FALSE,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

input1	Input raster file or constant value.
input2	Input raster file or constant value.
output	Output raster file.
incl_equals	Perform a greater-than-or-equal-to operation.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_hack_stream_order *Hack stream order*

Description

Assigns the Hack stream order to each tributary in a stream network.

Usage

```
wbt_hack_stream_order(  
    d8_pntr,  
    streams,  
    output,  
    esri_pntr = FALSE,  
    zero_background = FALSE,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

d8_pntr	Input raster D8 pointer file.
streams	Input raster streams file.
output	Output raster file.
esri_pntr	D8 pointer uses the ESRI style scheme.
zero_background	Flag indicating whether a background value of zero should be used.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_height_above_ground
Height above ground

Description

Normalizes a LiDAR point cloud, providing the height above the nearest ground-classified point.

Usage

```
wbt_height_above_ground(  
    input,  
    output = NULL,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

input	Input LiDAR file (including extension).
output	Output raster file (including extension).
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_help *Help description for WhiteboxTools*

Description

Help description for WhiteboxTools

Usage

```
wbt_help()
```


Value

Returns the help description for WhiteboxTools as an R character vector.

Examples

```
## Not run:
wbt_help()

## End(Not run)
```

wbt_highest_position *Highest position*

Description

Identifies the stack position of the maximum value within a raster stack on a cell-by-cell basis.

Usage

```
wbt_highest_position(
  inputs,
  output,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

inputs	Input raster files.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_high_pass_filter *High pass filter*

Description

Performs a high-pass filter on an input image.

Usage

```
wbt_high_pass_filter(  
    input,  
    output,  
    filterx = 11,  
    filtery = 11,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

input	Input raster file.
output	Output raster file.
filterx	Size of the filter kernel in the x-direction.
filtery	Size of the filter kernel in the y-direction.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_high_pass_median_filter
High pass median filter

Description

Performs a high pass median filter on an input image.

Usage

```
wbt_high_pass_median_filter(  
    input,  
    output,  
    filterx = 11,  
    filtery = 11,  
    sig_digits = 2,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

input	Input raster file.
output	Output raster file.
filterx	Size of the filter kernel in the x-direction.
filtery	Size of the filter kernel in the y-direction.
sig_digits	Number of significant digits.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

`wbt_hillshade`*Hillshade*

Description

Calculates a hillshade raster from an input DEM.

Usage

```
wbt_hillshade(  
    dem,  
    output,  
    azimuth = 315,  
    altitude = 30,  
    zfactor = NULL,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

<code>dem</code>	Input raster DEM file.
<code>output</code>	Output raster file.
<code>azimuth</code>	Illumination source azimuth in degrees.
<code>altitude</code>	Illumination source altitude in degrees.
<code>zfactor</code>	Optional multiplier for when the vertical and horizontal units are not the same.
<code>wd</code>	Changes the working directory.
<code>verbose_mode</code>	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
<code>compress_rasters</code>	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
<code>command_only</code>	Return command that would be executed by <code>system()</code> rather than running tool.

Value

Returns the tool text outputs.

wbt_hillslopes	<i>Hillslopes</i>
----------------	-------------------

Description

Identifies the individual hillslopes draining to each link in a stream network.

Usage

```
wbt_hillslopes(  
    d8_pntr,  
    streams,  
    output,  
    esri_pntr = FALSE,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

d8_pntr	Input raster D8 pointer file.
streams	Input raster streams file.
output	Output raster file.
esri_pntr	D8 pointer uses the ESRI style scheme.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_histogram_equalization
Histogram equalization

Description

Performs a histogram equalization contrast enhancement on an image.

Usage

```
wbt_histogram_equalization(  
    input,  
    output,  
    num_tones = 256,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

input	Input raster file.
output	Output raster file.
num_tones	Number of tones in the output image.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

`wbt_histogram_matching`*Histogram matching*

Description

Alters the statistical distribution of a raster image matching it to a specified PDF.

Usage

```
wbt_histogram_matching(  
    input,  
    histo_file,  
    output,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

<code>input</code>	Input raster file.
<code>histo_file</code>	Input reference probability distribution function (pdf) text file.
<code>output</code>	Output raster file.
<code>wd</code>	Changes the working directory.
<code>verbose_mode</code>	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
<code>compress_rasters</code>	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
<code>command_only</code>	Return command that would be executed by <code>system()</code> rather than running tool.

Value

Returns the tool text outputs.

`wbt_histogram_matching_two_images`*Histogram matching two images*

Description

This tool alters the cumulative distribution function of a raster image to that of another image.

Usage

```
wbt_histogram_matching_two_images(  
    input1,  
    input2,  
    output,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

<code>input1</code>	Input raster file to modify.
<code>input2</code>	Input reference raster file.
<code>output</code>	Output raster file.
<code>wd</code>	Changes the working directory.
<code>verbose_mode</code>	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
<code>compress_rasters</code>	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
<code>command_only</code>	Return command that would be executed by <code>system()</code> rather than running tool.

Value

Returns the tool text outputs.

wbt_hole_proportion *Hole proportion*

Description

Calculates the proportion of the total area of a polygon's holes relative to the area of the polygon's hull.

Usage

```
wbt_hole_proportion(
    input,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input	Input vector polygon file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_horizontal_excess_curvature
Horizontal excess curvature

Description

This tool calculates horizontal excess curvature from an input DEM.

Usage

```
wbt_horizontal_excess_curvature(
    dem,
    output,
    log = FALSE,
    zfactor = 1,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

dem	Name of the input raster DEM file.
output	Name of the output raster image file.
log	Display output values using a log-scale.
zfactor	Z conversion factor.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_horizon_angle	<i>Horizon angle</i>
-------------------	----------------------

Description

Calculates horizon angle (maximum upwind slope) for each grid cell in an input DEM.

Usage

```
wbt_horizon_angle(
    dem,
    output,
    azimuth = 0,
    max_dist = 100,
    wd = NULL,
```

```

    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)

```

Arguments

dem	Input raster DEM file.
output	Output raster file.
azimuth	Azimuth, in degrees.
max_dist	Optional maximum search distance (unspecified if none; in xy units). Minimum value is 5 x cell size.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_horton_stream_order
Horton stream order

Description

Assigns the Horton stream order to each tributary in a stream network.

Usage

```

wbt_horton_stream_order(
  d8_pntr,
  streams,
  output,
  esri_pntr = FALSE,
  zero_background = FALSE,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)

```

Arguments

d8_pntr	Input raster D8 pointer file.
streams	Input raster streams file.
output	Output raster file.
esri_pntr	D8 pointer uses the ESRI style scheme.
zero_background	Flag indicating whether a background value of zero should be used.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_hydrologic_connectivity
Hydrologic connectivity

Description

This tool evaluates hydrologic connectivity within a DEM.

Usage

```
wbt_hydrologic_connectivity(
  dem,
  output1,
  output2,
  exponent = 1,
  threshold = NULL,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

dem	Name of the input DEM raster file; must be depressionless.
output1	Name of the output downslope unsaturated length (DUL) file.
output2	Name of the output upslope disconnected saturated area (UDSA) file.
exponent	Optional exponent parameter; default is 1.0.
threshold	Optional convergence threshold parameter, in grid cells; default is infinity.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_hypsometrically_tinted_hillshade
Hypsometrically tinted hillshade

Description

Creates an colour shaded relief image from an input DEM.

Usage

```
wbt_hypsometrically_tinted_hillshade(  

  dem,  

  output,  

  altitude = 45,  

  hs_weight = 0.5,  

  brightness = 0.5,  

  atmospheric = 0,  

  palette = "atlas",  

  reverse = FALSE,  

  zfactor = NULL,  

  full_mode = FALSE,  

  wd = NULL,  

  verbose_mode = FALSE,  

  compress_rasters = FALSE,  

  command_only = FALSE  

)
```

Arguments

dem	Input raster DEM file.
output	Output raster file.
altitude	Illumination source altitude in degrees.
hs_weight	Weight given to hillshade relative to relief (0.0-1.0).
brightness	Brightness factor (0.0-1.0).
atmospheric	Atmospheric effects weight (0.0-1.0).
palette	Options include 'atlas', 'high_relief', 'arid', 'soft', 'muted', 'purple', 'viridi', 'gn_yl', 'pi_y_g', 'bl_yl_rd', and 'deep'.
reverse	Optional flag indicating whether to use reverse the palette.
zfactor	Optional multiplier for when the vertical and horizontal units are not the same.
full_mode	Optional flag indicating whether to use full 360-degrees of illumination sources.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_hypsometric_analysis
Hypsometric analysis

Description

Calculates a hypsometric curve for one or more DEMs.

Usage

```
wbt_hypsometric_analysis(  
  inputs,  
  output,  
  watershed = NULL,  
  wd = NULL,  
  verbose_mode = FALSE,  
  compress_rasters = FALSE,  
  command_only = FALSE  
)
```

Arguments

inputs	Input DEM files.
output	Output HTML file (default name will be based on input file if unspecified).
watershed	Input watershed files (optional).
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_idw_interpolation *Idw interpolation*

Description

Interpolates vector points into a raster surface using an inverse-distance weighted scheme.

Usage

```
wbt_idw_interpolation(  
  input,  
  field,  
  output,  
  use_z = FALSE,  
  weight = 2,  
  radius = NULL,  
  min_points = NULL,  
  cell_size = NULL,  
  base = NULL,  
  wd = NULL,  
  verbose_mode = FALSE,  
  compress_rasters = FALSE,  
  command_only = FALSE  
)
```

Arguments

input	Input vector Points file.
field	Input field name in attribute table.
output	Output raster file.
use_z	Use z-coordinate instead of field?.
weight	IDW weight value.
radius	Search Radius in map units.
min_points	Minimum number of points.
cell_size	Optionally specified cell size of output raster. Not used when base raster is specified.
base	Optionally specified input base raster file. Not used when a cell size is specified.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_ihs_to_rgb	<i>Ihs to rgb</i>
----------------	-------------------

Description

Converts intensity, hue, and saturation (IHS) images into red, green, and blue (RGB) images.

Usage

```
wbt_ihs_to_rgb(
  intensity,
  hue,
  saturation,
  red = NULL,
  green = NULL,
  blue = NULL,
  output = NULL,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```


Arguments

intensity	Input intensity file.
hue	Input hue file.
saturation	Input saturation file.
red	Output red band file. Optionally specified if colour-composite not specified.
green	Output green band file. Optionally specified if colour-composite not specified.
blue	Output blue band file. Optionally specified if colour-composite not specified.
output	Output colour-composite file. Only used if individual bands are not specified.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_image_autocorrelation
Image autocorrelation

Description

Performs Moran's I analysis on two or more input images.

Usage

```
wbt_image_autocorrelation(  
  inputs,  
  output,  
  contiguity = "Rook",  
  wd = NULL,  
  verbose_mode = FALSE,  
  compress_rasters = FALSE,  
  command_only = FALSE  
)
```

Arguments

inputs	Input raster files.
output	Output HTML file (default name will be based on input file if unspecified).
contiguity	Contiguity type.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by <code>system()</code> rather than running tool.

Value

Returns the tool text outputs.

`wbt_image_correlation` *Image correlation*

Description

Performs image correlation on two or more input images.

Usage

```
wbt_image_correlation(  
  inputs,  
  output = NULL,  
  wd = NULL,  
  verbose_mode = FALSE,  
  compress_rasters = FALSE,  
  command_only = FALSE  
)
```

Arguments

inputs	Input raster files.
output	Output HTML file (default name will be based on input file if unspecified).
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by <code>system()</code> rather than running tool.

Value

Returns the tool text outputs.

```
wbt_image_correlation_neighbourhood_analysis
    Image correlation neighbourhood analysis
```

Description

Performs image correlation on two input images neighbourhood search windows.

Usage

```
wbt_image_correlation_neighbourhood_analysis(
    input1,
    input2,
    output1,
    output2,
    filter = 11,
    stat = "pearson",
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input1	Input raster file.
input2	Input raster file.
output1	Output correlation (r-value or rho) raster file.
output2	Output significance (p-value) raster file.
filter	Size of the filter kernel.
stat	Correlation type; one of 'pearson' (default) and 'spearman'.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_image_regression *Image regression*

Description

Performs image regression analysis on two input images.

Usage

```
wbt_image_regression(
    input1,
    input2,
    output,
    out_residuals = NULL,
    standardize = FALSE,
    scattergram = FALSE,
    num_samples = 1000,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input1	Input raster file (independent variable, X).
input2	Input raster file (dependent variable, Y).
output	Output HTML file for regression summary report.
out_residuals	Output raster regression residual file.
standardize	Optional flag indicating whether to standardize the residuals map.
scattergram	Optional flag indicating whether to output a scattergram.
num_samples	Number of samples used to create scattergram.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

`wbt_image_segmentation`*Image segmentation*

Description

Performs a region-growing based segmentation on a set of multi-spectral images.

Usage

```
wbt_image_segmentation(  
    inputs,  
    output,  
    threshold = 0.5,  
    steps = 10,  
    min_area = 4,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

<code>inputs</code>	Names of the input band images.
<code>output</code>	Name of the output raster file.
<code>threshold</code>	Distance threshold, in z-scores.
<code>steps</code>	Number of steps.
<code>min_area</code>	Minimum object area, in grid cells (1-8).
<code>wd</code>	Changes the working directory.
<code>verbose_mode</code>	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
<code>compress_rasters</code>	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
<code>command_only</code>	Return command that would be executed by <code>system()</code> rather than running tool.

Value

Returns the tool text outputs.

wbt_image_slider *Image slider*

Description

This tool creates an image slider from two input images.

Usage

```
wbt_image_slider(
    input1,
    input2,
    output,
    palette1 = "grey",
    reverse1 = FALSE,
    label1 = "",
    palette2 = "grey",
    reverse2 = FALSE,
    label2 = "",
    height = 600,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input1	Name of the left input image file.
input2	Name of the right input image file.
output	Name of the output HTML file (*.html).
palette1	Left image palette; options are 'grey', 'atlas', 'high_relief', 'arid', 'soft', 'muted', 'purple', 'viridi', 'gn_yl', 'pi_y_g', 'bl_yl_rd', 'deep', and 'rgb'.
reverse1	Reverse left image palette?.
label1	Left image label (leave blank for none).
palette2	Right image palette; options are 'grey', 'atlas', 'high_relief', 'arid', 'soft', 'muted', 'purple', 'viridi', 'gn_yl', 'pi_y_g', 'bl_yl_rd', 'deep', and 'rgb'.
reverse2	Reverse right image palette?.
label2	Right image label (leave blank for none).
height	Image height, in pixels.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.

compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_image_stack_profile
Image stack profile

Description

Plots an image stack profile (i.e. signature) for a set of points and multispectral images.

Usage

```
wbt_image_stack_profile(  
  inputs,  
  points,  
  output,  
  wd = NULL,  
  verbose_mode = FALSE,  
  compress_rasters = FALSE,  
  command_only = FALSE  
)
```

Arguments

inputs	Input multispectral image files.
points	Input vector points file.
output	Output HTML file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_impoundment_size_index
Impoundment size index

Description

Calculates the impoundment size resulting from damming a DEM.

Usage

```
wbt_impoundment_size_index(  
    dem,  
    damlength,  
    out_mean = NULL,  
    out_max = NULL,  
    out_volume = NULL,  
    out_area = NULL,  
    out_dam_height = NULL,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

dem	Input raster DEM file.
damlength	Maximum length of the dam.
out_mean	Output mean flooded depth file.
out_max	Output maximum flooded depth file.
out_volume	Output flooded volume file.
out_area	Output flooded area file.
out_dam_height	Output dam height file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_increment	<i>Increment</i>
---------------	------------------

Description

Increases the values of each grid cell in an input raster by 1.0. (see also InPlaceAdd).

Usage

```
wbt_increment(  
    input,  
    output,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

input	Input raster file.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_init	<i>Initialize WhiteboxTools</i>
----------	---------------------------------

Description

`wbt_init()`: Check if a suitable WhiteboxTools executable is present. Search default path in package directory or set it manually with `exe_path`.

`wbt_options()`: Get/set package options

- `whitebox.exe_path` - character. Path to executable file. The default value is the package installation directory, subdirectory "WBT", followed by `whitebox_tools.exe` or `whitebox_tools`. Set the `whitebox.exe_path` option using `wbt_init()` `exe_path` argument
- `whitebox.wd` - character. Path to WhiteboxTools working directory. Used as `--wd` argument for tools that support it when `wd` is not specified elsewhere.
- `whitebox.verbose` - logical. Should standard output from calls to executable be `cat()` out for readability? Default is result of `interactive()`. Individual tools may have `verbose_mode` setting that produce only single-line output when `FALSE`. These argument values are left as the defaults defined in the package documentation for that function. When `whitebox.verbose=FALSE` no output is produced. Set the value of `whitebox.verbose` with `wbt_verbose()` `verbose` argument.
- `whitebox.compress_rasters` - logical. Should raster output from WhiteboxTools be compressed? Default: `FALSE`. Set the value of `whitebox.compress_rasters` with `wbt_compress_rasters()` `compress_rasters` argument.
- `whitebox.max_procs` - integer. Maximum number of processes for tools that run in parallel or partially parallelize. Default: `-1` uses all of the available cores.

`wbt_exe_path()`: Get the file path of the WhiteboxTools executable.

`wbt_wd()`: Get or set the WhiteboxTools working directory. Default: `""` (unset) is your R working directory if no other options are set.

`wbt_verbose()`: Check verbose options for WhiteboxTools

`wbt_compress_rasters()`: Check raster compression option for WhiteboxTools. Default: `FALSE`

`wbt_max_procs()`: Check maximum number of processes for for tools that run in parallel or partially parallelize. Default: `-1` uses all of the available cores.

Usage

```
wbt_init(exe_path = wbt_exe_path(shell_quote = FALSE), ...)
```

```
wbt_options(
  exe_path = NULL,
  wd = NULL,
  verbose = NULL,
  compress_rasters = NULL,
  max_procs = NULL
)
```

```
wbt_exe_path(exe_path = NULL, shell_quote = TRUE)
```

```
wbt_default_path()
```

```
wbt_wd(wd = NULL)

wbt_verbos(verbose = NULL)

wbt_compress_rasters(compress_rasters = NULL)

wbt_max_procs(max_procs = NULL)
```

Arguments

exe_path	Optional: User-supplied path to WhiteboxTools executable. Default: NULL
...	additional arguments to wbt_options()
wd	character; Default: NULL; if set the package option whitebox.wd is set specified path (if directory exists)
verbose	Default: NULL; if logical, set the package option whitebox.verbose to specified value
compress_rasters	Default: NULL; if logical, set the package option whitebox.compress_rasters to specified value
max_procs	Default: NULL; if integer, set the package option whitebox.max_procs to specified value
shell_quote	Return shQuote() result?

Details

wbt_exe_path(): Checks system environment variable R_WHITEBOX_EXE_PATH and package option whitebox.exe_path. Set your desired path with either Sys.setenv(R_WHITEBOX_EXE_PATH = "C:/path/to/whitebox_tools.exe") or options(whitebox.exe_path = "C:/path/to/whitebox_tools.exe"). The default, backwards-compatible path is returned by wbt_default_path()

wbt_wd(): Before you set the working directory in a session the default output will be in your current R working directory unless otherwise specified. You can change working directory at any time by setting the wd argument to wbt_wd() and running a tool. Note that once you have set a working directory, the directory needs to be set somewhere to "replace" the old value; just dropping the flag will not change the working directory back to the R working directory. To "unset" the option in the R package you can use wbt_wd("") which is equivalent to wbt_wd(getwd()).

Value

wbt_init(): logical; TRUE if binary file is found at exe_path

wbt_options(): an invisible list containing current whitebox.exe_path, whitebox.verbose, whitebox.compress_rasters, and whitebox.max_procs options

Returns the file path of WhiteboxTools executable.

wbt_wd(): character; when working directory is unset, will not add --wd= arguments to calls and should be the same as using getwd(). See Details.

wbt_verbos(): logical; defaults to result of interactive()

wbt_compress_rasters(): logical; defaults to NA

wbt_max_procs(): integer; defaults to NA_integer_

See Also

[install_whitebox\(\)](#) [whitebox](#)

Examples

```
## Not run:
## wbt_init():

# set path to binary as an argument
# wbt_init(exe_path = "not/a/valid/path/whitebox_tools.exe")

## End(Not run)
## Not run:

## wbt_options():

# set multiple options (e.g. exe_path and verbose) with wbt_options()
wbt_options(exe_path = "not/a/valid/path/whitebox_tools.exe", verbose = TRUE)

## End(Not run)
## Not run:
wbt_exe_path()

## End(Not run)
## Not run:

## wbt_wd():

# set WBT working directory to R working directory
wbt_wd(wd = getwd())

## End(Not run)
## Not run:

## wbt_verbose():

wbt_verbose(verbose = TRUE)

## End(Not run)
## Not run:

## wbt_compress_rasters():

wbt_compress_rasters(compress_rasters = TRUE)

## End(Not run)
## Not run:

## wbt_max_procs():

wbt_max_procs(max_procs = 2)
```

```
## End(Not run)
```

```
wbt_insert_dams      Insert dams
```

Description

Calculates the impoundment size resulting from damming a DEM.

Usage

```
wbt_insert_dams(
  dem,
  dam_pts,
  output,
  damlength,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

dem	Input raster DEM file.
dam_pts	Input vector dam points file.
output	Output file.
damlength	Maximum length of the dam.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

`wbt_install`*Download and Install WhiteboxTools*

Description

This function downloads the WhiteboxTools binary if needed. Pre-compiled binaries are only available for download for 64-bit Linux (Ubuntu 20.04), Windows and Mac OS (Intel) platforms. If you need WhiteboxTools for another platform follow the instructions here: <https://github.com/jblindsay/whitebox-tools>

Usage

```
wbt_install(pkg_dir = find.package("whitebox"), force = FALSE)
install_whitebox(pkg_dir = find.package("whitebox"), force = FALSE)
```

Arguments

<code>pkg_dir</code>	default install path is to whitebox package "WBT" folder
<code>force</code>	logical. Default FALSE. Force install?

Value

Prints out the location of the WhiteboxTools binary, if found. NULL otherwise.

Examples

```
## Not run:
install_whitebox()

## End(Not run)
```

`wbt_integer_division` *Integer division*

Description

Performs an integer division operation on two rasters or a raster and a constant value.

Usage

```
wbt_integer_division(
    input1,
    input2,
    output,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input1	Input raster file or constant value.
input2	Input raster file or constant value.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_integral_image	<i>Integral image</i>
--------------------	-----------------------

Description

Transforms an input image (summed area table) into its integral image equivalent.

Usage

```
wbt_integral_image(
    input,
    output,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input	Input raster file.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_intersect	<i>Intersect</i>
---------------	------------------

Description

Identifies the parts of features in common between two input vector layers.

Usage

```
wbt_intersect(
  input,
  overlay,
  output,
  snap = 0,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

input	Input vector file.
overlay	Input overlay vector file.
output	Output vector file.
snap	Snap tolerance.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.

compress_rasters Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.

command_only Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_inverse_principal_component_analysis
Inverse principal component analysis

Description

This tool performs an inverse principal component analysis on a series of input component images.

Usage

```
wbt_inverse_principal_component_analysis(  
  inputs,  
  report,  
  wd = NULL,  
  verbose_mode = FALSE,  
  compress_rasters = FALSE,  
  command_only = FALSE  
)
```

Arguments

inputs Name of the input PCA component images.

report Name of the PCA report file (*.html).

wd Changes the working directory.

verbose_mode Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.

compress_rasters Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.

command_only Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_in_place_add *In place add*

Description

Performs an in-place addition operation (input1 += input2).

Usage

```
wbt_in_place_add(
    input1,
    input2,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input1	Input raster file.
input2	Input raster file or constant value.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_in_place_divide *In place divide*

Description

Performs an in-place division operation (input1 /= input2).

Usage

```
wbt_in_place_divide(  
    input1,  
    input2,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

input1	Input raster file.
input2	Input raster file or constant value.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_in_place_multiply *In place multiply*

Description

Performs an in-place multiplication operation (input1 *= input2).

Usage

```
wbt_in_place_multiply(  
    input1,  
    input2,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

input1	Input raster file.
input2	Input raster file or constant value.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_in_place_subtract *In place subtract*

Description

Performs an in-place subtraction operation (input1 -= input2).

Usage

```
wbt_in_place_subtract(
  input1,
  input2,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

input1	Input raster file.
input2	Input raster file or constant value.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_isobasins	<i>Isobasins</i>
---------------	------------------

Description

Divides a landscape into nearly equal sized drainage basins (i.e. watersheds).

Usage

```
wbt_isobasins(
    dem,
    output,
    size,
    connections = FALSE,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

dem	Input raster DEM file.
output	Output raster file.
size	Target basin size, in grid cells.
connections	Output upstream-downstream flow connections among basins?.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_is_no_data	<i>Is no data</i>
----------------	-------------------

Description

Identifies NoData valued pixels in an image.

Usage

```
wbt_is_no_data(
  input,
  output,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

input	Input raster file.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_jenson_snap_pour_points	<i>Jenson snap pour points</i>
-----------------------------	--------------------------------

Description

Moves outlet points used to specify points of interest in a watershedding operation to the nearest stream cell.

Usage

```
wbt_jenson_snap_pour_points(
  pour_pts,
  streams,
  output,
  snap_dist,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

<code>pour_pts</code>	Input vector pour points (outlet) file.
<code>streams</code>	Input raster streams file.
<code>output</code>	Output vector file.
<code>snap_dist</code>	Maximum snap distance in map units.
<code>wd</code>	Changes the working directory.
<code>verbose_mode</code>	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
<code>compress_rasters</code>	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
<code>command_only</code>	Return command that would be executed by <code>system()</code> rather than running tool.

Value

Returns the tool text outputs.

<code>wbt_join_tables</code>	<i>Join tables</i>
------------------------------	--------------------

Description

Merge a vector's attribute table with another table based on a common field.

Usage

```
wbt_join_tables(
  input1,
  pkey,
  input2,
  fkey,
  import_field,
```

```

    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)

```

Arguments

input1	Input primary vector file (i.e. the table to be modified).
pkey	Primary key field.
input2	Input foreign vector file (i.e. source of data to be imported).
fkey	Foreign key field.
import_field	Imported field (all fields will be imported if not specified).
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_kappa_index	<i>Kappa index</i>
-----------------	--------------------

Description

Performs a kappa index of agreement (KIA) analysis on two categorical raster files.

Usage

```

wbt_kappa_index(
  input1,
  input2,
  output,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)

```


Arguments

input1	Input classification raster file.
input2	Input reference raster file.
output	Output HTML file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_knn_classification
Knn classification

Description

Performs a supervised k-nearest neighbour classification using training site polygons/points and predictor rasters.

Usage

```
wbt_knn_classification(  
  inputs,  
  training,  
  field,  
  output,  
  scaling = "Normalize",  
  k = 5,  
  clip = TRUE,  
  test_proportion = 0.2,  
  wd = NULL,  
  verbose_mode = FALSE,  
  compress_rasters = FALSE,  
  command_only = FALSE  
)
```

Arguments

inputs	Names of the input predictor rasters.
training	Name of the input training site polygons/points shapefile.
field	Name of the attribute containing class name data.
output	Name of the output raster file.
scaling	Scaling method for predictors. Options include 'None', 'Normalize', and 'Standardize'.
k	k-parameter, which determines the number of nearest neighbours used.
clip	Perform training data clipping to remove outlier pixels?.
test_proportion	The proportion of the dataset to include in the test split; default is 0.2.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_knn_regression	<i>Knn regression</i>
--------------------	-----------------------

Description

Performs a supervised k-nearest neighbour regression using training site points and predictor rasters.

Usage

```
wbt_knn_regression(
  inputs,
  training,
  field,
  scaling = "Normalize",
  output = NULL,
  k = 5,
  weight = TRUE,
  test_proportion = 0.2,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

inputs	Names of the input predictor rasters.
training	Name of the input training site points Shapefile.
field	Name of the attribute containing response variable name data.
scaling	Scaling method for predictors. Options include 'None', 'Normalize', and 'Standardize'.
output	Name of the output raster file.
k	k-parameter, which determines the number of nearest neighbours used.
weight	Use distance weighting?.
test_proportion	The proportion of the dataset to include in the test split; default is 0.2.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

```
wbt_ks_test_for_normality
      Ks test for normality
```

Description

Evaluates whether the values in a raster are normally distributed.

Usage

```
wbt_ks_test_for_normality(
  input,
  output,
  num_samples = NULL,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

input	Input raster file.
output	Output HTML file.
num_samples	Number of samples. Leave blank to use whole image.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_k_means_clustering

K means clustering

Description

Performs a k-means clustering operation on a multi-spectral dataset.

Usage

```
wbt_k_means_clustering(  
  inputs,  
  output,  
  classes,  
  out_html = NULL,  
  max_iterations = 10,  
  class_change = 2,  
  initialize = "diagonal",  
  min_class_size = 10,  
  wd = NULL,  
  verbose_mode = FALSE,  
  compress_rasters = FALSE,  
  command_only = FALSE  
)
```

Arguments

inputs	Input raster files.
output	Output raster file.
classes	Number of classes.
out_html	Output HTML report file.
max_iterations	Maximum number of iterations.
class_change	Minimum percent of cells changed between iterations before completion.
initialize	How to initialize cluster centres?.
min_class_size	Minimum class size, in pixels.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_k_nearest_mean_filter
K nearest mean filter

Description

A k-nearest mean filter is a type of edge-preserving smoothing filter.

Usage

```
wbt_k_nearest_mean_filter(  
  input,  
  output,  
  filterx = 11,  
  filtery = 11,  
  k = 5,  
  wd = NULL,  
  verbose_mode = FALSE,  
  compress_rasters = FALSE,  
  command_only = FALSE  
)
```

Arguments

input	Input raster file.
output	Output raster file.
filterx	Size of the filter kernel in the x-direction.
filtery	Size of the filter kernel in the y-direction.
k	k-value in pixels; this is the number of nearest-valued neighbours to use.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_laplacian_filter *Laplacian filter*

Description

Performs a Laplacian filter on an image.

Usage

```
wbt_laplacian_filter(
  input,
  output,
  variant = "3x3(1)",
  clip = 0,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

input	Input raster file.
output	Output raster file.
variant	Optional variant value. Options include 3x3(1), 3x3(2), 3x3(3), 3x3(4), 5x5(1), and 5x5(2) (default is 3x3(1)).

clip	Optional amount to clip the distribution tails by, in percent.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_laplacian_of_gaussian_filter
Laplacian of gaussian filter

Description

Performs a Laplacian-of-Gaussian (LoG) filter on an image.

Usage

```
wbt_laplacian_of_gaussian_filter(  
  input,  
  output,  
  sigma = 0.75,  
  wd = NULL,  
  verbose_mode = FALSE,  
  compress_rasters = FALSE,  
  command_only = FALSE  
)
```

Arguments

input	Input raster file.
output	Output raster file.
sigma	Standard deviation in pixels.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

<code>wbt_las_to_ascii</code>	<i>Las to ascii</i>
-------------------------------	---------------------

Description

Converts one or more LAS files into ASCII text files.

Usage

```
wbt_las_to_ascii(  
  inputs,  
  wd = NULL,  
  verbose_mode = FALSE,  
  compress_rasters = FALSE,  
  command_only = FALSE  
)
```

Arguments

<code>inputs</code>	Input LiDAR files.
<code>wd</code>	Changes the working directory.
<code>verbose_mode</code>	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
<code>compress_rasters</code>	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
<code>command_only</code>	Return command that would be executed by <code>system()</code> rather than running tool.

Value

Returns the tool text outputs.

wbt_las_to_laz	<i>Las to laz</i>
----------------	-------------------

Description

This tool converts one or more LAS files into the LAZ format.

Usage

```
wbt_las_to_laz(
    input,
    output = NULL,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input	Name of the input LAS files (leave blank to use all LAS files in WorkingDirectory).
output	Output LAZ file (including extension).
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_las_to_multipoint_shapefile	<i>Las to multipoint shapefile</i>
---------------------------------	------------------------------------

Description

Converts one or more LAS files into MultipointZ vector Shapefiles. When the input parameter is not specified, the tool grids all LAS files contained within the working directory.

Usage

```
wbt_las_to_multipoint_shapefile(
    input,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input	Input LiDAR file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_las_to_shapefile *Las to shapefile*

Description

Converts one or more LAS files into a vector Shapefile of POINT ShapeType.

Usage

```
wbt_las_to_shapefile(
    input,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input	Input LiDAR file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_las_to_zlidar	<i>Las to zlidar</i>
-------------------	----------------------

Description

Converts one or more LAS files into the zlidar compressed LiDAR data format.

Usage

```
wbt_las_to_zlidar(
  inputs = NULL,
  outdir = NULL,
  compress = "brotli",
  level = 5,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

inputs	Input LAS files.
outdir	Output directory into which zlidar files are created. If unspecified, it is assumed to be the same as the inputs.
compress	Compression method, including 'brotli' and 'deflate'.
level	Compression level (1-9).
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.

`compress_rasters` Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.

`command_only` Return command that would be executed by `system()` rather than running tool.

Value

Returns the tool text outputs.

`wbt_layer_footprint` *Layer footprint*

Description

Creates a vector polygon footprint of the area covered by a raster grid or vector layer.

Usage

```
wbt_layer_footprint(
    input,
    output,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

`input` Input raster or vector file.

`output` Output vector polygon file.

`wd` Changes the working directory.

`verbose_mode` Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.

`compress_rasters` Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.

`command_only` Return command that would be executed by `system()` rather than running tool.

Value

Returns the tool text outputs.

wbt_laz_to_las	<i>Laz to las</i>
----------------	-------------------

Description

This tool converts one or more LAZ files into the LAS format.

Usage

```
wbt_laz_to_las(
    input,
    output = NULL,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input	Name of the input LAZ files (leave blank to use all LAZ files in WorkingDirectory).
output	Output LAS file (including extension).
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_lee_sigma_filter	<i>Lee sigma filter</i>
----------------------	-------------------------

Description

Performs a Lee (Sigma) smoothing filter on an image.

Usage

```
wbt_lee_sigma_filter(
    input,
    output,
    filterx = 11,
    filtery = 11,
    sigma = 10,
    m = 5,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input	Input raster file.
output	Output raster file.
filterx	Size of the filter kernel in the x-direction.
filtery	Size of the filter kernel in the y-direction.
sigma	Sigma value should be related to the standard deviation of the distribution of image speckle noise.
m	M-threshold value the minimum allowable number of pixels within the intensity range.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_length_of_upstream_channels

Length of upstream channels

Description

Calculates the total length of channels upstream.

Usage

```
wbt_length_of_upstream_channels(
    d8_pntr,
    streams,
    output,
    esri_pntr = FALSE,
    zero_background = FALSE,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

d8_pntr	Input raster D8 pointer file.
streams	Input raster streams file.
output	Output raster file.
esri_pntr	D8 pointer uses the ESRI style scheme.
zero_background	Flag indicating whether a background value of zero should be used.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_less_than	<i>Less than</i>
---------------	------------------

Description

Performs a less-than comparison operation on two rasters or a raster and a constant value.

Usage

```
wbt_less_than(
  input1,
  input2,
  output,
  incl_equals = FALSE,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

input1	Input raster file or constant value.
input2	Input raster file or constant value.
output	Output raster file.
incl_equals	Perform a less-than-or-equal-to operation.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_license	<i>License information for WhiteboxTools</i>
-------------	--

Description

License information for WhiteboxTools

Usage

```
wbt_license()
```

Value

Returns the license information for WhiteboxTools as an R character vector.

Examples

```
## Not run:  
wbt_license()  
  
## End(Not run)
```

```
wbt_lidar_block_maximum  
Lidar block maximum
```

Description

Creates a block-maximum raster from an input LAS file. When the input/output parameters are not specified, the tool grids all LAS files contained within the working directory.

Usage

```
wbt_lidar_block_maximum(  
  input,  
  output = NULL,  
  resolution = 1,  
  wd = NULL,  
  verbose_mode = FALSE,  
  compress_rasters = FALSE,  
  command_only = FALSE  
)
```

Arguments

input	Input LiDAR file.
output	Output file.
resolution	Output raster's grid resolution.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

`wbt_lidar_block_minimum`*Lidar block minimum*

Description

Creates a block-minimum raster from an input LAS file. When the input/output parameters are not specified, the tool grids all LAS files contained within the working directory.

Usage

```
wbt_lidar_block_minimum(  
    input,  
    output = NULL,  
    resolution = 1,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

<code>input</code>	Input LiDAR file.
<code>output</code>	Output file.
<code>resolution</code>	Output raster's grid resolution.
<code>wd</code>	Changes the working directory.
<code>verbose_mode</code>	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
<code>compress_rasters</code>	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
<code>command_only</code>	Return command that would be executed by <code>system()</code> rather than running tool.

Value

Returns the tool text outputs.

```
wbt_lidar_classify_subset
    Lidar classify subset
```

Description

Classifies the values in one LiDAR point cloud that correspond with points in a subset cloud.

Usage

```
wbt_lidar_classify_subset(
    base,
    subset,
    output,
    subset_class,
    nonsubset_class = NULL,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

base	Input base LiDAR file.
subset	Input subset LiDAR file.
output	Output LiDAR file.
subset_class	Subset point class value (must be 0-18; see LAS specifications).
nonsubset_class	Non-subset point class value (must be 0-18; see LAS specifications).
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_lidar_colourize *Lidar colourize*

Description

Adds the red-green-blue colour fields of a LiDAR (LAS) file based on an input image.

Usage

```
wbt_lidar_colourize(  
    in_lidar,  
    in_image,  
    output,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

<code>in_lidar</code>	Input LiDAR file.
<code>in_image</code>	Input colour image file.
<code>output</code>	Output LiDAR file.
<code>wd</code>	Changes the working directory.
<code>verbose_mode</code>	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
<code>compress_rasters</code>	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
<code>command_only</code>	Return command that would be executed by <code>system()</code> rather than running tool.

Value

Returns the tool text outputs.

wbt_lidar_contour *Lidar contour*

Description

This tool creates a vector contour coverage from an input LiDAR point file.

Usage

```
wbt_lidar_contour(
  input,
  output = NULL,
  interval = 10,
  smooth = 5,
  parameter = "elevation",
  returns = "all",
  exclude_cls = NULL,
  minz = NULL,
  maxz = NULL,
  max_triangle_edge_length = NULL,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

input	Name of the input LiDAR points.
output	Name of the output vector lines file.
interval	Contour interval.
smooth	Smoothing filter size (in num. points), e.g. 3, 5, 7, 9, 11.
parameter	Interpolation parameter; options are 'elevation' (default), 'intensity', 'user_data'.
returns	Point return types to include; options are 'all' (default), 'last', 'first'.
exclude_cls	Optional exclude classes from interpolation; Valid class values range from 0 to 18, based on LAS specifications. Example, <code>-exclude_cls='3,4,5,6,7,18'</code> .
minz	Optional minimum elevation for inclusion in interpolation.
maxz	Optional maximum elevation for inclusion in interpolation.
max_triangle_edge_length	Optional maximum triangle edge length; triangles larger than this size will not be gridded.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.

`compress_rasters` Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.

`command_only` Return command that would be executed by `system()` rather than running tool.

Value

Returns the tool text outputs.

`wbt_lidar_digital_surface_model`
Lidar digital surface model

Description

Creates a top-surface digital surface model (DSM) from a LiDAR point cloud.

Usage

```
wbt_lidar_digital_surface_model(  
  input,  
  output = NULL,  
  resolution = 1,  
  radius = 0.5,  
  minz = NULL,  
  maxz = NULL,  
  max_triangle_edge_length = NULL,  
  wd = NULL,  
  verbose_mode = FALSE,  
  compress_rasters = FALSE,  
  command_only = FALSE  
)
```

Arguments

`input` Input LiDAR file (including extension).

`output` Output raster file (including extension).

`resolution` Output raster's grid resolution.

`radius` Search Radius.

`minz` Optional minimum elevation for inclusion in interpolation.

`maxz` Optional maximum elevation for inclusion in interpolation.

`max_triangle_edge_length` Optional maximum triangle edge length; triangles larger than this size will not be gridded.

`wd` Changes the working directory.

verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_lidar_elevation_slice

Lidar elevation slice

Description

Outputs all of the points within a LiDAR (LAS) point file that lie between a specified elevation range.

Usage

```
wbt_lidar_elevation_slice(  
  input,  
  output,  
  minz = NULL,  
  maxz = NULL,  
  cls = FALSE,  
  inclassval = 2,  
  outclassval = 1,  
  wd = NULL,  
  verbose_mode = FALSE,  
  compress_rasters = FALSE,  
  command_only = FALSE  
)
```

Arguments

input	Input LiDAR file.
output	Output LiDAR file.
minz	Minimum elevation value (optional).
maxz	Maximum elevation value (optional).
cls	Optional boolean flag indicating whether points outside the range should be retained in output but reclassified.
inclassval	Optional parameter specifying the class value assigned to points within the slice.

outclassval	Optional parameter specifying the class value assigned to points within the slice.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_lidar_ground_point_filter
Lidar ground point filter

Description

Identifies ground points within LiDAR dataset using a slope-based method.

Usage

```
wbt_lidar_ground_point_filter(  
  input,  
  output,  
  radius = 2,  
  min_neighbours = 0,  
  slope_threshold = 45,  
  height_threshold = 1,  
  classify = TRUE,  
  slope_norm = TRUE,  
  height_above_ground = FALSE,  
  wd = NULL,  
  verbose_mode = FALSE,  
  compress_rasters = FALSE,  
  command_only = FALSE  
)
```

Arguments

input	Input LiDAR file.
output	Output LiDAR file.
radius	Search Radius.

min_neighbours	The minimum number of neighbouring points within search areas. If fewer points than this threshold are identified during the fixed-radius search, a subsequent kNN search is performed to identify the k number of neighbours.
slope_threshold	Maximum inter-point slope to be considered an off-terrain point.
height_threshold	Inter-point height difference to be considered an off-terrain point.
classify	Classify points as ground (2) or off-ground (1).
slope_norm	Perform initial ground slope normalization?.
height_above_ground	Transform output to height above average ground elevation?.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_lidar_hex_binning *Lidar hex binning*

Description

Hex-bins a set of LiDAR points.

Usage

```
wbt_lidar_hex_binning(  
  input,  
  output,  
  width,  
  orientation = "horizontal",  
  wd = NULL,  
  verbose_mode = FALSE,  
  compress_rasters = FALSE,  
  command_only = FALSE  
)
```

Arguments

input	Input base file.
output	Output vector polygon file.
width	The grid cell width.
orientation	Grid Orientation, 'horizontal' or 'vertical'.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_lidar_hillshade *Lidar hillshade*

Description

Calculates a hillshade value for points within a LAS file and stores these data in the RGB field.

Usage

```
wbt_lidar_hillshade(
  input,
  output,
  azimuth = 315,
  altitude = 30,
  radius = 1,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

input	Input LiDAR file.
output	Output file.
azimuth	Illumination source azimuth in degrees.
altitude	Illumination source altitude in degrees.

radius	Search Radius.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_lidar_histogram *Lidar histogram*

Description

Creates a histogram of LiDAR data.

Usage

```
wbt_lidar_histogram(
  input,
  output,
  parameter = "elevation",
  clip = 1,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

input	Input LiDAR file.
output	Output HTML file (default name will be based on input file if unspecified).
parameter	Parameter; options are 'elevation' (default), 'intensity', 'scan angle', 'class', 'time'.
clip	Amount to clip distribution tails (in percent).
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_lidar_idw_interpolation
Lidar idw interpolation

Description

Interpolates LAS files using an inverse-distance weighted (IDW) scheme. When the input/output parameters are not specified, the tool interpolates all LAS files contained within the working directory.

Usage

```
wbt_lidar_idw_interpolation(
    input,
    output = NULL,
    parameter = "elevation",
    returns = "all",
    resolution = 1,
    weight = 1,
    radius = 2.5,
    exclude_cls = NULL,
    minz = NULL,
    maxz = NULL,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input	Input LiDAR file (including extension).
output	Output raster file (including extension).
parameter	Interpolation parameter; options are 'elevation' (default), 'intensity', 'class', 'return_number', 'number_of_returns', 'scan angle', 'rgb', 'user data'.
returns	Point return types to include; options are 'all' (default), 'last', 'first'.
resolution	Output raster's grid resolution.
weight	IDW weight value.
radius	Search Radius.
exclude_cls	Optional exclude classes from interpolation; Valid class values range from 0 to 18, based on LAS specifications. Example, <code>-exclude_cls='3,4,5,6,7,18'</code> .

minz	Optional minimum elevation for inclusion in interpolation.
maxz	Optional maximum elevation for inclusion in interpolation.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_lidar_info	<i>Lidar info</i>
----------------	-------------------

Description

Prints information about a LiDAR (LAS) dataset, including header, point return frequency, and classification data and information about the variable length records (VLRs) and geokeys.

Usage

```
wbt_lidar_info(
  input,
  output = NULL,
  vlr = TRUE,
  geokeys = TRUE,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

input	Input LiDAR file.
output	Output HTML file for summary report.
vlr	Flag indicating whether or not to print the variable length records (VLRs).
geokeys	Flag indicating whether or not to print the geokeys.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.

`compress_rasters` Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.

`command_only` Return command that would be executed by `system()` rather than running tool.

Value

Returns the tool text outputs.

wbt_lidar_join	<i>Lidar join</i>
----------------	-------------------

Description

Joins multiple LiDAR (LAS) files into a single LAS file.

Usage

```
wbt_lidar_join(
  inputs,
  output,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

`inputs` Input LiDAR files.

`output` Output LiDAR file.

`wd` Changes the working directory.

`verbose_mode` Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.

`compress_rasters` Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.

`command_only` Return command that would be executed by `system()` rather than running tool.

Value

Returns the tool text outputs.

wbt_lidar_kappa_index *Lidar kappa index*

Description

Performs a kappa index of agreement (KIA) analysis on the classifications of two LAS files.

Usage

```
wbt_lidar_kappa_index(  
    input1,  
    input2,  
    output,  
    class_accuracy,  
    resolution = 1,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

input1	Input LiDAR classification file.
input2	Input LiDAR reference file.
output	Output HTML file.
class_accuracy	Output classification accuracy raster file.
resolution	Output raster's grid resolution.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_lidar_nearest_neighbour_gridding

Lidar nearest neighbour gridding

Description

Grids LiDAR files using nearest-neighbour scheme. When the input/output parameters are not specified, the tool grids all LAS files contained within the working directory.

Usage

```
wbt_lidar_nearest_neighbour_gridding(
    input,
    output = NULL,
    parameter = "elevation",
    returns = "all",
    resolution = 1,
    radius = 2.5,
    exclude_cls = NULL,
    minz = NULL,
    maxz = NULL,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input	Input LiDAR file (including extension).
output	Output raster file (including extension).
parameter	Interpolation parameter; options are 'elevation' (default), 'intensity', 'class', 'return_number', 'number_of_returns', 'scan angle', 'rgb', 'user data'.
returns	Point return types to include; options are 'all' (default), 'last', 'first'.
resolution	Output raster's grid resolution.
radius	Search Radius.
exclude_cls	Optional exclude classes from interpolation; Valid class values range from 0 to 18, based on LAS specifications. Example, <code>-exclude_cls='3,4,5,6,7,18'</code> .
minz	Optional minimum elevation for inclusion in interpolation.
maxz	Optional maximum elevation for inclusion in interpolation.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.

compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_lidar_point_density
Lidar point density

Description

Calculates the spatial pattern of point density for a LiDAR data set. When the input/output parameters are not specified, the tool grids all LAS files contained within the working directory.

Usage

```
wbt_lidar_point_density(  
  input,  
  output = NULL,  
  returns = "all",  
  resolution = 1,  
  radius = 2.5,  
  exclude_cls = NULL,  
  minz = NULL,  
  maxz = NULL,  
  wd = NULL,  
  verbose_mode = FALSE,  
  compress_rasters = FALSE,  
  command_only = FALSE  
)
```

Arguments

input	Input LiDAR file (including extension).
output	Output raster file (including extension).
returns	Point return types to include; options are 'all' (default), 'last', 'first'.
resolution	Output raster's grid resolution.
radius	Search radius.
exclude_cls	Optional exclude classes from interpolation; Valid class values range from 0 to 18, based on LAS specifications. Example, <code>-exclude_cls='3,4,5,6,7,18'</code> .
minz	Optional minimum elevation for inclusion in interpolation.

maxz	Optional maximum elevation for inclusion in interpolation.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_lidar_point_return_analysis
Lidar point return analysis

Description

This tool performs a quality control check on the return values of points in a LiDAR file.

Usage

```
wbt_lidar_point_return_analysis(  
  input,  
  output = NULL,  
  wd = NULL,  
  verbose_mode = FALSE,  
  compress_rasters = FALSE,  
  command_only = FALSE  
)
```

Arguments

input	Name of the input LiDAR points.
output	Name of the output LiDAR points.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_lidar_point_stats *Lidar point stats*

Description

Creates several rasters summarizing the distribution of LAS point data. When the input/output parameters are not specified, the tool works on all LAS files contained within the working directory.

Usage

```
wbt_lidar_point_stats(  
    input,  
    resolution = 1,  
    num_points = TRUE,  
    num_pulses = FALSE,  
    avg_points_per_pulse = TRUE,  
    z_range = FALSE,  
    intensity_range = FALSE,  
    predom_class = FALSE,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

input	Input LiDAR file.
resolution	Output raster's grid resolution.
num_points	Flag indicating whether or not to output the number of points (returns) raster.
num_pulses	Flag indicating whether or not to output the number of pulses raster.
avg_points_per_pulse	Flag indicating whether or not to output the average number of points (returns) per pulse raster.
z_range	Flag indicating whether or not to output the elevation range raster.
intensity_range	Flag indicating whether or not to output the intensity range raster.
predom_class	Flag indicating whether or not to output the predominant classification raster.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_lidar_ransac_planes

Lidar ransac planes

Description

Performs a RANSAC analysis to identify points within a LiDAR point cloud that belong to linear planes.

Usage

```
wbt_lidar_ransac_planes(
    input,
    output,
    radius = 2,
    num_iter = 50,
    num_samples = 5,
    threshold = 0.35,
    model_size = 8,
    max_slope = 80,
    classify = FALSE,
    last_returns = FALSE,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input	Input LiDAR file.
output	Output LiDAR file.
radius	Search Radius.
num_iter	Number of iterations.
num_samples	Number of sample points on which to build the model.
threshold	Threshold used to determine inlier points.
model_size	Acceptable model size.
max_slope	Maximum planar slope.
classify	Classify points as ground (2) or off-ground (1).
last_returns	Only include last- and only-return points.

wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_lidar_rbf_interpolation
Lidar rbf interpolation

Description

Interpolates LAS files using a radial basis function (RBF) scheme. When the input/output parameters are not specified, the tool interpolates all LAS files contained within the working directory.

Usage

```
wbt_lidar_rbf_interpolation(
  input,
  output = NULL,
  parameter = "elevation",
  returns = "all",
  resolution = 1,
  num_points = 20,
  exclude_cls = NULL,
  minz = NULL,
  maxz = NULL,
  func_type = "ThinPlateSpline",
  poly_order = "none",
  weight = 5,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

input	Input LiDAR file (including extension).
output	Output raster file (including extension).
parameter	Interpolation parameter; options are 'elevation' (default), 'intensity', 'class', 'return_number', 'number_of_returns', 'scan angle', 'rgb', 'user data'.
returns	Point return types to include; options are 'all' (default), 'last', 'first'.
resolution	Output raster's grid resolution.
num_points	Number of points.
exclude_cls	Optional exclude classes from interpolation; Valid class values range from 0 to 18, based on LAS specifications. Example, <code>-exclude_cls='3,4,5,6,7,18'</code> .
minz	Optional minimum elevation for inclusion in interpolation.
maxz	Optional maximum elevation for inclusion in interpolation.
func_type	Radial basis function type; options are 'ThinPlateSpline' (default), 'PolyHarmonic', 'Gaussian', 'MultiQuadric', 'InverseMultiQuadric'.
poly_order	Polynomial order; options are 'none' (default), 'constant', 'affine'.
weight	Weight parameter used in basis function.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by <code>system()</code> rather than running tool.

Value

Returns the tool text outputs.

wbt_lidar_remove_duplicates
Lidar remove duplicates

Description

Removes duplicate points from a LiDAR data set.

Usage

```
wbt_lidar_remove_duplicates(
    input,
    output,
    include_z = FALSE,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input	Input LiDAR file.
output	Output LiDAR file.
include_z	Include z-values in point comparison?.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_lidar_remove_outliers
Lidar remove outliers

Description

Removes outliers (high and low points) in a LiDAR point cloud.

Usage

```
wbt_lidar_remove_outliers(
    input,
    output,
    radius = 2,
    elev_diff = 50,
    use_median = FALSE,
    classify = TRUE,
```

```

    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)

```

Arguments

input	Input LiDAR file.
output	Output LiDAR file.
radius	Search Radius.
elev_diff	Max. elevation difference.
use_median	Optional flag indicating whether to use the difference from median elevation rather than mean.
classify	Classify points as ground (2) or off-ground (1).
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

```

wbt_lidar_rooftop_analysis
    Lidar rooftop analysis

```

Description

Identifies roof segments in a LiDAR point cloud.

Usage

```

wbt_lidar_rooftop_analysis(
  buildings,
  output,
  input = NULL,
  radius = 2,
  num_iter = 50,
  num_samples = 10,
  threshold = 0.15,

```



```

    model_size = 15,
    max_slope = 65,
    norm_diff = 10,
    azimuth = 180,
    altitude = 30,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)

```

Arguments

buildings	Input vector build footprint polygons file.
output	Output vector polygon file.
input	Input LiDAR file.
radius	Search Radius.
num_iter	Number of iterations.
num_samples	Number of sample points on which to build the model.
threshold	Threshold used to determine inlier points (in elevation units).
model_size	Acceptable model size, in points.
max_slope	Maximum planar slope, in degrees.
norm_diff	Maximum difference in normal vectors, in degrees.
azimuth	Illumination source azimuth, in degrees.
altitude	Illumination source altitude in degrees.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

`wbt_lidar_segmentation`*Lidar segmentation*

Description

Segments a LiDAR point cloud based on differences in the orientation of fitted planar surfaces and point proximity.

Usage

```
wbt_lidar_segmentation(  
    input,  
    output,  
    radius = 2,  
    num_iter = 50,  
    num_samples = 10,  
    threshold = 0.15,  
    model_size = 15,  
    max_slope = 80,  
    norm_diff = 10,  
    maxzdiff = 1,  
    classes = FALSE,  
    ground = FALSE,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

<code>input</code>	Input LiDAR file.
<code>output</code>	Output LiDAR file.
<code>radius</code>	Search Radius.
<code>num_iter</code>	Number of iterations.
<code>num_samples</code>	Number of sample points on which to build the model.
<code>threshold</code>	Threshold used to determine inlier points.
<code>model_size</code>	Acceptable model size.
<code>max_slope</code>	Maximum planar slope.
<code>norm_diff</code>	Maximum difference in normal vectors, in degrees.
<code>maxzdiff</code>	Maximum difference in elevation (z units) between neighbouring points of the same segment.
<code>classes</code>	Segments don't cross class boundaries.

ground	Classify the largest segment as ground points?.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_lidar_segmentation_based_filter
Lidar segmentation based filter

Description

Identifies ground points within LiDAR point clouds using a segmentation based approach.

Usage

```
wbt_lidar_segmentation_based_filter(
  input,
  output,
  radius = 5,
  norm_diff = 2,
  maxzdiff = 1,
  classify = FALSE,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

input	Input LiDAR file.
output	Output file.
radius	Search Radius.
norm_diff	Maximum difference in normal vectors, in degrees.
maxzdiff	Maximum difference in elevation (z units) between neighbouring points of the same segment.
classify	Classify points as ground (2) or off-ground (1).

wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_lidar_shift	<i>Lidar shift</i>
-----------------	--------------------

Description

Shifts the x,y,z coordinates of a LiDAR file.

Usage

```
wbt_lidar_shift(
  input,
  output,
  x_shift = "",
  y_shift = "",
  z_shift = "",
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

input	Name of the input LiDAR points.
output	Name of the output LiDAR points.
x_shift	x-shift value, blank for none.
y_shift	y-shift value, blank for none.
z_shift	z-shift value, blank for none.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

```
wbt_lidar_sibson_interpolation
    Lidar sibson interpolation
```

Description

This tool interpolates one or more LiDAR tiles using Sibson's natural neighbour method.

Usage

```
wbt_lidar_sibson_interpolation(
    input,
    output = NULL,
    parameter = "elevation",
    returns = "all",
    resolution = 1,
    exclude_cls = NULL,
    minz = NULL,
    maxz = NULL,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input	Name of the input LiDAR points (leave blank to use all files in WorkingDirectory).
output	Output raster file (including extension).
parameter	Interpolation parameter; options are 'elevation' (default), 'intensity', 'class', 'return_number', 'number_of_returns', 'scan angle', 'user_data'.
returns	Point return types to include; options are 'all' (default), 'last', 'first'.
resolution	Output raster's grid resolution.
exclude_cls	Optional exclude classes from interpolation; Valid class values range from 0 to 18, based on LAS specifications. Example, <code>-exclude_cls='3,4,5,6,7,18'</code> .
minz	Optional minimum elevation for inclusion in interpolation.
maxz	Optional maximum elevation for inclusion in interpolation.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.

`compress_rasters` Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.

`command_only` Return command that would be executed by `system()` rather than running tool.

Value

Returns the tool text outputs.

`wbt_lidar_sort_by_time`

Lidar sort by time

Description

This sorts the points in a LiDAR file by the GPS time.

Usage

```
wbt_lidar_sort_by_time(
    input,
    output,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

`input` Name of the input LiDAR points.

`output` Name of the output LiDAR points.

`wd` Changes the working directory.

`verbose_mode` Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.

`compress_rasters` Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.

`command_only` Return command that would be executed by `system()` rather than running tool.

Value

Returns the tool text outputs.

wbt_lidar_thin	<i>Lidar thin</i>
----------------	-------------------

Description

Thins a LiDAR point cloud, reducing point density.

Usage

```
wbt_lidar_thin(
    input,
    output,
    resolution = 2,
    method = "lowest",
    save_filtered = FALSE,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input	Input LiDAR file.
output	Output LiDAR file.
resolution	The size of the square area used to evaluate nearby points in the LiDAR data.
method	Point selection method; options are 'first', 'last', 'lowest' (default), 'highest', 'nearest'.
save_filtered	Save filtered points to separate file?.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_lidar_thin_high_density
Lidar thin high density

Description

Thins points from high density areas within a LiDAR point cloud.

Usage

```
wbt_lidar_thin_high_density(  
    input,  
    output,  
    density,  
    resolution = 1,  
    save_filtered = FALSE,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

input	Input LiDAR file.
output	Output LiDAR file.
density	Max. point density (points / m ³).
resolution	Output raster's grid resolution.
save_filtered	Save filtered points to separate file?.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_lidar_tile	<i>Lidar tile</i>
----------------	-------------------

Description

Tiles a LiDAR LAS file into multiple LAS files.

Usage

```
wbt_lidar_tile(
  input,
  width = 1000,
  height = 1000,
  origin_x = 0,
  origin_y = 0,
  min_points = 2,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

input	Input LiDAR file.
width	Width of tiles in the X dimension; default 1000.0.
height	Height of tiles in the Y dimension.
origin_x	Origin point X coordinate for tile grid.
origin_y	Origin point Y coordinate for tile grid.
min_points	Minimum number of points contained in a tile for it to be saved.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

`wbt_lidar_tile_footprint`*Lidar tile footprint*

Description

Creates a vector polygon of the convex hull of a LiDAR point cloud. When the input/output parameters are not specified, the tool works with all LAS files contained within the working directory.

Usage

```
wbt_lidar_tile_footprint(  
    input,  
    output,  
    hull = FALSE,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

<code>input</code>	Input LiDAR file.
<code>output</code>	Output vector polygon file.
<code>hull</code>	Identify the convex hull around points.
<code>wd</code>	Changes the working directory.
<code>verbose_mode</code>	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
<code>compress_rasters</code>	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
<code>command_only</code>	Return command that would be executed by <code>system()</code> rather than running tool.

Value

Returns the tool text outputs.

```
wbt_lidar_tin_gridding
```

Lidar tin gridding

Description

Creates a raster grid based on a Delaunay triangular irregular network (TIN) fitted to LiDAR points.

Usage

```
wbt_lidar_tin_gridding(
  input,
  output = NULL,
  parameter = "elevation",
  returns = "all",
  resolution = 1,
  exclude_cls = "7,18",
  minz = NULL,
  maxz = NULL,
  max_triangle_edge_length = NULL,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

input	Input LiDAR file (including extension).
output	Output raster file (including extension).
parameter	Interpolation parameter; options are 'elevation' (default), 'intensity', 'class', 'return_number', 'number_of_returns', 'scan_angle', 'rgb', 'user_data'.
returns	Point return types to include; options are 'all' (default), 'last', 'first'.
resolution	Output raster's grid resolution.
exclude_cls	Optional exclude classes from interpolation; Valid class values range from 0 to 18, based on LAS specifications. Example, <code>-exclude_cls='3,4,5,6,7,18'</code> .
minz	Optional minimum elevation for inclusion in interpolation.
maxz	Optional maximum elevation for inclusion in interpolation.
max_triangle_edge_length	Optional maximum triangle edge length; triangles larger than this size will not be gridded.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.

compress_rasters Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.

command_only Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_lidar_tophat_transform
Lidar tophat transform

Description

Performs a white top-hat transform on a Lidar dataset; as an estimate of height above ground, this is useful for modelling the vegetation canopy.

Usage

```
wbt_lidar_tophat_transform(
  input,
  output,
  radius = 1,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

input Input LiDAR file.

output Output LiDAR file.

radius Search Radius.

wd Changes the working directory.

verbose_mode Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.

compress_rasters Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.

command_only Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_linearity_index *Linearity index*

Description

Calculates the linearity index for vector polygons.

Usage

```
wbt_linearity_index(  
    input,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

input	Input vector polygon file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_lines_to_polygons *Lines to polygons*

Description

Converts vector polylines to polygons.

Usage

```
wbt_lines_to_polygons(
    input,
    output,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input	Input vector line file.
output	Output vector polygon file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

```
wbt_line_detection_filter
    Line detection filter
```

Description

Performs a line-detection filter on an image.

Usage

```
wbt_line_detection_filter(
    input,
    output,
    variant = "vertical",
    absvals = FALSE,
    clip = 0,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input	Input raster file.
output	Output raster file.
variant	Optional variant value. Options include 'v' (vertical), 'h' (horizontal), '45', and '135' (default is 'v').
absvals	Optional flag indicating whether outputs should be absolute values.
clip	Optional amount to clip the distribution tails by, in percent.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_line_intersections
Line intersections

Description

Identifies points where the features of two vector line layers intersect.

Usage

```
wbt_line_intersections(
  input1,
  input2,
  output,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

input1	Input vector polyline file.
input2	Input vector polyline file.
output	Output vector point file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_line_thinning	<i>Line thinning</i>
-------------------	----------------------

Description

Performs line thinning a on Boolean raster image; intended to be used with the RemoveSpurs tool.

Usage

```
wbt_line_thinning(
  input,
  output,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

input	Input raster file.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_list_tools	<i>All available tools in WhiteboxTools</i>
----------------	---

Description

All available tools in WhiteboxTools

Usage

```
wbt_list_tools(keywords = "")
```

Arguments

keywords	Keywords may be used to search available tools. Default "" returns all available tools.
----------	---

Value

Return all available tools in WhiteboxTools that contain the keywords.

Examples

```
## Not run:
wbt_list_tools("lidar")

## End(Not run)
```

wbt_list_unique_values	<i>List unique values</i>
------------------------	---------------------------

Description

Lists the unique values contained in a field within a vector's attribute table.

Usage

```
wbt_list_unique_values(
  input,
  field,
  output,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

input	Input raster file.
field	Input field name in attribute table.
output	Output HTML file (default name will be based on input file if unspecified).
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_ln	<i>Ln</i>
--------	-----------

Description

Returns the natural logarithm of values in a raster.

Usage

```
wbt_ln(
  input,
  output,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

input	Input raster file.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

```
wbt_local_hypsometric_analysis
    Local hypsometric analysis
```

Description

This tool calculates a local, neighbourhood-based hypsometric integral raster.

Usage

```
wbt_local_hypsometric_analysis(
    input,
    out_mag,
    out_scale,
    min_scale = 4,
    step = 1,
    num_steps = 10,
    step_nonlinearity = 1,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input	Name of the input raster DEM file.
out_mag	Name of the openness output raster file.
out_scale	Name of the openness output raster file.
min_scale	Minimum search neighbourhood radius in grid cells.
step	Step size as any positive non-zero integer.
num_steps	Number of steps.
step_nonlinearity	Step nonlinearity factor (1.0-2.0 is typical).
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_local_quadratic_regression
Local quadratic regression

Description

This tool is an implementation of the constrained quadratic regression algorithm using a flexible window size described in Wood (1996).

Usage

```
wbt_local_quadratic_regression(  
    dem,  
    output,  
    filter = 3,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

dem	Name of the input DEM raster file.
output	Name of the output raster file.
filter	Edge length of the filter kernel.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_log10	<i>Log10</i>
-----------	--------------

Description

Returns the base-10 logarithm of values in a raster.

Usage

```
wbt_log10(
    input,
    output,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input	Input raster file.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_log2	<i>Log2</i>
----------	-------------

Description

Returns the base-2 logarithm of values in a raster.

Usage

```
wbt_log2(
  input,
  output,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

input	Input raster file.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by <code>system()</code> rather than running tool.

Value

Returns the tool text outputs.

wbt_logistic_regression
Logistic regression

Description

Performs a logistic regression analysis using training site polygons/points and predictor rasters.

Usage

```
wbt_logistic_regression(
  inputs,
  training,
  field,
  scaling = "Normalize",
  output = NULL,
  test_proportion = 0.2,
  wd = NULL,
  verbose_mode = FALSE,
```

```

    compress_rasters = FALSE,
    command_only = FALSE
)

```

Arguments

inputs	Names of the input predictor rasters.
training	Name of the input training site polygons/points shapefile.
field	Name of the attribute containing class data.
scaling	Scaling method for predictors. Options include 'None', 'Normalize', and 'Standardize'.
output	Name of the output raster file.
test_proportion	The proportion of the dataset to include in the test split; default is 0.2.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_longest_flowpath *Longest flowpath*

Description

Delineates the longest flowpaths for a group of subbasins or watersheds.

Usage

```

wbt_longest_flowpath(
  dem,
  basins,
  output,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)

```

Arguments

dem	Input raster DEM file.
basins	Input raster basins file.
output	Output vector file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_long_profile	<i>Long profile</i>
------------------	---------------------

Description

Plots the stream longitudinal profiles for one or more rivers.

Usage

```
wbt_long_profile(
  d8_pntr,
  streams,
  dem,
  output,
  esri_pntr = FALSE,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

d8_pntr	Input raster D8 pointer file.
streams	Input raster streams file.
dem	Input raster DEM file.
output	Output HTML file.
esri_pntr	D8 pointer uses the ESRI style scheme.

wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_long_profile_from_points
Long profile from points

Description

Plots the longitudinal profiles from flow-paths initiating from a set of vector points.

Usage

```
wbt_long_profile_from_points(  
  d8_pntr,  
  points,  
  dem,  
  output,  
  esri_pntr = FALSE,  
  wd = NULL,  
  verbose_mode = FALSE,  
  compress_rasters = FALSE,  
  command_only = FALSE  
)
```

Arguments

d8_pntr	Input raster D8 pointer file.
points	Input vector points file.
dem	Input raster DEM file.
output	Output HTML file.
esri_pntr	D8 pointer uses the ESRI style scheme.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.

compress_rasters Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.

command_only Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_lowest_position *Lowest position*

Description

Identifies the stack position of the minimum value within a raster stack on a cell-by-cell basis.

Usage

```
wbt_lowest_position(
  inputs,
  output,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

inputs Input raster files.

output Output raster file.

wd Changes the working directory.

verbose_mode Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.

compress_rasters Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.

command_only Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_low_points_on_headwater_divides
Low points on headwater divides

Description

This tool locates saddle points along ridges within a digital elevation model (DEM).

Usage

```
wbt_low_points_on_headwater_divides(  
    dem,  
    streams,  
    output,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

dem	Name of the input DEM raster file.
streams	Name of the input stream channel raster file.
output	Name of the output vector file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_majority_filter *Majority filter*

Description

Assigns each cell in the output grid the most frequently occurring value (mode) in a moving window centred on each grid cell in the input raster.

Usage

```
wbt_majority_filter(  
    input,  
    output,  
    filterx = 11,  
    filtery = 11,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

input	Input raster file.
output	Output raster file.
filterx	Size of the filter kernel in the x-direction.
filtery	Size of the filter kernel in the y-direction.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_map_off_terrain_objects
Map off terrain objects

Description

Maps off-terrain objects in a digital elevation model (DEM).

Usage

```
wbt_map_off_terrain_objects(  
    dem,  
    output,  
    max_slope = 40,  
    min_size = 1,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

dem	Input raster DEM file.
output	Output raster file.
max_slope	Maximum inter-cell absolute slope.
min_size	Minimum feature size, in grid cells.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_max	<i>Max</i>
---------	------------

Description

Performs a MAX operation on two rasters or a raster and a constant value.

Usage

```
wbt_max(
    input1,
    input2,
    output,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input1	Input raster file or constant value.
input2	Input raster file or constant value.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_maximal_curvature *Maximal curvature*

Description

Calculates a mean curvature raster from an input DEM.

Usage

```
wbt_maximal_curvature(  
    dem,  
    output,  
    log = FALSE,  
    zfactor = NULL,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

dem	Input raster DEM file.
output	Output raster file.
log	Display output values using a log-scale.
zfactor	Optional multiplier for when the vertical and horizontal units are not the same.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_maximum_filter *Maximum filter*

Description

Assigns each cell in the output grid the maximum value in a moving window centred on each grid cell in the input raster.

Usage

```
wbt_maximum_filter(  
    input,  
    output,  
    filterx = 11,  
    filtery = 11,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

input	Input raster file.
output	Output raster file.
filterx	Size of the filter kernel in the x-direction.
filtery	Size of the filter kernel in the y-direction.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_max_absolute_overlay
Max absolute overlay

Description

Evaluates the maximum absolute value for each grid cell from a stack of input rasters.

Usage

```
wbt_max_absolute_overlay(  
    inputs,  
    output,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

inputs	Input raster files.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_max_anisotropy_dev
Max anisotropy dev

Description

Calculates the maximum anisotropy (directionality) in elevation deviation over a range of spatial scales.

Usage

```
wbt_max_anisotropy_dev(
    dem,
    out_mag,
    out_scale,
    max_scale,
    min_scale = 3,
    step = 2,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

dem	Input raster DEM file.
out_mag	Output raster DEVmax magnitude file.
out_scale	Output raster DEVmax scale file.
max_scale	Maximum search neighbourhood radius in grid cells.
min_scale	Minimum search neighbourhood radius in grid cells.
step	Step size as any positive non-zero integer.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_max_anisotropy_dev_signature
Max anisotropy dev signature

Description

Calculates the anisotropy in deviation from mean for points over a range of spatial scales.

Usage

```
wbt_max_anisotropy_dev_signature(
    dem,
    points,
    output,
    max_scale,
    min_scale = 1,
    step = 1,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

dem	Input raster DEM file.
points	Input vector points file.
output	Output HTML file.
max_scale	Maximum search neighbourhood radius in grid cells.
min_scale	Minimum search neighbourhood radius in grid cells.
step	Step size as any positive non-zero integer.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_max_branch_length *Max branch length*

Description

Lindsay and Seibert's (2013) branch length index is used to map drainage divides or ridge lines.

Usage

```
wbt_max_branch_length(
  dem,
  output,
  log = FALSE,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

dem	Input raster DEM file.
output	Output raster file.
log	Optional flag to request the output be log-transformed.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_max_difference_from_mean	<i>Max difference from mean</i>
------------------------------	---------------------------------

Description

Calculates the maximum difference from mean elevation over a range of spatial scales.

Usage

```
wbt_max_difference_from_mean(
  dem,
  out_mag,
  out_scale,
  min_scale,
  max_scale,
  step = 1,
```

```

    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)

```

Arguments

dem	Input raster DEM file.
out_mag	Output raster DIFFmax magnitude file.
out_scale	Output raster DIFFmax scale file.
min_scale	Minimum search neighbourhood radius in grid cells.
max_scale	Maximum search neighbourhood radius in grid cells.
step	Step size as any positive non-zero integer.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

```

wbt_max_downslope_elev_change
    Max downslope elev change

```

Description

Calculates the maximum downslope change in elevation between a grid cell and its eight downslope neighbors.

Usage

```

wbt_max_downslope_elev_change(
  dem,
  output,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)

```

Arguments

dem	Input raster DEM file.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_max_elevation_deviation
Max elevation deviation

Description

Calculates the maximum elevation deviation over a range of spatial scales.

Usage

```
wbt_max_elevation_deviation(
  dem,
  out_mag,
  out_scale,
  min_scale,
  max_scale,
  step = 1,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

dem	Input raster DEM file.
out_mag	Output raster DEVmax magnitude file.
out_scale	Output raster DEVmax scale file.
min_scale	Minimum search neighbourhood radius in grid cells.

max_scale	Maximum search neighbourhood radius in grid cells.
step	Step size as any positive non-zero integer.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_max_elev_dev_signature

Max elev dev signature

Description

Calculates the maximum elevation deviation over a range of spatial scales and for a set of points.

Usage

```
wbt_max_elev_dev_signature(
  dem,
  points,
  output,
  min_scale,
  max_scale,
  step = 10,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

dem	Input raster DEM file.
points	Input vector points file.
output	Output HTML file.
min_scale	Minimum search neighbourhood radius in grid cells.
max_scale	Maximum search neighbourhood radius in grid cells.

step	Step size as any positive non-zero integer.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_max_overlay	<i>Max overlay</i>
-----------------	--------------------

Description

Evaluates the maximum value for each grid cell from a stack of input rasters.

Usage

```
wbt_max_overlay(
  inputs,
  output,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

inputs	Input raster files.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_max_upslope_elev_change
Max upslope elev change

Description

Calculates the maximum upslope change in elevation between a grid cell and its eight downslope neighbors.

Usage

```
wbt_max_upslope_elev_change(  
    dem,  
    output,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

dem	Input raster DEM file.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_max_upslope_flowpath_length
Max upslope flowpath length

Description

Measures the maximum length of all upslope flowpaths draining each grid cell.

Usage

```
wbt_max_upslope_flowpath_length(
    dem,
    output,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

dem	Input raster DEM file.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_md_inf_flow_accumulation
Md inf flow accumulation

Description

Calculates an FD8 flow accumulation raster from an input DEM.

Usage

```
wbt_md_inf_flow_accumulation(
    dem,
    output,
    out_type = "specific contributing area",
    exponent = 1.1,
    threshold = NULL,
    log = FALSE,
    clip = FALSE,
    wd = NULL,
)
```

```

    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)

```

Arguments

dem	Input raster DEM file.
output	Output raster file.
out_type	Output type; one of 'cells', 'specific contributing area' (default), and 'catchment area'.
exponent	Optional exponent parameter; default is 1.1.
threshold	Optional convergence threshold parameter, in grid cells; default is infinity.
log	Optional flag to request the output be log-transformed.
clip	Optional flag to request clipping the display max by 1 percent.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_mean_curvature	<i>Mean curvature</i>
--------------------	-----------------------

Description

Calculates a mean curvature raster from an input DEM.

Usage

```

wbt_mean_curvature(
  dem,
  output,
  log = FALSE,
  zfactor = NULL,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)

```

Arguments

dem	Input raster DEM file.
output	Output raster file.
log	Display output values using a log-scale.
zfactor	Optional multiplier for when the vertical and horizontal units are not the same.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_mean_filter	<i>Mean filter</i>
-----------------	--------------------

Description

Performs a mean filter (low-pass filter) on an input image.

Usage

```
wbt_mean_filter(
  input,
  output,
  filterx = 3,
  filtery = 3,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

input	Input raster file.
output	Output raster file.
filterx	Size of the filter kernel in the x-direction.
filtery	Size of the filter kernel in the y-direction.
wd	Changes the working directory.

verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_median_filter	<i>Median filter</i>
-------------------	----------------------

Description

Performs a median filter on an input image.

Usage

```
wbt_median_filter(
  input,
  output,
  filterx = 11,
  filtery = 11,
  sig_digits = 2,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

input	Input raster file.
output	Output raster file.
filterx	Size of the filter kernel in the x-direction.
filtery	Size of the filter kernel in the y-direction.
sig_digits	Number of significant digits.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_medoid	<i>Medoid</i>
------------	---------------

Description

Calculates the medoid for a series of vector features contained in a shapefile.

Usage

```
wbt_medoid(
  input,
  output,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

input	Input vector file.
output	Output vector file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

`wbt_merge_line_segments`*Merge line segments*

Description

Merges vector line segments into larger features.

Usage

```
wbt_merge_line_segments(  
    input,  
    output,  
    snap = 0,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

<code>input</code>	Input vector file.
<code>output</code>	Output vector file.
<code>snap</code>	Snap tolerance.
<code>wd</code>	Changes the working directory.
<code>verbose_mode</code>	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
<code>compress_rasters</code>	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
<code>command_only</code>	Return command that would be executed by <code>system()</code> rather than running tool.

Value

Returns the tool text outputs.

`wbt_merge_table_with_csv`*Merge table with csv*

Description

Merge a vector's attribute table with a table contained within a CSV text file.

Usage

```
wbt_merge_table_with_csv(  
  input,  
  pkey,  
  csv,  
  fkey,  
  import_field = NULL,  
  wd = NULL,  
  verbose_mode = FALSE,  
  compress_rasters = FALSE,  
  command_only = FALSE  
)
```

Arguments

<code>input</code>	Input primary vector file (i.e. the table to be modified).
<code>pkey</code>	Primary key field.
<code>csv</code>	Input CSV file (i.e. source of data to be imported).
<code>fkey</code>	Foreign key field.
<code>import_field</code>	Imported field (all fields will be imported if not specified).
<code>wd</code>	Changes the working directory.
<code>verbose_mode</code>	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
<code>compress_rasters</code>	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
<code>command_only</code>	Return command that would be executed by <code>system()</code> rather than running tool.

Value

Returns the tool text outputs.

wbt_merge_vectors	<i>Merge vectors</i>
-------------------	----------------------

Description

Combines two or more input vectors of the same ShapeType creating a single, new output vector.

Usage

```
wbt_merge_vectors(
    inputs,
    output,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

inputs	Input vector files.
output	Output vector file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_min	<i>Min</i>
---------	------------

Description

Performs a MIN operation on two rasters or a raster and a constant value.

Usage

```
wbt_min(
    input1,
    input2,
    output,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input1	Input raster file or constant value.
input2	Input raster file or constant value.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_minimal_curvature *Minimal curvature*

Description

Calculates a mean curvature raster from an input DEM.

Usage

```
wbt_minimal_curvature(
    dem,
    output,
    log = FALSE,
    zfactor = NULL,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

dem	Input raster DEM file.
output	Output raster file.
log	Display output values using a log-scale.
zfactor	Optional multiplier for when the vertical and horizontal units are not the same.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_minimum_bounding_box

Minimum bounding box

Description

Creates a vector minimum bounding rectangle around vector features.

Usage

```
wbt_minimum_bounding_box(
  input,
  output,
  criterion = "area",
  features = TRUE,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

input	Input vector file.
output	Output vector polygon file.
criterion	Minimization criterion; options include 'area' (default), 'length', 'width', and 'perimeter'.

features	Find the minimum bounding rectangles around each individual vector feature.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_minimum_bounding_circle
Minimum bounding circle

Description

Delineates the minimum bounding circle (i.e. smallest enclosing circle) for a group of vectors.

Usage

```
wbt_minimum_bounding_circle(
  input,
  output,
  features = TRUE,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

input	Input vector file.
output	Output vector polygon file.
features	Find the minimum bounding circle around each individual vector feature.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_minimum_bounding_envelope
Minimum bounding envelope

Description

Creates a vector axis-aligned minimum bounding rectangle (envelope) around vector features.

Usage

```
wbt_minimum_bounding_envelope(  
    input,  
    output,  
    features = TRUE,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

input	Input vector file.
output	Output vector polygon file.
features	Find the minimum bounding envelop around each individual vector feature.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

`wbt_minimum_convex_hull`*Minimum convex hull*

Description

Creates a vector convex polygon around vector features.

Usage

```
wbt_minimum_convex_hull(  
    input,  
    output,  
    features = TRUE,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

<code>input</code>	Input vector file.
<code>output</code>	Output vector polygon file.
<code>features</code>	Find the hulls around each vector feature.
<code>wd</code>	Changes the working directory.
<code>verbose_mode</code>	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
<code>compress_rasters</code>	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
<code>command_only</code>	Return command that would be executed by <code>system()</code> rather than running tool.

Value

Returns the tool text outputs.

wbt_minimum_filter *Minimum filter*

Description

Assigns each cell in the output grid the minimum value in a moving window centred on each grid cell in the input raster.

Usage

```
wbt_minimum_filter(  
    input,  
    output,  
    filterx = 11,  
    filtery = 11,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

input	Input raster file.
output	Output raster file.
filterx	Size of the filter kernel in the x-direction.
filtery	Size of the filter kernel in the y-direction.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_min_absolute_overlay
Min absolute overlay

Description

Evaluates the minimum absolute value for each grid cell from a stack of input rasters.

Usage

```
wbt_min_absolute_overlay(  
    inputs,  
    output,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

inputs	Input raster files.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_min_dist_classification
Min dist classification

Description

Performs a supervised minimum-distance classification using training site polygons and multi-spectral images.

Usage

```
wbt_min_dist_classification(
    inputs,
    polys,
    field,
    output,
    threshold = NULL,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

inputs	Names of the input band images.
polys	Name of the input training site polygons shapefile.
field	Name of the attribute containing class name data.
output	Name of the output raster file.
threshold	Distance threshold, in z-scores; blank for none.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_min_downslope_elev_change
Min downslope elev change

Description

Calculates the minimum downslope change in elevation between a grid cell and its eight downslope neighbors.

Usage

```
wbt_min_downslope_elev_change(
    dem,
    output,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

dem	Input raster DEM file.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_min_max_contrast_stretch
Min max contrast stretch

Description

Performs a min-max contrast stretch on an input greytone image.

Usage

```
wbt_min_max_contrast_stretch(
    input,
    output,
    min_val,
    max_val,
    num_tones = 256,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input	Input raster file.
output	Output raster file.
min_val	Lower tail clip value.
max_val	Upper tail clip value.
num_tones	Number of tones in the output image.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_min_overlay	<i>Min overlay</i>
-----------------	--------------------

Description

Evaluates the minimum value for each grid cell from a stack of input rasters.

Usage

```
wbt_min_overlay(
  inputs,
  output,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

inputs	Input raster files.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.

compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_modified_k_means_clustering
Modified k means clustering

Description

Performs a modified k-means clustering operation on a multi-spectral dataset.

Usage

```
wbt_modified_k_means_clustering(
  inputs,
  output,
  out_html = NULL,
  start_clusters = 1000,
  merge_dist = NULL,
  max_iterations = 10,
  class_change = 2,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

inputs	Input raster files.
output	Output raster file.
out_html	Output HTML report file.
start_clusters	Initial number of clusters.
merge_dist	Cluster merger distance.
max_iterations	Maximum number of iterations.
class_change	Minimum percent of cells changed between iterations before completion.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.

compress_rasters Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.

command_only Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_modify_no_data_value

Modify no data value

Description

Converts nodata values in a raster to zero.

Usage

```
wbt_modify_no_data_value(
  input,
  new_value = "-32768.0",
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

input Input raster file.

new_value New NoData value.

wd Changes the working directory.

verbose_mode Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.

compress_rasters Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.

command_only Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_modulo	<i>Modulo</i>
------------	---------------

Description

Performs a modulo operation on two rasters or a raster and a constant value.

Usage

```
wbt_modulo(  
    input1,  
    input2,  
    output,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

input1	Input raster file or constant value.
input2	Input raster file or constant value.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_mosaic	<i>Mosaic</i>
------------	---------------

Description

Mosaics two or more images together.

Usage

```
wbt_mosaic(
    output,
    inputs = NULL,
    method = "nn",
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

output	Output raster file.
inputs	Input raster files.
method	Resampling method; options include 'nn' (nearest neighbour), 'bilinear', and 'cc' (cubic convolution).
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

`wbt_mosaic_with_feathering`*Mosaic with feathering*

Description

Mosaics two images together using a feathering technique in overlapping areas to reduce edge-effects.

Usage

```
wbt_mosaic_with_feathering(  
    input1,  
    input2,  
    output,  
    method = "cc",  
    weight = 4,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

<code>input1</code>	Input raster file to modify.
<code>input2</code>	Input reference raster file.
<code>output</code>	Output raster file.
<code>method</code>	Resampling method; options include 'nn' (nearest neighbour), 'bilinear', and 'cc' (cubic convolution).
<code>weight</code>	.
<code>wd</code>	Changes the working directory.
<code>verbose_mode</code>	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
<code>compress_rasters</code>	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
<code>command_only</code>	Return command that would be executed by <code>system()</code> rather than running tool.

Value

Returns the tool text outputs.

wbt_multidirectional_hillshade
Multidirectional hillshade

Description

Calculates a multi-direction hillshade raster from an input DEM.

Usage

```
wbt_multidirectional_hillshade(  
    dem,  
    output,  
    altitude = 45,  
    zfactor = NULL,  
    full_mode = FALSE,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

dem	Input raster DEM file.
output	Output raster file.
altitude	Illumination source altitude in degrees.
zfactor	Optional multiplier for when the vertical and horizontal units are not the same.
full_mode	Optional flag indicating whether to use full 360-degrees of illumination sources.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_multiply	<i>Multiply</i>
--------------	-----------------

Description

Performs a multiplication operation on two rasters or a raster and a constant value.

Usage

```
wbt_multiply(  
    input1,  
    input2,  
    output,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

input1	Input raster file or constant value.
input2	Input raster file or constant value.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by <code>system()</code> rather than running tool.

Value

Returns the tool text outputs.

```
wbt_multiscale_elevation_percentile
    Multiscale elevation percentile
```

Description

Calculates surface roughness over a range of spatial scales.

Usage

```
wbt_multiscale_elevation_percentile(
    dem,
    out_mag,
    out_scale,
    sig_digits = 3,
    min_scale = 4,
    step = 1,
    num_steps = 10,
    step_nonlinearity = 1,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

dem	Input raster DEM file.
out_mag	Output raster roughness magnitude file.
out_scale	Output raster roughness scale file.
sig_digits	Number of significant digits.
min_scale	Minimum search neighbourhood radius in grid cells.
step	Step size as any positive non-zero integer.
num_steps	Number of steps.
step_nonlinearity	Step nonlinearity factor (1.0-2.0 is typical).
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

```
wbt_multiscale_roughness
    Multiscale roughness
```

Description

Calculates surface roughness over a range of spatial scales.

Usage

```
wbt_multiscale_roughness(
    dem,
    out_mag,
    out_scale,
    max_scale,
    min_scale = 1,
    step = 1,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

dem	Input raster DEM file.
out_mag	Output raster roughness magnitude file.
out_scale	Output raster roughness scale file.
max_scale	Maximum search neighbourhood radius in grid cells.
min_scale	Minimum search neighbourhood radius in grid cells.
step	Step size as any positive non-zero integer.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_multiscale_roughness_signature
Multiscale roughness signature

Description

Calculates the surface roughness for points over a range of spatial scales.

Usage

```
wbt_multiscale_roughness_signature(  

    dem,  

    points,  

    output,  

    max_scale,  

    min_scale = 1,  

    step = 1,  

    wd = NULL,  

    verbose_mode = FALSE,  

    compress_rasters = FALSE,  

    command_only = FALSE  

)
```

Arguments

dem	Input raster DEM file.
points	Input vector points file.
output	Output HTML file.
max_scale	Maximum search neighbourhood radius in grid cells.
min_scale	Minimum search neighbourhood radius in grid cells.
step	Step size as any positive non-zero integer.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_multiscale_std_dev_normals
Multiscale std dev normals

Description

Calculates surface roughness over a range of spatial scales.

Usage

```
wbt_multiscale_std_dev_normals(  

    dem,  

    out_mag,  

    out_scale,  

    min_scale = 1,  

    step = 1,  

    num_steps = 10,  

    step_nonlinearity = 1,  

    wd = NULL,  

    verbose_mode = FALSE,  

    compress_rasters = FALSE,  

    command_only = FALSE  

)
```

Arguments

dem	Input raster DEM file.
out_mag	Output raster roughness magnitude file.
out_scale	Output raster roughness scale file.
min_scale	Minimum search neighbourhood radius in grid cells.
step	Step size as any positive non-zero integer.
num_steps	Number of steps.
step_nonlinearity	Step nonlinearity factor (1.0-2.0 is typical).
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_multiscale_std_dev_normals_signature
Multiscale std dev normals signature

Description

Calculates the surface roughness for points over a range of spatial scales.

Usage

```
wbt_multiscale_std_dev_normals_signature(
    dem,
    points,
    output,
    min_scale = 1,
    step = 1,
    num_steps = 10,
    step_nonlinearity = 1,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

dem	Input raster DEM file.
points	Input vector points file.
output	Output HTML file.
min_scale	Minimum search neighbourhood radius in grid cells.
step	Step size as any positive non-zero integer.
num_steps	Number of steps.
step_nonlinearity	Step nonlinearity factor (1.0-2.0 is typical).
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_multiscale_topographic_position_image
Multiscale topographic position image

Description

Creates a multiscale topographic position image from three DEVmax rasters of differing spatial scale ranges.

Usage

```
wbt_multiscale_topographic_position_image(  
    local,  
    meso,  
    broad,  
    output,  
    lightness = 1.2,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

local	Input local-scale topographic position (DEVmax) raster file.
meso	Input meso-scale topographic position (DEVmax) raster file.
broad	Input broad-scale topographic position (DEVmax) raster file.
output	Output raster file.
lightness	Image lightness value (default is 1.2).
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_multi_part_to_single_part
Multi part to single part

Description

Converts a vector file containing multi-part features into a vector containing only single-part features.

Usage

```
wbt_multi_part_to_single_part(  
    input,  
    output,  
    exclude_holes = TRUE,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

input	Input vector line or polygon file.
output	Output vector line or polygon file.
exclude_holes	Exclude hole parts from the feature splitting? (holes will continue to belong to their features in output.).
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_narrowness_index *Narrowness index*

Description

Calculates the narrowness of raster polygons.

Usage

```
wbt_narrowness_index(  
    input,  
    output,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

input	Input raster file.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_natural_neighbour_interpolation
Natural neighbour interpolation

Description

Creates a raster grid based on Sibson's natural neighbour method.

Usage

```
wbt_natural_neighbour_interpolation(
    input,
    output,
    field = NULL,
    use_z = FALSE,
    cell_size = NULL,
    base = NULL,
    clip = TRUE,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input	Input vector points file.
output	Output raster file.
field	Input field name in attribute table.
use_z	Use the 'z' dimension of the Shapefile's geometry instead of an attribute field?.
cell_size	Optionally specified cell size of output raster. Not used when base raster is specified.
base	Optionally specified input base raster file. Not used when a cell size is specified.
clip	Clip the data to the convex hull of the points?.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_nearest_neighbour_gridding
Nearest neighbour gridding

Description

Creates a raster grid based on a set of vector points and assigns grid values using the nearest neighbour.

Usage

```
wbt_nearest_neighbour_gridding(
    input,
    field,
    output,
    use_z = FALSE,
    cell_size = NULL,
    base = NULL,
    max_dist = NULL,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input	Input vector Points file.
field	Input field name in attribute table.
output	Output raster file.
use_z	Use z-coordinate instead of field?.
cell_size	Optionally specified cell size of output raster. Not used when base raster is specified.
base	Optionally specified input base raster file. Not used when a cell size is specified.
max_dist	Maximum search distance (optional).
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_negate	<i>Negate</i>
------------	---------------

Description

Changes the sign of values in a raster or the 0-1 values of a Boolean raster.

Usage

```
wbt_negate(
    input,
    output,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input	Input raster file.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_new_raster_from_base
New raster from base

Description

Creates a new raster using a base image.

Usage

```
wbt_new_raster_from_base(
    base,
    output,
    value = "nodata",
    data_type = "float",
    cell_size = NULL,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

base	Input base raster file.
output	Output raster file.
value	Constant value to fill raster with; either 'nodata' or numeric value.
data_type	Output raster data type; options include 'double' (64-bit), 'float' (32-bit), and 'integer' (signed 16-bit) (default is 'float').
cell_size	Optionally specified cell size of output raster. Not used when base raster is specified.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_normalized_difference_index
Normalized difference index

Description

Calculate a normalized-difference index (NDI) from two bands of multispectral image data.

Usage

```
wbt_normalized_difference_index(  
  input1,  
  input2,  
  output,  
  clip = 0,  
  correction = 0,  
  wd = NULL,  
  verbose_mode = FALSE,  
  compress_rasters = FALSE,  
  command_only = FALSE  
)
```

Arguments

input1	Input image 1 (e.g. near-infrared band).
input2	Input image 2 (e.g. red band).
output	Output raster file.
clip	Optional amount to clip the distribution tails by, in percent.
correction	Optional adjustment value (e.g. 1, or 0.16 for the optimal soil adjusted vegetation index, OSAVI).
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_normal_vectors *Normal vectors*

Description

Calculates normal vectors for points within a LAS file and stores these data (XYZ vector components) in the RGB field.

Usage

```
wbt_normal_vectors(
  input,
  output,
  radius = 1,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

input	Input LiDAR file.
output	Output LiDAR file.
radius	Search Radius.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_not	<i>Not</i>
---------	------------

Description

Performs a logical NOT operator on two Boolean raster images.

Usage

```
wbt_not(
  input1,
  input2,
  output,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

input1	Input raster file.
input2	Input raster file.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_not_equal_to	<i>Not equal to</i>
------------------	---------------------

Description

Performs a not-equal-to comparison operation on two rasters or a raster and a constant value.

Usage

```
wbt_not_equal_to(
    input1,
    input2,
    output,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input1	Input raster file or constant value.
input2	Input raster file or constant value.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_num_downslope_neighbours
Num downslope neighbours

Description

Calculates the number of downslope neighbours to each grid cell in a DEM.

Usage

```
wbt_num_downslope_neighbours(  
    dem,  
    output,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

dem	Input raster DEM file.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_num_inflowing_neighbours
Num inflowing neighbours

Description

Computes the number of inflowing neighbours to each cell in an input DEM based on the D8 algorithm.

Usage

```
wbt_num_inflowing_neighbours(
    dem,
    output,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

dem	Input raster DEM file.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_num_upslope_neighbours
Num upslope neighbours

Description

Calculates the number of upslope neighbours to each grid cell in a DEM.

Usage

```
wbt_num_upslope_neighbours(
    dem,
    output,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

dem	Input raster DEM file.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_olympic_filter *Olympic filter*

Description

Performs an olympic smoothing filter on an image.

Usage

```
wbt_olympic_filter(
  input,
  output,
  filterx = 11,
  filtery = 11,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

input	Input raster file.
output	Output raster file.
filterx	Size of the filter kernel in the x-direction.
filtery	Size of the filter kernel in the y-direction.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.

compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by <code>system()</code> rather than running tool.

Value

Returns the tool text outputs.

wbt_opening	<i>Opening</i>
-------------	----------------

Description

An opening is a mathematical morphology operation involving a dilation (max filter) of an erosion (min filter) set.

Usage

```
wbt_opening(
  input,
  output,
  filterx = 11,
  filtery = 11,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

input	Input raster file.
output	Output raster file.
filterx	Size of the filter kernel in the x-direction.
filtery	Size of the filter kernel in the y-direction.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by <code>system()</code> rather than running tool.

Value

Returns the tool text outputs.

wbt_openness	<i>Openness</i>
--------------	-----------------

Description

This tool calculates the topographic openness index from an input DEM.

Usage

```
wbt_openness(  
    input,  
    pos_output,  
    neg_output,  
    dist = 20,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

input	Name of the input raster DEM file.
pos_output	Name of the positive openness output raster file.
neg_output	Name of the negative openness output raster file.
dist	Search distance, in grid cells.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_or	<i>Or</i>
--------	-----------

Description

Performs a logical OR operator on two Boolean raster images.

Usage

```
wbt_or(
  input1,
  input2,
  output,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

input1	Input raster file.
input2	Input raster file.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

`wbt_paired_sample_t_test`*Paired sample t test*

Description

Performs a 2-sample K-S test for significant differences on two input rasters.

Usage

```
wbt_paired_sample_t_test(  
    input1,  
    input2,  
    output,  
    num_samples = NULL,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

<code>input1</code>	First input raster file.
<code>input2</code>	Second input raster file.
<code>output</code>	Output HTML file.
<code>num_samples</code>	Number of samples. Leave blank to use whole image.
<code>wd</code>	Changes the working directory.
<code>verbose_mode</code>	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
<code>compress_rasters</code>	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
<code>command_only</code>	Return command that would be executed by <code>system()</code> rather than running tool.

Value

Returns the tool text outputs.

wbt_panchromatic_sharpening
Panchromatic sharpening

Description

Increases the spatial resolution of image data by combining multispectral bands with panchromatic data.

Usage

```
wbt_panchromatic_sharpening(
    pan,
    output,
    red = NULL,
    green = NULL,
    blue = NULL,
    composite = NULL,
    method = "brovey",
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

pan	Input panchromatic band file.
output	Output colour composite file.
red	Input red band image file. Optionally specified if colour-composite not specified.
green	Input green band image file. Optionally specified if colour-composite not specified.
blue	Input blue band image file. Optionally specified if colour-composite not specified.
composite	Input colour-composite image file. Only used if individual bands are not specified.
method	Options include 'brovey' (default) and 'ihs'.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_parallelepiped_classification
Parallelepiped classification

Description

Performs a supervised parallelepiped classification using training site polygons and multi-spectral images.

Usage

```
wbt_parallelepiped_classification(  
  inputs,  
  polys,  
  field,  
  output,  
  wd = NULL,  
  verbose_mode = FALSE,  
  compress_rasters = FALSE,  
  command_only = FALSE  
)
```

Arguments

inputs	Name of the input band images.
polys	Name of the input training site polygons shapefile.
field	Name of the attribute containing class name data.
output	Name of the output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_patch_orientation *Patch orientation*

Description

Calculates the orientation of vector polygons.

Usage

```
wbt_patch_orientation(  
    input,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

input	Input vector polygon file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_pennock_landform_class
Pennock landform class

Description

Classifies hillslope zones based on slope, profile curvature, and plan curvature.

Usage

```
wbt_pennock_landform_class(
    dem,
    output,
    slope = 3,
    prof = 0.1,
    plan = 0,
    zfactor = NULL,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

dem	Input raster DEM file.
output	Output raster file.
slope	Slope threshold value, in degrees (default is 3.0).
prof	Profile curvature threshold value (default is 0.1).
plan	Plan curvature threshold value (default is 0.0).
zfactor	Optional multiplier for when the vertical and horizontal units are not the same.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_percentage_contrast_stretch
Percentage contrast stretch

Description

Performs a percentage linear contrast stretch on input images.

Usage

```
wbt_percentage_contrast_stretch(
    input,
    output,
    clip = 1,
    tail = "both",
    num_tones = 256,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input	Input raster file.
output	Output raster file.
clip	Optional amount to clip the distribution tails by, in percent.
tail	Specified which tails to clip; options include 'upper', 'lower', and 'both' (default is 'both').
num_tones	Number of tones in the output image.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by <code>system()</code> rather than running tool.

Value

Returns the tool text outputs.

wbt_percentile_filter *Percentile filter*

Description

Performs a percentile filter on an input image.

Usage

```
wbt_percentile_filter(
    input,
    output,
    filterx = 11,
    filtery = 11,
    sig_digits = 2,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input	Input raster file.
output	Output raster file.
filterx	Size of the filter kernel in the x-direction.
filtery	Size of the filter kernel in the y-direction.
sig_digits	Number of significant digits.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_percent_elev_range
Percent elev range

Description

Calculates percent of elevation range from a DEM.

Usage

```
wbt_percent_elev_range(
    dem,
    output,
    filterx = 3,
    filtery = 3,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

dem	Input raster DEM file.
output	Output raster file.
filterx	Size of the filter kernel in the x-direction.
filtery	Size of the filter kernel in the y-direction.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_percent_equal_to *Percent equal to*

Description

Calculates the percentage of a raster stack that have cell values equal to an input on a cell-by-cell basis.

Usage

```
wbt_percent_equal_to(
    inputs,
    comparison,
    output,
    wd = NULL,
```

```

    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)

```

Arguments

<code>inputs</code>	Input raster files.
<code>comparison</code>	Input comparison raster file.
<code>output</code>	Output raster file.
<code>wd</code>	Changes the working directory.
<code>verbose_mode</code>	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
<code>compress_rasters</code>	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
<code>command_only</code>	Return command that would be executed by <code>system()</code> rather than running tool.

Value

Returns the tool text outputs.

`wbt_percent_greater_than`
Percent greater than

Description

Calculates the percentage of a raster stack that have cell values greater than an input on a cell-by-cell basis.

Usage

```

wbt_percent_greater_than(
  inputs,
  comparison,
  output,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)

```


Arguments

inputs	Input raster files.
comparison	Input comparison raster file.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_percent_less_than *Percent less than*

Description

Calculates the percentage of a raster stack that have cell values less than an input on a cell-by-cell basis.

Usage

```
wbt_percent_less_than(
  inputs,
  comparison,
  output,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

inputs	Input raster files.
comparison	Input comparison raster file.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.

`compress_rasters` Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.

`command_only` Return command that would be executed by `system()` rather than running tool.

Value

Returns the tool text outputs.

`wbt_perimeter_area_ratio`
Perimeter area ratio

Description

Calculates the perimeter-area ratio of vector polygons.

Usage

```
wbt_perimeter_area_ratio(
  input,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

`input` Input vector polygon file.

`wd` Changes the working directory.

`verbose_mode` Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.

`compress_rasters` Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.

`command_only` Return command that would be executed by `system()` rather than running tool.

Value

Returns the tool text outputs.

wbt_phi_coefficient *Phi coefficient*

Description

This tool performs a binary classification accuracy assessment.

Usage

```
wbt_phi_coefficient(  
    input1,  
    input2,  
    output,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

input1	Name of the first input raster image file.
input2	Name of the second input raster image file.
output	Name of the output HTML file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

`wbt_pick_from_list` *Pick from list*

Description

Outputs the value from a raster stack specified by a position raster.

Usage

```
wbt_pick_from_list(  
    inputs,  
    pos_input,  
    output,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

<code>inputs</code>	Input raster files.
<code>pos_input</code>	Input position raster file.
<code>output</code>	Output raster file.
<code>wd</code>	Changes the working directory.
<code>verbose_mode</code>	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
<code>compress_rasters</code>	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
<code>command_only</code>	Return command that would be executed by <code>system()</code> rather than running tool.

Value

Returns the tool text outputs.

wbt_plan_curvature *Plan curvature*

Description

Calculates a plan (contour) curvature raster from an input DEM.

Usage

```
wbt_plan_curvature(  
    dem,  
    output,  
    log = FALSE,  
    zfactor = NULL,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

dem	Input raster DEM file.
output	Output raster file.
log	Display output values using a log-scale.
zfactor	Optional multiplier for when the vertical and horizontal units are not the same.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_polygonize	<i>Polygonize</i>
----------------	-------------------

Description

Creates a polygon layer from two or more intersecting line features contained in one or more input vector line files.

Usage

```
wbt_polygonize(
    inputs,
    output,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

inputs	Input vector polyline file.
output	Output vector polygon file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_polygons_to_lines	<i>Polygons to lines</i>
-----------------------	--------------------------

Description

Converts vector polygons to polylines.

Usage

```
wbt_polygons_to_lines(
    input,
    output,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input	Input vector polygon file.
output	Output vector lines file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by <code>system()</code> rather than running tool.

Value

Returns the tool text outputs.

wbt_polygon_area	<i>Polygon area</i>
------------------	---------------------

Description

Calculates the area of vector polygons.

Usage

```
wbt_polygon_area(
    input,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input	Input vector polygon file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_polygon_long_axis *Polygon long axis*

Description

This tool can be used to map the long axis of polygon features.

Usage

```
wbt_polygon_long_axis(
  input,
  output,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

input	Input vector polygons file.
output	Output vector polyline file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_polygon_perimeter *Polygon perimeter*

Description

Calculates the perimeter of vector polygons.

Usage

```
wbt_polygon_perimeter(
    input,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input	Input vector polygon file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_polygon_short_axis
Polygon short axis

Description

This tool can be used to map the short axis of polygon features.

Usage

```
wbt_polygon_short_axis(
    input,
    output,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input	Input vector polygons file.
output	Output vector polyline file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_power	<i>Power</i>
-----------	--------------

Description

Raises the values in grid cells of one rasters, or a constant value, by values in another raster or constant value.

Usage

```
wbt_power(
    input1,
    input2,
    output,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input1	Input raster file or constant value.
input2	Input raster file or constant value.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_prewitt_filter *Prewitt filter*

Description

Performs a Prewitt edge-detection filter on an image.

Usage

```
wbt_prewitt_filter(
  input,
  output,
  clip = 0,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

input	Input raster file.
output	Output raster file.
clip	Optional amount to clip the distribution tails by, in percent.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_principal_component_analysis
Principal component analysis

Description

Performs a principal component analysis (PCA) on a multi-spectral dataset.

Usage

```
wbt_principal_component_analysis(  

    inputs,  

    output,  

    num_comp = NULL,  

    standardized = FALSE,  

    wd = NULL,  

    verbose_mode = FALSE,  

    compress_rasters = FALSE,  

    command_only = FALSE  

)
```

Arguments

inputs	Input raster files.
output	Output HTML report file.
num_comp	Number of component images to output; <= to num. input images.
standardized	Perform standardized PCA?.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_print_geo_tiff_tags
Print geo tiff tags

Description

Prints the tags within a GeoTIFF.

Usage

```
wbt_print_geo_tiff_tags(  
    input,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

input	Input GeoTIFF file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by <code>system()</code> rather than running tool.

Value

Returns the tool text outputs.

wbt_profile *Profile*

Description

Plots profiles from digital surface models.

Usage

```
wbt_profile(
  lines,
  surface,
  output,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

lines	Input vector line file.
surface	Input raster surface file.
output	Output HTML file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_profile_curvature *Profile curvature*

Description

Calculates a profile curvature raster from an input DEM.

Usage

```
wbt_profile_curvature(
  dem,
  output,
  log = FALSE,
  zfactor = NULL,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

dem	Input raster DEM file.
output	Output raster file.
log	Display output values using a log-scale.
zfactor	Optional multiplier for when the vertical and horizontal units are not the same.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_qin_flow_accumulation
Qin flow accumulation

Description

This tool calculates Qin et al. (2007) flow accumulation.

Usage

```
wbt_qin_flow_accumulation(
  dem,
  output,
  out_type = "specific contributing area",
  exponent = 10,
  max_slope = 45,
  threshold = NULL,
  log = FALSE,
  clip = FALSE,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

dem	Name of the input DEM raster file; must be depressionless.
output	Name of the output raster file.
out_type	Output type; one of 'cells', 'specific contributing area' (default), and 'catchment area'.
exponent	Optional upper-bound exponent parameter; default is 10.0.
max_slope	Optional upper-bound slope parameter, in degrees (0-90); default is 45.0.
threshold	Optional convergence threshold parameter, in grid cells; default is infinity.
log	Log-transform the output values?.
clip	Optional flag to request clipping the display max by 1 percent.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_quantiles	<i>Quantiles</i>
---------------	------------------

Description

Transforms raster values into quantiles.

Usage

```
wbt_quantiles(
  input,
  output,
  num_quantiles = 5,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```


Arguments

input	Input raster file.
output	Output raster file.
num_quantiles	Number of quantiles.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_quinn_flow_accumulation
Quinn flow accumulation

Description

This tool calculates Quinn et al. (1995) flow accumulation.

Usage

```
wbt_quinn_flow_accumulation(
  dem,
  output,
  out_type = "specific contributing area",
  exponent = 1,
  threshold = NULL,
  log = FALSE,
  clip = FALSE,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

dem	Name of the input DEM raster file; must be depressionless.
output	Name of the output raster file.
out_type	Output type; one of 'cells', 'specific contributing area' (default), and 'catchment area'.
exponent	Optional exponent parameter; default is 1.0.
threshold	Optional convergence threshold parameter, in grid cells; default is infinity.
log	Log-transform the output values?.
clip	Optional flag to request clipping the display max by 1 percent.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_radial_basis_function_interpolation
Radial basis function interpolation

Description

Interpolates vector points into a raster surface using a radial basis function scheme.

Usage

```
wbt_radial_basis_function_interpolation(
  input,
  field,
  output,
  use_z = FALSE,
  radius = NULL,
  min_points = NULL,
  func_type = "ThinPlateSpline",
  poly_order = "none",
  weight = 0.1,
  cell_size = NULL,
  base = NULL,
  wd = NULL,
```

```

    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)

```

Arguments

input	Input vector points file.
field	Input field name in attribute table.
output	Output raster file.
use_z	Use z-coordinate instead of field?.
radius	Search Radius (in map units).
min_points	Minimum number of points.
func_type	Radial basis function type; options are 'ThinPlateSpline' (default), 'PolyHarmonic', 'Gaussian', 'MultiQuadric', 'InverseMultiQuadric'.
poly_order	Polynomial order; options are 'none' (default), 'constant', 'affine'.
weight	Weight parameter used in basis function.
cell_size	Optionally specified cell size of output raster. Not used when base raster is specified.
base	Optionally specified input base raster file. Not used when a cell size is specified.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_radius_of_gyration
Radius of gyration

Description

Calculates the distance of cells from their polygon's centroid.

Usage

```
wbt_radius_of_gyration(
    input,
    output,
    text_output = FALSE,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input	Input raster file.
output	Output raster file.
text_output	Optional text output.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_raise_walls	<i>Raise walls</i>
-----------------	--------------------

Description

Raises walls in a DEM along a line or around a polygon, e.g. a watershed.

Usage

```
wbt_raise_walls(
    input,
    dem,
    output,
    breach = NULL,
    height = 100,
    wd = NULL,
    verbose_mode = FALSE,
```

```

    compress_rasters = FALSE,
    command_only = FALSE
)

```

Arguments

input	Input vector lines or polygons file.
dem	Input raster DEM file.
output	Output raster file.
breach	Optional input vector breach lines.
height	Wall height.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_random_field	<i>Random field</i>
------------------	---------------------

Description

Creates an image containing random values.

Usage

```

wbt_random_field(
  base,
  output,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)

```

Arguments

base	Input raster file.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_random_forest_classification
Random forest classification

Description

Performs a supervised random forest classification using training site polygons/points and predictor rasters.

Usage

```
wbt_random_forest_classification(
  inputs,
  training,
  field,
  output = NULL,
  split_criterion = "Gini",
  n_trees = 500,
  min_samples_leaf = 1,
  min_samples_split = 2,
  test_proportion = 0.2,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

inputs	Names of the input predictor rasters.
training	Name of the input training site polygons/points shapefile.
field	Name of the attribute containing class data.
output	Name of the output raster file.
split_criterion	Split criterion to use when building a tree. Options include 'Gini', 'Entropy', and 'ClassificationError'.
n_trees	The number of trees in the forest.
min_samples_leaf	The minimum number of samples required to be at a leaf node.
min_samples_split	The minimum number of samples required to split an internal node.
test_proportion	The proportion of the dataset to include in the test split; default is 0.2.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_random_forest_regression
Random forest regression

Description

Performs a random forest regression analysis using training site data and predictor rasters.

Usage

```
wbt_random_forest_regression(  
  inputs,  
  training,  
  field,  
  output = NULL,  
  n_trees = 100,
```

```

min_samples_leaf = 1,
min_samples_split = 2,
test_proportion = 0.2,
wd = NULL,
verbose_mode = FALSE,
compress_rasters = FALSE,
command_only = FALSE
)

```

Arguments

inputs	Names of the input predictor rasters.
training	Name of the input training site points shapefile.
field	Name of the attribute containing response variable name data.
output	Name of the output raster file. This parameter is optional. When unspecified, the tool will only build the model. When specified, the tool will use the built model and predictor rasters to perform a spatial prediction.
n_trees	The number of trees in the forest.
min_samples_leaf	The minimum number of samples required to be at a leaf node.
min_samples_split	The minimum number of samples required to split an internal node.
test_proportion	The proportion of the dataset to include in the test split; default is 0.2.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_random_sample	<i>Random sample</i>
-------------------	----------------------

Description

Creates an image containing randomly located sample grid cells with unique IDs.

Usage

```
wbt_random_sample(
    base,
    output,
    num_samples = 1000,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

base	Input raster file.
output	Output raster file.
num_samples	Number of samples.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_range_filter	<i>Range filter</i>
------------------	---------------------

Description

Assigns each cell in the output grid the range of values in a moving window centred on each grid cell in the input raster.

Usage

```
wbt_range_filter(
    input,
    output,
    filterx = 11,
    filtery = 11,
    wd = NULL,
    verbose_mode = FALSE,
```

```

    compress_rasters = FALSE,
    command_only = FALSE
)

```

Arguments

input	Input raster file.
output	Output raster file.
filterx	Size of the filter kernel in the x-direction.
filtery	Size of the filter kernel in the y-direction.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_rasterize_streams *Rasterize streams*

Description

Rasterizes vector streams based on Lindsay (2016) method.

Usage

```

wbt_rasterize_streams(
  streams,
  base,
  output,
  nodata = TRUE,
  feature_id = FALSE,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)

```

Arguments

streams	Input vector streams file.
base	Input base raster file.
output	Output raster file.
nodata	Use NoData value for background?.
feature_id	Use feature number as output value?.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_raster_area	<i>Raster area</i>
-----------------	--------------------

Description

Calculates the area of polygons or classes within a raster image.

Usage

```
wbt_raster_area(
  input,
  output = NULL,
  out_text = FALSE,
  units = "grid cells",
  zero_back = FALSE,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

input	Input raster file.
output	Output raster file.
out_text	Would you like to output polygon areas to text?.
units	Area units; options include 'grid cells' and 'map units'.
zero_back	Flag indicating whether zero values should be treated as a background.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_raster_calculator *Raster calculator*

Description

This tool performs a complex mathematical operations on one or more input raster images on a cell-to-cell basis.

Usage

```
wbt_raster_calculator(
  output,
  statement = "",
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

output	Name of the output raster file.
statement	Statement e.g. cos("raster1") * 35.0 + "raster2". This statement must be a valid Rust statement.
wd	Changes the working directory.

verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_raster_cell_assignment
Raster cell assignment

Description

Assign row or column number to cells.

Usage

```
wbt_raster_cell_assignment(  
  input,  
  output,  
  assign = "column",  
  wd = NULL,  
  verbose_mode = FALSE,  
  compress_rasters = FALSE,  
  command_only = FALSE  
)
```

Arguments

input	Input raster file.
output	Output raster file.
assign	Which variable would you like to assign to grid cells? Options include 'column', 'row', 'x', and 'y'.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_raster_histogram *Raster histogram*

Description

Creates a histogram from raster values.

Usage

```
wbt_raster_histogram(  
    input,  
    output,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

input	Input raster file.
output	Output HTML file (default name will be based on input file if unspecified).
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_raster_perimeter *Raster perimeter*

Description

Calculates the perimeters of polygons or classes within a raster image.

Usage

```
wbt_raster_perimeter(  
    input,  
    output = NULL,  
    out_text = FALSE,  
    units = "grid cells",  
    zero_back = FALSE,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

input	Input raster file.
output	Output raster file.
out_text	Would you like to output polygon areas to text?.
units	Area units; options include 'grid cells' and 'map units'.
zero_back	Flag indicating whether zero values should be treated as a background.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

`wbt_raster_streams_to_vector`*Raster streams to vector*

Description

Converts a raster stream file into a vector file.

Usage

```
wbt_raster_streams_to_vector(  
    streams,  
    d8_pntr,  
    output,  
    esri_pntr = FALSE,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

<code>streams</code>	Input raster streams file.
<code>d8_pntr</code>	Input raster D8 pointer file.
<code>output</code>	Output vector file.
<code>esri_pntr</code>	D8 pointer uses the ESRI style scheme.
<code>wd</code>	Changes the working directory.
<code>verbose_mode</code>	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
<code>compress_rasters</code>	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
<code>command_only</code>	Return command that would be executed by <code>system()</code> rather than running tool.

Value

Returns the tool text outputs.

wbt_raster_summary_stats
Raster summary stats

Description

Measures a rasters min, max, average, standard deviation, num. non-nodata cells, and total.

Usage

```
wbt_raster_summary_stats(  
    input,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

input	Input raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_raster_to_vector_lines
Raster to vector lines

Description

Converts a raster lines features into a vector of the POLYLINE shapetype.

Usage

```
wbt_raster_to_vector_lines(
    input,
    output,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input	Input raster lines file.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_raster_to_vector_points
Raster to vector points

Description

Converts a raster dataset to a vector of the POINT shapetype.

Usage

```
wbt_raster_to_vector_points(
    input,
    output,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input	Input raster file.
output	Output vector points file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_raster_to_vector_polygons
Raster to vector polygons

Description

Converts a raster dataset to a vector of the POLYGON shapetype.

Usage

```
wbt_raster_to_vector_polygons(
  input,
  output,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

input	Input raster file.
output	Output vector polygons file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_reciprocal	<i>Reciprocal</i>
----------------	-------------------

Description

Returns the reciprocal (i.e. $1/z$) of values in a raster.

Usage

```
wbt_reciprocal(
  input,
  output,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

input	Input raster file.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by <code>system()</code> rather than running tool.

Value

Returns the tool text outputs.

wbt_reclass	<i>Reclass</i>
-------------	----------------

Description

Reclassifies the values in a raster image.

Usage

```
wbt_reclass(
    input,
    output,
    reclass_vals,
    assign_mode = FALSE,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input	Input raster file.
output	Output raster file.
reclass_vals	Reclassification triplet values (new value; from value; to less than), e.g. '0.0;0.0;1.0;1.0;1.0;2.0'.
assign_mode	Optional Boolean flag indicating whether to operate in assign mode, reclass_vals values are interpreted as new value; old value pairs.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_reclass_equal_interval
Reclass equal interval

Description

Reclassifies the values in a raster image based on equal-ranges.

Usage

```
wbt_reclass_equal_interval(  
    input,  
    output,  
    interval = 10,  
    start_val = NULL,  
    end_val = NULL,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

input	Input raster file.
output	Output raster file.
interval	Class interval size.
start_val	Optional starting value (default is input minimum value).
end_val	Optional ending value (default is input maximum value).
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_reclass_from_file *Reclass from file*

Description

Reclassifies the values in a raster image using reclass ranges in a text file.

Usage

```
wbt_reclass_from_file(  
    input,  
    reclass_file,  
    output,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

input	Input raster file.
reclass_file	Input text file containing reclass ranges.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by <code>system()</code> rather than running tool.

Value

Returns the tool text outputs.

wbt_reconcile_multiple_headers
Reconcile multiple headers

Description

This tool adjusts the crop yield values for data sets collected with multiple headers or combines.

Usage

```
wbt_reconcile_multiple_headers(  
    input,  
    region_field,  
    yield_field,  
    output,  
    radius = NULL,  
    min_yield = NULL,  
    max_yield = NULL,  
    mean_tonnage = NULL,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

input	Name of the input points shapefile.
region_field	Name of the attribute containing region data.
yield_field	Name of the attribute containing yield data.
output	Name of the output points shapefile.
radius	Optional search radius, in metres. Only specify this value if you want to calculate locally normalized yield.
min_yield	Minimum yield value in output.
max_yield	Maximum yield value in output.
mean_tonnage	Use this optional parameter to force the output to have a certain overall average tonnage.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_recreate_pass_lines
Recreate pass lines

Description

This tool can be used to approximate the harvester pass lines from yield points.

Usage

```
wbt_recreate_pass_lines(  
    input,  
    yield_field_name,  
    output_lines,  
    output_points,  
    max_change_in_heading = 25,  
    ignore_zeros = FALSE,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

input	Name of the input points shapefile.
yield_field_name	Name of the attribute containing yield data.
output_lines	Name of the output pass lines shapefile.
output_points	Name of the output points shapefile.
max_change_in_heading	Max change in heading.
ignore_zeros	Ignore zero-valued yield points?.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_reinitialize_attribute_table
Reinitialize attribute table

Description

Reinitializes a vector's attribute table deleting all fields but the feature ID (FID).

Usage

```
wbt_reinitialize_attribute_table(  
    input,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

input	Input vector file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_related_circumscribing_circle
Related circumscribing circle

Description

Calculates the related circumscribing circle of vector polygons.

Usage

```
wbt_related_circumscribing_circle(  
    input,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

input	Input vector polygon file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_relative_aspect *Relative aspect*

Description

Calculates relative aspect (relative to a user-specified direction) from an input DEM.

Usage

```
wbt_relative_aspect(
    dem,
    output,
    azimuth = 0,
    zfactor = NULL,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

dem	Input raster DEM file.
output	Output raster file.
azimuth	Illumination source azimuth.
zfactor	Optional multiplier for when the vertical and horizontal units are not the same.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_relative_topographic_position
Relative topographic position

Description

Calculates the relative topographic position index from a DEM.

Usage

```
wbt_relative_topographic_position(
    dem,
    output,
    filterx = 11,
    filtery = 11,
```

```

    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)

```

Arguments

dem	Input raster DEM file.
output	Output raster file.
filterx	Size of the filter kernel in the x-direction.
filtery	Size of the filter kernel in the y-direction.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

```

wbt_remove_field_edge_points
    Remove field edge points

```

Description

This tool can be used to remove, or flag, most of the points along the edges from a crop yield data set.

Usage

```

wbt_remove_field_edge_points(
    input,
    output,
    dist = NULL,
    max_change_in_heading = 25,
    flag_edges = FALSE,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)

```

Arguments

input	Name of the input points shapefile.
output	Name of the output points shapefile.
dist	Average distance between passes, in meters.
max_change_in_heading	Max change in heading.
flag_edges	Don't remove edge points, just flag them in the attribute table?.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_remove_off_terrain_objects
Remove off terrain objects

Description

Removes off-terrain objects from a raster digital elevation model (DEM).

Usage

```
wbt_remove_off_terrain_objects(  
  dem,  
  output,  
  filter = 11,  
  slope = 15,  
  wd = NULL,  
  verbose_mode = FALSE,  
  compress_rasters = FALSE,  
  command_only = FALSE  
)
```

Arguments

dem	Input raster DEM file.
output	Output raster file.
filter	Filter size (cells).
slope	Slope threshold value.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_remove_polygon_holes
Remove polygon holes

Description

Removes holes within the features of a vector polygon file.

Usage

```
wbt_remove_polygon_holes(
  input,
  output,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

input	Input vector polygon file.
output	Output vector polygon file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.

compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_remove_short_streams
Remove short streams

Description

Removes short first-order streams from a stream network.

Usage

```
wbt_remove_short_streams(  
    d8_pntr,  
    streams,  
    output,  
    min_length,  
    esri_pntr = FALSE,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

d8_pntr	Input raster D8 pointer file.
streams	Input raster streams file.
output	Output raster file.
min_length	Minimum tributary length (in map units) used for network pruning.
esri_pntr	D8 pointer uses the ESRI style scheme.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_remove_spurs	<i>Remove spurs</i>
------------------	---------------------

Description

Removes the spurs (pruning operation) from a Boolean line image; intended to be used on the output of the LineThinning tool.

Usage

```
wbt_remove_spurs(
    input,
    output,
    iterations = 10,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input	Input raster file.
output	Output raster file.
iterations	Maximum number of iterations.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_repair_stream_vector_topology
Repair stream vector topology

Description

This tool resolves topological errors and inconsistencies associated with digitized vector streams.

Usage

```
wbt_repair_stream_vector_topology(  
    input,  
    output,  
    dist = "",  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

input	Name of the input lines vector file.
output	Name of the output lines vector file.
dist	Snap distance, in xy units (metres).
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_resample	<i>Resample</i>
--------------	-----------------

Description

Resamples one or more input images into a destination image.

Usage

```
wbt_resample(
    inputs,
    output,
    cell_size = NULL,
    base = NULL,
    method = "cc",
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

inputs	Input raster files.
output	Output raster file.
cell_size	Optionally specified cell size of output raster. Not used when base raster is specified.
base	Optionally specified input base raster file. Not used when a cell size is specified.
method	Resampling method; options include 'nn' (nearest neighbour), 'bilinear', and 'cc' (cubic convolution).
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_rescale_value_range

Rescale value range

Description

Performs a min-max contrast stretch on an input greytone image.

Usage

```
wbt_rescale_value_range(
    input,
    output,
    out_min_val,
    out_max_val,
    clip_min = NULL,
    clip_max = NULL,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input	Input raster file.
output	Output raster file.
out_min_val	New minimum value in output image.
out_max_val	New maximum value in output image.
clip_min	Optional lower tail clip value.
clip_max	Optional upper tail clip value.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_rgb_to_ihs	<i>Rgb to ihs</i>
----------------	-------------------

Description

Converts red, green, and blue (RGB) images into intensity, hue, and saturation (IHS) images.

Usage

```
wbt_rgb_to_ihs(
  intensity,
  hue,
  saturation,
  red = NULL,
  green = NULL,
  blue = NULL,
  composite = NULL,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

<code>intensity</code>	Output intensity raster file.
<code>hue</code>	Output hue raster file.
<code>saturation</code>	Output saturation raster file.
<code>red</code>	Input red band image file. Optionally specified if colour-composite not specified.
<code>green</code>	Input green band image file. Optionally specified if colour-composite not specified.
<code>blue</code>	Input blue band image file. Optionally specified if colour-composite not specified.
<code>composite</code>	Input colour-composite image file. Only used if individual bands are not specified.
<code>wd</code>	Changes the working directory.
<code>verbose_mode</code>	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
<code>compress_rasters</code>	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
<code>command_only</code>	Return command that would be executed by <code>system()</code> rather than running tool.

Value

Returns the tool text outputs.

```
wbt_rho8_flow_accumulation
    Rho8 flow accumulation
```

Description

This tool calculates Fairfield and Leymarie (1991) flow accumulation.

Usage

```
wbt_rho8_flow_accumulation(
    input,
    output,
    out_type = "specific contributing area",
    log = FALSE,
    clip = FALSE,
    pntr = FALSE,
    esri_pntr = FALSE,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input	Input DEM or Rho8 pointer file; if a DEM is used, it must be depressionless.
output	Name of the output raster file.
out_type	Output type; one of 'cells', 'specific contributing area' (default), and 'catchment area'.
log	Log-transform the output values?.
clip	Optional flag to request clipping the display max by 1 percent.
pntr	Is the input raster a Rho8 flow pointer rather than a DEM?.
esri_pntr	Does the input Rho8 pointer use the ESRI style scheme?.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_rho8_pointer	<i>Rho8 pointer</i>
------------------	---------------------

Description

Calculates a stochastic Rho8 flow pointer raster from an input DEM.

Usage

```
wbt_rho8_pointer(
    dem,
    output,
    esri_pntr = FALSE,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

dem	Input raster DEM file.
output	Output raster file.
esri_pntr	D8 pointer uses the ESRI style scheme.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_ring_curvature *Ring curvature*

Description

This tool calculates ring curvature from an input DEM.

Usage

```
wbt_ring_curvature(  
    dem,  
    output,  
    log = FALSE,  
    zfactor = 1,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

dem	Name of the input raster DEM file.
output	Name of the output raster image file.
log	Display output values using a log-scale.
zfactor	Z conversion factor.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_roberts_cross_filter
Roberts cross filter

Description

Performs a Robert's cross edge-detection filter on an image.

Usage

```
wbt_roberts_cross_filter(  
    input,  
    output,  
    clip = 0,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

input	Input raster file.
output	Output raster file.
clip	Optional amount to clip the distribution tails by, in percent.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_root_mean_square_error
Root mean square error

Description

Calculates the RMSE and other accuracy statistics.

Usage

```
wbt_root_mean_square_error(  
    input,  
    base,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

input	Input raster file.
base	Input base raster file used for comparison.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_rotor *Rotor*

Description

This tool calculates rotor from an input DEM.

Usage

```
wbt_rotor(
  dem,
  output,
  log = FALSE,
  zfactor = 1,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

dem	Name of the input raster DEM file.
output	Name of the output raster image file.
log	Display output values using a log-scale.
zfactor	Z conversion factor.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_round	<i>Round</i>
-----------	--------------

Description

Rounds the values in an input raster to the nearest integer value.

Usage

```
wbt_round(
  input,
  output,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

input	Input raster file.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_ruggedness_index *Ruggedness index*

Description

Calculates the Riley et al.'s (1999) terrain ruggedness index from an input DEM.

Usage

```
wbt_ruggedness_index(
  dem,
  output,
  zfactor = NULL,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

dem	Input raster DEM file.
output	Output raster file.
zfactor	Optional multiplier for when the vertical and horizontal units are not the same.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_run_tool	<i>Run a tool in WhiteboxTools by name</i>
--------------	--

Description

Runs a tool and specifies tool arguments. If the prefix "whitebox:." or "wbt_" is in tool_name it is removed to match the definitions in wbt_list_tools()

Usage

```
wbt_run_tool(tool_name, args, verbose_mode = FALSE, command_only = FALSE)
```

Arguments

tool_name	The name of the tool to run.
args	Tool arguments.
verbose_mode	Verbose mode. Without this flag, tool outputs will not be printed.
command_only	Return command that would be run with system()? Default: FALSE

Value

Returns the (character) output of the tool.

See Also

[wbt_list_tools](#)

Examples

```
## Not run:
tool_name <- "breach_depressions"
dem <- system.file("extdata", "DEM.tif", package="whitebox")
output <- "./output.tif"
arg1 <- paste0("--dem=", dem)
arg2 <- paste0("--output=", output)
args <- paste(arg1, arg2)
wbt_run_tool(tool_name, args)

## End(Not run)
```

wbt_scharr_filter *Scharr filter*

Description

Performs a Scharr edge-detection filter on an image.

Usage

```
wbt_scharr_filter(  
    input,  
    output,  
    clip = 0,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

input	Input raster file.
output	Output raster file.
clip	Optional amount to clip the distribution tails by, in percent.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_sediment_transport_index
Sediment transport index

Description

Calculates the sediment transport index.

Usage

```
wbt_sediment_transport_index(  
    sca,  
    slope,  
    output,  
    sca_exponent = 0.4,  
    slope_exponent = 1.3,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

sca	Input raster specific contributing area (SCA) file.
slope	Input raster slope file.
output	Output raster file.
sca_exponent	SCA exponent value.
slope_exponent	Slope exponent value.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by <code>system()</code> rather than running tool.

Value

Returns the tool text outputs.

wbt_select_tiles_by_polygon
Select tiles by polygon

Description

Copies LiDAR tiles overlapping with a polygon into an output directory.

Usage

```
wbt_select_tiles_by_polygon(  
    indir,  
    outdir,  
    polygons,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

indir	Input LAS file source directory.
outdir	Output directory into which LAS files within the polygon are copied.
polygons	Input vector polygons file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_set_nodata_value *Set nodata value*

Description

Assign a specified value in an input image to the NoData value.

Usage

```
wbt_set_nodata_value(  
    input,  
    output,  
    back_value = 0,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

input	Input raster file.
output	Output raster file.
back_value	Background value to set to nodata.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_shadow_animation *Shadow animation*

Description

This tool creates an animated GIF of shadows based on an input DEM.

Usage

```
wbt_shadow_animation(
    input,
    output,
    palette = "atlas",
    max_dist = "",
    date = "21/06/2021",
    interval = 15,
    location = "43.5448/-80.2482/-4",
    height = 600,
    delay = 250,
    label = "",
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input	Name of the input digital surface model (DSM) raster file.
output	Name of the output HTML file (*.html).
palette	DSM image palette; options are 'atlas', 'high_relief', 'arid', 'soft', 'muted', 'light_quant', 'purple', 'viridis', 'gn_yl', 'pi_y_g', 'bl_yl_rd', 'deep', and 'none'.
max_dist	Optional maximum search distance, in xy units. Minimum value is 5 x cell size.
date	Date in format DD/MM/YYYY.
interval	Time interval, in minutes (1-60).
location	Location, defined as Lat/Long/UTC-offset (e.g. 43.5448/-80.2482/-4).
height	Image height, in pixels.
delay	GIF time delay in milliseconds.
label	Label text (leave blank for none).
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_shadow_image	<i>Shadow image</i>
------------------	---------------------

Description

This tool creates a raster of shadow areas based on an input DEM.

Usage

```
wbt_shadow_image(
    input,
    output,
    palette = "soft",
    max_dist = "",
    date = "21/06/2021",
    time = "13:00",
    location = "43.5448/-80.2482/-4",
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input	Name of the input digital surface model (DSM) raster file.
output	Name of the output raster file.
palette	DSM image palette; options are 'atlas', 'high_relief', 'arid', 'soft', 'muted', 'light_quant', 'purple', 'viridi', 'gn_yl', 'pi_y_g', 'bl_yl_rd', 'deep', and 'none'.
max_dist	Optional maximum search distance, in xy unites. Minimum value is 5 x cell size.
date	Date in format DD/MM/YYYY.
time	Time in format HH::MM, e.g. 03:15AM or 14:30.
location	Location, defined as Lat/Long/UTC-offset (e.g. 43.5448/-80.2482/-4).
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_shape_complexity_index
Shape complexity index

Description

Calculates overall polygon shape complexity or irregularity.

Usage

```
wbt_shape_complexity_index(  
    input,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

input	Input vector polygon file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_shape_complexity_index_raster
Shape complexity index raster

Description

Calculates the complexity of raster polygons or classes.

Usage

```
wbt_shape_complexity_index_raster(  
    input,  
    output,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

input	Input raster file.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_shape_index *Shape index*

Description

This tool calculates the shape index from an input DEM.

Usage

```
wbt_shape_index(
    dem,
    output,
    zfactor = 1,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

dem	Name of the input raster DEM file.
output	Name of the output raster image file.
zfactor	Z conversion factor.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_shreve_stream_magnitude
Shreve stream magnitude

Description

Assigns the Shreve stream magnitude to each link in a stream network.

Usage

```
wbt_shreve_stream_magnitude(
    d8_pntr,
    streams,
    output,
    esri_pntr = FALSE,
    zero_background = FALSE,
    wd = NULL,
```

```

    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)

```

Arguments

d8_pntr	Input raster D8 pointer file.
streams	Input raster streams file.
output	Output raster file.
esri_pntr	D8 pointer uses the ESRI style scheme.
zero_background	Flag indicating whether a background value of zero should be used.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

```

wbt_sigmoidal_contrast_stretch
    Sigmoidal contrast stretch

```

Description

Performs a sigmoidal contrast stretch on input images.

Usage

```

wbt_sigmoidal_contrast_stretch(
  input,
  output,
  cutoff = 0,
  gain = 1,
  num_tones = 256,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)

```

Arguments

input	Input raster file.
output	Output raster file.
cutoff	Cutoff value between 0.0 and 0.95.
gain	Gain value.
num_tones	Number of tones in the output image.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_sin

Sin

Description

Returns the sine (sin) of each values in a raster.

Usage

```
wbt_sin(
  input,
  output,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

input	Input raster file.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.

compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_single_part_to_multi_part
Single part to multi part

Description

Converts a vector file containing multi-part features into a vector containing only single-part features.

Usage

```
wbt_single_part_to_multi_part(
    input,
    output,
    field = NULL,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input	Input vector line or polygon file.
output	Output vector line or polygon file.
field	Grouping ID field name in attribute table.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_sinh

Sinh

Description

Returns the hyperbolic sine (sinh) of each values in a raster.

Usage

```
wbt_sinh(
    input,
    output,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input	Input raster file.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_sink

Sink

Description

Identifies the depressions in a DEM, giving each feature a unique identifier.

Usage

```
wbt_sink(
    input,
    output,
    zero_background = FALSE,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input	Input raster DEM file.
output	Output raster file.
zero_background	Flag indicating whether a background value of zero should be used.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_slope	<i>Slope</i>
-----------	--------------

Description

Calculates a slope raster from an input DEM.

Usage

```
wbt_slope(
    dem,
    output,
    zfactor = NULL,
    units = "degrees",
    wd = NULL,
    verbose_mode = FALSE,
```

```

    compress_rasters = FALSE,
    command_only = FALSE
)

```

Arguments

dem	Input raster DEM file.
output	Output raster file.
zfactor	Optional multiplier for when the vertical and horizontal units are not the same.
units	Units of output raster; options include 'degrees', 'radians', 'percent'.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

```

wbt_slope_vs_aspect_plot
    Slope vs aspect plot

```

Description

This tool creates a slope-aspect relation plot from an input DEM.

Usage

```

wbt_slope_vs_aspect_plot(
  input,
  output,
  bin_size = 2,
  min_slope = 0.1,
  zfactor = 1,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)

```

Arguments

input	Name of the input raster image file.
output	Name of the output report file (*.html).
bin_size	Aspect bin size, in degrees.
min_slope	Minimum slope, in degrees.
zfactor	Z conversion factor.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_slope_vs_elevation_plot
Slope vs elevation plot

Description

Creates a slope vs. elevation plot for one or more DEMs.

Usage

```
wbt_slope_vs_elevation_plot(
  inputs,
  output,
  watershed = NULL,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

inputs	Input DEM files.
output	Output HTML file (default name will be based on input file if unspecified).
watershed	Input watershed files (optional).

wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_smooth_vectors	<i>Smooth vectors</i>
--------------------	-----------------------

Description

Smooths a vector coverage of either a POLYLINE or POLYGON base ShapeType.

Usage

```
wbt_smooth_vectors(  
    input,  
    output,  
    filter = 3,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

input	Input vector POLYLINE or POLYGON file.
output	Output vector file.
filter	The filter size, any odd integer greater than or equal to 3; default is 3.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_smooth_vegetation_residual
Smooth vegetation residual

Description

This tool can smooth the residual roughness due to vegetation cover in LiDAR DEMs.

Usage

```
wbt_smooth_vegetation_residual(  
    input,  
    output,  
    max_scale = 30,  
    dev_threshold = 1,  
    scale_threshold = 5,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

input	Name of the input digital elevation model (DEM) raster file.
output	Name of the output raster file.
max_scale	Maximum search neighbourhood radius in grid cells.
dev_threshold	DEVmax Threshold.
scale_threshold	DEVmax scale threshold.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_snap_pour_points *Snap pour points*

Description

Moves outlet points used to specify points of interest in a watershedding operation to the cell with the highest flow accumulation in its neighbourhood.

Usage

```
wbt_snap_pour_points(
    pour_pts,
    flow_accum,
    output,
    snap_dist,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

<code>pour_pts</code>	Input vector pour points (outlet) file.
<code>flow_accum</code>	Input raster D8 flow accumulation file.
<code>output</code>	Output vector file.
<code>snap_dist</code>	Maximum snap distance in map units.
<code>wd</code>	Changes the working directory.
<code>verbose_mode</code>	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
<code>compress_rasters</code>	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
<code>command_only</code>	Return command that would be executed by <code>system()</code> rather than running tool.

Value

Returns the tool text outputs.

wbt_sobel_filter *Sobel filter*

Description

Performs a Sobel edge-detection filter on an image.

Usage

```
wbt_sobel_filter(  
    input,  
    output,  
    variant = "3x3",  
    clip = 0,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

input	Input raster file.
output	Output raster file.
variant	Optional variant value. Options include 3x3 and 5x5 (default is 3x3).
clip	Optional amount to clip the distribution tails by, in percent (default is 0.0).
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_spherical_std_dev_of_normals
Spherical std dev of normals

Description

Calculates the spherical standard deviation of surface normals for a DEM.

Usage

```
wbt_spherical_std_dev_of_normals(  
    dem,  
    output,  
    filter = 11,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

dem	Input raster DEM file.
output	Output raster file.
filter	Size of the filter kernel.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_split_colour_composite
Split colour composite

Description

This tool splits an RGB colour composite image into separate multispectral images.

Usage

```
wbt_split_colour_composite(  
    input,  
    red = NULL,  
    green = NULL,  
    blue = NULL,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

input	Input colour composite image file.
red	Output red band file.
green	Output green band file.
blue	Output blue band file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

`wbt_split_vector_lines`*Split vector lines*

Description

This tool can be used to split a vector line coverage into even-lengthed segments.

Usage

```
wbt_split_vector_lines(  
    input,  
    output,  
    length = NULL,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

<code>input</code>	Name of the input lines shapefile.
<code>output</code>	Name of the output lines shapefile.
<code>length</code>	Maximum segment length (m).
<code>wd</code>	Changes the working directory.
<code>verbose_mode</code>	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
<code>compress_rasters</code>	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
<code>command_only</code>	Return command that would be executed by <code>system()</code> rather than running tool.

Value

Returns the tool text outputs.

wbt_split_with_lines *Split with lines*

Description

Splits the lines or polygons in one layer using the lines in another layer.

Usage

```
wbt_split_with_lines(  
    input,  
    split,  
    output,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

input	Input vector line or polygon file.
split	Input vector polyline file.
output	Output vector file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by <code>system()</code> rather than running tool.

Value

Returns the tool text outputs.

wbt_square	<i>Square</i>
------------	---------------

Description

Squares the values in a raster.

Usage

```
wbt_square(
    input,
    output,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input	Input raster file.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_square_root	<i>Square root</i>
-----------------	--------------------

Description

Returns the square root of the values in a raster.

Usage

```
wbt_square_root(
    input,
    output,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input	Input raster file.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_standard_deviation_contrast_stretch
Standard deviation contrast stretch

Description

Performs a standard-deviation contrast stretch on input images.

Usage

```
wbt_standard_deviation_contrast_stretch(
    input,
    output,
    stdev = 2,
    num_tones = 256,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input	Input raster file.
output	Output raster file.
stdev	Standard deviation clip value.
num_tones	Number of tones in the output image.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_standard_deviation_filter
Standard deviation filter

Description

Assigns each cell in the output grid the standard deviation of values in a moving window centred on each grid cell in the input raster.

Usage

```
wbt_standard_deviation_filter(  
  input,  
  output,  
  filterx = 11,  
  filtery = 11,  
  wd = NULL,  
  verbose_mode = FALSE,  
  compress_rasters = FALSE,  
  command_only = FALSE  
)
```


Arguments

input	Input raster file.
output	Output raster file.
filterx	Size of the filter kernel in the x-direction.
filtery	Size of the filter kernel in the y-direction.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by <code>system()</code> rather than running tool.

Value

Returns the tool text outputs.

wbt_standard_deviation_of_slope
Standard deviation of slope

Description

Calculates the standard deviation of slope from an input DEM.

Usage

```
wbt_standard_deviation_of_slope(  
  input,  
  output,  
  zfactor = NULL,  
  filterx = 11,  
  filtery = 11,  
  wd = NULL,  
  verbose_mode = FALSE,  
  compress_rasters = FALSE,  
  command_only = FALSE  
)
```

Arguments

input	Input raster DEM file.
output	Output raster DEM file.
zfactor	Optional multiplier for when the vertical and horizontal units are not the same.
filterx	Size of the filter kernel in the x-direction.
filtery	Size of the filter kernel in the y-direction.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_stochastic_depression_analysis
Stochastic depression analysis

Description

Performs a stochastic analysis of depressions within a DEM.

Usage

```
wbt_stochastic_depression_analysis(  
  dem,  
  output,  
  rmse,  
  range,  
  iterations = 100,  
  wd = NULL,  
  verbose_mode = FALSE,  
  compress_rasters = FALSE,  
  command_only = FALSE  
)
```

Arguments

dem	Input raster DEM file.
output	Output file.
rmse	The DEM's root-mean-square-error (RMSE), in z units. This determines error magnitude.
range	The error field's correlation length, in xy-units.
iterations	The number of iterations.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_strahler_order_basins
Strahler order basins

Description

Identifies Strahler-order basins from an input stream network.

Usage

```
wbt_strahler_order_basins(  
  d8_pntr,  
  streams,  
  output,  
  esri_pntr = FALSE,  
  wd = NULL,  
  verbose_mode = FALSE,  
  compress_rasters = FALSE,  
  command_only = FALSE  
)
```

Arguments

d8_pntr	Input raster D8 pointer file.
streams	Input raster streams file.
output	Output raster file.
esri_pntr	D8 pointer uses the ESRI style scheme.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_strahler_stream_order
Strahler stream order

Description

Assigns the Strahler stream order to each link in a stream network.

Usage

```
wbt_strahler_stream_order(
  d8_pntr,
  streams,
  output,
  esri_pntr = FALSE,
  zero_background = FALSE,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

d8_pntr	Input raster D8 pointer file.
streams	Input raster streams file.
output	Output raster file.

esri_pntr	D8 pointer uses the ESRI style scheme.
zero_background	Flag indicating whether a background value of zero should be used.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_stream_link_class *Stream link class*

Description

Identifies the exterior/interior links and nodes in a stream network.

Usage

```
wbt_stream_link_class(
    d8_pntr,
    streams,
    output,
    esri_pntr = FALSE,
    zero_background = FALSE,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

d8_pntr	Input raster D8 pointer file.
streams	Input raster streams file.
output	Output raster file.
esri_pntr	D8 pointer uses the ESRI style scheme.
zero_background	Flag indicating whether a background value of zero should be used.
wd	Changes the working directory.

<code>verbose_mode</code>	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
<code>compress_rasters</code>	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
<code>command_only</code>	Return command that would be executed by <code>system()</code> rather than running tool.

Value

Returns the tool text outputs.

`wbt_stream_link_identifier`
Stream link identifier

Description

Assigns a unique identifier to each link in a stream network.

Usage

```
wbt_stream_link_identifier(
    d8_pntr,
    streams,
    output,
    esri_pntr = FALSE,
    zero_background = FALSE,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

<code>d8_pntr</code>	Input raster D8 pointer file.
<code>streams</code>	Input raster streams file.
<code>output</code>	Output raster file.
<code>esri_pntr</code>	D8 pointer uses the ESRI style scheme.
<code>zero_background</code>	Flag indicating whether a background value of zero should be used.
<code>wd</code>	Changes the working directory.
<code>verbose_mode</code>	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.

compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_stream_link_length
Stream link length

Description

Estimates the length of each link (or tributary) in a stream network.

Usage

```
wbt_stream_link_length(
    d8_pntr,
    linkid,
    output,
    esri_pntr = FALSE,
    zero_background = FALSE,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

d8_pntr	Input raster D8 pointer file.
linkid	Input raster streams link ID (or tributary ID) file.
output	Output raster file.
esri_pntr	D8 pointer uses the ESRI style scheme.
zero_background	Flag indicating whether a background value of zero should be used.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_stream_link_slope *Stream link slope*

Description

Estimates the average slope of each link (or tributary) in a stream network.

Usage

```
wbt_stream_link_slope(
    d8_pntr,
    linkid,
    dem,
    output,
    esri_pntr = FALSE,
    zero_background = FALSE,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

d8_pntr	Input raster D8 pointer file.
linkid	Input raster streams link ID (or tributary ID) file.
dem	Input raster DEM file.
output	Output raster file.
esri_pntr	D8 pointer uses the ESRI style scheme.
zero_background	Flag indicating whether a background value of zero should be used.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

`wbt_stream_power_index`*Stream power index*

Description

Calculates the relative stream power index.

Usage

```
wbt_stream_power_index(  
    sca,  
    slope,  
    output,  
    exponent = 1,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

<code>sca</code>	Input raster specific contributing area (SCA) file.
<code>slope</code>	Input raster slope file.
<code>output</code>	Output raster file.
<code>exponent</code>	SCA exponent value.
<code>wd</code>	Changes the working directory.
<code>verbose_mode</code>	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
<code>compress_rasters</code>	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
<code>command_only</code>	Return command that would be executed by <code>system()</code> rather than running tool.

Value

Returns the tool text outputs.

wbt_stream_slope_continuous
Stream slope continuous

Description

Estimates the slope of each grid cell in a stream network.

Usage

```
wbt_stream_slope_continuous(  

    d8_pntr,  

    streams,  

    dem,  

    output,  

    esri_pntr = FALSE,  

    zero_background = FALSE,  

    wd = NULL,  

    verbose_mode = FALSE,  

    compress_rasters = FALSE,  

    command_only = FALSE  

)
```

Arguments

d8_pntr	Input raster D8 pointer file.
streams	Input raster streams file.
dem	Input raster DEM file.
output	Output raster file.
esri_pntr	D8 pointer uses the ESRI style scheme.
zero_background	Flag indicating whether a background value of zero should be used.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_subbasins	<i>Subbasins</i>
---------------	------------------

Description

Identifies the catchments, or sub-basin, draining to each link in a stream network.

Usage

```
wbt_subbasins(  
    d8_pntr,  
    streams,  
    output,  
    esri_pntr = FALSE,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

d8_pntr	Input D8 pointer raster file.
streams	Input raster streams file.
output	Output raster file.
esri_pntr	D8 pointer uses the ESRI style scheme.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by <code>system()</code> rather than running tool.

Value

Returns the tool text outputs.

wbt_subtract	<i>Subtract</i>
--------------	-----------------

Description

Performs a differencing operation on two rasters or a raster and a constant value.

Usage

```
wbt_subtract(  
    input1,  
    input2,  
    output,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

input1	Input raster file or constant value.
input2	Input raster file or constant value.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by <code>system()</code> rather than running tool.

Value

Returns the tool text outputs.

wbt_sum_overlay	<i>Sum overlay</i>
-----------------	--------------------

Description

Calculates the sum for each grid cell from a group of raster images.

Usage

```
wbt_sum_overlay(
    inputs,
    output,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

inputs	Input raster files.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_surface_area_ratio	<i>Surface area ratio</i>
------------------------	---------------------------

Description

Calculates a the surface area ratio of each grid cell in an input DEM.

Usage

```
wbt_surface_area_ratio(
    dem,
    output,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

dem	Input raster DEM file.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

```
wbt_svm_classification
    Svm classification
```

Description

Performs an SVM binary classification using training site polygons/points and multiple input images.

Usage

```
wbt_svm_classification(
    inputs,
    training,
    field,
    scaling = "Normalize",
    output = NULL,
    c = 200,
    gamma = 50,
```

```

    tolerance = 0.1,
    test_proportion = 0.2,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)

```

Arguments

inputs	Names of the input predictor rasters.
training	Name of the input training site polygons/points Shapefile.
field	Name of the attribute containing class data.
scaling	Scaling method for predictors. Options include 'None', 'Normalize', and 'Standardize'.
output	Name of the output raster file.
c	c-value, the regularization parameter.
gamma	Gamma parameter used in setting the RBF (Gaussian) kernel function.
tolerance	The tolerance parameter used in determining the stopping condition.
test_proportion	The proportion of the dataset to include in the test split; default is 0.2.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_svm_regression *Svm regression*

Description

Performs a supervised SVM regression analysis using training site points and predictor rasters.

Usage

```
wbt_svm_regression(
    inputs,
    training,
    field,
    scaling = "Normalize",
    output = NULL,
    c = 50,
    eps = 10,
    gamma = 0.5,
    test_proportion = 0.2,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

<code>inputs</code>	Names of the input predictor rasters.
<code>training</code>	Name of the input training site points Shapefile.
<code>field</code>	Name of the attribute containing class data.
<code>scaling</code>	Scaling method for predictors. Options include 'None', 'Normalize', and 'Standardize'.
<code>output</code>	Name of the output raster file.
<code>c</code>	c-value, the regularization parameter.
<code>eps</code>	Epsilon in the epsilon-SVR model.
<code>gamma</code>	Gamma parameter used in setting the RBF (Gaussian) kernel function.
<code>test_proportion</code>	The proportion of the dataset to include in the test split; default is 0.2.
<code>wd</code>	Changes the working directory.
<code>verbose_mode</code>	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
<code>compress_rasters</code>	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
<code>command_only</code>	Return command that would be executed by <code>system()</code> rather than running tool.

Value

Returns the tool text outputs.

`wbt_symmetrical_difference`*Symmetrical difference*

Description

Outputs the features that occur in one of the two vector inputs but not both, i.e. no overlapping features.

Usage

```
wbt_symmetrical_difference(  
    input,  
    overlay,  
    output,  
    snap = 0,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

<code>input</code>	Input vector file.
<code>overlay</code>	Input overlay vector file.
<code>output</code>	Output vector file.
<code>snap</code>	Snap tolerance.
<code>wd</code>	Changes the working directory.
<code>verbose_mode</code>	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
<code>compress_rasters</code>	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
<code>command_only</code>	Return command that would be executed by <code>system()</code> rather than running tool.

Value

Returns the tool text outputs.

wbt_tan	<i>Tan</i>
---------	------------

Description

Returns the tangent (tan) of each values in a raster.

Usage

```
wbt_tan(
    input,
    output,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input	Input raster file.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_tangential_curvature	<i>Tangential curvature</i>
--------------------------	-----------------------------

Description

Calculates a tangential curvature raster from an input DEM.

Usage

```
wbt_tangential_curvature(
    dem,
    output,
    log = FALSE,
    zfactor = NULL,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

dem	Input raster DEM file.
output	Output raster file.
log	Display output values using a log-scale.
zfactor	Optional multiplier for when the vertical and horizontal units are not the same.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_tanh	<i>Tanh</i>
----------	-------------

Description

Returns the hyperbolic tangent (tanh) of each values in a raster.

Usage

```
wbt_tanh(
    input,
    output,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input	Input raster file.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_thicken_raster_line

Thicken raster line

Description

Thickens single-cell wide lines within a raster image.

Usage

```
wbt_thicken_raster_line(
  input,
  output,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

input	Input raster file.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_time_in_daylight *Time in daylight*

Description

Calculates the proportion of time a location is not within an area of shadow.

Usage

```
wbt_time_in_daylight(
  dem,
  output,
  lat,
  long,
  az_fraction = 10,
  max_dist = 100,
  utc_offset = "00:00",
  start_day = 1,
  end_day = 365,
  start_time = "00:00:00",
  end_time = "23:59:59",
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

dem	Input raster DEM file.
output	Output raster file.
lat	Centre point latitude.
long	Centre point longitude.
az_fraction	Azimuth fraction in degrees.
max_dist	Optional maximum search distance. Minimum value is 5 x cell size.
utc_offset	UTC time offset, in hours (e.g. -04:00, +06:00).
start_day	Start day of the year (1-365).
end_day	End day of the year (1-365).
start_time	Starting hour to track shadows (e.g. 5, 5:00, 05:00:00). Assumes 24-hour time: HH:MM:SS. 'sunrise' is also a valid time.

end_time	Starting hour to track shadows (e.g. 21, 21:00, 21:00:00). Assumes 24-hour time: HH:MM:SS. 'sunset' is also a valid time.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_tin_gridding	<i>Tin gridding</i>
------------------	---------------------

Description

Creates a raster grid based on a triangular irregular network (TIN) fitted to vector points.

Usage

```
wbt_tin_gridding(
  input,
  output,
  field = NULL,
  use_z = FALSE,
  resolution = NULL,
  base = NULL,
  max_triangle_edge_length = NULL,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

input	Input vector points file.
output	Output raster file.
field	Input field name in attribute table.
use_z	Use the 'z' dimension of the Shapefile's geometry instead of an attribute field?.
resolution	Output raster's grid resolution.
base	Optionally specified input base raster file. Not used when a cell size is specified.

max_triangle_edge_length	Optional maximum triangle edge length; triangles larger than this size will not be gridded.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_toolbox	<i>The toolbox for a specific tool in WhiteboxTools</i>
-------------	---

Description

Retrieve the toolbox for a specific tool.

Usage

```
wbt_toolbox(tool_name = NULL)
```

Arguments

tool_name	The name of the tool.
-----------	-----------------------

Details

Leaving tool_name as default NULL returns results for all tools, but does not work on Windows.

Value

Returns the toolbox for a specific tool.

Examples

```
## Not run:
wbt_toolbox("breach_depressions")

## End(Not run)
```

wbt_tool_help	<i>Help description for a specific tool in WhiteboxTools</i>
---------------	--

Description

Retrieves the help description for a specific tool.

Usage

```
wbt_tool_help(tool_name = NULL)
```

Arguments

tool_name	The name of the tool.
-----------	-----------------------

Details

Leaving tool_name as default NULL returns results for all tools, but does not work on Windows.

Value

Returns the help description for a specific tool.

Examples

```
## Not run:  
wbt_tool_help("lidar_info")  
  
## End(Not run)
```

wbt_tool_parameters	<i>Tool parameter descriptions for a specific tool in WhiteboxTools</i>
---------------------	---

Description

Retrieves the tool parameter descriptions for a specific tool.

Usage

```
wbt_tool_parameters(tool_name, quiet = FALSE)
```

Arguments

tool_name	The name of the tool.
quiet	Prevent tool output being printed. Default: FALSE

Details

quiet argument can be set to TRUE to allow for "quiet" internal use within other functions.

Value

Returns the tool parameter descriptions for a specific tool.

Examples

```
## Not run:
wbt_tool_parameters("lidar_info")

## End(Not run)
```

wbt_tophat_transform *Tophat transform*

Description

Performs either a white or black top-hat transform on an input image.

Usage

```
wbt_tophat_transform(
  input,
  output,
  filterx = 11,
  filtery = 11,
  variant = "white",
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

input	Input raster file.
output	Output raster file.
filterx	Size of the filter kernel in the x-direction.
filtery	Size of the filter kernel in the y-direction.
variant	Optional variant value. Options include 'white' and 'black'.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.

`compress_rasters` Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.

`command_only` Return command that would be executed by `system()` rather than running tool.

Value

Returns the tool text outputs.

wbt_topographic_position_animation
Topographic position animation

Description

This tool creates an animated GIF of multi-scale local topographic position (elevation deviation).

Usage

```
wbt_topographic_position_animation(
    input,
    output,
    palette = "bl_yl_rd",
    min_scale = 1,
    num_steps = 100,
    step_nonlinearity = 1.5,
    height = 600,
    delay = 250,
    label = "",
    dev_max = FALSE,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

`input` Name of the input digital elevation model (DEM) raster file.

`output` Name of the output HTML file (*.html).

`palette` Image palette; options are 'bl_yl_rd', 'bl_w_rd', 'purple', 'gn_yl', 'pi_y_g', and 'viridis'.

`min_scale` Minimum search neighbourhood radius in grid cells.

`num_steps` Number of steps.

`step_nonlinearity` Step nonlinearity factor (1.0-2.0 is typical).

height	Image height, in pixels.
delay	GIF time delay in milliseconds.
label	Label text (leave blank for none).
dev_max	Do you want to use DEVmax instead of DEV for measuring local topographic position?.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_topological_stream_order
Topological stream order

Description

Assigns each link in a stream network its topological order.

Usage

```
wbt_topological_stream_order(
  d8_pntr,
  streams,
  output,
  esri_pntr = FALSE,
  zero_background = FALSE,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

d8_pntr	Input raster D8 pointer file.
streams	Input raster streams file.
output	Output raster file.

esri_pntr	D8 pointer uses the ESRI style scheme.
zero_background	Flag indicating whether a background value of zero should be used.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_total_curvature	<i>Total curvature</i>
---------------------	------------------------

Description

Calculates a total curvature raster from an input DEM.

Usage

```
wbt_total_curvature(
  dem,
  output,
  log = FALSE,
  zfactor = NULL,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

dem	Input raster DEM file.
output	Output raster file.
log	Display output values using a log-scale.
zfactor	Optional multiplier for when the vertical and horizontal units are not the same.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.

compress_rasters Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.

command_only Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_total_filter *Total filter*

Description

Performs a total filter on an input image.

Usage

```
wbt_total_filter(
  input,
  output,
  filterx = 11,
  filtery = 11,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

input Input raster file.

output Output raster file.

filterx Size of the filter kernel in the x-direction.

filtery Size of the filter kernel in the y-direction.

wd Changes the working directory.

verbose_mode Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.

compress_rasters Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.

command_only Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_to_degrees	<i>To degrees</i>
----------------	-------------------

Description

Converts a raster from radians to degrees.

Usage

```
wbt_to_degrees(
    input,
    output,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input	Input raster file.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_to_radians	<i>To radians</i>
----------------	-------------------

Description

Converts a raster from degrees to radians.

Usage

```
wbt_to_radians(
    input,
    output,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input	Input raster file.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

```
wbt_trace_downslope_flowpaths
    Trace downslope flowpaths
```

Description

Traces downslope flowpaths from one or more target sites (i.e. seed points).

Usage

```
wbt_trace_downslope_flowpaths(
    seed_pts,
    d8_pntr,
    output,
    esri_pntr = FALSE,
    zero_background = FALSE,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

seed_pts	Input vector seed points file.
d8_pntr	Input D8 pointer raster file.
output	Output raster file.
esri_pntr	D8 pointer uses the ESRI style scheme.
zero_background	Flag indicating whether a background value of zero should be used.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_trend_surface	<i>Trend surface</i>
-------------------	----------------------

Description

Estimates the trend surface of an input raster file.

Usage

```
wbt_trend_surface(
    input,
    output,
    order = 1,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input	Input raster file.
output	Output raster file.
order	Polynomial order (1 to 10).
wd	Changes the working directory.

verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_trend_surface_vector_points
Trend surface vector points

Description

Estimates a trend surface from vector points.

Usage

```
wbt_trend_surface_vector_points(  
    input,  
    field,  
    output,  
    cell_size,  
    order = 1,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

input	Input vector Points file.
field	Input field name in attribute table.
output	Output raster file.
cell_size	Optionally specified cell size of output raster. Not used when base raster is specified.
order	Polynomial order (1 to 10).
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.

compress_rasters Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.

command_only Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_tributary_identifier
Tributary identifier

Description

Assigns a unique identifier to each tributary in a stream network.

Usage

```
wbt_tributary_identifier(  
  d8_pntr,  
  streams,  
  output,  
  esri_pntr = FALSE,  
  zero_background = FALSE,  
  wd = NULL,  
  verbose_mode = FALSE,  
  compress_rasters = FALSE,  
  command_only = FALSE  
)
```

Arguments

d8_pntr Input raster D8 pointer file.

streams Input raster streams file.

output Output raster file.

esri_pntr D8 pointer uses the ESRI style scheme.

zero_background Flag indicating whether a background value of zero should be used.

wd Changes the working directory.

verbose_mode Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.

compress_rasters Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.

command_only Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_truncate	<i>Truncate</i>
--------------	-----------------

Description

Truncates the values in a raster to the desired number of decimal places.

Usage

```
wbt_truncate(
  input,
  output,
  num_decimals = NULL,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

input	Input raster file.
output	Output raster file.
num_decimals	Number of decimals left after truncation (default is zero).
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by <code>system()</code> rather than running tool.

Value

Returns the tool text outputs.

`wbt_turning_bands_simulation`*Turning bands simulation*

Description

Creates an image containing random values based on a turning-bands simulation.

Usage

```
wbt_turning_bands_simulation(  
    base,  
    output,  
    range,  
    iterations = 1000,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

<code>base</code>	Input base raster file.
<code>output</code>	Output file.
<code>range</code>	The field's range, in xy-units, related to the extent of spatial autocorrelation.
<code>iterations</code>	The number of iterations.
<code>wd</code>	Changes the working directory.
<code>verbose_mode</code>	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
<code>compress_rasters</code>	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
<code>command_only</code>	Return command that would be executed by <code>system()</code> rather than running tool.

Value

Returns the tool text outputs.

`wbt_two_sample_ks_test`*Two sample ks test*

Description

Performs a 2-sample K-S test for significant differences on two input rasters.

Usage

```
wbt_two_sample_ks_test(  
    input1,  
    input2,  
    output,  
    num_samples = NULL,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

<code>input1</code>	First input raster file.
<code>input2</code>	Second input raster file.
<code>output</code>	Output HTML file.
<code>num_samples</code>	Number of samples. Leave blank to use whole image.
<code>wd</code>	Changes the working directory.
<code>verbose_mode</code>	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
<code>compress_rasters</code>	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
<code>command_only</code>	Return command that would be executed by <code>system()</code> rather than running tool.

Value

Returns the tool text outputs.

wbt_union

Union

Description

Splits vector layers at their overlaps, creating a layer containing all the portions from both input and overlay layers.

Usage

```
wbt_union(
    input,
    overlay,
    output,
    snap = 0,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input	Input vector file.
overlay	Input overlay vector file.
output	Output vector file.
snap	Snap tolerance.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by <code>system()</code> rather than running tool.

Value

Returns the tool text outputs.

wbt_unnest_basins	<i>Unnest basins</i>
-------------------	----------------------

Description

Extract whole watersheds for a set of outlet points.

Usage

```
wbt_unnest_basins(  
    d8_pntr,  
    pour_pts,  
    output,  
    esri_pntr = FALSE,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

d8_pntr	Input D8 pointer raster file.
pour_pts	Input vector pour points (outlet) file.
output	Output raster file.
esri_pntr	D8 pointer uses the ESRI style scheme.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_unsharp_masking *Unsharp masking*

Description

An image sharpening technique that enhances edges.

Usage

```
wbt_unsharp_masking(  
    input,  
    output,  
    sigma = 0.75,  
    amount = 100,  
    threshold = 0,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

input	Input raster file.
output	Output raster file.
sigma	Standard deviation distance in pixels.
amount	A percentage and controls the magnitude of each overshoot.
threshold	Controls the minimal brightness change that will be sharpened.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_unsphericity	<i>Unsphericity</i>
------------------	---------------------

Description

This tool calculates the unsphericity curvature from an input DEM.

Usage

```
wbt_unsphericity(  
    dem,  
    output,  
    log = FALSE,  
    zfactor = 1,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

dem	Name of the input raster DEM file.
output	Name of the output raster image file.
log	Display output values using a log-scale.
zfactor	Z conversion factor.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

`wbt_update_nodata_cells`*Update nodata cells*

Description

Replaces the NoData values in an input raster with the corresponding values contained in a second update layer.

Usage

```
wbt_update_nodata_cells(  
    input1,  
    input2,  
    output,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

<code>input1</code>	Input raster file 1.
<code>input2</code>	Input raster file 2; update layer.
<code>output</code>	Output raster file.
<code>wd</code>	Changes the working directory.
<code>verbose_mode</code>	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
<code>compress_rasters</code>	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
<code>command_only</code>	Return command that would be executed by <code>system()</code> rather than running tool.

Value

Returns the tool text outputs.

wbt_upslope_depression_storage
Upslope depression storage

Description

Estimates the average upslope depression storage depth.

Usage

```
wbt_upslope_depression_storage(  
    dem,  
    output,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

dem	Input raster DEM file.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_user_defined_weights_filter
User ined weights filter

Description

Performs a user-defined weights filter on an image.

Usage

```
wbt_user_defined_weights_filter(
    input,
    weights,
    output,
    center = "center",
    normalize = FALSE,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input	Input raster file.
weights	Input weights file.
output	Output raster file.
center	Kernel center cell; options include 'center', 'upper-left', 'upper-right', 'lower-left', 'lower-right'.
normalize	Normalize kernel weights? This can reduce edge effects and lessen the impact of data gaps (nodata) but is not suited when the kernel weights sum to zero.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_vector_hex_binning

Vector hex binning

Description

Hex-bins a set of vector points.

Usage

```
wbt_vector_hex_binning(
    input,
    output,
    width,
    orientation = "horizontal",
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input	Input base file.
output	Output vector polygon file.
width	The grid cell width.
orientation	Grid Orientation, 'horizontal' or 'vertical'.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_vector_lines_to_raster
Vector lines to raster

Description

Converts a vector containing polylines into a raster.

Usage

```
wbt_vector_lines_to_raster(
    input,
    output,
    field = "FID",
    no_data = TRUE,
```

```

    cell_size = NULL,
    base = NULL,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)

```

Arguments

input	Input vector lines file.
output	Output raster file.
field	Input field name in attribute table.
nodata	Background value to set to NoData. Without this flag, it will be set to 0.0.
cell_size	Optionally specified cell size of output raster. Not used when base raster is specified.
base	Optionally specified input base raster file. Not used when a cell size is specified.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

```

wbt_vector_points_to_raster
    Vector points to raster

```

Description

Converts a vector containing points into a raster.

Usage

```

wbt_vector_points_to_raster(
  input,
  output,
  field = "FID",
  assign = "last",
  nodata = TRUE,

```

```

    cell_size = NULL,
    base = NULL,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)

```

Arguments

input	Input vector Points file.
output	Output raster file.
field	Input field name in attribute table.
assign	Assignment operation, where multiple points are in the same grid cell; options include 'first', 'last' (default), 'min', 'max', 'sum'.
nodata	Background value to set to NoData. Without this flag, it will be set to 0.0.
cell_size	Optionally specified cell size of output raster. Not used when base raster is specified.
base	Optionally specified input base raster file. Not used when a cell size is specified.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_vector_polygons_to_raster
Vector polygons to raster

Description

Converts a vector containing polygons into a raster.

Usage

```
wbt_vector_polygons_to_raster(
    input,
    output,
    field = "FID",
    nodata = TRUE,
    cell_size = NULL,
    base = NULL,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input	Input vector polygons file.
output	Output raster file.
field	Input field name in attribute table.
nodata	Background value to set to NoData. Without this flag, it will be set to 0.0.
cell_size	Optionally specified cell size of output raster. Not used when base raster is specified.
base	Optionally specified input base raster file. Not used when a cell size is specified.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_vector_stream_network_analysis

Vector stream network analysis

Description

This tool performs common stream network analysis operations on an input vector stream file.

Usage

```
wbt_vector_stream_network_analysis(
  streams,
  dem,
  output,
  cutting_height = 10,
  snap = 0.1,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

streams	Name of the input streams vector file.
dem	Name of the input DEM raster file.
output	Name of the output lines shapefile.
cutting_height	Maximum ridge-cutting height (z units).
snap	Snap distance, in xy units (metres).
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_version	<i>Version information for WhiteboxTools</i>
-------------	--

Description

Version information for WhiteboxTools

Usage

```
wbt_version()
```

Value

Returns the version information for WhiteboxTools as an R character vector.

Examples

```
## Not run:
wbt_version()

## End(Not run)
```

```
wbt_vertical_excess_curvature
    Vertical excess curvature
```

Description

This tool calculates vertical excess curvature from an input DEM.

Usage

```
wbt_vertical_excess_curvature(
  dem,
  output,
  log = FALSE,
  zfactor = 1,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

dem	Name of the input raster DEM file.
output	Name of the output raster image file.
log	Display output values using a log-scale.
zfactor	Z conversion factor.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_viewshed	<i>Viewshed</i>
--------------	-----------------

Description

Identifies the viewshed for a point or set of points.

Usage

```
wbt_viewshed(  
    dem,  
    stations,  
    output,  
    height = 2,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

dem	Input raster DEM file.
stations	Input viewing station vector file.
output	Output raster file.
height	Viewing station height, in z units.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_view_code *Source code for a specific tool in WhiteboxTools*

Description

Opens a web browser to view the source code for a specific tool on the projects source code repository.

Usage

```
wbt_view_code(tool_name, viewer = FALSE)
```

Arguments

tool_name	Name of the tool.
viewer	Show source code in browser? default: TRUE

Value

Returns a GitHub URL to view the source code of the tool.

Examples

```
## Not run:  
wbt_view_code("breach_depressions")  
  
## End(Not run)
```

wbt_visibility_index *Visibility index*

Description

Estimates the relative visibility of sites in a DEM.

Usage

```
wbt_visibility_index(  
  dem,  
  output,  
  height = 2,  
  res_factor = 2,  
  wd = NULL,  
  verbose_mode = FALSE,  
  compress_rasters = FALSE,  
  command_only = FALSE  
)
```

Arguments

dem	Input raster DEM file.
output	Output raster file.
height	Viewing station height, in z units.
res_factor	The resolution factor determines the density of measured viewsheds.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_voronoi_diagram *Voronoi diagram*

Description

Creates a vector Voronoi diagram for a set of vector points.

Usage

```
wbt_voronoi_diagram(  
  input,  
  output,  
  wd = NULL,  
  verbose_mode = FALSE,  
  compress_rasters = FALSE,  
  command_only = FALSE  
)
```

Arguments

input	Input vector points file.
output	Output vector polygon file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_watershed	<i>Watershed</i>
---------------	------------------

Description

Identifies the watershed, or drainage basin, draining to a set of target cells.

Usage

```
wbt_watershed(
    d8_pntr,
    pour_pts,
    output,
    esri_pntr = FALSE,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

d8_pntr	Input D8 pointer raster file.
pour_pts	Input pour points (outlet) file.
output	Output raster file.
esri_pntr	D8 pointer uses the ESRI style scheme.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_weighted_overlay *Weighted overlay*

Description

Performs a weighted sum on multiple input rasters after converting each image to a common scale. The tool performs a multi-criteria evaluation (MCE).

Usage

```
wbt_weighted_overlay(
  factors,
  weights,
  output,
  cost = NULL,
  constraints = NULL,
  scale_max = 1,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

factors	Input factor raster files.
weights	Weight values, contained in quotes and separated by commas or semicolons. Must have the same number as factors.
output	Output raster file.
cost	Weight values, contained in quotes and separated by commas or semicolons. Must have the same number as factors.
constraints	Input constraints raster files.
scale_max	Suitability scale maximum value (common values are 1.0, 100.0, and 255.0).
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_weighted_sum	<i>Weighted sum</i>
------------------	---------------------

Description

Performs a weighted-sum overlay on multiple input raster images.

Usage

```
wbt_weighted_sum(  
    inputs,  
    weights,  
    output,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

inputs	Input raster files.
weights	Weight values, contained in quotes and separated by commas or semicolons.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by <code>system()</code> rather than running tool.

Value

Returns the tool text outputs.

wbt_wetness_index	<i>Wetness index</i>
-------------------	----------------------

Description

Calculates the topographic wetness index, $\text{Ln}(A / \tan(\text{slope}))$.

Usage

```
wbt_wetness_index(  
    sca,  
    slope,  
    output,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

sca	Input raster specific contributing area (SCA) file.
slope	Input raster slope file (in degrees).
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by <code>system()</code> rather than running tool.

Value

Returns the tool text outputs.

`wbt_wilcoxon_signed_rank_test`*Wilcoxon signed rank test*

Description

Performs a 2-sample K-S test for significant differences on two input rasters.

Usage

```
wbt_wilcoxon_signed_rank_test(  
    input1,  
    input2,  
    output,  
    num_samples = NULL,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

<code>input1</code>	First input raster file.
<code>input2</code>	Second input raster file.
<code>output</code>	Output HTML file.
<code>num_samples</code>	Number of samples. Leave blank to use whole image.
<code>wd</code>	Changes the working directory.
<code>verbose_mode</code>	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
<code>compress_rasters</code>	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
<code>command_only</code>	Return command that would be executed by <code>system()</code> rather than running tool.

Value

Returns the tool text outputs.

wbt_write_function_memory_insertion
Write function memory insertion

Description

Performs a write function memory insertion for single-band multi-date change detection.

Usage

```
wbt_write_function_memory_insertion(  
    input1,  
    input2,  
    output,  
    input3 = NULL,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

input1	Input raster file associated with the first date.
input2	Input raster file associated with the second date.
output	Output raster file.
input3	Optional input raster file associated with the third date.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

`wbt_xor`*Xor*

Description

Performs a logical XOR operator on two Boolean raster images.

Usage

```
wbt_xor(  
    input1,  
    input2,  
    output,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

<code>input1</code>	Input raster file.
<code>input2</code>	Input raster file.
<code>output</code>	Output raster file.
<code>wd</code>	Changes the working directory.
<code>verbose_mode</code>	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
<code>compress_rasters</code>	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
<code>command_only</code>	Return command that would be executed by <code>system()</code> rather than running tool.

Value

Returns the tool text outputs.

wbt_yield_filter	<i>Yield filter</i>
------------------	---------------------

Description

Filters crop yield values of point data derived from combine harvester yield monitors.

Usage

```
wbt_yield_filter(
    input,
    yield_field,
    pass_field,
    output,
    width = 6.096,
    z_score_threshold = 2.5,
    min_yield = 0,
    max_yield = 99999.9,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input	Name of the input points shapefile.
yield_field	Name of the attribute containing yield data.
pass_field	Name of the attribute containing pass line ID.
output	Name of the output points shapefile.
width	Pass swath width (m).
z_score_threshold	Z-score threshold value (default=2.5).
min_yield	Minimum yield value in output.
max_yield	Maximum yield value in output.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_yield_map	<i>Yield map</i>
---------------	------------------

Description

This tool can be used to create a segmented-vector polygon yield map from a set of harvester points.

Usage

```
wbt_yield_map(
    input,
    pass_field_name,
    output,
    width = 6.096,
    max_change_in_heading = 25,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input	Name of the input points shapefile.
pass_field_name	Name of the attribute containing pass line ID.
output	Name of the output polygon shapefile.
width	Pass swath width (m).
max_change_in_heading	Max change in heading.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_yield_normalization
Yield normalization

Description

This tool can be used to normalize the yield points for a field.

Usage

```
wbt_yield_normalization(
    input,
    yield_field,
    output,
    standardize = FALSE,
    radius = NULL,
    min_yield = 0,
    max_yield = 99999.9,
    wd = NULL,
    verbose_mode = FALSE,
    compress_rasters = FALSE,
    command_only = FALSE
)
```

Arguments

input	Name of the input points shapefile.
yield_field	Name of the attribute containing yield data.
output	Name of the output points shapefile.
standardize	Should the yield values be standardized (converted to z-scores) rather than normalized?.
radius	Optional search radius, in metres. Only specify this value if you want to calculate locally normalized yield.
min_yield	Minimum yield value in output.
max_yield	Maximum yield value in output.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_zlidar_to_las *Zlidar to las*

Description

Converts one or more zlidar files into the LAS data format.

Usage

```
wbt_zlidar_to_las(
  inputs = NULL,
  outdir = NULL,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

inputs	Input ZLidar files.
outdir	Output directory into which zlidar files are created. If unspecified, it is assumed to be the same as the inputs.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

wbt_zonal_statistics *Zonal statistics*

Description

Extracts descriptive statistics for a group of patches in a raster.

Usage

```
wbt_zonal_statistics(
  input,
  features,
  output = NULL,
  stat = "mean",
  out_table = NULL,
  wd = NULL,
  verbose_mode = FALSE,
  compress_rasters = FALSE,
  command_only = FALSE
)
```

Arguments

input	Input data raster file.
features	Input feature definition raster file.
output	Output raster file.
stat	Statistic to extract, including 'mean', 'median', 'minimum', 'maximum', 'range', 'standard deviation', and 'total'.
out_table	Output HTML Table file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by <code>system()</code> rather than running tool.

Value

Returns the tool text outputs.

wbt_z_scores	<i>Z scores</i>
--------------	-----------------

Description

Standardizes the values in an input raster by converting to z-scores.

Usage

```
wbt_z_scores(  
    input,  
    output,  
    wd = NULL,  
    verbose_mode = FALSE,  
    compress_rasters = FALSE,  
    command_only = FALSE  
)
```

Arguments

input	Input raster file.
output	Output raster file.
wd	Changes the working directory.
verbose_mode	Sets verbose mode. If verbose mode is FALSE, tools will not print output messages.
compress_rasters	Sets the flag used by WhiteboxTools to determine whether to use compression for output rasters.
command_only	Return command that would be executed by system() rather than running tool.

Value

Returns the tool text outputs.

Index

- * **datasets**
 - wbttoolparameters, 14
 - wbttools, 15
- check_whitebox_binary, 13
- install_whitebox (wbt_install), 198
- install_whitebox(), 196
- sample_dem_data, 13

- wbt_absolute_value, 16
- wbt_accumulation_curvature, 16
- wbt_adaptive_filter, 17
- wbt_add, 18
- wbt_add_point_coordinates_to_table, 19
- wbt_aggregate_raster, 20
- wbt_and, 21
- wbt_anova, 22
- wbt_arc_cos, 23
- wbt_arc_sin, 24
- wbt_arc_tan, 25
- wbt_arcosh, 23
- wbt_arsinh, 26
- wbt_artanh, 27
- wbt_ascii_to_las, 27
- wbt_aspect, 28
- wbt_assess_route, 29
- wbt_atan2, 30
- wbt_attribute_correlation, 31
- wbt_attribute_correlation_neighbourhood_analysis, 31
- wbt_attribute_histogram, 32
- wbt_attribute_scattergram, 33
- wbt_average_flowpath_slope, 34
- wbt_average_normal_vector_angular_deviation, 35
- wbt_average_overlay, 36
- wbt_average_upslope_flowpath_length, 37

- wbt_balance_contrast_enhancement, 37
- wbt_basins, 38
- wbt_bilateral_filter, 39
- wbt_block_maximum_gridding, 40
- wbt_block_minimum_gridding, 41
- wbt_boundary_shape_complexity, 42
- wbt_breach_depressions, 43
- wbt_breach_depressions_least_cost, 44
- wbt_breach_single_cell_pits, 45
- wbt_buffer_raster, 45
- wbt_burn_streams_at_roads, 46
- wbt_canny_edge_detection, 47
- wbt_ceil, 48
- wbt_centroid, 49
- wbt_centroid_vector, 50
- wbt_change_vector_analysis, 51
- wbt_circular_variance_of_aspect, 52
- wbt_classify_buildings_in_lidar, 53
- wbt_classify_overlap_points, 54
- wbt_clean_vector, 55
- wbt_clip, 55
- wbt_clip_lidar_to_polygon, 56
- wbt_clip_raster_to_polygon, 57
- wbt_closing, 58
- wbt_clump, 59
- wbt_compactness_ratio, 60
- wbt_compress_rasters (wbt_init), 193
- wbt_conditional_evaluation, 60
- wbt_conservative_smoothing_filter, 61
- wbt_construct_vector_tin, 62
- wbt_contours_from_points, 63
- wbt_contours_from_raster, 64
- wbt_convert_nodata_to_zero, 65
- wbt_convert_raster_format, 66
- wbt_corner_detection, 67
- wbt_correct_vignetting, 68
- wbt_cos, 69
- wbt_cosh, 69
- wbt_cost_allocation, 70

- wbt_cost_distance, 71
- wbt_cost_pathway, 72
- wbt_count_if, 73
- wbt_create_colour_composite, 74
- wbt_create_hexagonal_vector_grid, 75
- wbt_create_plane, 76
- wbt_create_rectangular_vector_grid, 77
- wbt_crispness_index, 78
- wbt_cross_tabulation, 78
- wbt_csv_points_to_vector, 79
- wbt_cumulative_distribution, 80
- wbt_curvedness, 81
- wbt_d8_flow_accumulation, 82
- wbt_d8_mass_flux, 83
- wbt_d8_pointer, 84
- wbt_d_inf_flow_accumulation, 101
- wbt_d_inf_mass_flux, 102
- wbt_d_inf_pointer, 103
- wbt_dbscan, 85
- wbt_decrement, 86
- wbt_default_path(wbt_init), 193
- wbt_depth_in_sink, 86
- wbt_dev_from_mean_elev, 87
- wbt_diff_from_mean_elev, 90
- wbt_diff_of_gaussian_filter, 91
- wbt_difference, 88
- wbt_difference_curvature, 89
- wbt_direct_decorrelation_stretch, 93
- wbt_directional_relief, 92
- wbt_dissolve, 94
- wbt_distance_to_outlet, 95
- wbt_diversity_filter, 96
- wbt_divide, 97
- wbt_downslope_distance_to_stream, 98
- wbt_downslope_flowpath_length, 99
- wbt_downslope_index, 100
- wbt_edge_contamination, 103
- wbt_edge_density, 104
- wbt_edge_preserving_mean_filter, 105
- wbt_edge_proportion, 106
- wbt_elev_above_pit, 109
- wbt_elev_percentile, 109
- wbt_elev_relative_to_min_max, 110
- wbt_elev_relative_to_watershed_min_max, 111
- wbt_elevation_above_stream, 107
- wbt_elevation_above_stream_euclidean, 108
- wbt_eliminate_coincident_points, 112
- wbt_elongation_ratio, 113
- wbt_embankment_mapping, 114
- wbt_emboss_filter, 115
- wbt_equal_to, 116
- wbt_erase, 117
- wbt_erase_polygon_from_lidar, 118
- wbt_erase_polygon_from_raster, 119
- wbt_euclidean_allocation, 120
- wbt_euclidean_distance, 120
- wbt_evaluate_training_sites, 121
- wbt_exe_path(wbt_init), 193
- wbt_exe_path(), 13
- wbt_exp, 122
- wbt_exp2, 123
- wbt_export_table_to_csv, 124
- wbt_exposure_towards_wind_flux, 125
- wbt_extend_vector_lines, 126
- wbt_extract_nodes, 127
- wbt_extract_raster_values_at_points, 127
- wbt_extract_streams, 128
- wbt_extract_valleys, 129
- wbt_farthest_channel_head, 130
- wbt_fast_almost_gaussian_filter, 131
- wbt_fd8_flow_accumulation, 132
- wbt_fd8_pointer, 133
- wbt_feature_preserving_smoothing, 134
- wbt_fetch_analysis, 135
- wbt_fill_burn, 136
- wbt_fill_depressions, 137
- wbt_fill_depressions_planchon_and_darboux, 138
- wbt_fill_depressions_wang_and_liu, 139
- wbt_fill_missing_data, 140
- wbt_fill_single_cell_pits, 141
- wbt_filter_lidar_classes, 141
- wbt_filter_lidar_scan_angles, 142
- wbt_filter_raster_features_by_area, 143
- wbt_find_flightline_edge_points, 144
- wbt_find_lowest_or_highest_points, 145
- wbt_find_main_stem, 146
- wbt_find_no_flow_cells, 147
- wbt_find_parallel_flow, 147
- wbt_find_patch_or_class_edge_cells, 148
- wbt_find_ridges, 149

- wbt_fix_dangling_arcs, 150
- wbt_flatten_lakes, 151
- wbt_flightline_overlap, 152
- wbt_flip_image, 153
- wbt_flood_order, 154
- wbt_floor, 154
- wbt_flow_accumulation_full_workflow, 155
- wbt_flow_length_diff, 156
- wbt_gamma_correction, 157
- wbt_gaussian_contrast_stretch, 158
- wbt_gaussian_curvature, 159
- wbt_gaussian_filter, 160
- wbt_gaussian_scale_space, 161
- wbt_generalize_classified_raster, 162
- wbt_generalize_with_similarity, 163
- wbt_generating_function, 164
- wbt_geomorphons, 165
- wbt_greater_than, 166
- wbt_hack_stream_order, 167
- wbt_height_above_ground, 168
- wbt_help, 168
- wbt_high_pass_filter, 170
- wbt_high_pass_median_filter, 171
- wbt_highest_position, 169
- wbt_hillshade, 172
- wbt_hillslopes, 173
- wbt_histogram_equalization, 174
- wbt_histogram_matching, 175
- wbt_histogram_matching_two_images, 176
- wbt_hole_proportion, 177
- wbt_horizon_angle, 178
- wbt_horizontal_excess_curvature, 177
- wbt_horton_stream_order, 179
- wbt_hydrologic_connectivity, 180
- wbt_hypsometric_analysis, 182
- wbt_hypsometrically_tinted_hillshade, 181
- wbt_idw_interpolation, 183
- wbt_ihs_to_rgb, 184
- wbt_image_autocorrelation, 185
- wbt_image_correlation, 186
- wbt_image_correlation_neighbourhood_analysis, 187
- wbt_image_regression, 188
- wbt_image_segmentation, 189
- wbt_image_slider, 190
- wbt_image_stack_profile, 191
- wbt_impoundment_size_index, 192
- wbt_in_place_add, 202
- wbt_in_place_divide, 202
- wbt_in_place_multiply, 203
- wbt_in_place_subtract, 204
- wbt_increment, 193
- wbt_init, 193
- wbt_insert_dams, 197
- wbt_install, 198
- wbt_integer_division, 198
- wbt_integral_image, 199
- wbt_intersect, 200
- wbt_inverse_principal_component_analysis, 201
- wbt_is_no_data, 206
- wbt_isobasins, 205
- wbt_jenson_snap_pour_points, 206
- wbt_join_tables, 207
- wbt_k_means_clustering, 212
- wbt_k_nearest_mean_filter, 213
- wbt_kappa_index, 208
- wbt_knn_classification, 209
- wbt_knn_regression, 210
- wbt_ks_test_for_normality, 211
- wbt_laplacian_filter, 214
- wbt_laplacian_of_gaussian_filter, 215
- wbt_las_to_ascii, 216
- wbt_las_to_laz, 217
- wbt_las_to_multipoint_shapefile, 217
- wbt_las_to_shapefile, 218
- wbt_las_to_zlidar, 219
- wbt_layer_footprint, 220
- wbt_laz_to_las, 221
- wbt_lee_sigma_filter, 221
- wbt_length_of_upstream_channels, 222
- wbt_less_than, 223
- wbt_license, 224
- wbt_lidar_block_maximum, 225
- wbt_lidar_block_minimum, 226
- wbt_lidar_classify_subset, 227
- wbt_lidar_colourize, 228
- wbt_lidar_contour, 229
- wbt_lidar_digital_surface_model, 230
- wbt_lidar_elevation_slice, 231
- wbt_lidar_ground_point_filter, 232
- wbt_lidar_hex_binning, 233
- wbt_lidar_hillshade, 234
- wbt_lidar_histogram, 235

- wbt_lidar_idw_interpolation, 236
- wbt_lidar_info, 237
- wbt_lidar_join, 238
- wbt_lidar_kappa_index, 239
- wbt_lidar_nearest_neighbour_gridding, 240
- wbt_lidar_point_density, 241
- wbt_lidar_point_return_analysis, 242
- wbt_lidar_point_stats, 243
- wbt_lidar_ransac_planes, 244
- wbt_lidar_rbf_interpolation, 245
- wbt_lidar_remove_duplicates, 246
- wbt_lidar_remove_outliers, 247
- wbt_lidar_rooftop_analysis, 248
- wbt_lidar_segmentation, 250
- wbt_lidar_segmentation_based_filter, 251
- wbt_lidar_shift, 252
- wbt_lidar_sibson_interpolation, 253
- wbt_lidar_sort_by_time, 254
- wbt_lidar_thin, 255
- wbt_lidar_thin_high_density, 256
- wbt_lidar_tile, 257
- wbt_lidar_tile_footprint, 258
- wbt_lidar_tin_gridding, 259
- wbt_lidar_tophat_transform, 260
- wbt_line_detection_filter, 262
- wbt_line_intersections, 263
- wbt_line_thinning, 264
- wbt_linearity_index, 261
- wbt_lines_to_polygons, 261
- wbt_list_tools, 265, 405
- wbt_list_tools(), 15
- wbt_list_unique_values, 265
- wbt_ln, 266
- wbt_local_hypsometric_analysis, 267
- wbt_local_quadratic_regression, 268
- wbt_log10, 269
- wbt_log2, 269
- wbt_logistic_regression, 270
- wbt_long_profile, 272
- wbt_long_profile_from_points, 273
- wbt_longest_flowpath, 271
- wbt_low_points_on_headwater_divides, 275
- wbt_lowest_position, 274
- wbt_majority_filter, 276
- wbt_map_off_terrain_objects, 277
- wbt_max, 278
- wbt_max_absolute_overlay, 281
- wbt_max_anisotropy_dev, 281
- wbt_max_anisotropy_dev_signature, 282
- wbt_max_branch_length, 283
- wbt_max_difference_from_mean, 284
- wbt_max_downslope_elev_change, 285
- wbt_max_elev_dev_signature, 287
- wbt_max_elevation_deviation, 286
- wbt_max_overlay, 288
- wbt_max_procs (wbt_init), 193
- wbt_max_upslope_elev_change, 289
- wbt_max_upslope_flowpath_length, 289
- wbt_maximal_curvature, 279
- wbt_maximum_filter, 280
- wbt_md_inf_flow_accumulation, 290
- wbt_mean_curvature, 291
- wbt_mean_filter, 292
- wbt_median_filter, 293
- wbt_medoid, 294
- wbt_merge_line_segments, 295
- wbt_merge_table_with_csv, 296
- wbt_merge_vectors, 297
- wbt_min, 297
- wbt_min_absolute_overlay, 304
- wbt_min_dist_classification, 304
- wbt_min_downslope_elev_change, 305
- wbt_min_max_contrast_stretch, 306
- wbt_min_overlay, 307
- wbt_minimal_curvature, 298
- wbt_minimum_bounding_box, 299
- wbt_minimum_bounding_circle, 300
- wbt_minimum_bounding_envelope, 301
- wbt_minimum_convex_hull, 302
- wbt_minimum_filter, 303
- wbt_modified_k_means_clustering, 308
- wbt_modify_no_data_value, 309
- wbt_modulo, 310
- wbt_mosaic, 311
- wbt_mosaic_with_feathering, 312
- wbt_multi_part_to_single_part, 321
- wbt_multidirectional_hillshade, 313
- wbt_multiply, 314
- wbt_multiscale_elevation_percentile, 315
- wbt_multiscale_roughness, 316
- wbt_multiscale_roughness_signature, 317

- wbt_multiscale_std_dev_normals, 318
- wbt_multiscale_std_dev_normals_signature, 319
- wbt_multiscale_topographic_position_image, 320
- wbt_narrowness_index, 322
- wbt_natural_neighbour_interpolation, 322
- wbt_nearest_neighbour_gridding, 323
- wbt_negate, 324
- wbt_new_raster_from_base, 325
- wbt_normal_vectors, 327
- wbt_normalized_difference_index, 326
- wbt_not, 328
- wbt_not_equal_to, 329
- wbt_num_downslope_neighbours, 330
- wbt_num_inflowing_neighbours, 330
- wbt_num_upslope_neighbours, 331
- wbt_olympic_filter, 332
- wbt_opening, 333
- wbt_openness, 334
- wbt_options (wbt_init), 193
- wbt_or, 335
- wbt_paired_sample_t_test, 336
- wbt_panchromatic_sharpening, 337
- wbt_parallelepiped_classification, 338
- wbt_patch_orientation, 339
- wbt_pennock_landform_class, 339
- wbt_percent_elev_range, 342
- wbt_percent_equal_to, 343
- wbt_percent_greater_than, 344
- wbt_percent_less_than, 345
- wbt_percentage_contrast_stretch, 340
- wbt_percentile_filter, 341
- wbt_perimeter_area_ratio, 346
- wbt_phi_coefficient, 347
- wbt_pick_from_list, 348
- wbt_plan_curvature, 349
- wbt_polygon_area, 351
- wbt_polygon_long_axis, 352
- wbt_polygon_perimeter, 353
- wbt_polygon_short_axis, 353
- wbt_polygonize, 350
- wbt_polygons_to_lines, 350
- wbt_power, 354
- wbt_prewitt_filter, 355
- wbt_principal_component_analysis, 356
- wbt_print_geo_tiff_tags, 357
- wbt_profile, 357
- wbt_profile_curvature, 358
- wbt_qin_flow_accumulation, 359
- wbt_quantiles, 360
- wbt_quinn_flow_accumulation, 361
- wbt_radial_basis_function_interpolation, 362
- wbt_radius_of_gyration, 363
- wbt_raise_walls, 364
- wbt_random_field, 365
- wbt_random_forest_classification, 366
- wbt_random_forest_regression, 367
- wbt_random_sample, 368
- wbt_range_filter, 369
- wbt_raster_area, 371
- wbt_raster_calculator, 372
- wbt_raster_cell_assignment, 373
- wbt_raster_histogram, 374
- wbt_raster_perimeter, 375
- wbt_raster_streams_to_vector, 376
- wbt_raster_summary_stats, 377
- wbt_raster_to_vector_lines, 377
- wbt_raster_to_vector_points, 378
- wbt_raster_to_vector_polygons, 379
- wbt_rasterize_streams, 370
- wbt_reciprocal, 380
- wbt_reclass, 381
- wbt_reclass_equal_interval, 382
- wbt_reclass_from_file, 383
- wbt_reconcile_multiple_headers, 384
- wbt_recreate_pass_lines, 385
- wbt_reinitialize_attribute_table, 386
- wbt_related_circumscribing_circle, 387
- wbt_relative_aspect, 387
- wbt_relative_topographic_position, 388
- wbt_remove_field_edge_points, 389
- wbt_remove_off_terrain_objects, 390
- wbt_remove_polygon_holes, 391
- wbt_remove_short_streams, 392
- wbt_remove_spurs, 393
- wbt_repair_stream_vector_topology, 394
- wbt_resample, 395
- wbt_rescale_value_range, 396
- wbt_rgb_to_ihs, 397
- wbt_rho8_flow_accumulation, 398
- wbt_rho8_pointer, 399
- wbt_ring_curvature, 400
- wbt_roberts_cross_filter, 401

- wbt_root_mean_square_error, 402
- wbt_rotor, 402
- wbt_round, 403
- wbt_ruggedness_index, 404
- wbt_run_tool, 405
- wbt_scharr_filter, 406
- wbt_sediment_transport_index, 407
- wbt_select_tiles_by_polygon, 408
- wbt_set_nodata_value, 409
- wbt_shadow_animation, 410
- wbt_shadow_image, 411
- wbt_shape_complexity_index, 412
- wbt_shape_complexity_index_raster, 413
- wbt_shape_index, 413
- wbt_shreve_stream_magnitude, 414
- wbt_sigmoidal_contrast_stretch, 415
- wbt_sin, 416
- wbt_single_part_to_multi_part, 417
- wbt_sinh, 418
- wbt_sink, 418
- wbt_slope, 419
- wbt_slope_vs_aspect_plot, 420
- wbt_slope_vs_elevation_plot, 421
- wbt_smooth_vectors, 422
- wbt_smooth_vegetation_residual, 423
- wbt_snap_pour_points, 424
- wbt_sobel_filter, 425
- wbt_spherical_std_dev_of_normals, 426
- wbt_split_colour_composite, 427
- wbt_split_vector_lines, 428
- wbt_split_with_lines, 429
- wbt_square, 430
- wbt_square_root, 430
- wbt_standard_deviation_contrast_stretch, 431
- wbt_standard_deviation_filter, 432
- wbt_standard_deviation_of_slope, 433
- wbt_stochastic_depression_analysis, 434
- wbt_strahler_order_basins, 435
- wbt_strahler_stream_order, 436
- wbt_stream_link_class, 437
- wbt_stream_link_identifier, 438
- wbt_stream_link_length, 439
- wbt_stream_link_slope, 440
- wbt_stream_power_index, 441
- wbt_stream_slope_continuous, 442
- wbt_subbasins, 443
- wbt_subtract, 444
- wbt_sum_overlay, 445
- wbt_surface_area_ratio, 445
- wbt_svm_classification, 446
- wbt_svm_regression, 447
- wbt_symmetrical_difference, 449
- wbt_tan, 450
- wbt_tangential_curvature, 450
- wbt_tanh, 451
- wbt_thicken_raster_line, 452
- wbt_time_in_daylight, 453
- wbt_tin_gridding, 454
- wbt_to_degrees, 462
- wbt_to_radians, 462
- wbt_tool_help, 456
- wbt_tool_parameters, 456
- wbt_tool_parameters(), 15
- wbt_toolbox, 455
- wbt_tophat_transform, 457
- wbt_topographic_position_animation, 458
- wbt_topological_stream_order, 459
- wbt_total_curvature, 460
- wbt_total_filter, 461
- wbt_trace_downslope_flowpaths, 463
- wbt_trend_surface, 464
- wbt_trend_surface_vector_points, 465
- wbt_tributary_identifier, 466
- wbt_truncate, 467
- wbt_turning_bands_simulation, 468
- wbt_two_sample_ks_test, 469
- wbt_union, 470
- wbt_unnest_basins, 471
- wbt_unsharp_masking, 472
- wbt_unsphericity, 473
- wbt_update_nodata_cells, 474
- wbt_upslope_depression_storage, 475
- wbt_user_defined_weights_filter, 475
- wbt_vector_hex_binning, 476
- wbt_vector_lines_to_raster, 477
- wbt_vector_points_to_raster, 478
- wbt_vector_polygons_to_raster, 479
- wbt_vector_stream_network_analysis, 480
- wbt_verbose (wbt_init), 193
- wbt_version, 481
- wbt_vertical_excess_curvature, 482
- wbt_view_code, 484

wbt_viewshed, 483
wbt_visibility_index, 484
wbt_voronoi_diagram, 485
wbt_watershed, 486
wbt_wd (wbt_init), 193
wbt_weighted_overlay, 487
wbt_weighted_sum, 488
wbt_wetness_index, 489
wbt_wilcoxon_signed_rank_test, 490
wbt_write_function_memory_insertion,
 491
wbt_xor, 492
wbt_yield_filter, 493
wbt_yield_map, 494
wbt_yield_normalization, 495
wbt_z_scores, 497
wbt_zlidar_to_las, 496
wbt_zonal_statistics, 496
wbtoolparameters, 14, 15
wbtools, 15, 15
whitebox, 196